Towards A Unified Agent with Foundation Models

Abstract

Language Models and Vision Language Models have recently demonstrated un-precedented capabilities in terms of understanding human intentions, reasoning, scene understanding, and planning-like behaviour, in text form, among many others. In this work, we investigate how to embed and leverage such abilities in Reinforcement Learning (RL) agents. We design a framework that uses language as the core reasoning tool, exploring how this enables an agent to tackle a series of fundamental RL challenges, such as efficient exploration, reusing experience data, scheduling skills, and learning from observations, which traditionally require separate, vertically designed algorithms. We test our method on a sparse-reward simulated robotic manipulation environment, where a robot needs to stack a set of objects. We demonstrate substantial performance improvements over baselines in exploration efficiency and ability to reuse data from offline datasets, and illustrate how to reuse learned skills to solve novel tasks or imitate videos of human experts.

1 Introduction

In recent years, the literature has seen a series of remarkable Deep Learning (DL) success stories (3), with breakthroughs particularly in the fields of Natural Language Processing (4; 18; 8; 28) and Computer Vision (2; 24; 35; 36). Albeit different in modalities, these results share a common structure: large neural networks, often Transformers (45), trained on enormous web-scale datasets (38; 18) using self-supervised learning methods (18; 6). While simple in structure, this recipe led to the development of surprisingly effective Large Language Models (LLMs) (4), able to process and generate text with outstanding human-like capability, Vision Transformers (ViTs) (24; 12) able to extract meaningful representations from images and videos with no supervision (6; 17), and Vision-Language Models (VLMs) (2; 35; 27), that can bridge those data modalities describing visual inputs in language, or transforming language descriptions into visual outputs. The size and abilities of these models led the community to coin the term Foundation Models (3), suggesting how these models can be used as the backbone for downstream applications involving a variety of input modalities.

This led us to the following question: can we leverage the performance and capabilities of (Vision) Language Models to design more efficient and general reinforcement learning agents? After being trained on web-scaled textual and visual data, the literature has observed the emergence of common sense reasoning, proposing and sequencing sub-goals, visual understanding, and other properties in these models (18; 4; 8; 28). These are all fundamental characteristics for agents that need to interact with and learn from environments, but that can take an impractical amount of time to emerge tabula rasa from trial and error. Foundation Models are generally trained using thousands of PetaFLOPS/s-days (18), reutilising this computational effort to bootstrap learning, as well as leveraging their emergent properties in novel scenarios, is critical.

Figure 1: A high-level illustration of our framework.

Motivated by this idea, we design a framework that puts language at the core of an RL robotic agent, particularly in the context of learning from scratch. Our core contribution and finding is the following: we show that this framework, which leverages LLMs and VLMs, can tackle a series of fundamental problems in RL settings, such as **1) efficiently exploring** sparse-reward environments, **2) re-using collected data** to bootstrap the learning of new tasks sequentially, **3) scheduling learned skills** to solve novel tasks and **4) learning from observation** of expert agents. In the recent literature, these tasks need different, specifically designed algorithms to be tackled individually, while our proposed framework provides a more unified approach.

2 Related Work

Over the past few years, scaling the parameter count of models and the size and diversity of training datasets led to unprecedented capabilities in (Vision) Language Models ([4; 18; 2; 18; 8]). This in turn led to several applications leveraging these models within agents that interact with the world. Prior work has used LLMs and VLMs together with RL agents in simulated environments ([11; 43]), but they rely on collecting large amounts of demonstrations for training agents. Instead, we focus on the problem of learning RL agents from scratch and leverage LLMs and VLMs to accelerate progress.

Prior work has also looked at leveraging LLMs and VLMs for robotics applications; particularly ([1; 20; 49; 19]) leveraged LLMs for planning sub-goals in the context of long-horizon tasks together with VLMs for scene understanding and summarization. These sub-goals can then be grounded into actions through language-conditioned policies ([21; 29]). While most of these works focus on deploying and scheduling already learned skills through LLMs, albeit in the real world, our work focuses on an RL system that learns such behaviours from scratch, highlighting the benefits that these models bring to exploration, transfer and experience reuse.

Several methods have been proposed to tackle sparse-reward tasks, either through curriculum learning ([42; 50; 30; 15]), intrinsic motivation ([16; 34]), or hierarchical decomposition ([31; 26]). We demonstrate how LLMs can generate learning curriculums *zero-shot*, without any additional learning or finetuning, and VLMs can automatically provide rewards for these sub-goals, greatly improving learning speed.

Related work has also looked at reusing large datasets of robotic experience by learning a reward model for the new tasks at hand ([5]). However, numerous human annotations of desired rewards need to be gathered for each new task. Instead, as reported in concurrent related work ([47]), we show successful relabeling of past experience leveraging VLMs which can be finetuned with small amounts of data from the target domain.

([14]) is the most similar method to our work: they propose an interplay between LLMs and VLMs to learn sparse-reward tasks in Minecraft ([22; 23]). However, there are some notable differences: they use a vast internet dataset of videos, posts and tutorials to finetune their models, while we demonstrate that it is possible to effectively finetune a VLM with as few as 1000 datapoints, and use off-the-shelf LLMs; additionally, we also investigate and experiment how this framework can be used for data reuse and transfer and learning from observation, besides exploration and skills scheduling, proposing a more unified approach to some core challenges in reinforcement learning.

3   Preliminaries

We use the simulated robotic environment from Lee et al. (25) modelled with the MuJoCo physics simulator (44) for our experiments: a robot arm interacts with an environment composed of a red, a blue and a green object in a basket. We formalise it as a Markov Decision Process (MDP): the observation space $\mathcal{O}$ is composed of $128 \times 128 \times 3$ RGB images coming from two cameras fixed to the edges of the basket. The state space $\mathcal{S}$ represents the 3D position of the objects and the end-effector. The robot is controlled through position control: the action space $\mathcal{A}$ is composed of an x, y position, that we reach using the known inverse kinematics of the robot, where the robot arm can either pick or place an object, inspired by (48; 39). The agent receives a language description of the task $\mathcal{T}$ to solve, which can have two forms: either "*Stack X on top of Y*", where *X* and *Y* are taken from {"*the red object*", "*the green object*", "*the blue object*" } without replacement, or "Stack all three objects", that we also call *Triple Stack*.

A positive reward of $+1$ is provided if the episode is successful, while a reward of 0 is given in any other case. We define the *sparseness* of a task as the average number of environment steps needed, when executing random actions, to solve the task and receive a single reward. With the MDP design we adopt, stacking two objects has a sparseness of 10^3. Stacking all three objects has a sparseness of more than 10^6 as measured by evaluating trajectories from a random policy.

4   A Framework for Language-Centric Agents

The goal of this work is to investigate the use of Foundation Models (3), pre-trained on vast image and text datasets, to design a more general and unified RL robotic agent. We propose a framework that augments from-scratch RL agents with the ability to use the outstanding abilities of LLMs and VLMs to reason about their environment, their task, and the actions to take entirely through language.

To do so, the agent first needs to map visual inputs to text descriptions. Secondly, we need to prompt an LLM with such textual descriptions and a description of the task to provide language instructions to the agent. Finally, the agent needs to ground the output of the LLM into actions.

Bridging Vision and Language using VLMs: To describe the visual inputs taken from the RGB cameras (Sec. 3) in language form, we use **CLIP**, a large, contrastive visual-language model (35). CLIP is composed of an image-encoder ϕ_I and a text-encoder ϕ_T, trained on a vast dataset of noisily paired images and text descriptions, that we also refer to as captions. Each encoder outputs a 128-dimensional embedding vector: embeddings of images and matching text descriptions are optimised to have large cosine similarity. To produce a language description of an image from the environment, the agent feeds an observation o_t to ϕ_I and a possible caption l_n to ϕ_T (Fig. 2). We compute the dot product between the embedding vectors and considers the description correct if the

Figure 2: An illustration of CLIP computing the similarity, as dot product, between observations and text descriptions.

result is larger than γ, a hyperparameter ($\gamma = 0.8$ in our experiments, see Appendix for more details). As we focus on robotic stacking tasks, the descriptions are in the form "*The robot is grasping X*" or "*The X is on top of Y*", where *X* and *Y* are taken from {"*the red object*", "*the green object*", "*the blue object*" } without replacement. We finetune CLIP on a small amount of data from the simulated stacking domain; more details on how this works and analysis on data needs for finetuning are provided in the appendix.

Reasoning through Language with LLMs: Language Models take as input a prompt in the form of language and produce language as output by autoregressively computing the probability distribution of the next token and sampling from this distribution. In our setup, the goal of LLMs is to take a text instruction that represents the task at hand (e.g. "*Stack the red object on the blue object*"), and generate a set of sub-goals for the robot to solve. We use **InstructGPT**, an LLM finetuned on datasets

Figure 3: The VLM can act as an internal reward model by comparing language goals proposed by the LLM to the collected observations.

of language instructions. A qualitative analysis we performed showed that it performed slightly better than LLMs not finetuned on instructions.

The extraordinary in-context learning capabilities of these LLMs allowed us to use them off-the-shelf ([4; 33]), without the need for in-domain finetuning, and guide their behaviour by providing as few as two examples of task instruction and desired language outputs: we describe the environment setting, asking the LLM to find sub-goals that would lead to solving a proposed task, providing two examples of such tasks and relative sub-goals decomposition. With that, the LLM was able to emulate the desired behaviour, not only in content, but also in the formatting of the output language which allowed for efficient parsing. In the Appendix we provide a more detailed description of the prompts we use and the behaviour of the LLMs.

Grounding Instructions into Actions: The language goals provided by the LLMs are then grounded into actions using a language-conditioned policy network. This network, parameterized as a Transformer ([45]), takes an embedding of the language sub-goal and the state of the MDP including object and robot end-effector positions as input, each represented as a different vector, and outputs an action for the robot to execute. This network is trained from scratch within an RL loop as we describe below.

Collect & Infer Learning Paradigm: Our agent learns from interaction with the environment through a method inspired by the Collect & Infer paradigm ([37]). During the Collect phase, the agent interacts with the environment and collects data in the form of states, observations, actions and current goal as (s_t, o_t, a_t, g_i), predicting actions through its policy network, $f_\theta(s_t, g_i) \rightarrow a_t$. After each episode, the agent uses the VLM to infer if any sub-goals have been encountered in the collected data, extracting additional rewards, as we explain in more detail later. If the episode ends with a reward, or if any reward is provided by the VLM, the agent stores the episode data until the reward timestep $[(s_0, o_0, a_0, g_i), \ldots, (s_{T_r-1}, o_{T_r-1}, a_{T_r-1}, g_i)]$ in an experience buffer. We illustrate this pipeline in Fig. 4 (Left). These steps are executed by N distributed, parallel agents, that collect data into the same experience buffer ($N =1000$ in our work). During the Infer phase, we train the policy through Behavioural Cloning on this experience buffer after each agent has completed an episode, hence every N total episodes, implementing a form of Self-Imitation on successful episodes ([32; 13; 7]). The updated weights of the policy are then shared with all the distributed agents and the process repeats.

5 Applications and Results

We described the building blocks that compose our framework. The use of language as the core of the agent provides a unified framework to tackle a series of fundamental challenges in RL. In the following sections, we will investigate each of those contributions, focusing on **exploration**, **reusing past experience data**, **scheduling and reusing skills** and **learning from observation**. The overall framework is also described in Algorithm 1.

5.1 Exploration - Curriculum Generation through Language

RL benefits substantially from carefully crafted, dense rewards ([5]). However, the presence of dense rewards is rare in many real-world environments. Robotic agents need to be able to learn a wide range of tasks in complex environments, but engineering dense reward functions becomes prohibitively time-

Figure 4: **Left:** Illustration of our Collect & Infer pipeline. **Middle, Right**: Learning curves of our framework and a baseline in the *Stack Red on Blue* and *Triple Stack* tasks.

consuming as the number of tasks grows. Efficient and general exploration is therefore imperative to overcome these challenges and scale RL.

A wide variety of methods have been developed over the years to tackle exploration of sparse-reward environments (42; 50; 30; 15; 16; 34; 31; 26). Many propose decomposing a long-horizon task into shorter, easier to learn tasks, through curriculum generation and learning. Usually, these methods need to learn to decompose tasks from scratch, hindering overall learning efficiency. We demonstrate how an RL agent leveraging LLMs can take advantage of a curriculum of text sub-goals that are generated *without any past environment interaction*.

To guide exploration, the agent provides the task description $\mathcal{T}_n$ to the LLM, instructing it to decompose the task into shorter-horizon sub-goals, effectively generating a curriculum of goals $g_{0:G}$ in text form [1]. The agent selects actions as $f_\theta(s_t, \mathcal{T}_n) \to a_t$. While the environment provides a reward only if $\mathcal{T}_n$ is solved, the VLM is deployed to act as an additional, less sparse reward model: given the observations $o_{0:T}$ collected during the episode and all the text sub-goals $g_{0:G}$ proposed by the LLM, it verifies if any of the sub-goals were solved at any step.

We consider an observation o_t to represent a completion state for a sub-goal g_i if $\phi_T(g_i) \cdot \phi_I(o_t) > \gamma$. In that case, the agent adds $[(s_0, o_0, a_0, \mathcal{T}_n), \ldots, (s_{t-1}, o_{t-1}, a_{t-1}, \mathcal{T}_n)]$ to our experience buffer. The process is illustrated in Fig. 3, 11 (in the Appendix).

Algorithm 1 Language-Centric Agent

1: **// Training time:**
2: **for** task in tasks **do**
3:     subgoals = LLM(task) *//find text subgoals given task description*
4:     exp_buffer.append(VLM(offline_buffer, subgoals)) *//extract successful eps from offline buff. collected in past tasks* (**Sec. 5.2**)

5:     **for** ep in episodes **do**
6:         (**Sec. 5.1**)
7:         $E \leftarrow [s_{0:T}, o_{0:T}, a_{0:T}, g_i]$ *//collect ep. trajectory*
8:         $r \leftarrow$ collect final reward
9:         $r_{internal} \leftarrow$ VLM(E, subgoals) *//extract additional rewards for subgoals*
10:        **if** r or $r_{internal}$ **then**
11:            exp_buffer.append($E_{0:T_r}$)   *//Add timesteps until reward*
12:        **if** $ep\%N == 0$ **then**
13:            $\theta \leftarrow$ BC(episode_buffer) *//train agent with BC every N eps*
14: **// Test time:**
15: Receive *text_instruction* or *video_demo*
16: **if** *text_instruction* **then**
17:     subgoals = LLM(*text_instruction*) (**Sec. 5.3**)
18: **else if** *video_demo* **then**
    subgoals = VLM(*video_demo*) (**Sec. 5.4**)
19: execute(subgoals) (**Sec. 5.3**)

Results on Stack *X* on *Y* and Triple Stack. We compare our framework to a baseline agent that learns only through environment rewards in Fig. 4. The learning curves clearly illustrate how our method is substantially more efficient than the baseline on all the tasks. Noticeably, our agent's learning curve rapidly grows in the *Triple Stack* task, while the baseline agent still has to receive a single reward, due to the sparseness of the task being 10^6. We provide a visual example of the extracted sub-goals and rewards in the Appendix.

---

[1]For example, the LLM decomposes "*Stack the red object on the blue object*" into the following sub-goals: ["*The robot is grasping the red object*", "*The red object is on top of the blue object*"]

Decompose new task into text sub-goals. **Extract and relabel** past data using the VLM with the new LLM-extracted sub-goals. **Add** all successful trajectories to the new buffer.

Figure 6: Our framework can reutilise offline data collected on other tasks, extracting successful trajectories for the new task at hand, bootstrapping policy learning.

These results suggest something noteworthy: we can compare the sparseness of the tasks with the number of steps needed to reach a certain success rate, as in Fig. 5. We train our method also on the *Grasp the Red Object* task, the easiest of the three, with sparseness in the order of 10^1. We can see that, under our framework, the number of steps needed grows more slowly than the sparseness of the task. This is a particularly important result, as generally the opposite is true in Reinforcement Learning (34). This slower growth, enabled by the increase in the amount of sub-goals proposed by the LLM as the task becomes sparser, suggests that our framework can scale to even harder tasks and make them tractable, assuming sub-goals can be encountered with a uniform-like distribution at any point during exploration. Additionally, unlike prior approaches that need carefully crafted intrinsic rewards or proaches that need carefully crafted intrinsic rewards or other exploration bonuses our approach can directly leverage prior knowledge from LLMs and VLMs to generate a semantically meaningful curriculum for exploration, thereby paving the way for general agents that explore in a self-motivated manner even in sparse-reward environments.

Figure 5: With our framework, the number of steps needed to reach a certain success rate grows more slowly than the sparseness of the task.

5.2   Extract and Transfer - Efficient Sequential Tasks Learning by Reusing Offline Data

When interacting with their environments, our agents should be able to learn a series of tasks over time, reusing the prior collected data to bootstrap learning on any new task instead of starting *tabula rasa*. This is a fundamental ability to scale up RL systems that learn from experience. Recent work has proposed techniques to adapt task-agnostic offline datasets to new tasks, but they can require laborious human annotations and learning of reward models (5; 46; 9).

We leverage our language based framework to showcase bootstrapping based on the agent's past experience. We train three tasks in sequence: *Stack the red object on the blue object*, *Stack the blue object on the green object*, and *Stack the green object on the red object*, that we call $[\mathcal{T}_{R,B}, \mathcal{T}_{B,G}, \mathcal{T}_{G,R}]$. The intuition is simple: while exploring to solve, for example, $\mathcal{T}_{R,B}$, it is likely that the agent had solved other related tasks, like $\mathcal{T}_{B,G}$ or $\mathcal{T}_{G,R}$, either completely or partially. The agent should therefore be able to extract these examples when trying to solve the new tasks, in order not to start from scratch, but reuse all the exploration data gathered for previous tasks.

As discussed in Sec. 4, our agent gathers an experience buffer of interaction data. We now equip the agent with two different buffers: a *lifelong buffer*, or *offline buffer*, where the agent stores each episode of interaction data, and continues expanding it task after task. Then, the agent has a *new task buffer*, re-initialised at the beginning of each new task, that is filled, as in Sec. 5.1, with trajectories

that result in a reward, either external or internally provided by the VLM using LLM text sub-goals (Fig. 3). The policy network is optimised using the *new task buffer*.

Differently from before however, while the first task, $\mathcal{T}_{R,B}$, is learned from scratch, the agent reuses the data collected during task n to bootstrap the learning of the next task $n + 1$. The LLM decomposes $\mathcal{T}_{n+1}$ into text sub-goals $[g_0, \ldots, g_{L-1}]$. The agent then extracts from the *lifelong/offline buffer* each stored episode $\mathcal{E}_n = [(s_{0:T,n}, o_{0:T,n}, a_{0:T,n})]$. It then takes each episode's observation $o_{t,n}$ and uses the VLM to compute dot-products score between all image observations and all text sub-goals as $\phi_T(g_l) \cdot \phi_I(o_t)$. If the score is larger than the threshold γ the agent adds all the episode's timesteps up to t, $[(s_{0:t,n}, o_{0:t,n}, a_{0:t,n})]$ to the *new task buffer*. The process is illustrated in Fig. 6.

Figure 7: In our experiments, the agent can learn task $n + 1$ faster than task n by reusing past experience data.

This procedure is repeated for each new task at the beginning of training. Following this procedure, the agent does not start learning new tasks *tabula rasa*: at the beginning of task $\mathcal{T}_n$, the current experience buffer is filled with episodes useful to learn the task extracted from $\mathcal{T}_{0:n}$. When n increases, the amount of data extracted from $\mathcal{T}_{0:n}$ increases as well, speeding up learning.

Results on Experience Reuse for Sequential Tasks Learning. The agent applies this method to learn $[\mathcal{T}_{R,B}, \mathcal{T}_{B,G}, \mathcal{T}_{G,R}]$ in succession. At the beginning of each new task we re-initialise the policy weights: our goal is to investigate the ability of our framework to extract and re-use data, therefore we isolate and eliminate effects that could be due to network generalisation.

We plot how many interaction steps the agent needs to take in the environment to reach 50% success rate on each new task in Fig. 7. Our experiments clearly illustrate the effectiveness of our technique in reusing data collected for previous tasks, improving the learning efficiency of new tasks.

These results suggest that our framework can be employed to unlock lifelong learning capabilities in robotic agents: the more tasks are learned in succession, the faster the next one is learned. This can be particularly beneficial when deploying agents in open-ended environments, particularly in the real world; by leveraging data across its lifetime the agent has encountered it should be able to learn novel tasks far faster than learning purely from scratch.

5.3 Scheduling and Reusing Learned Skills

We described how our framework enables the agent with the ability to efficiently explore and learn to solve sparse-reward tasks, and to reuse and transfer data for lifelong learning.

Using its language-conditioned policy (Sec. 4), the agent can thus learn a series of M skills, described as a language goal $g_{0:M}$ (e.g. "*The green object is on top of the red object*" or "*The robot is grasping the blue object*").

Our framework allows the agent to schedule and reuse the M skills it has learned to solve novel tasks, beyond what the agent encountered during training. The paradigm follows

Figure 8: Our framework can break down a task into a list of skills using the LLM, and execute each skill until the VLM predicts that its sub-goal has been reached.

the same steps we encountered in the previous sections: a command like *Stack the green object on top of the red object* or *Stack the red on the blue and then the green on the red* is fed to the LLM, which is prompted to decompose it into a list of shorter-horizon goals, $g_{0:N}$. The agent can then ground these into actions using the policy network as $f_\theta(s_t, g_n) \rightarrow a_t$.

Figure 9: An illustration of the agent learning from observation using our framework.

When executing the n-th skill, the VLM computes at each timestep if $\phi_T(g_n) \cdot \phi_I(o_t) > \gamma$, thus checking if the goal of the skill has been reached in the current observation. In that case, the agent starts executing the $n + 1$-th skill, unless the task is solved.

5.4 Learning from Observation: Mapping Videos to Skills

Learning from observing an external agent is a desirable ability for general agents, but this often requires specifically designed algorithms and models (41; 10; 51). Our agent can be conditioned on a *video* of an expert performing the task, enabling *one-shot learning from observation*. In our tests, the agent takes a video of a human stacking the objects with their hand. The video is divided into F frames, $v_{0:F}$. The agent then uses the VLM, paired with the M textual description of the learned skills, expressed as sub-goals $g_{0:M}$, to detect what sub-goals the expert trajectory encountered as follows: (1) the agent embeds each learned skill/sub-goal through $\phi_T(g_m)$ and each video frame through $\phi_I(v_f)$ and compute the dot product between each pair. (2) it lists all the sub-goals that obtain a similarity larger than γ, collecting the chronological list of sub-goals the expert encountered during the trajectory. (3) It executes the list of sub-goals as described in Fig. 8.

Despite being finetuned only on images from the MuJoCo simulation (Sec. 4), the VLM was able to accurately predict the correct text-image correspondences on real-world images depicting both a robot or a human arm. Notice also how we still refer to it as "*the robot*" in the captions (Fig. 9), but the VLM generalises to a human hand regardless.

6   Conclusion

We propose a framework that puts language at the core of an agent. Through a series of experiments, we demonstrate how this framework provides a more unified approach with respect to the current literature to tackle a series of core RL challenges that would normally require separate algorithms and models: **1)** exploring in sparse-reward tasks **2)** reusing experience data to bootstrap learning of new skills **3)** scheduling learned skills to solve novel tasks and **4)** learning from observing expert agents. These initial results suggest that leveraging foundation models can lead to general RL algorithms that can tackle a variety of problems with improved efficiency and generality. By leveraging the prior knowledge within these models we can design better robotic agents that are capable of solving challenging tasks directly in the real world. We provide a list of current limitations and future work in the Appendix.

References

[1] Michael Ahn, Anthony Brohan, Noah Brown, Yevgen Chebotar, Omar Cortes, Byron David, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, et al. Do as i can, not as i say: Grounding language in robotic affordances. *arXiv preprint arXiv:2204.01691*, 2022.

[2] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *arXiv preprint arXiv:2204.14198*, 2022.

[3] Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

[4] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[5] Serkan Cabi, Sergio Gómez Colmenarejo, Alexander Novikov, Ksenia Konyushkova, Scott Reed, Rae Jeong, Konrad Zolna, Yusuf Aytar, David Budden, Mel Vecerik, et al. Scaling data-driven robotics with reward sketching and batch reinforcement learning. *arXiv preprint arXiv:1909.12200*, 2019.

[6] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 9650–9660, 2021.

[7] Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

[8] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

[9] Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

[10] Neha Das, Sarah Bechtle, Todor Davchev, Dinesh Jayaraman, Akshara Rai, and Franziska Meier. Model-based inverse reinforcement learning from visual demonstrations. In Jens Kober, Fabio Ramos, and Claire Tomlin, editors, *Proceedings of the 2020 Conference on Robot Learning*, volume 155 of *Proceedings of Machine Learning Research*, pages 1930–1942. PMLR, 16–18 Nov 2021. URL https://proceedings.mlr.press/v155/das21a.html.

[11] Ishita Dasgupta, Christine Kaeser-Chen, Kenneth Marino, Arun Ahuja, Sheila Babayan, Felix Hill, and Rob Fergus. Collaborating with language models for embodied reasoning. *arXiv preprint arXiv:2302.00763*, 2023.

[12] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[13] Adrien Ecoffet, Joost Huizinga, Joel Lehman, Kenneth O Stanley, and Jeff Clune. Go-explore: a new approach for hard-exploration problems. *arXiv preprint arXiv:1901.10995*, 2019.

[14] Linxi Fan, Guanzhi Wang, Yunfan Jiang, Ajay Mandlekar, Yuncong Yang, Haoyi Zhu, Andrew Tang, De-An Huang, Yuke Zhu, and Anima Anandkumar. Minedojo: Building open-ended embodied agents with internet-scale knowledge. *arXiv preprint arXiv:2206.08853*, 2022.

[15] Carlos Florensa, David Held, Markus Wulfmeier, Michael Zhang, and Pieter Abbeel. Reverse curriculum generation for reinforcement learning. In *Conference on robot learning*, pages 482–495. PMLR, 2017.

[16] Oliver Groth, Markus Wulfmeier, Giulia Vezzani, Vibhavari Dasagi, Tim Hertweck, Roland Hafner, Nicolas Heess, and Martin Riedmiller. Is curiosity all you need? on the utility of emergent behaviours from curious exploration. *arXiv preprint arXiv:2109.08603*, 2021.

[17] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16000–16009, 2022.

[18] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. *arXiv preprint arXiv:2203.15556*, 2022.

[19] Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. In *International Conference on Machine Learning*, pages 9118–9147. PMLR, 2022.

[20] Wenlong Huang, Fei Xia, Ted Xiao, Harris Chan, Jacky Liang, Pete Florence, Andy Zeng, Jonathan Tompson, Igor Mordatch, Yevgen Chebotar, et al. Inner monologue: Embodied reasoning through planning with language models. *arXiv preprint arXiv:2207.05608*, 2022.

[21] Eric Jang, Alex Irpan, Mohi Khansari, Daniel Kappler, Frederik Ebert, Corey Lynch, Sergey Levine, and Chelsea Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2022.

[22] Matthew Johnson, Katja Hofmann, Tim Hutton, and David Bignell. The malmo platform for artificial intelligence experimentation. In *International Joint Conference on Artificial Intelligence*, 2016.

[23] Anssi Kanervisto, Stephanie Milani, Karolis Ramanauskas, Nicholay Topin, Zichuan Lin, Jun-you Li, Jianing Shi, Deheng Ye, Qiang Fu, Wei Yang, et al. Minerl diamond 2021 competition: Overview, results, and lessons learned. *NeurIPS 2021 Competitions and Demonstrations Track*, pages 13–28, 2022.

[24] Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part V 16*, pages 491–507. Springer, 2020.

[25] Alex X Lee, Coline Manon Devin, Yuxiang Zhou, Thomas Lampe, Konstantinos Bousmalis, Jost Tobias Springenberg, Arunkumar Byravan, Abbas Abdolmaleki, Nimrod Gileadi, David Khosid, et al. Beyond pick-and-place: Tackling robotic stacking of diverse shapes. In *5th Annual Conference on Robot Learning*, 2021.

[26] Andrew Levy, George Konidaris, Robert Platt, and Kate Saenko. Learning multi-level hierar-chies with hindsight. *arXiv preprint arXiv:1712.00948*, 2017.

[27] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023.

[28] Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, et al. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097, 2022.

[29] Corey Lynch and Pierre Sermanet. Language conditioned imitation learning over unstructured data. *arXiv preprint arXiv:2005.07648*, 2020.

[30] Tambet Matiisen, Avital Oliver, Taco Cohen, and John Schulman. Teacher–student curriculum learning. *IEEE transactions on neural networks and learning systems*, 31(9):3732–3740, 2019.

[31] Ofir Nachum, Shixiang Shane Gu, Honglak Lee, and Sergey Levine. Data-efficient hierarchical reinforcement learning. *Advances in neural information processing systems*, 31, 2018.

[32] Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. In *International Conference on Machine Learning*, pages 3878–3887. PMLR, 2018.

[33] Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, et al. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*, 2022.

[34] Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International conference on machine learning*, pages 2778–2787. PMLR, 2017.

[35] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR, 2021.

[36] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

[37] Martin Riedmiller, Jost Tobias Springenberg, Roland Hafner, and Nicolas Heess. Collect & infer - a fresh look at data-efficient reinforcement learning. In *5th Annual Conference on Robot Learning, Blue Sky Submission Track*, 2021. URL https://openreview.net/forum?id=qscEfLT5VJK.

[38] Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, et al. Laion-5b: An open large-scale dataset for training next generation image-text models. *arXiv preprint arXiv:2210.08402*, 2022.

[39] Mohit Shridhar, Lucas Manuelli, and Dieter Fox. Cliport: What and where pathways for robotic manipulation. In *Conference on Robot Learning*, pages 894–906. PMLR, 2022.

[40] David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *arXiv preprint arXiv:1712.01815*, 2017.

[41] Laura Smith, Nikita Dhawan, Marvin Zhang, Pieter Abbeel, and Sergey Levine. Avid: Learning multi-stage tasks via pixel-level translation of human videos. *arXiv preprint arXiv:1912.04443*, 2019.

[42] Sainbayar Sukhbaatar, Zeming Lin, Ilya Kostrikov, Gabriel Synnaeve, Arthur Szlam, and Rob Fergus. Intrinsic motivation and automatic curricula via asymmetric self-play. *arXiv preprint arXiv:1703.05407*, 2017.

[43] Theodore Sumers, Kenneth Marino, Arun Ahuja, Rob Fergus, and Ishita Dasgupta. Distilling internet-scale vision-language models into embodied agents. *arXiv preprint arXiv:2301.12507*, 2023.

[44] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033, 2012. doi: 10.1109/IROS.2012.6386109.

[45] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[46] Christian Wirth, Riad Akrour, Gerhard Neumann, and Johannes Fürnkranz. A survey of preference-based reinforcement learning methods. *J. Mach. Learn. Res.*, 18:136:1–136:46, 2017.

[47] Ted Xiao, Harris Chan, Pierre Sermanet, Ayzaan Wahid, Anthony Brohan, Karol Hausman, Sergey Levine, and Jonathan Tompson. Robotic skill acquisition via instruction augmentation with vision-language models. *arXiv preprint arXiv:2211.11736*, 2022.

[48] Andy Zeng, Pete Florence, Jonathan Tompson, Stefan Welker, Jonathan Chien, Maria Attarian, Travis Armstrong, Ivan Krasin, Dan Duong, Vikas Sindhwani, et al. Transporter networks: Rearranging the visual world for robotic manipulation. In *Conference on Robot Learning*, pages 726–747. PMLR, 2021.

[49] Andy Zeng, Adrian Wong, Stefan Welker, Krzysztof Choromanski, Federico Tombari, Aveek Purohit, Michael Ryoo, Vikas Sindhwani, Johnny Lee, Vincent Vanhoucke, et al. Socratic models: Composing zero-shot multimodal reasoning with language. *arXiv preprint arXiv:2204.00598*, 2022.

[50] Yunzhi Zhang, Pieter Abbeel, and Lerrel Pinto. Automatic curriculum learning through value disagreement. *Advances in Neural Information Processing Systems*, 33:7648–7659, 2020.

[51] Yuxiang Zhou, Yusuf Aytar, and Konstantinos Bousmalis. Manipulator-independent representations for visual imitation. *arXiv preprint arXiv:2103.09016*, 2021.