Symbolic Explanations for Hyperparameter Optimization

Anonymous[1]

[1]Anonymous Institution

Abstract Hyperparameter optimization (HPO) methods can determine well-performing hyperparameter configurations efficiently but often lack insights and transparency. We propose to apply symbolic regression to meta-data collected with Bayesian optimization (BO) during HPO. In contrast to prior approaches explaining the effects of hyperparameters on model performance, symbolic regression allows for obtaining explicit formulas quantifying the relation between hyperparameter values and model performance. Overall, our approach aims to make the HPO process more explainable and human-centered, addressing the needs of multiple user groups: First, providing insights into the HPO process can support data scientists and machine learning practitioners in their decisions when using and interacting with HPO tools. Second, obtaining explicit formulas and inspecting their properties could help researchers better understand the HPO loss landscape. In an experimental evaluation, we find that naively applying symbolic regression directly to meta-data collected during HPO is affected by the sampling bias introduced by BO. However, the true underlying loss landscape can be approximated by fitting the symbolic regression on the surrogate model trained during BO. By penalizing longer formulas, symbolic regression furthermore allows the user to decide how to balance the accuracy and explainability of the resulting formulas.

1 Introduction

As the performance of machine learning (ML) models crucially depends on the choice of suitable hyperparameter configurations (Bischl et al., 2023; Feurer and Hutter, 2019), a plethora of tools focused on finding such configurations has been developed during the last years (Akiba et al., 2019; Awad et al., 2021; Balandat et al., 2020; Falkner et al., 2018; Li et al., 2018; Lindauer et al., 2022). Despite their efficiency in finding a well-performing configuration quickly, these tools are often not adopted in practice - an important reason for this is the lack of insights into the underlying HPO problem generated by the optimization process and in turn, the returned hyperparameter configuration (Blom et al., 2021). In fact, Godbole et al. (2023) advocate against plainly applying HPO tools in a recent publication and instead argue in favor of an interactive HPO process, tailored to gain insights into the problem. Considering that the vast majority of existing tools works in a black-box fashion without offering any form of insight from or explanation of both the optimization process and the returned configuration, practitioners' reluctance seems understandable.

In this work, we take a step to alleviate this situation by moving toward a more human-centered and interpretable HPO process (Moosbauer, Casalicchio, et al., 2022; Moosbauer, Herbinger, et al., 2021) that generates insights into the underlying HPO problem while searching for a well-performing hyperparameter configuration. To this end, we propose to apply symbolic regression to the meta-data collected with Bayesian optimization (BO) during HPO, allowing us to infer a closed-form expression of the relation between hyperparameter values and the performance of a hyperparameter configuration. The interpretability of this expression can be controlled via a parsimony hyperparameter trading off (a) the complexity of the expression and (b) how well it describes the actual dependency between hyperparameter values and model performance. We show that naively applying symbolic regression does not yield an expression with high explanation power due to the bias in the meta-data used for training, which is caused by the HPO process' sampling strategy, and suggest two strategies to mitigate this problem.

For practitioners, our approach offers two main advantages at the slight additional cost of training a symbolic regression model: First, they obtain a concrete insight into the HPO loss landscape at hand (Pushak and Hoos, 2022; Schneider et al., 2022) in the form of a formula analytically describing how hyperparameter values influence the performance of a configuration. Second, the quantification of the loss landscape allows to set the final configuration into a broader context by informing the user about the surrounding HPO configuration space regions. Moreover, although we focus on BO-powered HPO in this work, the approach can be applied on top of any sampling- and surrogate-based HPO tool, which collects corresponding meta-data. As such, it does not only make HPO more interpretable and insightful for a practitioner, but it is also applicable in a versatile manner, giving it the potential for a large impact on HPO in practice.

In an extensive experimental study, we show that the symbolic expressions indeed faithfully model the HPO loss landscape in terms of a low approximation error while still being of a low enough complexity to be interpretable. In addition, we analyze the trade-off between faithfulness and interpretability based on a sensitivity analysis of the parsimony hyperparameter of our approach.

Altogether, we make the following contributions:

1. We propose an easy workflow offering practitioners the ability to gain insights into the HPO process at little additional cost in the order of minutes.

2. As part of this, we leverage symbolic regression to learn an analytical, closed-form expression to model the dependency between the model performance, i.e., the performance of an HPO configuration, and the values of the corresponding hyperparameters.

3. We show that learning such a symbolic model naively on meta-data collected during the HPO process does not yield a good explanation due to the bias caused by the HPO sampling strategy.

4. We propose a systematic approach to support a practitioner in controlling the trade-off between the symbolic model's faithfulness and interpretability based on a parsimony hyperparameter.

2 Related work

Increased efforts towards explainable HPO approaches have been made by Hutter et al. (2014) and Jin (2022), who calculate hyperparameter importance values analogously to the concept of feature importance, and by Moosbauer, Herbinger, et al. (2020, 2021) and Probst et al. (2019), who leverage partial dependence plots (PDPs) as a posthoc explanation of the HPO process. PDPs (Friedman, 2001) can be used to visualize the marginal effect of one or two features on a model's prediction, i.e., in the context of HPO via BO, the marginal effect of a hyperparameter on the cost predicted by the surrogate model. A significant obstacle to the usage of PDPs for the analysis of the HPO process is posed by the bias introduced through the BO process due to the exploitative sampling of configurations during the search. While this limitation is addressed in a follow-up work by splitting up the hyperparameter space by certainty of the surrogate model as well as modifying the sampling strategy to mitigate the bias in the sampling (Moosbauer, Casalicchio, et al., 2022), the approach is inherently limited to the analysis of one or two hyperparameters at once due to the nature of the PDPs. Very recently, Sass et al. (2022) and Zöller et al. (2022) published first packages which unify a variety of explainability methods in frameworks that allow directly analyzing the optimization process of several automated machine learning tools.

Further, symbolic regression has recently successfully been applied in the context of explainable AutoML. Gijsbers et al. (2021) aim to learn a symbolic formula mapping dataset meta-features to default hyperparameter configurations. While explainability is not the main goal, the approach shows that symbolic regression can be used to find formulas that suggest hyperparameter configurations with competitive or better performance compared to hand-picked or default configurations. In comparison to our approach, the authors map dataset features to default configurations, whereas we aim to explain the relation between hyperparameters and costs of configurations.

$$s(\text{alpha}, \text{batch\_size}) = 0.078 \cdot \exp\left(\frac{\text{alpha}}{4 \cdot \text{batch\_size}}\right)$$

Figure 1: An example of a symbolic expression s, visualized as an expression tree. The formula expresses how two hyperparameters typical to neural networks, the regularization factor *alpha* and the *batch_size*, influence the predictive performance of the network.

3 Background

As a foundation for discussing our approach, aimed at making the HPO process more insightful and explainable, we provide brief introductions of HPO, BO, and symbolic regression.

Hyperparameter Optimization (HPO). Carefully choosing the hyperparameters of an ML model for a new task is essential to good model performance (Bischl et al., 2023; Feurer and Hutter, 2019). For a given dataset $\mathcal{D} = \{x_i, y_i\}_{i=1}^{n} \subset \mathcal{X} \times \mathcal{Y}$, the goal of HPO is to find a hyperparameter configuration $\lambda^* \in \Lambda$ from the configuration space $\Lambda \subseteq \mathbb{R}^d$ that minimizes a given cost function, i.e. $\lambda^* \in \arg\min_{\lambda \in \Lambda} c(\lambda)$. The cost function $c : \Lambda \to \mathbb{R}$ is an unknown *black-box function* that reflects the validation loss on the given dataset $\mathcal{D}$ of the model instantiated with the given hyperparameter configuration. For ease of notation, we do not make the dependence of c on the dataset $\mathcal{D}$ explicit.

Bayesian Optimization (BO). BO is a global optimization procedure that searches for the optimum of a given *black-box function* by sequentially evaluating the function at certain points (Mockus, 1989). A surrogate model is continuously updated with these points and serves as a basis for an acquisition function that, in turn, suggests the next evaluation point. Due to its sample efficiency and lack of assumptions about the optimized function, it is a popular approach to HPO and has compared favorably to manually tuning hyperparameters or using strategies such as random or grid search (Bergstra et al., 2011; Bischl et al., 2023; Snoek et al., 2012; Turner et al., 2021). When applying BO to HPO, the optimized black-box function is the cost function $c : \Lambda \to \mathbb{R}$, which should be minimized. Usual choices for surrogate models are Gaussian processes (GP) (Rasmussen and Williams, 2006) or, especially in the case of HPO, where the optimized function can have many parameters, a random forest (Breiman, 2001). As a drawback to their usefulness in the optimization process, the methods' complexity dictates that neither gives a clear insight into the relation between the in- and outputs of the black-box function and, thus, the optimization process.

Symbolic Regression. In contrast to solely performance-oriented approaches, symbolic regression (SR) approximates an unknown function from a set of samples $\mathcal{D} = \{x_i, y_i\}_{i=1}^{n} \subset \mathcal{X} \times \mathcal{Y}$ by constructing a model $s : \mathcal{X} \to \mathcal{Y}$ from mathematical operators, constants, and input variables with the goal to strike a balance between simplicity and accuracy of fit (Augusto and Barbosa, 2000). SR models can be represented as trees of expressions, as illustrated in Figure 1. If their complexity is sufficiently limited, they provide an explainable relationship between in- and outputs through the found expression itself as well as visualizations thereof in terms of plots or tree structures. Finding such an expression is an NP-hard problem; as such, it is often approximately solved with approaches such as genetic programming (Koza, 1994) and recently also methods employing gradient-descent (Alaa and Schaar, 2019; Crabbe et al., 2020; Petersen et al., 2021). Genetic programming refers to a class of evolutionary algorithms, which leverages a tree structure as genome representation. It iteratively refines a set $S \subset \mathcal{S}$ of individuals $s \in S$ by creating new candidates through genetic operations such as crossover and mutation, evaluating their fitness according to a fitness function $f : \mathcal{S} \to \mathbb{R}$, and subsequently selecting a new set of individuals based on their fitness.

Figure 2: This figure visualizes the overall process of our symbolic HPO explanation approach. The phases correspond to the ones described in Section 4.

4 Learning and Leveraging Symbolic Explanations

Arguably, automating hyperparameter optimization in an efficient way while still generating valuable insights for the practitioner is a challenging task. To move to such a more human-centered HPO process, we propose to learn a numerical expression explaining the relation between the values of optimized hyperparameters and the corresponding performance. The overall process is visualized in Figure 2 and consists of the following steps:

1. Run a BO-based HPO tool and collect (a) the meta-data consisting of the evaluated configurations and their performance and (b) the final surrogate model.

2. Learn a symbolic regression model on either (a) the collected meta-data, or (b) randomly sampled configurations, which are evaluated using the true cost function, or (c) randomly sampled configurations, whose performance is estimated using the Gaussian process.

3. Leverage the symbolic explanation of the underlying HPO loss landscape.

In the following sections, we explain Steps 2 and 3 in more detail, followed by an elaboration on the limitations of our approach.

4.1 Learning a Symbolic Hyperparameter Explanation

To learn a symbolic explanation of the relation between the hyperparameters' values and the corresponding configuration's performance, appropriate training data is needed. The most straightforward way is to learn a symbolic model $s : \Lambda \to \mathbb{R}$ from meta-data consisting of N configurations collected during the HPO process, which is of the form

$$\mathcal{D}_{meta} = \left\{ \left(\boldsymbol{\lambda}_i, c(\boldsymbol{\lambda}_i) \right) \right\}_{i=1}^{N} \subset \Lambda \times \mathbb{R} \ . \tag{1}$$

Although there is some work on learning such a symbolic model using gradient-based methods (Alaa and Schaar, 2019; Crabbe et al., 2020; Petersen et al., 2021), we found that the classical approach leveraging genetic programming (Koza, 1994) works most reliably.

4.1.1 Mitigating Sampling Bias.
As indicated by our experimental evaluation and recently observed by Moosbauer, Herbinger, et al. (2021), models trained on meta-data generated during the search process tend to be biased towards the well-performing regions of the HPO loss landscape. This is caused by the HPO process sampling these points, as it will - in most cases - prefer such well-performing regions, which leads to a $\mathcal{D}_{meta}$ whose points are not even roughly equally distributed across the entire HPO search space. This is visualized in Figure 3b, which shows the configurations sampled by the HPO tool at the top, and randomly drawn configurations in the middle. Correspondingly, directly training on the sampled data can lead to an explanation biased towards those regions.

(a)   (b)

Figure 3: This figure displays several representations of the HPO loss landscape defined by tuning the (log) regularization hyperparameter α and the (log) batch size of a neural network on the kc1 dataset with a limit of 200 samples for the HPO process. (a) The top element approximates the ground truth loss landscape by a fine-tuned grid-search over the configuration space. The bottom element visualizes the loss landscape obtained from the actual surrogate model of the HPO process. (b) The top element shows both the configurations sampled by the HPO process and the loss landscape obtained from the symbolic model fitted on the sampled meta-data. The middle element shows randomly sampled configurations and the loss landscape obtained from the symbolic model fitted on them. The bottom element visualizes the loss landscape obtained from the symbolic model fitted on the randomly sampled configurations, whose performance is approximated using the surrogate model of the HPO process.

As Figure 3b (middle) suggests, a solution to this problem is to fit the symbolic model s on randomly sampled configurations instead of the ones sampled by the HPO process to reach a sufficient coverage of the search space and allow for a good prediction performance. However, this comes with the drawback that these randomly sampled points might not have been evaluated during the HPO run, leading to an increased cost for the required additional evaluation of those points. This cost can be circumvented by not evaluating these points, but leveraging the surrogate model $\widehat{c}$ learned during the HPO process in order to predict the performance of these randomly sampled points. Although this offers a potential for error propagation if the surrogate model has a bad fit, this strategy tends to work well in practice as our experimental evaluation corroborates.

4.1.2 Ensuring Interpretability. To ensure that the resulting formula is still of an interpretable complexity, we employ a regularization penalty based on the size of the formula. More precisely, we assign a fitness $f : \mathcal{S} \to \mathbb{R}$ to the candidates of the populations to be a linear combination of their predictive performance and the complexity penalty of a formula $s : \Lambda \to \mathbb{R} \in \mathcal{S}$, i.e.,

$$f_c(s) = \mathcal{L}(c, s) + \zeta \cdot p(s) \ . \tag{2}$$

Here, $\mathcal{L}(c, s)$ returns the loss between the (approximated) performance of the sampled configurations according to a cost function c and the predicted cost according to the symbolic model s on the above mentioned training dataset $\mathcal{D}_{meta}$ (Equation 1), $p(s)$ returns the complexity penalty for formula s and $\zeta \in \mathbb{R}$ is a parsimony hyperparameter of our approach. For the third instantiation of our approach, we use the surrogate $\widehat{c}$ instead of c to approximate the performance of the sampled configurations as outlined at the beginning of Section 4. For this work, we chose the root-mean-square error for $\mathcal{L}$ and the length, i.e., number of operations of s as the penalty p.

In order to achieve a desired complexity, the parsimony hyperparameter ζ has to be set accordingly. Due to the potential difference between the scale of the loss $\mathcal{L}$ and the penalty function p, doing so is not a straightforward task. Similar problems are not unknown in the meta-algorithmics community, e.g., in combined ranking and regression approaches for algorithm selection (Fehring et al., 2022; Hanselle et al., 2020). As a solution, we suggest to leverage the elbow heuristic (Thorndike, 1953), which is well-known in clustering. The underlying idea is to fit the symbolic regression multiple times with different parsimony values as visualized in Figure 5, starting with a high value and decreasing it until the increase in performance no longer outweighs the increasing complexity and thus decreasing explainability. More details on this idea can be found in Appendix A.

4.2 Leveraging a Symbolic Hyperparameter Explanation

Once a symbolic regression model, as outlined in Section 4.1, is learned, we can quantify the relation between the values of the hyperparameters and the performance of the corresponding configuration in the form of a closed-form analytic expression, i.e., a formula. Below, we outline some exemplary uses cases for such a symbolic hyperparameter explanation.

4.2.1 Characterizing the HPO Loss Landscape.
While there has been work on characterizing the loss landscape of HPO problems (Pushak and Hoos, 2022; Schneider et al., 2022), the focus has mostly been on indirect characterization ways by computing certain statistics on sampled configurations and their performance. The symbolic model allows for a much more concrete characterization of the landscape in the form of a formula. This also gives an easy way to plot the landscape as Figure 3a demonstrates. The top element approximates the ground truth landscape based on a high resolution grid-search, the middle element shows the loss landscape as predicted by the original HPO surrogate model whereas the bottom element shows the loss landscape as predicted by the symbolic explanation model.

4.2.2 Theoretical Analysis of HPO Loss Landscapes.
A concrete closed-form expression quantifying the relation between the values of hyperparameters and the performance of the corresponding configuration has the potential to pave the way for a theoretical analysis of HPO loss landscapes. Under the assumption that the formula is at least roughly correct, theoreticians might be able to analyze the concrete interaction effects of hyperparameters on the performance, potentially across several datasets and thus might gain insights into why certain algorithms perform very well on some datasets and worse on others.

4.3 Limitations

As of now, our approach can only be used if the HPO configuration space consists solely of numerical and no categorical or other types of hyperparameters. This limitation arises as the formulas assume the hyperparameters to be real numbers. Moreover, the set of hyperparameters, which should be included in the explanation and the one being optimized by the HPO tool has to be the same as the construction of a meta-data training dataset for the symbolic regression is problematic due to noise imposed onto the performance by the hyperparameters unconsidered for the explanation. One way to alleviate this situation is to leverage the partial dependence function, as done by Moosbauer, Herbinger, et al. (2021), which essentially aims to express the expected performance of a configuration independent of a subset of the hyperparameters by integrating them out. Lastly, ensuring interpretability via the parsimony coefficient controlling the penalty is a very simple solution to the actual underlying multi-objective optimization problem. In the interest of space, we discuss these limitations in more detail in Appendix C.

5 Experimental Evaluation

In this section, we show that symbolic models can provide simple explanations of the HPO loss landscape while faithfully capturing its dynamics. Leveraging a subset of problems from HPOBench

(Eggensperger et al., 2021), a collection of benchmark problems for HPO, we apply symbolic regression to learn the dependency between hyperparameter values and performance for a large range of models, hyperparameters, and datasets. As the cost associated with a hyperparameter configuration, we consider the validation error rate evaluated via hold-out testing, using 0.33% of each dataset for validation. We use the BO-powered HPO tool SMAC (Lindauer et al., 2022) as a basis for the evaluation (Phase 1 in the description in Section 4) and then compare the three ways of training a symbolic explanation based on the HPO run as described in Section 4. SR(BO) refers to a symbolic regression fitted based on the meta-data collected by the HPO process, SR(Random) refers to a training based on randomly sampled configurations, which are evaluated, whereas SR(BO-GP) refers to a training based on randomly sampled points, whose performance is approximated using the surrogate model of the HPO process - in this case a Gaussian process (GP). Technical details on the experiments such as the number of seeds, the hardware for execution, and the used resources can be found in Appendix D. The code for running the experiments is provided online[1]. In the following sections, we analyze the accuracy of the symbolic explanation (Section 5.1) under varying HPO sample sizes and the trade-off between the faithfulness and explainability (Section 5.2).

5.1 Faithfulness of Symbolic Explanations

In Table 1, the root-mean-square error (RMSE) between the cost predicted by the symbolic regression and the true cost averaged over 100 test configurations is shown for the three meta-data generation procedures described in Section 4.1. The RMSE between the cost predicted by the GP and the true cost is shown as a baseline. As we expect due to sampling bias, when fitted on the BO samples directly, the RMSE is highest for most models and datasets, while fitting on random samples results in the lowest error in most cases, but not on average. However, we find that leveraging the GP to obtain the cost predictions for the random samples results in error values close to those we obtain when using the true cost values. This suggests that this approach is suitable to obtain a faithful explanation without evaluating additional hyperparameter configurations as SR (Random) does.

In addition, we study how the error of the symbolic regression and the GP baseline depends on the number of samples it is fit on, i.e., how faithful the symbolic explanation is under varying sample sizes. Figure 4 displays the results for two models on two datasets. Our results show that the error decreases slightly between 20 and 60 samples. However, adding more samples does not have a large effect on the error, suggesting that a small number of samples is sufficient for the studied models and datasets to apply symbolic regression as explainer. For more results, see Appendix E.

5.2 Faithfulness vs. Interpretability

By penalizing longer formulas, symbolic regression allows to balance the accuracy and interpretability of the resulting formulas via a parsimony hyperparameter ζ. Figure 5 shows the RMSE between the cost predicted by the symbolic regression and the true cost as well as the complexity expressed in terms of the number of operations being present in the resulting formulas for multiple values of ζ. As expected, for all shown models and datasets, the error decreases with increasing complexity. We suggest (cf. Section 4.1.2) using the elbow heuristic to select the appropriate value of ζ. The results depicted imply that this strategy is indeed justified.

Finally, we show some exemplary formulas obtained by our approach. They describe the dependency between the regularization hyperparameter α and the batch size of a neural network on the kc1 dataset, with the symbolic regression fitted on 400 random samples evaluated with the Gaussian process obtained after collecting 200 samples with BO with varying seeds.

$$s(\text{alpha, batch\_size}) = 0.078 \cdot \exp\left(\text{alpha}/(4 \cdot \text{batch\_size})\right)$$

$$s(\text{alpha, batch\_size}) = 0.104 \cdot \sqrt{|\sin(\text{alpha})|} + 0.07$$

---

[1] `https://anon-github.automl.cc/r/symbolic-reg-hpo-A6EE`

Figure 4: RMSE between the cost predicted by the SR and the true cost for different numbers of samples. The SR is fitted on either samples collected by BO (BO), random samples with their true cost (Random) or random samples evaluated with the GP (BO-GP). The RMSE of the GP (GP Baseline) is shown for comparison. The SR is fitted on the number of samples shown, with parsimony coefficient 0.0001. For GP-BO, it is fitted on random 400 samples evaluated with the GP obtained after collecting the shown number of samples with BO.

Figure 5: RMSE between the cost predicted by the SR and the true cost for different values of the parsimony coefficient ζ. The symbolic regression is fitted on random 400 samples evaluated with the Gaussian process obtained after collecting 200 samples with BO.

Model	Hyperparameters	Dataset	SR (BO)	SR (Random)	SR (BO-GP)	GP Baseline
Logistic Regression	alpha, eta0	blood-transfusion	0.015 ± 0.006	**0.010 ± 0.002**	0.016 ± 0.005	0.019 ± 0.009
		vehicle	0.045 ± 0.006	**0.035 ± 0.003**	0.041 ± 0.004	0.026 ± 0.004
		Australian	0.361 ± 1.275	**0.023 ± 0.007**	0.024 ± 0.005	0.024 ± 0.006
		car	0.029 ± 0.007	**0.025 ± 0.002**	0.026 ± 0.002	0.018 ± 0.002
		phoneme	0.012 ± 0.003	**0.010 ± 0.003**	0.011 ± 0.003	0.011 ± 0.003
		segment	0.062 ± 0.036	**0.028 ± 0.016**	0.033 ± 0.005	0.035 ± 0.005
		credit-g	0.028 ± 0.006	**0.024 ± 0.004**	0.028 ± 0.002	0.026 ± 0.001
		kc1	0.017 ± 0.004	0.020 ± 0.007	**0.016 ± 0.003**	0.015 ± 0.001
Support Vector Machine	C, gamma	blood-transfusion	0.036 ± 0.015	**0.032 ± 0.005**	0.034 ± 0.002	0.008 ± 0.001
		vehicle	0.133 ± 0.025	**0.094 ± 0.008**	0.097 ± 0.009	0.071 ± 0.014
		Australian	0.078 ± 0.012	**0.062 ± 0.005**	0.069 ± 0.010	0.061 ± 0.011
		car	0.070 ± 0.008	0.053 ± 0.003	**0.052 ± 0.002**	0.032 ± 0.010
		phoneme	0.067 ± 0.027	**0.044 ± 0.008**	0.047 ± 0.006	0.019 ± 0.002
		segment	0.178 ± 0.040	**0.128 ± 0.019**	0.133 ± 0.013	0.100 ± 0.011
		credit-g	0.041 ± 0.008	**0.038 ± 0.009**	0.039 ± 0.005	0.020 ± 0.003
		kc1	0.034 ± 0.015	0.029 ± 0.006	**0.024 ± 0.006**	0.007 ± 0.001
Random Forest	max_depth, max_features	blood-transfusion	0.016 ± 0.004	**0.015 ± 0.004**	0.017 ± 0.000	0.008 ± 0.001
		vehicle	0.034 ± 0.046	0.021 ± 0.008	**0.020 ± 0.004**	0.018 ± 0.003
		Australian	0.024 ± 0.009	0.022 ± 0.008	**0.018 ± 0.002**	0.016 ± 0.003
		car	0.035 ± 0.005	**0.030 ± 0.006**	0.031 ± 0.005	0.024 ± 0.002
		phoneme	0.015 ± 0.002	0.016 ± 0.002	**0.015 ± 0.002**	0.008 ± 0.002
		segment	0.040 ± 0.007	**0.035 ± 0.004**	0.039 ± 0.005	0.029 ± 0.006
		credit-g	0.025 ± 0.012	0.022 ± 0.006	**0.021 ± 0.003**	0.012 ± 0.002
		kc1	**0.015 ± 0.006**	0.015 ± 0.005	0.019 ± 0.001	0.005 ± 0.002
XGBoost	colsample_bytree, eta	blood-transfusion	0.018 ± 0.002	**0.017 ± 0.001**	0.017 ± 0.002	0.014 ± 0.001
		vehicle	**0.009 ± 0.001**	0.010 ± 0.001	0.009 ± 0.001	0.009 ± 0.001
		Australian	**0.011 ± 0.000**	0.011 ± 0.000	0.011 ± 0.000	0.010 ± 0.001
		car	0.031 ± 0.015	**0.018 ± 0.004**	0.020 ± 0.003	0.016 ± 0.005
		phoneme	0.013 ± 0.000	**0.012 ± 0.000**	0.013 ± 0.000	0.008 ± 0.001
		segment	**0.003 ± 0.000**	0.003 ± 0.000	0.003 ± 0.000	0.003 ± 0.001
		credit-g	0.011 ± 0.001	**0.011 ± 0.000**	0.011 ± 0.000	0.011 ± 0.001
		kc1	0.008 ± 0.000	0.008 ± 0.000	**0.008 ± 0.000**	0.006 ± 0.001
Neural Network	alpha, batch_size	blood-transfusion	0.016 ± 0.002	**0.013 ± 0.001**	0.014 ± 0.002	0.011 ± 0.001
		vehicle	0.024 ± 0.014	**0.018 ± 0.002**	0.029 ± 0.008	0.030 ± 0.006
		Australian	0.014 ± 0.003	**0.012 ± 0.003**	0.014 ± 0.003	0.014 ± 0.002
		car	0.010 ± 0.002	**0.008 ± 0.001**	0.010 ± 0.002	0.007 ± 0.003
		phoneme	0.026 ± 0.010	**0.012 ± 0.003**	0.014 ± 0.004	0.010 ± 0.003
		segment	0.015 ± 0.008	**0.012 ± 0.006**	0.022 ± 0.023	0.013 ± 0.004
		credit-g	**0.017 ± 0.006**	0.214 ± 0.722	0.019 ± 0.006	0.020 ± 0.007
		kc1	0.015 ± 0.004	0.014 ± 0.004	**0.012 ± 0.002**	0.007 ± 0.001
Average			0.0412	0.0306	**0.0274**	0.0200

Table 1: We show the RMSE between the cost predicted by the SR and the true cost. The SR is fitted either on samples collected by BO (BO), random samples with the true cost (Random) or random samples evaluated with the GP (BO-GP). For each row, the best/second best RMSE among the SR models is boldfaced/underlined. The surrogate model's RMSE (GP Baseline) is shown for comparison. The SR is fitted on 140 samples with $\zeta = 0.0001$. For GP-BO, it is fitted on random 400 samples evaluated with the GP obtained after running BO for 140 samples.

6 Conclusion and Future Work

In this work, we took a step toward a more human-centered HPO process by proposing an easy workflow for practitioners targeted at gaining insights about the underlying HPO problem. To this end, we leverage symbolic regression to learn an interpretable, analytic closed-form expression of the relation between hyperparameter values and their performance. We show that naively learning such a symbolic model on meta-data collected during the HPO process suffers from bias issues and suggest solving this solution by learning on randomly sampled configurations whose performance is approximated by the HPO process' surrogate model. In an experimental evaluation, we show that a trade-off between the interpretability and faithfulness of the symbolic model can be achieved with a systematic approach for setting a parsimony hyperparameter.

There are several interesting directions toward future work. As most modern HPO tools leverage multi-fidelity techniques to improve efficiency, we deem it worthwhile to extend our approaches to such a setting, where it is important to adapt the learning procedure of the symbolic regression to incorporate meta-data from several fidelities in a suitable manner. Furthermore, it is conceivable to incorporate the symbolic regression model as a surrogate model into BO-based HPO tools. Here, the main challenge is to find a suitable way to model the uncertainty of the symbolic model, which is required by many acquisition functions in practice. Last, we want to extend the workflow described in Section 4 by a step computing the partial dependence of hyperparameters such that formulas for subsets of hyperparameters can also be offered (cf. Section 4.3).

References

Akiba, T., S. Sano, T. Yanase, T. Ohta, and M. Koyama (2019). "Optuna: A Next-Generation Hyper-parameter Optimization Framework". In: *Proc. of KDD'19*, pp. 2623–2631.

Alaa, A. and M. van der Schaar (2019). "Demystifying black-box models with symbolic metamodels". In: *Proc. of NeurIPS'19*.

Augusto, D. and H. Barbosa (2000). "Symbolic regression via genetic programming". In: *Proc. of SBRN'00*. IEEE, pp. 173–178.

Awad, N., N. Mallik, and F. Hutter (2021). "DEHB: Evolutionary Hyberband for Scalable, Robust and Efficient Hyperparameter Optimization". In: *Proc. of IJCAI'21*, pp. 2147–2153.

Balandat, M., B. Karrer, D. Jiang, S. Daulton, B. Letham, A. Wilson, and E. Bakshy (2020). "BoTorch: A Framework for Efficient Monte-Carlo Bayesian Optimization". In: *Proc. of NeurIPS'20*.

Bergstra, J., R. Bardenet, Y. Bengio, and B. Kégl (2011). "Algorithms for Hyper-Parameter Optimization". In: *Proc. of NeurIPS'11*, pp. 2546–2554.

Bischl, B., M. Binder, M. Lang, T. Pielok, J. Richter, S. Coors, J. Thomas, T. Ullmann, M. Becker, A.-L. Boulesteix, D. Deng, and M. Lindauer (2023). "Hyperparameter optimization: Foundations, algorithms, best practices, and open challenges". In: *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, e1484.

Blom, K. van der, A. Serban, H. Hoos, and J. Visser (2021). "AutoML adoption in ML software". In: *ICML Workshop on AutoML*.

Breiman, L. (2001). "Random Forests". In: *MLJ* 45, pp. 5–32.

Crabbe, J., Y. Zhang, W. Zame, and M. van der Schaar (2020). "Learning outside the black-box: The pursuit of interpretable models". In: *Proc. of NeurIPS'20*. Vol. 33, pp. 17838–17849.

Deb, K. (2013). "Multi-objective optimization". In: *Search methodologies: Introductory tutorials in optimization and decision support techniques*. Springer, pp. 403–449.

Eggensperger, K., P. Müller, N. Mallik, M. Feurer, R. Sass, A. Klein, N. Awad, M. Lindauer, and F. Hutter (2021). "HPOBench: A Collection of Reproducible Multi-Fidelity Benchmark Problems for HPO". In: *Proc. of NeurIPS'21 Datasets and Benchmarks Track*.

Falkner, S., A. Klein, and F. Hutter (2018). "BOHB: Robust and Efficient Hyperparameter Optimization at Scale". In: *Proc. of ICML'18*, pp. 1437–1446.

Fehring, L., J. Hanselle, and A. Tornede (2022). "HARRIS: Hybrid Ranking and Regression Forests for Algorithm Selection". In: *MetaLearn'22*.

Feurer, M. and F. Hutter (2019). "Hyperparameter Optimization". In: *Automated Machine Learning: Methods, Systems, Challenges*. Ed. by F. Hutter, L. Kotthoff, and J. Vanschoren. Available for free at http://automl.org/book. Springer. Chap. 1, pp. 3–38.

Friedman, J. (2001). "Greedy function approximation: a gradient boosting machine". In: *Annals of statistics*, pp. 1189–1232.

Gevers, K., A. Tornede, M. Wever, V. Schöppner, and E. Hüllermeier (2022). "A comparison of heuristic, statistical, and machine learning methods for heated tool butt welding of two different materials". In: *Welding in the World* 66.10, pp. 2157–2170.

Gijsbers, P., F. Pfisterer, J. N. van Rijn, B. Bischl, and J. Vanschoren (2021). "Meta-learning for symbolic hyperparameter defaults". In: *Proc. of GECCO'21*, pp. 151–152.

Godbole, V., G. E. Dahl, J. Gilmer, C. J. Shallue, and Z. Nado (2023). *Deep Learning Tuning Playbook*. Version 1.

Hanselle, J., A. Tornede, M. Wever, and E. Hüllermeier (2020). "Hybrid Ranking and Regression for Algorithm Selection". In: *Proc. of (KI'20)*, pp. 59–72.

Hutter, F., H. Hoos, and K. Leyton-Brown (2014). "An Efficient Approach for Assessing Hyperparameter Importance". In: *Proc. of ICML'14*, pp. 754–762.

Imrie, F., B. Cebere, E. McKinney, and M. van der Schaar (2022). "AutoPrognosis 2.0: Democratizing Diagnostic and Prognostic Modeling in Healthcare with Automated Machine Learning". In: *arXiv:2210.12090 [cs.LG]*.

Jin, H. (2022). "Hyperparameter Importance for Machine Learning Algorithms". In: *arXiv:2201.05132 [stat.ML]*.

Kotthoff, L., S. Dey, J. Heil, V. Jain, T. Muller, A. Tyrrell, H. Wahab, and P. Johnson (2022). "Optimizing Laser-Induced Graphene Production". In: *PAIS@ECAI*. Vol. 351, pp. 31–44.

Koza, J. (1994). *Genetic programming II.* Vol. 17. MIT press Cambridge.

Li, L., K. Jamieson, G. DeSalvo, A. Rostamizadeh, and A. Talwalkar (2018). "Hyperband: A Novel Bandit-Based Approach to Hyperparameter Optimization". In: *JMLR* 18.185, pp. 1–52.

Lindauer, M., K. Eggensperger, M. Feurer, A. Biedenkapp, D. Deng, C. Benjamins, T. Ruhkopf, R. Sass, and F. Hutter (2022). "SMAC3: A Versatile Bayesian Optimization Package for Hyperparameter Optimization". In: *JMLR* 23.54, pp. 1–9.

Mockus, J. (1989). *Bayesian approach to global optimization. Theory and Applications.* Kluwer Academic Publishers.

Moosbauer, J., G. Casalicchio, M. Lindauer, and B. Bischl (2022). "Enhancing Explainability of Hyperparameter Optimization via Bayesian Algorithm Execution". In: *arXiv:2206.05447 [cs.LG]*.

Moosbauer, J., J. Herbinger, G. Casalicchio, M. Lindauer, and B. Bischl (2020). "Towards explaining hyperparameter optimization via partial dependence plots". In: *ICML Workshop on AutoML*.

Moosbauer, J., J. Herbinger, G. Casalicchio, M. Lindauer, and B. Bischl (2021). "Explaining Hyperparameter Optimization via Partial Dependence Plots". In: *Proc. of NeurIPS'21*.

Petersen, B., M. Landajuela, T. Mundhenk, C. Santiago, S. Kim, and J. Taery Kim (2021). "Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients". In: *Proc. of ICLR'21*.

Probst, P., A. Boulesteix, and B. Bischl (2019). "Tunability: Importance of Hyperparameters of Machine Learning Algorithms". In: *JMLR* 20.53, pp. 1–32.

Proc. of NeurIPS'20 (2020).

Pushak, Y. and H. Hoos (2022). "AutoML Loss Landscapes". In: *ACM TEL* 2.3, pp. 1–30.

Rasmussen, C. and C. Williams (2006). *Gaussian Processes for Machine Learning.* The MIT Press.

Sass, R., E. Bergman, A. Biedenkapp, F. Hutter, and M. Lindauer (2022). "DeepCAVE: An Interactive Analysis Tool for Automated Machine Learning". In: *ReALML@ICML'22*.

Schneider, L., L. Schäpermeier, R. Prager, B. Bischl, H. Trautmann, and P. Kerschke (2022). "HPO× ELA: Investigating Hyperparameter Optimization Landscapes by Means of Exploratory Landscape Analysis". In: *Proc. of (PPSN'22)*. Springer, pp. 575–589.

Snoek, J., H. Larochelle, and R. Adams (2012). "Practical Bayesian Optimization of Machine Learning Algorithms". In: *Proc. of NeurIPS'12*, pp. 2960–2968.

Thorndike, R. (1953). "Who belongs in the family?" In: *Psychometrika* 18.4, pp. 267–276.

Tornede, T., A. Tornede, J. Hanselle, M. Wever, F. Mohr, and E. Hüllermeier (2021). "Towards Green Automated Machine Learning: Status Quo and Future Directions". In: *arXiv:2111.05850 [cs.LG]*.

Turner, R., D. Eriksson, M. McCourt, J. Kiili, E. Laaksonen, Z. Xu, and I. Guyon (2021). "Bayesian Optimization is Superior to Random Search for Machine Learning Hyperparameter Tuning: Analysis of the Black-Box Optimization Challenge 2020". In: *Proc. of NeurIPS'20 Competition and Demonstration*, pp. 3–26.

Zöller, M., W. Titov, T. Schlegel, and M. F. Huber (2022). "XAutoML: A Visual Analytics Tool for Establishing Trust in Automated Machine Learning". In: *arXiv:2202.11954 [cs.LG]*.

7 Broader Impact Statement

HPO and thus also the approach presented in this paper can be used in virtually any ML applications and, in principle, even for most general configuration problems, e.g., in mechanical engineering (Gevers et al., 2022; Kotthoff et al., 2022). Correspondingly, it can have a positive or negative impact

on society based on the application it is used for. If it is used with malicious intent or within a socially critical application such as face recognition, it can lead to giving practitioners more insights, which might allow for increasing the performance and, thus, the potential harmfulness of the corresponding tool. However, at the same time, when used within applications with a positive impact on society, such as most medical applications (Imrie et al., 2022), similar improvements are conceivable and conversely, a positive impact on society.

A Applying the Elbow Heuristic

We propose the use of the elbow heuristic as a systematic approach to balancing the interpretability and faithfulness of the symbolic model via a parsimony parameter. Examples support the applica-

bility of the method; however, we refrain from including an application of the heuristic since it is highly dependent on a practitioner's needs. The method suggests starting with a low complexity (and in turn, usually relatively lower performance), and decreasing the parsimony parameter until the benefits of increased performance no longer outweigh the increased complexity of the resulting formula. Two conceivable ways a practitioner could put this into practice are by setting thresholds for gain of performance/ loss of interpretability (e.g., a .005% gain of performance is not worth any loss in interpretability) or by defining a relative trade-off point between accuracy and complexity changes where on would stop (e.g. stopping once the increase in complexity is larger than the relative gain of performance).

B On the Operation Count for Symbolic Expressions

As a measure for the complexity of a symbolic expression, we use the operation count in the formula as computed by the *SymPy* library. Operations are all functions with an arity > 0, i.e. all nodes in an expression tree except leaf nodes. For example, the expression $s(\text{alpha}, \text{batch size}) = 0.078 \cdot \exp(\text{alpha}/(4 \cdot \text{batch size}))$ depicted in Figure 1 has 4 operations. An expression with 0 operations is a constant or a variable.

C Limitations

In its current state, our approach has several limitations, which we discuss here together with possible remedies:

Numerical Hyperparameters. As of now, our approach can only be used if the HPO configuration space consists solely of numerical and no categorical or other types of hyperparameters. This limitation arises from the fact that hyperparameters are treated as variables in the symbolic regression, whose values must be able to be plugged in correspondingly. As usual in such cases, any other type of hyperparameter can be supported by providing a suitable mapping of the space to a numerical space, such as a one-hot-encoding for categorical hyperparameters. However, it is unclear how well this works in practice in this case.

Optimizable Hyperparameters. As of now, the set of hyperparameters, which should be included in the explanation and the one being optimized by the HPO tool has to be the same. If this is not the case, maybe because a user wants to optimize 10 hyperparameters, but only wants to have an explanation of the relation of two of those, designing the training dataset for the symbolic regression (Equation 1) is not straightforward as the corresponding evaluations $c(\lambda)$ of datapoints from $\mathcal{D}_{train}$ is also influenced by those hyperparameters, which should not be included, and correspondingly very noisy. One way to alleviate this situation, is to leverage the partial dependence function, as done by Moosbauer, Herbinger, et al. (2021), which essentially aims to express the expected performance of a configuration independent of a subset of the hyperparameters by integrating them out. After computing the partial dependence for the corresponding set of hyperparamters for which a practitioner wants an explanation, our approach can be applied straightforward.

Multi-Objective Optimization. As noted in Section 4.1.2, we ensure interpretability by penalizing very complex formulas through a penalty term in their fitness value. This is an instantiation of scalarization (Deb, 2013) for solving multi-objective optimization problems (Deb, 2013). Since we actually want to optimize for both accuracy/faithfulness of the explainer, i.e. the symbolic regression model, and the complexity of the corresponding formula, a more sophisticated approach would be to employ Pareto-based multi-objective approaches. This would also improve the usability for the practitioner as they would not need to specify the penalty in advance, but could pick a formula from the Pareto front at the end of the optimization, which offers a compromise between accuracy and interpretability to their taste.

D Detailed Experimental Setup

For all experiments, we used 5 seeds to obtain the training data points, i.e., configurations for the symbolic regression and the corresponding performances. Furthermore, we repeated learning the symbolic expression three times with different seeds. All results are averaged, and error bars as well as standard deviations computed across the $5 \times 3 = 15$ repetitions. Experiments are run on cluster nodes equipped with two AMD Milan 7763 with 2×64 cores@2.45 GHz and were limited to 64 CPUs and 64GB of RAM. In the interest of GreenAutoML (Tornede et al., 2021), we aim to be transparent regarding the computational resources required for our experiments, which consumed about 700.000 CPU hours in total. As the cluster is exclusively powered by renewable energy, the experiments did not cause any CO_2 equivalents when considering only the energy required to run them.

Bayesian Optimization. We use the HPO tool SMAC (Lindauer et al., 2022) for running BO in our experiments. We use the BlackBoxFacade with the default settings, except for the config selector, where we set retrain_after=1 to update the surrogate model each time when returning a new hyperparameter configuration.

Symbolic Regression. To learn the symbolic regression models we use *gplearn*[2], a library to perform genetic programming based symbolic regression. We fit the Symbolic Regressor with a population size of 5000, evolving over 20 generations and optimizing the RMSE. The parsimony coefficient is set to 0.0001 in our experiments except for the parsimony variation study. We allow the functions addition, substraction, multiplication, division, square root, logarithm, exponential, sinus, cosinus, and absolute value when building and evolving the formulas. For all other hyperparameters, we use the default values. The formulas are simplified with the *SymPy*[3] tool.

E Detailed Results

Extending the results presented in Section 5.1, Figure 6, 7, and 8 display the error of the symbolic regression and the GP baseline for varying sample sizes for different models, hyperparameters, and datasets.

---

[2]https://gplearn.readthedocs.io/en/stable/intro.html
[3]https://www.sympy.org/en/index.html

Figure 6: RMSE between the cost predicted by the SR and the true cost for different numbers of samples. The symbolic regression is fitted on either samples collected by BO (BO), random samples with their true cost (Random) or random samples evaluated with the GP (BO-GP). The RMSE of the GP (GP Baseline) is shown for comparison. The symbolic regression is fitted on the number of samples shown, with parsimony coefficient 0.0001. For GP-BO, it is fitted on random 400 samples evaluated with the GP obtained after collecting the shown number of samples with BO.

Figure 7: RMSE between the cost predicted by the SR and the true cost for different numbers of samples. The symbolic regression is fitted on either samples collected by BO (BO), random samples with their true cost (Random) or random samples evaluated with the GP (BO-GP). The RMSE of the GP (GP Baseline) is shown for comparison. The symbolic regression is fitted on the number of samples shown, with parsimony coefficient 0.0001. For GP-BO, it is fitted on random 400 samples evaluated with the GP obtained after collecting the shown number of samples with BO.

Figure 8: RMSE between the cost predicted by the SR and the true cost for different numbers of samples. The symbolic regression is fitted on either samples collected by BO (BO), random samples with their true cost (Random) or random samples evaluated with the GP (BO-GP). The RMSE of the GP (GP Baseline) is shown for comparison. The symbolic regression is fitted on the number of samples shown, with parsimony coefficient 0.0001. For GP-BO, it is fitted on random 400 samples evaluated with the GP obtained after collecting the shown number of samples with BO.