Reinforcement learning for optimization of variational quantum circuit architectures

Abstract

The study of Variational Quantum Eigensolvers (VQEs) has been in the spotlight in recent times as they may lead to real-world applications of near-term quantum devices. The performance of a chosen variational ansatz depends on the structure and in general, improves in the depth of its corresponding circuit. At the same time, near-term restrictions limit the depth of the circuit we can expect to run. Thus, the optimization of the VQE ansatz requires maximizing the expressivity of the circuit while maintaining low depth. In recent years, various methods for VQE structure optimization have been introduced but the capacities of machine learning to aid with this problem have not yet been extensively investigated. In this work, we propose a reinforcement learning algorithm that autonomously explores the space of possible ansatzes, identifying economic circuits which still yield accurate ground energy estimates. The algorithm uses a feedback-driven curriculum learning method that autonomously adapts the complexity of the learning problem to the current performance of the learning algorithm and it incrementally improves the accuracy of the result while minimizing the circuit depth. We showcase the performance of our algorithm on the problem of estimating the ground-state energy of lithium hydride (LiH) in various configurations. In this well-known benchmark problem, we achieve chemical accuracy and we also beat standard ansatzes and state-of-the-art results in terms of circuit depth.

1 Introduction

As we are entering the so called Noisy Intermediate Scale Quantum (NISQ) [1] technology era, the search for more suitable algorithms under NISQ restrictions is becoming ever more important. A truly compatible NISQ application must first be amenable to architecture constraints and size limits. Furthermore, to minimize the adverse effects of gate errors and decoherence, it is important that the circuits are as gate-frugal, and as shallow as possible.

Perhaps the most promising classes of such algorithms are based on variational circuit methods, with which we have high expectations when applied to problems in quantum chemistry. A key problem in this field is the computing of ground state energies and low energy properties of chemical systems (the chemical structure problem). This problem is believed to be intractable in general, yet the quantum Variational Quantum Eigensolver (VQE) [2] algorithm can provide solutions in regimes which lie beyond the reach of classical algorithms, while maintaining NISQ-friendly properties [3, 4].

VQE is a hybrid quantum-classical algorithm, where a parametrized quantum state is prepared on a quantum computer, the parameters of which are selected using classical optimization methods.

The objective is to prepare the state $|\psi(\vec{\theta})\rangle$ which can be used to approximate the ground state of a given Hamiltonian H by the variational principle

$$E_{\min} \leq \min_{\vec{\theta}}(\langle\psi(\vec{\theta})|H|\psi(\vec{\theta})\rangle) , \qquad (1)$$

where $E_{\min}$ is the true ground state energy of H. The parametrized state is prepared by applying $U(\vec{\theta})$, which is a parametrized quantum circuit (typically with a fixed architecture), where the angles $\vec{\theta} = (\theta_1...\theta_n)$ specify the rotation angles of the local unitary rotations present in the circuit. This circuit, known as the *ansatz* is applied to an initial state $|\psi_0\rangle$, usually chosen to be the fiducial "all zero" state $|00...0\rangle$, to prepare the state $|\psi(\vec{\theta})\rangle = U(\vec{\theta})|\psi_0\rangle$.

It is well established that the structure of the ansatz can dramatically influence the VQE's performance [4, 5], as the closeness of the estimated ground state to the true one depends on the state manifold accessible by the ansatz. Thus finding new architecture construction methods could lead to breakthroughs in quantum variational methods for chemistry (e.g. for strongly-correlated systems, for which standard ansatzes might fail), but also in other domains which utilize variational circuits such as machine learning and optimization [6, 7, 8, 9].

Currently, the foremost ansatzes fall primarily in two classes: chemistry-inspired (e.g. the unitary coupled-cluster ansatz [2, 10]) and hardware-inspired (e.g. the hardware efficient ansatz [11]). Architectures from both of these classes entail using a fixed architecture [2, 10, 11, 12] determining the unitary $U(\vec{\theta})$, and hence the corresponding ansatz. The ansatz circuit is then usually decomposed into two-qubit CNOT and one-qubit rotation gates parametrized by $(\theta_1, \theta_2, \ldots, \theta_n) \in [0, 2\pi]^n$ to be optimized by a classical subroutine. However, the architecture itself can also be optimized. This results in a hard structure optimization problem, as it is a combinatorial optimization problem which must balance two competing factors. On the one hand the ansatz needs to be expressive enough to guarantee a good approximation of the ground state energy. On the other hand, the depth and size of the circuit needs to be controlled in order for the latter to be compatible with NISQ restrictions.

Contributions In this work, we propose a general optimization procedure for VQE based on deep reinforcement learning (RL) which is designed to yield quantum circuits that are both gate and depth efficient. We supplement this RL approach with curriculum learning [13, 14], a powerful machine learning method for solving complex problems by leveraging the solutions of previously-solved simpler instances. Specifically, we introduce a feedback-driven curriculum learning method that autonomously adapts the complexity of the learning problem to the current performance of the learning algorithm. We apply our architecture to the well-established benchmarking problem of finding the ground state energy of the LiH molecule [15, 3] and observe chemical accuracy while maintaining a low-depth quantum circuit and achieving state-of-the-art results in terms of gate efficiency. Moreover, the proposed method is much broader than just for the ground state finding, it can be applied to any variational-circuit-based algorithm.

The rest of the paper is organized as follows. In Section 2 we discuss the related works. In Section 3 we introduce our method with simplistic assumptions about the exact value of the ground state energy. At the end of this section we provide a method circumventing this unrealistic requirement. To ease the experiments, in Section 4 we present the results assuming the access to the exact value of energy. In Section 5 we provide the results for the full method that utilizes a rough proxy of energy obtained with classical methods. We conclude the paper with the discussion of possible future directions.

2 Related Work

The automatic construction of quantum circuits with the use of heuristics/machine learning methods is a topic that has recently been gaining more attention [16, 17, 18, 19, 20]. In particular, the construction of quantum circuits in the context of quantum chemistry has been discussed in articles such as: in [21] authors use evolutionary algorithms to optimize the structure of VQE circuits for quantum chemistry and combinatorial optimization. The gate set in this algorithm is composed of one-qubit universal gates and two-qubit controlled universal gates, which after optimization procedure, are decomposed into CNOT gates and one-qubit universal rotation gates. Another evolutionary strategy was explored in [22], where a multi-objective genetic algorithm is used to optimize the

structure of the VQE ansatz in the context of quantum chemistry problems. The topology of the circuits is optimized by a non-dominated sorting genetic algorithm while the parameters are globally tuned by Covariance Matrix Adaptation Evolution Strategy (CMA-ES) [23]. On the other hand non-evolutionary approach was proposed in the manuscript [24], the authors apply a set of rules to both grow and remove quantum gates during the optimization. The above three manuscripts focus on solving the problem of quantum chemistry by constructing the shortest possible quantum circuits.

3 Methods

In this section, we discuss our approach for constructing VQE ansatzes using RL. We discuss the state and action representations, as well as the reward function used in this work. We then introduce a novel adaptation of curriculum learning applied to VQE circuit construction with different parameter optimization strategies.

3.1 Ansatz optimization as a reinforcement learning problem

We describe ansatz optimization as a reinforcement learning environment, where the states encode the current circuit. The actions encode a gate that is added to the current circuit. The environmental transitions are deterministic because the subsequent state is defined by the previous state appended by the taken action. At each time step t the agent receives the reward R according to the following formula:

$$
R = \begin{cases} 5 & \text{if } E_t < \xi \\ -5 & \text{if } t \geq L \text{ and } E_t \geq \xi \\ \max\left(\frac{E_{t-1}-E_t}{E_{t-1}-E_{\min}}, -1\right) & \text{otherwise} \end{cases} ,
\tag{2}
$$

The goal of the agent is to reach the minimal energy $E_{\min}$ within a predefined threshold ξ. The energy E_t is calculated for the current circuit representing the quantum state $|\psi(\vec{\theta})\rangle$ according to:

$$
E_t = \langle \psi(\vec{\theta})|H|\psi(\vec{\theta})\rangle,
\tag{3}
$$

where $\vec{\theta}$ describes the angles of the rotation gates. In order to obtain the reward R, the vector $\vec{\theta}$ needs to be separately optimized. This optimization subroutine is a crucial hyperparameter of this RL environment and it is discussed in more detail in the following two sections. The details on the reward shaping are discussed in Supplementary Materials.

We utilize deep RL methods, thus the states and actions are represented in a neural network-friendly form. Namely, each state is represented as an ordered list of layers that are composed of single quantum gates. Thus the environmental state which is represented by this list, fully represents the whole circuit (with a clearly specified gate ordering). For constructing the circuits, we use CNOT and one qubit rotation gates – which are realizable on currently available quantum devices. CNOT gates are encoded by two values indicating position of *control* and *target* qubits (position is enumerated from 0). Rotation gates are encoded with respective positional number (starting from 0) indicating the qubit on which to apply the rotation, and the axis of rotation ($X - 1$, $Y - 2$, $Z - 3$). We deliberately omit continuous parameter describing the angle of the rotation from the state representation. At the end of each state's representation we append the energy estimated for the state. The user needs to define the maximum number of circuit layers (L). If a given circuit has fewer layers than L, the remaining ones are filled with identity operators (c.f. Fig. 1). The agent constructs the circuit iteratively, starting from an empty list, and adding a single quantum gate at the end of the current circuit. This way the agent starts each episode with exactly the same conditions, *i.e.* an empty state, avoiding an additional source of randomness tied to the initial state. Thus, the set of all possible actions is equivalent to the set of all possible quantum gates that the agent can select. The size of the set of all possible actions for the agent is then $3|Q| + 2\binom{|Q|}{2} = |Q|(|Q| + 2)$, where $|Q|$ is the number of qubits, $3|Q|$ is the number of single qubit gates and $2\binom{|Q|}{2}$ is the number of two qubit gates the agent can choose from. We use a simple one-hot encoding for the actions.

3.2 Specification of the agent and the environment

We employ a Double Deep-Q network [25] (DDQN) with an ϵ-greedy policy and an ADAM optimizer for better stability. More technical details about the Reinforcement Learning procedure are

Figure 1: Example of state representation. In this example maximum length of the circuit (L) is set to 5, and the number of qubits to 4. Since we count qubits from 0, the lack of particular gate at each layer is represented with the maximum number of qubits, which in this case is 4, therefore the last two columns represent layers with identity operators.

described in the Experiments section. As described in the previous section, to obtain a reward R for each circuit, an optimization subroutine needs to be applied to determine the continuous values of the rotation gate angles. We use the well developed methods for continuous optimization such as Constrained Optimization By Linear Approximation (COBYLA) [26] and Rotosolve [27]. Whilst we could use an agent for this purpose as well, we abstain from doing so for two main reasons. Firstly, in this work we aim at assessing the efficacy of RL for circuit structure optimization, rather than for parameter searching. The latter is investigated extensively in other literature and thus treated as a separate subroutine that can be solved by other, more developed, tools. The second reason is practical, as training the agent to reliably predict values of angles would result in significantly longer training periods.

For the above reasons, our approach is hybrid: the agent learns how to, and is rewarded for, constructing particular circuits given set of parameters determined by an independent optimization algorithm. We apply the angle optimization subroutine only after the steps in which the agent appends a rotation gate to the circuit, thus eliminating the necessity of including the parameters in the state representation. The number of angles optimized at a given step is a hyperparameter in our method, the choice of which will be analyzed in Sec. 4.2. In this work, we consider optimizing all angles at once (*global strategy*), as well as optimizing a few angles at a time (*local strategy*) . These different experimental settings allow us to check whether the rough energy approximation obtained from only optimizing a subset of the circuit angles is sufficient to create sufficiently good circuits.

3.3 Intrinsically motivated curriculum learning

As explained, the agent is rewarded for creating circuits that pass a given threshold. In our experiments, we set the threshold to so called chemical accuracy, which corresponds to an energy that differs from the ground state energy by less than 0.0016 Hartree. Even in cases where the exact value of minimum energy is known, setting the value of threshold ξ directly to chemical precision from the beginning of the training may result in the agent failing due to poor exploration. One of the possible solutions is to introduce the agent to tasks of increasing difficulty known as curriculum learning [13] which was found to be beneficial for neural network training [14]. However, this approach requires the user to design a task sequence which, without *a priori* knowledge of the relationship between the threshold value and the corresponding task difficulty, may lead to the agent reaching undesired local minima.[1]

Inspired by the body of works exploring intrinsic motivation in RL [28], we propose the intrinsically motivated curriculum learning in which the difficulty of the current task is dynamically adjusted based on the current performance of the agent. Hence, the agent does not rely on a human-defined task schedule and builds its knowledge gradually at the pace that is reflective of the agent's performance. The proposed method, illustrated in Fig. 2, starts with an arbitrary threshold ξ_1 that is decreased according to two rules. First rule decreases the threshold greedily to the best energy obtained so far ξ_2 after each G episodes. Additionally, the amortization factor δ is added to the threshold at the moment of greedy shift and each time the agent fails to solve multiple consecutive episodes. To gradually decrease the amount of added amortisation δ, after a few successful episodes we decrease the amortisation δ by a certain factor until the agent reach energy that was greedily obtained at first.

---

[1] We tested multiple hard-coded schedules for shifting the threshold. However, the algorithm did not pass the desired lowest threshold while using these pre-defined sequences of thresholds.

Figure 2: Illustration of the moving threshold (orange) procedure, showing the effects of two amortization events (blue), the value of which is represented by δ. The first event follows a non-zero change in threshold from ξ_1 to ξ_2, *i.e.* the agent manages to find a better energy estimate during training. The second amortization event illustrates what happens when the agent fails to improve on the current threshold ξ_2 (or the improvement is smaller than the amortization value): the threshold increases suddenly due to the resetting of the amortization value. Note that the final threshold after the second amortization drops to zero can also be lower than ξ_2.

Note that due to the relative nature of our reward system we can substitute the true value of E_{min}, which is in practical cases unknown, with an arbitrary value α that is lower than minimum energy E_{min} and set a threshold ξ to a value that guarantees that the exact energy falls into the range $E_{min} \in (\alpha + \xi, \alpha)$. Note that, in principle, the method does not pose any restrictions on the starting threshold and the agent can start learning from any point, so we can set the ξ arbitrarily big to make sure that the E_{min} is in the range. Analogously, the α value can be set, however a simple methods to roughly estimate the lower bound of energy can be utilized to that end. If the agent is able to create circuits with chemical precision relative to any (reasonably) higher energy, the training with every-increasing difficulty will ultimately lead to that point without computing the exact energy. Experiments proving validity of this argument are presented in Section 4.2.

4 Experiments

We start this section with description of chemical problems on which we evaluate the proposed approach. Next we will describe experiment setup and present our results.

4.1 Experimental setup

In our analysis of RL for VQE circuit synthesis we focus on the problem of finding the ground state energy of the lithium hydride (LiH) molecule for various intramolecular distances, as well as Hamiltonians on differing qubit numbers, which stem from different approximations of the true chemical problem. All experiments are divided into two parts. In the first part we explain the how the choice of optimizer and number of optimized parameters per step impact the performance of the RL approach. This part is evaluated on less challenging problem instances, i.e. with the smaller quantum system, action space and state space sizes. The second part, on the other hand, will be performed on the same molecule, but simulated on a higher dimensional system. We assume that the number of measurements is sufficiently large that sampling noise is negligible. Whilst this is a significant assumption to make, and current limitation of our method, in this work we are interested in a proof of concept for RL-based circuit synthesis. Thus we do not include the additional overhead incurred by finite measurements, which is left for future work.

Quantum chemistry problems.   As mentioned earlier, in this work we focus on finding the ground state energy of the LiH molecule, although our approach design is not specific to this molecule. The Hamiltonians are computed in STO-3G basis. In the first part of our analysis we consider a simpler approximation of LiH molecule which, after taking into account the symmetry of the molecule and removing the orbitals with weak interaction, results in a Hamiltonian defined on 4 qubits. Thus, state space and action space are significantly smaller than the ones for the full LiH Hamiltonian. In this model we utilize the parity mapping to convert molecular Hamiltonian to qubit Hamiltonian [29]. We examine proposed method on three values of LiH bond distances, 1.2Å, 2.2Å and 3.4Å. In the second experiment we use the larger Hamiltonian which only takes into account the symmetry of the molecule, and is therefore defined on 6 qubits, for which we use the Jordan-Wigner mapping [30].

We opted to switch from the parity to the Jordan-Wigner mapping when considering the 6 qubit Hamiltonian in order to compare our results with previous literature which tackled this problem using a different approach [21]. We only focus one a single geometry for this case, i.e. for bond distance 2.2Å. All Hamiltonians were generated using the Qiskit library [31] (Apache License 2.0).

Implementation details.   In all experiments we utilize n-step DDQN algorithm, with the discount factor set to $\gamma = 0.88$, and the probability of a random action being selected is set by an $\varepsilon-$greedy policy, with ε decayed in each step by a factor of 0.99995 from its initial value 1, down to a minimal value $\varepsilon = 0.05$. Memory replay buffer size was set to 20,000. The target network in the DDQN training procedure is updated after each 500 actions. After each training episode, we included a testing phase where probability of random actions is set to $\epsilon = 0$ and experience replay procedure is turn off, i.e. the experiences obtained during testing phase are not included in the memory replay buffer.

In our experiments we use differing step sizes in the n-step trajectory rollout updates [32], which specify how exactly the Q-function approximations are updated. This hyperparameter of the model was set to $n = 1$ for first part of experiments. The reported results correspond to the experiment performed with the value $n = 6$. In the moving threshold approach, the threshold is changed greedily after 2000 episodes with amortization radius 0.0001. After 50 successfully solved episodes, amortization is decreased by 0.00001. The initial threshold value is set to $\xi = 0.005$. Simulations of quantum circuits were performed using Qulacs library [33] (MIT License). The hyperparameters were selected through coarse grain search. All experiments were performed on three computing clusters - 4 Titan RTX GPUs, 4 Titan V GPUs and 4 Tesla V100 GPUs.

Evaluation.   To validate capabilities of reinforcement learning approach we compare it with well established architectures, namely the Hardware Efficient (HE) [11] ansatz and UCCSD [34, 35] ansatz. The number of layers of the HE ansatz is tailored to each Hamiltonian considered. We report the smallest number of layers for which we have achieved chemical accuracy using our chosen optimizers. Moreover, the naive approach of UCCSD is used, and it is likely possible to find a shallower implementation of this ansatz, but for the purposes of this manuscript, it is an acceptable benchmark.

In all experiments we compare the minimal depth and number of gates of the obtained circuits. By depth we mean the length of the longest path between input and the output along qubit wires, without taking into account quantum gates commutation. Each RL experiment runs on 10 trials, i.e. experiments run on 10 different random seeds. For the first part of experiments we consider two optimization methods: Rotosolve and COBYLA. Both of these optimization methods can be applied with a *local strategy*, where the optimizer updates the last five rotation gates after each agent step, or a *global strategy*, where after each time step a full update is performed. For the local optimization strategy, we set the number of available iterations of Rotosolve to 5, whilst for the global strategy, the number of iterations for is chosen to be 25. By iterations (for Rotosolve) we mean one complete cycle updating all the parameters under consideration. COBYLA in both strategies will have 100 iterations. Due to the fact that the number of iterations is fixed, convergence is not always guaranteed. However, in most cases, these values were sufficient and more iterations did not improve the energy estimate.

In the LiH 4-qubit experiments, we were able to establish the strategy and the optimiser to use in the LiH experiments with 6-qubits. For the setup with 6-qubit, we chose global optimization in each step and COBYLA with 200 iterations.

4.2 Results

LiH - 4-qubit - different bond distances.   In this section, we discuss the results of the LiH experiments with 4 qubits. In Fig. 3, the depth (left) and the total number of gates (right) of the circuits which achieve chemical accuracy are presented, with the average taken over the minimal values from the different trials. For bond distances 1.2Å and 2.2Å, the agent proposed quantum circuits which were shallower and contained fewer gates than the standard approaches, in every trial. For bond distance 3.4Å, the agent using local COBYLA optimization found quantum circuits satisfying chemical accuracy in 2 out of 10 trials, whereas the agent using local Rotosolve did so in 3 out of 10 trials. On the other hand, while using global optimization, the agent found circuits satisfying chemi-

Figure 3: Comparison of minimum depth (left) and gate count (right) of the quantum circuits on which chemical accuracy has been achieved for different strategies. The above results are for the 4 qubit LiH Hamiltonian for several intramolecular separations, shown in the legend. The experiments testing the RL approach were run 10 times on different seeds for the networks' parameters and the ε-greedy random actions. Each bar labelled by "avg" in the legend represents the average over the results from the different trials, whereas each one labelled by "min" is smallest values obtained over the trials. For the local optimization strategy with bond distance 3.4Å, the agent found circuits achieving chemical accuracy in two out of ten trials using COBYLA and three out of ten using Rotosolve.

cal accuracy in every trial, regardless of the optimizer used. In almost all cases, the average minimal depth and gate count are less than those obtained using standard approaches, i.e. HE and UCCSD, the exception being the agent using local Rotosolve, which resulted in circuits deeper than the HE ansatz. Given the above results, COBYLA seems to outperform Rotosolve for this task. Moreover, taking into account number of successful trials, we conclude that our approach gains a lot when all angles are optimized.

LiH - 6-qubits - moving threshold. In this section, we discuss the results of the LiH experiments with 6 qubits. We evaluated the fixed threshold approach on the 6 qubit LiH Hamiltonian case, which, however, did not give any positive results. Agents using global optimization after each step were unable to construct circuits achieving chemical accuracy, which seems to stem from the reward function with chemical accuracy threshold being too sparse. Whilst gradually decreasing the threshold is the obvious next step, we opted for the curriculum learning approach based on intrinsically-driven moving thresholds, in order to decrease the threshold automatically rather than manually. As one can see in Table 1, curriculum agents provide better results than standard approaches. To the best of our knowledge, the only previous work done tackling this problem for the 6 qubit LiH Hamiltonian is [21]. Whilst we cannot quantitatively compare our results with their work due to differing gate compilations, we note out that our approach seems to generate circuits roughly 5 times shallower than the ones obtained in [21].

By looking closely at how the moving threshold guides the agent in the direction of chemical accuracy, we can analyze the mean difference between the exact energy and the energy estimate using the agent's circuit from the end of each episode. In Fig. 4 we plot this error for a particular case at different scales to understand better what happens at different training stages. The blue dots representing the error in the agent energy estimates, whilst the orange curve represents the moving threshold. The left of Fig. 4 shows this error for the entire training period, but does not provide much information due to the large deviation in the error. On the other hand, in the right plot of Fig. 4, we focus more on episodes which resulted in errors closer to chemical accuracy. The agent is guided by a decreasing moving threshold, with the threshold occasionally increasing abruptly due to amortization, which helps the agent adapt to a new lower threshold.

Table 1: Comparing the minimum depth and the number of gates obtained using the threshold RL approach with those obtained using the standard HE and UCCSD anstäze for circuits which achieve chemical accuracy. The experiments were performed on the 6 qubit LiH molecule with bond distance 2.2Å. For the RL data, "avg" denotes the average over minimum depths over different trials, whereas "min" denotes the minimum value achieved over all trials. For the standard anstäze, the minimum depth and number of gates are obviously fixed by the architectures themselves. The RL approach successfully generated circuits achieving chemical accuracy in 7 out of 10 trials.

	avg depth	min depth	avg # gates	min # gates
RL global COBYLA	**16**	**11**	**35**	**27**
HE	17	17	63	63
UCCSD	377	377	610	610

Figure 4: An example of final errors during training, i.e. the difference between minimal energy and energy obtained from the circuits at the end of each episode, with the blue dots representing the error after every episode and the energy threshold, the orange curve showing the energy threshold used to guide the agent, and the red line marking the chemical accuracy. The different plots focus on different error ranges to illustrate the effects of decreasing the threshold, as well as the sudden increases in the latter due to the introduction of amortization values.

5 Learning procedure with lower-bound approximation to the ground-state energy

So far we have relied on the assumption that the agent uses the energy error with respect to exact solution as a learning metric. This assumption in practice is of course not reasonable, as estimating the energy to this precision is a main objective of VQE algorithms to start with. One way to relax the assumption of knowing the exact energy to just reasonable information about the lower and upper bounds, and classical and cheaper methods, respectively, and which incurs only a logarithmic overhead in the precision by using a binary search for the best achievable energy. Another solution stems from our moving threshold approach.

The moving threshold approach discussed in the previous sections not only allows us to solve more demanding problems, like the 6 qubit Hamiltonian, but also removes the requirement of knowing the exact energy. In order to demonstrate this method, we performed an additional experiment on the 4 qubit LiH Hamiltonian at bond distance 2.2Å. Instead of using the exact energy, i.e. ≈ -7.8448Ha, we used the negative sum of the absolute values of the Hamiltonian's Pauli coefficients, i.e. for a Hamiltonian $H = \sum_{j=1}^{M} c_j P_j$, we take $-\sum_{j=1}^{M} |c_j|$ to guide the agent. This is an example of a very rough easy-to-compute lower bound on the energy, but requires the Hamiltonian to be local. For this LiH geometry, this weight sum evaluated to -10.0604Ha. We set the amortization radius to 0.005, the number of episodes after greedily shifting the threshold to 500 and the amortization radius is decreased after every 25 successfully solved episodes. The initial threshold value we set to $\xi = 4$. We used global COBYLA with 100 iterations to optimize the angles of the quantum circuit.

As one can see in Fig. 5 , the agent successfully manages to reach the exact energy within chemical accuracy, despite having a lower bound below the exact value. Moreover, it can be seen that the initial threshold is well above the error that the agent reaches, which also removes the requirement

Figure 5: An example of final energies applied to the moving threshold approach without exact energy knowledge. The blue dots represent the energy estimate from the agent's final circuit at the end of each episode, and the orange curve shows the energy threshold used to guide the agent. The agent manages to reach the exact energy (yellow line) within chemical accuracy (red line) despite the provided estimate (purple line) being well below the exact value.

of human input to set the threshold schedule. Similar experiments were performed on bond distances 1.2Å and 3.4Å with the same results.

6 Discussion

The molecular electronic structure problem is a promising near-term application for quantum computers. The performance of a chosen variational ansatz depends on the structure and depth of its corresponding circuit. Near-term quantum devices pose restrictions on the depth of the VQE circuit. Thus, VQE structure optimization for near-term quantum computers is a multi-objective optimization problem that requires maximizing the expressivity and reducing the depth of the corresponding circuits. Reinforcement learning by design aims at obtaining the shortest optimal solution for a given problem and thus offers a viable approach for structure learning.

In this work, we present a deep reinforcement learning architecture with intrinsically-motivated curriculum learning to optimize the structure of VQE circuits. The goal of this approach is to design circuits that estimate the ground state energy of molecules within chemical accuracy while keeping the circuit depth as low as possible. In our approach, instead of confronting the RL agent with the full-scale problem from the beginning, the agent first starts training on a simpler instance and autonomously adjusts the task complexity until chemical accuracy is achieved. In particular, we demonstrate that our approach yields the ground state energy of LiH within chemical accuracy for several bond distances. While other VQE approaches also reach chemical accuracy for this benchmark, our approach consistently outperforms the others in terms of circuit depth. Hence, the unique combination of deep RL and intrinsic motivation for structure learning yields an interesting new approach for solving VQE problems.

We emphasize that whilst we focus specifically on the molecular electronic structure problem for LiH, the reinforcement learning approach presented in this paper can be adapted for optimizing other VQE architectures [36, 7]. The method is also directly compatible with other reinforcement learning algorithms, and the angle optimization algorithms are not restricted to the methods investigated in this paper.

In summary, the methods proposed in this work provide state-of-the-art results in electronic structure problem experiments, and lay the foundations for the application of deep reinforcement learning methods to VQE optimization problems. And, as is often the case when new methods are employed, we envision numerous follow-up avenues which will reveal the true capacities of such automated ML methods for VQE-type problems.

References

[1] John Preskill. Quantum computing in the NISQ era and beyond. *Quantum*, 2:79, 2018.

[2] Alberto Peruzzo, Jarrod McClean, Peter Shadbolt, Man-Hong Yung, Xiao-Qi Zhou, Peter J Love, Alán Aspuru-Guzik, and Jeremy L O'brien. A variational eigenvalue solver on a photonic quantum processor. *Nature Communications*, 5:4213, 2014.

[3] Abhinav Kandala, Antonio Mezzacapo, Kristan Temme, Maika Takita, Markus Brink, Jerry M Chow, and Jay M Gambetta. Hardware-efficient variational quantum eigensolver for small molecules and quantum magnets. *Nature*, 549(7671):242–246, 2017.

[4] Harper R. Grimsley, Sophia E. Economou, Edwin Barnes, and Nicholas J. Mayhall. An adaptive variational algorithm for exact molecular simulations on a quantum computer. *Nature Communications*, 10(1):3007, Jul 2019.

[5] Ho Lun Tang, V. O. Shkolnikov, George S. Barron, Harper R. Grimsley, Nicholas J. Mayhall, Edwin Barnes, and Sophia E. Economou. qubit-ADAPT-VQE: An adaptive algorithm for constructing hardware-efficient ansatze on a quantum processor. *arXiv e-prints*, November 2019.

[6] Pierre-Luc Dallaire-Demers and Nathan Killoran. Quantum generative adversarial networks. *Phys. Rev. A*, 98:012324, Jul 2018.

[7] Marcello Benedetti, Erika Lloyd, Stefan Sack, and Mattia Fiorentini. Parameterized quantum circuits as machine learning models. *Quantum Science and Technology*, 4(4):043001, nov 2019.

[8] Leo Zhou, Sheng-Tao Wang, Soonwon Choi, Hannes Pichler, and Mikhail D. Lukin. Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices. *Phys. Rev. X*, 10:021067, Jun 2020.

[9] Jonathan Romero and Alán Aspuru-Guzik. Variational quantum generators: Generative adversarial quantum machine learning for continuous distributions. *Advanced Quantum Technologies*, 4(1):2000003, 2021.

[10] M.-H. Yung, J. Casanova, A. Mezzacapo, J. McClean, L. Lamata, A. Aspuru-Guzik, and E. Solano. From transistor to trapped-ion computers for quantum chemistry. *Scientific Reports*, 4(1):3589, Jan 2014.

[11] Abhinav Kandala, Antonio Mezzacapo, Kristan Temme, Maika Takita, Markus Brink, Jerry M. Chow, and Jay M. Gambetta. Hardware-efficient variational quantum eigensolver for small molecules and quantum magnets. *Nature*, 549(7671):242–246, Sep 2017.

[12] Marcello Benedetti, Mattia Fiorentini, and Michael Lubasch. Hardware-efficient variational quantum algorithms for time evolution, 2020.

[13] Jeffrey L. Elman. Learning and development in neural networks: the importance of starting small. *Cognition*, 48(1):71–99, 1993.

[14] Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *ACM International Conference Proceeding Series*, volume 382, pages 1–8, New York, New York, USA, 2009. ACM Press.

[15] IG Csizmadia, BT Sutcliffe, and MP Barnett. A group orbital study of lithium hydride. *Canadian Journal of Chemistry*, 42(7):1645–1663, 1964.

[16] Steven Herbert and Akash Sengupta. Using reinforcement learning to find efficient qubit routing policies for deployment in near-term quantum computers. *arXiv preprint arXiv:1812.11619*, 2018.

[17] M Sohaib Alam. Quantum logic gate synthesis as a markov decision process. *arXiv preprint arXiv:1912.12002*, 2019.

[18] Mohammad Pirhooshyaran and Tamas Terlaky. Quantum circuit design search. *arXiv preprint arXiv:2012.04046*, 2020.

[19] Thomas Fösel, Murphy Yuezhen Niu, Florian Marquardt, and Li Li. Quantum circuit optimization with deep reinforcement learning, 2021.

[20] Shi-Xin Zhang, Chang-Yu Hsieh, Shengyu Zhang, and Hong Yao. Neural predictor based quantum architecture search. *arXiv preprint arXiv:2103.06524*, 2021.

[21] Arthur G. Rattew, Shaohan Hu, Marco Pistoia, Richard Chen, and Steve Wood. A domain-agnostic, noise-resistant, hardware-efficient evolutionary variational quantum eigensolver. *arXiv: Quantum Physics*, 2019.

[22] D Chivilikhin, A Samarin, V Ulyantsev, I Iorsh, AR Oganov, and O Kyriienko. Mog-vqe: Multiobjective genetic variational quantum eigensolver. *arXiv preprint arXiv:2007.04424*, 2020.

[23] Nikolaus Hansen and Andreas Ostermeier. Completely derandomized self-adaptation in evolution strategies. *evol. Comput.*, 9(2):159–195, June 2001.

[24] M Bilkis, M Cerezo, Guillaume Verdon, Patrick J Coles, and Lukasz Cincio. A semi-agnostic ansatz with variable structure for quantum machine learning. *arXiv preprint arXiv:2103.06712*, 2021.

[25] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. In *NIPS Deep Learning Workshop*. 2013.

[26] Michael JD Powell. A direct search optimization method that models the objective and constraint functions by linear interpolation. In *Advances in optimization and numerical analysis*, pages 51–67. Springer, 1994.

[27] Mateusz Ostaszewski, Edward Grant, and Marcello Benedetti. Structure optimization for parameterized quantum circuits. *Quantum*, 5:391, 2021.

[28] Arthur Aubret, Laëtitia Matignon, and Salima Hassas. A survey on intrinsic motivation in reinforcement learning. *CoRR*, abs/1908.06976, 2019.

[29] Jacob T. Seeley, Martin J. Richard, and Peter J. Love. The bravyi-kitaev transformation for quantum computation of electronic structure. *The Journal of Chemical Physics*, 137(22):224109, 2012.

[30] P. Jordan and E. Wigner. Über das paulische äquivalenzverbot. *Zeitschrift für Physik*, 47(9):631–651, Sep 1928.

[31] Qiskit: An open-source framework for quantum computing, 2019.

[32] R. S. Sutton and A. G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, Cambridge, MA, second edition, 2018.

[33] Yasunari Suzuki, Yoshiaki Kawase, Yuya Masumura, Yuria Hiraga, Masahiro Nakadai, Jiabao Chen, Ken M Nakanishi, Kosuke Mitarai, Ryosuke Imai, Shiro Tamiya, et al. Qulacs: a fast and versatile quantum circuit simulator for research purpose. *arXiv preprint arXiv:2011.13524*, 2020.

[34] Mark R. Hoffmann and Jack Simons. A unitary multiconfigurational coupled-cluster method: Theory and applications. *The Journal of Chemical Physics*, 88(2):993–1002, 1988.

[35] Alternative coupled-cluster ansätze ii. the unitary coupled-cluster method. *Chemical Physics Letters*, 155(1):133 – 140, 1989.

[36] Marco Cerezo, Andrew Arrasmith, Ryan Babbush, Simon C Benjamin, Suguru Endo, Keisuke Fujii, Jarrod R McClean, Kosuke Mitarai, Xiao Yuan, Lukasz Cincio, et al. Variational quantum algorithms. *arXiv preprint arXiv:2012.09265*, 2020.