PATH AUXILIARY PROPOSAL FOR MCMC IN DISCRETE SPACE

ABSTRACT

Energy-based Models (EBMs) offer a powerful approach for modeling discrete structure, but both inference and learning of EBM are hard as it involves sampling from discrete distributions. Recent work shows Markov Chain Monte Carlo (MCMC) with the informed proposal is a powerful tool for such sampling. However, an informed proposal only allows local updates as it requires evaluating all energy changes in the neighborhood. In this work, we present a path auxiliary algorithm that uses a composition of local moves to efficiently explore large neighborhoods. We also give a fast version of our algorithm that only queries the evaluation of energy function twice for each proposal via linearization of the energy function. Empirically, we show that our path auxiliary algorithms considerably outperform other generic samplers on various discrete models for sampling, inference, and learning. Our method can also be used to train deep EBMs for high dimensional discrete data.

1 INTRODUCTION

Many real-world problems involve discrete structured data modeling, such as syntax trees for natural language processing(Tai et al., 2015), graphical model for molecules(Gilmer et al., 2017), etc. A powerful approach for modelling the distribution over structured data is Energy Based Models(LeCun et al., 2006) (EBMs). EBMs define the distribution with an unnormalized energy function, which allows great flexibility to fit the target distribution. However, this flexibility also results in the difficulties in inference and learning, as they require sampling from the EBM (Andrieu et al., 2003; Hinton, 2002), where the partition function is intractable in many cases.

Markov Chain Monte Carlo (MCMC) algorithms are one of the most widely used methodologies to sample from intractable distributions (Robert & Casella, 2013). The efficiency for MCMC depends drastically on the proposal distribution. For example, in continuous space, Metropolis-adjusted Langevin algorithm (MALA) exploits the gradient of the target in single step walk and biases the proposal distribution toward high probability region (Rossky et al., 1978; Roberts & Rosenthal, 1998; Welling & Teh, 2011); Hamiltonian Monte Carlo (HMC) employs multi-step walk and explores the distribution more efficiently(Neal, 2004; Girolami & Calderhead, 2011; Hoffman et al., 2014). These methods substantially improve the performance of the MCMC algorithm in theory and in practice. However, their proposal distributions are derived as discretization of continuous diffusion process and it is still not clear how to appropriately extend such methods into discrete space(Zanella, 2020).

Recently, Zanella (2020) proposed a general framework called pointwise informed proposal (PIP) that shows promising results on directly sampling from discrete distributions. PIP utilizes the energy change in the neighborhood of current state to propose a new state. Following this work, Grathwohl et al. (2021) propose a more efficient sampler that uses Taylor series to estimate the energy change in the neighborhood. However, both methods only focus on proposing from a small neighborhood, for example, a 1-Hamming ball. This is due to the computational expense of evaluating the energy change or approximation error of Taylor series for a large neighborhood. As a result, the samples in Markov chain will have strong correlation or even be trapped at local optimum, which deteriorates the sampling efficiency.

In order to efficiently explore a larger neighborhood, we propose a path auxiliary algorithm. In each step of the path, we employ a local proposal distribution to make a sequence of small movements

to reach a new state in long distance. A typical challenge for such multi-step proposal is that the accept ratio could decrease very fast when the number of steps increases. Surprisingly, we show that the accept ratio of our path auxiliary proposal is *independent* of the path and only determined by the information at the current state and the proposed state. As a result, our algorithm is able to maintain a high accept ratio with multiple local steps. We can provably show that the locally balancing functions are asymptotically optimal for our sampler. We also introduce an efficient version of the algorithm that uses linearization and can be applied to smooth target distributions.

We empirically evaluate our methods in inference, sampling, and learning on various discrete EBMs. We demonstrate that our methods significantly improve the efficiency on parity model, weighted permutation model, Ising model, Restricted Boltzmann Machine, and Factorized Hidden Markov Model. Our method can also learn competitive deep EBMs on discrete image data.

2 BACKGROUND

Energy Based Model: Let $\mathcal{X}$ be a finite state space. An EBM defines an energy function $f : \mathcal{X} \to \mathbb{R}$ with target distribution $\pi(x) = e^{-f(x)}/Z$, where $Z = \sum_{z \in \mathcal{X}} e^{-f(z)}$ (LeCun et al., 2006; Wainwright & Jordan, 2008; Du & Mordatch, 2019). The unnormalized energy function provides great flexibility to characterize complex distribution. However, this can also make the partition function Z intractable to calculate and exacerbate the difficulties of learning and inference.

Metropolis-Hastings: MCMC is a commonly used methodology to sample from an intractable distribution. Metropolis-Hastings (MH) is one of the most commonly used framework for MCMC(Metropolis et al., 1953; Hastings, 1970). Given the current state x, a proposal distribution $Q(x, \cdot)$ gives a new state y, then MH algorithm accept y with probability of $\min\{1, \frac{\pi(y)Q(y,x)}{\pi(x)Q(x,y)}\}$ to guarantee the Markov chain is π-reversible. The efficiency of MH algorithm highly depends on the selection of proposal distribution Q.

Peskun Ordering: Peskun ordering provides a method to compare the efficiency for two MCMC algorithms (Peskun, 1973; Tierney, 1998). Let P_1, P_2 be π-reversible Markov transition kernels on $\mathcal{X}$ such that $P_1(x, y) > cP_2(x, y)$ for all $x \neq y$ for a fixed $c > 0$, then we say P_1 is c-times more efficient than P_2 as the following holds: 1) $\text{var}_\pi(h, P_1) \leq \frac{1}{c}\text{var}_\pi(h, P_2) + \frac{1-c}{c}\text{var}_\pi(h)$, $\forall h : \mathcal{X} \to \mathbb{R}$; 2) $\text{Gap}(P_1) \geq c\, \text{Gap}(P_2)$. A smaller *asymptotic variance* $\text{var}_\pi(h, P)$ means a better estimation for the expectation of h and a larger *spectral gap* $\text{Gap}(P)$ means a faster convergence of the Markov chain.

Pointwise Informed Proposals and Locally Balancing Function: A pointwise informed proposal (PIP) is a MH algorithm in discrete space (Zanella, 2020). PIP uses proposal distribution $Q_g(x, y) = g(\frac{\pi(y)}{\pi(x)})I(x, y)/Z_g(x)$, where the $I(x, y) = 1_{\{y \in \mathcal{N}(x)\}}$ is the membership indicator w.r.t a symmetric neighborhood $\mathcal{N}(\cdot)$, and $Z_g(x) = \sum_{z \in \mathcal{X}} g(\frac{\pi(z)}{\pi(x)})I(x, z)$. The weight function g determines the efficiency of PIP. Zanella (2020) show that the family of locally balancing functions $\mathcal{G} = \{g : \mathbb{R}_+ \to \mathbb{R}_+, g(t) = tg(\frac{1}{t}), \forall t > 0\}$ is asymptotically optimal for PIP w.r.t. Peskun ordering. Empirically, Zanella (2020) shows $g(t) = \sqrt{t}$ and $g(t) = \frac{t}{t+1}$ have the best performance. Despite being powerful, PIP requires the calculatation of the weight $g(\frac{\pi(z)}{\pi(x)})$ for all states in the neighborhood. Hence, only a small neighborhood, usually a 1-Hamming ball, is used in existing methods.

3 PATH AUXILIARY PROPOSAL

Problems occur in point-wise informed proposal (PIP) when merely considering a small neighborhood, especially for distributions with many local optima. For example, consider a parity distribution where the state space $\mathcal{X} = \{0, 1\}^p$, and the energy function $f(x) = U$ if the number of 1s in x is odd, otherwise $f(x) = 0$. When a 1-Hamming ball neighborhood is used, by symmetry, a PIP will have a uniform probability to propose a new state from neighborhood. Then, the expected time to leave a low energy state is $O(e^U)$, which could be very inefficient when U is large. When a r-Hamming ball larger neighborhood is used, a PIP can efficiently escape a low energy state. How-

ever, the neighborhood will contain $O(n^r)$ states, which could be computationally prohibitive when n or r is large.

To address such problems with PIP, we propose a path auxiliary sampler. Instead of directly sampling from a large neighborhood, path auxiliary sampler sequentially samples new state from a local proposal distribution Q_0. The computation cost at each step is still manageable as Q_0 still samples locally. Then the composition of small movements forms a path that can lead to a new state that is distant from the current state. The complexity of the sampling grows linearly instead of exponentially w.r.t. r. In this section, we first present the framework of our algorithm. Then, we discuss the choice of the weight function for path auxiliary sampler. And finally, we introduce a fast version of path auxiliary sampler.

3.1 PROPOSAL VIA AUXILIARY PATH

We first define an auxiliary path. Given the neighborhood function $\mathcal{N}$, the set of auxiliary paths on $\mathcal{X}$ is defined as

$$\Sigma(\mathcal{X}, \mathcal{N}) := \{(\sigma, L) : \sigma_i \in \mathcal{X}, i = 0, ..., L; \sigma_l \in \mathcal{N}(\sigma_{l-1})), l = 1, ..., L\} \tag{1}$$

To obtain the auxiliary path, we employ a PIP $Q_0(\cdot, \cdot)$ to make local movements. We also sample path length from a prior $\alpha(\cdot)$ to assure our chain is aperiodic. The path auxiliary sampler is defined as follows

1. Sample a path length L from a prior $\alpha(L)$.

2. Denote the current state $x_t = \sigma_0$, sample $\sigma_l \sim Q_0(\sigma_{l-1}, \cdot)$ for $l = 1, ..., L$.

3. Accept $x_{t+1} = \sigma_L$ in probability $A(x, \sigma, L) = \min\left\{1, \frac{\pi(\sigma_L)\prod_{l=1}^{L} Q_0(\sigma_l, \sigma_{l-1})}{\pi(\sigma_0)\prod_{l=1}^{L} Q_0(\sigma_{l-1}, \sigma_l)}\right\}$, else $x_{t+1} = x_t$.

Theorem 1. *The path auxiliary proposal transition rule described above satisfies the detailed balance and induces a reversible Markov chain with π as its invariant distribution.*

3.2 BENEFIT FROM AUXILIARY PATH

We first analyze the performance of path auxiliary sampler on parity distribution mentioned above. Assume we use a uniform prior $\alpha(1) = \alpha(2) = \frac{1}{2}$. If we sample $L = 2$, then we will transit back to a new state with same energy as the current state, hence the accept ratio will be 1. As a result, we can always escape from a state in $O(1)$ steps in expectation.

Having a path auxiliary sampler to sample from L-Hamming ball at each step is more efficient than performing L steps of MH sampling in a 1-Hamming ball. To mathematically justify it, we show the accept ratio comparison between the path auxiliary sampler and 1-Hamming ball PIP sampler with the same Q_0 for proposal. Consider a path (σ, L), we compare the accept ratio below:

$$\min\left\{1, \frac{\pi(\sigma_L)\prod_{l=1}^{L} Q_0(\sigma_l, \sigma_{l-1})}{\pi(\sigma_0)\prod_{l=1}^{L} Q_0(\sigma_{l-1}, \sigma_l)}\right\} \geq \prod_{l=1}^{L} \min\left\{1, \frac{\pi(\sigma_l)Q_0(\sigma_l, \sigma_{l-1})}{\pi(\sigma_{l-1})Q_0(\sigma_{l-1}, \sigma_l)}\right\} \tag{2}$$

We can notice that the accept ratio for path auxiliary sampler is the product of the probability for single-step method before the minimum operator. As a result, an auxiliary path can have a high accept ratio as long as the product is large. On the contrary, in the multiple local MH case, the transition can probably be blocked at some steps in the path with low accept ratios.

3.3 BALANCED PROPOSAL

Although the product in equation 2 allows the Markov chain to escape from a local optimum when some steps in the path have high accept ratio, it can also exponentially decrease the accept ratio w.r.t. the path length L when every step has a low accept ratio. Hence, it is important to select a good local proposal Q_0. In this section, we show that the locally balancing function Zanella (2020) is asymptotically optimal for path auxiliary sampler. We first define a sub-class of weight function named as ideal function:

Definition 1. *$\mathcal{F}$ is the set of ideal function. A function $f \in \mathcal{F}$ if and only if following conditions holds: 1) $f : \mathbb{R}_+ \to \mathbb{R}_+$; 2) $f(1) = 1$; 3) $f(t)$ is monotonic increasing; 4) $f(t)f(\frac{1}{t})t \leq 1, \forall t \leq 1$*

The next theorem shows that locally balancing function $\mathcal{G}$ is asymptotically better than ideal function $\mathcal{F}$ in Peskun Ordering.

Theorem 2. *Consider the state space in Cartesian products $\mathcal{X} = \times_{i=1}^{n} \mathcal{X}_i$, where each $\mathcal{X}_i$ is a finite space with M elements, and the neighborhood is defined as 1-Hamming ball. Let d_n be the maximum degree in conditional independence graph. If 1) $\lim_{n \to \infty} \frac{d_n}{n} = 0$; 2) the target distribution satisfies $\frac{\pi(y)}{\pi(x)} \leq C < \infty, \forall y \in \mathcal{N}(x)$; 3) the path length prior α is bounded by U. Then for any $f \in \mathcal{F}$, we have a function $g \in \mathcal{G} = \{g(\cdot) : g(t) = tg(\frac{1}{t})\}$ that is asymptotically more efficient than f, which implies $\mathcal{G}$ is asymptotically optimal in $\mathcal{F}$.*

The idea to prove this theorem is to use $\bar{f}(t) := \sqrt{f(t)f(\frac{1}{t})t}$. By definition, we have:

$$\bar{f}(t) = \sqrt{f(t)f(\frac{1}{t})t} = t\sqrt{f(t)f(\frac{1}{t})\frac{1}{t}} = t\bar{f}(\frac{1}{t}) \tag{3}$$

which means $\bar{f} \in \mathcal{G}$. Then, the theorem is proved by showing the π-reversible Markov transition kernel $P_{\bar{f}}(x, y) \geq P_f(x, y)$ asymptotically holds. The proof is given in Sec A.5

Although Definition 1 has some constraints, it already contains almost all natural choices of weight functions, such as $f(t) = \frac{2t}{1+t}, f(t) = \min\{1, t\}, f(t) = \max\{1, t\}$, and $f(t) = t^\alpha, \alpha \geq 0$. Hence, the asymptotic optimality for locally balanced function $\mathcal{G}$ in ideal function $\mathcal{F}$ strongly suggest that locally balanced function is a good choice for path auxiliary sampler. More discussion for ideal function can be found in Sec A.3

Property 1. *When using a locally balancing function $g \in \mathcal{G}$ as the weight function, the accept ratio for path auxiliary sampler can be written as:*

$$A(x, y, \sigma, L) = \min\left\{1, \frac{Z_g(x)}{Z_g(y)}\right\} \tag{4}$$

The path independent form in Property 1 makes the accept ratio only depends on the intrinsic structure of the target distribution. Intuitively, if the energy function is smooth enough, we can imagine that the accept ratio in equation 4 will be high when y is close to x. By selecting $g(t) = \sqrt{t} \in \mathcal{G}$, we give our path auxiliary sampler (PAS) in Algorithm 1.

3.4 SCALABLE PATH AUXILIARY ALGORITHM

Although path auxiliary proposal only samples from a small neighborhood for each step in the path σ, it still requires $O(nL)$ evaluations of the probability $\pi(x)$ in total, where n is the radius of the neighborhood. In cases where the computational bottleneck is evaluating the target probability, this cost will be expensive. Fortunately, most distributions of interest have differentiable energy functions, such as deep EBMs. Hence, we can use the linearization as approximation. Given the current state σ_0, the linearization is

$$\tilde{f}_{\sigma_0}(z) = f(\sigma_0) + \langle \nabla f(\sigma_0), z - \sigma_0 \rangle \tag{5}$$

we can estimate $\tilde{\pi}_{\sigma_0}(y)/\tilde{\pi}_{\sigma_0}(x) = e^{-\langle \nabla f(\sigma_0), y - x \rangle}$, and define our proposal distribution $\tilde{Q}_{g,\sigma_0}(x, y) = g(\frac{\tilde{\pi}_0(y)}{\tilde{\pi}_0(x)})/\tilde{Z}_{g,\sigma_0}(x)$, and the normalizer $Z_{g,\sigma_0}(x) = \sum_{z \in \mathcal{N}(x)} g(\frac{\tilde{\pi}_0(z)}{\tilde{\pi}_0(x)})$. to sample an auxiliary path σ. After obtaining σ_L, we use the linearization $\tilde{f}_{\sigma_L}$ at σ_L to compute the accept ratio w.r.t. the auxiliary path

$$A(x, \sigma, L) = \min\left\{1, \frac{\pi(y) \prod_{l=1}^{L} \tilde{Q}_{g,\sigma_L}(\sigma_l, \sigma_{l-1})}{\pi(x) \prod_{l=1}^{0} \tilde{Q}_{g,\sigma_0}(\sigma_{l-1}, \sigma_l)}\right\} \tag{6}$$

By using approximation, we only need to evaluate $\pi(y), \pi(x), \nabla f(y), \nabla f(x)$ once in every proposal, which is a significant reduction of the computational cost. We name this algorithm as path auxiliary fast sampler (PAFS) (see Algorithm 1). Our algorithm has similar framework as GWG Grathwohl et al. (2021). The difference is that GWG draw all indices from the linearization at σ_0. As a result, GWG can repeatedly select the same indices and exacerbates the efficiency, especially after mixing. Our PAFS sampler uses the linearization at each state σ_l and effectively avoid

---

Algorithm 1: Path Auxiliary Sampler (PAS) and the fast version (PAFS)

Input: Target Distribution π, Initial state x_0, Path Length Prior α, Weight Function $g(t) = \sqrt{t}$
Output: Sample sequence $(x_1, x_2, ...)$

1 **repeat**
2   Sample path length $L \sim \alpha(L)$
3   Denote $\sigma_0 = x_t$, sample $\sigma_l \sim Q_g(\sigma_{l-1}, \cdot)$ or $\sigma_l \sim \tilde{Q}_{g,\sigma_0}(\sigma_{l-1}, \cdot)$ for $l = 1, ..., L$.
4   Accept $x_{t+1} = \sigma_L$ in probability $A(x, \sigma, L) = \min\{1, \frac{Z_g(x_t)}{Z_g(\sigma_L)}\}$
5   or $A(x, \sigma, L) = \min\left\{1, \frac{\pi(y)\prod_{l=1}^{L}\tilde{Q}_{g,\sigma_L}(\sigma_l, \sigma_{l-1})}{\pi(x)\prod_{l=1}^{0}\tilde{Q}_{g,\sigma_0}(\sigma_{l-1}, \sigma_l)}\right\}$, else $x_{t+1} = x_t$.
6 **until** *finish sampling*;

---

the backtrack. Though a simple modification, PAFS shows substantial improvements compared to GWG, e.g. in figure 6. Similar to GWG (Grathwohl et al., 2021), the decrease of the quality from this approximation can be bounded.

Theorem 3. *Assume the energy function $f(x)$ is differentiable, $\nabla f(x)$ is K-Lipschitz. Consider we use weight function $g(t) = \sqrt{t}$, path length prior α bounded by U, and 1-Hamming ball as neighborhood. Denote P and $\tilde{P}$ as the transition kernel by path auxiliary sampler and path auxiliary faster sampler, respectively, we have*

$$\tilde{P}(x,y) \geq e^{-K\frac{U(U+1)}{2}}P(x,y) \tag{7}$$

Using the Peskun ordering, we know PAFS is at least $e^{-K\frac{U(U+1)}{2}}$ times as efficient as PAS. When the energy function is smooth enough, we can save $O(nU)$ evaluations of energy function without losing too much proposal quality. See the proof and discussion in Sec A.7.

4 RELATED WORKS

Informed proposal for Metropolis-Hastings (MH) algorithm has been extensively studied in the continuous space(Robert & Casella, 2013). The most famous algorithms are Metropolis-adjusted Langevein algorithm (MALA) (Roberts & Rosenthal, 1998) and Hamiltonian Monte Carlo (HMC). MALA, HMC, and their variants (Girolami & Calderhead, 2011; Hoffman et al., 2014; Welling & Teh, 2011; Titsias & Papaspiliopoulos, 2018) exploit the gradient of the target distribution to bias the proposal distribution towards high probability regions. Although gradient-based methods having brought substantial improvements in continuous space, it is still unclear how to extend them to discrete space.

A number of methods try to map the discrete space to a continuous space using relaxation, apply informed methods in continuous space, and then map the new state back into discrete space(Zhang et al., 2012; Pakman & Paninski, 2013; Nishimura et al., 2017; Han & Liu, 2018; Jaini et al., 2021) via Gaussian Integral Trick, uniform dequantization, or SurVAE flow. Such methods work in some scenarios, but a key challenge is the embedding of discrete space into continuous space can destroy the inherent discrete structure, resulting in highly multi-modal and irregular target distribution in continuous spaces.

Another group of methods directly work on discrete space. Dai et al. (2020) introduces the path as latent variable in the variational distribution for initializing PCD, but still relies on slow Gibbs sampling for improvement; Titsias & Yau (2017) augment the discrete space with auxiliary variable and perform Gibbs sampling in the augmented space based on informed proposal. Zanella (2020) shows that a family of locally balancing function is asymptotically optimal for informed proposal. Following Zanella (2020), Power & Goldman (2019) extends the framework to Markov jumping process, and Sansone (2021) parameterize locally balanced function to tune it via mutual information to select good weight function from the locally balanced class. When the target distribution is smooth enough, Grathwohl et al. (2021) employs a Taylor's series to approximate the target distribution and further improve the sampling efficiency. Though these informed proposal algorithms successfully show orders of magnitude improvements when using 1-Hamming ball as neighborhood, they are

not able to explore a large neighborhood. An extension of GWG (Grathwohl et al., 2021) can partially address this problem via sampling multiple dimensions to modify in one step. However, such procedure can easily lead to backtracks thereby reducing its efficiency.

5 EXPERIMENTS

5.1 SAMPLERS UNDER CONSIDERATION

In this section, we empirically evaluate the sampling efficiency of path auxiliary sampler (PAS) and path auxiliary fast sampler (PAFS). We choose the path length prior α as a uniform distribution on $\{1, ..., 2X - 1\}$ and denote the corresponding samplers as PAS-X and PAFS-X.

We compare our methods with five types of baselines: random walk sampler (RW), Gibbs sampler (Gibbs), Hamming ball sampler (HB), locally balanced sampler (LB), Gibbs with gradient sampler (GWG). RW is an informed proposal with $g(t) = 1$ that uniformly propose new state from neighborhood. Gibbs partitions the dimension of a state x into two groups x_u and x_{-u}, then updates the state from conditional distribution $p(x_u|x_{-u})$. We denote it as Gibbs-X, where X refers to the dimension of x_u. HB is a two-stage Gibbs sampler on the extended state space (x, x') (Titsias & Yau, 2017). We use HB-10-1, where 10 is the block size, and 1 is the hamming ball size. LB (Zanella, 2020) is implemented as a single-step PIP with $g(t) = \sqrt{t}$. GWG (Grathwohl et al., 2021) is a fast approximation of LB, which uses first order Taylor's series at the starting state σ_0 to draw indices to flip. We denote the algorithm as GWG-X, where X indicates that the number of indices to modify per step is uniformly sampled from $\{1, ..., 2X - 1\}$.

5.2 INFERENCE ON ENERGY BASED MODEL

Parity Model: We first demonstrate the benefit of path auxiliary sampler versus single-step sampler in a inference task that estimates the mean μ of a parity distribution. A parity distribution has state space $\mathcal{X} = \{0, 1\}^p$ and energy function

$$f(x) = ((\sum_{i=1}^{p} x_i) \bmod 2)U \tag{8}$$

i.e. a state has energy U if it has an odd number of 1s, otherwise 0. The neighborhood is defined as 1-Hamming ball. We run the simulation with $p = 100$ and $U = \{1, 3, 5\}$, and report the estimation

Figure 1: Estimation Error of Distribution Mean on Parity Model

error $E_n := \|\hat{\mu}_n - \mu\|_2$, where $\hat{\mu}_n = \sum_{i=1}^{n} X_i$ is the sample mean of the Markov chain at step n. For each setting and method, we run 5 chains for 20,000 steps, and we plot the mean and standard deviation of the estimation error in figure 1. We can observe that the efficiency of single step sampler decreases exponentially when U increases. On the contrary, the path auxiliary sampler can always escape from the local optima in parity distribution and estimate the distribution mean efficiently.

Weighted Permutation Model: We consider an optimization task on weighted permutation model. The state space $\mathcal{X} = S_p$ is a symmetric group, i.e. for any $\rho \in \mathcal{X}$, ρ is a permutation of $1, 2, ..., p$. The energy function is defined as:

$$f(\rho) = \sum_{i=1}^{p} w_{i, \rho(i)} \tag{9}$$

Following Zanella (2020), the weight $\{w_{ij}\}_{i,j=1}^{p}$ are i.i.d. sampled from Gaussian$(0, \sigma^2)$. The neighborhood is determined by one exchange of the permutation. We use MCMC algorithms to find good permutations with small energy. We use $p = 100$, $\sigma = 3, 5, 10$, and run 5 simulations for each configurations. Since our formulation of weighted permutation model does not have gradient, we

Figure 2: Energy Trace on Weighted Permutation Model

Figure 3: PAS and PAFS in different lengths on 200×200 Ising Model

did not compare with GWG. From figure 2, we can see that LB sampler is trapped at local optimum, especially when σ is large and the distribution is sharp. However, PAS can always efficiently find good solutions via auxiliary path.

5.3 SAMPLING ON ENERGY BASED MODEL

Lattice Ising Model: Consider the state space $\mathcal{X} = \{-1, 1\}^{V_p}$, where (V_p, E_p) is the $p \times p$ square lattice graph. For each $x \in \mathcal{X}$, the energy function is defined as:

$$f(x) = -\sum_{i \in V_p} \alpha_i x_i - \lambda \sum_{(i,j) \in E_p} x_i x_j \tag{10}$$

$\alpha_i \in \mathbb{R}$ are bias terms representing the property of x_i and λ is a global interaction term. We first compare PAS and PAFS in different path lengths. For each length, we run 100 chains with 100,000 steps. We report the burn-in stage as well as effective sample size (ESS) [1] in terms of both MCMC steps and energy function evaluation times. From figure 3, we can see that, 1) PAS has slight improvement in terms of energy function evaluations when we increase the path length; 2) comparing to PAS, PAFS has very similar proposal quality and significantly better efficiency. We also compare our sampler with other competitors. For each sampler, we run 5 Markov chains with 1,000,000 steps and report the ESS to compare the proposal quality. From figure 4, we can see our sampler leads in both quality and efficiency. More results are given in Sec B.1.

Factorized Hidden Markov Model: FHMM is a statistical model that use latent variables in $\mathcal{X} = \{0, 1\}^{N \times K}$ to characterize time series data $y \in \mathbb{R}^N$. Denote $p(x)$ for hidden variables, and $p(y|x)$ for likelihood:

$$p(x) = \prod_{n=1}^{N} p(x_{n,1}) \prod_{k=2}^{K} p(x_{n,k}|x_{n,k-1}), \quad p(y|x) = \prod_{n=1}^{N} \text{Gaussian}(y_n; wx_n + b, \sigma^2) \tag{11}$$

---

[1] Computed follows Tensorflow Probability

Figure 4: ESS for Different Samplers on 200×200 Ising model

Figure 5: BurnIn in FHMM

Given data y, we use MCMC to sample x from the posterior $p(x|y)$ and compare the mixing for different samplers. We choose parameters $N = 1000, K = 10$, $\mathbb{P}(x_{n,1} = 1) = 0.05$, $\mathbb{P}(X_{n,k} = x_{n,k-1}) = 0.85$, $w \in \text{Gaussian}(0, I_K)$, $b \in \text{Gaussian}(0, 1)$, and $\sigma^2 = 0.25$. We run each chain 5 times and report the mean and std for the energy (negative log joint density) $E(\hat{x}) = -\log p(\hat{x})p(y|\hat{x})$ and the reconstruction error $\|y - w\hat{x}\|_2$ w.r.t. the number of evaluations of energy function. From figure 5 we can see that both GWG and PAFS gain significant improvements in mixing by using a larger neighborhood. More results are given in Sec **??**

Restricted Boltzmann Machine: RBM is bipartite latent-variable model, whose energy function is defined as:

$$f(x) = \log(1 + e^{w^T x + c}) + b^T x \tag{12}$$

where $\{W, b, c\}$ are parameters and $x \in \{0, 1\}^D$. We follow Grathwohl et al. (2021) to train a RBM with 500 hidden units on the MNIST dataset using contrastive divergence(Hinton, 2002). We generate samples via various MCMC samplers on the trained RBM. Besides reporting ESS, we also estimate the maximum mean discrepancy (MMD) (Gretton et al., 2012) w.r.t. a set of "ground truth" samples generated by structure known Block-Gibbs sampler. Figure 7 shows PAFS has large ESS and can efficiently match the "ground truth" samples. We also demonstrate an ablation study on different the approximations of auxiliary path. Specifically, we evaluate GWG, PAFS with different lengths. For each sampler, we run 100 chains and report their ESS and average hop distance, where the summary statistics for ESS is the energy and the hop distance is the hamming distance between consecutive states. We can notice GWG suffers from a large path length L as we discussed at

Figure 6: Sampling on RBM with Different Path Length

the end of Sec 3.4, while our PAFS obtains robust improvements for all L via employing a soft no replacement sampling. This result indicates our PAFS provides an efficient framework to sample from a large neighborhood. We also try hard no replacement sampler, which strictly forbids selecting an index multiple time in the auxiliary path. However, it causes difficulty in mixing when L is large. More results and discussions are given in Sec 6 and Sec B.3).

5.4 LEARNING ON ENERGY BASED MODEL

Learning an EBM is a challenge task. Consider the target distribution is π and our energy function f_θ is parameterized by θ. The gradient for the likelihood of $\pi_\theta(x) \propto e^{-f_\theta(x)}$ is:

$$\nabla_\theta \log p(x) = \mathbb{E}_\pi[\nabla_\theta f_\theta(x)] - \mathbb{E}_{\pi_\theta}[\nabla_\theta f_\theta(x)] \tag{13}$$

The first expectation can be estimated using the data from true distribution. The second expectation requires samples from the current model, which is typically obtained via MCMC. Hence, the success of training an EBM relies on efficient MCMC algorithms to get an accurate estimation of the second expectation.

Figure 7: Sampling on RBM trained on MNIST

Figure 8: Learning Ising

Dataset	VAE (MLP)	VAE (Conv)	EBM (GWG)	EBM (Gibbs)	EBM (PAFS)	RBM	DBN
Static MNIST	-86.05	-82.41	-80.01	-117.17	**-79.58**	-86.39	-85.67
Dynamic MNIST	-82.42	-80.40	-80.51	-121.19	**-79.59**	-	-
Omniglot	-103.52	-97.65	-94.72	-142.06	**-90.75**	-100.47	-100.78
Caltech Silhouettes	-112.08	-106.35	-96.20	-163.50	**-84.56**	-	-

Table 1: Evaluation of different discrete models on the held-out test set.

Ising model We first learn an Ising model following the setting in Grathwohl et al. (2021), where the energy function $f(x) = \theta x^T J x$. Given a set of samples $\{x_i\}$, the task is to learn an EBM via recovering the connectivity matrix J. We generate a 25×25 2D cyclic lattice with $\theta = 0.25$ and sample training data with a long-run Gibbs chain. We train the models to maximize the likelihood of samples using persistent contrastive divergence (PCD)(Tieleman & Hinton, 2009) and report the root mean squared error (RMSE) between the inferred connectivity matrix $\hat{J}$ and the true matrix J. For fair comparison, we also include GWG-eq, which runs GWG-1 with more steps such that it has the same time cost as our PAFS-5. figure 8 shows larger neighborhood can effectively help learn the Ising model. Also, GWG-5 having similar performance as PAFS-5 indicates that, using PCD, the learning efficiency of Ising model is mainly determined by the mixing of the Markov chain.

Deep EBM We evaluate path auxiliary sampler by learning a deep EBM. The experiment follows the setting in (Grathwohl et al., 2021). We train deep EBMs paramterized by Residual Networks(He et al., 2016) on small binary image datasets using PCD(Tieleman & Hinton, 2009) with a replay buffer(Du & Mordatch, 2019). We compare our methods with Variational Autoencoders Kingma & Welling (2013), GWG (Grathwohl et al., 2021), RBM and a Deep Belief Network(Hinton, 2009). We estimate the likelihoods using Annealed Importance Sampling(Neal, 2001) and report the results in table.1. The results for VAE is taken from Tomczak & Welling (2018), RBM and DBN are taken from Burda et al. (2015), GWG is taken from Grathwohl et al. (2021). We can see that our approach improves the log-likelihoods for deep EBMs on all datasets.

6 Discussion and Conclusion

In this work, we use a prior $\alpha(L) \sim \mathrm{Uniform}(0, U)$ for path length. To determine how to select U, we compare PAS or PAFS with different path length in Ising, FHMM, and RBM in terms of energy function evaluations. For PAS, we observe the improvements of both mixing and ESS in Ising. However, in FHMM, improving the path length only helps mixing but does not increase the ESS. This means the effectiveness for PAS depends on the structure of the target distribution and we need more investigation to figure out a rule to select the path length. For PAFS, employing a soft no replacement sampling, it obtains robust improvements under different path length in both Ising and FHMM. Even if L is larger than the optimal length, PAFS only stops obtaining improvements from increasing L and still have good proposal quality. For this reason, when the computational bottleneck is evaluating the energy function, we can employ an aggressive policy to select large path length for PAFS.

More sophisticated policy can let $\alpha(L|x)$ depends the current state Girolami & Calderhead (2011); Hoffman et al. (2014). As mentioned in Power & Goldman (2019), with locally balanced proposal, the Markov chain is paired with a Markov Jumping process. With this observation, we believe the path length can be selected based on the holding time in the jumping process. Another idea is renewing the gradient when sampling the auxiliary path. Borrowing the idea from HMC, the frequency to renew the gradient can be adaptively selected based on the approximation error Andrieu & Thoms (2008); Beskos et al. (2013), and the path length can be tuned by maximizing the average hop distance(Hoffman et al., 2014; 2021).

In summary, informed proposal has shown good results for inference, sampling, and learning EBMs in discrete spaces. Our path auxiliary sampler provides an approach allowing informed proposal to efficiently explore large neighborhoods. We believe there is considerable room for future works to improve the sampling methods in discrete space.

REFERENCES

Christophe Andrieu and Johannes Thoms. A tutorial on adaptive mcmc. *Statistics and computing*, 18(4):343–373, 2008.

Christophe Andrieu, Nando De Freitas, Arnaud Doucet, and Michael I Jordan. An introduction to mcmc for machine learning. *Machine learning*, 50(1):5–43, 2003.

Alexandros Beskos, Natesh Pillai, Gareth Roberts, Jesus-Maria Sanz-Serna, and Andrew Stuart. Optimal tuning of the hybrid monte carlo algorithm. *Bernoulli*, 19(5A):1501–1534, 2013.

Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Accurate and conservative estimates of mrf log-likelihood using reverse annealing. In *Artificial Intelligence and Statistics*, pp. 102–110. PMLR, 2015.

Hanjun Dai, Rishabh Singh, Bo Dai, Charles Sutton, and Dale Schuurmans. Learning discrete energy-based models via auxiliary-variable local exploration. *arXiv preprint arXiv:2011.05363*, 2020.

Yilun Du and Igor Mordatch. Implicit generation and generalization in energy-based models. *arXiv preprint arXiv:1903.08689*, 2019.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Mark Girolami and Ben Calderhead. Riemann manifold langevin and hamiltonian monte carlo methods. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 73(2): 123–214, 2011.

Will Grathwohl, Kevin Swersky, Milad Hashemi, David Duvenaud, and Chris J Maddison. Oops i took a gradient: Scalable sampling for discrete distributions. *arXiv preprint arXiv:2102.04509*, 2021.

Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012.

Jun Han and Qiang Liu. Stein variational gradient descent without gradient. In *International Conference on Machine Learning*, pp. 1900–1908. PMLR, 2018.

W Keith Hastings. Monte carlo sampling methods using markov chains and their applications. 1970.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Geoffrey E Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 14(8):1771–1800, 2002.

Geoffrey E Hinton. Deep belief networks. *Scholarpedia*, 4(5):5947, 2009.

Matthew Hoffman, Alexey Radul, and Pavel Sountsov. An adaptive-mcmc scheme for setting trajectory lengths in hamiltonian monte carlo. In *International Conference on Artificial Intelligence and Statistics*, pp. 3907–3915. PMLR, 2021.

Matthew D Hoffman, Andrew Gelman, et al. The no-u-turn sampler: adaptively setting path lengths in hamiltonian monte carlo. *J. Mach. Learn. Res.*, 15(1):1593–1623, 2014.

Priyank Jaini, Didrik Nielsen, and Max Welling. Sampling in combinatorial spaces with survae flow augmented mcmc. In *International Conference on Artificial Intelligence and Statistics*, pp. 3349–3357. PMLR, 2021.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, and F Huang. A tutorial on energy-based learning. *Predicting structured data*, 1(0), 2006.

Nicholas Metropolis, Arianna W Rosenbluth, Marshall N Rosenbluth, Augusta H Teller, and Edward Teller. Equation of state calculations by fast computing machines. *The journal of chemical physics*, 21(6):1087–1092, 1953.

Radford M Neal. Annealed importance sampling. *Statistics and computing*, 11(2):125–139, 2001.

Radford M Neal. Improving asymptotic variance of mcmc estimators: Non-reversible chains are better. *arXiv preprint math/0407281*, 2004.

Akihiko Nishimura, David Dunson, and Jianfeng Lu. Discontinuous hamiltonian monte carlo for sampling discrete parameters. *arXiv preprint arXiv:1705.08510*, 853, 2017.

Ari Pakman and Liam Paninski. Auxiliary-variable exact hamiltonian monte carlo samplers for binary distributions. *arXiv preprint arXiv:1311.2166*, 2013.

Peter H Peskun. Optimum monte-carlo sampling using markov chains. *Biometrika*, 60(3):607–612, 1973.

Samuel Power and Jacob Vorstrup Goldman. Accelerated sampling on discrete spaces with non-reversible markov processes. *arXiv preprint arXiv:1912.04681*, 2019.

Christian Robert and George Casella. *Monte Carlo statistical methods*. Springer Science & Business Media, 2013.

Gareth O Roberts and Jeffrey S Rosenthal. Optimal scaling of discrete approximations to langevin diffusions. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 60(1): 255–268, 1998.

Peter J Rossky, JD Doll, and HL Friedman. Brownian dynamics as smart monte carlo simulation. *The Journal of Chemical Physics*, 69(10):4628–4633, 1978.

Emanuele Sansone. Lsb: Local self-balancing mcmc in discrete spaces. *arXiv preprint arXiv:2109.03867*, 2021.

Kai Sheng Tai, Richard Socher, and Christopher D Manning. Improved semantic representations from tree-structured long short-term memory networks. *arXiv preprint arXiv:1503.00075*, 2015.

Tijmen Tieleman and Geoffrey Hinton. Using fast weights to improve persistent contrastive divergence. In *Proceedings of the 26th annual international conference on machine learning*, pp. 1033–1040, 2009.

Luke Tierney. A note on metropolis-hastings kernels for general state spaces. *Annals of applied probability*, pp. 1–9, 1998.

Michalis K Titsias and Omiros Papaspiliopoulos. Auxiliary gradient-based sampling algorithms. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 80(4):749–767, 2018.

Michalis K Titsias and Christopher Yau. The hamming ball sampler. *Journal of the American Statistical Association*, 112(520):1598–1611, 2017.

Jakub Tomczak and Max Welling. Vae with a vampprior. In *International Conference on Artificial Intelligence and Statistics*, pp. 1214–1223. PMLR, 2018.

Martin J Wainwright and Michael Irwin Jordan. *Graphical models, exponential families, and variational inference*. Now Publishers Inc, 2008.

Max Welling and Yee W Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proceedings of the 28th international conference on machine learning (ICML-11)*, pp. 681–688. Citeseer, 2011.

Joe Whittaker. *Graphical models in applied multivariate statistics*. Wiley Publishing, 2009.

Giacomo Zanella. Informed proposals for local mcmc in discrete spaces. *Journal of the American Statistical Association*, 115(530):852–865, 2020.

Yichuan Zhang, Zoubin Ghahramani, Amos J Storkey, and Charles Sutton. Continuous relaxations for discrete hamiltonian monte carlo. *Advances in Neural Information Processing Systems*, 25: 3194–3202, 2012.

A PROOFS

A.1 PROOF FOR THEOREM 1

Proof. Denote $K(x, y)$ as the probability that x transit to a different state y, then we have:

$$\pi(x)K(x, y) \tag{14}$$

$$= \pi(x) \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \left[\left(\prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l) \right) \min \left\{ 1, \frac{\pi(y) \prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1})}{\pi(x) \prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l)} \right\} \right] \tag{15}$$

$$= \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \left[\pi(x) \left(\prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l) \right) \min \left\{ 1, \frac{\pi(y) \prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1})}{\pi(x) \prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l)} \right\} \right] \tag{16}$$

$$= \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \min \left\{ \pi(x) \prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l), \pi(y) \prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1}) \right\} \tag{17}$$

$$= \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \left[\pi(y) \left(\prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1}) \right) \min \left\{ \frac{\pi(x) \prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l)}{\pi(y) \prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1})}, 1 \right\} \right] \tag{18}$$

$$= \pi(y) \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = y, \sigma_L = x}} \left[\left(\prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1}) \right) \min \left\{ \frac{\pi(x) \prod_{l=1}^L Q_0(\sigma_l, \sigma_{l-1})}{\pi(y) \prod_{l=1}^L Q_0(\sigma_{l-1}, \sigma_l)}, 1 \right\} \right] \tag{19}$$

$$= \pi(y)K(y, x) \tag{20}$$

Since the path (σ, L) is symmetric w.r.t. its two ends, when σ is a path from x to y, σ is also a path from y to σ. Hence, if we exchange x, y, the summation is still applied on same paths. This implies the detailed balance condition $\pi(x)K(x, y) = \pi(y)K(y, x)$ □

A.2 PROOF FOR LEMMA 1

Lemma 1. *$\mathcal{X}$ is a finite state space with distribution π and a neighborhood function $\mathcal{N}$ such that every state has equal number of states. $\mathcal{F}$ is a class of weight functions, such that for any $f \in \mathcal{F}$, 1) $f : \mathbb{R}_+ \to \mathbb{R}_+$, 2) $f(1) = 1$, 3) $f(t)$ is monotonically increasing, 4) $f(t)f(\frac{1}{t})t \le 1, \forall t \le 1$. $\forall f \in \mathcal{F}$, define $\bar{f}(t) = \sqrt{f(t)f(\frac{1}{t})t}$, we have*

$$\min_{x \in \mathcal{X}} Z_{\bar{f}}(x) \le \max_{y \in \mathcal{X}} Z_f(y) \tag{21}$$

Proof. Since $\mathcal{X}$ is finite, we can always find state x_1, x_2 having highest and lowest probability, respectively. Then, we have:

$$Z_{\bar{f}}(x_1) = \sum_{z \in \mathcal{N}(x_1)} \bar{f}(\frac{\pi(z)}{\pi(x_1)}) \le |\mathcal{N}(x_1)| = |\mathcal{N}(x_2)| \le \sum_{z \in \mathcal{N}(x_2)} f(\frac{\pi(z)}{\pi(x_2)}) = Z_f(x_2) \tag{22}$$

□

A.3 DISCUSSION FOR IDEAL FUNCTION

We define ideal function as a stepping stone to show the advantage of locally balanced function. We name it "ideal" as the its properties are ideal assumption for a weight function in PIP. Conditions 1) $f : \mathbb{R}_+ \to \mathbb{R}_+$ is a natural requirement for weight function. Condition 2) $f(1) = 1$ can be easily realized by substituting $f(t)$ by $f(t)/f(1)$, as PIP only depends on the ratio of weights. condition 3) $f(t)$ is monotonically increasing, and condition 4) $f(t)f(\frac{1}{t})t \le 1, \forall t \le 1$, though, are

technical requirements, it is reasonable for weight functions. Monotonic increasing in 3) indicates the proposal distribution match the target distribution, where a point z has a higher probability in target distribution should also has a higher probability in proposal distribution. Condition 4) is weaker than the following condition: $f(t) \leq t, \forall t \geq 1$, hence condition 4) is easier to satisfy.

Currently definition of ideal function class already contains most of commonly used weight function, such as $f(t) = \frac{2t}{1+t}, f(t) = \max\{1, t\}, f(t) = \min\{1, t\}$, and $f(t) = t^{\alpha}$, where $\alpha \geq 0$. Also, we can following properties

Property 2. *The logarithm of ideal function is closed in convex combination. That's to say, $\forall f_1, ..., f_n \in \mathcal{F}$, and $\forall \lambda_1, ..., \lambda_n$, s.t $\lambda_i \geq 0$ and $\sum_{i=1}^{n} \lambda_i = 1$, we have*

$$F(t) = e^{\sum_{i=1}^{n} \lambda_i \log f_i(t)} \in \mathcal{F} \tag{23}$$

Proof. Let f_i and λ_i be defined as above. Obviously, F is positive and $F(1) = 1$, hence satisfies condition 1) and 2). For condition 3), we have:

$$F(t)F(\frac{1}{t})t = e^{\sum_{i=1}^{n} \lambda_i \log f_i(t)} \cdot e^{\sum_{i=1}^{n} \lambda_i \log f_i(\frac{1}{t})} \cdot e^{\sum_{i=1}^{n} \lambda_i \log t} \tag{24}$$

$$= e^{\sum_{i=1}^{n} \lambda_i (\log f_i(t) + \log f_i(\frac{1}{t}) + \log t)} \tag{25}$$

$$= e^{\sum_{i=1}^{n} \lambda_i \log(f_i(t) f_i(\frac{1}{t})t)} \tag{26}$$

Hence, $\forall t \leq 1$, we have:

$$F(t)f(\frac{1}{t})t \leq e^{\sum_{i=1}^{n} \lambda_i 0} = 1 \tag{27}$$

which implies $F(t) \in \mathcal{F}$. $\square$

Property 3. *Ideal function is a superset for normalized monotonically increasing locally balanced function $\mathcal{G}_I := \{g \in \mathcal{G} : g(1) = 1, g \text{ is monotonically increasing}\}$.*

Proof. $\forall g \in \mathcal{G}_I$, condition 1), 2) and 3) are obviously satisfied. For condition 4), since $g(t)$ is locally balanced, we have:

$$g(t)g(\frac{1}{t})t = g^2(t) \leq g^2(1) = 1 \tag{28}$$

implies $g \in \mathcal{F}$. $\square$

Considering the ideal function cover such a large number of functions, we believe the asymptotic optimality over ideal function strongly suggests locally balanced function is a good choice for path auxiliary sampler.

A.4 PROOF FOR LEMMA 2

The (undirected) conditional independence graph corresponds to Markov random fields:

Definition 2. *The conditional independence graph of X is the undirected graph $G = (K, E)$, where $K = \{1, ..., k\}$ and $(i, j) \notin E$ if and only if $X_i \perp X_j | X_{K \setminus \{i,j\}}$.*

More details can be found in p.60 Whittaker (2009).

Lemma 2. *Consider the state space in Cartesian products $\mathcal{X} = \times_{i=1}^{n} \mathcal{X}_i$, where each $\mathcal{X}_i$ is a finite space with M elements, and the neighborhood is defined as 1-Hamming ball. Let d_n be the maximum degree in conditional independence graph. Define $c_g^{(n)} := \sup_{y \in \mathcal{N}(x)} \frac{Z_g(y)}{Z_g(x)}$. If 1) $\lim_{n \to \infty} \frac{d_n}{n} = 0$; 2) the target distribution satisfies $\frac{\pi(y)}{\pi(x)} \leq C < \infty, \forall y \in \mathcal{N}(x)$, then we have:*

$$1 \leq c_g^{(n)} \leq 1 + \mathcal{O}(\frac{d_n g(C)}{n g(\frac{1}{C})}) \quad as \ n \to \infty, \quad \forall g \in \mathcal{F} \tag{29}$$

To simplify the notation, we assume $M = 2$ in this proof. It is straightforward to extend the proof to any finite M.

Proof. On one side, by definition, we can easily see that $c_g^{(n)} \geq 1$. On the other side, given x, we use index i represent that we select $y \in \mathcal{N}(x)$ by flipping index i for x. We denote $g_x(j) = g(\pi(z))/g(\pi(x))$ where z is obtained by flipping index j for x, and we denote $g_i(j) = g(\pi(z))/g(\pi(y))$, where z is obtained by flipping index j for y. We also denote $B(i)$ as the Markov boundary for i, which means given $B(i)$, i is independent with remaining nodes. Then, we can write

$$c_g^{(n)} = \sup_{x \in \mathcal{X}} \sup_{i \in [M]} \frac{\sum_{j=1}^{n} g_i(j)}{\sum_{j=1}^{n} g_x(j)} \tag{30}$$

$$= \sup_{x \in \mathcal{X}} \sup_{i \in [M]} \frac{\sum_{j \in B(i)} g_i(j) + \sum_{j \notin B(i)} g_i(j)}{\sum_{j \in B(i)} g_x(j) + \sum_{j \notin B(i)} g_x(j)} \tag{31}$$

$$\leq \sup_{x \in \mathcal{X}} \sup_{i \in [M]} \frac{\sum_{j \in B(i)} g_i(j)}{\sum_{j \in B(i)} g_x(j)} + \frac{\sum_{j \notin B(i)} g_i(j)}{\sum_{j \in B(i)} g_x(j) + \sum_{j \notin B(i)} g_x(j)} \tag{32}$$

$$\leq \sup_{x \in \mathcal{X}} \sup_{i \in [M]} 1 + \frac{\sum_{j \notin B(i)} g_i(j)}{\sum_{j \in B(i)} g_x(j) + \sum_{j \notin B(i)} g_x(j)} \tag{33}$$

$$\leq \sup_{x \in \mathcal{X}} \sup_{i \in [M]} 1 + \frac{d_n g(C)}{n g(\frac{1}{C})} \tag{34}$$

$$\leq 1 + \frac{d_n g(C)}{n g(\frac{1}{C})} \tag{35}$$

If $B(i)$ is not empty, the first term in equation 32 equals to 1. If $B(i)$ is empty, the first term in equation 32 does not exist, hence it can still be bounded by 1. $\square$

Remark: For a fixed ideal function $g \in \mathcal{F}$, Lemma 2 shows $c^{(n)}$ converges to 1 at a rate $1 + \mathcal{O}(\frac{d_n}{n})$

A.5 PROOF FOR THEOREM 2

We prove the theorem by using Lemma 1 and Lemma 2.

Proof. We first show that, for all $g \in \mathcal{F}$, the transition probability:

$$P_{\bar{g}}(x, y) \geq (\frac{1}{c_g c_{\hat{g}}})^U P_g(x, y) \tag{36}$$

where c_g is defined in Lemma 2. We temporarily ignore the superscription and will add it back at the end of the proof. Consider a path (σ, L), we denote $t_{j,k} = \frac{\pi(\sigma_k)}{\pi(\sigma_j)}$. Then the probability that $x = \sigma_0$ transits to $y = \sigma_L$ is:

$$P_g(x, y, \sigma | L) = \prod_{l=1}^{L} Q_g(\sigma_{l-1}, \sigma_l) \min \left\{ 1, \frac{\pi(y) \prod_{l=1}^{L} Q_g(\sigma_l, \sigma_{l-1})}{\pi(x) \prod_{l=1}^{L} Q_g(\sigma_{l-1}, \sigma_l)} \right\} \tag{37}$$

$$= \min \left\{ \prod_{l=1}^{L} \frac{g(t_{l-1,l})}{Z_g(\sigma_{l-1})}, \prod_{l=1}^{L} t_{l-1,l} \frac{g(t_{l,l-1})}{Z_g(\sigma_l)} \right\} \tag{38}$$

By definition of c_g, we have:

$$P_g(x, y, \sigma | L) \leq c_g^L \frac{\min \left\{ \prod_{l=1}^{L} g(t_{l-1,l}), \prod_{l=1}^{L} t_{l-1,l} g(t_{l,l-1}) \right\}}{\max_{z \in \mathcal{X}^{(n)}} Z_g^L(z)} \tag{39}$$

$$P_{\bar{g}}(x, y, \sigma | L) \geq \frac{1}{c_{\bar{g}}^L} \frac{\min \left\{ \prod_{l=1}^{L} \bar{g}(t_{l-1,l}), \prod_{l=1}^{L} t_{l-1,l} \bar{g}(t_{l,l-1}) \right\}}{\min_{z \in \mathcal{X}^{(n)}} Z_{\bar{g}}^L(z)} \tag{40}$$

Use the property of $\bar{g}$, we have

$$\min \left\{ \prod_{l=1}^{L} g(t_{l-1,l}), \prod_{l=1}^{L} t_{l-1,l} g(t_{l,l-1}) \right\} \leq \sqrt{\prod_{l=1}^{L} g(t_{l-1,l}) g(t_{l,l-1}) t_{l-1,l}} = \prod_{l=1}^{L} \bar{g}(t_{l-1,l}) \tag{41}$$

Combining equation 39, equation 40, equation 41, and Lemma 1 we have:

$$P_{\bar{g}}(x, y, \sigma | L) \geq \frac{1}{c_{\bar{g}}^L} \frac{\prod_{l=1}^{L} \bar{g}(t_{l-1,l})}{\min_{z \in \mathcal{X}^{(n)}} Z_{\bar{g}}^L(z)} \tag{42}$$

$$\geq \frac{1}{c_{\bar{g}}^L} \frac{\min\left\{\prod_{l=1}^{L} g(t_{l-1,l}), \prod_{l=1}^{L} t_{l-1,l} g(t_{l,l-1})\right\}}{\max_{z \in \mathcal{X}^{(n)}} Z_g^L(z)} \tag{43}$$

$$\geq \frac{1}{c_{\bar{g}}^L c_g^L} P_g(x, y, \sigma | L) \tag{44}$$

The inequality holds for arbitrary auxiliary path (σ, L) and the path length $L \leq U$, hence we prove the first step. Then $\forall g \in \mathcal{F}$, we use the estimation of $c_g^{(n)}$ in Lemma 2, we have

$$P_{\bar{g}}(x, y) \geq C_g^{(n)} P_g(x, y) \tag{45}$$

where

$$C_g^{(n)} = 1 - \mathcal{O}(U \frac{d_n g(C)}{n g(\frac{1}{C})}) \tag{46}$$

This indicates $\bar{g}$ is asymptotically better than g and proves the theorem. □

Remark: In the proof, equation 46 shows the convergence rate depends on g, this factor prevents a uniform convergence rate for the ideal function class $\mathcal{F}$. We can obtain a uniform rate when we constraint in smaller function class, for example, if we restrict to $\mathcal{F}_M := \{f \in \mathcal{F} : f(C)/f(\frac{1}{C}) \leq M\}$, the convergence rate is $1 - \mathcal{O}(\frac{d_n}{n})$.

A.6 Proof for Property 1

Proof.

$$A(x, y, \sigma, L) = \min\left\{1, \frac{\pi(y) \prod_{l=1}^{L} Q(\sigma_l, \sigma_{l-1})}{\pi(x) \prod_{l=1}^{L} Q(\sigma_{l-1}, \sigma_l)}\right\} \tag{47}$$

$$= \min\left\{1, \left(\prod_{l=1}^{L} \frac{\pi(\sigma_l)}{\pi(\sigma_{l-1})}\right) \frac{\prod_{l=1}^{L} g(\frac{\pi(\sigma_{l-1})}{\pi(\sigma_l)})/Z_g(\sigma_l)}{\prod_{l=1}^{L} g(\frac{\pi(\sigma_l)}{\pi(\sigma_{l-1})})/Z_g(\sigma_{l-1})}\right\} \tag{48}$$

$$= \min\left\{1, \left(\prod_{l=1}^{L} \frac{\pi(\sigma_l)}{\pi(\sigma_{l-1})} \frac{g(\frac{\pi(\sigma_{l-1})}{\pi(\sigma_l)})}{g(\frac{\pi(\sigma_l)}{\pi(\sigma_{l-1})})}\right) \left(\prod_{l=1}^{L} \frac{Z_g(\sigma_{l-1})}{Z_g(\sigma_l)}\right)\right\} \tag{49}$$

$$= \min\left\{1, \frac{Z_g(x)}{Z_g(y)}\right\} \tag{50}$$

□

A.7 Proof for Theorem 3

The idea to proof theorem 3 is similar to Grathwohl et al. (2021), which uses the Lipschitz condition to bound the estimation error. The different is, in PAFS, we use the linearization at each state σ_l to propose the next state σ_{l+1}, hence to need to accumulate the error at each step to obtain our final result.

Proof. For any path (σ, L), we first bound the estimation error $\tilde{f}_0(z) - \tilde{f}_0(\sigma_{l-1})$, for $z \in \mathcal{N}(\sigma_{l-1})$. Since f is M-smooth, we have:

$$f(z) - f(\sigma_{l-1}) \tag{51}$$

$$\leq \langle \nabla f(\sigma_{l-1}), z - \sigma_{l-1} \rangle + \frac{K}{2} \|z - \sigma_{l-1}\|^2 \tag{52}$$

$$= \langle \nabla f(\sigma_0), z - \sigma_{l-1} \rangle + \langle \nabla f(\sigma_{l-1}) - \nabla f(\sigma_0), z - \sigma_{l-1} \rangle + \frac{K}{2} \|z - \sigma_{l-1}\|^2 \tag{53}$$

$$\leq \langle \nabla f(\sigma_0), z - \sigma_{l-1} \rangle + K(l - \frac{1}{2}) \tag{54}$$

Similarly, we also have:

$$f(z) - f(\sigma_{l-1}) \geq \langle \nabla f(\sigma_0), z - \sigma_{l-1} \rangle + K(l + \frac{1}{2}) \tag{55}$$

With this estimation, we have:

$$\tilde{Q}_0(\sigma_{l-1}, \sigma_l) = \frac{e^{-\frac{1}{2}\langle \nabla f(\sigma_0), \sigma_l - \sigma_{l-1} \rangle}}{\sum_{z \in \mathcal{N}(\sigma_{l-1})} e^{-\frac{1}{2}\langle \nabla f(\sigma_0), \sigma_l - \sigma_{l-1} \rangle}} \tag{56}$$

$$\geq \frac{e^{-\frac{1}{2}[f(\sigma_l) - f(\sigma_{l-1}) - K(l - \frac{1}{2})]}}{\sum_{z \in \mathcal{N}(\sigma_{l-1})} e^{-\frac{1}{2}[f(z) - f(\sigma_{l-1}) + K(l + \frac{1}{2})]}} \tag{57}$$

$$= Q(\sigma_{l-1}, \sigma_l) e^{-Kl} \tag{58}$$

Similarly, we can also obtain

$$\tilde{Q}_L(\sigma_l, \sigma_{l-1}) \geq Q(\sigma_l, \sigma_{l-1}) e^{K(L-l)} \tag{59}$$

Now, consider the transition kernel

$$\tilde{P}(x, y) = \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \prod_{l=1}^L \tilde{Q}_0(\sigma_{l-1}, \sigma_l) \min\left\{1, \frac{\pi(y)}{\pi(x)} \frac{\prod_{l=1}^L \tilde{Q}_L(\sigma_l, \sigma_{l-1})}{\prod_{l=1}^L \tilde{Q}_0(\sigma_{l-1}, \sigma_l)}\right\} \tag{60}$$

$$= \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \min\left\{\prod_{l=1}^L \tilde{Q}_0(\sigma_{l-1}, \sigma_l), \frac{\pi(y)}{\pi(x)} \prod_{l=1}^L \tilde{Q}_L(\sigma_l, \sigma_{l-1})\right\} \tag{61}$$

$$\geq \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} \min\left\{\prod_{l=1}^L Q(\sigma_{l-1}, \sigma_l) e^{-Kl}, \frac{\pi(y)}{\pi(x)} \prod_{l=1}^L Q(\sigma_l, \sigma_{l-1}) e^{-K(L-l)}\right\} \tag{62}$$

$$\geq \sum_L \alpha(L) \sum_{\substack{(\sigma, L) \in \Sigma(\mathcal{X}, \mathcal{N}): \\ \sigma_0 = x, \sigma_L = y}} e^{-K\frac{L(L+1)}{2}} \min\left\{\prod_{l=1}^L Q(\sigma_{l-1}, \sigma_l), \frac{\pi(y)}{\pi(x)} \prod_{l=1}^L Q(\sigma_l, \sigma_{l-1})\right\} \tag{63}$$

$$\geq e^{-K\frac{U(U+1)}{2}} P(x, y) \tag{64}$$

$\square$

Remark: Though the theorem proved above is very loose, it provides a framework to prove approximation bound for path auxiliary sampler via single step approximation in equation 58. More sophisticated bounds can be obtained by improving the single step estimation in equation 58 via the property of the conditional independence. Specifically, a local modifying of the state usually does not influence most of the indices, which for example can be characterized by the Markov boundary. Then, with high probability, the auxiliary path can avoid manipulating correlated indices and hence result in the approximation error in equation 58 be controlled by a constant, rather than e^{-Kl}. For example, in Ising model, an auxiliary path has high probability to avoid manipulating two adjacent nodes, and in this case, the linearization is accurate and we loose nothing in approximation. In deep EBMs, the conditional independence is usually not available, but we can still expect low correlation between most of dimensions. Such analysis relies on more accurate assumption of conditional independence and we will leave it to our future work.

Figure 9: PAS and PAFS in different lengths on 50×50 Ising Model

Figure 10: PAS and PAFS in different lengths on 100×100 Ising Model

B   DETAILS FOR EXPERIMENTS

B.1   SAMPLING ON ISING

Following Zanella (2020), we set the interaction term $\lambda = 1$, and we set $\alpha_i = \mu + Z_i$ if i in the center of the square lattice, and $\alpha_i = -\mu + Z_i$ otherwise, where $\mu = 2$ and $Z_i \sim \text{Unif}(-3, 3)$. We generate the lattice Ising model in four sizes: $p = 50, 100, 150, 200$. We first run PAS and PAFS with path lengh $L = 1, 2, 3, 5, 10$ on Ising model with size $p = 50, 100, 150, 200$. For each path length and each model size, we run 100 chains 100,000 steps and compute the ESS using the last 50,000 steps. The results for $p = 200$ is given in figure 3. We give the results for $p = 50, 100, 150$ in the following.   From figure 9, figure 10, figure 11, and figure 3, we can see that the difference between PAS and PAFS in terms of MCMC steps is decreasing when the model size is increasing. The reason is that when the model becomes larger, most of the nodes are conditionally independent. When the auxiliary path does not involve two adjacent nodes, the approximation has zero error. This observation provides a possibility to further improve the approximation bound in Theorem 3. We will study this in our future work.

For comparing with other samplers, we report the results for each problem size $p = 50, 100, 150, 200$ in figure 12, figure 13, figure 14, figure 4. Our path auxiliary samplers substantially outperform other competitors.

B.2   SAMPLING ON FHMM

We compare PAS and PAFS with different path length on FHMM. We choose parameters $K = 10$, $\mathbb{P}(x_{n,1} = 1) = 0.05$, $\mathbb{P}(X_{n,k} = x_{n,k-1}) = 0.85$, $w \in \text{Gaussian}(0, I_K)$, $b \in \text{Gaussian}(0, 1)$, and $\sigma^2 = 0.25$. We simulate PAS, PAFS with path length $L = 1, 2, 3, 5, 10$ on FHMM with $N = 500, 1000, 1500, 2000$. For each configuration, we run 100 chains and report the burn in period, as well as the ESS in terms of MCMC steps and energy function evaluations.

Figure 11: PAS and PAFS in different lengths on 150×150 Ising Model

Figure 12: Sampling on 50×50 Ising model

Figure 13: Sampling on 100×100 Ising model

We can observe that: 1) in terms of MCMC steps, PAFS has very similar burn in time in energy compared to PAS, while the the gap in ESS is larger than the gap in Ising. The reason is FHMM is not as close to linear model as Ising and PAFS has larger estimation error. 2) in terms of energy function evaluations, PAFS still leads the performance as other models. PAS only obtains faster mixing, and no improvements in ESS. The results show that whether PAS can help depends on the property of the target distribution.

B.3   SAMPLING ON RBM

We compare GWG, PAFS, and NB with different path lengths on RBM trained on MNIST dataset. GWG (Grathwohl et al., 2021) samples all indices to manipulate based on the linearization at starting state of the path σ_0, and we classify it as sampling with replacement. Our PAFS samples the indices based on the linearization at current state σ_l and we classify it as sampling with soft no replacement. Specifically, consider a binary case, when we flip index i at state σ_l, then in the remaining of the path, the energy change for index i will be reversed. Hence, if we flip an index and reduce the system's energy, we will have small probability flip it back. A third type sampler is No Backtrack (NB) sampler. It is also a path auxiliary sampler and it rules out the indices have been selected to assure

Figure 14: Sampling on 150×150 Ising model

Figure 15: PAS and PAFS in different path lengths on FHMM N=500

Figure 16: PAS and PAFS in different path lengths on FHMM N=1000

it is sampling with hard no replacement. Specifically, NB first calculate the probability for indices based on $\nabla f(\sigma_0)$ as GWG. Then, once selecting an index i at σ_l, NB manipulates the probability for selecting index i in the remaining path. For each sampler with path length $L = 1, ..., 20$, we run 100 chains and report the MMD (Gretton et al., 2012) w.r.t. a set of "ground truth" samples generated by structure known Block-Gibbs sampler. We can see that, when increasing the path length, PAFS has steady fast mixing, GWG decreases the efficiency in mixing, and NB fails in mixing. For this reason, we only compare the statistics for GWG and PAFS in our main text in figure 6.

B.4 RUNNING TIME IN LEARNING ISING

We follow the experiments in Grathwohl et al. (2021). GWG runs faster 1.4x than our PAFS-5 as the energy function computation is cheap in this experiment. To obtain a fair comparison, we add GWG-equivalent-length (GWG-eq), which we allow GWG-1 to run 1.4x more sampling steps such that its running time is the same as our PAFS. When our PAFS runs 5, 10, 25, 50 steps, GWG-eq runs 6, 13 34, 69 steps. Hence, when we draw figure 8, the point for GWG-eq at step 5, 10, 25, 50 using the RMSE obtained at setp 6, 13, 34, 69.

B.5 DETAILS IN LEARNING DEEP EBMS

DataSet	Static MNIST	Omniglot	Caltech
PAFS-3	0.685	0.885	0.893
PAFS-5	0.746	0.980	0.962
PAFS-7	0.775	1.030	1.010
GWG	0.877	1.130	1.140

Table 2: Run Time for One Batch for different discrete models.

Figure 17: PAS and PAFS in different path lengths on FHMM N=1500

Figure 18: PAS and PAFS in different path lengths on FHMM N=2000

Figure 19: ESS for PAS and PAFS in different path lengths on FHMM

We use the same setting as Grathwohl et al. (2021), including the batch size, number of iterations, the PCD hyper parameters, etc. In principle, both PAFS and GWG requires two energy function evaluations per MCMC step, despite that PAFS explores much larger neighborhood space via path auxiliary. As the energy function evaluation and gradient calculation usually dominates the computation, we expect these two should have similar runtime.

In practice, we report the average running time per batch of 100 chains in table 2. We can see for deep EBMs, our PAFS with different path lengths run slightly faster than GWG. Given that both of the methods implemented using pytorch, the minor speed up might be due to the implementation issue. So overall we think it is fair to say the two methods run equally fast in most cases. For this reason, we use the same number of steps when we train the deep EBMs. As is reported in Grathwohl et al. (2021), we the same number of steps (40) to train the binary deep EBMs. For our method, we also tune the expected path length in $\{3, 5, 7\}$, and report the result with the best validation likelihood.

Figure 20: GWG Burn In

Figure 21: PAFS Burn In

Figure 22: NB Burn In