When Trump Shakes Biden's Hand: Tracking Real-World Interactions in Time and Space from Textual Records

Abstract

Interpersonal interactions provide important insights into political, cultural, and historical phenomena. Existing research mainly analyzes online interactions (e.g., retweets, mentions, follows), but such signals poorly capture real-world encounters, are often biased, and cover only recent decades. In contrast, **historical texts such as encyclopedias and news record real-world interactions across centuries, together with temporal and spatial context**. However, extracting structured interaction quadruplets *(Person1, Person2, Time, Location)* remains challenging due to complex spatio-temporal dependencies and indirect mentions. **To address this, we construct the *WikiInteraction* dataset (4,507 annotated quadruplets) and propose FALCON**, which integrates AR-BERT, multi-task learning, and feature transfer to model such dependencies. FALCON achieves 86.51% F1, outperforming all baselines including GPT-o1 at substantially lower cost, and generalizes well to *Encyclopedia Britannica* and news corpora. Applied at scale, it extracts **658,966 Wikipedia quadruplets spanning over 1,000 years and 77,836 news quadruplets**. For each quadruplet, we further showcase how open-domain interaction type (e.g., cooperation, debate) can be inferred via LLM. In a case study, we analyze the 5-tuples (typed quadruplets) of US politicians (1960–2024, 7,891 figures), revealing long-term polarization highly consistent with a classic index constructed from congressional votes, which is hardly covered by online data. Code and datasets (5-tuples) are available[1].

1 Introduction

Interpersonal interactions, especially among notable individuals, reveal insights into cultural, economic, political, scientific, and historical perspectives (Jackson, 2011; O'Neill, 2014), as seen in scientists (Newman, 2001; Fortunato et al., 2018), politicians (Hsu and Park, 2012; Plotkowiak and Stanoevska-Slabeva, 2013), and authors (Börner et al., 2004; Sun et al., 2011). Much existing research focuses on social media interactions (e.g., retweets, mentions, follows) (Kubin and Von Sikorski, 2021; Donkers and Ziegler, 2025), offering scale and accessibility. However, these virtual signals poorly capture real-world encounters (e.g., collaborations, negotiations) and suffer fundamental limitations. In political polarization, uneven platform adoption leads to skewed datasets (Pokhriyal et al., 2023), while fake news (Van der Linden et al., 2020), bots (Deb et al., 2019), and coordinated disinformation (Nizzoli et al., 2021; Cinus et al., 2025) compromise analysis. Moreover, social media only covers recent decades, limiting historical analyses.

In contrast, textual records like encyclopedias, news, and books provide an ideal source for extracting long-term interactions with temporal and spatial contexts. While LLMs demonstrate strong extraction capabilities, corpus-level mining remains prohibitively expensive—processing Wikipedia with GPT-o1 exceeds $1.2 million (Appendix A.8). Task-specific models can match LLM performance at significantly lower cost (Chen and Varoquaux, 2025; Obeidat et al., 2025), making specialized approaches essential for large-scale spatio-temporal interaction extraction.

However, existing task-specific methods (Gergaud et al., 2016; Tao and Zhang, 2020) focus solely on person pairs, omitting time and location—two dimensions fundamental to understanding social dynamics (Barabâsi et al., 2002; Crandall et al., 2010) **but challenging to extract jointly**.

We formalize this new task: extracting interaction quadruplets *(Person1, Person2, Time, Location)* from unstructured text, where *Person1* and *Person2* engage in a direct interaction at *Time* in *Location*. Following prior work (Nijila and Kala, 2018; Labatut and Bost, 2019), we define an inter-

[1] https://anonymous.4open.science/r/FALCON-7EF9. Full datasets will be available upon acceptance.

Figure 1: Example of extracted quadruplets and their contexts. (a) A valid spatio-temporal interaction where scattered entities must be linked. (b) An incorrect interaction inferred from mere proximity.

action as a direct action between two individuals (e.g., marriage, collaboration, competition).

Prior work (Tang et al., 2007; Gergaud et al., 2016; Tao and Zhang, 2020) identifies interactions by classifying person pairs, but extending to quadruplets faces two challenges. **First, entity association is unreliable**: heuristic methods applying NER to detect nearby temporal and spatial entities often fail—the nearest entities may not correspond to the actual interaction. In Fig. 1(b), this incorrectly identifies (*Joseph*, *Mary*, *1970*, *New York*), whereas they met in *Washington* in *1993*. Similarly, spatio-temporal co-occurrence methods (Zhang et al., 2025) produce false positives. **Second, mentions are scattered with varying importance**: relevant entities are dispersed across text and connected through indirect mentions. In Fig. 1(a), *Niemans* is first mentioned in *The Hague*, then associated with *1950*, and finally linked to *Berg*. Accurately linking these scattered mentions requires careful aggregation, as not all mentions are equally important.

Our Approach. To address these challenges, we propose FALCON (AR-Bert model utilizing Feature Transfer and Multi-Task Learning strategies for extracting spatio-temporal Life InteraCtiONs). FALCON reframes the problem as selecting correct quadruplets from all possible NER combinations. Given candidate quadruplets (*Person1*, *Person2*, *Time*, *Location*) with their contexts, FALCON classifies them as "interaction" or "not interaction."

We decompose this into two complementary tasks: (1) a **main task** determining whether *Person1* and *Person2* interact at a given *Time* and *Location*, and (2) an **auxiliary task** defined as a "trajectory task," which verifies their spatio-temporal co-occurrence by classifying triplets (*Person*, *Time*, *Location*) as valid trajectories. The auxiliary task provides reliable spatio-temporal evidence that directly supports the main task. This multi-task learning framework encourages the model to capture spatio-temporal correlations crucial for both tasks,

while transfer learning incorporates features from the auxiliary task into interaction detection. To handle scattered mentions with varying importance, we utilize AR-Bert (Attention-enhanced R-Bert) as our feature extractor. By augmenting R-Bert (Wu and He, 2019) with an attention mechanism, it dynamically assigns higher weights to informative occurrences, overcoming uniform weighting.

We select Wikipedia biographies as our primary extraction target and construct *WikiInteraction*, a manually annotated dataset with 4,507 quadruplets. **Trained on Wikipedia, FALCON applies well to Encyclopedia Britannica and news archives.** Applied at scale, FALCON extracts **658,966 Wikipedia quadruplets** spanning over 1,000 years and **77,836 news quadruplets**.

We further introduce a post-processing step to infer interaction types (e.g., cooperation, debate, mentoring), thereby extending quadruplets into typed 5-tuples. Since interaction types are diverse and often implicit in text, type acquisition is an open-domain inference problem. We therefore use LLMs to infer interaction types from the quadruplet and its context. Unlike full-scale processing, this process is applied only to extracted quadruplets, so the additional computational cost is low.We validate its effectiveness and showcase its utility in specific analysis scenarios.

Specifically, our case study on US political polarization (1960-2024, 7,891 figures) constructs a weighted network of adversarial, cooperative, and neutral interactions. Unlike studies relying on polls (Fiorina and Abrams, 2008; Pew Research Center, 2017, 2019), social media (Conover et al., 2011; Garimella and Weber, 2017; Flamino et al., 2023), or behavioral analysis (Fos et al., 2022), our approach reveals long-term geo-temporal trends invisible in online data, uncovering escalating polarization since the 1960s, accelerating sharply under Obama and Trump. Moreover, our polarization metric is highly consistent with the DW-NOMINATE polarization index (Lewis et al., 2019), an authoritative benchmark based on U.S. congressional roll-call votes.

Our contributions include:

- We introduce the task of extracting spatio-temporal interactions from unstructured text and construct *WikiInteraction*, a manually annotated benchmark dataset.

- We propose **FALCON**, integrating multi-task learning, transfer learning, and AR-BERT.

It achieves 86.51% F1, outperforming both LLMs and specialized models, while incurring significantly lower computational costs than LLMs. Furthermore, it demonstrates superior cross-domain applicability.

- We release 658,966 Wikipedia quadruplets spanning over 1,000 years and 77,836 news quadruplets, constituting the largest spatio-temporal interaction dataset to date. For each extracted quadruplet, we provide an LLM-inferred interaction type, extending the quadruplets into 5-tuples. We also release code to facilitate future research. A 60-year political polarization case study reveals geo-temporal trends invisible in online data while being highly consistent with a classic index constructed from congressional votes.

2 Related Work

2.1 Social Media vs. Real-World Interactions

Social media data has been widely used to study political polarization (Conover et al., 2011), scientific collaboration (Romero et al., 2011), and cultural diffusion (Centola, 2010). However, such data often suffers from limited temporal coverage (Tufekci, 2014), noise from bots and disinformation (Allcott and Gentzkow, 2017; Cinus et al., 2025), and representational bias (Lutz and Hoffmann, 2017). By contrast, real-world interaction data derived from historical archives can reveal authentic interpersonal dynamics over much longer periods, as shown in studies of Florentine families (Padgett and Ansell, 1993) and Broadway collaborations (Uzzi and Spiro, 2005). Yet these studies are usually limited to small, domain-specific settings. Our work addresses this gap by constructing large-scale real-world interaction data with explicit spatio-temporal information, supporting broader research on network evolution (Barabâsi et al., 2002) and geographic dynamics (Onnela et al., 2011).

2.2 Interaction Extraction from Text

Interaction extraction has developed from early rule-based methods (Backstrom et al., 2006; Tang et al., 2007) to neural approaches. Early studies relied on named entity recognition with co-occurrence rules (Gergaud et al., 2016) or trigger word detection (Agarwal, 2016), while later work used deep models such as CNNs (Nijila and Kala, 2018) and Bi-LSTMs (Tao and Zhang, 2020) to better capture semantic context. More recently,

large language models have shown strong potential for information extraction (Xu et al., 2024), but their use for corpus-level mining remains expensive. Moreover, existing methods mainly focus on whether an interaction occurs, while overlooking its temporal and spatial attributes. We address this limitation by proposing a new task of extracting spatio-temporal interaction quadruplets and a specialized framework based on multi-task learning and attention mechanisms.

3 Formulation of Task and Annotation

We formulate the task as determining whether two individuals interact at a specified time and location within a given text segment. For each candidate quadruple $(Person1, Person2, Time, Location)$ extracted from a paragraph, the model predicts whether a valid interaction exists, where interaction requires both co-occurrence and a meaningful connection, such as dialogue or collaboration.

We initialize extraction with a trajectory mining pipeline adapted from (Zhang et al., 2024), which uses NER and dependency parsing to extract spatio-temporal triplets and align them by strict co-occurrence, producing 4,226,049 candidate interaction quadruples from English Wikipedia. We then manually annotate 4,507 quadruples using a three-person protocol (two annotators and one checker).[2] For auxiliary supervision, each quadruple is decomposed into two trajectory triples, yielding 9,014 trajectory instances. Label statistics are shown in Table 1. (See details in appendix A.1)

Type	Positive	Negative	Total
Interaction	2,351	2,156	4,507
Trajectory	5,730	3,284	9,014

Table 1: Distribution of the $WikiInteraction$ Dataset.

4 Method

Our FALCON framework (Fig. 2) processes candidate interactions comprising a text segment s and a quadruple q. First, q is decomposed into two trajectory triplets (t_1, t_2). The quadruple q drives the main **Interaction Classification** task, while the triplets t_1 and t_2 drive the auxiliary **Trajectory Classification** task.

We employ a trainable AR-BERT model as the primary feature extractor for both tasks, yielding

---

[2]The inter-annotator agreement (Cohen's Kappa) is 0.73, indicating substantial agreement (Landis and Koch, 1977); disagreements are resolved by the checker.

Figure 2: The framework of FALCON. The candidate interaction is decomposed into trajectory. The main task handles interaction classification, while the auxiliary task handles trajectory classification via multi-task learning.

interaction features H'_{inter} and trajectory features H'_{tra}. Simultaneously, a *frozen* AR-BERT model, pre-trained solely on trajectory data, extracts trajectory features H_{tra}. Transfer learning is incorporated by fusing H'_{inter} and H_{tra} into H'_{fusion} for the final interaction prediction. The model is jointly trained using multi-task learning.

Beyond FALCON, we further introduce a post-processing stage to infer interaction types for downstream analysis.

4.1 AR-BERT

The architecture of AR-BERT, designed to enhance BERT's understanding of entities in a given text.

Input and Special Markers. Given an input text segment s and a set of entities $E = \{e_1, e_2, \ldots, e_n\}$, we insert special tokens to enhance entity capture. Specifically, we use '#' for *Person1*, '\$' for *Person2*, '*' for *Time*, and '&' for *Location*. The modified sentence is fed into BERT, where the final hidden state of the [CLS] token serves as the global representation.

Entity Information Representation. We employ a multi-step process to represent entities. First, we obtain the vector for the k-th occurrence of entity e_i via mean pooling:

$$H_i^k = \frac{1}{d - c + 1} \sum_{t=c}^{d} \mathbf{H}_t, \qquad (1)$$

where c and d denote the start and end positions of the entity. Next, an attention mechanism fuses these occurrences. The importance weight w_i^k and normalized score δ_i^k are computed as:

$$w_i^k = \tanh\left(\boldsymbol{W}_{attn} H_i^k + \boldsymbol{b}_{attn} \right), \qquad (2)$$

$$\delta_i^k = \frac{\exp(w_i^k)}{\sum_{u=1}^{v} \exp(w_i^u)}. \qquad (3)$$

The final entity embedding is the weighted sum:

$$H_i = \sum_{k=1}^{v} \delta_i^k H_i^k. \qquad (4)$$

Feature Concatenation. Each entity embedding H_{e_i} and the global sentence representation $\mathbf{H}_0$ (the hidden state of the [CLS] token) pass through a fully connected layer with activation:

$$H'_{e_i} = \mathbf{W}_i \left(\tanh(H_{e_i}) \right) + \mathbf{b}_i, \qquad (5)$$

$$H'_0 = \mathbf{W}_0 \left(\tanh(\mathbf{H}_0) \right) + \mathbf{b}_0. \qquad (6)$$

Concatenate them to form the output feature:

$$\begin{aligned} H' &= \mathbf{AR\_BERT}(s, E) \\ &= \text{concat}\left(H'_0, H'_{e_1}, \ldots, H'_{e_n} \right), \end{aligned} \qquad (7)$$

where $H' \in \mathbb{R}^{(n+1)d}$.

4.2 Main Task: Interaction Classification

The input consists of text s_{inter} and quadruple E_q. The base interaction feature is extracted as $H'_{inter} = \mathbf{AR\_BERT}(s_{inter}, E_q) \in \mathbb{R}^{5d}$.

Feature Transfer. To leverage trajectory knowledge, we utilize a frozen trajectory extractor f_{tra}, which is built upon the AR-BERT architecture yet pre-trained on a separate trajectory dataset (Zhang et al., 2025). Crucially, we decompose the interaction quadruple $E_q = (\text{Person}_1, \text{Person}_2, \text{Time}, \text{Location})$ into two constituent trajectory triplets: $E_{t_1} = (\text{Person}_1, \text{Time}, \text{Location})$ and $E_{t_2} = (\text{Person}_2, \text{Time}, \text{Location})$. These triplets are individually fed into the extractor to obtain independent trajectory features $H_{tra_i}^t = f_{tra}(s_{inter}, E_{t_i}) \in \mathbb{R}^d$ for $i \in \{1, 2\}$, which capture the spatio-temporal validity of each participant.

We integrate these features using a **Gating Mechanism** followed by **Cross-Attention**. The gating filters the trajectory information:

$$\mathbf{gate}_{\text{tra}_i} = \sigma \left(\mathbf{W}_{\text{gate}} H^t_{\text{tra}_i} \right), \qquad (8)$$

$$H^g_{\text{tra}_i} = \mathbf{gate}_{\text{tra}_i} \odot H^t_{\text{tra}_i}, \qquad (9)$$

where $\mathbf{W}_{\text{gate}} \in \mathbb{R}^{d \times d}$. Subsequently, cross-attention is applied using H'_{inter} as the query source:

$$Q = \mathbf{W}_Q H'_{\text{inter}}, \qquad (10)$$

$$H^a_{\text{tra}_i} = \sigma \left(\frac{Q (H^g_{\text{tra}_i})^\top}{\sqrt{d}} \right) H^g_{\text{tra}_i}, \qquad (11)$$

where $\mathbf{W}_Q \in \mathbb{R}^{d \times 5d}$. The final fused feature H'_{fusion} is obtained by concatenating the interaction feature with the attended trajectory features:

$$H'_{fusion} = \text{concat}\left(H'_{\text{inter}}, H^a_{\text{tra}_1}, H^a_{\text{tra}_2} \right). \qquad (12)$$

Loss Function. The prediction is $\hat{y}_{inter} = \text{Softmax}(W_{inter} H'_{\text{fusion}})$. We use the cross-entropy loss:

$$
\begin{aligned}
\mathcal{L}_{\text{inter}} = - \sum_{j=1}^{J} \Big[& y^j_{inter} \log(\hat{y}^j_{inter}) \\
& + (1 - y^j_{inter}) \log(1 - \hat{y}^j_{inter}) \Big].
\end{aligned}
$$
$$(13)$$

4.3 Auxiliary Task: Trajectory Classification

The interaction data provides two auxiliary trajectory samples per instance. Features are extracted via AR-BERT as $H'_{tra_i} = \mathbf{AR\_BERT}(t_{tra_i}, E_{t_i})$. The prediction is $\hat{y}_{tra_i} = \text{Softmax}(W_{tra} H'_{\text{tra}_i})$. The auxiliary loss is the average of the two trajectory losses:

$$
\begin{aligned}
\mathcal{L}_{\text{tra}_i} = - \sum_{j=1}^{J} \Big[& y^j_{tra_i} \log(\hat{y}^j_{tra_i}) \\
& + (1 - y^j_{tra_i}) \log(1 - \hat{y}^j_{tra_i}) \Big], \quad (14)
\end{aligned}
$$

$$\mathcal{L}_{\text{tra}} = \frac{1}{2}(\mathcal{L}_{\text{tra}_1} + \mathcal{L}_{\text{tra}_2}). \qquad (15)$$

4.4 Multi-Task Learning

We jointly train the model using adaptive weighting (Liebel and Körner, 2018) to balance the tasks:

$$
\begin{aligned}
\mathcal{L} = \frac{1}{2c_1^2} \mathcal{L}_{\text{inter}} + \frac{1}{2c_2^2} \mathcal{L}_{\text{tra}} \\
+ \log \left(1 + c_1^2 \right) + \log \left(1 + c_2^2 \right), \qquad (16)
\end{aligned}
$$

where c_1 and c_2 are learnable parameters initialized to 1.

4.5 Post-processing for Type Inference

Interaction type is important for downstream analysis, but it is often implicit in text: in our sampled analysis, only 11.4% of contexts explicitly mention it. Moreover, interaction types are diverse (e.g., cooperation, mentorship, and investment), and different downstream tasks may require different schemas. Therefore, type inference is an open-domain inference problem. We thus adopt an LLM-based post-processing solution. Given a quadruplet q, its text segment s, and a task-defined schema $\mathcal{S}$ (e.g., the three-way schema used in §6.1.1), the interaction type is inferred as:

$$class = \text{LLM}(s, q, \mathcal{S}), \quad class \in \mathcal{S}. \qquad (17)$$

5 Experiments

5.1 Train/Test Split

For data partitioning, we isolate by "biography pages" and split the primary *WikiInteraction* dataset into training, validation, and test sets with a 7:1:2 ratio. This ensures that all information about any individual appears in only one subset, strictly preventing data leakage. **To evaluate cross-domain generalization, we additionally annotate 500 samples from Encyclopedia Britannica[3] and 500 from news archives[4].**

5.2 Evaluation Metrics

To quantitatively evaluate our model, we assess its classification performance on the interaction task by computing Accuracy (Acc), Precision (P), Recall (R), and F1-score (F1).

5.3 Baseline Methods

To evaluate the effectiveness of FALCON, we compare it against a diverse set of baselines, categorized into Small Language Models (SLMs) and LLMs. For SLMs, we employ **BERT** (Devlin, 2018) as a standard pretraining baseline and **RoBERTa** (Liu, 2019), which optimizes representation learning via dynamic masking and removing the NSP objective. We also include **R-Bert** (Wu and He, 2019), which enhances entity context by explicitly marking target entities and integrating their position-aware representations. Additionally, we adapt **COSMOS** (Zhang et al., 2025), a trajectory-focused model that does not explicitly model entity

---

[3] https://www.britannica.com/
[4] https://huggingface.co/datasets/rjac/all-the-news-2-1-Component-one

Type	Methods	Wiki (In-Domain)				Britannica (Out-of-Domain)				News (Out-of-Domain)			
		Acc	P	R	F1	Acc	P	R	F1	Acc	P	R	F1
LLMs	GPT-4o-mini (zero-shot)	74.17	72.69	80.60	76.44	73.85	72.10	80.15	75.91	73.12	71.88	79.40	75.45
	GPT-4o-mini (few-shot)	79.15	76.12	85.47	80.53	75.88	71.93	82.97	77.06	75.05	71.40	82.38	76.50
	GPT-o1 (zero-shot)	79.95	77.09	84.53	80.64	79.82	76.55	84.10	80.15	79.45	76.12	83.85	79.81
	GPT-o1 (few-shot)	83.50	79.13	**91.76**	84.98	81.05	75.68	**87.96**	_81.37_	80.60	75.60	_85.72_	80.34
	Claude 4 Sonnet (zero-shot)	80.42	77.15	86.35	81.49	79.15	75.30	84.20	79.50	78.80	75.10	83.90	79.26
	Claude 4 Sonnet (few-shot)	_83.95_	80.12	_90.78_	_85.12_	_80.50_	76.20	_87.05_	81.26	79.85	75.56	**85.95**	_80.42_
SLMs	BERT	76.61	73.33	84.43	78.49	73.02	70.88	79.36	74.88	72.45	70.21	78.64	74.18
	RoBERTa	80.16	74.87	89.55	81.55	75.18	69.75	83.42	75.97	74.62	69.12	82.51	75.22
	COSMOS	81.93	_81.01_	85.73	83.30	78.21	_78.02_	79.14	78.58	77.61	_77.10_	78.55	77.82
	R-Bert	82.37	79.69	88.70	84.01	78.47	76.95	82.01	79.40	77.98	76.30	81.69	78.90
	FALCON (ours)	**85.48**	**83.67**	89.55	**86.51**	**82.54**	**82.33**	83.19	**82.76**	**80.78**	**80.58**	81.67	**81.12**

Table 2: Models are trained on Wiki and evaluated on Wiki, Britannica, and News (Acc, P, R, and F1 in %). Results are averaged over 5 independent runs. The methods are categorized into LLMs and SLMs.

relationships, by retraining it specifically for the interaction quadruple extraction task. Regarding LLMs, we assess a range of representative models: the **GPT-4o-mini** to evaluate generative reasoning, the more advanced **GPT-o1**, as well as **Claude 4 Sonnet**. We evaluate these models under both zero-shot (utilizing CoT) and Few-shot settings. For the Few-shot setting, we employ a RAG approach to retrieve five relevant demonstrations from the *Wiki-Interaction* training set (prompt in Appendix A.6). **For SLMs, results are averaged over five runs with different random seeds, with standard errors reported in Appendix A.2. For LLMs, the temperature is set to 0.**

5.4 Experimental Results

Table 2 presents the evaluation results across three datasets. FALCON consistently achieves the highest F1 scores: 86.51% on Wiki, 82.76% on Britannica, and 81.12% on News, outperforming all baselines in both in-domain and out-of-domain settings. Overall, Claude 4 Sonnet (few-shot) ranks second, followed by R-BERT.

Comparison with LLMs. FALCON demonstrates consistent improvements over state-of-the-art LLMs, with gains of 1.39-1.53% on Wiki and 0.70-1.39% on out-of-domain datasets. The advantage primarily comes from higher precision (83.67% vs. 79-80%), with FALCON achieving 3-4% better precision while trading off only 1-2% in recall compared to LLMs. Beyond performance, using LLMs for large-scale extraction is prohibitively expensive. For instance, processing all Wikipedia biographies with GPT-o1 costs over $1.2 million, while our candidate classification approach still incurs approximately $157k (details in Appendix A.8). In contrast, FALCON achieves this with negligible GPU costs.

Comparison with small models. FALCON shows larger improvements over small models, outperforming R-BERT by 2.50% on Wiki, 3.36% on Britannica, and 2.22% on News. Despite sharing the same BERT base, this significant margin indicates the contribution of the proposed components.

5.5 Ablation Study

We conduct an ablation study on the *WikiInteraction* benchmark to evaluate the effectiveness of key components, as shown in Table 3. Specifically, $FALCON_{w/o\ ft}$ excludes the feature transfer module, $FALCON_{w/o\ mt}$ omits the multi-task learning strategy, and $FALCON_{w/o\ ft\&mt}$ removes both components. Consistent with our expectations, FALCON achieves the best performance, while $FALCON_{w/o\ ft\&mt}$ exhibits the worst performance, underscoring the effectiveness of each component. Notably, $FALCON_{w/o\ mt}$ achieves the highest Recall. This suggests that the multi-task learning mechanism enforces stricter spatio-temporal verification; while this causes a slight reduction in Recall, it yields a substantial gain in Precision, resulting in superior overall performance.

Additionally, we conduct detailed ablations on the design of multi-task learning and feature transfer in Appendix A.5.

Methods	Acc (%)	P (%)	R (%)	F1 (%)
$FALCON_{w/o\ ft\&mt}$	83.70	82.33	87.42	84.80
$FALCON_{w/o\ mt}$	83.81	80.76	**90.40**	85.31
$FALCON_{w/o\ ft}$	84.70	82.26	89.98	85.94
$FALCON$	**85.48**	**83.67**	89.55	**86.51**

Table 3: Results of the ablation study.

5.6 Validation of Interaction Type Inference

Since interaction type inference is an open-domain problem, exhaustive evaluation is difficult. Our

evaluation considers errors from the previous extraction stage, and we conduct both small-scale manual validation and large-scale LLM-based validation. First, we conduct a fine-grained validation in our political scenario (see § 6.1.1), where manual verification yields an accuracy of 93.50%. Second, we perform a cross-validation using an LLM-as-a-judge protocol, where two independent judge models report accuracies of 89.27% and 89.75%, respectively; details are provided in Appendix A.9. Both evaluations support the effectiveness of this strategy. Based on this design, users can flexibly define task-specific schemas, and we also provide LLM-inferred open-ended interaction types for quadruplets.

6 Analysis of Extracted Interactions

We extract **658,966** spatio-temporal interaction quadruples from **4,226,049** candidates generated from English Wikipedia, and further infer their interaction types using GPT-4o-mini, thereby extending them into typed 5-tuplets. Manual evaluation of 300 extracted samples showed an accuracy of 82% (246 quadruplets). Conversely, inspection of 100 samples labeled as negative by FALCON confirmed that 93% were indeed incorrect, aligning with the model's test set performance. To further assess the objectivity of the manual evaluations reported in this section, including those below, we additionally perform an independent LLM-based cross-validation, which yields high agreement with the manual evaluations; see Appendix A.3.

To ensure data uniqueness and spatial precision for downstream analysis, we apply post-processing procedures described in Appendix A.7. **This yields a refined dataset of 293,586 distinct quadruples, in which each individual is linked to a separate Wikipedia page.** The dataset spans 1000–2024[5], and contains 291,136 unique individuals and 49,579 locations.

In Appendix A.13, we present the complete dataset from the perspectives of geography and spatio-temporal networks. In the following section, we demonstrate the data's utility by analyzing interactions among US political figures, offering a new perspective on political polarization. Additionally, we extracted 77,836 raw interaction quadruples from news data (see Appendix A.14 for details).

---

[5]Wikipedia dump: January 11, 2025 (https://dumps.wikimedia.org/).

6.1 Case Study: Long-term Analysis of US Political Polarization

6.1.1 Data Source and Classification

Data Source. We focus on the real-world interactions of US political figures extracted from Wikipedia to examine political polarization. Utilizing our extracted data, we identify 14,084 interactions among 3,896 Republicans and 3,995 Democrats (1960–2024). These interactions are categorized as intra-party, where individuals belong to the same party, or inter-party, where they come from different parties.

Interaction Type Inference and Validation. For the political polarization case study, we instantiate the post-processing method in Section 4.5 with a **task-specific three-way schema:** *Adversarial* (conflicting interests, e.g., debates), *Cooperative* (joint actions, e.g., legislation), and *Neutral* (symbolic events, e.g., ceremonies). We use GPT-4o-mini to infer the type for each extracted quadruplet. While *Adversarial* and *Cooperative* align with established political frameworks (Bassan-Nygate and Weiss, 2022; Bendix and MacKay, 2017), *Neutral* captures additional interactions beyond these categories. Table 4 reports the resulting distribution.

To validate the reliability of this schema-based classification, we manually verify 200 randomly sampled cases and obtain an accuracy of 93.50%. We further conduct independent cross-validation with Gemini-3-pro and GPT-5, which yield accuracies of 92.50% and 91.00%, respectively, with a human–LLM agreement of 92.50%. Details of the prompts and validation protocols are provided in Appendix A.10 and Appendix A.3.

Type	Intra-party	Inter-party
Cooperative	5,182	1,670
Adversarial	1,634	2,317
Neutral	1,468	1,812

Table 4: Detailed statistics of interaction types.

6.1.2 Rising Adversarial Interactions

In terms of inter-party dynamics, we observe that the proportion of inter-party interactions has dropped significantly from 47% (1960s) to 24% (2020s). Notably, within this reduced volume, *Adversarial* interactions have surged from 32.8% to 66.7% (Fig.3), while *Cooperative* and *Neutral* types have declined. This trend aligns with observations of growing polarization in the US (Fiorina and Abrams, 2008).

Figure 3: Evolution of inter-party interaction types.

Figure 4: US political interaction network (1960-2024). Edges are weighted: Neutral (+1), Cooperative (+2), Adversarial (-2).

Figure 5: (a) National polarization trend; (b) State-level trends.

6.1.3 Network-Based Polarization and Regional Divergence

To further capture the complexity of political interactions, we examine polarization by constructing interaction networks, referencing the classic study on political polarization (Conover et al., 2011).

In our network, each node represents a political figure, and edges denote interactions. Adopting the *Weighted Signed Networks* (WSN) (Kumar et al., 2016), we assign signed weights to edges to reflect the nature of the interactions (refer to the Appendix A.11 for specific weight assignments). Figure 4 visualizes the cumulative network spanning 1960–2024 using the ForceAtlas2 algorithm. In this visualization, nodes are color-coded by political party, with red representing Republicans and blue representing Democrats, clearly revealing distinct partisan clusters.

To quantify polarization over time, we compute *standardized modularity* (details in Appendix A.11). Longitudinal results (Figure 5a) confirm a continuous rise in national polarization, with the sharpest acceleration occurring during the Obama and Trump administrations. These findings align with poll-based conclusions that partisan divisions have reached record levels during these periods (Doherty et al., 2017). However, regional trends vary significantly (Figure 5b). Massachusetts shows consistent growth to lead in 2024, while California presents a unique case with recent declines. Most strikingly, Washington D.C. demonstrates the steepest increase among major political centers, rising from the lowest initial polarization to the second highest.

To further validate our analysis, we correlate standardized modularity with the DW-NOMINATE polarization index derived from historical U.S. congressional roll-call votes, whose first dimension captures legislators' positions on the liberal–conservative spectrum; we use the inter-party mean gap on this dimension as an indicator of ideological distance (Lewis et al., 2019). We find a highly significant positive correlation ($r = 0.969$, $p < 0.001$), showing that the polarization patterns revealed by our data are highly consistent with established political science benchmarks and that our metric effectively captures macro-level political polarization trends (see Appendix A.12 for details).

7 Conclusion

We propose a new task of extracting spatio-temporal interactions from unstructured text and introduce FALCON. By integrating AR-Bert, feature transfer, and multi-task learning, FALCON provides an efficient and effective solution for large-scale extraction of human spatio-temporal interactions. Although trained on Wikipedia, FALCON demonstrates broad cross-domain applicability, extending effectively to Encyclopedia Britannica and News datasets. To validate the method and showcase the potential of the extracted data, we analyze US political interactions, offering a new perspective on political polarization. We hope that the open-source code, the extracted interactions, and the *WikiInteraction* ground-truth dataset can support future research on spatio-temporal interaction extraction and downstream analytical studies. As the largest dataset of its kind, our resource can serve as a basis for data-driven historical narratives and the study of human interaction mechanisms.

Limitations

Despite the effectiveness of FALCON in extracting spatio-temporal interactions, several limitations remain:

- **Dependency on External LLMs:** While FALCON extracts interactions efficiently, the subsequent classification of interaction types relies on GPT-4o-mini. This introduces a dependency on external APIs, which future work aims to address with a dedicated end-to-end architecture.

- **Source Bias:** Our reliance on English Wikipedia inherits its inherent Western-centric biases. Consequently, the extracted networks potentially underrepresent figures from non-English speaking regions or marginalized communities.

- **Language Specificity:** The model is trained and evaluated solely on English corpora. Although the architecture is language-agnostic, its generalization to other languages remains untested.

Ethics Statement

Our study uses the English Wikipedia and public news archives, and we ensure that our data collection process does not violate any privacy or confidentiality concerns. A potential ethical concern is the misuse to extract spatio-temporal interactions of individual users (non-famous people). However, since our framework relies on detailed textual descriptions of public events, the risk arises from the availability of personal information in such descriptions, rather than the framework itself. Therefore, we believe that there are no essential ethical questions raised by our study.

References

Apoorv Agarwal. 2016. Social Network Extraction from Text. Ph.D. thesis, Columbia University.

Hunt Allcott and Matthew Gentzkow. 2017. Social media and fake news in the 2016 election. Journal of economic perspectives, 31(2):211–236.

Lars Backstrom, Daniel P. Huttenlocher, Jon M. Kleinberg, and Xiangyang Lan. 2006. Group formation in large social networks: membership, growth, and evolution. In Knowledge Discovery and Data Mining.

Albert-Laszlo Barabâsi, Hawoong Jeong, Zoltan Néda, Erzsebet Ravasz, Andras Schubert, and Tamas Vicsek. 2002. Evolution of the social network of scientific collaborations. Physica A: Statistical mechanics and its applications, 311(3-4):590–614.

Lotem Bassan-Nygate and Chagai M Weiss. 2022. Party competition and cooperation shape affective polarization: Evidence from natural and survey experiments in israel. Comparative Political Studies, 55(2):287–318.

William Bendix and Jon MacKay. 2017. Partisan infighting among house republicans: leaders, factions, and networks of interests. Legislative Studies Quarterly, 42(4):549–577.

Katy Börner, Jeegar T Maru, and Robert L Goldstone. 2004. The simultaneous evolution of author and paper networks. Proceedings of the National Academy of Sciences, 101(suppl_1):5266–5273.

Damon Centola. 2010. The spread of behavior in an online social network experiment. science, 329(5996):1194–1197.

Lihu Chen and Gaël Varoquaux. 2025. What is the role of small models in the llm era: A survey. Preprint, arXiv:2409.06857.

Federico Cinus, Marco Minici, Luca Luceri, and Emilio Ferrara. 2025. Exposing cross-platform coordinated inauthentic activity in the run-up to the 2024 us election. In Proceedings of the ACM on Web Conference 2025, pages 541–559.

Michael Conover, Jacob Ratkiewicz, Matthew Francisco, Bruno Gonçalves, Filippo Menczer, and Alessandro Flammini. 2011. Political polarization on twitter. In Proceedings of the international aaai conference on web and social media, volume 5, pages 89–96.

David J Crandall, Lars Backstrom, Dan Cosley, Siddharth Suri, Daniel Huttenlocher, and Jon Kleinberg. 2010. Inferring social ties from geographic coincidences. Proceedings of the National Academy of Sciences, 107(52):22436–22441.

Ashok Deb, Luca Luceri, Adam Badaway, and Emilio Ferrara. 2019. Perils and challenges of social media and election manipulation analysis: The 2018 us midterms. In Companion proceedings of the 2019 world wide web conference, pages 237–247.

Jacob Devlin. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805.

Carroll Doherty, Jocelyn Kiley, and Bridget Johnson. 2017. The partisan divide on political values grows even wider. Pew Research Center, 5.

Tim Donkers and Jürgen Ziegler. 2025. Understanding online polarization through human-agent interaction in a synthetic llm-based social network. In

Proceedings of the International AAAI Conference on Web and Social Media, volume 19, pages 457–478.

Morris P Fiorina and Samuel J Abrams. 2008. Political polarization in the american public. Annu. Rev. Polit. Sci., 11(1):563–588.

James Flamino, Alessandro Galeazzi, Stuart Feldman, Michael W Macy, Brendan Cross, Zhenkun Zhou, Matteo Serafino, Alexandre Bovet, Hernán A Makse, and Boleslaw K Szymanski. 2023. Political polarization of news media and influencers on twitter in the 2016 and 2020 us presidential elections. Nature Human Behaviour, 7(6):904–916.

Santo Fortunato, Carl T Bergstrom, Katy Börner, James A Evans, Dirk Helbing, Staša Milojević, Alexander M Petersen, Filippo Radicchi, Roberta Sinatra, Brian Uzzi, and 1 others. 2018. Science of science. Science, 359(6379):eaao0185.

Vyacheslav Fos, Elisabeth Kempf, and Margarita Tsoutsoura. 2022. The political polarization of corporate america. Technical report, National Bureau of Economic Research.

Venkata Rama Kiran Garimella and Ingmar Weber. 2017. A long-term analysis of polarization on twitter. In Proceedings of the International AAAI Conference on Web and social media, volume 11, pages 528–531.

Olivier Gergaud, Morgane Laouenan, and Etienne Wasmer. 2016. A brief history of human time. exploring a database of "notable people"'. LIEPP Working Paper, (46).

Chien-leng Hsu and Han Woo Park. 2012. Mapping online social networks of korean politicians. Government information quarterly, 29(2):169–181.

Johannes Illenberger, Kai Nagel, and Gunnar Flötteröd. 2013. The role of spatial interaction in social networks. Networks and Spatial Economics, 13:255–282.

Matthew O Jackson. 2011. An overview of social networks and economic applications. Handbook of social economics, 1:511–585.

Emily Kubin and Christian Von Sikorski. 2021. The role of (social) media in political polarization: a systematic review. Annals of the International Communication Association, 45(3):188–206.

Srijan Kumar, Francesca Spezzano, VS Subrahmanian, and Christos Faloutsos. 2016. Edge weight prediction in weighted signed networks. In 2016 IEEE 16th international conference on data mining (ICDM), pages 221–230. IEEE.

Vincent Labatut and Xavier Bost. 2019. Extraction and analysis of fictional character networks: A survey. ACM Computing Surveys (CSUR), 52(5):1–40.

J Richard Landis and Gary G Koch. 1977. The measurement of observer agreement for categorical data. biometrics, pages 159–174.

Jeffrey B Lewis, Keith Poole, Howard Rosenthal, Adam Boche, Aaron Rudkin, and Luke Sonnet. 2019. Voteview: Congressional roll-call votes database. See https://voteview. com/(accessed 27 July 2018).

Lukas Liebel and Marco Körner. 2018. Auxiliary tasks in multi-task learning. arXiv preprint arXiv:1805.06334.

Yinhan Liu. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692, 364.

Christoph Lutz and Christian Pieter Hoffmann. 2017. The dark side of online participation: exploring non-, passive and negative participation. Information, Communication & Society, 20(6):876–897.

Cedric Möller, Jens Lehmann, and Ricardo Usbeck. 2022. Survey on english entity linking on wikidata: Datasets and approaches. Semantic Web, 13(6):925–966.

Mark EJ Newman. 2001. Scientific collaboration networks. i. network construction and fundamental results. Physical review E, 64(1):016131.

M Nijila and M T Kala. 2018. Extraction of relationship between characters in narrative summaries. In 2018 International Conference on Emerging Trends and Innovations In Engineering And Technological Research (ICETIETR), pages 1–5.

Leonardo Nizzoli, Serena Tardelli, Marco Avvenuti, Stefano Cresci, and Maurizio Tesconi. 2021. Coordinated behavior on social media in 2019 uk general election. In Proceedings of the international AAAI conference on web and social media, volume 15, pages 443–454.

Motasem S Obeidat, Md Sultan Al Nahian, and Ramakanth Kavuluru. 2025. Do llms surpass encoders for biomedical ner? In 2025 IEEE 13th International Conference on Healthcare Informatics (ICHI), pages 352–358.

Lindsay O'Neill. 2014. The opened letter: Networking in the Early modern British world. University of Pennsylvania Press.

Jukka-Pekka Onnela, Samuel Arbesman, Marta C González, Albert-László Barabási, and Nicholas A Christakis. 2011. Geographic constraints on social network groups. PLoS one, 6(4):e16939.

John F Padgett and Christopher K Ansell. 1993. Robust action and the rise of the medici, 1400-1434. American journal of sociology, 98(6):1259–1319.

Pew Research Center. 2017. The partisan divide on political values grows even wider. Trust, facts and democracy.

Pew Research Center. 2019. Partisan antipathy: More intense, more personal. Pew Research Center.

Thomas Plotkowiak and Katarina Stanoevska-Slabeva. 2013. German politicians and their twitter networks in the bundestag election 2009. First Monday.

Neeti Pokhriyal, Benjamin A Valentino, and Soroush Vosoughi. 2023. Quantifying participation biases on social media. EPJ Data Science, 12(1):26.

Daniel M Romero, Wojciech Galuba, Sitaram Asur, and Bernardo A Huberman. 2011. Influence and passivity in social media. In Proceedings of the 20th international conference companion on World wide web, pages 113–114.

Yizhou Sun, Rick Barber, Manish Gupta, Charu C Aggarwal, and Jiawei Han. 2011. Co-author relationship prediction in heterogeneous bibliographic networks. In 2011 International Conference on Advances in Social Networks Analysis and Mining, pages 121–128. IEEE.

Jie Tang, Duo Zhang, and Limin Yao. 2007. Social network extraction of academic researchers. In Seventh IEEE International Conference on Data Mining (ICDM 2007), pages 292–301. IEEE.

Lu Tao and Shunxiang Zhang. 2020. Character relationship extraction method based on bilstm. In International Conference on Applications and Techniques in Cyber Intelligence ATCI 2019: Applications and Techniques in Cyber Intelligence 7, pages 1432–1441. Springer.

Zeynep Tufekci. 2014. Big questions for social media big data: Representativeness, validity and other methodological pitfalls. In Proceedings of the international AAAI conference on web and social media, volume 8, pages 505–514.

Brian Uzzi and Jarrett Spiro. 2005. Collaboration and creativity: The small world problem. American journal of sociology, 111(2):447–504.

Sander Van der Linden, Costas Panagopoulos, and Jon Roozenbeek. 2020. You are fake news: political bias in perceptions of fake news. Media, culture & society, 42(3):460–470.

Shanchan Wu and Yifan He. 2019. Enriching pre-trained language model with entity information for relation classification. In Proceedings of the 28th ACM international conference on information and knowledge management, pages 2361–2364.

Derong Xu, Wei Chen, Wenjun Peng, Chao Zhang, Tong Xu, Xiangyu Zhao, Xian Wu, Yefeng Zheng, Yang Wang, and Enhong Chen. 2024. Large language models for generative information extraction: A survey. Frontiers of Computer Science, 18(6):186357.

Ying Zhang, Xiaofeng Li, Zhaoyang Liu, and Haipeng Zhang. 2024. Paths of a million people: Extracting life trajectories from wikipedia. arXiv preprint arXiv:2406.00032.

Ying Zhang, Xiaofeng Li, Zhaoyang Liu, and Haipeng Zhang. 2025. Paths of a million people: Extracting life trajectories from wikipedia. In Proceedings of the International AAAI Conference on Web and Social Media, volume 19, pages 2226–2240.

A Appendix

A.1 Acquisition of Training Data

Since there is no existing dataset that directly captures the focus of our study, namely spatio-temporal interactions, we construct a new ground-truth dataset. This section details the process of creating the $WikiInteraction$ dataset.

The dataset is derived from the biography sections of English Wikipedia. We obtain the list of individuals and the links to their corresponding Wikipedia biography pages through Wikidata (Möller et al., 2022).

This section describes the methodology used to extract and label potential quadruples in the form of (*Person1*, *Person2*, *Time*, *Location*) from biography pages.

A.1.1 Extracting Quadruples

Building upon an existing pipeline that extracts trajectory triplets from text based on the combination of NER and syntax trees (Zhang et al., 2025), we construct candidate interaction quadruples (*Person1*, *Person2*, *Time*, *Location*) by pairing trajectory triplets that co-occur, i.e., two triplets sharing the same time and location.

To evaluate the coverage of this candidate generation stage, we compare the interactions mentioned in the original biography pages with those extracted from the corresponding target text segments. Specifically, we manually review 12 biography pages containing a total of 103 interaction descriptions. Our extraction pipeline is able to capture at least 94.00% of the interactions across these pages. The missed cases are typically those in which the interaction must be inferred from multiple distant text segments, making them difficult to identify even for human annotators.

To further evaluate whether the recall of the NER-based candidate generation stage declines on texts describing earlier historical periods, we additionally conduct a century-stratified evaluation. Specifically, we divide the timeline from 1600 to 2024 into five historical periods: the 17th century (1600–1699), 18th century (1700–1799), 19th century (1800–1899), 20th century (1900–1999), and 21st century (2000–2024). From each period, we randomly sample 50 biography pages, yielding a total of 250 pages.

We then measure the recall of the heuristic candidate generation stage against these references. Table 5 shows that recall remains highly stable across all five historical periods under both Gemini-3-pro and GPT-5.

Historical Period	Gemini-3-pro	GPT-5
17th century (1600–1699)	92.7%	93.2%
18th century (1700–1799)	93.1%	93.8%
19th century (1800–1899)	93.4%	94.1%
20th century (1900–1999)	93.9%	94.5%
21st century (2000–2024)	93.4%	93.9%

Table 5: Recall of the heuristic candidate generation stage across different historical periods, evaluated against reference interactions annotated by two independent LLM judges.

A one-way ANOVA further shows that there is no statistically significant association between historical period and recall ($p > 0.05$). This suggests that the candidate generation stage remains robust across different time periods, despite potential concerns about NER performance on historical figures. One possible explanation is that Wikipedia biographies, even for earlier historical figures, are written in a relatively standardized modern English narrative style, which helps mitigate temporal variation in surface expression.

A.1.2 Annotating

Given that valid interactions are inherently sparse in the full candidate space, directly annotating all candidate quadruples would not only make it difficult to obtain sufficient positive examples efficiently, but would also result in a highly imbalanced dataset that may adversely affect model training. To balance the training data and improve annotation efficiency, we first use a trajectory classifier (COSMOS (Zhang et al., 2025)) to filter trajectory triplets, and then construct interaction quadruples for annotation by pairing triplets that co-occur in time and location. Following this procedure, we ultimately construct and annotate 4,507 interaction quadruples.

Furthermore, since trajectory detection serves as the auxiliary task in our multi-task learning framework, we further split each interaction quadruple (*Person1*, *Person2*, *Time*, *Location*) into two trajectory triplets (*Person*, *Time*, *Location*) for trajectory-level annotation. Our annotation process involves three undergraduate students: two annotators and one checker. The inter-annotator agreement, measured by Cohen's Kappa, is 0.73, indicating substantial agreement (Landis and Koch, 1977). Disagreements were further resolved by the checker to minimize annotation bias. In total, we annotate

4,507 interaction quadruples and 9,014 trajectory triplets. The distribution of positive and negative samples is presented in the main text.

It should be noted that, because we adopt a relatively balanced sampling strategy during annotation, the class distribution of the training data does not fully match the natural distribution in the raw candidate space. To further verify that this annotation strategy does not distort the model's output ratio in realistic deployment, we additionally randomly sampled 300 raw candidate quadruples for manual inspection. The results show that the true positive rate in the raw candidate space is approximately 16.3%, which is very close to FALCON's overall extraction ratio of 15.6% on the full dataset. This suggests that the model's positive output rate is broadly consistent with the natural distribution of valid interactions in the candidate space, indicating that our annotation strategy does not lead to substantial deviation from the real-world distribution during large-scale deployment.

A.2 Detailed SLM Results with Standard Errors

In this section, we report the detailed SLMs results of Table 2. Following the main paper, all models are trained on Wiki and evaluated on Wiki, Britannica, and News. For SLMs, we report the mean and standard error over 5 independent runs with different random seeds. The detailed results for the in-domain Wiki set are shown in Table 6, while the results for the out-of-domain Britannica and News sets are shown in Table 7 and Table 8, respectively.

A.3 Independent Validation of Manual Meta-evaluations

To further assess the objectivity of the manual meta-evaluations used in our study, we performed an independent cross-validation of these human judgments using an *LLM-as-a-judge* protocol. This validation covers the manual evaluation of extraction performance and interaction type identification accuracy reported in the main paper.

Scope of the original manual evaluations. In the main paper, manual evaluation was conducted on the following three aspects:

- **Extraction Precision:** verifying whether each extracted interaction quadruplet is correct ($N = 300$).

- **True Negative Rate (TNR):** measuring the effectiveness of negative filtering by verifying whether the samples filtered out by FALCON are indeed non-interaction cases ($N = 100$).

- **Classification Accuracy:** verifying whether the assigned interaction type is correct ($N = 200$).

Independent validation protocol. To quantify the objectivity of these manual evaluations, we asked two independent large language models, Gemini-3-pro and GPT-5, to re-evaluate all samples in the above three evaluation sets. For each sample, the judge model was asked to make the same binary decision as the human evaluator (e.g., correct/incorrect). We define **human–LLM agreement** as the proportion of cases in which the judge model makes exactly the same decision as the human evaluator.

In addition to agreement, we also computed the corresponding evaluation metrics derived from the LLM judgments and compared them with the original human-reported results.

Results. The two independent LLM judges show consistently high agreement with the original human evaluations across all three tasks. Table 9 summarizes the results. For extraction precision, human–LLM agreement reaches 91.3%, and the precision estimated from LLM judgments (81.3% for Gemini-3-pro and 82.7% for GPT-5) is very close to the original manually reported precision of 82.0%. For true negative rate, human–LLM agreement reaches 94.0%, with LLM-estimated TNR values of 92.0% and 91.0%, compared with the original result of 93.0%. For interaction type classification, human–LLM agreement reaches 92.5%, and the LLM-estimated classification accuracy (92.5% for Gemini-3-pro and 91.0% for GPT-5) is also close to the original manually reported accuracy of 93.5%.

Conclusion. These results indicate that the criteria used in our original manual evaluations are objective and reproducible to a high degree. The strong agreement between human judgments and two independent LLM judges, together with the close alignment of the resulting metrics, suggests that the reported manual evaluation results are unlikely to be artifacts of subjective bias.

Methods	Acc	P	R	F1
BERT	$76.61_{\pm.17}$	$73.33_{\pm.21}$	$84.43_{\pm.15}$	$78.49_{\pm.18}$
RoBERTa	$80.16_{\pm.15}$	$74.87_{\pm.19}$	$89.55_{\pm.13}$	$81.55_{\pm.16}$
COSMOS	$81.93_{\pm.14}$	$81.01_{\pm.18}$	$85.73_{\pm.12}$	$83.30_{\pm.15}$
R-Bert	$82.37_{\pm.14}$	$79.69_{\pm.17}$	$88.70_{\pm.12}$	$84.01_{\pm.15}$
FALCON (ours)	$85.48_{\pm.13}$	$83.67_{\pm.16}$	$89.55_{\pm.11}$	$86.51_{\pm.14}$

Table 6: Detailed SLM results on **Wiki** (in-domain). Results are reported as mean $\pm$ standard error over 5 independent runs.

Methods	Acc	P	R	F1
BERT	$73.02_{\pm.19}$	$70.88_{\pm.23}$	$79.36_{\pm.16}$	$74.88_{\pm.20}$
RoBERTa	$75.18_{\pm.17}$	$69.75_{\pm.21}$	$83.42_{\pm.14}$	$75.97_{\pm.18}$
COSMOS	$78.21_{\pm.16}$	$78.02_{\pm.20}$	$79.14_{\pm.13}$	$78.58_{\pm.17}$
R-Bert	$78.47_{\pm.16}$	$76.95_{\pm.20}$	$82.01_{\pm.13}$	$79.40_{\pm.17}$
FALCON (ours)	$82.54_{\pm.15}$	$82.33_{\pm.19}$	$83.19_{\pm.12}$	$82.76_{\pm.16}$

Table 7: Detailed SLM results on **Britannica** (out-of-domain). Results are reported as mean $\pm$ standard error over 5 independent runs.

Methods	Acc	P	R	F1
BERT	$72.45_{\pm.18}$	$70.21_{\pm.22}$	$78.64_{\pm.16}$	$74.18_{\pm.19}$
RoBERTa	$74.62_{\pm.16}$	$69.12_{\pm.20}$	$82.51_{\pm.14}$	$75.22_{\pm.17}$
COSMOS	$77.61_{\pm.15}$	$77.10_{\pm.19}$	$78.55_{\pm.13}$	$77.82_{\pm.16}$
R-Bert	$77.98_{\pm.15}$	$76.30_{\pm.19}$	$81.69_{\pm.14}$	$78.90_{\pm.18}$
FALCON (ours)	$80.78_{\pm.15}$	$80.58_{\pm.18}$	$81.67_{\pm.13}$	$81.12_{\pm.17}$

Table 8: Detailed SLM results on **News** (out-of-domain). Results are reported as mean $\pm$ standard error over 5 independent runs.

A.4 Implementation Details

In this paper, we use a BERT-base[6] model to generate word embeddings. While any suitable model can be employed as well, in FALCON , we set $d = 768$. We train FALCON using the AdamW optimizer with a learning rate configuration of $5\mathrm{e}^{-5}$. All the aforementioned experiments are conducted on two RTX 3090 GPUs.

A.5 Detailed Ablation

We conduct specific ablation studies on multi-task learning and feature transfer, as shown in Table 10. For multi-task learning, we validate the effectiveness of the adaptive task weighting strategy. Specifically, FALCON$_{\text{w/o aw}}$ denotes the model without the adaptive task weighting strategy. The results show a significant decrease in overall metrics. The adaptive weighting strategy enables the model to automatically focus on more challenging interaction tasks, thereby enhancing its performance on this task. Regarding feature transfer, we assess the effectiveness of the feature fusion module. FALCON$_{\text{concat}}$ represents the model where the feature fusion module is removed and trajectory features and interaction features are merely concatenated. We observe that compared to FALCON$_{\text{w/o ft}}$ (refer to Table 3), which does not utilize any fea-

ture transfer strategy, FALCON$_{\text{concat}}$ only achieves a marginal improvement in the F1 score. Although precision increases by 2.59%, recall decreases by 2.77%. This indicates that the concatenation strategy in our task trades recall for precision. In contrast, FALCON, which employs a feature fusion module in its feature transfer strategy, manages to robustly increase precision while only slightly sacrificing recall, thereby achieving better improvements in the overall metrics of F1 and recall.

A.6 Prompt for LLM Baseline

Figure 6 shows the prompt provided when we use LLMs. The temperature here is set to 0 and one trial is performed for each input.

Prompt:

You will be provided with a text and a quadruple of entities (*Person1*, *Person2*, *Time*, *Location*). If *Person1* and *Person2* are both present at the specified *Time* and *Location*, and there is an association between *Person1* and *Person2*, we consider that an interaction has occurred between them.

Your task is to answer ``Yes" or ``No" to indicate whether the interaction occurred. No additional explanations or responses are required.

Text Content: {*Text*}

Quadruple: {*Person1*, *Person2*, *Time*, *Location*}

Reasoning Steps:
1. Identify the presence of *Person1* at the specified *Time* and *Location*.
2. Identify the presence of *Person2* at the specified *Time* and *Location*.
3. Determine if there is a association between *Person1* and *Person2*.
4. If all the above conditions are satisfied, answer "Yes". Otherwise, answer "No".

Is the interaction present? Yes or No.

Figure 6: The zero-shot prompt for LLM Baseline.

[6]https://github.com/google-research/bert

Task	Human Result	Gemini-3-pro	GPT-5	Human–LLM Agreement
Extraction Precision	82.0%	81.3%	82.7%	91.3%
True Negative Rate (TNR)	93.0%	92.0%	91.0%	94.0%
Classification Accuracy	93.5%	92.5%	91.0%	92.5%

Table 9: Independent validation of manual meta-evaluations using two LLM judges.

Methods	Acc (%)	P (%)	R (%)	F1 (%)
$FALCON_{w/o\ aw}$	84.26	81.20	89.34	85.51
$FALCON_{concat}$	85.25	**84.85**	87.21	86.01
$FALCON$	**85.48**	83.67	**89.55**	**86.51**

Table 10: Specific ablation study.

Prompt:
You will be provided with a text and a quadruple of entities (*Person1, Person2, Time, Location*). If *Person1* and *Person2* are both present at the specified *Time* and *Location*, and there is an association between *Person1* and *Person2*, we consider that an interaction has occurred between them.
Your task is to answer "Yes" or "No" to indicate whether the interaction occurred. No additional explanations or responses are required.

Reasoning Steps:
1. Identify the presence of *Person1* at the specified *Time* and *Location*.
2. Identify the presence of *Person2* at the specified *Time* and *Location*.
3. Determine if there is an association between *Person1* and *Person2*.
4. If all the above conditions are satisfied, answer "Yes". Otherwise, answer "No".
Examples:{*Examples*}
Now, analyze the following new case:
    Text Content:{*Text*}
    Quadruple:{*Person1,Person2,Time,Location*}
Is the interaction present? Yes or No.

Figure 7: The few-shot prompt for LLM Baseline.

A.7 Data Post-Processing Protocols

To ensure the reliability of the extracted interactions, we apply different post-processing protocols depending on the corpus type.

Post-processing for Wikipedia. For Wikipedia-derived interactions, we apply the following protocols:

- **Entity Deduplication:** To address naming ambiguities and duplicate records arising from mutual references (i.e., the same interaction appearing on both participants' pages), we utilize the unique Wikipedia URL of each entity as a distinct identifier. This enables rigorous deduplication by merging entries sharing identical entity IDs, timestamps, and locations.

- **Spatial Standardization:** To mitigate location misclassification and ensure spatial resolution, we employ a geocoding service[7] to standardize location names into precise coordinates.

---

[7]https://developers.google.com/maps/documentation/geocoding

Auxiliary Processing for Entity Disambiguation in Other Corpora. To mitigate entity ambiguity in other corpora that lack the unique page identifiers provided by Wikipedia, we restore most person mentions to full names during preprocessing via coreference resolution, and full-name forms themselves can substantially reduce ambiguity caused by abbreviations, pronouns, or vague references. In the Wikipedia data, this preprocessing increases the proportion of full-name mentions to 85.41%, indicating its effectiveness for mention normalization. In addition, the quadruples extracted by FALCON contain temporal information, which provides a further auxiliary cue for downstream entity disambiguation. Based on the principle that homonymous entities with widely separated active periods are unlikely to refer to the same person, downstream analysis can further leverage temporal differences to distinguish same-name individuals, thereby mitigating entity ambiguity to some extent.

A.8 Cost Analysis of Large Language Models

Taking GPT-o1 as an example, we provide a detailed cost analysis. Our calculation involves two components: deterministic input costs based on dataset size, and estimated inference costs (reasoning + generation) derived from pilot experiments.

A.8.1 Methodology

We calculate the **Input Cost** using the standard pricing of $15.00 per 1 million input tokens. However, since the costs for reasoning and output tokens are dynamic and priced significantly higher (e.g., $60.00 per 1M tokens for GPT-o1), we estimate them through a sampling strategy:

1. We randomly sample 20 cases for each scenario and process them via the API to obtain the *Total Cost* per case.

2. For each case, we calculate the *Input Cost* based on its input token count.

3. The **Inference Cost** (covering both reasoning and output tokens) is derived by subtracting

the calculated Input Cost from the Total Cost:

$$\text{Cost}_{\text{inf}} = \text{Cost}_{\text{total}} - \text{Cost}_{\text{in}} \quad (18)$$

4. We then calculate the average Inference Cost per case and project it to the full dataset.

A.8.2 Full Corpus Extraction

This scenario corresponds to the direct processing of the entire English Wikipedia biography corpus.

- **Dataset Scope**: The corpus consists of 1,930,519 biography pages.

- **Input Cost (Calculated)**: Processing the raw text involves a total of 71,290,205,632 tokens.

$$\text{Cost}_{\text{in}} = \frac{71,290,205,632}{1,000,000} \times \$15.00 \\ \approx \$1,069,353.08 \quad (19)$$

- **Total Cost Projection**: Based on our pilot study of 20 documents:

  - *Avg. Inference Cost*: After subtracting input costs, the residual cost for reasoning and generation averages **\$0.102 per document**.
  - *Projected Inference Cost*:

  $$\text{Cost}_{\text{inf}} = 1,930,519 \times \$0.102 \approx \$196,912.94 \quad (20)$$

- **Estimated Total**: The aggregate cost rises to approximately **\$1,266,266.02**. In this scenario, due to the massive length of raw texts, input processing remains the dominant cost factor.

A.8.3 Candidate Quadruple Classification

This scenario corresponds to our experimental baseline setting, where the model classifies pre-extracted candidate quadruples using the Few-Shot strategy.

- **Workload**: The heuristic method generates 4,226,049 candidate interaction quadruplets.

- **Input Cost (Calculated)**: Including the system prompt, context, and few-shot demonstrations, the total input volume is 5,714,640,772 tokens.

$$\text{Cost}_{\text{in}} = \frac{5,714,640,772}{1,000,000} \times \$15.00 \\ \approx \$85,719.61 \quad (21)$$

- **Total Cost Projection**: Based on the pilot study of 20 candidate samples:

  - *Avg. Inference Cost*: Using the subtraction method ($\text{Cost}_{\text{total}} - \text{Cost}_{\text{in}}$), the average cost for reasoning and verification logic is **\$0.017 per candidate**.
  - *Projected Inference Cost*:

  $$\text{Cost}_{\text{inf}} = 4,226,049 \times \$0.017 \approx \$71,842.83 \quad (22)$$

- **Estimated Total**: The aggregate cost is approximately **\$157,562.44**. Although our proposed problem formulation—transforming the extraction task into a candidate classification problem—significantly reduces the token consumption compared to full corpus processing, the expense remains prohibitively high for LLMs.

A.9 Additional Experimental Validation of Interaction Type Inference

To further evaluate whether large language models can reliably perform open-domain interaction type inference over large-scale extracted data, we conducted an additional large-scale validation experiment. In this experiment, we did not predefine a label schema, but instead directly used the LLM for open-ended inference. To account for error propagation, we count cases where the quadruplet itself is incorrect as interaction type errors as well, and assess reliability from two complementary perspectives. The details are as follows:

1. **Objective.** The goal of this experiment is to examine whether an LLM can infer interaction types for spatio-temporal interaction quadruplets in an open-domain manner, without relying on a predefined label space.

2. **Experimental Setup** ($N = 10{,}000$). We randomly sampled 10,000 interaction quadruplets from the full extracted dataset. Instead of defining a closed set of interaction labels in advance, we followed the paradigm of Open Information Extraction and used GPT-4o-mini to directly generate an open-ended interaction type for each quadruplet based on its supporting context.

3. **Evaluation Protocol (LLM-as-a-judge).** To assess the quality of the generated interaction types, we adopted an LLM-as-a-judge protocol. Specifically, we used Gemini-3-pro and

GPT-5 as two independent judge models to evaluate whether the interaction type generated by GPT-4o-mini was accurate given the corresponding context and quadruplet.

4. **Results.** The two independent judge models produced highly consistent evaluation results. Gemini-3-pro reported an accuracy of 89.27%, while GPT-5 reported an accuracy of 89.75%.

5. **Conclusion.** These results suggest that LLMs can reliably infer interaction types for large-scale extracted quadruplets in an open-domain setting, without requiring a fixed predefined taxonomy. This finding supports the practicality of our decoupled design: FALCON is used to efficiently extract general spatio-temporal interaction quadruplets at scale, while LLMs are employed on demand to provide flexible semantic typing for downstream applications.

A.10 Case Study Interaction Type Inference Prompt

Figure 8 presents the specific prompt used by GPT-4o-mini to categorize political interactions into *Adversarial*, *Cooperative*, and *Neutral* types, as discussed in the case study.

Prompt:

You will be provided with a text, a quadruple of *entities (Person1, Person2, Time, Location)* and the political party information of *Person1* and *Person2*.

Please analyze the interaction between *Person 1* and *Person 2* :

  1. Understand this interaction

  2.Categorize this interaction with definitions:

    • Cooperative: Joint actions towards common political goals (e.g., political work cooperation, face-to-face supportt)

    • Adversarial: Conflicting political interests (e.g., election competition, debate)

    • Neutral: Non-political/symbolic interactions (e.g., personal relationships, ceremonial meetings)

  3. Return only the category label

Text to analyze: {*Text*}

Quadruple: {*Person1, Person2, Time, Location*}

Political party information: {*Person1:Party1, Person2:Party2*}

Figure 8: Prompt used by GPT-4o-mini to map political interactions into the predefined schema in the case study.

A.11 Network Construction and Polarization Metrics

A.11.1 Weighting Scheme

In our network analysis, nodes represent political figures, and edges represent interactions. Following the Weighted Signed Networks (WSN) framework (Kumar et al., 2016), we assigned specific signed weights to capture both polarity and magnitude:

- −2 (*Adversarial*): Reflects strong negative relational dynamics.

- +2 (*Cooperative*): Reflects strong positive collaboration.

- +1 (*Neutral*): Assigned a positive but lower weight. Unlike previous studies that might assign 0, we argue that neutral interactions in political contexts imply a baseline of civil discourse and goodwill, distinct from the absence of interaction.

Time Period	Artist	Scientist	Athlete
1920 - 1940	Fletcher Henderson	Albert Einstein	Babe Ruth
1940 - 1960	Frank Sinatra	Sydney Brenner	Antonino Rocca
1960 - 1980	Bob Dylan	Andrei Sakharov	Warren Bockwinkel
1980 - 2000	Robert De Niro	Andy Bechtolsheim	Lindsay Davenport
2000 - 2020	Jennifer Lopez	Stephen Hawking	LeBron James

Figure 9: (a) In the constructed network, the distribution of node degrees adheres to a power-law distribution. (b) Clustering coefficient c and power-law distribution parameter α over 20-year intervals from 1920 to 2020. (c) From 1920 to 2020, every 20 years, the top-ranked individuals in the professions of artists, scientists, and athletes according to their PageRank.

A.11.2 Calculation of Standardized Modularity

Following Conover et al. (Conover et al., 2011), we implement their normalized modularity calculation method to quantify polarization. As direct comparison of modularity values across networks with varying sizes and connection densities is challenging, their approach evaluates the relative quality of cluster assignments. The implementation involves:

- Generating $N = 1000$ randomized network samples preserving both degree sequence and edge weight distribution (for weighted graphs in our scenario).

- Computing the mean (μ) and standard deviation (σ) of modularity Q from randomized samples.

- Deriving the Z-score: $Z = (Q_{\text{original}} - \mu)/\sigma$.

This normalization procedure quantifies how significantly the observed community structure deviates from random expectation, while maintaining the original network's topological characteristics through degree- and weight-preserving randomization.

A.12 Empirical Validation of Polarization Metrics

To further validate the reliability of our analysis, we conducted a correlation analysis between the standardized modularity of our extracted interaction networks and the DW-NOMINATE polarization index from the Voteview database (Lewis et al., 2019).

Metric Description The DW-NOMINATE score is calculated based on historical congressional roll-call voting records. Its first dimension quantifies legislators' positions on the "liberal-conservative" spectrum, effectively reflecting their political ideology. For our analysis, we calculated the difference between the mean scores of Republican and Democratic members on this first dimension for each Congress. This difference serves as a quantitative measure of the objective ideological distance between the two major parties.

Correlation Methodology The correlation analysis was conducted following these steps:

- **Time Span:** The analysis covers the period from 1960 to 2024.

- **Data Alignment:** Because the DW-NOMINATE index is published on a per-Congress basis (every two years), we temporally aligned our data by aggregating our annual standardized modularity metric, calculating the average modularity for each corresponding congressional term.

- **Calculation:** Subsequently, we computed the Pearson correlation coefficient between these two aligned time series.

Results and Analysis The analysis reveals a highly significant positive correlation between our network modularity and the DW-NOMINATE index ($r = 0.969$, $p < 0.001$). This demonstrates that the political polarization patterns extracted from our textual data are statistically consistent with widely recognized polarization benchmarks in the field of political science. This strong alignment validates the efficacy of our methodology in accurately capturing macro-level political polarization trends.

A.13 Additional Analysis

A.13.1 Overall Analysis

Figure 10 illustrates the global distributions of these interactions, showing that most interactions occur in North America and Europe, followed by Southeast Asia and Australia.

Figure 10: A geographic heatmap of interaction locations, where darker colors indicate a higher number of interaction events.

With these interactions, we then build an interaction network. In Figure 9 (a), we illustrate the degree distribution across the entire network, observing a conforming pattern to the power-law distribution.

We further examine the temporal perspective. Using data from each 20-year interval from 1920 to 2020, we construct 5 sub-networks. For each sub-network, we calculate the clustering coefficient c and the power-law distribution parameter α. As we can see from Figure 9 (b), c exhibits an increasing trend, while the α shows a decreasing trend, indicating the interaction networks are becoming centralized over time.

For each 20-year interval, we identify the top individuals in the occupations of artist, scientist, and athlete, respectively, ranked by PageRank scores. This is illustrated in Figure 9 (c).

A.13.2 Interaction Distance

We define interaction distance as the cumulative distance from *Location* to both *Person1*'s and *Person2*'s birthplaces, indicating the travel distance required for the interaction. As illustrated in Figure 11 (a), the average interaction distance exhibits a growing trend over time, likely attributable to advancements in modern transportation and communication. In contrast, Figure 11 (b) shows that most interactions occur over short distances, with the distribution conforming to a power-law pattern.

Figure 11: (a) From 1900 to 2020, the evolution of the average interaction distance. (b) The distributional relationship between the number of interactions and the distance of these interactions.

These findings are consistent with those reported by Illenberger et al. (2013).

A.14 Extraction from News Archives

Building upon the experimental results in Section 6.4, which demonstrated FALCON's robust cross-domain applicability on news media, we extended our extraction pipeline to the large-scale *all-the-news-2-1* dataset[8]. This corpus contains a total of **2,688,868** articles published by major American news outlets between 2016 and 2020.

The extraction process was conducted in two phases:

Figure 12: The architecture of AR-BERT.

Candidate Generation. We applied the same trajectory mining pipeline used for Wikipedia to the raw news texts. By filtering for text segments containing the co-occurrence of at least two *Person* entities alongside explicit *Time* and *Location* mentions, we generated **552,534** candidate interaction quadruplets.

---

[8] https://huggingface.co/datasets/rjac/all-the-news-2-1-Component-one

Inference and Extraction. We then utilized the FALCON model (trained on Wikipedia) to classify these candidates. Consistent with its performance in our experimental evaluation, FALCON successfully identified **77,836** valid spatio-temporal interaction quadruplets. This resulting dataset captures contemporary interactions spanning from 2016 to 2020.

A.15 AR-BERT Figure

Figure 12 presents a schematic illustration of the AR-BERT framework.