Zero-Shot Video-Text Retrieval with Hallucination-Based Captioning and Structural Information Extraction

Abstract

While recent progress in video-text retrieval has been advanced by the exploration of better representation learning, in this paper, we present a novel zero-shot framework, HALISIE, to retrieve video/text with off-the-shelf captioning methods, large language models (LLMs), and text retrieval methods. Specifically, we first map videos into captions with video captioning methods and then retrieve video captions and text using text retrieval methods, without any training or fine-tuning on models. However, due to the limited power of captioning methods, the captions often miss important content in the video, resulting in unsatisfactory retrieval performance. To translate more information into video captions, we designed a novel **hallucination-based caption generation** method, that injects LLMs' hallucinated information into video captions. Moreover, to emphasize key information in the video, we extract key visual tokens from captions and design different templates for structuring these tokens with the proposed **structural information extraction**, further boosting the retrieval performance. Benefiting from the hallucinated captions and structuralized information, extensive experiments on several video-text retrieval benchmarks demonstrate the superiority of our proposed zero-shot method, HALISIE, over existing fine-tuned and pretraining methods without any data. Codes and data will be released.

1 Introduction

Video-text retrieval (VTR) (Luo et al., 2022; Gao et al., 2021; Ma et al., 2022; Liu et al., 2022a; Zhao et al., 2022; Gorti et al., 2022; Fang et al., 2022) aims to retrieve the corresponding video or text given the query in another modality. Recent years have witnessed the rapid development of VTR with the support from powerful pretraining models (Luo et al., 2022; Gao et al., 2021; Ma et al., 2022; Liu et al., 2022a), improved retrieval methods (Bertasius et al., 2021; Dong et al., 2019; Jin et al., 2021),

and video-language datasets construction (Xu et al., 2016). However, it remains challenging to precisely match video and language due to the raw data being in heterogeneous spaces with significant differences.

The most popular paradigm in VTR (Luo et al., 2022; Ma et al., 2022; Liu et al., 2022b) firstly learns a joint feature space across modalities and then compares representations in this space. However, with the discrepancy between different modalities and the design of modality-independent encoders, it is challenging to directly compare and calculate the similarities between representations of different modalities generated from different encoders (Liang et al., 2022). A pioneering work (Wang et al., 2022e) converts videos into captions to eliminate this discrepancy for better presentation learning on video-language tasks. It demonstrates that vision-language models with image captioners are able to do multiple few-show tasks.

In this work, to take one step forward, we present a zero-shot video-text retrieval paradigm, HALISIE, along with our proposed hallucination-based captioning and structural information extraction. HALISIE first captions videos into video captions. However, we notice that the captions always miss important information in the video, thus leading to bad retrieval performance (see table 1 without paraphrase and visual tokens). To this end, we propose **hallucination-based captioning**, which augments video captions by leveraging the hallucination of large language models (LLMs). Later, to emphasize the important information in the captions, *e.g.*, objects, events, and attributes, we design a **structural information extraction** procedure for extracting "visual tokens". Finally, HALISIE utilizes off-the-shelf text retrieval methods for zero-shot text retrieval using captions and corresponding visual tokens.

Finally, to evaluate the effectiveness of our pro-

posed HALISIE, we conducted experiments on three representative video-text benchmarks (Chen and Dolan, 2011; Fabian Caba Heilbron and Niebles, 2015; Xu et al., 2016). Results show that our proposed zero-shot method outperforms previous methods, including fine-tuning methods and few-shot methods, on multiple metrics, benefiting from hallucination-based captioning and structural information extraction.

In summary, our contributions are as follows:

- We propose a real zero-shot video-text retrieval method without requiring any training procedure or human-annotated data, only using the off-the-shelf captioning method, large language models, and text retrieval methods.

- Our proposed HALISIE achieves SOTA performance on several metrics across three VTR benchmarks.

- Detailed analysis reveals the importance of hallucination-based captioning and structural information extraction.

- We will open-source the code and data to facilitate future research.

2   Related Work

In this section, we briefly review the literature on video-text retrieval and zero-shot cross-modal retrieval.

Video-text retrieval, which involves cross-modal alignment and abstract understanding of temporal images (videos), has been a popular and fundamental task of language-grounding problems (Wang et al., 2020a,b, 2021; Yu et al., 2023). Most of the existing video-text retrieval frameworks (Yu et al., 2017; Dong et al., 2019; Zhu and Yang, 2020; Miech et al., 2020; Gabeur et al., 2020; Dzabraev et al., 2021; Croitoru et al., 2021) focus on learning powerful representations for video and text and extracting separated representations. For example, in Dong et al. (2019), videos and texts are encoded using convolutional neural networks and a bi-GRU (Schuster and Paliwal, 1997) while mean pooling is employed to obtain multi-level representations. MMT (Gabeur et al., 2020) uses a cross-modal encoder to aggregate features extracted by temporal images, audio, and speech for encoding videos. Following that, MDMMT (Dzabraev et al., 2021) further utilizes knowledge

learned from multi-domain datasets to improve performance empirically. Further, MIL-NCE (Miech et al., 2020) adopts Multiple Instance Learning and Noise Contrastive Estimation for end-to-end video representation learning, addressing the problem of visually misaligned narrations from uncurated videos.

Recently, with the success of self-supervised pretraining methods (Devlin et al., 2019; Radford et al., 2019; Brown et al., 2020), vision-language pretraining (Li et al., 2020b; Gan et al., 2020; Singh et al., 2022) on large-scale unlabeled cross-modal data has shown promising performance in various tasks, *e.g.*, image retrieval (Radford et al., 2021), image captioning (Chan et al., 2023), and video retrieval (Luo et al., 2022; Wang and Shi, 2023a). Recent works (Lei et al., 2021; Cheng et al., 2021; Gao et al., 2021; Ma et al., 2022; Park et al., 2022a; Wang et al., 2022b,d; Zhao et al., 2022; Gorti et al., 2022) have attempted to pretrain or fine-tune video-text retrieval models in an end-to-end manner. CLIPBERT (Lei et al., 2021; Bain et al., 2021), as a pioneer, proposes to sparsely sample video clips for end-to-end training to obtain clip-level predictions and then summarize them. Frozen in time (Bain et al., 2021) uses end-to-end training on both image-text and video-text pairs data by uniformly sampling video frames. CLIP4Clip (Luo et al., 2022) finetunes models and investigates three similarity calculation approaches for video-sentence contrastive learning on CLIP (Radford et al., 2021). Further, TS2-Net (Liu et al., 2022b) proposes a novel token shift and selection transformer architecture that adjusts the token sequence and selects informative tokens in both temporal and spatial dimensions from input video samples. While the mainstream of VTR models (Xue et al., 2023; Wu et al., 2023) focuses on fine-tuning powerful image-text pre-trained models, on the other side, as a pioneer, (Tiong et al., 2022; Wang et al., 2022e) propose to use large language models (LLMs) for zero-shot video question answering.

Zero-shot cross-modal retrieval. With the huge success of pretrained visual-language model (Radford et al., 2021; Luo et al., 2022), zero-shot cross-modal retrieval has attracted more and more research interest recently. Due to the powerful representation learning ability in image and text domains, CLIP (Radford et al., 2021) achieves satisfying zero-shot retrieval performance on several representative image-text retrieval bench-

Figure 1: The illustration of our proposed HALISIE. HALISIE includes four steps. First, we generate video captions for video using off-the-shelf video captioning methods. Second, to enrich the captions, we propose the hallucination-based caption-generation method using large language models. Third, to emphasize the important information in the captions, we propose a novel structural information extract module. Finally, after obtaining structured video captions, we employ off-the-shelf text retrieval methods to perform zero-shot video-text retrieval.

marks (Huiskes and Lew, 2008; Lin et al., 2014). Inspired by this achievement, Liu et al. (2023a,b); Chen et al. (2023c); Liu et al. (2024); Guo et al. (2024) boost the performance of zero-shot image-text retrieval by better representation learning methods. On the other side, benefiting from large-scale video-text benchmarks (Xu et al., 2016; Chen and Dolan, 2011; Fabian Caba Heilbron and Niebles, 2015), video-language pre-trained models (Wang et al., 2022c; Chen et al., 2023a; Xu et al., 2023; Chen et al., 2023c; Li et al., 2023; Liu et al., 2023c; Zhu et al., 2024) also achieve satisfying zero-shot video-text retrieval results.

In this paper, inspired by these pioneering works, to explore zero-shot video-text retrieval, we step forward and propose a simple but effective zero-shot video-text retrieval method, HALISIE, by utilizing off-the-shelf captioning, large language models, and text retrieval methods.

3 HALISIE - Zero-Shot Video Text Retrieval

In this section, we present the details of our proposed method, HALISIE. Specifically, we first generate captions for videos using video caption generation methods. Then, to cover most of the details in videos, with our proposed hallucination-based caption generation, we obtain a detailed caption containing almost all the details of the video. Finally, to ease the job of the text retrieval method, we use the proposed structural information extraction to emphasize important information in the captions for better video-text retrieval performance. The whole procedure is summarized in fig. 1.

3.1 Video Caption Generation

To generate captions for videos, we employ two methods and combine the generated text to serve as the final caption.

Crawling of Video Titles. We extract video titles using the meta information in the dataset, where we retrieve the title of the video from its original source (*e.g.*, YouTube) using the video's unique identifier. This title is then used as the video's caption.

Video Captioning with Off-the-shelf Models. In contrast to the previous approach that relies on the meta information, we use off-the-shelf large-scale captioning models to generate varied and detailed captions. To achieve this, we employ Tewel et al. (2021, 2022) to generate video captions and then use GPT-2 (Radford et al., 2019) to enrich sentences using the prompts, *i.e.*, "Video presents".

3.2 Hallucination-Based Caption Generation

As shown in fig. 3, we notice that the generated captions always miss some important information that is vital in the video, leading to unsatisfying retrieval performance. A simple solution to this problem is to fine-tune the captioning models, which will improve their caption-generation abilities. However, this approach needs a huge amount of annotated video-caption data and expensive computation resources, and the fine-tuned models are always not able to be transferred to other benchmarks. To this end, we propose the **hallucination-based caption generation**, which is training-free and able to generate detailed captions that contain almost every detail of the video.

Specifically, we use large language models

(LLMs) (Touvron et al., 2023; Brown et al., 2020) to conduct the hallucination-based generation using the following prompt template.

```
The following is a caption from a
video: ["] + <Video Caption> + ["].
Based on this caption, generate two
paraphrased captions capturing the
key information and main themes,
each of which should be in one
sentence with up to twenty words.
Meanwhile, please be creative, you
can have some imagination and add
the necessary details. Generated
sentences should be in the number
list. Also please generate text
without any comment.
```

Our proposed method generates multiple captions (*e.g.*, 1, 2, and 3). However, some of these captions might introduce noise or lack strong relevance to the video's content. To mitigate potential negative impacts, we apply a filtering method to assess the semantic similarity between hallucinated captions and the original video caption by leveraging a pre-trained text encoder (Reimers and Gurevych, 2019). Then we concatenate the filtered captions along with the original video caption to obtain the final captions.

3.3 Structural Information Extraction

To understand which kind of information is essential to video-text retrieval, we analyze the contextual text of video captions by breaking down the video captions into four different visual tokens using NLTK (Bird et al., 2009), *i.e.*, phrase, object, event, and attribute. Then we structure the information into the following structure.

```
<Caption> <Phrases> <Attributes> <
Events> <Objects>
```

3.4 Video (Video Caption)-Text Retrieval

Finally, after obtaining structured video caption data, we are ready to perform the retrieval step. Specifically, we compute the similarity score at the video level between text and video caption using off-the-shelf retrieval methods (Robertson and Walker, 1994; Reimers and Gurevych, 2019).

Due to the computational resource limit, we use BM25 (Robertson and Walker, 1994) and Sentence transformers (Reimers and Gurevych, 2019) to perform HALISIE.

4 Experiments

4.1 Benchmarks, Baselines, and Evaluation Metrics

Benchmarks. Following previous work (Luo et al., 2022; Ma et al., 2022), we use three representative benchmarks for evaluating HALISIE, *i.e.*, MSR-VTT, MSVD, and ActivityNet.

Baselines. To show the empirical efficiency of our HALISIE, we compare it with fine-tuned models (LiteVL (Chen et al., 2022), NCL (Park et al., 2022b), TABLE (Chen et al., 2023b), VOP (Huang et al., 2023), X-CLIP (Ma et al., 2022), Discrete-Codebook (Liu et al., 2022a), TS2-Net (Liu et al., 2022b), VCM (Cao et al., 2022), HiSE (Wang et al., 2022b), CenterCLIP (Zhao et al., 2022), X-Pool (Gorti et al., 2022), and S3MA (Wang and Shi, 2023b)), pre-trained methods (VLM (Xu et al., 2021a), HERO (Li et al., 2020a), VideoCLIP (Xu et al., 2021b), EvO (Shvetsova et al., 2022), OA-Trans (Wang et al., 2022a), RaP (Wu et al., 2022), OmniVL (Wang et al., 2022c), mPLUG-2 (Xu et al., 2023), InternVL (Chen et al., 2023c), and Lan-gaugeBind (Zhu et al., 2024)), and a few-shot method, *i.e.*, VidIL (Wang et al., 2022e).

Evaluation metric. To evaluate the retrieval performance of our proposed model, we use recall at Rank K (R@K, higher is better), median rank (MdR, lower is better), and mean rank (MnR, lower is better) as retrieval metrics, which are widely used in previous retrieval works (Radford et al., 2021; Luo et al., 2022; Ma et al., 2022).

4.2 Implementation Details

For video caption generation, we use Tewel et al. (2021, 2022) to generate video captions and GPT-2 (Radford et al., 2019) to enrich sentences. For hallucination-based caption generation, we employ LLaMA2-7b-chat-hf (Touvron et al., 2023) and get two hallucinated captions. For structural information extraction, we use NLTK (Bird et al., 2009). For text retrieval, we use BM25 (Robertson and Walker, 1994).

4.3 Quantitative Results

In this part, we present the qualitative results of our proposed HALISIE on three representative benchmarks in video-text retrieval.

MSR-VTT. We found that the contextual video text obtained directly through video captioning methods generally have mediocre performance (R@1:

Methods	Venue	Text-to-Video Retrieval					Video-to-Text Retrieval				
		R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
Training-based											
LiteVL-S	EMNLP'22	46.7	71.8	81.7	2.0	-	-	-	-	-	-
X-Pool	CVPR'22	46.9	72.8	82.2	2.0	14.3	-	-	-	-	-
CenterCLIP	SIGIR'22	44.2	71.6	82.1	2.0	15.1	42.8	71.7	82.2	2.0	10.9
TS2-Net	ECCV'22	47.0	74.5	83.8	2.0	13.0	45.3	74.1	83.7	2.0	9.2
X-CLIP	ACM MM'22	46.1	74.3	83.1	2.0	13.2	46.8	73.3	84.0	2.0	9.1
NCL	EMNLP'22	43.9	71.2	81.5	2.0	15.5	44.9	71.8	80.7	2.0	12.8
TABLE	AAAI'23	47.1	74.3	82.9	2.0	13.4	47.2	74.2	84.2	2.0	11.0
VOP	CVPR'23	44.6	69.9	80.3	2.0	16.3	44.5	70.7	80.6	2.0	11.5
DiscreteCodebook	ACL'22	43.4	72.3	81.2	-	14.8	42.5	71.2	81.1	-	12.0
VCM	AAAI'22	43.8	71.0	-	2.0	14.3	45.1	72.3	82.3	2.0	10.7
CenterCLIP	SIGIR'22	48.4	73.8	82.0	2.0	13.8	47.7	75.0	83.3	2.0	10.2
HiSE	ACM MM'22	45.0	72.7	81.3	2.0	-	46.6	73.3	82.3	2.0	-
TS2-Net	ECCV'22	49.4	75.6	85.3	2.0	13.5	46.6	75.9	84.9	2.0	8.9
S3MA	EMNLP'23	53.1	78.2	86.2	1.0	10.5	52.7	79.2	86.3	1.0	8.2
Zero-Shot (Pretrained Models)											
VLM	ACL'21	28.1	55.5	67.4	4.0	-	-	-	-	-	-
HERO	EMNLP'21	16.8	43.3	57.7	-	-	-	-	-	-	-
VideoCLIP	EMNLP'21	30.9	55.4	66.8	-	-	-	-	-	-	-
EvO	CVPR'22	23.7	52.1	63.7	4.0	-	-	-	-	-	-
OA-Trans	CVPR'22	35.8	63.4	76.5	3.0	-	-	-	-	-	-
RaP	EMNLP'22	40.9	67.2	76.9	2.0	-	-	-	-	-	-
OmniVL	NeurIPS'22	34.6	58.4	66.6	-	-	-	-	-	-	-
mPLUG-2	ICML'23	48.3	75.0	83.2	-	-	-	-	-	-	-
InternVL	Arxiv'23	42.4	65.9	75.4	-	-	**46.3**	**70.5**	**79.6**	-	-
LanguageBind	ICLR'24	42.6	65.4	75.5	-	-	-	-	-	-	-
Few-Shot											
VidIL	NeurIPS'22	40.8	65.2	-	-	-	39.6	64.5	-	-	-
Zero-Shot											
HALISIE w/o paraphrase and visual tokens		20.3	40.9	51.7	9.0	60.3	17.5	36.7	47.3	12.0	82.3
HALISIE w/o visual tokens		54.0	73.9	80.2	1.0	24.5	27.9	41.3	47.3	15.0	136.2
HALISIE		**58.2**	**75.8**	**83.9**	1.0	**18.9**	36.4	56.5	63.8	3.0	**75.7**

Table 1: Video-Text retrieval results on MSR-VTT. The best results are marked in **bold**. The second best results are underlined. "NC" refers to Neurocomputing.

Figure 2: These figures illustrate the distribution of the rank of each (test) gallery video (captions) retrieved by (test) text queries.

20.3) compared to other baseline Text-Video Retrieval method. However, after using LLM to do hallucination-based generation from the video caption, the R@1 of our method nearly doubled (R@1 = 40.9) shown in Table 5 . Therefore, we further hallucinated each sentence and expanded it into two sentences. From the results presented in Table 1, it can be seen that this approach outperforms the second-best method by 9.9. This indicates the significant impact of hallucinating and expanding captions on enhancing the performance of Text-Video Retrieval systems. Compared to DiscreteCode-book (Liu et al., 2022a), which aligns modalities in an unsupervised manner, HALISIE outperforms DiscreteCodebook on every metric. Meanwhile, HALISIE also outperforms VidIL (Wang et al., 2022e), which uses few-shot prompting, demonstrating the usability of integrating zero-shot LLM on text-to-video retrieval. This suggests that leveraging zero-shot on large language models (LLMs) is a promising approach to enhance text-to-video retrieval performance.

Also, we notice that HALISIE has bad results on mean rank. To understand why this happens,

Caption	Phrase	Object	Event	Attribute	Text-to-Video Retrieval					Video-to-Text Retrieval				
					R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
✓					54.0	73.9	80.2	1.0	24.5	27.9	41.3	47.3	15.0	136.2
✓	✓				57.4	76.2	83.0	1.0	19.3	29.9	45.6	52.3	8.0	115.4
✓		✓			56.9	**77.5**	83.8	1.0	18.6	35.8	56.9	64.8	3.0	73.9
✓			✓		54.2	73.2	79.6	1.0	24.9	28.4	42.7	49.1	12.0	130.3
✓				✓	55.0	74.2	80.2	1.0	24.1	28.6	43.3	48.9	11.0	132.2
✓	✓	✓			57.4	76.2	83.9	1.0	18.7	34.5	54.0	62.5	4.0	79.9
✓	✓		✓		57.3	76.3	82.6	1.0	19.8	31.5	47.3	54.2	7.0	109.0
✓	✓			✓	57.6	76.3	83.5	1.0	19.1	31.0	47.4	54.7	7.0	110.5
✓		✓	✓		56.9	76.6	83.2	1.0	19.3	35.9	57.9	65.6	3.0	71.2
✓		✓		✓	57.6	77.4	83.8	1.0	**18.2**	37.4	58.5	66.3	3.0	71.8
✓			✓	✓	54.0	73.3	79.6	1.0	24.9	30.0	44.3	51.1	10.0	126.1
✓	✓	✓	✓		58.0	75.9	83.7	1.0	19.3	35.1	55.1	63.0	4.0	77.3
✓	✓	✓		✓	57.8	76.3	**84.1**	1.0	18.3	35.7	55.5	63.1	3.0	78.3
✓	✓		✓	✓	57.8	76.0	82.5	1.0	19.5	31.8	48.5	55.2	6.0	106.6
✓		✓	✓	✓	57.3	76.7	83.2	1.0	18.9	**37.5**	**59.4**	**67.0**	3.0	**69.2**
✓	✓	✓	✓	✓	**58.2**	75.8	83.9	1.0	18.9	36.4	56.5	63.8	3.0	75.7

Table 2: Retrieval performance with different combinations of four visual tokens (Phrase, Object, Event, Attribute) on MSR-VTT using HALISIE.Best in **Bold**.

Methods	Venue	Text-to-Video Retrieval			
		R@1↑	R@5↑	R@10↑	MnR↓
MSVD					
RaP	EMNLP'22	35.9	64.3	73.7	-
LanguageBind	ICLR'24	52.2	79.4	87.3	-
HALISIE		**57.2**	**80.0**	**88.2**	15.6
ActivityNet					
LanguageBind	ICLR'24	35.1	63.4	76.6	-
HALISIE		**59.0**	**71.4**	**77.0**	387.4

Table 3: Text-Video retrieval results on MSVD and ActivityNet. The best results are marked in **bold**.

we visualize the distribution of rank in fig. 2. It is obvious that though most of the videos have very good rank, *e.g.*, lower than 10, there are still some captions ranked in the last. This might be due to the failure of caption generation for some videos, where the generated captions do not contain any information from the video.

MSVD and ActivityNet. The results on MSVD and ActicityNet are shown in Table 3. HALISIE achieves the best R@1 on text-to-video retrieval on two datasets compared to the previous methods.

4.4 Ablation Studies

In this part, we present a series of ablation experiments on MSR-VTT to better understand the effectiveness of different components of HALISIE, using LLaMA2-7b-chat-hf and BM25. Due to space limitations, the ablation study on different retrieval methods is presented in appendix A.2.

Impact of combination of structural information (visual tokens). To choose the best combination method for the extracted visual tokens (phrases, attributes, objects, and events), we conduct experiments using different arrangements of these visual tokens, as shown in Table 2. By reducing the inclusion of visual tokens, the retrieval performance of HALISIE decreases, thereby proving the superiority of integrating these four visual tokens together.

The order of different structural information. Another important factor to consider is the order of these visual tokens. To this end, we systematically evaluate which specific order of <phrase>, <object>, <attribute>, and <event> maximizes the efficiency and accuracy of the retrieval process. The results are shown in Table 4. We discover that among various arrangements, the model performs best when either phrases or objects are placed at the end of the sequence. This superior performance might be due to the detailed and specific information that phrases and objects offer, enhancing the model's ability to accurately match and retrieve relevant video content.

Number of hallucinated captions (visual tokens). In this part, we aim to explore how many hallucinated captions work the best. More captions have the potential to offer more detailed descriptions, which may enhance the viewer's comprehension of the visual content. Previous studies (Biten et al., 2019; Tang et al., 2023) have demonstrated that longer captions tend to be more descriptive and semantically rich, achieving improved comprehension and retrieval performance. However, more hallucinated captions also mean more noises are injected. So balancing the number of hallucinated captions would be highly important. From the re-

Order List	Text-to-Video Retrieval					Video-to-Text Retrieval				
	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
Order List 1	**58.2**	75.8	**83.9**	1.0	18.9	36.4	56.5	63.8	3.0	**75.7**
Order List 2	57.9	**75.9**	83.6	1.0	**18.7**	**36.7**	56.4	**64.4**	3.0	75.3
Order List 3	58.0	75.7	83.5	1.0	19.1	36.3	**56.6**	64.2	3.0	75.0

Table 4: Retrieval performance with different order of four visual tokens (Phrase, Object, Event, Attribute) on MSR-VTT using HALISIE. Best in **Bold**. We discovered three unique sequencing methods for visual tokens, each producing distinct outcomes based on their specific arrangements. Order List 1 places objects or phrases to the end, *i.e.*, {Caption}, . . ., {Phrase/Object}, Order List 2 represents {Caption}, . . ., {Event}, and Order List 3 represents {Caption}, . . ., {Attribute}.

# of Hullucinated Captions	Text-to-Video Retrieval					Video-to-Text Retrieval				
	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
1	40.9	55.5	60.9	3.0	227.3	34.3	54.2	62.6	4.0	114.0
2	**58.2**	**75.8**	**83.9**	1.0	**18.9**	**36.4**	**56.5**	**63.8**	3.0	**75.7**
3	55.7	73.9	82.2	1.0	21.2	35.1	52.8	62.4	4.0	87.1

Table 5: Retrieval performance with different numbers of hallucinated captions on MSR-VTT using HALISIE. Best in **Bold**.

Template	Text-to-Video Retrieval					Video-to-Text Retrieval				
	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
Basic Template	**58.2**	**75.8**	**83.9**	1.0	**18.9**	**36.4**	**56.5**	**63.8**	3.0	**75.7**
Structured Template	55.7	74.6	81.2	1.0	21.1	31.0	45.4	51.5	9.0	77.2
Template with Detailed Description	55.9	74.6	81.7	1.0	21.2	34.3	53.9	61.7	4.0	84.7
Narrative Format Template	56.5	74.7	81.7	1.0	20.9	26.9	43.4	49.0	11.0	129.7

Table 6: Retrieval performance with different template formats on MSR-VTT using HALISIE. Best in **Bold**.

sults shown in Table 5, we notice that paraphrasing into two or three sentences significantly improved R@1, R@5, and R@10. Considering computational constraints and the similar effectiveness of paraphrasing into two and three sentences, we decide to hallucinate into two sentences.

Complexity of prompt templates for structural information extraction. The complexity of the prompt plays a pivotal role in shaping the output generated by the model, influencing the depth of analysis and the richness of information conveyed. An intricate prompt may provide the model with additional context and guidance, enabling it to produce more detailed responses. Specifically, we compare four templates (Basic, Structured, Detailed Description, and Narrative Format) offering different levels of complexity for organizing video content as follows,

1. Basic Template: the simplest, providing a straightforward list of video elements, the one shown in section 3.3.

2. Structured Template: It adds categorized elements, making the information easier to navi-

gate for the retrieval method.

```
Video Caption : <Caption>. Key
Phrases: <{Phrases}>. Main
Objects: <Objects>. Notable
Features: <{Attributes}>. Key
Events: <Events>
```

3. Template with Detailed Description: This further elaborates on each element, offering in-depth insights.

```
Detailed Video Description:
Caption: <{Caption}> Objects and
 Attributes Overview: Each
object, <{Objects}>, is detailed
 with attributes such as <{
Attributes}> to provide a
clearer image. Event Analysis:
The video's narrative is driven
by events like <{Events}>, which
 are elaborated for better
understanding. Phrases Insight:
Phrases like <{Phrases}> are
explained for their significance
 to the content.
```

LLM	Text-to-Video Retrieval					Video-to-Text Retrieval				
	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
LLaMA	58.2	75.8	83.9	1.0	18.9	**36.4**	56.5	63.8	3.0	**75.7**
GPT 3.5	**61.2**	**80.4**	**86.8**	1.0	**15.0**	35.5	**58.3**	**65.5**	3.0	77.6

Table 7: Retrieval performance with different LLM models on MSR-VTT using HALISIE. Best in **Bold**.

Video

Ground Truth Text

a girl wearing red top and black trouser is putting a sweater on a dog…

Video Caption

HAMSTER'S New Home Tour
a girl putting a sweater on the dog…

Hallucinated Captions

The pink-clad girl dresses her dog in a matching sweater, creating a cute and cozy pair. A stylish dog is accessorized with a pink sweater, complementing its owner's fashionable outfit.

Structured Captions

The pink-clad girl dresses her dog in a matching sweater, creating a cute and cozy pair. A stylish dog is accessorized with a pink sweater, complementing its owner's fashionable outfit. <The pink-clad girl her dog a matching sweater a cute and cozy pair A stylish dog a pink sweater its owner's fashionable outfit> <cute cozy stylish pink fashionable> <clad matching creating accessorized complementing> <girl dresses dog sweater pair dog sweater owner outfit>

Figure 3: An example. Hallucinated captions contain more information compared to vanilla video captions in the video though some noises are also injected.

4. Narrative Format Template: it weaves the elements into a cohesive story, enhancing engagement and providing a thematic understanding.

```
Caption: <Caption> In this video
, we observe <{Objects}> with <{
Attributes}>, a vivid
representation of <{Events}>.
Phrases such as <{Phrases}>
punctuate the narrative,
offering insights into the
unfolding story.
```

Each template caters to different needs, from quick reference to comprehensive analysis, reflecting a progression from functional simplicity to narrative depth. The results are shown in Table 6. We notice that intricate prompts provide the model with additional context and guidance, enabling it to produce more detailed responses. However, it may also lead to a loss of information, which is important for the retrieval performance. The results show that with the narrative format template, R@1, R@5, and R@10 on text-to-video retrieval are improved. This might be because the simplest format template provides insights into storytelling elements such as objects, events, and phrases, which leads to more precise keyword assignments.

4.5 Qualitative Results

To qualitatively validate the effectiveness of HAL-ISIE, we present an example in fig. 3, respectively. The retrieval results show that hallucinated captions have more information in the video than vanilla video captions. Moreover, our proposed structural information extraction methods clearly emphasize the important visual tokens, *i.e.*, phrase, object, event, and attribute, which further boosts the performance.

5 Conclusion

In this paper, we present an innovative zero-shot framework, HALISIE, which revolutionizes video-text retrieval by capitalizing on existing captioning methods, large language models (LLMs), and text retrieval techniques. By sidestepping the need for model training or fine-tuning, our framework offers a streamlined approach to retrieval. To overcome the shortcomings of traditional captioning methods, we propose a groundbreaking hallucination-based caption generation technique that incorporates LLMs' hallucinated information into video captions. Moreover, our introduction of structural information extraction further enhances retrieval performance by highlighting key visual tokens. Through extensive experimentation across diverse benchmarks, we demonstrate the superior efficacy of HALISIE compared to conventional fine-tuned and pretraining methods, even in the absence of training data.

Limitations

In the future, it would be interesting to explore more detailed methods for zero-shot video-text retrieval, such as incorporating the audio modality and corresponding off-the-shelf foundation models. Moreover, as a pioneering work, our work mainly focuses on establishing the paradigm. It would be great if we could explore more text retrieval methods, video captioning methods, and LLMs for hallucinated caption generation.

References

Max Bain, Arsha Nagrani, Gül Varol, and Andrew Zisserman. 2021. Frozen in time: A joint video and image encoder for end-to-end retrieval. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pages 1708–1718. IEEE.

Gedas Bertasius, Heng Wang, and Lorenzo Torresani. 2021. Is space-time attention all you need for video understanding? In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 813–824. PMLR.

Steven Bird, Ewan Klein, and Edward Loper. 2009. *Natural language processing with Python: analyzing text with the natural language toolkit*. " O'Reilly Media, Inc.".

Ali Furkan Biten, Lluis Gomez, Marcal Rusinol, and Dimosthenis Karatzas. 2019. Good news, everyone! context driven entity-aware captioning for news images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Shuqiang Cao, Bairui Wang, Wei Zhang, and Lin Ma. 2022. Visual consensus modeling for video-text retrieval. In *Thirty-Sixth AAAI Conference on Artificial Intelligence, AAAI 2022, Thirty-Fourth Conference on Innovative Applications of Artificial Intelligence, IAAI 2022, The Twelveth Symposium on Educational Advances in Artificial Intelligence, EAAI 2022 Virtual Event, February 22 - March 1, 2022*, pages 167–175. AAAI Press.

David M. Chan, Austin Myers, Sudheendra Vijaya-narasimhan, David A. Ross, and John Canny. 2023. IC^3: Image Captioning by Committee Consensus. ArXiv:2302.01328 [cs].

David Chen and William Dolan. 2011. Collecting highly parallel data for paraphrase evaluation. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 190–200, Portland, Oregon, USA. Association for Computational Linguistics.

Dongsheng Chen, Chaofan Tao, Lu Hou, Lifeng Shang, Xin Jiang, and Qun Liu. 2022. LiteVL: Efficient video-language learning with enhanced spatial-temporal modeling. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 7985–7997, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Sihan Chen, Handong Li, Qunbo Wang, Zijia Zhao, Mingzhen Sun, Xinxin Zhu, and Jing Liu. 2023a. VAST: A vision-audio-subtitle-text omni-modality foundation model and dataset. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Yizhen Chen, Jie Wang, Lijian Lin, Zhongang Qi, Jin Ma, and Ying Shan. 2023b. Tagging before Alignment: Integrating Multi-Modal Tags for Video-Text Retrieval. In *AAAI Conference on Artificial Intelligence*. arXiv. ArXiv:2301.12644 [cs].

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, Bin Li, Ping Luo, Tong Lu, Yu Qiao, and Jifeng Dai. 2023c. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. *arXiv preprint arXiv:2312.14238*.

Xing Cheng, Hezheng Lin, Xiangyu Wu, Fan Yang, and Dong Shen. 2021. Improving video-text retrieval by multi-stream corpus alignment and dual softmax loss. *CoRR*, abs/2109.04290.

Ioana Croitoru, Simion-Vlad Bogolin, Marius Leordeanu, Hailin Jin, Andrew Zisserman, Samuel Albanie, and Yang Liu. 2021. Teachtext: Crossmodal generalized distillation for text-video retrieval. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pages 11563–11573. IEEE.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for*

Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Jianfeng Dong, Xirong Li, Chaoxi Xu, Shouling Ji, Yuan He, Gang Yang, and Xun Wang. 2019. Dual encoding for zero-example video retrieval. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pages 9346–9355. Computer Vision Foundation / IEEE.

Maksim Dzabraev, Maksim Kalashnikov, Stepan Komkov, and Aleksandr Petiushko. 2021. MDMMT: multidomain multimodal transformer for video retrieval. In *IEEE Conference on Computer Vision and Pattern Recognition Workshops, CVPR Workshops 2021, virtual, June 19-25, 2021*, pages 3354–3363. Computer Vision Foundation / IEEE.

Bernard Ghanem Fabian Caba Heilbron, Victor Escorcia and Juan Carlos Niebles. 2015. Activitynet: A large-scale video benchmark for human activity understanding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 961–970.

Xiang Fang, Daizong Liu, Pan Zhou, and Yuchong Hu. 2022. Multi-modal cross-domain alignment network for video moment retrieval. *IEEE Transactions on Multimedia*.

Valentin Gabeur, Chen Sun, Karteek Alahari, and Cordelia Schmid. 2020. Multi-modal transformer for video retrieval. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part IV*, volume 12349 of *Lecture Notes in Computer Science*, pages 214–229. Springer.

Zhe Gan, Yen-Chun Chen, Linjie Li, Chen Zhu, Yu Cheng, and Jingjing Liu. 2020. Large-scale adversarial training for vision-and-language representation learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Zijian Gao, Jingyu Liu, Sheng Chen, Dedan Chang, Hao Zhang, and Jinwei Yuan. 2021. CLIP2TV: an empirical study on transformer-based methods for video-text retrieval. *CoRR*, abs/2111.05610.

Satya Krishna Gorti, Noël Vouitsis, Junwei Ma, Keyvan Golestan, Maksims Volkovs, Animesh Garg, and Guangwei Yu. 2022. X-pool: Cross-modal language-video attention for text-video retrieval. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2022, New Orleans, LA, USA, June 18-24, 2022*, pages 4996–5005. IEEE.

Qingpei Guo, Furong Xu, Hanxiao Zhang, Wang Ren, Ziping Ma, Lin Ju, Jian Wang, Jingdong Chen, and Ming Yang. 2024. M2-encoder: Advancing bilingual image-text understanding by large-scale efficient pre-training.

Siteng Huang, Biao Gong, Yulin Pan, Jianwen Jiang, Yiliang Lv, Yuyuan Li, and Donglin Wang. 2023. VoP: Text-Video Co-Operative Prompt Tuning for Cross-Modal Retrieval. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6565–6574.

Mark J. Huiskes and Michael S. Lew. 2008. The MIR Flickr Retrieval Evaluation. In *Proceedings of the 1st ACM International Conference on Multimedia Information Retrieval*, MIR '08, pages 39–43, New York, NY, USA. Association for Computing Machinery. Event-place: Vancouver, British Columbia, Canada.

Weike Jin, Zhou Zhao, Pengcheng Zhang, Jieming Zhu, Xiuqiang He, and Yueting Zhuang. 2021. Hierarchical cross-modal graph consistency learning for video-text retrieval. In *SIGIR '21: The 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, Virtual Event, Canada, July 11-15, 2021*, pages 1114–1124. ACM.

Jie Lei, Linjie Li, Luowei Zhou, Zhe Gan, Tamara L. Berg, Mohit Bansal, and Jingjing Liu. 2021. Less is more: Clipbert for video-and-language learning via sparse sampling. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, pages 7331–7341. Computer Vision Foundation / IEEE.

Kunchang Li, Yali Wang, Yizhuo Li, Yi Wang, Yinan He, Limin Wang, and Yu Qiao. 2023. Unmasked teacher: Towards training-efficient video foundation models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19948–19960.

Linjie Li, Yen-Chun Chen, Yu Cheng, Zhe Gan, Licheng Yu, and Jingjing Liu. 2020a. HERO: Hierarchical encoder for Video+Language omni-representation pre-training. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2046–2065, Online. Association for Computational Linguistics.

Xiujun Li, Xi Yin, Chunyuan Li, Pengchuan Zhang, Xiaowei Hu, Lei Zhang, Lijuan Wang, Houdong Hu, Li Dong, Furu Wei, Yejin Choi, and Jianfeng Gao. 2020b. Oscar: Object-semantics aligned pre-training for vision-language tasks. In *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XXX*, volume 12375 of *Lecture Notes in Computer Science*, pages 121–137. Springer.

Weixin Liang, Yuhui Zhang, Yongchan Kwon, Serena Yeung, and James Zou. 2022. Mind the gap: Understanding the modality gap in multi-modal contrastive representation learning. In *Advances in neural information processing systems*.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. 2014. Microsoft COCO: Common Objects in Context. In *Computer Vision –*

ECCV 2014, pages 740–755, Cham. Springer International Publishing.

Alexander Liu, SouYoung Jin, Cheng-I Lai, Andrew Rouditchenko, Aude Oliva, and James Glass. 2022a. Cross-modal discrete representation learning. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3013–3035, Dublin, Ireland. Association for Computational Linguistics.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2023a. Improved baselines with visual instruction tuning.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024. Llava-next: Improved reasoning, ocr, and world knowledge.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023b. Visual instruction tuning.

Ruyang Liu, Chen Li, Yixiao Ge, Ying Shan, Thomas H Li, and Ge Li. 2023c. One for all: Video conversation is feasible without video instruction tuning. *arXiv preprint arXiv:2309.15785*.

Yuqi Liu, Pengfei Xiong, Luhui Xu, Shengming Cao, and Qin Jin. 2022b. Ts2-net: Token shift and selection transformer for text-video retrieval. In *Computer Vision - ECCV 2022 - 17th European Conference, Tel Aviv, Israel, October 23-27, 2022, Proceedings, Part XIV*, volume 13674 of *Lecture Notes in Computer Science*, pages 319–335. Springer.

Huaishao Luo, Lei Ji, Ming Zhong, Yang Chen, Wen Lei, Nan Duan, and Tianrui Li. 2022. Clip4clip: An empirical study of CLIP for end to end video clip retrieval and captioning. *Neurocomputing*, 508:293–304.

Yiwei Ma, Guohai Xu, Xiaoshuai Sun, Ming Yan, Ji Zhang, and Rongrong Ji. 2022. X-CLIP: End-to-end multi-grained contrastive learning for video-text retrieval. In *ACM international conference on multimedia*, MM '22, pages 638–647, New York, NY, USA. Association for Computing Machinery. Number of pages: 10 Place: Lisboa, Portugal.

Antoine Miech, Jean-Baptiste Alayrac, Lucas Smaira, Ivan Laptev, Josef Sivic, and Andrew Zisserman. 2020. End-to-end learning of visual representations from uncurated instructional videos. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pages 9876–9886. Computer Vision Foundation / IEEE.

Antoine Miech, Dimitri Zhukov, Jean-Baptiste Alayrac, Makarand Tapaswi, Ivan Laptev, and Josef Sivic. 2019. Howto100m: Learning a text-video embedding by watching hundred million narrated video clips. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, pages 2630–2640. IEEE.

Jae Sung Park, Sheng Shen, Ali Farhadi, Trevor Darrell, Yejin Choi, and Anna Rohrbach. 2022a. Exposing the limits of video-text models through contrast sets. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3574–3586, Seattle, United States. Association for Computational Linguistics.

Yookoon Park, Mahmoud Azab, Seungwhan Moon, Bo Xiong, Florian Metze, Gourab Kundu, and Kirmani Ahmed. 2022b. Normalized contrastive learning for text-video retrieval. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 248–260, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763. PMLR.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

Stephen E Robertson and Steve Walker. 1994. Some simple effective approximations to the 2-poisson model for probabilistic weighted retrieval. In *SIGIR'94: Proceedings of the Seventeenth Annual International ACM-SIGIR Conference on Research and Development in Information Retrieval, organised by Dublin City University*, pages 232–241. Springer.

Mike Schuster and Kuldip K. Paliwal. 1997. Bidirectional recurrent neural networks. *IEEE Trans. Signal Process.*, 45(11):2673–2681.

Nina Shvetsova, Brian Chen, Andrew Rouditchenko, Samuel Thomas, Brian Kingsbury, Rogerio Feris, David Harwath, James Glass, and Hilde Kuehne. 2022. Everything at Once – Multi-modal Fusion Transformer for Video Retrieval. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 19988–19997, New Orleans, LA, USA. IEEE.

Amanpreet Singh, Ronghang Hu, Vedanuj Goswami, Guillaume Couairon, Wojciech Galuba, Marcus Rohrbach, and Douwe Kiela. 2022. FLAVA: A foundational language and vision alignment model. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2022, New Orleans, LA, USA, June 18-24, 2022*, pages 15617–15629. IEEE.

Benny J Tang, Angie Boggust, and Arvind Satyanarayan. 2023. Vistext: A benchmark for semantically rich chart captioning. *arXiv preprint arXiv:2307.05356*.

Yoad Tewel, Yoav Shalev, Roy Nadler, Idan Schwartz, and Lior Wolf. 2022. Zero-shot video captioning with evolving pseudo-tokens. *arXiv preprint arXiv:2207.11100*.

Yoad Tewel, Yoav Shalev, Idan Schwartz, and Lior Wolf. 2021. Zero-shot image-to-text generation for visual-semantic arithmetic. *arXiv preprint arXiv:2111.14447*, 1(3):6.

Anthony Meng Huat Tiong, Junnan Li, Boyang Li, Silvio Savarese, and Steven C.H. Hoi. 2022. Plug-and-play VQA: Zero-shot VQA by conjoining large pre-trained models with zero training. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 951–967, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. Llama 2: Open foundation and fine-tuned chat models.

Alex Jinpeng Wang, Yixiao Ge, Guanyu Cai, Rui Yan, Xudong Lin, Ying Shan, Xiaohu Qie, and Mike Zheng Shou. 2022a. Object-aware Video-language Pre-training for Retrieval. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3303–3312, New Orleans, LA, USA. IEEE.

Haoran Wang, Di Xu, Dongliang He, Fu Li, Zhong Ji, Jungong Han, and Errui Ding. 2022b. Boosting video-text retrieval with explicit high-level semantics. In *MM '22: The 30th ACM International Conference on Multimedia, Lisboa, Portugal, October 10 - 14, 2022*, pages 4887–4898. ACM.

Junke Wang, Dongdong Chen, Zuxuan Wu, Chong Luo, Luowei Zhou, Yucheng Zhao, Yujia Xie, Ce Liu, Yu-Gang Jiang, and Lu Yuan. 2022c. Omnivl: One foundation model for image-language and video-language tasks. In *Advances in Neural Information Processing Systems*, volume 35, pages 5696–5710. Curran Associates, Inc.

Xiaohan Wang, Linchao Zhu, Zhedong Zheng, Mingliang Xu, and Yi Yang. 2022d. Align and tell: Boosting text-video retrieval with local alignment and fine-grained supervision. *IEEE Transactions on Multimedia*, pages 1–11.

Yimu Wang, Shiyin Lu, and Lijun Zhang. 2020a. Searching privately by imperceptible lying: A novel private hashing method with differential privacy. In *Proceedings of the 28th ACM International Conference on Multimedia*, page 2700–2709.

Yimu Wang and Peng Shi. 2023a. Video-Text Retrieval by Supervised Multi-Space Multi-Grained Alignment. ArXiv:2302.09473 [cs].

Yimu Wang and Peng Shi. 2023b. Video-text retrieval by supervised sparse multi-grained learning. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 633–649, Singapore. Association for Computational Linguistics.

Yimu Wang, Xiu-Shen Wei, Bo Xue, and Lijun Zhang. 2020b. Piecewise hashing: A deep hashing method for large-scale fine-grained search. In *Pattern Recognition and Computer Vision - Third Chinese Conference, PRCV 2020, Nanjing, China, October 16-18, 2020, Proceedings, Part II*, pages 432–444.

Yimu Wang, Bo Xue, Quan Cheng, Yuhui Chen, and Lijun Zhang. 2021. Deep unified cross-modality hashing by pairwise data alignment. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21*, pages 1129–1135.

Zhenhailong Wang, Manling Li, Ruochen Xu, Luowei Zhou, Jie Lei, Xudong Lin, Shuohang Wang, Ziyi Yang, Chenguang Zhu, Derek Hoiem, Shih-Fu Chang, Mohit Bansal, and Heng Ji. 2022e. Language models with image descriptors are strong few-shot video-language learners. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*.

Wenhao Wu, Haipeng Luo, Bo Fang, Jingdong Wang, and Wanli Ouyang. 2023. Cap4Video: What Can Auxiliary Captions Do for Text-Video Retrieval? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10704–10713.

Xing Wu, Chaochen Gao, Zijia Lin, Zhongyuan Wang, Jizhong Han, and Songlin Hu. 2022. RaP: Redundancy-aware video-language pre-training for text-video retrieval. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 3036–3047, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Haiyang Xu, Qinghao Ye, Ming Yan, Yaya Shi, Jiabo Ye, Yuanhong Xu, Chenliang Li, Bin Bi, Qi Qian, Wei Wang, Guohai Xu, Ji Zhang, Songfang Huang, Fei Huang, and Jingren Zhou. 2023. mplug-2: A modularized multi-modal foundation model across text, image and video. *ArXiv*, abs/2302.00402.

Hu Xu, Gargi Ghosh, Po-Yao Huang, Prahal Arora, Masoumeh Aminzadeh, Christoph Feichtenhofer, Florian Metze, and Luke Zettlemoyer. 2021a. VLM: Task-agnostic video-language model pre-training for video understanding. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 4227–4239, Online. Association for Computational Linguistics.

Hu Xu, Gargi Ghosh, Po-Yao Huang, Dmytro Okhonko, Armen Aghajanyan, Florian Metze, Luke Zettlemoyer, and Christoph Feichtenhofer. 2021b. Video-CLIP: Contrastive pre-training for zero-shot video-text understanding. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6787–6800, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Jun Xu, Tao Mei, Ting Yao, and Yong Rui. 2016. MSR-VTT: A Large Video Description Dataset for Bridging Video and Language. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5288–5296, Las Vegas, NV, USA. IEEE.

Hongwei Xue, Yuchong Sun, Bei Liu, Jianlong Fu, Ruihua Song, Houqiang Li, and Jiebo Luo. 2023. CLIP-ViP: Adapting Pre-trained Image-Text Model to Video-Language Alignment. In *The Eleventh International Conference on Learning Representations*.

Qiying Yu, Yang Liu, Yimu Wang, Ke Xu, and Jingjing Liu. 2023. Multimodal federated learning via contrastive representation ensemble. In *The Eleventh International Conference on Learning Representations*.

Youngjae Yu, Jongseok Kim, and Gunhee Kim. 2018. A joint sequence fusion model for video question answering and retrieval. In *Computer Vision - ECCV 2018 - 15th European Conference, Munich, Germany, September 8-14, 2018, Proceedings, Part VII*, volume 11211 of *Lecture Notes in Computer Science*, pages 487–503. Springer.

Youngjae Yu, Hyungjin Ko, Jongwook Choi, and Gunhee Kim. 2017. End-to-end concept word detection for video captioning, retrieval, and question answering. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pages 3261–3269. IEEE Computer Society.

Shuai Zhao, Linchao Zhu, Xiaohan Wang, and Yi Yang. 2022. Centerclip: Token clustering for efficient text-video retrieval. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '22, page 970–981, New York, NY, USA. Association for Computing Machinery.

Bin Zhu, Bin Lin, Munan Ning, Yang Yan, Jiaxi Cui, WANG HongFa, Yatian Pang, Wenhao Jiang, Junwu Zhang, Zongwei Li, Cai Wan Zhang, Zhifeng Li, Wei Liu, and Li Yuan. 2024. Languagebind: Extending video-language pretraining to n-modality by language-based semantic alignment. In *The Twelfth International Conference on Learning Representations*.

Linchao Zhu and Yi Yang. 2020. Actbert: Learning global-local video-text representations. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pages 8743–8752. Computer Vision Foundation / IEEE.

A   Experiments

A.1   Details of Benchmarks

- **MSR-VTT** (Xu et al., 2016) contains 10,000 videos with length varying from 10 to 32 seconds, each paired with about 20 human-labeled captions. Following the evaluation protocol from previous works (Yu et al., 2018; Miech et al., 2019), we use the training-9k / test 1k-A splits for training and testing respectively.

- **MSVD** (Chen and Dolan, 2011) contains 1,970 videos with a split of 1200, 100, and 670 as the train, validation, and test set, respectively. The duration of videos varies from 1 to 62 seconds. Each video is paired with 40 English captions.

- **ActivityNet** (Fabian Caba Heilbron and Niebles, 2015) is consisted of 20,000 Youtube videos with 100,000 densely annotated descriptions. For a fair comparison, following the previous setting (Luo et al., 2022; Gabeur et al., 2020), we concatenate all captions together as a paragraph to perform a video-paragraph retrieval task by concatenating all the descriptions of a video. Performances are reported on the "val1" split of the ActivityNet.

A.2   Choice of Retrieval Methods

In this part, we investigate the impact of different retrieval methods, *i.e.*, BM25 (Robertson and Walker, 1994) and sentence transformers (Reimers and Gurevych, 2019). The results are shown in section 5. It shows that BM25 outperforms the sentence transformer.

Retrieval Methods	Text-to-Video Retrieval					Video-to-Text Retrieval				
	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓	R@1↑	R@5↑	R@10↑	MdR↓	MnR↓
BM25	**58.2**	**75.8**	**83.9**	1.0	**18.9**	**36.4**	56.5	63.8	3.0	75.7
Sentence Transformer	41.2	62.1	70.5	2.0	33.5	34.7	**57.8**	**67.5**	3.0	**36.0**

Table 8: Retrieval performance with different retrieval models on MSR-VTT using HALISIE. Best in **Bold**.