Free Lunch for Few-shot Learning: Distribution Calibration

Abstract

Learning from a limited number of samples is challenging since the learned model can easily become overfitted based on the biased distribution formed by only a few training examples. In this paper, we calibrate the distribution of these few-sample classes by transferring statistics from the classes with sufficient examples, then an adequate number of examples can be sampled from the calibrated distribution to expand the inputs to the classifier. We assume every dimension in the feature representation follows a Gaussian distribution so that the mean and the variance of the distribution can borrow from that of similar classes whose statistics are better estimated with an adequate number of samples. Our method can be built on top of off-the-shelf pretrained feature extractors and classification models without extra learnable parameters. We show that a simple logistic regression classifier trained using the features sampled from our calibrated distribution can outperform the state-of-the-art accuracy on two datasets ($\sim$5% improvement on *mini*ImageNet compared to the next best). The visualization of these generated features demonstrates that our calibrated distribution is an accurate estimation.

1 Introduction

Learning from a limited number of training samples has drawn increasing attention due to the high cost of collecting and annotating a large amount of data. Researchers have developed algorithms to improve the performance of models that have been trained with very few data. Finn et al. (2017); Snell et al. (2017) train models in a meta-learning fashion so that the model can adapt quickly on tasks with only a few training samples available. Hariharan & Girshick (2017); Wang et al. (2018b) try to synthesize data or features by learning a generative model to alleviate the data insufficiency problem. Ren et al. (2018) propose to leverage unlabeled data and predict pseudo labels to improve the performance of few-shot learning.

Table 1: The class mean similarity ("mean sim") and class variance similarity ("var sim") between Arctic fox and different classes.

	Arctic fox	
	mean sim	var sim
white wolf	97%	97%
malamute	85%	78%
lion	81%	70%
meerkat	78%	70%
jellyfish	46%	26%
orange	40%	19%
beer bottle	34%	11%

While most previous works focus on developing stronger models, scant attention has been paid to the property of the data itself. It is natural that when the number of data grows, the ground truth distribution can be more accurately uncovered. Models trained with a wide coverage of data can generalize well during evaluation. On the other hand, when training a model with only a few training data, the model tends to overfit on these few samples by minimizing the training loss over these samples. These phenomena are illustrated in Figure 1. This biased distribution based on a few examples can damage the generalization ability of the model since it is far from mirroring the ground truth distribution from which test cases are sampled during evaluation.

Here, we consider calibrating this biased distribution into a more accurate approximation of the ground truth distribution. In this way, a model trained with inputs sampled from the calibrated distribution can generalize over a broader range of data from a more accurate distribution rather than only fitting itself to those few samples. Instead of calibrating the distribution of the original data space, we try to calibrate the distribution in the feature space, which has much lower dimensions and is easier to calibrate (Xian et al. (2018)). We assume every dimension in the feature vectors follows

Figure 1: Training a classifier from few-shot features makes the classifier overfit to the few examples (Left). Classifier trained with features sampled from calibrated distribution has better generalization ability (Right).

a Gaussian distribution and observe that similar classes usually have similar mean and variance of the feature representations, as shown in Table 1. Thus, the mean and variance of the Gaussian distribution can be transferred across similar classes (Salakhutdinov et al. (2012)). Meanwhile, the statistics can be estimated more accurately when there are adequate samples for this class. Based on these observations, we reuse the statistics from many-shot classes and transfer them to better estimate the distribution of the few-shot classes according to their class similarity. More samples can be generated according to the estimated distribution which provides sufficient supervision for training the classification model.

In the experiments, we show that a simple logistic regression classifier trained with our strategy can achieve state-of-the-art accuracy on two datasets. Our distribution calibration strategy can be paired with any classifier and feature extractor with no extra learnable parameters. Training with samples selected from the calibrated distribution can achieve 12% accuracy gain compared to the baseline which is only trained with the few samples given in a 5way1shot task. We also visualize the calibrated distribution and show that it is an accurate approximation of the ground truth that can better cover the test cases.

2 RELATED WORKS

Few-shot classification is a challenging machine learning problem and researchers have explored the idea of learning to learn or meta-learning to improve the quick adaptation ability to alleviate the few-shot challenge. One of the most general algorithms for meta-learning is the optimization-based algorithm. Finn et al. (2017) and Li et al. (2017) proposed to learn how to optimize the gradient descent procedure so that the learner can have a good initialization, update direction, and learning rate. For the classification problem, researchers proposed simple but effective algorithms based on metric learning. MatchingNet (Vinyals et al. (2016)) and ProtoNet (Snell et al. (2017)) learned to classify samples by comparing the distance to the representatives of each class. Our distribution calibration and feature sampling procedure does not include any learnable parameters and the classifier is trained in a traditional supervised learning way.

Another line of algorithms is to compensate for the insufficient number of available samples by generation. Most methods use the idea of Generative Adversarial Networks (GANs) (Goodfellow et al., 2014) or autoencoder (Rum) to generate samples (Zhang et al. (2018); Chen et al. (2019); Schwartz et al. (2018); Gao et al. (2018)) or features (Xian et al. (2018); Zhang et al. (2019)) to augment the training set. Specifically, Zhang et al. (2018) and Xian et al. (2018) proposed to synthesize data by introducing an adversarial generator conditioned on tasks. Zhang et al. (2019) tried to learn a variational autoencoder to approximate the distribution and predict labels based on the estimated statistics. The autoencoder can also augment samples by projecting between the visual space and the semantic space (Chen et al., 2019) or encoding the intra-class deformations (Schwartz et al., 2018). While these methods can generate extra samples or features for training, they require the design of a complex model and loss function to learn how to generate. However, our distribution calibration strategy is simple and does not need extra learnable parameters.

Data augmentation is a traditional and effective way of increasing the number of training samples. Qin et al. (2020) and Antoniou & Storkey (2019) proposed the used of the traditional data augmen-

tation technique to construct pretext tasks for unsupervised few-shot learning. Wang et al. (2018a) and Hariharan & Girshick (2017) leveraged the general idea of data augmentation, they designed a hallucination model to generate the augmented version of the image with different choices for the model's input, i.e., an image and a noise (Wang et al., 2018a) or the concatenation of multiple features (Hariharan & Girshick, 2017). Park et al. (2020) tried to augment feature representations by sampling from an estimated variance. These methods learn to augment from the original samples or their feature representation while we try to estimate the class-level distribution and thus can eliminate the inductive bias from a single sample and provide more diverse generations from the calibrated distribution.

3   MAIN APPROACH

In this section, we introduce the few-shot classification problem definition in Section 3.1 and details of our proposed approach in Section 3.2.

3.1   PROBLEM DEFINITION

We follow a typical few-shot classification setting. Given a dataset with data-label pairs $\mathcal{D} = \{(\boldsymbol{x}_i, y_i)\}$ where $\boldsymbol{x}_i \in \mathbb{R}^d$ is the feature vector of a sample and $y_i \in C$, where C denotes the set of classes. This set of classes is divided into *base classes* C_b and *novel classes* C_n, where $C_b \cap C_n = \emptyset$ and $C_b \cup C_n = C$. The goal is to train a model on the data from the base classes so that the model can generalize well on tasks sampled from the novel classes. In order to evaluate the fast adaptation ability or the generalization ability of the model, there are only a few available labeled samples for each task $\mathcal{T}$. The most common way to build a task is called an N-way-K-shot task (Vinyals et al. (2016)), where N classes are sampled from the novel set and only K (e.g., 1 or 5) labeled samples are provided for each class. The few available labeled data are called *support set* $\mathcal{S} = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^{N \times K}$ and the model is evaluated on another query set $\mathcal{Q} = \{(\boldsymbol{x}_i, y_i)\}_{i=N \times K+1}^{N \times K + N \times q}$, where every class in the task has q test cases. Thus, the performance of a model is evaluated as the averaged accuracy on (the query set of) multiple tasks sampled from the novel classes.

3.2   DISTRIBUTION CALIBRATION

As introduced in Section 3.1, the base classes have a sufficient amount of data while the evaluation tasks sampled from the novel classes only have a limited number of labeled samples. The statistics of the distribution for the base class can be estimated more accurately compared to the estimation based on few-shot samples, which is an ill-posed problem. As shown in Table 1, we observe that if we assume the feature distribution is Gaussian, the mean and variance with respect to each class are correlated to the semantic similarity of each class. With this in mind, the statistics can be transferred from the base classes to the novel classes if we learn how similar the two classes are. In the following sections, we discuss how we calibrate the distribution estimation of the classes with only a few samples (Section 3.2.2) with the help of the statistics of the base classes (Section 3.2.1). We will also elaborate on how do we leverage the calibrated distribution to improve the performance of few-shot learning (Section 3.2.3).

Note that our distribution calibration strategy is over the feature-level and is agnostic to any feature extractor. Thus, it can be built on top of any pretrained feature extractors without further costly fine-tuning. In our experiments, we use the pretrained WideResNet following previous work (Mangla et al. (2020)). The WideResNet is trained to classify the base classes, along with a self-supervised pretext task to learn the general-purpose representations suitable for image understanding tasks. Please refer to their paper for more details on training the feature extractor.

3.2.1   STATISTICS OF THE BASE CLASSES

We assume the feature distribution of base classes is Gaussian. The mean of the feature vector from a base class i is calculated as the mean of every single dimension in the vector:

$$\boldsymbol{\mu}_i = \frac{\sum_{j=1}^{n_i}(\boldsymbol{x}_j)}{n_i}, \tag{1}$$

Algorithm 1 Training procedure for an N-way-K-shot task

Require: Support set features $\mathcal{S} = (\boldsymbol{x}_i, y)_{i=1}^{N \times K}$
Require: Base classes' statistics $\{\boldsymbol{\mu}_i\}_{i=1}^{|C_b|}, \{\boldsymbol{\Sigma}_i\}_{i=1}^{|C_b|}$
 1: Transform $(\boldsymbol{x}_i)_{i=1}^{N \times K}$ with Tukey's Ladder of Powers as Equation 3
 2: **for** $(\boldsymbol{x}_i, y_i) \in \mathcal{S}$ **do**
 3:     Calibrate the mean $\boldsymbol{\mu}'$ and the covariance $\boldsymbol{\Sigma}'$ for class y_i using $\boldsymbol{x}_i$ with Equation 6
 4:     Sample features for class y_i from the calibrated distribution as Equation 7
 5: **end for**
 6: Train a classifier using both support set features and all sampled features as Equation 8

---

where $\boldsymbol{x}_j$ is a feature vector of the j-th sample from the base class i and n_i is the total number of samples in class i. As the feature vector $\boldsymbol{x}_j$ is multi-dimensional, we use covariance for a better representation of the variance between any pair of elements in the feature vector. The covariance matrix $\boldsymbol{\Sigma}_i$ for the features from class i is calculated as:

$$\boldsymbol{\Sigma}_i = \frac{1}{n_i - 1} \sum_{j=1}^{n_i} (\boldsymbol{x}_j - \boldsymbol{\mu}_i) (\boldsymbol{x}_j - \boldsymbol{\mu}_i)^T. \tag{2}$$

3.2.2 Calibrating statistics of the novel classes

Here, we consider an N-way-K-shot task sampled from the novel classes.

Tukey's Ladder of Powers Transformation

To make the feature distribution more Gaussian-like, we first transform the features of the support set and query set in the target task using Tukey's Ladder of Powers transformation (Tukey (1977)). Tukey's Ladder of Powers transformation is a family of power transformations which can reduce the skewness of distributions and make distributions more Gaussian-like. Tukey's Ladder of Powers transformation is formulated as:

$$\tilde{\mathbf{x}} = \left\{ \begin{array}{ll} \boldsymbol{x}^\lambda & \text{if } \lambda \neq 0 \\ \log(\boldsymbol{x}) & \text{if } \lambda = 0 \end{array} \right. \tag{3}$$

where λ is a hyper-parameter to adjust how to correct the distribution. The original feature can be recovered by setting λ as 1. Decreasing λ makes the distribution less positively skewed and vice versa.

Calibration through statistics transfer

Using the statistics from the base classes introduced in Section 3.2.1, we transfer the statistics from the base classes which are estimated more accurately on sufficient data to the novel classes. The transfer is based on the Euclidean distance between the feature space of the novel classes and the mean of the features from the base classes $\boldsymbol{\mu}_i$ as computed in Equation 1. Specifically, we select the top k base classes with the closest distance to the feature of a sample $\tilde{\boldsymbol{x}}$ from the support set:

$$\mathbb{S}_d = \{ -\|\boldsymbol{\mu}_i - \tilde{\boldsymbol{x}}\|^2 \mid i \in C_b \}, \tag{4}$$

$$\mathbb{S}_N = \{ i \mid -\|\boldsymbol{\mu}_i - \tilde{\boldsymbol{x}}\|^2 \in topk(\mathbb{S}_d) \}, \tag{5}$$

where $topk(\cdot)$ is an operator to select the top elements from the input distance set $\mathbb{S}_d$. $\mathbb{S}_N$ stores the k nearest base classes with respect to a feature vector $\tilde{\boldsymbol{x}}$. Then, the mean and covariance of the distribution is calibrated by the statistics from the nearest base classes:

$$\boldsymbol{\mu}' = \frac{\Sigma_{i \in \mathbb{S}_N} \boldsymbol{\mu}_i + \tilde{\boldsymbol{x}}}{k+1}, \boldsymbol{\Sigma}' = \frac{\Sigma_{i \in \mathbb{S}_N} \boldsymbol{\Sigma}_i}{k} + \alpha, \tag{6}$$

where α is a hyper-parameter that determines the degree of dispersion of features sampled from the calibrated distribution.

For few-shot learning with more than one shot, the aforementioned procedure of the distribution calibration should be undertaken multiple times with each time using one feature vector from the support set. This avoids the bias provided by one specific sample and potentially achieves more diverse and accurate distribution estimation. Thus, for simplicity, we denote the calibrated distribution as a set

Table 2: 5way1shot and 5way5shot classification results on *mini*ImageNet and CUB with 95% confidence intervals. We report our Distribution Calibration (DC) on two linear classifiers: SVM and Logistic Regression. The numbers in **bold** have intersecting confidence intervals with the most accurate method.

Methods	*mini*ImageNet		CUB	
	5way1shot	5way5shot	5way1shot	5way5shot
Optimization-based				
MAML (Finn et al. (2017))	48.70 ± 1.84	63.10 ± 0.92	50.45 ± 0.97	59.60 ± 0.84
Meta-SGD (Li et al. (2017))	50.47 ± 1.87	64.03 ± 0.94	53.34 ± 0.97	67.59 ± 0.82
LEO (Rusu et al. (2019))	61.76 ± 0.08	77.59 ± 0.12	-	-
E3BM (Liu et al. (2020b))	63.80 ± 0.40	80.29 ± 0.25	-	-
Metric-based				
Matching Net (Vinyals et al. (2016))	43.56 ± 0.84	55.31 ± 0.73	56.53 ± 0.99	63.54 ± 0.85
Prototypical Net (Snell et al. (2017))	54.16 ± 0.82	73.68 ± 0.65	72.99 ± 0.88	86.64 ± 0.51
Baseline++ (Chen et al. (2019))	51.87 ± 0.77	75.68 ± 0.63	67.02 ± 0.90	83.58 ± 0.54
Variational Few-shot(Zhang et al. (2019))	61.23 ± 0.26	77.69 ± 0.17	-	-
Negative-Cosine(Liu et al. (2020a))	62.33 ± 0.82	80.94 ± 0.59	72.66 ± 0.85	89.40 ± 0.43
Generation-based				
MetaGAN (Zhang et al. (2018))	52.71 ± 0.64	68.63 ± 0.67	-	-
Delta-Encoder (Schwartz et al. (2018))	59.9	69.7	69.8	82.6
TriNet (Chen et al. (2019))	58.12 ± 1.37	76.92 ± 0.69	69.61 ± 0.46	84.10 ± 0.35
Meta Variance Transfer (Park et al. (2020))	-	67.67 ± 0.70	-	80.33 ± 0.61
SVM with DC (Ours)	$\mathbf{67.31 \pm 0.83}$	$\mathbf{82.30 \pm 0.34}$	$\mathbf{79.49 \pm 0.33}$	$\mathbf{90.26 \pm 0.98}$
Logistic Regression with DC (Ours)	$\mathbf{68.57 \pm 0.55}$	$\mathbf{82.88 \pm 0.42}$	$\mathbf{79.56 \pm 0.87}$	$\mathbf{90.67 \pm 0.35}$

of statistics. For a class $y \in C_n$, we denote the set of statistics as $\mathbb{S}_y = \{(\boldsymbol{\mu}_1^{'}, \boldsymbol{\Sigma}_1^{'}), ..., (\boldsymbol{\mu}_K^{'}, \boldsymbol{\Sigma}_K^{'})\}$, where $\boldsymbol{\mu}_i^{'}, \boldsymbol{\Sigma}_i^{'}$ are the calibrated mean and covariance, respectively, computed based on the i-th feature in the support set of class y. Here, the size of the set is the value of K for an N-way-K-shot task.

3.2.3 How to leverage the calibrated distribution?

With a set of calibrated statistics $\mathbb{S}_y$ for class y in a target task, we generate a set of feature vectors with label y by sampling from the calibrated Gaussian distributions:

$$\mathbb{D}_y = \{(\boldsymbol{x}, y) | \boldsymbol{x} \sim \mathcal{N}(\boldsymbol{\mu}, \boldsymbol{\Sigma}), \forall (\boldsymbol{\mu}, \boldsymbol{\Sigma}) \in \mathbb{S}^y\}. \tag{7}$$

Here, the total number of generated features per class is set as a hyperparameter and they are equally distributed for every calibrated distribution in $\mathbb{S}_y$. The generated features along with the original support set features for a few-shot task is then served as the training data for a task-specific classifier. We train the classifier for a task by minimizing the cross-entropy loss over both the features of its support set $\mathcal{S}$ and the generated features $\mathbb{D}_y$:

$$\ell = \sum_{(\boldsymbol{x}, y) \sim \tilde{\mathcal{S}} \cup \mathbb{D}_{y}, y \in \mathcal{Y}^{\mathcal{T}}} - \log \Pr(y|\boldsymbol{x}; \theta), \tag{8}$$

where $\mathcal{Y}^{\mathcal{T}}$ is the set of classes for the task $\mathcal{T}$. $\tilde{\mathcal{S}}$ denotes the support set with features transformed by Turkey's Ladder of Powers transformation and the classifier model is parameterized by θ.

4 Experiments

In this section, we answer the following questions:

- How does our distribution calibration strategy perform compared to the state-of-the-art methods?

- What does calibrated distribution look like? Is it an accurate approximation for this class?

- How does Tukey's Ladder of Power transformation interact with the feature generations? How important is each in relation to performance?

4.1 EXPERIMENTAL SETUP

4.1.1 DATASETS

We evaluate our distribution calibration strategy on *mini*ImageNet (Ravi & Larochelle (2017)) and CUB (Welinder et al. (2010)). *mini*ImageNet has a brand range of classes including various animals and objects while CUB is a more fine-grained dataset that includes various species of birds. Datasets with different levels of granularity may have different distributions for their feature space. We want to show the effectiveness and generality of our strategy on both.

***mini*ImageNet** is derived from ILSVRC-12 dataset (Russakovsky et al. (2014)). It contains 100 diverse classes with 600 samples per class. The image size is $84 \times 84 \times 3$. We follow the splits used in previous works (Ravi & Larochelle (2017)), which split the dataset into 64 base classes, 16 validation classes, and 20 novel classes.

CUB is a fine-grained few-shot classification benchmark. It contains 200 different classes of birds with a total of 11,788 images of size $84 \times 84 \times 3$. Following previous works (Chen et al., 2019), we split the dataset into 100 base classes, 50 validation classes, and 50 novel classes.

4.1.2 EVALUATION METRIC

We use the top-1 accuracy as the evaluation metric to measure the performance of our method. We report the accuracy on 5way1shot and 5way5shot settings for both *mini*ImageNet and CUB. The reported results are the averaged classification accuracy over 10,000 tasks.

4.1.3 IMPLEMENTATION DETAILS

For feature extractor, we use the WideResNet trained following previous work (Mangla et al. (2020)). For each dataset, we train the feature extractor with base classes and test the performance using novel classes. Note that the feature representation is extracted from the penultimate layer (with a ReLU activation function) from the feature extractor, thus the values are all non-negative so that the inputs to Tukey's Ladder of Powers transformation in Equation 3 are valid. At the distribution calibration stage, we compute the base class statistics and transfer them to calibrate novel class distribution for each dataset. Two simple linear classifiers are considered in our experiment, logistic regression (LR) and support vector machine (SVM), we use the implementation of scikit-learn (Pedregosa et al. (2011)) with the default settings. The source code is available at the anonymous link: `https://anonymous.4open.science/r/4d235eef-03e5-47a2-89e8-ea18f7cb3122/`

4.2 COMPARISION TO STATE-OF-THE-ART

Table 2 presents the 5way1shot and 5way5shot classification results of our method on both *mini*ImageNet and CUB. We compare our method with the three groups of the few-shot learning method, *optimization-based*, *metric-based*, and *generation-based*. Our method can be built on top of any classifier, and we use two popular and simple classifiers, namely SVM and LR to prove the effectiveness of our method. Simple linear classifiers equipped with our method perform better than the state-of-the-art few-shot classification method and achieve the best performance on both 1-shot and 5-shot settings of *mini*ImageNet and CUB. The performance of our distribution calibration surpasses the state-of-the-art *generation-based* method by 10% for the 5way1shot setting, which proves that our method can handle extremely low-shot classification tasks better. Compared to other *generation-based* methods, which require the design of a generative model with extra training costs on the learnable parameters, our method is much more simple, effective and flexible and can be equipped with any feature extractors and classifier model structures.

4.3 VISUALIZATION OF GENERATED SAMPLES

We show what the calibrated distribution looks like by visualizing the generated features sampled from the distribution. In Figure 2, we show the t-SNE representation (van der Maaten & Hinton (2008)) of the original support set (a), the generated features (b,c) as well as the query set (d). Based on the calibrated distribution, the sampled features form a Gaussian distribution and more samples (c) can have a more comprehensive representation of the distribution. Due to the limited number

Figure 2: t-SNE visualization of our distribution estimation. Different colors represent different classes. '★' represents support set features, 'x' in figure (d) represents query set features, '▲' in figure (b)(c) represents generated features.

Figure 3: Left: Accuracy when increasing the power in Tukey's transformation when training with (red) or without (blue) the generated features. Right: Accuracy when increasing the number of generated features with the features are transformed by Tukey's transformation (red) and without Tukey's transformation (blue).

of examples in the support set, only 1 in this case, the samples from the query set usually cover a greater area and are a mismatch with the support set. This mismatch can be fixed to some extent by the generated features, i.e., the generated features in (c) can overlap areas of the query set. Thus, training with these generated features can alleviate the mismatch between the distribution estimated only from the few-shot samples and the ground truth distribution.

4.4 EFFECTS OF FEATURE TRANSFORMATION AND TRAINING WITH GENERATED FEATURES

Ablation Study

Table 3 shows the performance when our model is trained without Tukey's Ladder of Powers transformation for the features as in Equation 3 and when it is trained without the generated features as in Equation 7. It is clear that there is a severe decline in performance of over 10% if both are not used in the 5way1shot setting. The ablation of either one results in a performance drop of around 5% in the 5way1shot setting.

Choices of Power for Tukey's Ladder of Powers Transformation

The left side of Figure 3 shows the 5way1shot accuracy when choosing different powers for the Tukey's transformation in Equation 3 when training the classifier with the generated features (red) and without (blue). Note that when the power λ equals 1, the transformation keeps the original feature representations. There is a consistent general tendency for training with and without the generated features and in both cases, we found $\lambda = 0.5$ is the optimum choice. With the Tukey's transformation, the distribution of query set features in target tasks become more aligned to the calibrated Gaussian distribution, thus benefits the classifier which is trained on features sampled from the calibrated distribution.

Number of generated features

Table 3: Ablation study on *mini*ImageNet 5way1shot and 5way5shot showing accuracy with 95% confidence intervals.

Tukey transformation	Training with generated features	*mini*ImageNet	
		5way1shot	5way5shot
✗	✗	56.37 ± 0.68	79.03 ± 0.51
✓	✗	64.30 ± 0.53	81.33 ± 0.35
✗	✓	63.70 ± 0.38	82.26 ± 0.73
✓	✓	$\mathbf{68.57 \pm 0.55}$	$\mathbf{82.88 \pm 0.42}$

The right side of Figure 3 analyzes whether more generated features results in consistent improvement in both cases, namely when the features of support and query set are transformed by Tukey's transformation (red) and when they are not (blue). We found that when the number of generated features is below 500, both cases can benefit from more generated features. However, when more features are sampled, the performance of the classifier tested on untransformed features begins to decline. By training with the generated samples, the simple logistic regression classifier has a 12% relative performance improvement in a 1-shot classification setting.

4.5 OTHER HYPER-PARAMETERS

We select the hyperparameters based on the performance of the validation set. The k base class statistics to calibrate the novel class distribution in Equation 5 is set to 2. Figure 4 shows the effect of different values of k. The α in Equation 6 is a constant added on each element of the estimated covariance matrix, which can determine the degree of dispersion of features sampled from the calibrated distributions. An appropriate value of α can ensure a good decision boundary for the classifier. Different datasets have different statistics and an appropriate value of α may vary for different datasets. Figure 5 explores the effect of α on two datasets, i.e. *mini*ImageNet and CUB. We observe that the best α for *mini*ImageNet and CUB are different, i.e., 0.3 for CUB and 0.21 for *mini*ImageNet. But in each dataset, the performance of the validation set and the novel (testing) set generally has the same tendency, which indicates that the variance is dataset-dependent and is not overfitting to a specific set.

Figure 4: The effect of different values of k.   Figure 5: The effect of different values of α.

5 CONCLUSION AND FUTURE WORKS

We propose a simple but effective distribution calibration strategy for few-shot classification. Without complex generative models, training loss and extra parameters to learn, a simple logistic regression trained with features generated by our strategy outperforms the current state-of-the-art methods by $\sim 5\%$ on *mini*ImageNet. The calibrated distribution is visualized and demonstrates an accurate estimation of the feature distribution. Future works will explore the applicability of distribution calibration on more problem settings, such as multi-domain few-shot classification, and more methods, such as metric-based meta-learning algorithms.

REFERENCES

Antreas Antoniou and Amos Storkey. Assume, augment and learn: Unsupervised few-shot meta-learning via random labels and data augmentation, 2019.

Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Frank Wang, and Jia-Bin Huang. A closer look at few-shot classification, 2019.

Z. Chen, Y. Fu, Y. Zhang, Y. Jiang, X. Xue, and L. Sigal. Multi-level semantic feature augmentation for one-shot learning. *IEEE Transactions on Image Processing*, 28(9):4594–4605, 2019.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, 2017.

Hang Gao, Zheng Shou, Alireza Zareian, Hanwang Zhang, and Shih-Fu Chang. Low-shot learning via covariance-preserving adversarial augmentation networks. In *Advances in Neural Information Processing Systems 31*, pp. 975–985. 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in Neural Information Processing Systems 27*. 2014.

Bharath Hariharan and Ross Girshick. Low-shot visual recognition by shrinking and hallucinating features. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3018–3027, 2017.

Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. Meta-sgd: Learning to learn quickly for few shot learning. *CoRR*, 2017.

Bin Liu, Yue Cao, Yutong Lin, Qi Li, Zheng Zhang, Mingsheng Long, and Han Hu. Negative margin matters: Understanding margin in few-shot classification. *arXiv preprint arXiv:2003.12060*, 2020a.

Yaoyao Liu, Bernt Schiele, and Qianru Sun. An ensemble of epoch-wise empirical bayes for few-shot learning. In *European Conference on Computer Vision (ECCV)*, 2020b.

Puneet Mangla, Nupur Kumari, Abhishek Sinha, Mayank Singh, Balaji Krishnamurthy, and Vineeth N Balasubramanian. Charting the right manifold: Manifold mixup for few-shot learning. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, March 2020.

Seong-Jin Park, Seungju Han, Ji-won Baek, Insoo Kim, Juhwan Song, Hae Beom Lee, Jae-Joon Han, and Sung Ju Hwang. Meta variance transfer: Learning to augment from the others. In *Proceedings of Machine Learning and Systems 2020*, pp. 3752–3762. 2020.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Tiexin Qin, Wenbin Li, Yinghuan Shi, and Yang Gao. Diversity helps: Unsupervised few-shot learning via distribution shift-based data augmentation, 2020.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *ICLR*, 2017.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. *arXiv preprint arXiv:1803.00676*, 2018.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S. Bernstein, Alexander C. Berg, and Fei-Fei Li. Imagenet large scale visual recognition challenge. *CoRR*, abs/1409.0575, 2014.

Andrei A. Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. In *ICLR*, 2019.

Ruslan Salakhutdinov, Joshua Tenenbaum, and Antonio Torralba. One-shot learning with a hierarchical nonparametric bayesian model. Proceedings of Machine Learning Research, Bellevue, Washington, USA, 02 Jul 2012. JMLR Workshop and Conference Proceedings.

Eli Schwartz, Leonid Karlinsky, Joseph Shtok, Sivan Harary, Mattias Marder, Abhishek Kumar, Rogerio Feris, Raja Giryes, and Alex Bronstein. Delta-encoder: an effective sample synthesis method for few-shot object recognition. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 2845–2855. 2018.

Jake Snell, Kevin Swersky, and Richard S. Zemel. Prototypical networks for few-shot learning. In *NeurIPS*, 2017.

John W Tukey. *Exploratory data analysis*. Addison-Wesley Series in Behavioral Science. Addison-Wesley, Reading, MA, 1977. URL https://cds.cern.ch/record/107005.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 2008.

Oriol Vinyals, Charles Blundell, Tim Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *NeurIPS*, 2016.

Yu-Xiong Wang, Ross Girshick, Martial Hebert, and Bharath Hariharan. Low-shot learning from imaginary data. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018a.

Yu-Xiong Wang, Ross Girshick, Martial Hebert, and Bharath Hariharan. Low-shot learning from imaginary data. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7278–7286, 2018b.

P. Welinder, S. Branson, T. Mita, C. Wah, F. Schroff, S. Belongie, and P. Perona. Caltech-UCSD Birds 200. Technical Report CNS-TR-2010-001, California Institute of Technology, 2010.

Yongqin Xian, Tobias Lorenz, Bernt Schiele, and Zeynep Akata. Feature generating networks for zero-shot learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5542–5551, 2018.

Jian Zhang, Chenglong Zhao, Bingbing Ni, Minghao Xu, and Xiaokang Yang. Variational few-shot learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.

Ruixiang Zhang, Tong Che, Zoubin Ghahramani, Yoshua Bengio, and Yangqiu Song. Metagan: An adversarial approach to few-shot learning. In *Advances in Neural Information Processing Systems 31*. 2018.

A APPENDIX

You may include other additional sections here.