SLAPS: Self-Supervision Improves Structure Learning for Graph Neural Networks

Abstract

Graph neural networks (GNNs) work well when the graph structure is provided. However, this structure may not always be available in real-world applications. One solution to this problem is to infer a task-specific latent structure and then apply a GNN to the inferred graph. Unfortunately, the space of possible graph structures grows super-exponentially with the number of nodes and so the task-specific supervision may be insufficient for learning both the structure and the GNN parameters. In this work, we propose the **S**imultaneous **L**earning of **A**djacency and GNN **P**arameters with **S**elf-supervision, or SLAPS, a method that provides more supervision for inferring a graph structure through self-supervision. A comprehensive experimental study demonstrates that SLAPS scales to large graphs with hundreds of thousands of nodes and outperforms several models that have been proposed to learn a task-specific graph structure on established benchmarks.

1 Introduction

Graph representation learning has grown rapidly and found applications in domains where a natural graph of the data points is available [2, 23]. Graph neural networks (GNNs) [35] have been a key component to the success of the research in this area. Specifically, GNNs have shown promising results for semi-supervised classification when the available graph structure exhibits a high degree of homophily (i.e. connected nodes often belong to the same class) [52].

We study the applicability of GNNs to (semi-supervised) classification problems where a graph structure is *not* readily available. The existing approaches for this problem either fix a similarity graph between the nodes, or learn the GNN parameters and a graph structure simultaneously (see Related Work). In both cases, one main goal is to construct or learn a graph structure with a high degree of homophily with respect to the labels to aid the GNN classification. The latter approach is sometimes called *latent graph learning* and often results in higher predictive performance compared to the former approach (see, e.g., [10]).

We identify a supervision starvation problem in latent graph learning approaches in which the edges between pairs of nodes that are far from labeled nodes receive insufficient supervision; this results in learning poor structures away from labeled nodes and hence poor generalization. We propose a solution for this problem by adopting a multi-task learning framework in which we supplement the classification task with a self-supervised task. The self-supervised task is based on the hypothesis that a graph structure that is suitable for predicting the node features is also suitable for predicting the node labels. It works by masking some input features (or adding noise to them) and training a separate GNN aiming at updating the adjacency matrix in such a way that it can recover the masked (or noisy) features. The task is generic and can be combined with several existing latent graph learning approaches.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

We develop a latent graph learning model, dubbed SLAPS, that adopts the proposed self-supervised task. We provide a comprehensive experimental study on nine datasets (thirteen variations) of various sizes and from various domains and perform thorough analyses to show the merit of SLAPS.

Our main contributions include: 1) identifying a supervision starvation problem for latent graph learning, 2) proposing a solution for the identified problem through self-supervision, 3) developing SLAPS, a latent graph learning model that adopts the self-supervised solution, 4) providing comprehensive experimental results showing SLAPS substantially outperforms existing latent graph learning baselines from various categories on various benchmarks, and 5) providing an implementation for latent graph learning that scales to graphs with hundreds of thousands of nodes.

2   Related work

Existing methods that relate to this work can be grouped into the following categories. We discuss selected work from each category and refer the reader to [55] for a full survey.

Similarity graph: One approach for inferring a graph structure is to select a similarity metric and set the edge weight between two nodes to be their similarity [34, 39, 1]. To obtain a sparse structure, one may create a kNN similarity graph, only connect pairs of nodes whose similarity surpasses some predefined threshold, or do sampling. As an example, in [12] a (fixed) kNN graph using the cosine similarity of the node features is created. In [42], this idea is extended by creating a fresh graph in each layer of the GNN based on the node embedding similarities in that layer. Instead of choosing a single similarity metric, in [13] several (potentially weak) measures of similarity are fused. The quality of the predictions of these methods depends heavily on the choice of the similarity metric(s).

Fully connected graph: Another approach is to start with a fully connected graph and assign edge weights using the available meta-data or employ the GNN variants that provide weights for each edge via an attention mechanism [40, 48]. This approach has been used in computer vision [e.g., 38], natural language processing [e.g., 51], and few-shot learning [e.g., 11]. The complexity of this approach grows rapidly making it applicable only to small-sized graphs. Zhang et al. [49] propose to define local neighborhoods for each node and only assume that these local neighborhoods are fully connected. Their approach relies on an initial graph structure to define the local neighborhoods.

Latent graph learning: Instead of a similarity graph based on the initial features, one may use a graph generator with learnable parameters. In [27], a fully connected graph is created based on a bilinear similarity function with learnable parameters. In [10], a Bernoulli distribution is learned for each possible edge and graph structures are created through sampling from these distributions. In [44], the input structure is updated to increase homophily based on the labels and model predictions. In [4], an iterative approach is proposed that iterates over projecting the nodes to a latent space and constructing an adjacency matrix from the latent representations multiple times. A common approach in this category is to learn a projection of the nodes to a latent space where node similarities correspond to edge weights or edge probabilities. In [43], the nodes are projected to a latent space by learning weights for each of the input features. In [33, 19, 6], a multi-layer perceptron is used for projection. In [47, 50], a GNN is used for projection; it uses the node features and an initial graph structure. In our experiments, we compare with several approaches from this category.

Leveraging domain knowledge: In some applications, one may leverage domain knowledge to guide the model toward learning specific structures. For example, in [22], abstract syntax trees and regular languages are leveraged in learning graph structures of Python programs that aid reasoning for downstream tasks. In [21], the structure learning is guided for robustness to adversarial attacks through the domain knowledge that clean adjacency matrices are often sparse and low-rank and exhibit feature smoothness along connected nodes. Other examples in this category include [17, 33]. In our paper, we experiment with general-purpose datasets without access to domain knowledge.

Proposed method: Our model falls within the latent graph learning category. We supplement the training with a self-supervised objective to increase the amount of supervision in learning a structure. Our self-supervised task is inspired by, and similar to, the pre-training strategies for GNNs [15, 16, 20, 46, 53] (specifically, we adopt the multi-task learning framework of You et al. [46]), but it differs from this line of work as we use self-supervision for learning a graph structure whereas the above methods use it to learn better (and, in some cases, transferable) GNN parameters.

Figure 1: Overview of SLAPS. At the top, a generator receives the node features and produces a non-symmetric, non-normalized adjacency having (possibly) both positive and negative values (Section 4.1). The adjacency processor makes the values positive, symmetrizes and normalizes the adjacency (Section 4.2). The resulting adjacency and the node features go into $\mathsf{GNN_C}$ which predicts the node classes (Section 4.3). At the bottom, some noise is added to the node features. The resulting noisy features and the generated adjacency go into $\mathsf{GNN_{DAE}}$ which then denoises the features (Section 4.5).

3 Background and notation

We use lowercase letters to denote scalars, bold lowercase letters to denote vectors and bold uppercase letters to denote matrices. $\boldsymbol{I}$ represents an identity matrix. For a vector $\boldsymbol{v}$, we represent its i^{th} element as $\boldsymbol{v}_i$. For a matrix $\boldsymbol{M}$, we represent the i^{th} row as $\boldsymbol{M}_i$ and the element at the i^{th} row and j^{th} column as $\boldsymbol{M}_{ij}$. For an attributed graph, we use n, m and f to represent the number of nodes, edges, and features respectively, and denote the graph as $\mathcal{G} = \{\mathcal{V}, \boldsymbol{A}, \boldsymbol{X}\}$ where $\mathcal{V} = \{v_1, \dots, v_n\}$ is a set of nodes, $\boldsymbol{A} \in \mathbb{R}^{n \times n}$ is an adjacency matrix with $\boldsymbol{A}_{ij}$ indicating the weight of the edge from v_i to v_j ($\boldsymbol{A}_{ij} = 0$ implies no edge), and $\boldsymbol{X} \in \mathbb{R}^{n \times f}$ is a matrix whose rows correspond to node features.

Graph convolutional networks (GCNs) [24] are a powerful variant of GNNs. For a graph $\mathcal{G} = \{\mathcal{V}, \boldsymbol{A}, \boldsymbol{X}\}$ with a degree matrix $\boldsymbol{D}$, layer l of the GCN architecture can be defined as $\boldsymbol{H}^{(l)} = \sigma(\hat{\boldsymbol{A}} \boldsymbol{H}^{(l-1)} \boldsymbol{W}^{(l)})$ where $\hat{\boldsymbol{A}}$ represents a normalized adjacency matrix, $\boldsymbol{H}^{(l-1)} \in \mathbb{R}^{n \times d_{l-1}}$ represents the node representations in layer l-1 ($\boldsymbol{H}^{(0)} = \boldsymbol{X}$), $\boldsymbol{W}^{(l)} \in \mathbb{R}^{d_{l-1} \times d_l}$ is a weight matrix, σ is an activation function such as ReLU [30], and $\boldsymbol{H}^{(l)} \in \mathbb{R}^{n \times d_l}$ is the updated node embeddings. For undirected graphs where the adjacency is symmetric, $\hat{\boldsymbol{A}} = \boldsymbol{D}^{-\frac{1}{2}}(\boldsymbol{A} + \boldsymbol{I})\boldsymbol{D}^{-\frac{1}{2}}$ corresponds to a row-and-column normalized adjacency with self-loops, and for directed graphs where the adjacency is not necessarily symmetric, $\hat{\boldsymbol{A}} = \boldsymbol{D}^{-1}(\boldsymbol{A} + \boldsymbol{I})$ corresponds to a row normalized adjacency matrix with self-loops. Here, $\boldsymbol{D}$ is a (diagonal) degree matrix for $(\boldsymbol{A} + \boldsymbol{I})$ defined as $\boldsymbol{D}_{ii} = 1 + \sum_j \boldsymbol{A}_{ij}$.

4 Proposed method: SLAPS

SLAPS consists of four components: 1) generator, 2) adjacency processor, 3) classifier, and 4) self-supervision. Figure 1 illustrates these components. In the next three subsections, we explain the first three components. Then, we point out a supervision starvation problem for a model based only on these components. Then we describe the self-supervision component as a solution to the supervision starvation problem and the full SLAPS model.

4.1 Generator

The generator is a function $\mathsf{G} : \mathbb{R}^{n \times f} \to \mathbb{R}^{n \times n}$ with parameters $\boldsymbol{\theta}_\mathsf{G}$ which takes the node features $\boldsymbol{X} \in \mathbb{R}^{n \times f}$ as input and produces a matrix $\tilde{\boldsymbol{A}} \in \mathbb{R}^{n \times n}$ as output. We consider the following two generators and leave experimenting with more sophisticated graph generators (e.g., [45, 29, 28]) and models with tractable adjacency computations (e.g., [5]) as future work.

Full parameterization (FP): For this generator, $\boldsymbol{\theta}_{\mathsf{G}} \in \mathbb{R}^{n \times n}$ and the generator function is defined as $\tilde{\boldsymbol{A}} = \mathsf{G}_{FP}(\boldsymbol{X}; \boldsymbol{\theta}_{\mathsf{G}}) = \boldsymbol{\theta}_{\mathsf{G}}$. That is, the generator ignores the input node features and directly optimizes the adjacency matrix. FP is similar to the generator in [10] except that they treat each element of $\tilde{\boldsymbol{A}}$ as the parameter of a Bernoulli distribution and sample graph structures from these distributions. FP is simple and flexible for learning any adjacency matrix, but adds n^2 parameters which limits scalability and makes the model susceptible to overfitting.

MLP-kNN: Here, $\boldsymbol{\theta}_{\mathsf{G}}$ corresponds to the weights of a multi-layer perceptron (MLP) and $\tilde{\boldsymbol{A}} = \mathsf{G}_{\mathsf{MLP}}(\boldsymbol{X}; \boldsymbol{\theta}_{\mathsf{G}}) = \mathsf{kNN}(\mathsf{MLP}(\boldsymbol{X}))$, where $\mathsf{MLP} : \mathbb{R}^{n \times f} \to \mathbb{R}^{n \times f'}$ is an MLP that produces a matrix with updated node representations $\boldsymbol{X}'$; $\mathsf{kNN} : \mathbb{R}^{n \times f'} \to \mathbb{R}^{n \times n}$ produces a sparse matrix. The implementation details for the kNN operation is provided in the supplementary material.

Initialization and variants of MLP-kNN: Let $\boldsymbol{A}^{kNN}$ represent an adjacency matrix created by applying a kNN function on the initial node features. One smart initialization for $\boldsymbol{\theta}_{\mathsf{G}}$ is to initialize it in a way that the generator initially generates $\boldsymbol{A}^{kNN}$ (i.e. $\tilde{\boldsymbol{A}} = \boldsymbol{A}^{kNN}$ before training starts). This can be trivially done for the FP generator by initializing $\boldsymbol{\theta}_{\mathsf{G}}$ to $\boldsymbol{A}^{kNN}$. For MLP-kNN, we consider two variants. In one, hereafter referred to simply as MLP, we keep the input dimension the same throughout the layers. In the other, hereafter referred to as MLP-D, we consider MLPs with diagonal weight matrices (i.e., except the main diagonal, all other parameters in the weight matrices are zero). For both variants, we initialize the weight matrices in $\boldsymbol{\theta}_{\mathsf{G}}$ with the identity matrix to ensure that the output of the MLP is initially the same as its input and the kNN graph created on these outputs is equivalent to $\boldsymbol{A}^{kNN}$ (Alternatively, one may use other MLP variants but pre-train the weights to output $\boldsymbol{A}^{kNN}$ before the main training starts.). MLP-D can be thought of as assigning different weights to different features and then computing node similarities.

4.2 Adjacency processor

The output $\tilde{\boldsymbol{A}}$ of the generator may have both positive and negative values, may be non-symmetric and non-normalized. We let $\boldsymbol{A} = \frac{1}{2}\boldsymbol{D}^{-\frac{1}{2}}(\mathsf{P}(\tilde{\boldsymbol{A}}) + \mathsf{P}(\tilde{\boldsymbol{A}})^T)\boldsymbol{D}^{-\frac{1}{2}}$. Here P is a function with a non-negative range applied element-wise on its input – see supplementary material for details. The sub-expression $\frac{1}{2}(\mathsf{P}(\tilde{\boldsymbol{A}}) + \mathsf{P}(\tilde{\boldsymbol{A}})^T)$ makes the resulting matrix $\mathsf{P}(\tilde{\boldsymbol{A}})$ symmetric. To understand the reason for taking the mean of $\mathsf{P}(\tilde{\boldsymbol{A}})$ and $\mathsf{P}(\tilde{\boldsymbol{A}})^T$, assume $\tilde{\boldsymbol{A}}$ is generated by $\mathsf{G}_{\mathsf{MLP}}$. If v_j is among the k most similar nodes to v_i and vice versa, then the strength of the connection between v_i and v_j will remain the same. However, if, say, v_j is among the k most similar nodes to v_i but v_i is not among the top k for v_j, then taking the average of the similarities reduces the strength of the connection between v_i and v_j. Finally, once we have a symmetric adjacency with non-negative values, we normalize $\frac{1}{2}(\mathsf{P}(\tilde{\boldsymbol{A}}) + \mathsf{P}(\tilde{\boldsymbol{A}})^T)$ by computing its degree matrix $\boldsymbol{D}$ and multiplying it from left and right to $\boldsymbol{D}^{-\frac{1}{2}}$.

4.3 Classifier

The classifier is a function $\mathsf{GNN}_{\mathsf{C}} : \mathbb{R}^{n \times f} \times \mathbb{R}^{n \times n} \to \mathbb{R}^{n \times |\mathcal{C}|}$ with parameters $\boldsymbol{\theta}_{\mathsf{GNN}_{\mathsf{C}}}$. It takes the node features $\boldsymbol{X}$ and the generated adjacency $\boldsymbol{A}$ as input and provides for each node the logits for each class. $\mathcal{C}$ corresponds to the classes and $|\mathcal{C}|$ corresponds to the number of classes. We use a two-layer GCN for which $\boldsymbol{\theta}_{\mathsf{GNN}_{\mathsf{C}}} = \{\boldsymbol{W}^{(1)}, \boldsymbol{W}^{(2)}\}$ and define our classifier as $\mathsf{GNN}_{\mathsf{C}}(\boldsymbol{A}, \boldsymbol{X}; \boldsymbol{\theta}_{\mathsf{GNN}_{\mathsf{C}}}) = \boldsymbol{A}\mathsf{ReLU}(\boldsymbol{A}\boldsymbol{X}\boldsymbol{W}^{(1)})\boldsymbol{W}^{(2)}$ but other GNN variants can be used as well (recall that $\boldsymbol{A}$ is normalized). The training loss $\mathcal{L}_C$ for the classification task is computed by taking the softmax of the logits to produce a probability distribution for each node and then computing the cross-entropy loss.

4.4 Why not just the first three components?

One may create a model using only the three components described so far corresponding to the top part of Figure 1. As we will explain here, however, this model may suffer severely from supervision starvation. The same problem also applies to many existing approaches for latent graph learning, as they can be formulated as a combination of variants of these three components.

Consider a scenario during training where two unlabeled nodes v_i and v_j are not directly connected to any labeled nodes according to the generated structure. Then, since a two-layer GCN makes predictions for the nodes based on their two-hop neighbors, the classification loss

165 (i.e. $\mathcal{L}_C$) is not affected by the edge between v_i and v_j and this
166 edge receives no supervision[1]. Figure 2 provides an example
167 of such a scenario. Let us call the edges that do not affect the
168 loss function $\mathcal{L}_C$ (and consequently do not receive supervision)
169 as *starved edges*. These edges are clearly problematic because
170 although they may not affect the training loss, the predictions
171 at the test time depend on these edges and if their values are
172 learned without enough supervision, the model may make poor
173 predictions at the test time. A natural question concerning the
174 extent of the problem caused by such edges is the proportion of
175 starved edges. The following theorem formally establishes the
176 extent of the problem for Erdős-Rényi graphs [8]. An *Erdős-Rényi*
177 graph with n nodes and m edges is a graph chosen uniformly at
178 random from the collection of all graphs which have n nodes and m edges.

Figure 2: Using a two-layer GCN, the predictions made for the labeled nodes are not affected by the dashed (starved) edge.

179 **Theorem 1** *Let $\mathcal{G}(n, m)$ be an Erdős-Rényi graph with n nodes and m edges. Assume we have*
180 *labels for q nodes selected uniformly at random. The probability of an edge being a starved edge*
181 *with a two-layer GCN is equal to $(1 - \frac{q}{n})(1 - \frac{q}{n-1})\prod_{i=1}^{2q}(1 - \frac{m-1}{\binom{n}{2}-i})$.*

182 We defer the proof to the supplementary material. To put the numbers from the theorem in perspective,
183 let us consider three established benchmarks for semi-supervised node classification namely *Cora*,
184 *Citeseer*, and *Pubmed* (the statistics for these datasets can be found in the Appendix). For an
185 Erdős-Rényi graph with similar statistics as the Cora dataset ($n = 2708$, $m = 5429$, $q = 140$), the
186 probability of an edge being a starved edge is 59.4% according to the above theorem. For Citeseer and
187 Pubmed, this number is 75.7% and 96.7% respectively. While Theorem 1 is stated for Erdős-Rényi
188 graphs, the identified problem also applies to natural graphs. For the original structures of Cora,
189 Citeseer, and Pubmed, for example, 48.8%, 65.2%, and 91.6% of the edges are starved edges.

4.5 Self-supervision

191 One possible solution to the supervision starvation problem is to define a *prior graph structure* and
192 regularize the learned structure toward it. This leads the starved edges toward the prior structure as
193 opposed to neglecting them. The choice of the prior is important as it determines the inductive bias
194 incorporated into the model. We define a prior structure based on the following hypothesis:

195 **Hypothesis 1** *A graph structure that is suitable for predicting the node features is also suitable for*
196 *predicting the node labels.*

197 We first explain why the above hypothesis is reasonable for an extreme case that is easy to understand
198 and then extend the explanation to the general case. Consider an extreme scenario where one of the
199 node features is the same as the node labels. A graph structure that is suitable for predicting this
200 feature exhibits homophily for it. Because of the equivalence between this feature and the labels, the
201 graph structure also exhibits homophily for the labels, so it is also suitable for predicting the labels.
202 In the general (non-extreme) case, there may not be a single feature that is equivalent to the labels but
203 a subset of the features may be highly predictive of the labels. A graph structure that is suitable for
204 predicting this subset exhibits homophiliy for the features in the subset. Because this subset is highly
205 predictive of the labels, the structure also exhibits a high degree of homophiliy for the labels, so it is
206 also suitable for predicting the node labels.

207 Next, we explain how to design a suitable graph structure for predicting the features and how to
208 regularize toward it. One could design such a structure manually (e.g., by handcrafting a graph
209 that connects nodes based on the collective homophily between their individual features) and then
210 penalize the difference between this prior graph and the learned graph. Alternatively, in this paper we
211 take a learning-based approach based on self-supervision where we not only use the learned graph
212 structure for the classification task, but also for denoising the node features. The self-supervised task
213 encourages the model to learn a structure that is suitable for predicting the node features. We describe
214 this approach below and provide comparisons to the manual approach in the supplementary material.

---

[1]While using more layers may somewhat alleviated this problem, deeper GCNs typically produce inferior results, e.g., due to oversmoothing [26, 31] – see the supplementary material for empirical evidence.

Our self-supervised task is based on denoising autoencoders [41]. Let $\mathsf{GNN_{DAE}} : \mathbb{R}^{n \times f} \times \mathbb{R}^{n \times n} \rightarrow \mathbb{R}^{n \times f}$ be a GNN with parameters $\boldsymbol{\theta}_{\mathsf{GNN_{DAE}}}$ that takes node features and a generated adjacency as input and provides updated node features with the same dimension as output. We train $\mathsf{GNN_{DAE}}$ such that it receives a noisy version $\tilde{\boldsymbol{X}}$ of the features $\boldsymbol{X}$ as input and produces the denoised features $\boldsymbol{X}$ as output. Let idx represent the indices corresponding to the elements of $\boldsymbol{X}$ to which we have added noise, and $\boldsymbol{X}_{idx}$ represent the values at these indices. During training, we minimize:

$$\mathcal{L}_{DAE} = \mathsf{L}(\boldsymbol{X}_{idx}, \mathsf{GNN_{DAE}}(\tilde{\boldsymbol{X}}, \boldsymbol{A}; \boldsymbol{\theta}_{\mathsf{GNN_{DAE}}})_{idx}) \tag{1}$$

where $\boldsymbol{A}$ is the generated adjacency matrix and L is a loss function. For datasets where the features consist of binary vectors, idx consists of r percent of the indices of $\boldsymbol{X}$ whose values are 1 and $r\eta$ percent of the indices whose values are 0, both selected uniformly at random in each epoch. Both r and η (corresponding to the negative ratio) are hyperparameters. In this case, we add noise by setting the 1s in the selected mask to 0s and L is the binary cross-entropy loss. For datasets where the input features are continuous numbers, idx consists of r percent of the indices of $\boldsymbol{X}$ selected uniformly at random in each epoch. We add noise by either replacing the values at idx with 0 or by adding independent Gaussian noises to each of the features. In this case, L is the mean-squared error loss.

Note that the self-supervised task in equation 1 is generic and can be added to different GNNs as well as latent graph learning models. It can be also combined with other techniques in the literature that encourage learning more homophilous structures or increase the amount of supervision. In our experiments, we test the combination of our self-supervised task with two such techniques namely *self-training* [26] and *AdaEdge* [3]. Self-training helps the model "see" more labeled nodes and AdaEdge helps iteratively create graph structure with higher degrees of homophily. We refer the reader to the supplementary material for descriptions of self-training and AdaEdge.

4.6 SLAPS

Our final model is trained to minimize $\mathcal{L} = \mathcal{L}_C + \lambda \mathcal{L}_{DAE}$ where $\mathcal{L}_C$ is the classification loss, $\mathcal{L}_{DAE}$ is the denoising autoencoder loss (see Equation 1), and λ is a hyperparameter controlling the relative importance of the two losses.

To verify the merit of the $\mathsf{GNN_{DAE}}$ for learning an adjacency matrix in isolation, we also consider a variant of SLAPS named $SLAPS_{2s}$ that is trained in two stages. We first train the $\mathsf{GNN_{DAE}}$ model by minimizing $\mathcal{L}_{DAE}$ described in in Equation 1. Recall that $\mathcal{L}_{DAE}$ depends on the parameters $\boldsymbol{\theta}_{\mathsf{G}}$ of the generator and the parameters $\boldsymbol{\theta}_{\mathsf{GNN_{DAE}}}$ of the denoising autoencoder. After every t epochs of training, we fix the adjacency matrix, train a classifier with the fixed adjacency matrix, and measure classification accuracy on the validation set. We select the epoch that produces the adjacency providing the best validation accuracy for the classifier. Note that in $SLAPS_{2s}$, the adjacency matrix only receives gradients from the self-supervised task in Equation 1.

5 Experiments

In this section, we report our key results. More empirical comparisons, experimental analyses, and ablation studies are presented in the supplementary material.

Baselines: We compare our proposal to several baselines with different properties. The first baseline is a multi-layer perceptron (MLP) which does not take the graph structure into account. We also compare against MLP-GAM* [37] which learns a fully connected graph structure and uses this structure to supplement the loss function of the MLP toward predicting similar labels for neighboring nodes. Our third baseline is label propagation (LP) [54], a well-known model for semi-supervised learning. Similar to [10], we also consider a baseline named *kNN-GCN* where we create a kNN graph based on the node feature similarities and feed this graph to a GCN; the graph structure remains fixed in this approach. We also compare with prominent existing latent graph learning models including LDS [10], GRCN [47], DGCNN [42], and IDGL [4]. We feed a kNN graph to the models requiring an initial graph structure. We also explore how adding self-training and AdaEdge impact the performance of kNN-GCN as well as SLAPS.

Datasets: We use three established benchmarks in the GNN literature namely Cora, Citeseer, and Pubmed [36] as well as the *ogbn-arxiv* dataset [14] that is orders of magnitude larger than the other three datasets and is more challenging due to the more realistic split of the data into train, validation,

Table 1: Results of SLAPS and the baselines on established node classification benchmarks. † indicates results have been taken from Franceschi et al. [10]. ‡ indicates results have been taken from Stretcu et al. [37]. Bold and underlined values indicate best and second-best mean performances respectively. *OOM* indicates out of memory. *OOT* indicates out of time (we allowed 24h for each run). *NA* indicates not applicable.

Model	Cora	Citeseer	Cora390	Citeseer370	Pubmed	ogbn-arxiv
MLP	$56.1 \pm 1.6^{\dagger}$	$56.7 \pm 1.7^{\dagger}$	65.8 ± 0.4	67.1 ± 0.5	71.4 ± 0.0	54.7 ± 0.1
MLP-GAM*	$70.7^{\ddagger}$	$70.3^{\ddagger}$	–	–	$71.9^{\ddagger}$	–
LP	37.6 ± 0.0	23.2 ± 0.0	36.2 ± 0.0	29.1 ± 0.0	41.3 ± 0.0	OOM
kNN-GCN	$66.5 \pm 0.4^{\dagger}$	$68.3 \pm 1.3^{\dagger}$	72.5 ± 0.5	71.8 ± 0.8	70.4 ± 0.4	49.1 ± 0.3
LDS	–	–	$71.5 \pm 0.8^{\dagger}$	$71.5 \pm 1.1^{\dagger}$	OOM	OOM
GRCN	67.4 ± 0.3	67.3 ± 0.8	71.3 ± 0.9	70.9 ± 0.7	67.3 ± 0.3	OOM
DGCNN	56.5 ± 1.2	55.1 ± 1.4	67.3 ± 0.7	66.6 ± 0.8	70.1 ± 1.3	OOM
IDGL	70.9 ± 0.6	68.2 ± 0.6	73.4 ± 0.5	72.7 ± 0.4	72.3 ± 0.4	OOM
kNN-GCN + AdaEdge	67.7 ± 1.0	68.8 ± 1.0	72.2 ± 0.4	71.8 ± 0.6	OOT	OOT
kNN-GCN + self-training	67.3 ± 0.3	69.8 ± 1.0	71.1 ± 0.3	72.4 ± 0.2	72.7 ± 0.1	NA
SLAPS (FP)	72.4 ± 0.4	70.7 ± 0.4	**76.6 ± 0.4**	73.1 ± 0.6	OOM	OOM
SLAPS (MLP)	72.8 ± 0.8	70.5 ± 1.1	75.3 ± 1.0	73.0 ± 0.9	**74.4 ± 0.6**	**56.6 ± 0.1**
SLAPS (MLP-D)	73.4 ± 0.3	72.6 ± 0.6	75.1 ± 0.5	**73.9 ± 0.4**	73.1 ± 0.7	52.9 ± 0.1
SLAPS (MLP) + AdaEdge	72.8 ± 0.7	70.6 ± 1.5	75.2 ± 0.6	72.6 ± 1.4	OOT	OOT
SLAPS (MLP) + self-training	**74.2 ± 0.5**	**73.1 ± 1.0**	75.5 ± 0.7	73.3 ± 0.6	74.3 ± 1.4	NA

and test sets. For these datasets, we only feed the node features to the models and not their original graph structure. Following [10, 4], we also experiment with several classification (non-graph) datasets available in scikit-learn [32] including Wine, Cancer, Digits, and 20News. Furthermore, following [18], we provide results on the MNIST dataset [25] in the supplementary. Dataset statistics can be found in the supplementary. For Cora and Citeseer, the LDS model uses the train data for learning the parameters of the classification GCN, half of the validation for learning the parameters of the adjacency matrix (in their bi-level optimization setup, these are considered as hyperparameters), and the other half of the validation set for early stopping and tuning the other hyperparameters. Besides experimenting with the original setups of these two datasets, we also consider a setup that is closer to that of LDS: we use the train set and half of the validation set for training and the other half of validation for early stopping and hyperparameter tuning. We name the modified versions Cora390 and Citeseer370 respectively where the number proceeding the dataset name shows the number of labels from which gradients are computed. We follow a similar procedure for the scikit-learn datasets.

Implementation: We defer the implementation details and the best hyperparameter settings for our model on all the datasets to the supplementary material.

5.1 Comparative results

The results of SLAPS and the baselines on our benchmarks are reported in Tables 1 and 2. We start by analyzing the results in Table 1 first. Starting with the baselines, we see that learning a fully connected graph in MLP-GAM* makes it outperform MLP. kNN-GCN significantly outperforms MLP on Cora and Citeseer but underperforms on Pubmed and ogbn-arxiv. Furthermore, both self-training and AdaEdge improve the performance of kNN-GCN. This shows the importance of the similarity metric and the graph structure that is fed into GCN; a low-quality structure can harm model performance. LDS outperforms MLP but the fully parameterized adjacency matrix of LDS results in memory issues for Pubmed and ogbn-arxiv. As for GRCN, it was shown in the original paper that GRCN can revise a good initial adjacency matrix and provide a substantial boost in performance. However, as evidenced by the results, if the initial graph structure is somewhat poor, GRCN's performance becomes on par with kNN-GCN. IDGL is the best performing baseline.

SLAPS consistently outperforms the baselines in some cases by large margins. Among the generators, the winner is dataset-dependent with MLP-D mostly outperforming MLP on datasets with many features and MLP outperforming on datasets with small numbers of features. Using the software that was publicly released by the authors, the baselines that learn a graph structure fail on ogbn-arxiv; our implementation, on the other hand, scales to such large graphs. Adding self-training helps further improve the results of SLAPS. Adding AdaEdge, however, does not seem effective, probably because the graph structure learned by SLAPS already exhibits a high degree of homophily (see Section 5.4).

Table 2: Results on classification datasets. † indicates results have been taken from Franceschi et al. [10]. Bold and underlined values indicate best and second-best mean performances respectively.

Model	Wine	Cancer	Digits	20news
MLP	96.1 ± 1.0	95.3 ± 0.9	81.9 ± 1.0	30.4 ± 0.1
kNN-GCN	93.5 ± 0.7	95.3 ± 0.4	$\mathbf{95.4 \pm 0.4}$	46.3 ± 0.3
LDS	$\mathbf{97.3 \pm 0.4}^{\dagger}$	$94.4 \pm 1.9^{\dagger}$	$92.5 \pm 0.7^{\dagger}$	$46.4 \pm 1.6^{\dagger}$
IDGL	97.0 ± 0.7	94.2 ± 2.3	92.5 ± 1.3	48.5 ± 0.6
SLAPS (FP)	96.6 ± 0.4	94.6 ± 0.3	$\underline{94.4 \pm 0.7}$	44.4 ± 0.8
SLAPS (MLP)	96.3 ± 1.0	$\underline{96.0 \pm 0.8}$	92.5 ± 0.7	$\mathbf{50.4 \pm 0.7}$
SLAPS (MLP-D)	96.5 ± 0.8	$\mathbf{96.6 \pm 0.2}$	94.2 ± 0.1	$\underline{49.8 \pm 0.9}$

In Table 2, we only compared SLAPS with the best performing baselines from Table 1 (kNN-GCN, LDS and IDGL). We also included an MLP baseline for comparison. On three out of four datasets, SLAPS outperforms the LDS and IDGL baselines. For the Digits dataset, interestingly kNN-GCN outperforms the learning-based models. This could be because the initial kNN structure for this dataset is already a good structure. Among the datasets on which we can train SLAPS with the FP generator, 20news has the largest number of nodes (9,607 nodes). On this dataset, we observed that an FP generator suffers from overfitting and produces weaker results compared to other generators due to its large number of parameters.

5.2 The effectiveness of self-supervision

SLAPS$_{2s}$: To provide more insight into the value provided by the self-supervision task and the generalizability of the adjacency learned through this task, we conduct experiments with SLAPS$_{2s}$. Recall from Section 4.6 that in SLAPS$_{2s}$, the adjacency is learned only based on the self-supervision task and the node labels are only used for early stopping, hyperparameter tuning, and training GCN$_C$. Figure 3 shows the performance of SLAPS and SLAPS$_{2s}$ on Cora and compares them with kNN-GCN. Although SLAPS$_{2s}$ does not use the node labels in learning an adjacency matrix, it outperforms kNN-GCN (8.4% improvement when using an FP generator). With an FP generator, SLAPS$_{2s}$ even achieves competitive performance with SLAPS; this is mainly because FP does not leverage the supervision provided by GCN$_C$ toward learning generalizable patterns that can be used for nodes other than those in the training set.

Figure 3: SLAPS vs SLAPS$_{2s}$ on Cora with different generators.

These results corroborate the effectiveness of the self-supervision task for learning an adjacency matrix. Besides, the results show that learning the adjacency using both self-supervision and the task-specific node labels results in higher predictive accuracy.

The value of λ: Figure 4 shows the performance of SLAPS[2] on Cora and Citeseer with different values of λ. When $\lambda = 0$, corresponding to removing self-supervision, the model performance is somewhat poor. As soon as λ becomes positive, both models see a large boost in performance showing that self-supervision is crucial to the high performance of SLAPS. Increasing λ further provides larger boosts until it becomes so large that the self-supervision loss dominates the classification loss and the performance deteriorates. Note that with $\lambda = 0$, SLAPS with the MLP generator becomes a variant of the model proposed in [6], but with a different similarity function.

Figure 4: The performance of SLAPS with MLP graph generator as a function of λ.

The effect of the training set size: According to Theorem 1, a smaller q (corresponding to the training set size) results in more starved edges in each epoch. To explore the effect of self-supervision as a function of q, we compared SLAPS with and without supervision on Cora and Citeseer while reducing

---

[2]The generator used in this experiment is MLP; other generators produced similar results.

the number of labeled nodes per class from 20 to 5. We used the FP generator for this experiment. With 5 labeled nodes per class, adding self-supervision provides 16.7% and 22.0% improvements on Cora and Citeseer respectively, which is substantially higher than the corresponding numbers when using 20 labeled nodes per class (10.0% and 7.0% respectively). This provides empirical evidence for Theorem 1. Note that the results on Cora390 and Citeseer 370 datasets provide evidence that the self-supervised task is effective even when the label rate is high.

5.3 Experiments with noisy graphs

The performance of GNNs highly depends on the quality of the input graph structure and deteriorates when the graph structure is noisy [see 56, 7, 9]. Here, we verify whether self-supervision is also helpful when a noisy structure is provided as input. Toward this goal, we experiment with Cora and Citeseer and provide noisy versions of the input graph as input. The provided noisy graph structure is used only for initialization; it is then further optimized by SLAPS. We perturb the graph structure by replacing ρ percent of the edges in the original structure (selected uniformly at random) with random edges. Figure 5 shows the performance of SLAPS with and without self-supervision ($\lambda = 0$ corresponds to no supervision). We also report the results of vanilla GCN on these perturbed graphs for comparison. It can be viewed that self-supervision consistently provides a boost in performance especially for higher values of ρ.

Figure 5: Performance comparison when noisy graphs are provided as input (ρ indicates the percentage of perturbations).

5.4 Analyses of the learned adjacency

Noisy graphs: Following the experiment in Section 5.3, we compared the learned and original structures by measuring the number of random edges added during perturbation but removed by the model and the number of edges removed during the perturbation but recovered by the model. For Cora, SLAPS removed 76.2% and 70.4% of the noisy edges and recovered 58.3% and 44.5% of the removed edges for $\rho = 25\%$ and $\rho = 50\%$ respectively while SLAPS with $\lambda = 0$ only removed 62.8% and 54.9% of the noisy edges and recovered 51.4% and 35.8% of the removed edges. This provides evidence on self-supervision being helpful for structure learning.

Homophily: As explained earlier, a properly learned graph for semi-supervised classification with GNNs exhibits high homophily. To verify the quality of the learned adjacency with respect to homophily, for every pair of nodes in the test set, we compute the odds of the two nodes sharing the same label as a function of the normalized weight of the edge connecting them. Figure 6 represents the odds for different weight intervals (recall that A is row and column normalized). For both Cora and Citeseer, nodes connected with higher edge weights are more likely to share the same label compared to nodes with lower or zero edge weights. Specifically, when $A_{ij} \geq 0.1$, v_i and v_j are almost 2.5 and 2.0 times more likely to share the same label on Cora and Citeseer respectively.

Figure 6: The odds of two nodes in the test set sharing the same label as a function of the edge weights learned by SLAPS.

6 Conclusion

We proposed SLAPS which is a model for learning the parameters of a graph neural network and the graph structure of the nodes simultaneously based on self-supervision. We explored the design space of SLAPS by comparing different graph generation and symmetrization approaches. We showed the effectiveness of our model using a comprehensive set of experiments and analyses.

References

[1] Mikhail Belkin, Partha Niyogi, and Vikas Sindhwani. Manifold regularization: A geometric framework for learning from labeled and unlabeled examples. *JMLRR*, 7(Nov):2399–2434, 2006.

[2] Ines Chami, Sami Abu-El-Haija, Bryan Perozzi, Christopher Ré, and Kevin Murphy. Machine learning on graphs: A model and comprehensive taxonomy. *arXiv preprint arXiv:2005.03675*, 2020.

[3] Deli Chen, Yankai Lin, Wei Li, Peng Li, Jie Zhou, and Xu Sun. Measuring and relieving the over-smoothing problem for graph neural networks from the topological view. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 3438–3445, 2020.

[4] Yu Chen, Lingfei Wu, and Mohammed J. Zaki. Deep iterative and adaptive learning for graph neural networks. In *The First International Workshop on Deep Learning on Graphs: Methodologies and Applications (with AAAI)*, February 2020. URL `https://dlg2019.bitbucket.io/aaai20`.

[5] Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. *arXiv preprint arXiv:2009.14794*, 2020.

[6] Luca Cosmo, Anees Kazi, Seyed-Ahmad Ahmadi, Nassir Navab, and Michael Bronstein. Latent patient network learning for automatic diagnosis. *arXiv preprint arXiv:2003.13620*, 2020.

[7] Hanjun Dai, Hui Li, Tian Tian, Xin Huang, Lin Wang, Jun Zhu, and Le Song. Adversarial attack on graph structured data. *arXiv preprint arXiv:1806.02371*, 2018.

[8] Paul Erdős and Alfred Rényi. On random graphs. *Publicationes Mathematicae Debrecen*, 6:290–297, 1959.

[9] James Fox and Sivasankaran Rajamanickam. How robust are graph neural networks to structural noise? *arXiv preprint arXiv:1912.10206*, 2019.

[10] Luca Franceschi, Mathias Niepert, Massimiliano Pontil, and Xiao He. Learning discrete structures for graph neural networks. In *ICML*, 2019.

[11] Victor Garcia and Joan Bruna. Few-shot learning with graph neural networks. *arXiv preprint arXiv:1711.04043*, 2017.

[12] Spyros Gidaris and Nikos Komodakis. Generating classification weights with gnn denoising autoencoders for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 21–30, 2019.

[13] Jonathan Halcrow, Alexandru Mosoi, Sam Ruth, and Bryan Perozzi. Grale: Designing networks for graph learning. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 2523–2532, 2020.

[14] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

[15] Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. In *ICLR*, 2020.

[16] Ziniu Hu, Yuxiao Dong, Kuansan Wang, Kai-Wei Chang, and Yizhou Sun. Gpt-gnn: Generative pre-training of graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1857–1867, 2020.

[17] Soobeom Jang, Seong-Eun Moon, and Jong-Seok Lee. Brain signal classification via learning connectivity structure. *arXiv preprint arXiv:1905.11678*, 2019.

[18] Bo Jiang, Ziyan Zhang, Doudou Lin, Jin Tang, and Bin Luo. Semi-supervised learning with graph learning-convolutional networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11313–11320, 2019.

[19] Bo Jiang, Ziyan Zhang, Doudou Lin, Jin Tang, and Bin Luo. Semi-supervised learning with graph learning-convolutional networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11313–11320, 2019.

[20] Wei Jin, Tyler Derr, Haochen Liu, Yiqi Wang, Suhang Wang, Zitao Liu, and Jiliang Tang. Self-supervised learning on graphs: Deep insights and new direction. *arXiv preprint arXiv:2006.10141*, 2020.

[21] Wei Jin, Yao Ma, Xiaorui Liu, Xianfeng Tang, Suhang Wang, and Jiliang Tang. Graph structure learning for robust graph neural networks. *arXiv preprint arXiv:2005.10203*, 2020.

[22] Daniel D Johnson, Hugo Larochelle, and Daniel Tarlow. Learning graph structure with a finite-state automaton layer. *arXiv preprint arXiv:2007.04929*, 2020.

[23] Seyed Mehran Kazemi, Rishab Goel, Kshitij Jain, Ivan Kobyzev, Akshay Sethi, Peter Forsyth, and Pascal Poupart. Representation learning for dynamic graphs: A survey. *JMLR*, 2020.

[24] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

[25] Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

[26] Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *AAAI*, 2018.

[27] Ruoyu Li, Sheng Wang, Feiyun Zhu, and Junzhou Huang. Adaptive graph convolutional neural networks. *arXiv preprint arXiv:1801.03226*, 2018.

[28] Renjie Liao, Yujia Li, Yang Song, Shenlong Wang, Charlie Nash, William L Hamilton, David Duvenaud, Raquel Urtasun, and Richard S Zemel. Efficient graph generation with graph recurrent attention networks. *arXiv preprint arXiv:1910.00760*, 2019.

[29] Jenny Liu, Aviral Kumar, Jimmy Ba, Jamie Kiros, and Kevin Swersky. Graph normalizing flows. In *NeurIPS*, pages 13556–13566, 2019.

[30] Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Icml*, 2010.

[31] Kenta Oono and Taiji Suzuki. Graph neural networks exponentially lose expressive power for node classification. In *ICLR*, 2020.

[32] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *JMLR*, 12:2825–2830, 2011.

[33] Shah Rukh Qasim, Jan Kieseler, Yutaro Iiyama, and Maurizio Pierini. Learning representations of irregular particle-detector geometry with distance-weighted graph networks. *The European Physical Journal C*, 79(7):1–11, 2019.

[34] Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500):2323–2326, 2000.

[35] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2008.

[36] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

[37] Otilia Stretcu, Krishnamurthy Viswanathan, Dana Movshovitz-Attias, Emmanouil Platanios, Sujith Ravi, and Andrew Tomkins. Graph agreement models for semi-supervised learning. In *NeurIPS*, pages 8713–8723, 2019.

[38] Mohammed Suhail and Leonid Sigal. Mixture-kernel graph attention network for situation recognition. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 10363–10372, 2019.

[39] Joshua B Tenenbaum, Vin De Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500):2319–2323, 2000.

[40] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. In *ICLR*, 2018.

[41] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *ICML*, pages 1096–1103, 2008.

[42] Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *Acm Transactions On Graphics (tog)*, 38(5):1–12, 2019.

[43] Xuan Wu, Lingxiao Zhao, and Leman Akoglu. A quest for structure: Jointly learning the graph structure and semi-supervised classification. In *CIKM*, pages 87–96, 2018.

[44] Liang Yang, Zesheng Kang, Xiaochun Cao, Di Jin, Bo Yang, and Yuanfang Guo. Topology optimization based graph convolutional network. In *IJCAI*, pages 4054–4061, 2019.

[45] Jiaxuan You, Rex Ying, Xiang Ren, William L Hamilton, and Jure Leskovec. Graphrnn: Generating realistic graphs with deep auto-regressive models. *arXiv preprint arXiv:1802.08773*, 2018.

[46] Yuning You, Tianlong Chen, Zhangyang Wang, and Yang Shen. When does self-supervision help graph convolutional networks? *arXiv preprint arXiv:2006.09136*, 2020.

[47] Donghan Yu, Ruohong Zhang, Zhengbao Jiang, Yuexin Wu, and Yiming Yang. Graph-revised convolutional network. In *ECML PKDD*, 2020.

[48] Jiani Zhang, Xingjian Shi, Junyuan Xie, Hao Ma, Irwin King, and Dit-Yan Yeung. Gaan: Gated attention networks for learning on large and spatiotemporal graphs. *arXiv preprint arXiv:1803.07294*, 2018.

[49] Jiawei Zhang, Haopeng Zhang, Congying Xia, and Li Sun. Graph-bert: Only attention is needed for learning graph representations. *arXiv preprint arXiv:2001.05140*, 2020.

[50] Tong Zhao, Yozen Liu, Leonardo Neves, Oliver Woodford, Meng Jiang, and Neil Shah. Data augmentation for graph neural networks. *arXiv preprint arXiv:2006.06830*, 2020.

[51] Hao Zhu, Yankai Lin, Zhiyuan Liu, Jie Fu, Tat-seng Chua, and Maosong Sun. Graph neural networks with generated parameters for relation extraction. *arXiv preprint arXiv:1902.00756*, 2019.

[52] Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *Advances in Neural Information Processing Systems*, 33, 2020.

[53] Qikui Zhu, Bo Du, and Pingkun Yan. Self-supervised training of graph convolutional networks. *arXiv preprint arXiv:2006.02380*, 2020.

[54] Xiaojin Zhu and Zoubin Ghahramani. Learning from labeled and unlabeled data with label propagation. 2002.

[55] Yanqiao Zhu, Weizhi Xu, Jinghao Zhang, Qiang Liu, Shu Wu, and Liang Wang. Deep graph structure learning for robust representations: A survey. *arXiv preprint arXiv:2103.03036*, 2021.

[56] Daniel Zügner, Amir Akbarnejad, and Stephan Günnemann. Adversarial attacks on neural networks for graph data. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 2847–2856, 2018.