Learning Models for Actionable Recourse

Abstract

As machine learning models are increasingly deployed in high-stakes domains
such as legal and financial decision-making, there has been growing interest in
post-hoc methods for generating counterfactual explanations. Such explanations
provide individuals adversely impacted by predicted outcomes (e.g., an applicant
denied a loan) with *recourse*—i.e., a description of how they can change their
features to obtain a positive outcome. We propose a novel algorithm that leverages
adversarial training and PAC confidence sets to learn models that *theoretically
guarantee* recourse to affected individuals with high probability. We demonstrate
the efficacy of our approach with extensive experiments on real data.

1 Introduction

In recent years, there has been a growing interest in using machine learning to inform consequential
decisions in legal and financial decision-making—e.g., deciding whether to give an applicant a
loan [Hardt et al., 2016], or whether to grant bail to a defendant [Lakkaraju and Rudin, 2017] or
parole to a prisoner [Zeng et al., 2017]. Because these decisions have an impact on the lives of the
concerned individuals, it is critical to explain why the model made its prediction. Explanations are
important not only to ensure that there are no issues with the way the prediction is made (e.g., making
sure the decision is free of racial/gender bias [Hardt et al., 2016] and does not suffer from causal
issues [Bastani et al., 2017]), but also to give the affected individual a justification for the decision.
Thus, there has been a great deal of recent interest in explainable machine learning [Lou et al., 2012,
Wang and Rudin, 2015, Ribeiro et al., 2016b, Lakkaraju et al., 2019].

We focus on *counterfactual explanations* [Wachter et al., 2017], which specify how features can be
changed to obtain a different model prediction. These explanations can be used to provide individuals
who are negatively impacted by model outcomes with *actionable recourses*—i.e., actions they can
take to receive a positive outcome [Ustun et al., 2019]. For instance, for an applicant denied a loan,
a counterfactual explanation might be: "to get a loan, increase your income by $1,000". Such an
explanation must satisfy two properties: (i) it only changes features that the individual can realistically
modify—e.g., it cannot change race or gender, but can change income, and (ii) the magnitude of the
change must be reasonable. The specific set of permissible changes is domain-specific.

Prior research has proposed algorithms for computing individual recourses corresponding to certain
kinds of models—e.g., using integer linear programming in the context of linear models [Ustun
et al., 2019], or using gradient descent on the input for differentiable models [Wachter et al., 2017].
However, these approaches do not guarantee that actionable recourses exist; at best, Ustun et al. [2019]
guarantee that they find one if it exists, and only for linear models. In other words, many affected
individuals may not even be prescribed any actions that they can take to change their outcome.

We propose a novel algorithm for learning models in a way that is designed to *ensure* the existence of
actionable recourses so that affected individuals receive recourse with a high probability. To the best
of our knowledge, our approach is the first to train models for which recourse is likely to exist with a

high probability. It builds on adversarial training [Goodfellow et al., 2015a], which is designed to ensure that models are robust to adversarial examples. At a high level, given a binary classification model $f_\theta : \mathcal{X} \to \mathcal{Y}$, where $\mathcal{Y} = \{0, 1\}$, an adversarial example is a perturbation $\delta \in \Delta$ to an input $x \in \mathcal{X}$ such that $f_\theta(x + \delta) \neq f_\theta(x)$. In a typical adversarial training setting, we choose Δ to be "small" in some sense (e.g., in terms of L_∞ norm of $\delta \in \Delta$) and aim to guarantee that adversarial examples do not exist—i.e., $f(x + \delta) = f(x)$ for all $\delta \in \Delta$.

In contrast, in our setting, we intuitively want to ensure that adversarial examples *do* exist. In particular, given an input x for which $f(x) = 0$, we want there to exist recourse $\delta \in \Delta$ such that $f(x + \delta) = 1$, where in our case, Δ is the given set of all permissible recourses for the application domain. Thus, we adapt existing adversarial training algorithms to ensure the existence of recourse. As an added benefit, these algorithms can compute recourse significantly faster than existing techniques for general differentiable models [Wachter et al., 2017].

While adversarial training heuristically encourages recourse to exist, it does not provide any theoretical guarantees. We build on PAC confidence sets [Park et al., 2020] to guarantee that recourse exists with high probability (assuming the test distribution is the same as the training distribution).

We evaluate the efficacy of our approach on four real world datasets that cover lending, recidivism, bail, and credit outcomes. Our results demonstrate that our approach is very effective at improving recourse rates (i.e., the probability that individuals are given recourse) without noticeably reducing accuracy.

In addition, we show that we achieve this improvement in recourse rates without noticeably harming the quality of recourses or the underlying model. Firstly, we empirically demonstrate that our approach improves the rate at which models provide *correct* recourses (i.e., whether the ground truth label for an individual changes if they change their features as specified by the recourse); we find that our approach encourages the existence of recourses that obey causal constraints driven by real-world causal relationships. Secondly, we show that our approach encourages the existence of robust recourses. Lastly, we show that these improvements in recourse rates do not render the underlying classifier brittle.

Related work. Beyond Wachter et al. [2017], Ustun et al. [2019], several other approaches have also been proposed to generate individual recourses [Zhang et al., 2018, Hendricks et al., 2018, Mothilal et al., 2020, Looveren and Klaise, 2019, Poyiadzi et al., 2020, Karimi et al., 2020a,b,c]. However, all these works focus on how to *compute* recourse for different kinds of predictive models; in contrast, our goal is to learn predictive models that provide counterfactual explanations at high rates. Any of these methods can be used in conjunction with our framework. Our work also builds on adversarial training [Szegedy et al., 2014, Goodfellow et al., 2015b, Bastani et al., 2016, Shaham et al., 2018]. While recent work in model explainability has leveraged adversarial training to improve robustness of explanations [Lakkaraju et al., 2020b], their goal was to *reduce* the rate of adversarial examples and our goal is to *increase* the rate of recourses.

2 Problem Formulation

Preliminaries. Consider a binary classifier $f_\theta : \mathcal{X} \to \mathcal{Y}$, where $x \in \mathcal{X} \subseteq \mathbb{R}^{n_X}$ are the features, $y \in \mathcal{Y} = \{0, 1\}$ are the labels, and $\theta \in \Theta \subseteq \mathbb{R}^{n_\Theta}$ are the parameters. We assume that f_θ has the form $f_\theta(x) = \mathbb{1}(g_\theta(x) \geq \theta_0)$, where $g_\theta : \mathcal{X} \to [0, 1]$ is a scoring function and $\theta_0 \in \mathbb{R}$ is a decision threshold. We assume that g_θ is differentiable in x—i.e., $\nabla_x g_\theta(x)$ exists almost everywhere.[1]

Recourse. We seek to ensure that individuals given negative outcomes by f_θ are also given *recourse*.

Definition 2.1. Given a classifier $f_\theta : \mathcal{X} \to \mathcal{Y}$ and a set $\Delta \subseteq \mathbb{R}^{n_X}$, an input $x \in \mathcal{X}$ has *recourse* if there exists $\delta \in \Delta$ such that $f(x + \delta) = 1$.

We use $\mathcal{X}_\theta^R$ to denote the set of inputs for which recourse exists. The specific design of the set of permissible recourses $\Delta \subseteq \mathbb{R}^{n_X}$ is domain specific. We assume that $0 \in \Delta$; then, recourse automatically exists for positive outcomes $f_\theta(x) = 1$ by taking $\delta = 0$. In addition, we assume that Δ is a polytope—i.e., $\Delta = \{\delta \in \mathbb{R}^{n_X} \mid A\delta + b \geq 0\}$ for some $A \in \mathbb{R}^{k \cdot n_X}$ and $b \in \mathbb{R}^k$. That is, Δ can be expressed as a set of affine constraints. This assumption is required for computational tractability.

---

[1]Note that we have focused on real-valued features. We discuss how our algorithm can be extended to handling categorical features in Section B.2.

A standard choice is $\Delta = \{\delta \mid \|\delta\|_\infty \leq \delta_{\max}\}$, which says that the recourse can suggest changes to any feature by a bounded amount. We can apply this constraint after an affine transformation of δ—e.g., to appropriately scale different covariates. In addition, we often want to restrict features—e.g., to avoid suggesting that an individual change their age, we can constrain $\delta_i = 0$, or to avoid suggesting that an individual decrease their income to qualify for a loan, we can constrain $\delta_i \geq 0$. In principle, Δ can also be tailored to individuals—e.g., disallow suggesting increased education for individuals who cannot afford to do so. Finally, Δ should be designed large enough so it includes a plausible recourse for every individual, yet small enough to ensure that the recourses do not overburden the individuals. All of these considerations are domain-specific; we describe our choices for datasets in our experiments in Section 4.

Probably Approximately has REcourse (PARE). Our goal is to ensure that recourse exists for most individuals. Given a confidence level $\epsilon \in \mathbb{R}_{>0}$, we say that θ *approximately has recourse* if

$$\mathbb{P}_{p(x)}\left[x \in \mathcal{X}_\theta^R\right] \geq 1 - \epsilon,$$

i.e., recourse exists for f_θ with probability at least $1 - \epsilon$ w.r.t. the distribution $p(x)$ over individuals.

Then, our goal is to design an algorithm for estimating the model parameters θ so that f_θ approximately has recourse. To do so, our algorithm takes as input a held-out calibration dataset $Z \subseteq \mathcal{X} \times \mathcal{Y}$ of examples $(x, y) \sim p$, where $p(x, y)$ is the distribution over labeled examples, and outputs model parameters $\hat{\theta}(Z)$. Then, as in the probably approximately correct (PAC) learning framework [Valiant, 1984], our algorithm might additionally fail due to the randomness in Z. Thus, given a second confidence level $\alpha \in \mathbb{R}_{>0}$, we say that $\hat{\theta}$ *Probably Approximately has REcourse (PARE)* if

$$\mathbb{P}_{p(Z)}\left[\hat{\theta}(Z) \text{ approximately has recourse}\right] \geq 1 - \alpha,$$

where $p(Z) = \prod_{(x,y) \in Z} p(x, y)$. In other words, our algorithm produces a model that approximately has recourse with probability at least $1 - \delta$ over $p(Z)$.

Constructing a PARE classifier. Note that we can trivially obtain a PARE classifier f_θ by choosing the decision threshold $\theta_0 = 0$, in which case $f_\theta(x) = 1$ for all $x \in \mathcal{X}$. However, this approach is undesirable since it assigns a positive outcome to all individuals. Instead, we want to maximize the performance of f_θ (e.g., in terms of accuracy, F_1 score, etc.) subject to a constraint that f_θ is PARE. Thus, we divide the problem of constructing a PARE classifier into two parts (i) increasing recourse rate: we train g_θ in a way that heuristically increases the rate at which inputs $x \in \mathcal{X}$ have recourse (for any θ_0), and (ii) guaranteeing recourse: we choose θ_0 to guarantee that the resulting f_θ is PARE.

3 Our Algorithm

We describe our algorithm for learning models that satisfy PARE while achieving good performance. We describe Step 1 (increasing recourse rate) in Section 3.1 and Step 2 (guaranteeing recourse) in Section 3.3. We describe ways to compute recourse in Section 3.2.

3.1 Step 1: Increasing Recourse Rate

Background: adversarial training. Consider a classifier $f_\theta : \mathcal{X} \to \mathcal{Y}$ and perturbations $\Delta \subseteq \mathbb{R}^{n_X}$. Given $x \in \mathcal{X}$, an *adversarial example* [Szegedy et al., 2014] for x is a perturbation $\delta \in \Delta$ such that $f_\theta(x + \delta) \neq f_\theta(x)$—i.e., the perturbation δ (restricted to be small) changes the predicted label of x.

Adversarial examples are undesirable because they indicate that f_θ is not robust to small changes to the input that should not affect the class label (e.g., according to human predictions). Thus, there has been a great deal of interest in designing algorithms for improving robustness to adversarial examples. The basic approach is *adversarial training* [Goodfellow et al., 2015b], which dynamically computes adversarial examples for inputs in the training set and adds these to the objective as additional training examples similar to data augmentation. In particular, given a loss function $\ell : \mathbb{R} \times \mathcal{Y} \to \mathbb{R}$, where $\ell(g_\theta(x), y)$ is the loss for training example (x, y), they seek to compute

$$\theta^* = \underset{\theta \in \Theta}{\arg\min}\, \ell_A(\theta) \quad \text{where} \quad \ell_A(\theta) = \mathbb{E}_{p(x,y)}\left[\ell(g_\theta(x), y) + \lambda \cdot \max_{\delta \in \Delta} \ell(g_\theta(x + \delta), y)\right].$$

In $\ell_A(\theta)$, the first term is the supervised learning loss, the second is the adversarially robust loss (i.e., encourage g_θ to be robust to adversarial examples $x + \delta$), and $\lambda \in \mathbb{R}_{\geq 0}$ is a hyperparameter.

The challenge in optimizing $\ell_A(\theta)$ is computing the maximum over $\delta \in \Delta$. To address this challenge, existing adversarial training algorithms leverage approximations enabling efficient computation of δ.

Our approach. We use adversarial training to learn a model f_θ for which inputs $x \in \mathcal{X}$ have recourse at higher rates compared to models trained using conventional approaches. There are two key differences compared to adversarial training. First, we want recourse to exist, which corresponds to *encouraging* the existence of adversarial examples. Second, we only care about changing negative labels $f_\theta(x) = 0$ to positive ones $f_\theta(x + \delta) = 1$, not vice versa. Thus, we want to solve

$$\theta^* = \underset{\theta \in \Theta}{\arg\min}\, \ell_R(\theta) \quad \text{where} \quad \ell_R(\theta) = \mathbb{E}_{p(x,y)}\left[\ell(g_\theta(x), y) + \lambda \cdot \underset{\delta \in \Delta}{\min}\, \ell(g_\theta(x + \delta), 1)\right]. \quad (1)$$

Compared to ℓ_A, ℓ_R has a different second term in two ways: (i) the maximum over δ with a minimum, and (ii) the label y is replaced with the label 1. We note that when $\lambda = 0$, Eq. 1 is supervised learning.

We optimize Eq. 1 using *adversarial training* [Goodfellow et al., 2015a, Shaham et al., 2018, Lakkaraju et al., 2020a], which performs stochastic gradient descent on $\ell_R(\theta)$. The key challenge to computing $\nabla_\theta \ell_R(\theta)$ is computing the gradient of the second term. We approximate it as follows:

$$\nabla_\theta \underset{\delta \in \Delta}{\min}\, \ell(g_\theta(x + \delta), 1) \approx \nabla_\theta \ell(g_\theta(x + \delta^*), 1),$$

where δ^* is the perturbation that maximizes the likelihood of positive outcome, or minimizes the loss between predicted and positive outcomes—i.e.,

$$\delta^* = \underset{\delta \in \Delta}{\arg\min}\, \ell(g_\theta(x + \delta), 1). \quad (2)$$

Computing δ^* remains computationally challenging; thus, we use a Taylor approximation of the loss $\ell(g_\theta(x + \delta), 1) \approx \ell(g_\theta(x), 1) + \nabla_x \ell(g_\theta(x), 1)^\top \delta$. Using this approximation, Eq. 2 becomes

$$\delta^* = \underset{\delta \in \Delta}{\arg\min}\, \ell(g_\theta(x + \delta), 1) \approx \underset{\delta \in \Delta}{\arg\min}\, \nabla_x \ell(g_\theta(x), 1)^\top \delta,$$

where we have dropped the term $\ell(g_\theta(x), 1)$ since it is constant with respect to δ. Finally, note that the optimization problem on the last step is a linear program (LP), since we have assumed that $\delta \in \Delta$ can be expressed as a set of affine constraints and since the objective is linear in δ. In summary, we optimize Eq. 1 using stochastic gradient descent, where at each step we solve an LP to approximate the second term—i.e., given parameters θ_i and example (x_i, y_i) on gradient step i, and step size $\eta_i \in \mathbb{R}_{>0}$ on step i, we use the stochastic gradient update

$$\theta_{i+1} = \theta_i + \eta_i \left(\nabla_\theta \ell(g_\theta(x), y) + \lambda \cdot \nabla_\theta \ell(g_\theta(x + \delta_i^*), 1)\right) \quad \text{where} \quad \delta_i^* = \underset{\delta \in \Delta}{\arg\min}\, \nabla_x \ell(g_\theta(x), 1)^\top \delta.$$

3.2 Computing Recourse

So far, we have focused on how to train a model f_θ that provides recourse. Once we have trained f_θ, we still need a way to compute recourse for a given individual x—i.e., an algorithm $\mathcal{A} : \mathcal{X} \rightarrow \Delta$ for computing $\delta_x = \mathcal{A}(x)$ such that $f(x + \delta_x) = 1$. We describe three such algorithms; in general, any algorithm designed to output recourses can be used [Karimi et al., 2020a, Poyiadzi et al., 2020].

Gradient descent. The approach proposed in Wachter et al. [2017] can directly be applied to compute recourse. They solve the problem

$$\delta_x = \underset{\delta \in \Delta}{\arg\min}\{\ell(g_\theta(x + \delta, 1) + \lambda' \cdot \|\delta\|_2\},$$

where $\lambda' \in \mathbb{R}_{\geq 0}$ is a hyperparameter, using gradient descent on δ. The term $\|\delta\|_2$ is designed to encourage the recourse δ to be small, which is often desirable in practice (we have excluded it from our formulation for simplicity). While this approach is generally effective, it can be very slow since we need to solve an optimization problem for each individual.

Adversarial training. We can also use adversarial training to compute recourse—i.e.,

$$\delta_x = \underset{\delta \in \Delta}{\arg\min}\, \nabla_x \ell(g_\theta(x), 1)^\top \delta.$$

167 This approach approximates the gradient descent approach, but can be computed much more effi-
168 ciently. Furthermore, since our objective in Eq. 1 is designed to encourage this specific perturbation
169 to provide recourse, it performs nearly as well as gradient descent when f_θ is trained with $\lambda > 0$.

170 **Linear approximation.** Finally, Ustun et al. [2019] propose an approach to compute recourse
171 when $f_\theta(x) = \mathbb{1}(\beta^\top x \geq \beta_0)$ is a linear model. In this case, they compute δ_x using an integer
172 linear program (ILP). For nonlinear models, we can instead use the linear approximation of g_θ near
173 x. Letting $\delta_x = \mathcal{A}(x; \beta_0, \beta)$ be the recourse generated by their algorithm, and using the Taylor
174 expansion $g_\theta(x') \approx g_\theta(x) + \nabla_x g_\theta(x)^\top (x' - x)$, we can use their approach to compute the recourse

$$\delta_x = \mathcal{A}(x; \theta_0 - g_\theta(x), \nabla_x g_\theta(x)).$$

175 However, this approach only works well when g_θ is approximately linear as a function of x; otherwise,
176 the Taylor approximation may be poor and δ_x may not satisfy the desired condition $f_\theta(x + \delta_x) = 1$.

3.3 Step 2: Guaranteeing Recourse

178 Finally, we describe how we choose θ_0 to ensure that f_θ provides recourse with high probability.
179 Note that θ_0 also controls the fraction of individuals given a positive outcome *without* the need for
180 recourse; thus, choose θ_0 to optimize the performance of f_θ subject to a constraint that f_θ is PARE.

181 **Background: PAC confidence sets.** We build on work constructing PAC confidence sets [Park et al.,
182 2020]. Given $x \in \mathcal{X}$, they construct a model $\tilde{h}_{\theta,\tau} : \mathcal{X} \to \mathcal{P}(\mathcal{Y})$ (where $\mathcal{P}$ is the power set) that
183 returns the set of all labels y with score above threshold $\tau \in \mathbb{R}$—i.e.,

$$\tilde{h}_{\theta,\tau}(x) = \{y \in \mathcal{Y} \mid h_\theta(x, y) \geq \tau\} \quad \text{where} \quad h_\theta(x, y) = \begin{cases} g_\theta(x) & \text{if } y = 1 \\ 1 - g_\theta(x) & \text{if } y = 0. \end{cases}$$

184 Given $\epsilon \in \mathbb{R}_{>0}$, we say τ is *approximately correct* if

$$\mathbb{P}_{p(x,y)}[y \in \tilde{h}_{\theta,\tau}(x)] \geq 1 - \epsilon,$$

185 i.e., $\tilde{h}_{\theta,\tau}(x)$ contains the true label for x with high probability over $p(x, y)$. Note that $\tau = 0$ satisfies
186 this condition, since $\tilde{h}_{\theta,0}(x) = \{0, 1\}$ for all x. The goal is to choose τ as large as possible while
187 ensuring approximate correctness.

188 Park et al. [2020] proposes an estimator $\hat{\tau}$ that takes as input (i) the pretrained model $g_\theta : \mathcal{X} \to [0, 1]$,
189 (ii) a calibration dataset $Z \subseteq \mathcal{X} \times \mathcal{Y}$ of i.i.d. samples $(x, y) \sim p$, and (iii) confidence levels
190 $\epsilon, \alpha \in \mathbb{R}_{>0}$, and constructs a threshold $\hat{\tau}(Z) \in [0, 1]$ that is *probably approximately correct (PAC)*:

$$\mathbb{P}_{p(Z)}[\hat{\tau}(Z) \text{ is approximately correct}] \geq 1 - \alpha. \tag{3}$$

191 In other words, $\hat{\tau}(Z)$ is approximately correct with probability at least $1 - \alpha$ according to $p(Z)$.
192 Their approach leverages the fact that $\hat{\tau}(Z)$ is an estimator for a single parameter; thus, they can use
193 learning theory to obtain PAC guarantees [Kearns et al., 1994].

194 **PARE models via PAC confidence sets.** Given a model $g_\theta : \mathcal{X} \to \mathbb{R}$, an algorithm $\mathcal{A} : \mathcal{X} \to \Delta$ for
195 computing recourse, and a calibration set $Z \subseteq \mathcal{X} \times \mathcal{Y}$, our algorithm leverages PAC confidence sets
196 to choose a threshold $\theta_0 = \hat{\theta}_0(Z)$ that ensures the resulting model $f_{\hat{\theta}}$ satisfies the PARE constraint.

197 First, our algorithm uses the PAC confidence set algorithm constructs the new calibration dataset

$$Z' = \{(x + \mathcal{A}(x), 1) \mid (x, y) \in Z\}.$$

198 Intuitively, Z' says that the "correct" label for every input $x + \mathcal{A}$ should be 1—i.e., the recourse
199 constructed by $\mathcal{A}$ should satisfy $f_\theta(x + \mathcal{A}(x)) = 1$.

200 Then, our algorithm constructs $\tilde{h}_{\theta,\hat{\tau}(Z)}$ using g_θ, Z', and the given ϵ, α. The PAC guarantee in Eq. 3
201 says that with probability at least $1 - \alpha$ over $p(Z)$, we have

$$\mathbb{P}_{p(Z)}\left[\mathbb{P}_{p(x,y)}[y' \in \tilde{h}_{\theta,\hat{\tau}(Z')}(x')]] \geq 1 - \epsilon\right] \geq 1 - \alpha, \tag{4}$$

202 where $(x', y') \in Z'$ is the example constructed from $(x, y) \in Z$ as described above. Note that the
203 outer probability is over $p(Z)$ since Z' is a deterministic function of the random variable Z. Plugging
204 in the definitions $x' = x + \mathcal{A}(x)$ and $y' = 1$, Eq. 4 becomes

$$\mathbb{P}_{p(Z)}\left[\mathbb{P}_{p(x,y)}[1 \in \tilde{h}_{\theta,\hat{\tau}(Z')}(x + \mathcal{A}(x))] \geq 1 - \epsilon\right] \geq 1 - \alpha,$$

Metrics	Adult		Compas		Bail		German	
	Baseline	Ours	Baseline	Ours	Baseline	Ours	Baseline	Ours
F1 score	**0.697**	0.636	**0.739**	0.717	**0.775**	0.760	**0.455**	0.397
Accuracy	**0.830**	0.787	**0.667**	0.565	**0.643**	0.629	**0.577**	0.550
Precision	**0.621**	0.555	**0.655**	0.561	**0.646**	0.644	**0.357**	0.318
Recall	**0.799**	0.752	0.850	**0.991**	**0.968**	0.930	**0.645**	0.588
Linear approx.	**0.220**	0.053	**0.156**	0.068	**0.102**	0.029	**0.204**	0.086
Gradient desc.	0.210	**0.496**	0.579	**1.000**	0.317	**1.000**	**0.833**	0.826
Adversarial train.	0.007	**0.498**	0.000	**0.967**	0.000	**0.993**	0.165	**0.936**
Linear approx.	**0.453**	0.328	0.773	**0.982**	0.957	**0.981**	**0.607**	0.593
Gradient desc.	0.461	**0.661**	0.883	**1.000**	0.970	**1.000**	**0.913**	0.873
Adversarial train.	0.321	**0.659**	0.722	**0.999**	0.952	**0.999**	0.580	**0.950**

Table 1: Performance and recourse for the baseline model ($\lambda = 0$) and the model trained with our algorithm ($\lambda = 0.8$), and for each of the three algorithms for computing recourse in Section 3.2. We bold the higher value between the baseline and our algorithm.

Figure 1: How performance and recourse vary with λ; $\lambda = 0$ is the baseline and $\lambda > 0$ is our approach. The first row shows performance metrics; the second and third show recourse metrics. *Performance:* ■ F_1 ■ Accuracy. *Recourse Algorithm:* ■ "gradient descent" ■ "adversarial training".

and plugging in the definition of $\tilde{h}_{\theta,\tau}$, it becomes

$$\mathbb{P}_{p(Z)}\left[\mathbb{P}_{p(x,y)}[g_\theta(x + \mathcal{A}(x)) \geq \hat{\tau}(Z')] \geq 1 - \epsilon\right] \geq 1 - \alpha. \tag{5}$$

Then, our algorithm returns $\hat{\theta}_0(Z) = \hat{\tau}(Z')$ (with given parameters θ as the remaining parameters). Since Eq. 5 is equivalent to the PARE condition, we have:

Theorem 3.1. $\hat{\theta}$ *satisfies the PARE condition.*

4 Experiments

We evaluate our approach and show how it can effectively improve recourse rate while preserving accuracy. We also demonstrate how it can improve the correctness and robustness of recourses. In Appendix B, we provide additional results on how our approach affects fairness of models, as well as results on an NLP task with discrete covariates to demonstrate the flexibility of our framework.

4.1 Experimental Setup

Datasets. We use four real-world datasets. The first contains **adult income** information from the 1994 United States Census Bureau. It includes information about adults' demographics, education, and occupations. Each adult is labeled as making below or $> \$50K$ a year, which can be thought of as a proxy for whether an individual will be able to repay a loan or not. The second contains information collected by Propublica about criminal defendants' **compas recidivism scores** [Angwin et al., 2016]. This dataset includes information about defendants' demographics and crimes, and each defendant

Figure 2: How performance and recourse vary with θ_0, for our approach ($\lambda = 0.8$, left) and the baseline ($\lambda = 0$, right). *Performance:* ■ F_1 ■ Accuracy. *Recourse:* ■ Recourse neg ■ Recourse all.

is labeled as having either a high or low likelihood of reoffending, as measured by the compas assessment tool. The third dataset represents **bail outcomes** from two different U.S. state courts from 1990-2009. It includes information about individuals' criminal histories and demographics. Each defendant is labeled as having a high or low risk of recidivism. The fourth dataset is the **german credit** dataset [Dua and Graff, 2017], which contains individuals' demographic, personal, and financial information. Each applicant is labeled as either having high or low credit risk.

We standardize all continuous features to have mean 0 and variance 1. We randomly split each dataset into 80% train and 20% validation sets. We experiment with 3 random data splits and report mean results across splits throughout the rest of this section. For compas and adult, we hold out 500 examples from the validation set to form a test set; for german, we hold out 100 examples. For bail, we evaluate on a 500-instance subset of the test set. All results are reported on the test set.[2]

Models. All models are neural networks with 3 100-node hidden layers, dropout probability 0.3, and tanh activations. For evaluation, we choose the epoch achieving the highest validation F_1 score.

Parameters. We experimented with λ from 0.0 to 2.0 in increments of 0.1 and found that $\lambda = 0.8$ provided the best tradeoff between F_1 score and recourse rate across all datasets; we evaluate how our results vary with λ below. For Δ, we choose the set of actionable features (i.e., features that can be changed as part of the recourse) based on the dataset (two features for adult, bail, german; one for compas); we set $\delta_{\max} = 0.75$ after standardizing all features to have mean zero and standard deviation one. We also include domain-specific linear constraints in Δ—i.e., for the adult dataset, recourse can only require that hours worked increases. See Appendix A.3 for more details about our choices of Δ.

We choose the decision threshold θ_0 to maximize F1 score rather than to obtain PAC guarantees, since our goal is to understand the tradeoffs between model performance and recourse rates with a fixed underlying predictive model f_θ. We evaluate the effects of rigorously choosing θ_0 in Section 4.2.

Baselines. To the best of our knowledge, our approach is the first to train models with the objective of providing recourse at a higher rate. Thus, we compare to a baseline that omits our recourse loss—i.e., $\lambda = 0.0$. For our approach and this baseline, we evaluate the performance of each of the three different algorithms for computing recourse described in Section 3.2. We use the alibi implementation [Klaise et al., 2019] of the gradient descent algorithm for computing recourse [Wachter et al., 2017] and set the initial value of the hyperparameter $\lambda' = 0.001$. We use LIME [Ribeiro et al., 2016a] as our linear approximation method with the approach proposed by Ustun et al. [2019].

Metrics. We evaluate our approach and the baselines with the following metrics: (i) standard performance metrics of accuracy and F_1 score, (ii) "recourse neg", the proportion of instances x such that $f(x) = 0$ but $f(x + \delta^*) = 1$, and (iii) "recourse all", the proportion of instances such that *either* $f(x) = 1$ *or* $f(x) = 0$ but $f(x + \delta^*) = 1$. Metric (iii) is most useful for measuring recourse, since we want to include individuals who are already assigned a positive outcome.

4.2 Efficacy of Our Framework

In Table 1, we show the performance and recourse rates of models trained with our approach and baseline models. Overall, our approach significantly improves recourse without sacrificing performance. Across datasets, models trained using our approach offer recourse at significantly higher rates than the baseline model, for both the "adversarial training" and "gradient descent"

---

[2]Our processed datasets have sizes: adult $\approx 32.5K$, compas $\approx 6K$, bail $\approx 8K$, german $\approx 1K$.

| | **Adult** | | **Compas** | | **Bail** | | **German** | |
	F_1	Recourse	F_1	Recourse	F_1	Recourse	F_1	Recourse
BL + F_1 max	0.697	0.321	0.739	0.722	0.775	0.952	0.455	0.580
BL + PARE	0.400	0.981	0.722	0.972	0.777	0.996	0.442	0.997
Ours + F_1 max	0.636	0.659	0.717	0.999	0.760	0.999	0.397	0.950
Ours + PARE	0.526	0.974	0.721	0.999	0.776	0.999	0.443	0.997

Table 2: Impact of choosing decision threshold θ_0 to satisfy the PARE constraint. We show F_1 scores for the baseline model and the model trained with our algorithm using two methods of determining θ_0: (i) maximize the F_1 score, and (ii) guarantee that the model satisfies the PARE constraint (+PARE, bolded). For the baseline model (BL), $\lambda = 0$; for our model (Ours), $\lambda = 0.8$.

Figure 3: "Recourse neg" for the german dataset using the causal recourse computing algorithm proposed by Karimi et al. [2020b]. We show results for varying values of λ.

approaches to computing recourse. We do not observe this trend when using "linear approximation" to compute recourse; in this case, both the baseline and our approach perform poorly. We believe this effect can be explained by poor LIME approximations of f_θ, which are exacerbated by adversarial training since it increases the nonlinearity of f_θ. Figure 1 shows how these results vary with λ: F_1 scores and accuracies are relatively stable as a function of λ.

In Figure 2, we plot how these results vary with θ_0 (for $\lambda = 0.8$). High values of θ_0 lead to lower recourse rates in all cases. The curves for performance are similar for the baseline and for our approach, but the decline in recourse values begins at lower thresholds in the case of the baseline. Thus, our approach improves recourse for most choices of θ_0 without sacrificing performance. The trade-off between recourse and performance depends on the dataset. For adult, performance increases while recourse decreases since the majority label in this dataset is negative, whereas for bail and compas, performance and recourse both decrease as θ_0 increases since the majority label is positive.

Performance under PARE guarantees. Next, we show that we can often obtain PARE guarantees without significantly reducing performance. We compare the performance of choosing the decision threshold θ_0 to maximize F_1 score to that of θ_0 chosen to obtain PARE classifiers. Specifically, for the latter, we compute θ_0 using the approach described in Section 3.3 with parameters $\epsilon = \alpha = 0.05$. Then, we evaluate models at thresholds in 10 equally spaced increments from 0 to the upper bound and fix θ_0 to maximize F1 score. For these experiments, we use the "adversarial training" algorithm to compute recourse; we observed similar trends for the "gradient descent" algorithm.

Results are shown in Table 2. In all cases, choosing θ_0 to satisfy the PARE condition yields a classifier that returns recourse at a rate $\geq 1 - \epsilon = 0.95$, which validates our theoretical guarantees. Furthermore, on all three datasets, the F_1 score does not significantly decrease when imposing the PARE condition. We do see a decrease in F_1 score for the baseline model on the adult dataset, but the decrease for our model is smaller, suggesting that our end-to-end framework of training models and fixing θ_0 is successful at guaranteeing recourse without a big drop in accuracy.[3]

Recourse correctness. One key question is whether the recourses of models trained with our approach are *correct*—i.e., whether they are plausible modifications of the ground truth label. For instance, if an individual is denied a loan, they should be given a recourse such that if they take the specified action, they actually increase their likelihood of paying back the loan; an individual

---

[3]We can obtain a weaker theoretical guarantee at a smaller cost in performance. For instance, applying PARE to our model in Table 2 with $\epsilon = \alpha = 0.25$ results in an F1 score of 0.613 on the adult dataset.

Robustness Exp.	Recourse Alg.	Adult		Compas		Bail		German	
		BL	Ours	BL	Ours	BL	Ours	BL	Ours
Recourse	Grad. desc.	1.000	0.865	1.000	1.000	1.000	1.000	0.949	0.898
	Advers. train.	1.000	0.841	1.000	1.000	1.000	1.000	0.857	1.000
Model	–	0.976	0.926	0.980	1.000	0.994	0.996	0.970	0.920

Table 3: The first row shows the percentage of recourses found that are robust to noise. The second row shows the percentage of test inputs that are robust to noise in the recourse dimensions. We show results for varying λ ($\lambda = 0$ indicates the baseline, and $\lambda = 0.8$ indicates our approach), as well as the "gradient descent" and "adversarial training" algorithms for computing recourse in Section 3.2.

may increase their income and be given a loan, but still fail to repay it. We want to ensure that our training approach increases the rate of recourses that obey causal relationships in the world, rather than recourses that exploit spurious correlations between features.

Directly evaluating correctness of recourses is challenging, since we cannot know the ground truth label for the suggested recourse. Thus, we choose to the measure the rate at which causally sound recourses are offered by models trained with our approach. Specifically, we apply the algorithm for computing causal recourses (CR) introduced by Karimi et al. [2020b] to evaluate whether our proposed training algorithm improves the rate at which causally grounded recourses are offered.

Because CR requires access to an underlying structural causal model (SCM) of the world, we only experiment with the german dataset, for which Karimi et al. [2020b] provide an associated SCM. We measure the proportion of test instances x for which the CR algorithm computes a valid recourse that satisfies the constraint that perturbations be bounded by $\delta_{\max}$—i.e. "recourse neg".[4] As shown in Figure 3, with increasing λ, the rate at which recourses are by the CR algorithm increases. This finding suggests that our training algorithm encourages the existence of causally grounded recourses.

Robustness. Another key question is whether the recourses generated using our approach are *robust*— i.e., whether small changes to the recourse result in valid recourses. For instance, if an individual increases their income by more (or even slightly less) than the amount suggested in the recourse, they would expect to still be provided with a positive decision.

For each computed recourse δ, we compute a noisy recourse δ' by adding i.i.d. Gaussian noise to each actionable feature of δ—i.e., $\delta'_i = \delta_i + \mathcal{N}(0, 0.1)$. We consider a recourse δ *robust* if its noisy recourse δ' is valid—i.e. if $f(x + \delta') = 1$.. In the top row of Table 3, we report the percentage of recourses found that are robust for a baseline model and models trained with our adversarial approach. As shown, our training approach does not significantly reduce the robustness of recourses: There is a slight drop in robustness for the adult dataset and for the "gradient descent" recourse algorithm for the german dataset; however, for compas and bail, recourses remain robust.

Effect on classifier brittleness. We also investigate the effect of our adversarial training approach on model brittleness. In particular, we measure how sensitive models trained with our adversarial algorithm are to noises in the recourse dimensions, as compared to baseline models. We add i.i.d. Gaussian noise, as described above, to the actionable dimensions of *original inputs*, and compute the proportion of test instances for which the trained model is robust to this noise. As shown in the bottom row of Table 3, our training approach does not significantly increase model brittleness—we observe a small drop in model robustness in the recourse dimensions for the adult and german datasets and a small increase in robustness for the compas and bail datasets. These results suggest that our training approach effectively ensures recourse without rendering classifiers brittle.

5 Conclusion

We have proposed a novel algorithm for training models that are guaranteed to provide recourse for reversing adverse outcomes with high probability. Our experiments show that our algorithm trains models that provide recourse at high rates without sacrificing accuracy compared to traditional learning algorithms. Future work includes extending our techniques beyond binary classification.

---

[4]We select hyperparameters for the CR algorithm that maximize "recourse neg" on the train set.

References

Julia Angwin, Jeff Larson, Surya Mattu, and Lauren Kirchner. How we analyzed the compas recidivism algorithm. *Propublica*, 2016.

Osbert Bastani, Yani Ioannou, Leonidas Lampropoulos, Dimitrios Vytiniotis, Aditya Nori, and Antonio Criminisi. Measuring neural net robustness with constraints. In *Advances in neural information processing systems*, pages 2613–2621, 2016.

Osbert Bastani, Carolyn Kim, and Hamsa Bastani. Interpreting blackbox models via model extraction. *arXiv preprint arXiv:1705.08504*, 2017.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015a.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015b.

Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In *Advances in neural information processing systems*, pages 3315–3323, 2016.

Lisa Anne Hendricks, Ronghang Hu, Trevor Darrell, and Zeynep Akata. Generating counterfactual explanations with natural language. *arXiv preprint arXiv:1806.09809*, 2018.

Amir-Hossein Karimi, Gilles Barthe, Borja Balle, and Isabel Valera. Model-agnostic counterfactual explanations for consequential decisions. In *International Conference on Artificial Intelligence and Statistics*, pages 895–905, 2020a.

Amir-Hossein Karimi, Bernhard Schölkopf, and Isabel Valera. Algorithmic recourse: from counterfactual explanations to interventions, 2020b.

Amir-Hossein Karimi, Julius von Kügelgen, Bernhard Schölkopf, and Isabel Valera. Algorithmic recourse under imperfect causal knowledge: a probabilistic approach, 2020c.

Michael J Kearns, Umesh Virkumar Vazirani, and Umesh Vazirani. *An introduction to computational learning theory*. MIT press, 1994.

Janis Klaise, Arnaud Van Looveren, Giovanni Vacanti, and Alexandru Coca. Alibi: Algorithms for monitoring and explaining machine learning models, 2019. URL https://github.com/SeldonIO/alibi.

Himabindu Lakkaraju and Cynthia Rudin. Learning cost-effective and interpretable treatment regimes. In *Artificial Intelligence and Statistics*, pages 166–175, 2017.

Himabindu Lakkaraju, Ece Kamar, Rich Caruana, and Jure Leskovec. Faithful and customizable explanations of black box models. In *Proceedings of the 2019 AAAI/ACM Conference on AI, Ethics, and Society*, pages 131–138. ACM, 2019.

Himabindu Lakkaraju, Nino Arsov, and Osbert Bastani. Robust and Stable Black Box Explanations. *Icml*, 2020a.

Himabindu Lakkaraju, Nino Arsov, and Osbert Bastani. Robust and stable black box explanations. In *ICML*, 2020b.

Arnaud Van Looveren and Janis Klaise. Interpretable counterfactual explanations guided by proto-types, 2019.

Yin Lou, Rich Caruana, and Johannes Gehrke. Intelligible models for classification and regression. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 150–158, 2012.

Ramaravind K Mothilal, Amit Sharma, and Chenhao Tan. Explaining machine learning classifiers through diverse counterfactual explanations. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, pages 607–617, 2020.

Sangdon Park, Osbert Bastani, Nikolai Matni, and Insup Lee. Pac confidence sets for deep neural networks via calibrated prediction. In *ICLR*, 2020.

Rafael Poyiadzi, Kacper Sokol, Raul Santos-Rodriguez, Tijl De Bie, and Peter Flach. Face: Feasible and actionable counterfactual explanations. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, AIES '20, page 344–350, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450371100. doi: 10.1145/3375627.3375850. URL https://doi.org/10.1145/3375627.3375850.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, CA, USA, August 13-17, 2016*, pages 1135–1144, 2016a.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. " why should i trust you?" explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1135–1144, 2016b.

Uri Shaham, Yutaro Yamada, and Sahand Negahban. Understanding adversarial training: Increasing local stability of supervised models through robust optimization. *Neurocomputing*, 307:195–204, 2018.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1631–1642, Seattle, Washington, USA, October 2013. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/D13-1170.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

Berk Ustun, Alexander Spangher, and Yang Liu. Actionable recourse in linear classification. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, pages 10–19, 2019.

Leslie G Valiant. A theory of the learnable. *Communications of the ACM*, 27(11):1134–1142, 1984.

S. Wachter, Brent D. Mittelstadt, and Chris Russell. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *European Economics: Microeconomics & Industrial Organization eJournal*, 2017.

Fulton Wang and Cynthia Rudin. Falling rule lists. In *Artificial Intelligence and Statistics*, pages 1013–1022, 2015.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Huggingface's transformers: State-of-the-art natural language processing, 2019.

Jiaming Zeng, Berk Ustun, and Cynthia Rudin. Interpretable classification models for recidivism prediction. *Journal of the Royal Statistical Society: Series A (Statistics in Society)*, 3(180):689–722, 2017.

Xin Zhang, Armando Solar-Lezama, and Rishabh Singh. Interpreting neural network judgments via minimal, stable, and symbolic corrections. In *Advances in Neural Information Processing Systems*, pages 4874–4885, 2018.