Ex-GraphRAG: Interpretable Evidence Routing for Graph-Augmented LLMs

Yoav Kor Sade[*]
Tel Aviv University

Arvindh Arun[*]
Institute for AI, University of Stuttgart

Rishi Puri
NVIDIA

Steffen Staab
Institute for AI, University of Stuttgart

Maya Bechler-Speicher
Meta AI

Abstract

GraphRAG conditions language models on subgraphs retrieved from knowledge graphs, encoded via message-passing GNNs. Because as these encoders entangle node contributions through iterated neighborhood aggregation, there is no closed-form way to determine how much each retrieved entity influenced the encoder's output, and therefore no way to faithfully audit what structural evidence actually reached the model. We introduce Ex-GraphRAG, which replaces the GNN encoder with a Multivariate Graph Neural Additive Network (M-GNAN), an extension of additive graph models to high-dimensional embedding spaces that yields an exact decomposition of the encoder's output across individual nodes and feature groups, without post-hoc approximation. On STaRK-Prime, this auditable encoder matches black-box performance. Using it to audit evidence routing, we uncover a semantic-structural mismatch: the nodes that dominate the encoder's output are structurally disconnected in the retrieved subgraph, held together by low-attribution intermediaries whose removal degrades multi-hop QA by up to 28%. This mismatch, invisible to any opaque encoder, reveals that semantic importance and structural connectivity are governed by disjoint sets of nodes, with direct implications for retrieval pruning, context construction, and failure diagnosis in graph-augmented LLMs.

1 Introduction

Retrieval-Augmented Generation (RAG) improves the factuality of Large Language Models (LLMs) by conditioning generation on external knowledge retrieved at inference time (Lewis et al., 2020; Gao et al., 2024). GraphRAG extends this to structured knowledge: given a natural-language query, a query-specific subgraph is retrieved from a knowledge graph, encoded with a Graph Neural Network (GNN), and projected into the LLM's input

space as a soft prompt (He et al., 2024; Han et al., 2025). The GNN encoder acts as an information bottleneck, compressing hundreds of retrieved entities and relations into latent vectors. Standard GNN encoders like GCN (Kipf and Welling, 2017), GAT (Veličković et al., 2018), and GIN (Xu et al., 2019) have repeated neighborhood aggregation followed by nonlinear transformations across multiple layers, producing representations that entangle the contributions of each node with those of its multi-hop neighborhood. The result is that prompt vectors fed to the LLM have no closed-form per-node decomposition, making it impossible to faithfully audit which retrieved entities actually influenced the model's conditioning.

Auditing a GraphRAG pipeline requires knowing what the encoder did: which nodes it weighted, which it suppressed, and whether the graph-conditioned prompt reflects the relevant structural evidence. When the system produces an incorrect answer, the failure can originate at the retriever, the encoder, or the LLM, and disentangling these requires per-node attribution at the encoder level. In high-stakes settings such as biomedical QA and regulatory compliance, this kind of auditing is not optional (Rudin, 2019). Post-hoc explainability methods can be applied to the encoder: GNNExplainer (Ying et al., 2019) optimizes a mutual information objective, SubgraphX (Yuan et al., 2021) uses Shapley-value-based search, and attention weights from GAT layers are sometimes treated as importance scores. But these provide approximations whose faithfulness to the model's actual computation is not guaranteed (Yuan et al., 2023). Attention weights in particular correlate poorly with the features that causally influence predictions (Jain and Wallace, 2019; Wiegreffe and Pinter, 2019). For faithful auditing, approximate methods are insufficient.

To make the graph encoder auditable, we replace it with a Multivariate Graph Neural Additive Net-

---

[*]Equal contribution.

work (M-GNAN). Building on GNAN (Bechler-Speicher et al., 2024), which decomposes graph-level predictions additively across nodes and features by architectural design, M-GNAN extends the formalism to *feature groups*, accommodating the high-dimensional embedding vectors used in GraphRAG systems where individual dimensions carry no independent semantic meaning. We call the resulting framework EX-GRAPHRAG, whose importance scores are exact partial sums of the encoder's output rather than post-hoc approximations.

We audit evidence routing in GraphRAG to explicitly quantify the semantic-structural mismatch: we demonstrate precisely how

We audit evidence routing on a biomedical KGQA dataset using EX-GRAPHRAG, to explicitly quantify the *semantic-structural mismatch* in the retrieved subgraphs: we demonstrate precisely how the nodes that dominate the encoder's output are typically poorly connected to one another. Low-importance intermediary nodes (drug classes, pathway identifiers, shared protein families) serve as structural bridges between them, and pruning these bridges degrades multi-hop QA by up to 28%. This mismatch between semantic importance and structural connectivity is invisible to opaque encoders and would be obscured by post-hoc approximations. Our main contributions are:

- We audit evidence routing in GraphRAG and uncover a *semantic-structural mismatch*: the nodes that dominate the encoder's output are structurally disconnected, connected through low-attribution intermediaries whose removal degrades multi-hop reasoning by up to 28%.

- To enable this audit, we introduce *M-GNAN*, extending GNAN to feature-group embeddings, and integrate it into the G-Retriever framework as an intrinsically decomposable encoder (EX-GRAPHRAG).

- On STaRK-Prime, EX-GRAPHRAGmatches the QA performance of black-box encoders (GAT, GCN, GIN) while producing exact node-level attribution.

- We characterize additional capabilities that auditable encoders enable: retrieval debugging, importance-guided context construction, and multi-granularity attribution.

2 Related Work

2.1 Graph Retrieval-Augmented Generation

GraphRAG systems integrate structured knowledge from graphs into LLM generation pipelines. G-Retriever (He et al., 2024) retrieves query-specific subgraphs via Prize-Collecting Steiner Trees, encoding them with a GNN, and projecting the resulting representations into the LLM's input space. Subsequent work has explored alternative graph-text integration strategies (Perozzi et al., 2024), community-level graph summarization for broader query coverage (Edge et al., 2024), GNN-based dense retrieval for LLM reasoning (Mavromatis and Karypis, 2025), relation-path-grounded reasoning for interpretable KG-QA (Luo et al., 2024), and some works covering the broader integration of LLMs with knowledge graphs (Pan et al., 2024). Earlier work on GNN-augmented QA over knowledge graphs, notably QA-GNN (Yasunaga et al., 2021), demonstrated the value of jointly reasoning over language context and graph structure, but did not address the transparency of the graph encoder itself. Surveys of the GraphRAG landscape (Han et al., 2025) identify the GNN encoder as a central but underexamined component: while retrieval strategies and LLM architectures receive significant attention, the encoder is typically treated as an interchangeable module evaluated only by downstream task performance. Several of these systems offer partial transparency at other stages: G-Retriever returns the retrieved subgraph, giving visibility into *what* was retrieved but not how the encoder weighted it; GNN-RAG (Mavromatis and Karypis, 2025) assigns importance scores to nodes for retrieval ranking, but these scores guide subgraph selection, not encoder auditing; RoG (Luo et al., 2024) grounds reasoning in relation paths, sidestepping the encoder entirely. None make the encoder itself transparent. Our work addresses this gap: we replace the encoder with an intrinsically decomposable architecture so that per-node attribution is exact and available for auditing.

2.2 Explainability for Graph Neural Networks

Explainability methods for GNNs fall broadly into post-hoc and intrinsic categories (Yuan et al., 2023). Post-hoc methods explain a trained model after the fact: GNNExplainer (Ying et al., 2019) identifies important substructures by maximizing mutual information between explanation and predic-

tion; PGExplainer (Luo et al., 2020) amortizes this via a learned mask generator; SubgraphX (Yuan et al., 2021) searches for explanatory subgraphs using Monte Carlo tree search with Shapley values; gradient-based and perturbation-based approaches compute attribution scores through backpropagation or input masking. Attention-based attribution interprets the learned coefficients of GAT-style models as importance, though this interpretation is contested. Jain and Wallace (2019) showed that attention weights frequently fail to correlate with gradient-based importance, and Brody et al. (2022) demonstrated that standard GAT computes a limited form of static attention that cannot fully rank neighbor importance. Wiegreffe and Pinter (2019) argued that attention can carry explanatory signal under certain conditions, but the consensus remains that attention weights are unreliable as faithful attributions (Yuan et al., 2023).

Intrinsic methods instead constrain the architecture so that explanations follow directly from the computation. This tradition extends from Generalized Additive Models (Hastie and Tibshirani, 1990), which decompose predictions as sums of univariate functions, through gradient-boosted GAMs (Lou et al., 2012, 2013) and Neural Additive Models (Agarwal et al., 2021), to GNAN (Bechler-Speicher et al., 2024), which brings the additive principle to graph-structured data. Unlike post-hoc methods such as SHAP (Lundberg and Lee, 2017), which estimate per-feature contributions by sampling perturbations of a black-box model, intrinsic additive models produce importance scores that are the literal terms in the summation constituting the output, without any estimation or approximation involved. To our knowledge, no prior work has applied an intrinsically decomposable GNN as the encoder in a GraphRAG system.

3 Methodology

The standard GraphRAG pipeline uses a message-passing GNN (GCN, GAT, or GIN) to encode the retrieved subgraph into node representations, which are then aggregated and projected into the LLM's embedding space. These encoders interleave neighborhood aggregation with nonlinear transformations across L layers, producing representations where the contribution of any single input node is entangled with the contributions of its multi-hop neighborhood. The output has no closed-form per-node decomposition.

GNAN (Bechler-Speicher et al., 2024) takes a different architectural approach. Rather than entangling node contributions through message passing, GNAN computes each node's contribution to the output independently through learned *shape functions*, then combines contributions additively with distance-based weighting. The result is a graph-level prediction that decomposes exactly into a sum over nodes (and over features within each node), where each term can be computed and inspected independently. This additive structure is what makes the encoder auditable: given its output, we can read off how much each retrieved node contributed, without approximation.

The EX-GRAPHRAG pipeline proceeds as follows: (1) embedding the query, retrieving seed nodes by vector similarity and expanding seeds into a subgraph via PCST (Section 3.1), (2) encoding the subgraph with M-GNAN, producing node representations alongside per-node importance scores (Section 3.2), and (3) projecting the representations into the LLM's input space (Section 3.3). The importance scores are not computed separately, but they are partial sums of the encoder's output, extracted directly from the forward pass.

3.1 Graph Construction for Knowledge Graph Question Answering

Given a natural-language question, we construct a question-specific subgraph that serves as the encoder's input. Both pipelines below start from the same seed selection: we embed the question with a sentence transformer and retrieve the top-$k = 4$ seed nodes by cosine similarity from the knowledge graph's node embeddings. They differ in how they expand from these seeds.

Single-hop PCST-merge. From the seed nodes, we perform a 1-hop expansion to form a candidate pool. We then run the Prize-Collecting Steiner Tree algorithm, assigning prizes to the top-100 nodes by query similarity and using uniform edge costs. To ensure high recall of semantically relevant entities, we merge the PCST output with the induced subgraph of the top-200 most similar nodes from the candidate pool.

Multi-hop PCST-merge. To capture longer-range dependencies, we expand from seeds for $h = 3$ hops, pruning the frontier at each step by retaining only the top-$k_{\text{seed}} = 5$ neighbors per node (ranked by query similarity) to manage graph size.

After expansion, we apply the same PCST-plus-merge procedure. The multi-hop pipeline produces larger, more structurally complex subgraphs that can capture reasoning chains spanning several entity types, at the cost of including more noise and more intermediary nodes. As we show in Section 6, these intermediaries turn out to play a critical structural role.

3.2 Extension of GNAN to Node Embedding Vectors (M-GNAN)

GNAN is defined over per-feature shape functions: each scalar feature has its own univariate function, and importance is attributed per-feature. But GraphRAG nodes are typically represented by high-dimensional embedding vectors (e.g., 768 or 1536 dimensions from sentence transformers) whose individual coordinates lack independent semantic meaning. Attributing importance to, say, dimension 437 of a sentence embedding is uninterpretable. To bridge this gap, we extend GNAN to operate on *feature groups*: subsets of the feature vector that are treated as a unit for both computation and attribution. We call this extension *Multivariate GNAN* (M-GNAN).

We partition the feature space into G groups, where each group $g \in \{1, \ldots, G\}$ contains a subset of feature indices $\mathcal{F}_g \subseteq \{1, \ldots, d\}$. In the common GraphRAG setting of a single embedding vector per node, we set $G = 1$ and $\mathcal{F}_1 = \{1, \ldots, d\}$, so that the entire embedding is one group. For each feature group g, we define a *multivariate shape function*:

$$f_g(\mathbf{x}_g; \theta_g) : \mathbb{R}^{|\mathcal{F}_g|} \to \mathbb{R},$$
$$\mathbf{x}_g = [x_{k_1}, \ldots, x_{k_{|\mathcal{F}_g|}}], \quad k_i \in \mathcal{F}_g,$$

parameterized as a multi-layer perceptron. Note that while the shape function is a flexible nonlinear function of its input group, the overall model remains additive across groups and nodes. The expressiveness constraint is on how nodes *combine*, not on how individual node features are processed. The representation for node i in feature group g is:

$$[\mathbf{h}_i]_g = \sum_{j=1}^{N} \frac{1}{\#\text{dist}(j,i)} \cdot \rho\left(\frac{1}{1 + \text{dist}(j,i)}\right)$$
$$\cdot f_g\left([\mathbf{x}_j]_{\mathcal{F}_g}\right),$$

where $\text{dist}(j,i)$ is the shortest-path distance between nodes j and i in the subgraph, $\#\text{dist}(j,i)$ is the number of nodes at the same distance from

i as j (a normalization factor that prevents distant, well-connected neighborhoods from dominating), and ρ is a learnable monotone function that controls how influence decays with graph distance. For graph-level prediction, the output decomposes as:

$$\sigma\left(\sum_{g=1}^{G} \sum_{i=1}^{N} [\mathbf{h}_i]_g\right) = \sigma\left(\sum_{g=1}^{G} \sum_{j=1}^{N} f_g\left([\mathbf{x}_j]_{\mathcal{F}_g}\right)\right.$$
$$\left. \cdot \sum_{i=1}^{N} \frac{1}{\#\text{dist}(j,i)} \cdot \rho\left(\frac{1}{1 + \text{dist}(j,i)}\right)\right),$$

which provides an exact additive decomposition over both nodes and feature groups. The importance of node j in group g is the corresponding inner term. It is not estimated, but computed directly from the model's forward pass.

3.3 Projection and Generation

Following He et al. (2024), the LLM receives two versions of the retrieved subgraph. First, M-GNAN's node representations are mapped to the LLM's hidden dimension via a learned MLP, producing a graph token that is prepended to the input as a soft prompt. Second, the subgraph is linearized into text by flattening node and edge descriptions, and concatenated with the query as standard textual input. The LLM attends to both the graph-conditioned soft prompt and the textualized subgraph during generation. We fine-tune the LLM with LoRA (Hu et al., 2022) while jointly training the M-GNAN encoder and projection layer end-to-end.

4 What Auditable Graph Encoding Enables

An auditable encoder opens capabilities that opaque encoders cannot support. Because M-GNAN's output decomposes additively across nodes, per-node importance scores are available at inference time as a byproduct of encoding, without additional forward passes or post-hoc analysis. We demonstrate two of these capabilities in Sections 5 and 6; we briefly note additional directions the formalism supports at the end of this section.

4.1 Auditing and Debugging Retrieval Pipelines

When a GraphRAG system produces an incorrect answer, the failure can originate at any pipeline stage: the query embedding may miss relevant seed

nodes, the PCST expansion may select a poorly connected subgraph, the GNN encoder may misweight the evidence, or the LLM may ignore the graph-conditioned prompt entirely. With opaque encoders, disentangling retrieval failures from encoding failures is difficult. EX-GRAPHRAG's importance decomposition enables targeted analysis: if importance concentrates on query-relevant entities but the LLM still makes an error, the encoder is functioning correctly and the problem lies downstream. If importance concentrates on irrelevant nodes, the encoder's training or the subgraph's composition is at fault. Stage-wise debugging follows directly from exact per-node attribution.

4.2 Disentangling Semantic and Structural Importance

EX-GRAPHRAG's additive decomposition quantifies each node's direct semantic contribution to the encoder's output. But as we show in Section 6, semantic importance is not the only dimension along which nodes matter: structural importance, the role a node plays in connecting other nodes, is distinct and sometimes conflicting. We term this divergence the *semantic-structural mismatch*. Combining EX-GRAPHRAG's semantic scores with graph-theoretic structural measures (e.g., betweenness centrality) could produce composite importance maps that classify nodes along both dimensions. We examine the mismatch empirically in Section 6.

Further capabilities. The exact decomposition supports additional applications that we do not evaluate in this work. On the context construction side, node importance scores could guide the linearization order of subgraph descriptions passed to the LLM, placing high-importance nodes earlier to mitigate known positional biases in long-context attention (Liu et al., 2024); our PCST + Top-25 configuration (Section 5) is a simple instance of this idea. On the attribution side, M-GNAN's formalism generalizes to multiple feature groups ($G > 1$), allowing separate attribution of importance, e.g., to a node's textual embedding versus its molecular fingerprint. We leave both of these as potential directions for future work to explore.

5 Empirical Evaluation

The capabilities above rest on an assumption that M-GNAN can replace standard GNN encoders without substantial loss in downstream QA performance. We evaluate this on knowledge graph

Table 1: **Single-hop PCST-merge retrieval.** M-GNAN provides exact node-level attribution while maintaining competitive performance. Best results in **bold**.

GNN	Context	Hits@1	Hits@5	F1	MRR
Black-box baselines					
GAT	PCST	**0.297**	**0.335**	**0.243**	**0.313**
GCN	PCST	0.291	0.331	0.239	0.308
GIN	PCST	0.292	0.336	0.239	0.310
Auditable (Ours)					
M-GNAN	PCST	0.285	0.335	0.236	0.306
M-GNAN	PCST + Top-25	0.289	0.332	0.237	0.307
M-GNAN	Top-25 only	0.257	0.306	0.220	0.279

question answering, focusing on two questions: (1) does M-GNAN maintain competitive performance relative to black-box encoders? and (2) what happens when its importance scores are used to filter or emphasize the context passed to the LLM?

Dataset. STaRK-Prime (Wu et al., 2024), a knowledge graph QA benchmark built on a biomedical knowledge graph. We use the standard train/val/test splits.

Baselines. G-Retriever with GAT, GCN, and GIN encoders using PCST-based subgraph retrieval, following the same setup as He et al. (2024). Llama 3.1 8B (Grattafiori et al., 2024) is used as the LLM backbone for all configurations.

Context configurations. For each retrieval pipeline, we evaluate three configurations using M-GNAN:

- **PCST:** Full PCST subgraph linearized and passed to the LLM (standard).

- **Top-25 only:** Only the top-25 nodes by M-GNAN importance score, discarding the rest.

- **PCST + Top-25:** Full PCST subgraph with the top-25 important nodes emphasized via ordering and special markers in the text context.

Metrics. Hits@1, Hits@5, F1 score, and Mean Reciprocal Rank (MRR).

Results. In the single-hop setting (Table 1), M-GNAN with the full PCST context achieves 0.285 Hits@1, within 0.012 of the best baseline (GAT, 0.297), and matches the baselines on Hits@5 (0.335). The gap is small and consistent across metrics, M-GNAN pays a modest cost for exact decomposability.

The multi-hop setting (Table 2) is more mixed. M-GNAN (0.293 Hits@1) surpasses GAT (0.282)

Table 2: **Multi-hop PCST-merge retrieval.** In the more challenging multi-hop setting, GNAN remains competitive with GAT and GCN but trails GIN, reflecting the expressiveness–auditability tradeoff. Best results in **bold**.

GNN	Context	Hits@1	Hits@5	F1	MRR
Black-box baselines					
GAT	PCST	0.282	0.331	0.231	0.302
GCN	PCST	0.291	0.331	0.235	0.309
GIN	PCST	**0.341**	**0.387**	**0.291**	**0.361**
Auditable (Ours)					
M-GNAN	PCST	0.293	0.337	0.239	0.312
M-GNAN	PCST + Top-25	0.283	0.330	0.234	0.303
M-GNAN	Top-25 only	0.212	0.253	0.175	0.229

and matches GCN (0.291), but trails GIN (0.341). This gap is expected. GIN is maximally expressive among message-passing GNNs in the WL hierarchy (Xu et al., 2019), and that expressiveness matters more in larger multi-hop subgraphs with more complex structure. M-GNAN's additive constraint, the property that enables exact decomposition, limits its capacity to model certain interaction effects between nodes. This is the explicit tradeoff: M-GNAN gives up expressiveness in the hardest setting for guarantees about its importance scores.

Pruning less important nodes. Filtering context to only the top-25 nodes by importance (Top-25 only) degrades performance substantially, as shown in Table 3. Hits@1 drops from 0.285 to 0.257 (-9.8%) in single-hop and from 0.293 to 0.212 (-27.6%) in multi-hop. The multi-hop degradation is nearly three times worse. This asymmetry reflects the structure of multi-hop subgraphs: they are larger, contain more intermediary entities, and depend more on structural bridges between answer-relevant nodes. The emphasis configuration (PCST + Top-25) recovers performance in the single-hop setting (0.289) but only partially in multi-hop (0.283). The next section examines why through a closer look at importance distributions.

6 Auditing Evidence Routing

The pruning results raise a natural question: *if the top-scoring nodes account for most of the encoder's output, why does removing the rest hurt performance so badly?* We use M-GNAN's exact decomposition to examine this on a representative query.

Table 3: **Effect of context configuration on M-GNAN performance.** Aggressive pruning (Top-25 only) degrades performance substantially, with the effect nearly three times worse in multi-hop settings. The emphasis configuration (PCST + Top-25) partially recovers performance by retaining structural context while highlighting important nodes.

Retrieval	Context	Hits@1	∆Hits@1	F1	∆F1
Single-hop	PCST	0.285	—	0.236	—
	PCST + Top-25	0.289	+1.4%	0.237	+0.4%
	Top-25 only	0.257	−9.8%	0.220	−6.8%
Multi-hop	PCST	0.293	—	0.239	—
	PCST + Top-25	0.283	−3.4%	0.234	−2.1%
	Top-25 only	0.212	−27.6%	0.175	−26.8%

Figure 1: **Node importance scores for a representative query.** M-GNAN importance scores for the query *"Could you list the tablet or capsule medications that act on the MAPK1 gene/protein?"* Three nodes (MAPK1, MAPK14, MAP3K4) account for approximately 60% of total importance; the remaining 180 nodes each contribute less than 0.05. Yet removing these low-scoring nodes causes 28% performance degradation in multi-hop settings (Table 2).

6.1 Node Importance Distributions

Figure 1 shows M-GNAN's importance scores for a representative query from STaRK-Prime: *"Could you list the tablet or capsule medications that act on the MAPK1 gene/protein?"* Importance distribution is very skewed, with just three nodes: MAPK1 (0.252), MAPK14 (0.234), and MAP3K4 (0.114), which account for roughly 60% of total importance. After rank 10, scores drop below 0.05; the vast majority of the 200 nodes contribute less than 0.02 each.

The concentration aligns with domain knowledge: MAPK1 is the query target, MAPK14 is a closely related kinase, and MAP3K4 is an upstream activator in the same signaling cascade. In a subgraph spanning hundreds of nodes across multiple entity types (drugs, proteins, pathways, diseases), the encoder's output is driven by a small seman-

Figure 2: **Full subgraph vs. induced subgraph on high-importance nodes.** Left: the full retrieved subgraph for the MAPK1 query, colored by M-GNAN importance (dark red = high, yellow = low). High-importance nodes sit within a dense network of low-importance intermediaries. Right: the induced subgraph on the top-10 important nodes and their immediate neighbors. Removing bridge nodes fragments the graph into disconnected components.

tic core. However, semantic irrelevance does not imply structural irrelevance. Removing these low-scoring nodes degrades QA performance by up to 28% (Section 5), with more details in Figure 2.

6.2 Structural Fragmentation Under Pruning

Figure 2 visualizes the same query's subgraph in two views. The left panel shows the full retrieved subgraph colored by importance: high-importance nodes (dark red) sit within a larger network of low-importance intermediaries (yellow). The right panel restricts to the top-10 important nodes and their immediate neighbors. The graph fragments into disconnected components. Nodes that were close together in the full subgraph become distant once intermediaries are removed.

We term these *bridge nodes*: entities with negligible M-GNAN importance that maintain connectivity between high-importance nodes. In the MAPK1 example, bridges include intermediate drug classes connecting medications to target proteins, pathway identifiers linking kinases within the MAPK cascade, and shared protein families providing categorical links between otherwise unrelated entities. None are answers to the query, and M-GNAN correctly assigns them low importance. But removing them fragments the graph, destroying the relational context the LLM needs for reasoning.

The 28% Hits@1 degradation in multi-hop pruning (Table 2) follows from this: multi-hop subgraphs span more entity types and longer reasoning chains, requiring more bridges. Without them, the LLM receives disconnected entity descriptions rather than a connected subgraph.

6.3 The Semantic-Structural Mismatch

Semantic relevance and structural connectivity divergence in knowledge graphs is not a new observation (Yuan et al., 2023; Edge et al., 2024); what has been lacking is the ability to quantify this divergence faithfully within a specific encoder, on a per-query basis. M-GNAN provides exactly this: turning a qualitative intuition into a per-node, per-query diagnostic without post-hoc approximation. M-GNAN's scores measure each node's direct additive contribution to the encoder's output, i.e., its semantic importance. But downstream reasoning also depends on structural connectivity, a global property that no per-node score can capture. A node can be indispensable for reasoning (its removal disconnects the graph) while contributing almost nothing to the output in isolation.

Any node-level attribution method faces this mismatch (Yuan et al., 2023). Exact decomposition does not resolve it, but it does surface it. With a post-hoc method, bridge nodes might receive moderate importance scores, obscuring whether they genuinely contribute to the computation or just serve as neighbors to nodes that do. M-GNAN's exact scores make the bimodal structure of the importance landscape clear: a small core of high-attribution semantic nodes, surrounded by low-attribution structural bridges.

Combining semantic importance from M-GNAN with graph-theoretic structural measures (e.g., betweenness centrality) could yield composite scores that account for both dimensions, enabling principled pruning that retains both the semantic core and the structural bridges. This connects to the multi-granularity capability described in Section 4.

7 Discussion

The expressiveness-auditability tradeoff. Our results make the tradeoff between expressiveness and interpretability concrete. In the single-hop setting, M-GNAN's performance cost relative to black-box encoders is small (0.285 vs. 0.297 Hits@1 for GAT). In multi-hop, the gap widens against GIN (0.293 vs. 0.341), though M-GNAN still matches or exceeds GAT and GCN. The GIN gap reflects the architectural cost of additive decomposability (see Section 5). When faithful attribution

is a requirement (Rudin, 2019), this cost is justified; when maximum accuracy is the sole priority, GIN with post-hoc attribution remains a reasonable alternative. The semantic-structural mismatch (Section 6) is one example of the insights this transparency makes accessible; while the theoretical divergence between structural and semantic node roles is a known concept in graph learning, EX-GRAPHRAG provides the mechanism to reliably audit and isolate this behavior in production retrieval pipelines. Retrieval debugging, importance-guided context construction, and multi-granularity attribution are other areas that remain to be explored empirically.

Limitations. We evaluate on a single dataset (STaRK-Prime), and our quantitative findings may not generalize to other knowledge graphs, question types, or LLM backbones. The audit covers one query in detail; broader analysis of the mismatch across queries and graph domains would strengthen the finding. We do not compare M-GNAN's importance scores against post-hoc attributions applied to the same pipeline, report error bars across training runs, or conduct user studies on whether importance scores improve human verification of LLM answers.

Future work. The most immediate extensions are multi-dataset evaluation (STaRK-MAG and other KGQA benchmarks), empirical comparisons with post-hoc explainability methods using the same G-Retriever pipeline, and composite importance scores that combine M-GNAN's semantic attribution with graph-theoretic structural measures. User studies measuring whether practitioners can diagnose retrieval failures faster with EX-GRAPHRAG than with opaque baselines would validate the practical utility of the approach.

8 Conclusion

We audited evidence routing in GraphRAG and uncovered a semantic-structural mismatch: the nodes most important to the encoder's output are structurally disconnected, held together by low-attribution intermediaries whose removal degrades multi-hop reasoning by up to 28%. This finding was made possible by EX-GRAPHRAG, which replaces the GNN encoder with M-GNAN, an intrinsically decomposable architecture that yields exact per-node attribution at competitive performance. The mismatch is invisible to opaque encoders and

would be obscured by post-hoc approximations that blur the boundary between semantic and structural roles. As GraphRAG systems are deployed in high-stakes settings, the ability to audit the encoder through tools like EX-GRAPHRAG, not just the retriever or the LLM, will be increasingly important.

References

Rishabh Agarwal, Levi Melnick, Nicholas Frosst, Xuezhou Zhang, Ben Lengerich, Rich Caruana, and Geoffrey E. Hinton. 2021. Neural additive models: Interpretable machine learning with neural nets. In *Advances in Neural Information Processing Systems*, volume 34, pages 4699–4711.

Maya Bechler-Speicher, Amir Globerson, and Ran Gilad-Bachrach. 2024. The intelligible and effective graph neural additive network. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Shaked Brody, Uri Alon, and Eran Yahav. 2022. How attentive are graph attention networks? In *International Conference on Learning Representations*.

Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, and Jonathan Larson. 2024. From local to global: A graph RAG approach to query-focused summarization. *Preprint*, arXiv:2404.16130.

Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Qianyu Guo, Meng Wang, and Haofen Wang. 2024. Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:2312.10997*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, and 1 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Haoyu Han, Yu Wang, Harry Shomer, Kai Guo, Jiayuan Ding, Yongjia Lei, Mahantesh Halappanavar, Ryan A. Rossi, Subhabrata Mukherjee, Xianfeng Tang, Qi He, Zhigang Hua, Bo Long, Tong Zhao, Neil Shah, Amin Javari, Yinglong Xia, and Jiliang Tang. 2025. Retrieval-augmented generation with graphs (graphrag). *Preprint*, arXiv:2501.00309.

Trevor J. Hastie and Robert J. Tibshirani. 1990. *Generalized Additive Models*. Chapman and Hall/CRC.

Xiaoxin He, Yijun Tian, Yifei Sun, Nitesh V. Chawla, Thomas Laurent, Yann LeCun, Xavier Bresson, and Bryan Hooi. 2024. G-retriever: retrieval-augmented generation for textual graph understanding and question answering. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NIPS '24, Red Hook, NY, USA. Curran Associates Inc.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Sarthak Jain and Byron C. Wallace. 2019. Attention is not explanation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3543–3556. Association for Computational Linguistics.

Thomas N. Kipf and Max Welling. 2017. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.

Yin Lou, Rich Caruana, and Johannes Gehrke. 2012. Intelligible models for classification and regression. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 150–158. ACM.

Yin Lou, Rich Caruana, Johannes Gehrke, and Giles Hooker. 2013. Accurate intelligible models with pairwise interactions. In *Proceedings of the 19th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 623–631. ACM.

Scott M. Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, pages 4766–4777.

Dongsheng Luo, Wei Cheng, Dongkuan Xu, Wenchao Yu, Bo Zong, Haifeng Chen, and Xiang Zhang. 2020. Parameterized explainer for graph neural network. In *Advances in Neural Information Processing Systems*, volume 33, pages 19620–19631.

Linhao Luo, Yuan-Fang Li, Gholamreza Haffari, and Shirui Pan. 2024. Reasoning on graphs: Faithful and interpretable large language model reasoning. In *International Conference on Learning Representations*.

Costas Mavromatis and George Karypis. 2025. GNN-RAG: Graph neural retrieval for large language model reasoning. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 16682–16699. Association for Computational Linguistics.

Shirui Pan, Linhao Luo, Yufei Wang, Chen Chen, Jiapu Wang, and Xindong Wu. 2024. Unifying large language models and knowledge graphs: A roadmap. *IEEE Transactions on Knowledge and Data Engineering*, 36(7):3580–3599.

Bryan Perozzi, Bahare Fatemi, Dustin Zelle, Anton Tsitsulin, Mehran Kazemi, Rami Al-Rfou, and Jonathan Halcrow. 2024. Let your graph do the talking: Encoding structured data for llms. *Preprint*, arXiv:2402.05862.

Cynthia Rudin. 2019. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1:206–215.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. 2018. Graph attention networks. In *International Conference on Learning Representations*.

Sarah Wiegreffe and Yuval Pinter. 2019. Attention is not not explanation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 11–20. Association for Computational Linguistics.

Shirley Wu, Shiyu Zhao, Michihiro Yasunaga, Kexin Huang, Kaidi Cao, Qian Huang, Vassilis N. Ioannidis, Karthik Subbian, James Zou, and Jure Leskovec. 2024. STaRK: Benchmarking LLM retrieval on textual and relational knowledge bases. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. 2019. How powerful are graph neural networks? In *International Conference on Learning Representations*.

Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. 2021. QA-GNN: Reasoning with language models and knowledge graphs for question answering. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics*, pages 535–546. Association for Computational Linguistics.

Rex Ying, Dylan Bourgeois, Jiaxuan You, Marinka Zitnik, and Jure Leskovec. 2019. *GNNExplainer: generating explanations for graph neural networks*. Curran Associates Inc., Red Hook, NY, USA.

Hao Yuan, Haiyang Yu, Shurui Gui, and Shuiwang Ji. 2023. Explainability in graph neural networks: A taxonomic survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(5):5782–5799.

Hao Yuan, Haiyang Yu, Jie Wang, Kang Li, and Shuiwang Ji. 2021. On explainability of graph neural networks via subgraph explorations. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 12241–12252. PMLR.