FOURIER REPRESENTATIONS FOR BLACK-BOX OPTIMIZATION OVER CATEGORICAL VARIABLES

ABSTRACT

Optimization of real-world black-box functions defined over purely categorical variables is an active area of research. In particular, optimization and design of biological sequences with specific functional or structural properties have a profound impact in medicine, materials science, and biotechnology. Standalone acquisition methods, such as simulated annealing (SA) and Monte Carlo tree search (MCTS), are typically used for such optimization problems. In order to improve the performance and sample efficiency of such acquisition methods, we propose to use existing acquisition methods in conjunction with a surrogate model for the black-box evaluations over purely categorical variables. To this end, we present two different representations, a group-theoretic Fourier expansion and an abridged one-hot encoded Boolean Fourier expansion. To learn such models, characters of each representation are considered as experts and their respective coefficients are updated via an exponential weight update rule each time the black box is evaluated. Numerical experiments over synthetic benchmarks as well as real-world RNA sequence optimization and design problems demonstrate the representational power of the proposed methods, which achieve competitive or superior performance compared to state-of-the-art counterparts, while improving the computational cost and/or sample efficiency substantially.

1 INTRODUCTION

A plethora of practical optimization problems involve black-box functions, with no simple analytical closed forms, that can be evaluated at any arbitrary point in the domain. Optimization of such black-box functions poses a unique challenge due to restrictions on the number of possible function evaluations, as evaluating functions of real-world complex processes is often expensive and time consuming. Efficient algorithms for global optimization of expensive black-box functions take past queries into account in order to select the next query to the black-box function more intelligently. While black-box optimization of real-world functions defined over integer, continuous, and mixed variables has been studied extensively in the literature, limited work has addressed incorporation of purely categorical type input variables.

Categorical type variables are particularly challenging when compared to integer or continuous variables, as they do not have a natural ordering. However, many real-world functions are defined over categorical variables. One such problem, which is of wide interest, is the design of optimal chemical or biological (protein, RNA, and DNA) molecule sequences, which are constructed using a vocabulary of fixed size, e.g. 4 for DNA/RNA. Designing optimal molecular sequences with improved or novel structures and/or functionalities is of paramount importance in material science, drug and vaccine design, synthetic biology and many other applications (see Dixon et al. (2010); Ng et al. (2019); Hoshika et al. (2019); Yamagami et al. (2019)). Design of optimal sequences is a difficult black-box optimization problem over a combinatorially large search space (Stephens et al. (2015)), in which function evaluations often rely on either wet-lab experiments, physics-inspired simulators, or knowledge-based computational algorithms, which are slow and expensive in practice. Another problem of interest is the constrained design problem, e.g. find a sequence given a specific structure (or property), which is inverse of the well-known folding problem discussed in Dill & MacCallum (2012). This problem is complex due to the strict structural constraints imposed on the sequence. In fact one of the ways to represent such a complex structural constraint is to constrain the next choice

sequentially based on the sequence elements that have been chosen a priori. Therefore, we divide the black box optimization problem into two settings, depending on the constraint set: (i) Generic Black Box Optimization (BBO) problem referring to the unconstrained case and (ii) Design Problem that refers to the case with complex sequential constraints.

Let x_t be the t-th sequence evaluated by the black box function f. The key question in both settings is the following: Given prior queries $x_1, x_2 \ldots x_t$ and their evaluations $f(x_1) \ldots f(x_t)$, *how to choose the next query x_{t+1}?* This acquisition must be devised so that over a finite budget of black-box evaluations, one is closest to the minimizer in an expected sense over the acquisition randomness.

In the literature, for design problems with sequential constraints, MCTS (Monte Carlo Tree Search) based acquisitions are often used with real function evaluations $f(x_t)$. In the generic BBO problems in the unconstrained scenario, Simulated Annealing (SA) based techniques are typically used as acquisition functions. A key *missing* ingredient in the categorical domain is a surrogate model for the black-box evaluations that can interpolate between such evaluations and use *cost-free* approximate evaluations from the surrogate model internally (in acquisition functions) in order to reduce the need for frequently accessing real evaluations. This leads to improved sample efficiency in acquisition functions. Due to the lack of efficient interpolators in the categorical domains, existing acquisition functions suffer under a finite budget constraint, due to reliance on only real black-box evaluations.

Contributions: We address the above problem in our work. Our main contributions are as follows:

1. We present two representations for modeling real-valued combinatorial functions over categorical variables, which we then use in order to learn a surrogate model for the generic BBO problem and the design problem. The surrogate model is updated via a hedge algorithm where the basis functions in our representations act as experts. The latter update happens once for every real black-box evaluation. To the best of our knowledge, the representations and/or their use in black-box optimization of functions over categorical variables are novel to this work.

2. In the BBO problem, the proposed method uses a version of simulated annealing that utilizes the current surrogate model for many internal cost-free evaluations before producing the next black-box query.

3. In the design problem, the proposed method uses a version of MCTS in conjunction with the current surrogate model as reward function of the terminal states during intermediate tree traversals/backups in order to improve the sample efficiency of the search algorithm.

4. Numerical results, over synthetic benchmarks as well as real-world biological (RNA) sequence optimization and design problems demonstrate the competitive or superior performance of the proposed methods over state-of-the-art counterparts, while substantially reducing the computation time and sample efficiency, respectively.

2 RELATED WORK

Bayesian Optimization (BO) is a commonly used approach for optimization of black-box functions (Shahriari et al. (2015)). However, limited work has addressed incorporation of categorical variables in BO. Early attempts based on converting the black-box optimization problem over categorical variables to that of continuous variables have not been very successful (Gómez-Bombarelli et al. (2018); Golovin et al. (2017); Garrido-Merchán & Hernández-Lobato (2020)). A few BO algorithms have been specifically designed for black-box functions over combinatorial domains. In particular, the BOCS algorithm Ricardo Baptista (2018), primarily devised for Boolean functions, employs a sparse monomial representation to model the interactions among different variables, and uses a sparse Bayesian linear regression method to learn the model coefficients. The COMBO algorithm of Oh et al. (2019) uses Graph Fourier Transform (GFT) over a combinatorial graph, constructed via graph cartesian product of variable subgraphs, to gauge the smoothness of the black-box function. However, both BOCS and COMBO are hindered by associated high computational complexities, which grow polynomially with both the number of variables and the number of function evaluations.

More recently, a computationally efficient black-box optimization algorithm (COMEX) (Dadkhahi et al. (2020)) was introduced to address the computational impediments of its Bayesian counterparts. COMEX adopts a Boolean Fourier representation as its surrogate model, which is updated via an exponential weight update rule. Nevertheless, COMEX is limited to functions over the Boolean hypercube. We generalize COMEX to handle functions over categorical variables by proposing two representations for modeling functions over categorical variables: an abridged one-hot encoded

Boolean Fourier representation and Fourier representation on finite Abelian groups. The utilization of the latter representation as a surrogate model in combinatorial optimization algorithms is novel to this work. Factorizations based on one-hot encoding has been previously (albeit briefly) suggested in Ricardo Baptista (2018) to enable black-box optimization algorithms designed for Boolean variables to address problems over categorical variables. Different from Ricardo Baptista (2018), we show that we can significantly reduce the number of additional variables introduced upon one-hot encoding, and that such a reduced representation is in fact complete and unique.

For design problems, we focus on the RNA sequence design problem (RNA inverse folding). The goal is to find an RNA sequence consistent with a given secondary structure, as the functional state of the RNA molecule is determined by the latter structure (Hofacker et al. (1994)). Earlier RNA design methods explore the search space by trial and error and use classic cost function minimization approaches such as adaptive random walk (Hofacker (2003)), probabilistic sampling (Zadeh et al. (2011)), and genetic algorithms (Taneda (2015)). Recent efforts employ more advanced machine learning methods such as different Monte Carlo Tree Search (MCTS) algorithms, e.g. MCTS-RNA (Yang et al. (2017)) or Nested MCTS (Portela (2018)), and reinforcement learning that either performs a local search as in Eastman et al. (2018) or learns complete candidate solutions from scratch (Runge et al. (2018)). In all these approaches, the assumption is that the algorithm has access to a large number of function evaluations, whereas we are interested in sample efficiency of each algorithm.

3 BLACK-BOX OPTIMIZATION OVER CATEGORICAL VARIABLES

Problem Setting: Given the combinatorial categorical domain $\mathcal{X} = [k]^n$ and a constraint set $\mathcal{C} \subseteq \mathcal{X}$, with n variables each of cardinality k, the objective is to find

$$x^* = \arg\min_{x \in \mathcal{C}} f(x) \tag{1}$$

where $f : \mathcal{X} \mapsto \mathbb{R}$ is a real-valued combinatorial function. We assume that f is a black-box function, which is computationally expensive to evaluate. As such, we are interested in finding x^* in as few evaluations as possible. We consider two variations of the problem depending on how the constraint set $\mathcal{C}$ is specified.

Generic BBO Problem: In this case, the constraint set $\mathcal{C} = \mathcal{X}$. For example, RNA sequence optimization problem that searches for an RNA sequence with a specific property optimized lies within this category. A score for every RNA sequence, reflecting the property we wish to optimize, is evaluated by a black box function.

Design Problem: The constraint set is complex and is only sequentially specified. For every sequence of $x_1 x_2 \ldots x_i$ consisting of i characters from the alphabet $[k]$, the choice of the next character $x_{i+1} \in \mathcal{C}(x_1 x_2 \ldots x_i) \subseteq [k]$ is specified by a constraint set function $\mathcal{C}(x_1 \ldots x_i)$. The RNA inverse folding problem in Runge et al. (2018) falls into this category, where the constraints on the RNA sequence are determined by the sequential choices one makes during the sequence design. The goal is to find the sequence that is optimal with respect to a pre-specified structure that also obeys complex sequential constraints.

Our Techniques: In order to address this problem, we adopt a surrogate model-acquisition function based learning framework, where an estimate for the black-box function $\hat{f}$ (i.e. the surrogate model) is updated sequentially via black-box function evaluations observed until time step t. The selection of candidate points for black-box function evaluation is carried out via an acquisition function, which uses the surrogate model $\hat{f}$ as an inexpensive proxy (to make many internal calls) for the black-box function and produces the next candidate point to be evaluated. The sequence proceeds as follows:

Surrogate model updated on $(x_t, f(x_t)) \rightarrow$ Acquisition function makes (many) calls to Surrogate model to propose $x_{t+1} \rightarrow$ Surrogate model updated on $(x_{t+1}, f(x_{t+1}))$

In the sequel, we propose two representations that can be used as surrogate models for black-box combinatorial functions over categorical variables. These representations serve as direct generalizations of the Boolean surrogate model based on Fourier expansion proposed in Dadkhahi et al. (2020) in the sense that they reduce to the Fourier representation for real-valued Boolean functions when the cardinality of the categorical variables is two. In addition, both approaches can be modified to

address the more general case where different variables are of different cardinalities. However, for ease of exposition, we assume that all the variables are of the same cardinality. Finally, we introduce two popular acquisition function to be used in conjunction with the proposed surrogate models in order to propose new queries for subsequent black-box function evaluations.

3.1 REPRESENTATIONS FOR THE SURROGATE MODEL

We present two representations for combinatorial functions $f : [k]^n \to \mathbb{R}$ and an algorithm to update from the black-box evaluations. The representations use the Fourier basis in two different ways.

Abridged One-Hot Encoded Boolean Fourier Representation: The one-hot encoding of each variable $x_i : i \in [n]$ can be expressed as a $(k-1)$-tuple $(x_{i1}, x_{i2}, \ldots, x_{i(k-1)})$, where $x_{ij} \in \{-1, 1\}$ are Boolean variables with the constraint that at most one such variable can be equal to -1 for any given $x_i \in [k]$.

We consider the following representation for the combinatorial function f:

$$f_\alpha(x) = \sum_{m=0}^{n} \sum_{\mathcal{I} \in \binom{[n]}{m}} \sum_{\mathcal{J} \in [k-1]^{|\mathcal{I}|}} \alpha_{\mathcal{I},\mathcal{J}} \psi_{\mathcal{I},\mathcal{J}}(x) \tag{2}$$

where $[k-1]^{|\mathcal{I}|}$ denotes $|\mathcal{I}|$-fold cartesian product of the set $[k-1] = \{1, 2, \ldots, k-1\}$, $\binom{[n]}{m}$ designates the set of m-subsets of the set $[n]$, and the monomials $\psi_{\mathcal{I},\mathcal{J}}(x)$ can be written as

$$\psi_{\mathcal{I},\mathcal{J}}(x) = \prod_{\{(i,j):i=\mathcal{I}_\ell, j=\mathcal{J}_\ell, \ell \in [|\mathcal{I}|]\}} x_{ij} \tag{3}$$

A second order approximation (i.e. at $m = 2$) of the representation in (2) can be expanded in the following way:

$$\widehat{f}_\alpha(x) = \alpha_0 + \sum_{i \in [n]} \sum_{\ell \in [k-1]} \alpha_{i\ell} x_{i\ell} + \sum_{(i,j) \in \binom{[n]}{2}} \sum_{(p,q) \in [k-1]^2} \alpha_{ijpq} x_{ip} x_{jq}. \tag{4}$$

Example. *For $n = 2$ variables x_1 and x_2, each of which with cardinality $k = 3$, we have the one-hot encoding of (x_{11}, x_{12}) and (x_{21}, x_{22}) respectively. From Equation (4), the one-hot encoding factorization for this example can be written as*

$$f(x) = \alpha_0 + \alpha_1 x_{11} + \alpha_2 x_{12} + \alpha_3 x_{21} + \alpha_4 x_{22} + \alpha_5 x_{11} x_{21} + \alpha_6 x_{11} x_{22} + \alpha_7 x_{12} x_{21} + \alpha_8 x_{12} x_{22}.$$

Note that the representation in Equation (2) has far less terms than a vanilla one-hot encoding with all the combinations of one-hot variables included (as suggested in Ricardo Baptista (2018)). The reason for this reduction is two-fold: (i) $(k-1)$ Boolean variables model each categorical variable of cardinality k, and more importantly (ii) each monomial term has at most one Boolean variable x_{ij} from its corresponding parent categorical variable x_i. The following theorem states that this reduced representation is in fact unique and complete.

Theorem 3.1. *The representation in Equation (2) is complete and unique for any real-valued combinatorial function.*

Fourier Representation on Finite Abelian Groups: We define a cyclic group structure $\mathbb{Z}/k_i\mathbb{Z}$ over the elements of each categorical variable x_i ($i \in [n]$), where k_i is the cardinality of the latter variable. From the fundamental theorem of abelian groups Terras (1999), there exists an abelian group G which is isomorphic to the direct sum (a.k.a direct product) of the cyclic groups $\mathbb{Z}/k_i\mathbb{Z}$ corresponding to the n categorical variables:

$$G \cong \mathbb{Z}/k_1\mathbb{Z} \oplus \mathbb{Z}/k_2\mathbb{Z} \oplus \ldots \oplus \mathbb{Z}/k_n\mathbb{Z} \tag{5}$$

where the latter group consists of all vectors $(a_1, a_2, \ldots, a_n)$ such that $a_i \in \mathbb{Z}/k_i\mathbb{Z}$ and $\cong$ denotes group isomorphism. We assume that $k_i = k$ ($\forall i \in [n]$) for simplicity, but the following representation could be easily generalized to the case of arbitrary cardinalities for different variables.

The Fourier representation of any complex-valued function $f(x)$ on the finite abelian group G is given by Terras (1999)

$$f(x) = \sum_{\mathcal{I} \in [k]^n} \alpha_{\mathcal{I}} \psi_{\mathcal{I}}(x) \tag{6}$$

where $\alpha_{\mathcal{I}}$ are (in general complex) Fourier coefficients, $[k]^n$ is the n-fold cartesian product of the set $[k]$ and $\psi_{\mathcal{I}}(x)$ are complex exponentials [1] (k-th roots of unity) given by

$$\psi_{\mathcal{I}}(x) = \exp(2\pi j \langle x, \mathcal{I} \rangle / k).$$

Note that the latter complex exponentials are the *characters* of the representation, and reduce to the *monomials* (i.e. in $\{-1, 1\}$) when the cardinality of each variable is two. A second order approximation of the representation in (6) can be written as:

$$\widehat{f}_\alpha(x) = \alpha_0 + \sum_{i \in [n]} \sum_{\ell \in [k-1]} \alpha_{i\ell} \exp(2\pi j x_i \ell / k) + \sum_{(i,j) \in \binom{[n]}{2}} \sum_{(p,q) \in [k-1]^2} \alpha_{ijpq} \exp(2\pi j (x_i p + x_j q)/k). \quad (7)$$

For a real-valued function $f_\alpha(x)$ (which is of interest here), the representation in (6) reduces to

$$f_\alpha(x) = \Re\left\{ \sum_{\mathcal{I} \in [k]^n} \alpha_{\mathcal{I}} \psi_{\mathcal{I}}(x) \right\} = \sum_{\mathcal{I} \in [k]^n} \alpha_{r,\mathcal{I}} \psi_{r,\mathcal{I}}(x) - \sum_{\mathcal{I} \in [k]^n} \alpha_{i,\mathcal{I}} \psi_{i,\mathcal{I}}(x) \quad (8)$$

where

$$\psi_{r,\mathcal{I}}(x) = \cos(2\pi \langle x, \mathcal{I} \rangle / k) \quad \text{and} \quad \psi_{i,\mathcal{I}}(x) = \sin(2\pi \langle x, \mathcal{I} \rangle / k) \quad (9)$$

We note that the number of characters utilized in this representation is almost twice as many as that of monomials used in the previous representation.

Surrogate Model Learning: We adopt the learning algorithm of combinatorial optimization with expert advice Dadkhahi et al. (2020) in the following way. We consider the monomials $\psi_{\mathcal{I},\mathcal{J}}(x)$ in (3) and the characters $\psi_{\ell,\mathcal{I}}(x)$ in (9) as experts. For each surrogate model, we maintain a pool of such experts, the coefficients of which are refreshed sequentially via an exponential weight update rule. We refer to the proposed algorithm as *Expert-Based Categorical Optimization* (ECO) and the two versions of the algorithm with the two proposed surrogate models are called ECO-F (based on the One-Hot Encoded Boolean Fourier Representation) and ECO-G (based on Fourier Representation on Finite Abelian Groups), respectively. A summary of the algorithm is given in the Appendix.

3.2 Acquisition Functions

In this subsection, we discuss how two popular acquisition functions, namely Simulated Annealing (SA) and Monte Carlo Tree Search (MCTS), work with a surrogate model and use cost-free evaluations of the surrogate model to select the next query for the black box evaluation. In the literature, SA has been used for the generic BBO problems whereas MCTS has been used for the design problems.

SA as Acquisition Function: Our acquisition function is devised so as to minimize $\widehat{f}_\alpha(x)$, the current estimate for the surrogate model. A simple strategy to minimize $\widehat{f}_\alpha(x)$ is to iteratively switch each variable into the value that minimizes $\widehat{f}_\alpha$ given the values of all the remaining variables, until no more changes occur after a sweep through all the variables x_i ($\forall i \in [n]$). A strategy to escape local minima in this context Pincus (1970) is to allow for occasional increases in $\widehat{f}_\alpha$ by generating a Markov Chain (MC) sample sequence (for x), whose stationary distribution is proportional to $\exp(-\widehat{f}_\alpha(x)/s)$, where s is gradually reduced to zero. This optimization strategy was first applied by Kirkpatrick et al. (1983) in their Simulated Annealing algorithm to solve combinatorial optimization problems. We use the Gibbs sampler Geman & Geman (1984) to generate such a MC by sampling from the full-conditional distribution of the stationary distribution, which in our case is given by the softmax distribution over $\{-\widehat{f}_\alpha(x_i = \ell, x_{-i})/s\}_{\ell \in [k]}$, for each variable x_i conditional on the values of the remaining variables x_{-i}. By decreasing s from a high value to a low one, we allow the MC to first search at a coarse level avoiding being trapped in local minima.

Algorithm 1 presents our simulated annealing (SA) version for categorical domains, where $s(t)$ is an annealing schedule, which is a non-increasing function of t. We use the annealing schedule suggested in Spears (1993), which follows an exponential decay with parameter ℓ given by $s(t) = \exp(-\ell t / n)$. In each step of the algorithm, we pick a variable x_i ($i \in [n]$) uniformly at random, evaluate the

---

[1]Note that in the general case of different cardinalities for different variables, $\mathcal{I} \in [k_1] \times [k_2] \times \ldots \times [k_n]$ where $\times$ denotes the cartesian product and the exponent denominator in the complex exponential character is replaced by $k = \mathsf{LCM}(k_1, k_2, \ldots, k_n)$.

surrogate model (possibly in parallel) k times, once for each categorical value $\ell \in [k]$ for the chosen variable x_i given the current values x_{-i} for the remaining variables. We then update x_i with the sampled value in $[k]$ from the corresponding softmax distribution.

MCTS as Acquisition Function: We formulate the design problem as an undiscounted Markov decision process $(\mathcal{S}, \mathcal{A}, T, R)$. Each state $s \in \mathcal{S}$ corresponds to a partial or full sequence of categorical variables of lengths in $[0, n]$. The process in each episode starts with an empty sequence s_0, the initial state. Actions are selected from the set of permissible additions to the current state (sequence) s_t at each time step t, $\mathcal{A}_t = \mathcal{A}(s_t) \subset \mathcal{A}$. The transition function T is deterministic, and defines the sequence obtained from the juxtaposition of the current state s_t with the action a_t, i.e. $s_{t+1} = T(s_t, a_t) = s_t \circ a_t$. The transitions leading to incomplete sequences yield a reward of zero. Complete sequences are considered as terminal states, from which no further transitions (juxtapositions) can be made. Once the sequence is complete (i.e. at a terminal state), the reward is obtained from the current surrogate reward model $\widehat{f}_\alpha$. Thus, the reward function is defined as $R(s_t, a_t, s_{t+1}) = -\widehat{f}_\alpha(s_{t+1})$ if s_{t+1} is terminal, and zero otherwise.

MCTS is a popular search algorithm used for design problems. MCTS is a rollout algorithm which keeps track of the value estimates obtained via Monte Carlo simulations in order to progressively make better selections. The UCT selection criteria, see Kocsis & Szepesvári (2006), is typically used as tree policy, where action a_t at state s_t in the tree search is selected via: $\pi^{\mathcal{T}}(s_t) = \arg\max_{a \in \mathcal{A}(s_t)} Q(s_t, a) + c\sqrt{\ln N(s_t)/N(s_t, a)}$, where $\mathcal{T}$ is the search tree, c is the exploration parameter, $Q(s, a)$ is the state-action value estimate, and $N(s)$ and $N(s, a)$ are the visit counts for the parent state node and the candidate state-action edge, respectively. For the selection of actions in states outside the tree search, a random default policy is used: $\pi^{RS}(s_t) = \text{unif}(\mathcal{A}_t)$.

A summary of the proposed algorithm is given in Algorithm 2. Starting with an empty sequence s_0 at the root of the tree, we follow the tree policy until a leaf node of the search tree is reached (selection step). At this point, we append the state corresponding to the leaf node to the tree and initialize a value function estimate for its children (extension step). From the reached leaf node we follow the default policy until a terminal state is reached. At this point, we plug the sequence corresponding to this terminal state into the surrogate reward model $-\widehat{f}_\alpha$ and observe the reward r. This reward is backed up from the leaf node to the root of the tree in order to update the value estimates $Q(s, a)$ via Monte Carlo (i.e. using the average reward) for all visited (s, a) pairs along the path. This process is repeated until a stopping criterion (typically a max number of playouts) is met, at which point the sequence s_{best} with maximum reward r_{best} is returned as the output of the algorithm.

Algorithm 1 SA for Categorical Variables with Surrogate Model

1: **Inputs:** surrogate model $\widehat{f}_\alpha$, annealing schedule $s(t)$, categorical domain $\mathcal{X}$
2: Initialize $x \in \mathcal{X}$
3: $t = 0$
4: **repeat**
5:     $i \sim \text{unif}([n])$
6:     $x_i | x_{-i} \sim$ $\text{Softmax}\left(\left\{-\widehat{f}_{\alpha_t}(x_i = \ell, x_{-i})/s(t)\right\}_{\ell \in [k]}\right)$
7:     $t \leftarrow t + 1$
8: **until** Stopping Criteria
9: **return** x

Algorithm 2 MCTS with Surrogate Reward

1: **Inputs:** surrogate model $\widehat{f}_\alpha$, search tree $\mathcal{T}$
2: Initialize $s_{\text{best}} = \{\}, r_{\text{best}} = -\infty$
3: **repeat**
4:     $s_{\text{leaf}} \leftarrow \text{Selection}(\pi^{\mathcal{T}})$
5:     $\mathcal{T} \leftarrow \mathcal{T} \cup \{s_{\text{leaf}}\}$
6:     $s_t \leftarrow \text{Simulation}(\pi^{RS}, s_{\text{leaf}})$
7:     $r \leftarrow -\widehat{f}_\alpha(s_t)$
8:     $\text{Backup}(s_{\text{leaf}}, r)$
9:     **if** $r > r_{\text{best}}$ **then**
10:       $r_{\text{best}} \leftarrow r$ and $s_{\text{best}} \leftarrow s_t$
11:     **end if**
12: **until** Stopping Criteria
13: **return** s_{best}

Computational Complexity: The computational complexity per time step associated with learning the surrogate model, for both representations introduced in 3.1, is in $\mathcal{O}(d) = \mathcal{O}(k^{m-1}n^m)$, and is thus linear in the number of experts d. Moreover, the complexity of the simulated annealing algorithm (Algorithm 1) is in $\mathcal{O}(kk^{m-1}n^{m-1}n) = \mathcal{O}(kd)$, assuming that the number of iterations in each SA run is in $\mathcal{O}(n)$. As a result, the overall complexity of the algorithm is in $\mathcal{O}(kd)$. Finally, the computational complexity of each playout in Algorithm 2 is in $(O)(kn)$, leading to an overall complexity of $(O)(kd)$, assuming $(O)(d/n)$ playouts per time step.

4   EXPERIMENTS AND RESULTS

In this section, we measure the performance of the proposed representations, when used as surrogate/reward model in conjunction with search algorithms (SA and MCTS) in BBO and design problems. The learning rate used in exponential weight updates is selected via the anytime learning rate schedule suggested in Dadkhahi et al. (2020) and Gerchinovitz & Yu (2011) (see Appendix). The maximum degree of interactions used in our surrogate models is set to two for all the problems; increasing the max order improved the results only marginally. The sparsity parameter λ in exponential weight updates is set to 1 in all the experiments following the same choice made in Dadkhahi et al. (2020). Experimentally, the learning algorithm is fairly insensitive to the variations in the latter parameter. In each experiment, we report the results averaged over multiple runs (20 runs in BBO experiments and 10 runs in design experiments) $\pm$ one standard error of the mean. The experiments were run on machines with CPU cores from the Intel Xeon E5-2600 v3 family.

BBO Experiments: We compare the performance of our ECO algorithms in conjunction with SA with two baselines, random search (RS) and simulated annealing (SA), as well as a state-of-the-art Bayesian combinatorial optimization algorithm (COMBO) Oh et al. (2019). In particular, we consider two synthetic benchmarks (Latin square problem and pest control problem) and a real-word sequence design problem in biology: RNA sequence optimization. In addition to the performance of the algorithms in terms of the best value of $f(x)$ observed until a given time step t, we measure the average computation time per time step of our algorithm versus that of COMBO. The decay parameter used in the annealing schedule of SA is set to $\ell = 3$ in all the experiments. In addition, the number of SA iterations in our surrogate models is set to $T = 3 \times n$. Intuitively, each of these parameters creates an exploration-exploitation trade-off. The smaller (larger) the value of ℓ or T, the more exploratory (exploitative) is the behavior of SA. The selected values seem to create a reasonable balance; tuning these parameters may improve the performance of the acquisition function.

Synthetic Benchmarks: We consider two synthetic problems: Latin square problem Colbourn & Dinitz (2006), a commonly used combinatorial optimization benchmark, and the pest control problem considered in Oh et al. (2019) (see Appendix for the latter results). In both problems, we have $n = 25$ categorical variables, each of cardinality $k = 5$. A Latin square of order k is a $k \times k$ matrix of elements $x_{ij} \in [k]$, such that each number appears in each row and column exactly once. When $k = 5$, the problem of finding a Latin square has $161,280$ solutions in a space of dimensionality 5^{25}. We formulate the problem of finding a Latin square of order k as a black-box optimization by imposing an additive penalty of one for any repetition of numbers in any row or column. Hence, function evaluations are in the range $[0, 2k(k-1)]$, and a function evaluation of zero corresponds to a Latin square of order k. We consider a noisy version of this problem, where an additive Gaussian noise with zero mean and standard deviation of 0.1 is added to function evaluations observed by each algorithm. Both ECO-F and ECO-G outperform the baselines with a considerable margin. In addition, ECO-G outperforms COMBO until time step $t = 190$. At larger time steps, COMBO outperforms the other algorithms, however, this performance comes at the price of a far larger computation time. ECO-F and ECO-G offer a speed-up over COMBO by a factor of roughly 100 and 50, respectively.

RNA Sequence Optimization Problem: Consider an RNA sequence as a string $A = a_1 \ldots a_n$ of n letters (nucleotides) over the alphabet $\Sigma = \{A, U, G, C\}$. A pair of complementary nucleotides a_i and a_j, where $(i < j)$, can interact with each other and form a base pair (denoted by (i, j)), A-U, C-G and G-U being the energetically stable pairs. Thus, the secondary structure, i.e. the minimum free energy structure, of an RNA can be represented by an ensemble of pairing bases. A number of RNA folding algorithms Lorenz et al. (2011); Markham & Zuker (2008) use a thermodynamic model (e.g. Zuker & Stiegler (1981)) and dynamic programming to estimate MFE of a sequence. However, the $O(n^3)$ time complexity of these algorithms prohibits their use for evaluating substantial numbers of RNA sequences Gould et al. (2014) and exhaustively searching the space to identify the global free energy minimum, as the number of sequences grows exponentially as 4^n.

We formulate the RNA sequence optimization problem as follows: For a sequence of length n, find the RNA sequence which folds into a secondary structure with the lowest MFE. In our experiments, we initially set $n = 30$ and $k = 4$. We then use the popular RNAfold package Lorenz et al. (2011) to evaluate the MFE for a given sequence. The goal is to find the lowest MFE sequence by calling the MFE evaluator minimum number of times. As depicted in Figure 1, both ECO-F and particularly ECO-G outperform the baselines as well as COMBO by a considerable margin.

Figure 1: RNA BBO Problem with $n = 30$ Figure 2: Eterna100 puzzle #41 ($n = 35$)

RNA Design Experiments: The problem is to find a primary RNA sequence ϕ which folds into a target structure w, given a folding algorithm F. Such target structures can be represented as a sequence of dots (for unpaired bases) and brackets (for paired bases). In our algorithm, the action sets are defined as follows. For unpaired sites $\mathcal{A}_t = \{A, G, C, U\}$ and for paired sites $\mathcal{A}_t = \{GC, CG, AU, UA\}$. At the beginning of each run of our algorithm (ECO-F and ECO-G in conjunction with MCTS acquisition), we draw a random permutation for the order of locations to be selected in each level of the tree. The reward value offered by the environment (i.e. the black-box function) at any time step t corresponds to the normalized Hamming distance between the target structure ω and the structure $y_t = F(x_t)$ of the sequence x_t found by each algorithm, i.e. $d_H(w, y_t)$.

We compare the performance of our algorithms against RS as a baseline, where random search is carried out over the given structure (i.e. default policy π^{RS}) rather than over unstructured random sequences. We also include two state-of-the-art algorithms in our experiments: MCTS-RNA of Yang et al. (2017) and LEARNA of Runge et al. (2019). MCTS-RNA has an exploration parameter, which we tune in advance (per sequence). LEARNA has a set of 14 hyper-parameters tuned a priori using training data and is provided by the authors of Runge et al. (2019). Note that the latter training phase (for LEARNA) as well as the former exploration parameter tuning (for MCTS-RNA) is offered to the respective algorithms as an advantage, whereas for our algorithm we use a global set of heuristic choices for the two hyper-parameters, rather than attempting to tune the two hyper-parameters. In particular, we set the exploration parameter c to 0.5 and the number of MCTS playouts at each time step to $30 \times h$, where h is the height of the tree (i.e. number of dots and bracket pairs). The latter heuristic choice is made since the bigger the tree, the more playouts are needed to explore the space.

We point out that the entire design pipeline in state-of-the-art algorithms typically also includes a local improvement step (as a post-processing step), which is either a rule-based search (e.g. in Yang et al. (2017)) or an exhaustive search (e.g. in Runge et al. (2019)) over the mismatched sites. We do not include the local improvement step in our experiments, since we are interested in measuring sample efficiency of different algorithms. In other words, the question is the following: given a fixed and finite evaluation budget, which algorithm is able to get closer to the target structure.

For our experiments, we focus on three puzzles from the Eterna-100 dataset Anderson-Lee et al. (2016). Two of the selected puzzles (#15 and #41 of lengths 30 and 35, resp.), despite their fairly small lengths, are challenging for many algorithms (see Anderson-Lee et al. (2016)). In both puzzles, our algorithms ECO-F and ECO-G (with MCTS acquisition) are able to significantly improve the performance of MCTS when limited number of black-box evaluations is available. All algorithms outperformed RS as expected. Within the given 500 evaluation budget, ECO-G, and especially ECO-F, are superior to LEARNA by a substantial margin (see Appendix). In puzzle number 41 (Figure 13), again both ECO-G and ECO-F significantly outperform LEARNA, over the given number of evaluations. Interestingly, ECO-F is able to outperform LEARNA throughout the evaluation process, and in average finds a far better final solution than LEARNA. See Appendix for the third puzzle.

Conclusions: We propose novel Fourier representations as surrogate models for black box optimization over categorical variables and show performance improvements over existing baselines when combined with state-of-the-art acquisition functions.

REFERENCES

Jeff Anderson-Lee, Eli Fisker, Vineet Kosaraju, Michelle Wu, Justin Kong, Jeehyung Lee, Minjae Lee, Mathew Zada, Adrien Treuille, and Rhiju Das. Principles for predicting rna secondary structure design difficulty. *Journal of Molecular Biology*, 428(5, Part A):748 – 757, 2016. Challenges in RNA Structural Modeling and Design.

Frances H Arnold. Design by directed evolution. *Accounts of chemical research*, 31(3):125–131, 1998.

Nicholas Bogard, Johannes Linder, Alexander B Rosenberg, and Georg Seelig. A deep neural network for predicting and engineering alternative polyadenylation. *Cell*, 178(1):91–106, 2019.

David H Brookes, Hahnbeom Park, and Jennifer Listgarten. Conditioning by adaptive sampling for robust design. *arXiv preprint arXiv:1901.10060*, 2019.

J Ross Buchan and Ian Stansfield. Halting a cellular production line: responses to ribosomal pausing during translation. *Biology of the Cell*, 99(9):475–487, 2007.

Charles J. Colbourn and Jeffrey H. Dinitz. *Handbook of Combinatorial Designs, Second Edition (Discrete Mathematics and Its Applications)*. Chapman & Hall/CRC, 2006.

Hamid Dadkhahi, Karthikeyan Shanmugam, Jesus Rios, Payel Das, Samuel Hoffman, Troy David Loeffler, and Subramanian Sankaranarayanan. Combinatorial black-box optimization with expert advice. In *KDD*, 2020.

Matthew Davis, Selena M Sagan, John P Pezacki, David J Evans, and Peter Simmonds. Bioinformatic and physical characterizations of genome-scale ordered rna structure in mammalian rna viruses. *Journal of virology*, 82(23):11824–11836, 2008.

Ken A Dill and Justin L MacCallum. The protein-folding problem, 50 years on. *science*, 338(6110): 1042–1046, 2012.

Neil Dixon, John N Duncan, Torsten Geerlings, Mark S Dunstan, John EG McCarthy, David Leys, and Jason Micklefield. Reengineering orthogonally selective riboswitches. *Proceedings of the National Academy of Sciences*, 107(7):2830–2835, 2010.

Peter Eastman, Jade Shi, Bharath Ramsundar, and Vijay S Pande. Solving the rna design problem with reinforcement learning. *PLoS computational biology*, 14(6):e1006176, 2018.

Eduardo C Garrido-Merchán and Daniel Hernández-Lobato. Dealing with categorical and integer-valued variables in bayesian optimization with gaussian processes. *Neurocomputing*, 380:20–35, 2020.

Stuart Geman and Donald Geman. Stochastic relaxation, gibbs distributions, and the bayesian restoration of images. *IEEE Transactions on pattern analysis and machine intelligence*, 6:721–741, 1984.

Sébastien Gerchinovitz and Jia Yuan Yu. Adaptive and optimal online linear regression on $\ell 1$-balls. In *Algorithmic Learning Theory*, pp. 99–113. Springer Berlin Heidelberg, 2011.

Daniel Golovin, Benjamin Solnik, Subhodeep Moitra, Greg Kochanski, John Karro, and D Sculley. Google vizier: A service for black-box optimization. In *Proceedings of the 23rd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1487–1495, 2017.

Rafael Gómez-Bombarelli, Jennifer N Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, Ryan P Adams, and Alán Aspuru-Guzik. Automatic chemical design using a data-driven continuous representation of molecules. *ACS central science*, 4(2):268–276, 2018.

Nathan Gould, Oliver Hendy, and Dimitris Papamichail. Computational tools and algorithms for designing customized synthetic genes. *Frontiers in bioengineering and biotechnology*, 2:41, 2014.

Anvita Gupta and James Zou. Feedback gan for dna optimizes protein functions. *Nature Machine Intelligence*, 1(2):105–111, 2019.

Ivo L Hofacker. Vienna rna secondary structure server. *Nucleic acids research*, 31(13):3429–3431, 2003.

Ivo L Hofacker, Walter Fontana, Peter F Stadler, L Sebastian Bonhoeffer, Manfred Tacker, and Peter Schuster. Fast folding and comparison of rna secondary structures. *Monatshefte für Chemie/Chemical Monthly*, 125(2):167–188, 1994.

John H Holland and Judith S Reitman. Cognitive systems based on adaptive algorithms. In *Pattern-directed inference systems*, pp. 313–329. Elsevier, 1978.

Shuichi Hoshika, Nicole A Leal, Myong-Jung Kim, Myong-Sang Kim, Nilesh B Karalkar, Hyo-Joong Kim, Alison M Bates, Norman E Watkins, Holly A SantaLucia, Adam J Meyer, et al. Hachimoji dna and rna: A genetic system with eight building blocks. *Science*, 363(6429):884–887, 2019.

J. Kennedy and R. Eberhart. Particle swarm optimization. In *Proceedings of ICNN'95 - International Conference on Neural Networks*, volume 4, pp. 1942–1948 vol.4, 1995.

Nathan Killoran, Leo J Lee, Andrew Delong, David Duvenaud, and Brendan J Frey. Generating and designing dna with deep generative models. *arXiv preprint arXiv:1712.06148*, 2017.

S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. Optimization by simulated annealing. *Science*, 220 (4598):671–680, 1983.

Levente Kocsis and Csaba Szepesvári. Bandit based monte-carlo planning. In *Proceedings of the 17th European Conference on Machine Learning*, ECML'06, pp. 282–293. Springer-Verlag, 2006.

Hui Li, Taek Lee, Thomas Dziubla, Fengmei Pi, Sijin Guo, Jing Xu, Chan Li, Farzin Haque, Xing-Jie Liang, and Peixuan Guo. Rna as a stable polymer to build controllable and defined nanostructures for material and biomedical applications. *Nano today*, 10(5):631–655, 2015.

Johannes Linder and Georg Seelig. Fast differentiable DNA and protein sequence optimization for molecular design. Available at: https://arxiv.org/pdf/2005.11275, 2020.

Ge Liu, Haoyang Zeng, Jonas Mueller, Brandon Carter, Ziheng Wang, Jonas Schilz, Geraldine Horny, Michael E Birnbaum, Stefan Ewert, and David K Gifford. Antibody complementarity determining region design using high-capacity machine learning. *Bioinformatics*, 36(7):2126–2133, 2020.

Ronny Lorenz, Stephan H. Bernhart, Christian Höner zu Siederdissen, Hakim Tafer, Christoph Flamm, Peter F. Stadler, and Ivo L. Hofacker. Viennarna package 2.0. *Algorithms for Molecular Biology*, 6(1):26, 2011.

Nicholas R Markham and Michael Zuker. Unafold. In *Bioinformatics*, pp. 3–31. Springer, 2008.

Andrew H Ng, Taylor H Nguyen, Mariana Gómez-Schiavon, Galen Dods, Robert A Langan, Scott E Boyken, Jennifer A Samson, Lucas M Waldburger, John E Dueber, David Baker, et al. Modular and tunable biological feedback control using a de novo protein switch. *Nature*, 572(7768):265–269, 2019.

Changyong Oh, Jakub Tomczak, Efstratios Gavves, and Max Welling. Combinatorial bayesian optimization using the graph cartesian product. In *Advances in Neural Information Processing Systems 32*, pp. 2910–2920. Curran Associates, Inc., 2019.

Martin Pincus. Letter to the editor—a monte carlo method for the approximate solution of certain types of constrained optimization problems. *Operations Research*, 18(6):1225–1228, 1970.

Fernando Portela. An unexpectedly effective monte carlo technique for the rna inverse folding problem. *BioRxiv*, pp. 345587, 2018.

Matthias Poloczek Ricardo Baptista. Bayesian optimization of combinatorial structures. In *ICML*, 2018.

Frederic Runge, Danny Stoll, Stefan Falkner, and Frank Hutter. Learning to design rna. *arXiv preprint arXiv:1812.11951*, 2018.

Frederic Runge, Danny Stoll, Stefan Falkner, and Frank Hutter. Learning to design RNA. In *International Conference on Learning Representations*, 2019.

Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P Adams, and Nando De Freitas. Taking the human out of the loop: A review of bayesian optimization. *Proceedings of the IEEE*, 104(1): 148–175, 2015.

William M. Spears. Simulated annealing for hard satisfiability problems. In *DIMACS Workshop: Cliques, Coloring, and Satisfiability*, pp. 533–557, 1993.

Zachary D Stephens, Skylar Y Lee, Faraz Faghri, Roy H Campbell, Chengxiang Zhai, Miles J Efron, Ravishankar Iyer, Michael C Schatz, Saurabh Sinha, and Gene E Robinson. Big data: astronomical or genomical? *PLoS biology*, 13(7):e1002195, 2015.

Akito Taneda. Multi-objective optimization for rna design with multiple target secondary structures. *BMC bioinformatics*, 16(1):280, 2015.

Audrey Terras. *Fourier Analysis on Finite Groups and Applications*. London Mathematical Society Student Texts. Cambridge University Press, 1999.

Edoardo Trotta. On the normalization of the minimum free energy of rnas by sequence length. *PLoS one*, 9(11), 2014.

Ryota Yamagami, Mohammad Kayedkhordeh, David H Mathews, and Philip C Bevilacqua. Design of highly active double-pseudoknotted ribozymes: a combined computational and experimental study. *Nucleic acids research*, 47(1):29–42, 2019.

Xiufeng Yang, Kazuki Yoshizoe, Akito Taneda, and Koji Tsuda. Rna inverse folding using monte carlo tree search. *BMC Bioinformatics*, 8:468, 2017.

Joseph N Zadeh, Conrad D Steenberg, Justin S Bois, Brian R Wolfe, Marshall B Pierce, Asif R Khan, Robert M Dirks, and Niles A Pierce. Nupack: Analysis and design of nucleic acid systems. *Journal of computational chemistry*, 32(1):170–173, 2011.

Michael Zuker and Patrick Stiegler. Optimal computer folding of large rna sequences using thermodynamics and auxiliary information. *Nucleic acids research*, 9(1):133–148, 1981.