LOGICAL ENTITY REPRESENTATION IN KNOWLEDGE-GRAPHS FOR DIFFERENTIABLE RULE LEARNING

ABSTRACT

Probabilistic logical rule learning has shown great strength in logical rule mining and knowledge graph completion. It learns logical rules to predict missing edges by reasoning on existing edges in the knowledge graph. However, previous efforts have largely been limited to only modeling chain-like Horn clauses such as $R_1(x, z) \wedge R_2(z, y) \Rightarrow H(x, y)$. This formulation overlooks additional contextual information from neighboring sub-graphs of entity variables x, y and z. Intuitively, there is a large gap here, as local sub-graphs have been found to provide important information for knowledge graph completion. Inspired by these observations, we propose *Logical Entity RePresentation (LERP)* to encode contextual information of entities in the knowledge graph. A LERP is designed as a vector of probabilistic logical functions on the entity's neighboring sub-graph. It is an interpretable representation while allowing for differentiable optimization. We can then incorporate LERP into probabilistic logical rule learning to learn more expressive rules. Empirical results demonstrate that with LERP, our model outperforms other rule learning methods in knowledge graph completion and is comparable or even superior to state-of-the-art black-box methods. Moreover, we find that our model can discover a more expressive family of logical rules. LERP can also be further combined with embedding learning methods like TransE to make it more interpretable. [1]

1   INTRODUCTION

In recent years, the use of logical formulation has become prominent in knowledge graph (KG) reasoning and completion (Teru et al., 2020; Campero et al., 2018; Payani & Fekri, 2019), mainly because a logical formulation can be used to enforce strong prior knowledge on the reasoning process. In particular, probabilistic logical rule learning methods (Sadeghian et al., 2019; Yang et al., 2017) have shown further desirable properties including efficient differentiable optimization and explainable logical reasoning process. These properties are particularly beneficial for KGs since KGs are often large in size, and modifying KGs has social impacts so rationales are preferred by human readers.

Due to the large search space of logical rules, recent efforts Sadeghian et al. (2019); Yang et al. (2017); Payani & Fekri (2019) focus on learning *chain-like Horn clauses* of the following form:

$$r_1(x, z_1) \wedge r_2(z_1, z_2) \wedge \cdots \wedge r_K(z_{K-1}, y) \Rightarrow H(x, y), \quad (1)$$

where r_k represents relations and x, y z_k represent entities in the graph. Even though this formulation is computationally efficient (see Section 3), it overlooks potential contextual information coming from local sub-graphs neighboring the entities (variables x, y, and all z_i) . However, this kind of contextual information can be important for reasoning on knowledge graphs. Figure 1(b) shows an example. If we only know that z is mother of x and y, we are not able to infer if y is a brother or sister of x. However, in Figure 1(c), with the contextual logical information that $\exists z'$ $is\_son\_of(y, z')$ we can infer that y is a male and that y should be the brother rather than the sister of x.

Recent deep neural network models based on Graph Neural Networks (GNNs) (Teru et al., 2020; Mai et al., 2021) have utilized local sub-graphs as an important inductive bias in knowledge graph

---

[1]All code and data will be made publicly available upon publication.

Figure 1: Incorporating contextual information of entities can benefit missing link prediction.

completion. Although GNNs can efficiently incorporate neighboring information via message-passing mechanisms to improve prediction performance (Zhang et al., 2019; Lin et al., 2022), they are not capable of discovering explicit logical rules, and the reasoning process of GNNs is largely unexplainable.

In this paper, we propose *Logical Entity RePresentation (LERP)* to incorporate information from local sub-graphs into probabilistic logic rule learning. LERP is a logical contextual representation for entities in knowledge graph. For an entity e, a LERP $L(e)$ is designed as a vector of logical functions $L_i(e)$ on e's neighboring sub-graph and the enclosed relations. We then incorporate LERP in probabilistic logical rule learning methods to provide contextual information for entities. Different from other embedding learning methods, LERP encodes contextual information rather than identity information of entities. In the example discussed above in Figure 1, an ideal LERP for y might contain logical functions like $L_i(y) = \exists z'\ is\_son\_of(y, z')$. Therefore, when predicting the relation *is_brother_of*, the rule learning model can select L_i from LERP and get the rule written in Figure 1(c). In our model, LERP can be jointly optimized with probabilistic logical rules. We empirically show that our model outperforms previous logical rule learning methods on knowledge graph completion benchmarks. We also find that LERP allows our model to compete, and sometimes even exceed, strong black-box baselines. Moreover, LERP is itself an interpretable representation, so our model is able to discover more complex logical rules from data. In Section 5.4 we demonstrate that LERP can also be combinedd with embedding-learning models like TransE (Bordes et al., 2013) to construct a hybrid model that learns interpretable embeddings.

2 RELATED WORK

Logical Rule Learning This work is closely related to the problem of learning logical rules for knowledge graph reasoning. Traditional rule learning approaches search for the logical rules with heuristic metrics such as support and confidence, and then learn a scalar weight for each rule. Representative methods include Markov Logic Networks (Richardson & Domingos, 2006; Khot et al., 2011), relational dependency networks (Neville & Jensen, 2007; Natarajan et al., 2010), rule mining algorithms (Galárraga et al., 2013; Meilicke et al., 2019), path finding and ranking approaches (Lao & Cohen, 2010; Lao et al., 2011; Chen et al., 2016), and probabilistic personalized page rank (ProPPR) models (Wang et al., 2013; 2014a). However, most traditional methods face the problem of large searching space of logical rules, or rely on predefined heuristics to guide searching. These heuristic measures are designed by humans and fixed, and may not necessarily be generalizable to different tasks.

Probabilistic Logical Rule Learning Recently, another trend of methods propose jointly learning the logical rule form and the weights in a differentiable manner. Representative models include the embedding-based method of Yang et al. (2015), Neural LP (Yang et al., 2017), DRUM (Sadeghian et al., 2019) and RLvLR (Omran et al., 2018). Furthermore, some efforts have applied reinforcement learning to rule learning. The idea is to train agents to search for paths in the knowledge graph connecting the start and destination entities. Then, the connecting path can be extracted as a logical rule (Xiong et al., 2017; Chen et al., 2018; Das et al., 2018; Lin et al., 2018; Shen et al., 2018). These methods are mostly focused on learning chain-like Horn clauses like Equation 1. This formulation limits logical rules from using extra contextual information about local subgraphs. In contrast, we

(a) tree-like logical function   (b) parametrized probabilistic LERP

Figure 2: Illustration of our construction of logical entity function and representation. (a): Each logical function is defined in a recursive manner with operations defined in Definition 1 (b): we build LERP in a feed-forward style, by constructing intermediate logical functions column by column.

propose to use LERP to incorporate contextual information into logical rules, and are capable of modeling a more expressive family of rules.

Embedding-Based Neural Graph Reasoning   Our work is also related and compared to graph embedding-based methods. However, those models do not explicitly model logic rules, but reason about entities and relations over the latent space. Representative work include TransE (Bordes et al., 2013), RotatE (Sun et al., 2018), ConvE (Dettmers et al., 2018), ComplEx (Trouillon et al., 2016), TransH (Wang et al., 2014b), HolE (Nickel et al., 2016), KBGAN (Cai & Wang, 2018), TuckER (Balažević et al., 2019) and Yang et al. (2015). Although LERP also learns representation for entities, LERP is different from these latent embeddings because LERP encodes contextual information rather than identity information of entities like in TransE. LERP is composed of vectors of interpretable logical functions, and can be applied to explicitly learning of more complex logical rules. Yang et al. (2015) also learns entity embeddings for rule learning, but the rule form is still limited to chain-like rules, and the embedding is not interpretable.

3   Problem Statement

Chain-like Horn Clauses   are a set of first-order logic rules that have been widely studied in logical rule learning (Sadeghian et al., 2019; Yang et al., 2017). Formally, the task setting provides a knowledge graph $G = \{(s, r, o)|s, o \in \mathcal{E}, r \in \mathcal{R}\}$, where $\mathcal{E}$ is the set of entities and $\mathcal{R}$ is the set of relation types. The chain-like Horn clauses are defined as in Equation 1, where $x, y, z_k \in \mathcal{E}$ (for $k \in [1, K-1]$) and $H, r_k \in \mathcal{R}$ (for $k \in [1, K]$). The "reverse" edges $r'(z, z') = r(z', z)$ are often added to the edge type set $\mathcal{R}$. $r_1(x, z_1) \wedge \cdots \wedge r_K(z_{K-1}, y)$ is typically named the "body" of the rule.

A computational convenience of this formulation is that, if x is known, the rule can be evaluated by computing a sequence of matrix multiplications. We can first order entities in $\mathcal{E}$ from 1 to $n = |\mathcal{E}|$, let $\mathbf{v}_x$ be an n-dimensional one-hot vector of x's index, and let $\boldsymbol{A}_{r_k}$ be the adjacency matrix of r_k. In this way, we can compute $\mathbf{v}_x^\top \prod_{k=1}^{K} \boldsymbol{A}_{r_k}$ in $O(Kn^2)$ time. It is easy to verify that this result is an n-dimensional vector counting how many paths connect x and y following the relation sequence $r_1, r_2 \cdots r_K$. This formulation has been widely adopted by previous methods.

Logical Entity Representation (LERP)   In this work, we introduce LERP in logical rules to provide additional local contextual information for entities in the knowledge graph. A LERP for entity e is formatted as a vector $\boldsymbol{L}(e) = (L_1(e), \cdots, L_m(e))$ where the dimension m is a hyper-parameter. Each $L_i(e)$ is a logical function over e's surrounding sub-graph. To enable efficient evaluation of $L_i(e)$, we limit $L_i(e)$ to a family of *tree-like logical functions* as defined below:

Definition 1 *(Tree-like logical function)*

Given a binary predicate set $\mathcal{R}$, the family of tree-like logical functions $\mathcal{T}$ is recursively constructed with the following operations:

   1. (True function) $f(w_0) = true$ belongs to $\mathcal{T}$.

Category	Model	WN18RR				WN18			
		MRR	H@1	H@3	H@10	MRR	H@1	H@3	H@10
No Rule Learning	ComplEx	0.44	0.41	0.46	0.51	0.941	0.936	0.936	0.947
	TransE	0.466	0.4226	-	0.556	0.495	0.113	0.888	0.943
	ConvE	0.43	0.40	0.44	0.52	0.943	0.935	0.946	0.956
	LinearRE	0.495	0.453	0.509	0.578	0.952	0.947	0.955	0.961
	Inverse Model	0.35	0.35	0.35	0.35	**0.963**	**0.953**	0.964	0.964
	QuatDE	0.489	0.438	0.509	0.586	0.95	0.944	0.954	0.961
	MLMLM	0.502	0.439	0.542	0.611	-	-	-	-
	kNN-KGE	0.579	0.525	0.604	**0.683**	-	-	-	-
Rule Learning	Neural LP	0.435	0.371	0.434	0.566	0.94	–	-	0.945
	DRUM	0.486	0.425	0.513	0.586	0.944	0.939	0.943	0.954
	RNNLogic+	0.513	0.471	0.532	0.597	-	-	-	-
	LERP	**0.622**	**0.593**	**0.634**	0.682	0.958	0.932	**0.982**	**0.987**

Table 1: Experiment results on knowledge graph completion tasks on WN18RR and WN18.

2. *(Chaining) For any $f(w_i) \in \mathcal{T}$ and $r \in \mathcal{R}$, $f'(w_{i+1}) = \exists w_i : f(w_i) \wedge r(w_i, w_{i+1})$ also belongs to $\mathcal{T}$.*

3. *(Negation) For any $f(w_i) \in \mathcal{T}$, $f'(w_i) = \neg f(w_i)$ belongs to $\mathcal{T}$.*

4. *(Merging) For any $f(w_i), f'(w_{i'}) \in \mathcal{T}$, let $i'' = \max(i, i') + 1$, after applying substitution $\{w_i \mapsto w_{i''}\}$ and $\{w_{i'} \mapsto w_{i''}\}$ to two functions respectively, $f''(w_{i''}) = f(w_{i''}) \wedge f'(w_{i''})$ ($\wedge$-merging) and $f''(w_{i''}) = f(w_{i''}) \vee f'(w_{i''})$ ($\vee$-merging) belong to $\mathcal{T}$.*

This definition includes arbitrarily complex functions, but in practice we limit a maximum number of operations. Intuitively, one can think of a function $f(w_i) \in \mathcal{T}$ as mimicking the shape of a local tree spanning from w_i as in Figure 2(a). Specifically, this is because it gathers information together recursively through logical operations. $\boldsymbol{L}(e)$ then serves as a logical contextual representation for e's local surrounding sub-graph. We then extend Equation 1 into the following formula to incorporate contextual information from $\boldsymbol{L}(e)$:

$$r_1(x, z_1) \wedge r_2(z_1, z_2) \wedge \cdots \wedge r_K(z_{K-1}, y) \wedge \left(\bigwedge_{z' \in \{x, y, z_1, \cdots\}} L_{i_{z'}}(z') \right) \Rightarrow H(x, y), \quad (2)$$

where $i_{z'} \in [1..m]$ is an index to select logical functions from LERP. Now the rule in Figure 1(c) is an example of this form by setting $L_{i_x}(x) = true$, $L_{i_y}(y) = true$, $L_{i_{z_1}}(z_1) = \exists z_2 : is\_son\_of(z_1, z_2)$. In fact, this extension does not break the computational efficiency of chain-like Horn clauses (proofs are included in Appendix):

Theorem 1 *For any rule expressed in Equation 2, if x is known, the evaluation of its LHS over x and all $y \in \mathcal{E}$ (considering all possible z_i), can be determined in $O(Cn^2)$ time where $n = |\mathcal{E}|$ is the size of the entity set and C is a constant related to the rule.*

4 FRAMEWORK

4.1 DERIVATION OF LERP

This section describes our computational modeling of LERP and how to incorporate it in probabilistic logic rule learning. In Definition 1 we have defined a family of tree-like logical functions which enables efficient evaluation. However, the selection of predicates and its logical form is still discrete and can lead to huge searching complexity. Borrowing ideas from Yang et al. (2017); Sadeghian et al. (2019) we relax LERP to the probabilistic domain to make its results continuous, which also allows us to use gradient-based methods for optimization.

Figure 2(b) provides an illustration of our method. We compute the tree-like probabilistic logical functions L_i^{Θ} parameterized by Θ by adopting a feed-forward paradigm, and compute intermediate functions $f_{j,i}^{\Theta}(z_{j,i})$ column by column. The first column contains only *true* functions

	Family				**Kinship**				**UMLS**			
	MRR	H@1	H@3	H@10	MRR	H@1	H@3	H@10	MRR	H@1	H@3	H@10
MLN	-	-	-	-	0.351	0.189	0.408	0.707	0.688	0.587	0.755	0.869
Boosted RDN	-	-	-	-	0.469	0.395	0.520	0.567	0.227	0.147	0.256	0.376
PathRank	-	-	-	-	0.369	0.272	0.416	0.673	0.197	0.148	0.214	0.252
MINERVA	-	-	-	-	0.401	0.235	0.467	0.766	0.564	0.426	0.658	0.814
NeuralLP	0.931	0.880	0.978	0.994	0.302	0.167	0.339	0.596	0.483	0.332	0.563	0.775
DRUM	0.958	0.927	0.987	0.996	0.534	0.367	0.628	0.885	0.695	0.546	0.808	0.935
RNNLogic	0.893	0.862	0.923	0.928	0.639	0.495	0.731	0.924	0.745	0.630	0.833	0.924
LERP	**0.970**	**0.947**	**0.991**	**0.997**	**0.643**	**0.499**	**0.735**	**0.931**	**0.762**	**0.646**	**0.855**	**0.942**

Table 2: Experiment results on statistical relation learning datasets.

$f_{0,i}^{\Theta}(z_{0,i}) = true$. For $j > 0$, each $f_{j,i}^{\Theta}(z_{j,i})$ is constructed from the previous column by 6 possible operations: *true function*, *chaining*, *negation*, $\wedge$-*merging*, and $\vee$-*merging* from Definition 1, as well as an additional *copy* operation that simply copies $f_{j-1,i}^{\Theta}(z_{j-1,i})$. Note that the result of $f_{j,i}^{\Theta}(z_{j,i})$ over $\mathcal{E}$ can be represented as a $|\mathcal{E}|$-dimensional vector $\mathbf{v}_{j,i}$. Taking this notation, the formulae for the 6 possible types of $f_{j,i}^{\Theta}(z_{j,i})$ are:

$$\mathbf{v}_{j,i;\text{true}} = \mathbf{1} \qquad\qquad \mathbf{v}_{j,i;\text{chaining}} = \left(\mathbf{v}_{j-1,i}^{\top} \sum_{r \in \mathcal{R}} \alpha_{r,j,i} \boldsymbol{A}_r \right)^{\top}$$

$$\mathbf{v}_{j,i;\neg} = \mathbf{1} - \mathbf{v}_{j-1,i} \qquad\qquad \mathbf{v}_{j,i;\text{copy}} = \mathbf{v}_{j-1,i}$$

$$\mathbf{v}_{j,i;\wedge} = \mathbf{v}_{j-1,i} \odot \sum_{i'=1}^{m} \beta_{j,i,i'}^{\wedge} \mathbf{v}_{j-1,i'} \qquad \mathbf{v}_{j,i;\vee} = \mathbf{1} - (\mathbf{1} - \mathbf{v}_{j-1,i}) \odot (\mathbf{1} - \sum_{i'=1}^{m} \beta_{j,i,i'}^{\vee} \mathbf{v}_{j-1,i'})$$

where $\odot$ denotes Hadamard product. Note that we pose normalization constraints so that $\alpha_{r,j,i} > 0$, $\sum_r \alpha_{r,j,i} = 1$, $\beta_{j,i,i'}^{*} > 0$, $\sum_{i'} \beta_{j,i,i'}^{*} = 1$. These 6 types of scores are then gathered by a probability distribution $p_{j,i,*}$:

$$\mathbf{v}_{j,i} = p_{j,i,1} \mathbf{v}_{j,i;\text{true}} + p_{j,i,2} \mathbf{v}_{j,i;\text{chaining}} + p_{j,i,3} \mathbf{v}_{j,i;\neg} + p_{j,i,4} \mathbf{v}_{j,i;\text{copy}} + p_{j,i,5} \mathbf{v}_{j,i;\wedge} + p_{j,i,6} \mathbf{v}_{j,i;\vee}$$

Thereby $\mathbf{v}_{j,i}$ represents the result of the probabilistic logical function $f_{j,i}^{\Theta}$ on all entities. p, α, β are all learnable parameters in Θ. There are a total of $T + 1$ columns of intermediate functions. Finally we use the last column of functions $f_{T,i}^{\Theta}$ as L_i^{Θ}, and $\boldsymbol{L}^{\Theta}(e) = (L_1^{\Theta}(e), \cdots, L_m^{\Theta}(e))$ is our logical entity representation LERP on e.

Next we explain the computation of chain-like probabilistic logical rules, and how to further incorporate LERP. In Yang et al. (2017), they model a probabilistic selection of logical predicates, so that the rules can be differentiably evaluated. Suppose for the chain-like rules in Equation 1, the predicate of r_k is selected according to a distribution $a_{r,k}$. Then the probability that the clause body is true between each $x, y \in \mathcal{E}$ can be given by

$$\prod_{k=1}^{K} \left(\sum_{r \in \mathcal{R}} a_{r,k} \boldsymbol{A}_r \right) \tag{3}$$

Now we want to also add a logical function constraint $L_{i_k}^{\Theta}$ from $\boldsymbol{L}^{\Theta}$. Denote $\boldsymbol{L}^{\Theta}(\mathcal{E})$ as an $m \times |\mathcal{E}|$ matrix by iterating $\boldsymbol{L}^{\Theta}(e)$ over all $e \in \mathcal{E}$. We can select $L_{i_k}^{\Theta}$ from $\boldsymbol{L}^{\Theta}$ according to a probabilistic distribution $\boldsymbol{\rho_k}$ over $[1..m]$. Then the results of $L_{i_k}^{\Theta}(z_k)$ on $\mathcal{E}$ can be written in vector form $\boldsymbol{L}^{\Theta}(\mathcal{E})^{\top} \boldsymbol{\rho}_k$. Finally, the evaluation of the body in Equation 2 can be written as

$$\prod_{k=1}^{K} \left(\sum_{r \in \mathcal{R}} a_{r,k} \boldsymbol{A}_r \right) \text{diag} \left(\boldsymbol{L}^{\Theta^{\top}} \boldsymbol{\rho}_k \right) \tag{4}$$

This is the evaluation for a single logical rule. In practice we can have multiple rules to predict one target relation (e.g., in DRUM, there are up to 4), and there are multiple types of target relations in the dataset. So, we learn individual sets of parameters $a_{r,k}$ and $\boldsymbol{\rho}_k$ for different rules, but the parameter Θ for LERP is shared across rules.

weight	logical rule
0.10	$(\nexists z_2 : sister(z_2, x)) \wedge mother(z_1, x) \wedge son(y, z_1) \Rightarrow brother(y, x)$
0.016	$mother(z_1, x) \wedge mother(z_1, y) \wedge (\nexists z_3 : sister(y, z_3)) \Rightarrow brother(y, x)$
0.11	$son(z_1, x) \wedge brother(y, z_1) \Rightarrow son(y, x)$
0.004	$(\nexists z_2 : sister(z_2, x)) \wedge brother(z_1, x) \wedge (\nexists z_3 : sister(z_3, z_1)) \wedge mother(y, z_1) \Rightarrow son(x, y)$
0.039	$wife(x, y) \Rightarrow husband(y, x)$
0.024	$mother(x, z_1) \wedge father(y, z_1) \Rightarrow husband(y, x)$

Table 3: A set of logical rules discovered from the Family dataset.

weight	logical function	weight	logical function
0.99	$\nexists z_1 : sister(e, z_1)$	0.56	$\exists z_1 : brother(e, z_1) \wedge \exists z_2 : aunt(z_2, e)$
0.99	$\nexists z_1 : brother(e, z_1)$	0.46	$\exists z_1 : aunt(e, z_1) \wedge \exists z_2 : daughter(z_2, e)$
0.96	$\nexists z_1 : sister(z_1, e)$	0.39	$\nexists z_1 : uncle(e, z_1)$
0.68	$\exists z_1 : sister(e, z_1) \wedge \exists z_2 : sister(z_2, e)$	0.25	$\exists z_1 : brother(e, z_1) \wedge \exists z_2 : daughter(z_2, e)$

Table 4: The list of logical functions $L_i(e)$ learned in LERP $\boldsymbol{L}(e)$.

4.2 REASONING AND TRAINING

In the task of knowledge graph completion, the model is given a set of queries $r(h, ?)$ and required to find the entity $t \in \mathcal{E}$ that satisfies relation $r(h, t)$. During reasoning and training, we denote $\mathbf{h}$ as the one-hot vector of entity h, and multiply it with Equation 4 to calculate

$$\hat{\mathbf{t}}^\top = \mathbf{h}^\top \prod_{k=1}^{K} \left(\sum_{r \in \mathcal{R}} a_{r,k} \boldsymbol{A}_r \right) \text{diag} \left(\boldsymbol{L}^{\Theta^\top} \boldsymbol{\rho}_k \right)$$

This then can be calculated as a sequence of vector-matrix multiplications. The resulting vector is indicating which entity t is satisfying the query $r(h, ?)$. For training criterion, we use the cross entropy between the normalized prediction $\frac{\hat{\mathbf{t}}}{\|\hat{\mathbf{t}}\|_1}$ and ground-truth one-hot vector $\mathbf{t}$. The loss is differentiable with respect to all the parameters in our model, so we can apply gradient-based optimization methods such as Adam (Kingma & Ba, 2015). During evaluation, we use $\hat{\mathbf{t}}$ as scores and sort it to obtain a ranked entity list for calculating mean reciprocal rank (MRR), Hits, etc.

5 EXPERIMENTS

5.1 KNOWLEDGE GRAPH COMPLETION

Datasets We follow previous works (Yang et al., 2017; Sadeghian et al., 2019) and evaluate on the Unified Medical Language System (UMLS), Kinship, and Family datasets (Kok & Domingos, 2007) as well as the WN18 (Bordes et al., 2013) and WN18RR (Dettmers et al., 2018) datasets. The task is to predict missing edges in theses dataset, and is named "knowldge graph completion" on knowledge graphs like WN18RR and WN18 and "statistical relation learning" on smaller datasets like UMLS, Kinship and Family. For all experiments, we evaluate under the setting of using no external data. For Kinship and UMLS, we follow the data split from Qu et al. (2020), and for Family, we follow the split used by Sadeghian et al. (2019).

For rule learning baselines, we compare with Markov Logic Networks (MLN) (Richardson & Domingos, 2006), Boosted RDN (Natarajan et al., 2010), and path ranking (PathRank) (Lao & Cohen, 2010) as well as other differentiable rule learning baselines such as NeuralLP (Yang et al., 2017) and DRUM (Sadeghian et al., 2019). We also include a reinforcement learning method MIN-ERVA (Das et al., 2018) and an expectation-maximization method RNNLogic (Qu et al., 2020) in baselines. On knowledge graph completion task, we further compare with the following powerful black-box embedding-based models: ComplEx (Trouillon et al., 2016), TransE (Bordes et al., 2013), ConvE and Linear Model (Dettmers et al., 2018), LinearRE (Peng & Zhang, 2020), QuatDE (Gao et al., 2021), MLMLM (Clouatre et al., 2021), and kNN-KGE (Zhang et al., 2022).

Figure 3: Visualization of the space of LERP on the Family dataset. In each of the four figures, we color as red entities of different relative roles (e.g., people who *are daughters*, *sons*, or *have sisters* or *brothers*).

For evaluation, following the setting in Sadeghian et al. (2019), we we adopt filtered ranking and evaluate models on mean reciprocal rank (MRR) as well as the Hits@$\{1, 3, 10\}$ metrics. We adopt the hyperparameters dimension $m = 80$ and depth $T = 2$ for LERP, and the maximum rule length of $K = 3$. We use 4 rules for WN18RR and WN18 and Family and 200 rules per target relation type for Kinship and UMLS dataset. Our model is trained for 4 epochs for WN18RR and WN18 and 10 epochs for Family, Kinship, and UMLS. As DRUM runs on fewer number of rules by default, we re-run DRUM with larger number of rules to match the configuration of our model and RNNLogic. For optimization, we use Adam with a learning rate of 0.1, $\beta_1 = 0.9$, and $\beta_2 = 0.999$.

The results for are demonstrated in Tables 1 and 2. Compared with other rule learning methods, our model obtains higher performance across the board. This validates the importance of contextual information provided by LERP, especially after considering that this is the only difference in model design between DRUM and our model. Black box models, which do not conduct rule learning, generally achieve higher scores than rule learning methods. This is both because of the strong fitting power of black-box models and because rule learning models also need to explicitly learn logical rules. However, our model achieves performance comparable or even superior to black-box baselines. Even on metrics where LERP's performance falls short of that of state-of-the-art models (like Hits@10 on WN18RR dataset), the difference is marginal. We attribute this to the property of LERP modeling a more expressive set of logical rules, allowing it to achieve data-fitting power similar to black-box neural models.

5.2 INTERPRETABILITY OF LERP AND LOGICAL RULES

An important advantage of logical rules is that they help humans to better comprehend the reasoning process of the algorithm. In this subsection, we provide a case study on the interpretability of LERP and our model on Family dataset.

In Table 3, we sort the logical rules according to their weights, and show the top-ranked logical rules for three relations. We can see that these logical rules are more complex than chain-like Horn clauses as in Equation 1. For example, in the second row, the logical function $\nexists sister(y, z_3)$ provides contextual information that y is not sister of anybody. [2] Therefore, y is more likely to be the brother than sister of x. Similarly, in the fourth row, $\nexists z_3 : sister(z_3, z_1)$ provides information that z_1 has no sister, so x can only be the brother of z_1 and thus the son of y. We can also observe some verbosity in the learned rules, like the logical function $\nexists z_2 : sister(z_2, x)$ in the first row. This is not necessary since $son(y, z_1)$ is enough for predicting that y is the brother of x. But this kind of verbosity is inevitable since rules of the same meaning are equivalent from the model's perspective.

Since LERP is itself an interpretable representation, we can inspect it directly in Table 4. We sort the logical functions L_i^Θ according to the weights, and filter out the repeated functions. Some logical functions are related to the gender information of entities. For example, $\nexists sister(e, z_1)$ might suggest (although with uncertainty) that e is a male. Other logical functions are longer and contain more complex information of entities. For instance, $\exists z_1 : brother(e, z_1) \land \exists z_2 : daughter(z_2, e)$ tells us e is a brother and has a daughter, which might help predict the nephew/aunt-uncle relationship between his sibling and daughter.

---

[2]Note that in the Family dataset ontology, $\{$`relation`$\}(a, b)$ means that a is the $\{$`relation`$\}$ of b (e.g., $son(a, b)$ means a is b's son).

Figure 4: Analysing LERP's performance under different configurations.

We notice that the weights of some interpreted logical functions are not close to 1.0, and the actual utility of some logic functions are not easy to guess merely from the interpreted logic form. To better understand the space of LERP representation, we conduct 3-dimensional principle component analysis (PCA) on LERP vectors of entities in the graph. We select entities with some relational roles such as *being a daughter*, *being a son*, *having a sister*, or *having a brother*, and mark them with red circles in contrast to the blue pluses of the other entities. For better visualization, we also plot the plane dividing them from the rest of entities. The results are shown in Figure 3. We find that the lower-dimensional space of LERP is well organized according to these roles. Note that the role of *having a brother* is not explicitly stated in the learned logical functions in Table 4. We hypothesize that it might come from a combination of other logical functions like $\exists z_1 : brother(e, z_1) \land \exists z_2 : aunt(z_2, e)$ and $\exists z_1 : brother(e, z_1) \land \exists z_2 : daughter(z_2, e)$. This demonstrates that logical functions in LERP can be combined to represent extra logical information.

5.3 MODEL ANALYSIS

In this section, we ask and answer a list of questions by analyzing the behaviors of LERP on Kinship dataset.

Is contextual information from LERP useful? This work is motivated by including contextual information for rule learning. To validate our hypothesis, we vary the depth of LERP from 0 to 4 and observe the performance. This hyper-parameter controls the complexity of logical functions learned in LERP. When depth is 0, our model does not use contextual information from LERP and defaults back to the DRUM baseline. Results are shown in Figure 4(a). We see that even with a depth of 1, LERP boosts our model's accuracy by a large margin compared with the depth of 0. Similar conclusion can also come from the comparison between DRUM and LERP in Table 2 and 1, because DRUM can be viewed as an ablation study counterpart of LERP by removing contextual information from LERP. This comparison verifies that the performance gain is indeed coming from contextual information in LERP.

Is a higher dimension of LERP always better? The answer is no. Similar to embedding-based models like TransE, a larger dimension may cause LERP to overfit the training data and perform worse on the test set. In Figure 4(b), we set the width of LERP to $\{3, 10, 40, 100, 200, 400\}$. We observe a $\cap$-shaped curve with 40 giving optimal test performance.

Does the model benefit from larger number of logical rules? The default number of logical rules can be different across models. For example, RNNLogic uses 100~200 rules per relations, but DRUM only uses 1~4 rules by default. To better analyze the model's performance, we vary the number of rules in our model. We also compare with DRUM. In Figure 4(c), both models' performance increase with larger number of rules, but with diminishing returns (note the logarithmic scale of the x-axis). Our model achieves higher scores even with fewer number of rules. We attribute this to LERP helping to learn higher quality rules.

5.4 AUGMENTING EMBEDDING LEARNING MODELS WITH LERP

LERP is designed to learn an interpretable logical representation for entities in graphs. One question then arises: can LERP work together with other embedding-learning methods such as

logical function	relations	logical function	relations
$\exists z : niece(e, z)$	daughter,niece	$\exists z : aunt(e, z) \vee \exists z : niece(e, z)$	mother
$\not\exists z : niece(e, z)$	father,husband,son	$\exists z : aunt(e, z) \wedge \exists z : niece(e, z)$	
$\not\exists z : uncle(e, z)$	aunt,sister	$\exists z_1, z_2 : mother(z_1, e) \wedge : niece(z_1, z_2)$	brother,nephew

Table 5: The list of logical functions $L_i(e)$ learned when optimizing TransE+LERP. We also project the learned translation vectors l back to the LERP space, and identify their most correlated logical functions.

TransE (Bordes et al., 2013), to combine the logic structure in LERP and strong fitting power of TransE? Inspired by this idea, we design a hybrid model TransE+LERP. We use the training framework and training criterion on TransE, but the entities' embeddings are now defined as $Embed'(e) = Embed(e) + R\boldsymbol{L}^{\boldsymbol{\Theta}}(e)$. $Embed(e)$ is set as a 20-dimensional entity-specific embedding. We also set the width and depth of LERP to be 8 and 2. R is a 20×8 matrix to transform LERP to the embedding space. Besides the loss in original TransE framework, we add a regularization term $\eta \frac{\sum_e \|Embed(e)\|_2}{\sum_e \|R\boldsymbol{L}^{\boldsymbol{\Theta}}(e)\|_2}$ to encourage LERP to encode important information during optimization. We also introduce an advanced version TransE+LERP+entropy by adding an extra entropy regularization term $\gamma H(\Theta)$ on LERP's weights. This term is added to loss and encourage LERP to assign more weights to fewer logical rules. In experiments, we set $\eta = 10$ and $\gamma = 1$.

We evaluate the models on Family dataset and results are presented in Figure 5. The vanilla TransE model tends to overfit the training set (>95% training set accuracy) because Family dataset contains a limited number of training triplets. TransE+LERP achieves higher test set performance. We hypothesize that LERP provides logical regularization on the embedding $Embed'(e)$ and makes it more generalizable. After adding the entropy regularization term, the performance further improves. We attribute this to that the regulation encourages learning more explicit logical functions, which serves as a prior in embedding learning.

Figure 5: Incorporating LERP representation improves TransE's performance on Family dataset.

We also study the interpretability of the hybrid model. In Table 5 we list the logical functions that are learned by TransE+LERP. There are 2 repetitions in logical functions which are removed. We also manage to identify the correlation between relations in TransE and logical functions. In TransE, each relationship has a vector l to denote a translation in the embedding space. l resides in the embedding space, and we want to find a vector l' in LERP space so that $Rl' \approx l$. As R is not square matrix, we use R's Moore–Penrose inverse R^+ to project the translation vectors to R^+l. We then look for dimensions with highest values in R^+l, and results are listed in the 2nd and 4nd columns in Table 5. We can observe that these functions encode rich information. For example, relations like *daughter* and niece are associated with $\exists z : niece(e, z)$ which suggests a female gender and lower rank in the family tree.

6 CONCLUSIONS AND FUTURE WORK

In this work, we propose a logical entity representation (LERP) and demonstrate that we can incorporate contextual information of local subgraphs to probabilistic logical rule learning. Therefore we are able to learn a more expressive family of logical rules in a fully differentiable manner. In experiments on graph completion benchmarks, our model outperforms rule learning baselines and competes with or even exceeds state-of-the-art black box models. LERP is itself an interpretable representation of entities. We also find that LERP can be combined with latent embedding learning methods to learn interpretable embeddings. For future work, we expect that LERP can be combined with a wider range of neural networks to provide logical constraints and learn interpretable embeddings.

Reproducibility Statement   The datasets, split and the configuration of the model are introduced in Section 5.1. The statistics of the datasets used are also included in Appendix D. We also conduct analysis of the model behavior in Section 5.3. In the additional experiments of combining TransE and LERP, we provide details of implementation in Section 5.4, including the hyper-parameters and rationale for some technical decisions. For Theorem 1, we provide proof in Appendix A.

REFERENCES

Ivana Balažević, Carl Allen, and Timothy Hospedales. Tucker: Tensor factorization for knowledge graph completion. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5185–5194, 2019.

Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. volume 26, 2013.

Liwei Cai and William Yang Wang. Kbgan: Adversarial learning for knowledge graph embeddings. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1470–1480, 2018.

Andres Campero, Aldo Pareja, Tim Klinger, Josh Tenenbaum, and Sebastian Riedel. Logical rule induction and theory learning using neural theorem proving. *arXiv preprint arXiv:1809.02193*, 2018.

Wenhu Chen, Wenhan Xiong, Xifeng Yan, and William Yang Wang. Variational knowledge graph reasoning. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1823–1832, 2018.

Yang Chen, Sean Goldberg, Daisy Zhe Wang, and Soumitra Siddharth Johri. Ontological pathfinding: Mining first-order knowledge from large knowledge bases. In *Proceedings of the 2016 International Conference on Management of Data*, pp. 835–846, 2016.

Louis Clouatre, Philippe Trempe, Amal Zouaq, and Sarath Chandar. Mlmlm: Link prediction with mean likelihood masked language model. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 4321–4331, 2021.

Rajarshi Das, Shehzaad Dhuliawala, Manzil Zaheer, Luke Vilnis, Ishan Durugkar, Akshay Krishnamurthy, Alex Smola, and Andrew McCallum. Go for a walk and arrive at the answer: Reasoning over paths in knowledge bases using reinforcement learning. In *International Conference on Learning Representations*, 2018.

Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Luis Antonio Galárraga, Christina Teflioudi, Katja Hose, and Fabian Suchanek. Amie: association rule mining under incomplete evidence in ontological knowledge bases. In *Proceedings of the 22nd international conference on World Wide Web*, pp. 413–422, 2013.

Haipeng Gao, Kun Yang, Yuxue Yang, Rufai Yusuf Zakari, Jim Wilson Owusu, and Ke Qin. Quatde: Dynamic quaternion embedding for knowledge graph completion. *arXiv preprint arXiv:2105.09002*, 2021.

Tushar Khot, Sriraam Natarajan, Kristian Kersting, and Jude Shavlik. Learning markov logic networks via functional gradient boosting. In *2011 IEEE 11th international conference on data mining*, pp. 320–329. IEEE, 2011.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

Stanley Kok and Pedro Domingos. Statistical predicate invention. In *Proceedings of the 24th international conference on Machine learning*, pp. 433–440, 2007.

Ni Lao and William W Cohen. Relational retrieval using a combination of path-constrained random walks. *Machine learning*, 81(1):53–67, 2010.

Ni Lao, Tom Mitchell, and William Cohen. Random walk inference and learning in a large scale knowledge base. In *Proceedings of the 2011 conference on empirical methods in natural language processing*, pp. 529–539, 2011.

Manling Li, Sha Li, Zhenhailong Wang, Lifu Huang, Kyunghyun Cho, Heng Ji, Jiawei Han, and Clare Voss. Future is not one-dimensional: Graph modeling based complex event schema induction for event prediction. *Proc. The 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP2021)*, 2021.

Qika Lin, Jun Liu, Fangzhi Xu, Yudai Pan, Yifan Zhu, Lingling Zhang, and Tianzhe Zhao. Incorporating context graph with logical reasoning for inductive relation prediction. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 893–903, 2022.

Xi Victoria Lin, Richard Socher, and Caiming Xiong. Multi-hop knowledge graph reasoning with reward shaping. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3243–3253, 2018.

Sijie Mai, Shuangjia Zheng, Yuedong Yang, and Haifeng Hu. Communicative message passing for inductive relation reasoning. In *AAAI*, pp. 4294–4302, 2021.

Christian Meilicke, Melisachew Wudage Chekol, Daniel Ruffinelli, and Heiner Stuckenschmidt. Anytime bottom-up rule learning for knowledge graph completion. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*, pp. 3137–3143, 2019.

Sriraam Natarajan, Tushar Khot, Kristian Kersting, Bernd Gutmann, and Jude Shavlik. Boosting relational dependency networks. In *Online Proceedings of the International Conference on Inductive Logic Programming 2010*, pp. 1–8, 2010.

Jennifer Neville and David Jensen. Relational dependency networks. *Journal of Machine Learning Research*, 8(3), 2007.

Maximilian Nickel, Lorenzo Rosasco, and Tomaso Poggio. Holographic embeddings of knowledge graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

Pouya Ghiasnezhad Omran, Kewen Wang, and Zhe Wang. Scalable rule learning via learning representation. In *IJCAI*, pp. 2149–2155, 2018.

Ali Payani and Faramarz Fekri. Inductive logic programming via differentiable deep neural logic networks. *arXiv preprint arXiv:1906.03523*, 2019.

Jian Pei, Jiawei Han, Behzad Mortazavi-Asl, Helen Pinto, Qiming Chen, Umeshwar Dayal, and Meichun Hsu. Prefixspan: Mining sequential patterns by prefix-projected growth. In *Proceedings of the 17th International Conference on Data Engineering*, pp. 215–224, 2001.

Yanhui Peng and Jing Zhang. Lineare: Simple but powerful knowledge graph embedding for link prediction. In *2020 IEEE International Conference on Data Mining (ICDM)*, pp. 422–431. IEEE, 2020.

Meng Qu, Junkun Chen, Louis-Pascal Xhonneux, Yoshua Bengio, and Jian Tang. Rnnlogic: Learning logic rules for reasoning on knowledge graphs. In *International Conference on Learning Representations*, 2020.

Matthew Richardson and Pedro Domingos. Markov logic networks. *Machine learning*, 62(1):107–136, 2006.

Rachel Rudinger, Pushpendre Rastogi, Francis Ferraro, and Benjamin Van Durme. Script induction as language modeling. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 1681–1686, 2015.

Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. Drum: End-to-end differentiable rule mining on knowledge graphs. *Advances in Neural Information Processing Systems*, 32, 2019.

Yelong Shen, Jianshu Chen, Po-Sen Huang, Yuqing Guo, and Jianfeng Gao. M-walk: Learning to walk over graphs using monte carlo tree search. *Advances in Neural Information Processing Systems*, 31, 2018.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*, 2018.

Komal Teru, Etienne Denis, and Will Hamilton. Inductive relation prediction by subgraph reasoning. In *International Conference on Machine Learning*, pp. 9448–9457. PMLR, 2020.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International conference on machine learning*, pp. 2071–2080. PMLR, 2016.

William Yang Wang, Kathryn Mazaitis, and William W Cohen. Programming with personalized pagerank: a locally groundable first-order probabilistic logic. In *Proceedings of the 22nd ACM international conference on Information & Knowledge Management*, pp. 2129–2138, 2013.

William Yang Wang, Kathryn Mazaitis, and William W Cohen. Proppr: Efficient first-order probabilistic logic programming for structure discovery, parameter learning, and scalable inference. In *Workshops at the Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014a.

Zhen Wang, Jianwen Zhang, Jianlin Feng, and Zheng Chen. Knowledge graph embedding by translating on hyperplanes. In *Proceedings of the AAAI conference on artificial intelligence*, volume 28, 2014b.

Wenhan Xiong, Thien Hoang, and William Yang Wang. Deeppath: A reinforcement learning method for knowledge graph reasoning. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 564–573, 2017.

Bishan Yang, Scott Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2015.

Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. *Advances in neural information processing systems*, 30, 2017.

Ningyu Zhang, Xin Xie, Xiang Chen, Shumin Deng, Chuanqi Tan, Fei Huang, Xu Cheng, and Huajun Chen. Reasoning through memorization: Nearest neighbor knowledge graph embeddings. *arXiv preprint arXiv:2201.05575*, 2022.

Yuyu Zhang, Xinshi Chen, Yuan Yang, Arun Ramamurthy, Bo Li, Yuan Qi, and Le Song. Efficient probabilistic logic reasoning with graph neural networks. In *International Conference on Learning Representations*, 2019.

A PROOF OF THEOREM 1

More specifically, we will prove that when $C = K(1 + D)$, where K is the length of the rule in Equation 2 and D is the maximum number of used operations in Definition 1 for constructing each $L_{i_{z'}}$, the computation time for evaluating x and any $y \in \mathcal{E}$ can be bounded by $O(Cn^2)$ where $n = |\mathcal{E}|$. This is an asymptotically tight bound, because reading all the edge information naturally requires a lower bound of $\Omega(\min(C, |\mathcal{R}|)n^2)$ time.

First it is easy to see that all tree-like functions only have one free variable. We will bound the computation time of evaluating tree-like functions $f(e) \in \mathcal{T}$ over all entities in $\mathcal{E}$. Let $\mathbf{v}(f)$ be the vector of scores of f on $\mathcal{E}$, and $d(f)$ be the number of operations used for constructing f, we recursively prove that $\mathbf{v}(f)$ can be calculated in $O(d(f)n^2)$ time. First for an all true function $d(f) = 1$, $\mathbf{v}(f)$ contains only 1 can be directly written in $O(n)$ time. For a negation operator $f = \neg f'$, $\mathbf{v}(f)$ only needs negating $\mathbf{v}(f')$ and takes $O((d(f) - 1)n^2) + n \leq O(d(f)n^2)$ time. Similarly for a merging operation $f = f_1 \wedge f_2$, $\mathbf{v}(f)$ can be derived by processing elements of $\mathbf{v}(f_1)$ and $\mathbf{v}(f_2)$ sequentially and needs $O((d(f) - 1)n^2) + 2n \leq O(d(f)n^2)$ time. Finally for a f constructed by chaining f' and relation r, $\mathbf{v}(f)$ is just $\mathbf{v}(f')^\top \boldsymbol{A}_r$ in binary field and takes $O((d(f) - 1)n^2) + n^2 \leq O(d(f)n^2)$ time.

So getting result vectors for all tree-like logical functions takes no more than $O(KDn^2)$ time. We then plus the time for evaluating the main body in Equation 2. we start from a one-hot vector $\mathbf{v} = \mathbf{v}_x$. After chaining each relation r_k, the partial evaluation of the logical rule $r_1(x, z_1) \wedge r_2(z_1, z_2) \wedge \cdots \wedge r_k(z_{k-1}, y) \wedge \left(\bigwedge_{z' \in \{x, z_1, \cdots, z_{k-1}\}} L_{i_{z'}}(z') \right)$ can be computed by $\mathbf{v}\top \leftarrow \mathbf{v}\top \boldsymbol{A}_{r_k}$. Applying the new constraint $L_{i_{z_k}}(z_k)$ is another element-wise logical and between $\mathbf{v}$ and $\mathbf{v}(L_{i_{z_k}})$ which takes $O(n)$ time. Summing together, the total time for evaluating the whole rule can be bounded by $O(KDn^2 + Kn + Kn^2) \leq O(K(1 + D)n^2)$.

B EVENT PREDICTION

Dataset	Model	MRR	HITS@1
General	Event Language Model (Rudinger et al., 2015)	0.367	0.497
	Sequential Pattern Mining (Pei et al., 2001)	0.330	0.478
	Human Schema (Li et al., 2021)	0.173	0.205
	Event Graph Model (Li et al., 2021)	**0.401**	0.520
	LERP	0.347	**.672**
IED	Event Language Model (Rudinger et al., 2015)	0.169	0.513
	Sequential Pattern Mining (Pei et al., 2001)	0.138	0.378
	Human Schema (Li et al., 2021)	0.072	0.222
	Event Graph Model (Li et al., 2021)	0.223	0.691
	LERP	**0.242**	**0.978**

Table 6: Experiment results on ending event prediction.

Dataset	Split	#doc	#graph	#event	#arg	#rel
General	**Train**	451	451	6,040	10,720	6,858
	Dev	83	83	1,044	1,762	1,112
	Test	83	83	1,211	2,112	1,363
IED	**Train**	5,247	343	41,672	136,894	122,846
	Dev	575	42	4,661	15,404	13,320
	Test	577	45	5,089	16,721	14,054

Table 7: Dataset statistics for event prediction datasets (Li et al., 2021).

One driving force for humans to understand logic is to interpret the past and predict the future. Going beyond instincts, logic provides humans with the ability of explainable and reasoning-based prediction. In this section, we evaluate LERP's ability on an ending-event prediction task. This task is different from the link completion task of Subsection 5.1. The goal is to deduce the existence of future events given an input event graph, typically produced by human annotation or information extraction from news or stories.

Benchmark Datasets We conduct experiments on the graph-based event prediction datasets from Li et al. (2021), including a general scenario (General Schema Learning Corpus) and a more specific bombing scenario (IED Schema Learning Corpus). More specifically, the General Schema Learning Corpus is released by Linguistic Data Consortium (LDC2020E25) – including 82 types of events, such as Disease Outbreak and Shop Online. The original improvised explosive device (IED) dataset was collected by Li et al. (2021). They conduct a two-round annotation process with linguists to ensure quality of the annotated schemas/graphs. The dataset statistics can be found in Table 7.

Evaluation Metrics and Training Objective Following prior work (Li et al., 2021), we adopt MRR (Mean Reciprocal Rank) and HITS@1 as evaluation metrics. An event is predicted correctly if the event type matches one of the ending event types in the gold-standard event graph. Considering that there can be multiple ending events in one instance graph, we rank event types with their prediction scores. The model adopts multiple output heads, and uses categorical cross entropy for training objective.

Baselines Event Language Model (Rudinger et al., 2015) learns the probability of temporal event sequences, and obtain the event sequences prediction from language model. Sequential Pattern Mining (Pei et al., 2001) is a classic method that explores prefix-projection in sequential pattern mining. The most frequent mined patterns/event graphs are used for predicting the ending event. Event Graph Model (Li et al., 2021) is the state-of-the-art model on the ending event prediction task. It proposes a temporal event graph model that predicts the future event type given the current (incomplete) event graph. Finally, we also add human schema as a reference (Li et al., 2021). We match expert-created event schemas to test data graphs and fill in the matched ending event type.

Results and Analysis In Table 6, we present the results on these two datasets. We find that all of the learning-based methods outperform pattern mining-based method (Pei et al., 2001) on both datasets. Our model further outperforms the baselines on most evaluation categories including the Event Graph Model on HITS@1. We attribute the inferior performance of the human schema matching baseline to that real event graphs are highly variational, so fixed schemas do not generalize well to the test graphs.

C LOGICAL EVENT EQUATION INDUCTION

Figure 6: Induced event relation examples from IED (Li et al., 2021).

One important feature of LERP is its ability to learn explainable first-order logical formulae. In this section, we train the model to induce logical relations among events. Specifically, we use IED dataset (Li et al., 2021) for training. Specifically, we adopted contrastive training to encourage LERP to distinguish positive (real) and negative (incomplete) event graphs. The training dataset is used directly as the positive graph. We randomly sample an event graph instance, and randomly remove 30 event nodes to build a negative graph. The negative graph is then upsampled to match the number of all positive graphs. The training objective of LERP is the contrastive loss between positive and negative graphs.

Induced examples are shown in Figure 6. We rank and filter the induced logical equations by the model confidence, and let human annotators to assess the quality of induced equations. As model are able to induce logical formulae in arbitrary form, we provide a visual illustration for each logic

	Family	UMLS	Kinship
#Triplets	28356	5960	9587
#Relations	12	46	25
#Entities	3007	135	104

	#Relation	#Entity	#Train	#Valid	#Test
WN18	18	40,943	141,442	5,000	5,000
WN18RR	11	40,943	86,835	3,034	3,134

Table 8: Dataset statistics for statistical relation learning (Sadeghian et al., 2019) tasks.

Table 9: Dataset statistics for knowledge graphs. WN18RR is a more challenging version of WN18 by filtering out some data bias.

formula, so as to unify the form and provide easier human interpretation. These induced equations demonstrate LERP's ability of learning complex relations from data, which are highlt scored by humans.

D DATASET STATISTICS

We also list the dataset statistics in Table 9. Family, UMLS and Kinship are smaller scale datasets. WN18 and WN18RR contains a larger number of entities and relations.