LiNo: Advancing Recursive Residual Decomposition of Linear and Nonlinear Patterns for Robust Time Series Forecasting

Abstract

Forecasting models are pivotal in a data-driven world with vast volumes of time series data that appear as a compound of vast **Li**near and **No**nlinear patterns. Recent deep time series forecasting models struggle to utilize seasonal and trend decomposition to separate the entangled components. Such a strategy only explicitly extracts simple linear patterns like trends, leaving the other linear modes and vast unexplored nonlinear patterns to the residual. Their flawed linear and nonlinear feature extraction models and shallow-level decomposition limit their adaptation to the diverse patterns present in real-world scenarios. Given this, we innovate Recursive Residual Decomposition by introducing explicit extraction of both linear and nonlinear patterns. This deeper-level decomposition framework, which is named **LiNo**, captures linear patterns using a Li block which can be a moving average kernel, and models nonlinear patterns using a No block which can be a Transformer encoder. The extraction of these two patterns is performed alternatively and recursively. To achieve the full potential of LiNo, we develop the current simple linear pattern extractor to a general learnable autoregressive model, and design a novel No block that can handle all essential nonlinear patterns. Remarkably, the proposed LiNo achieves state-of-the-art on thirteen real-world benchmarks under univariate and multivariate forecasting scenarios. Experiments show that current forecasting models can deliver more robust and precise results through this advanced Recursive Residual Decomposition. We hope this work could offer insight into designing more effective forecasting models. Code is available at this anonymous repository: `https://anonymous.4open.science/r/LiNo-8225/`.

1 Introduction

Time series forecasting (TSF) is a long-established task (Lim & Zohren, 2021; Wang et al., 2024b), with a wide range of applications (Zhou et al., 2022a; Liu et al., 2022a; Piao et al., 2024). Notably, numerous deep learning methods have been employed to address the TSF problem, utilizing architectures such as Recurrent Neural Networks (RNNs) (Elman, 1990; Lin et al., 2023), Temporal Convolutional Networks (TCNs) (Donghao & Xue, 2024; Wu et al., 2023), Multilayer Perceptron (MLP) (Liu et al., 2023; Challu et al., 2023) and Transformers (Liu et al., 2022b; Kitaev et al., 2020). Recent advancements in the time series forecasting community have suggested that seasonal (nonlinear) and trend (linear) decomposition can enhance forecasting performance (Zhang et al., 2022b; Wu et al., 2021). This is typically performed once, with the trend component being extracted using methods such as the simple moving average kernel (MOV) (Zhou et al., 2022b; Wang et al., 2023), the exponential smoothing function (ESF) (Woo et al., 2022), or a learnable 1D convolution kernel (LD) (Yu et al., 2024). The seasonal component is then obtained by subtracting the trend part from the original time series.

Real-world time series data often exhibit more complex structures, combining multiple levels of linear and nonlinear characteristics (Stock & Watson, 1998; Dama & Sinoquet, 2021; Agrawal & Adhikari, 2013), as illustrated in Figure 1. Simple seasonal and trend decomposition faces three main challenges when deployed in real-world time series data. Firstly, these methods rely on simple techniques (MOV, LD, ESF). MOV and LD employed a fixed window size, which cannot fully extract all linear patterns, while the non-learnability of ESF limits its performance. They can only extract simple linear features

Figure 1: Example of the multi-level linear and nonlinear patterns in real-world time series. We take the ETTh2 dataset as an example and decompose a raw time series (**Raw**) into four signals through linear and nonlinear patterns decomposition. Linear 1&2 is the obtained linear patterns using the proposed Li block, and Nonlinear 1&2 is the obtained nonlinear patterns using No block.

such as trends, while other linear features like cyclic patterns and autoregression (Chatfield & Xing, 2019) remain underutilized. Secondly, we argue the obtained seasonal part is actually a residual consisting of all the unextracted linear and nonlinear information. Without further separating the nonlinear part from the residual severely hinders its extraction. Since it's extremely challenging for deep models to extract useful information from such mixtures (Bengio et al., 2013; Tishby & Zaslavsky, 2015). Another problem is the design of current nonlinear models, which mainly focus on one or two types of nonlinear patterns (temporal variations, frequency information, inter-series dependencies, etc). Such designs cannot satisfy our requirements in the real world. Thirdly, their shallow-level decomposition is incompatible with the multi-level characteristics of real-world time series. In contrast, numerous studies have shown that deeper-level decomposition can lead to better time series analysis (Huang et al., 1998; Rilling et al., 2003). Therefore, it is crucial to develop advanced decomposition methods capable of multi-granularity separation of various modes, and better linear and nonlinear pattern extractors to provide a more nuanced understanding of the signal's structure and potentially improve forecasting performance.

To address the challenges above, we propose adopting Recursive Residual Decomposition (RRD), a method used in Empirical Mode Decomposition (EMD) (Huang et al., 1998; Rilling et al., 2003), to decompose a time series into multiple patterns. This process is performed recursively. Each pattern is extracted based on the residual obtained by subtracting previously extracted patterns from the original signal, utilizing Intrinsic Mode Functions (IMF) to identify similar characteristics. Specifically, We can employ a Li block (MOV, LD, ESF, etc.) as the IMF for extracting linear patterns and a No block (Transformer, RNN, etc.) as the IMF for extracting nonlinear patterns. Then, the RRD is performed on a deeper level. We denote the proposed overall framework as **LiNo**. To fully realize RRD's potential, we propose an advanced **LiNo**, Specifically, we enhance the Li block to a general learnable autoregressive model with a full receptive field and propose a novel No block capable of modeling essential nonlinear features, such as temporal variations, period information, and inter-series dependencies in multivariate forecasting.

In summary, our contributions can be delineated as follows.

- We advance current shallow linear and nonlinear decomposition by innovating Recursive Residual Decomposition.

- Proposed No block demonstrates better nonlinear pattern extraction ability than current SOTA nonlinear models, such as iTransformer and TSMixer.

- LiNo consistently delivers top-tier performance in multivariate and univariate forecasting scenarios, demonstrating robust resilience against noise disturbances.

- The significant improvement by more nuanced and deeper linear and nonlinear decomposition provides insight for designing more effective and robust forecasting models.

2 RELATED WORK

Advancement in recent time series forecasting. Time series forecasting is a critical area of research that finds applications in both industry and academia. With the powerful representation capability of neural networks, deep forecasting models have undergone a rapid development (Wang et al., 2024b; Lim & Zohren, 2021; Torres et al., 2021). Recent research endeavors have focused on segmenting the sequence into a series of patches (Nie et al., 2023; Zhang & Yan, 2023), better modeling the relationships between variables (Ng et al., 2022; Chen et al., 2024), the dynamic changes within a sequence (Wu et al., 2023; Du et al., 2023), or both (Yu et al., 2024; Liu et al., 2024a). Some works strive for more efficient forecasting solutions (Lin et al., 2024; Xu et al., 2024). Other efforts aim to revitalize existing architectures, such as RNN (Lin et al., 2023), Transformer (Liu et al., 2024b), TCN (Donghao & Xue, 2024), with new ideas, or to explore the potential of outstanding architectures from other domains, such as MLP-Mixer (Chen et al., 2023; Wang et al., 2024a), Mamba (Ahamed & Cheng, 2024; Wang et al., 2024c), Graph Neural Network (Yi et al., 2023; Shao et al., 2022), even Large Language Models (Jin et al., 2024; Liu et al., 2024c; Pan et al., 2024; Bian et al., 2024; Gruver et al., 2024), for application in time series forecasting. Notably, some efforts also begin to ponder the role of self-attention in time series forecasting (Ilbert et al., 2024).

Importance of linear and nonlinear patterns. Deep time series models that are dedicated to model nonlinear patterns such as non-stationarity (Liu et al., 2022c), time-variant and time-invariant features (Liu et al., 2023), and frequency bias (Piao et al., 2024) have delivered outstanding performance in various domains. In contrast, recent advances have proved the importance of attention to linear patterns in time series (Toner & Darlow, 2024). For instance, DLinear (Zeng et al., 2023) and RLinear (Li et al., 2023a) achieve results comparable to, or even surpassing, many intricately designed nonlinear models in certain scenarios, using only simple linear layers. FITS (Xu et al., 2024) even achieves SOTA performance with merely $10k$ parameters. This suggests that balanced consideration of both linear and nonlinear patterns can be crucial for enhancing predictive performance in time series forecasting, which is unexplored in the current simple seasonal and trend decomposition.

Decomposition based on Residual. **Autoformer** (Wu et al., 2021) first explored a rudimentary seasonal (**Nonlinear**) and trend (**Linear**) decomposition based on residual. The trend part is extracted using linear models like a moving average kernel, and the seasonal part is the residual of subtracting the input feature using the trend part. The earlier and more pioneering residual-based decomposition in deep learning time series was explored in **N-BEATS** (Oreshkin et al., 2020). N-BEATS is built using stacked residual blocks, where each block refines the forecast by predicting based on the residual errors of previous predictions. Instead of directly modeling the time series components (e.g., trend or seasonality), the model iteratively adjusts the residuals at each step.

Our LiNo develops the decomposition strategy in Autoformer by explicitly capturing both seasonal (**Nonlinear**) and trend (**Linear**) components and performing at a deeper level. Though LiNo and N-BEATS share some similarities, such as both employing the concept of Recursive Residual Decomposition (RRD), they are fundamentally different. First, N-BEATS does not explicitly capture linear and nonlinear separately. Second, as a univariate model, N-BEATS cannot handle more complex multivariate time series. Third, the role of RRD differs in each model: while N-BEATS uses RRD to refine the final prediction based on residual errors from previous predictions, LiNo employs RRD to capture more nuanced linear and nonlinear patterns. To empirically compare their differences, we designed a model based on the N-BEATS framework, where the internal components are identical to those of the proposed LiNo. In the subsequent experiments, we will denote this model as **Mu**. A more detailed comparison of LiNo and N-BEATS is left in Appendix F.

3 METHODOLOGY

3.1 PRELIMINARY

Given a multivariate time series $X \in \mathbb{R}^{C \times T}$ with a length of T time steps, time series forecasting tasks are designed to predict its future F time steps $\hat{Y} \in \mathbb{R}^{C \times F}$, where C is the number of variate or channel ($C = 1$ in univariate case), and T represents the look-back window. We aim to make $\hat{Y}$ close to the ground truth $Y \in \mathbb{R}^{C \times F}$.

Figure 2: Framework of LiNo. Li block and No block extract patterns from the embedded input alternatively, in an RRD manner. The final prediction is aggregated from all blocks.

Without loss of generality and to simplify the analysis, we assume a real-world univariate time series X consisting of S linear patterns, S nonlinear patterns, and a white noise ε. We denote $X = L_1 + N_1 + \cdots + L_S + N_S + \varepsilon$, where L_i is a **L**inear signal, N_i is a **No**nlinear signal. During the 'Recursive Residual Decomposition' (RRD) process of LiNo, if we denote the extracted linear and nonlinear patterns using different IMFs (such as MOV, LD, ESF for linear, Transformer, MLP-Mixer for nonlinear) at each time as $\hat{L}_i$ and $\hat{N}_i$, we have

$$R_1^L = X - \hat{L}_1, \;\; R_1^N = R_1^L - \hat{N}_1,$$
$$\cdots \tag{1}$$
$$R_S^L = R_{S-1}^N - \hat{L}_S, \;\; R_S^N = R_S^L - \hat{N}_S.$$

where $\lim_{i \to \infty} R_i^N = 0$. The modeling error will be $\delta = X - (\hat{L}_1 + \hat{N}_1 + \cdots + \hat{L}_n + \hat{N}_n) = (L_1 - \hat{L}_1) + (N_1 - \hat{N}_1) + (L_2 - \hat{L}_2) + (N_2 - \hat{N}_2) + \cdots + (L_S - \hat{L}_S) + (N_S - \hat{N}_S) + \varepsilon$. By alternating the extraction of linear and nonlinear features with subtracting the extracted features from the original input representation, we ensure previously extracted features do not affect the extraction of subsequent features, guaranteeing the independence of the resulting linear and nonlinear patterns. Moreover, $\lim_{i \to \infty} R_i^N = 0$ ensures that all valuable information in the sequence is fully extracted if the decomposition level is deep enough, preventing any loss of information. This design takes the existing shallow RRD to a deeper level, introducing the extraction of nonlinear patterns. Such a refined design ensures the model achieves more robust forecasting results. Notably, if set the RRD level to 1, then we get $Trend = IMF(X) = \hat{L}_1$, and $Seasonal = X - Trend = R_1^L$, where IMF can be MOV, LD, or ESF, which is equivalent to the former seasonal and trend decomposition.

3.2 LiNo Pipeline

The structure of the LiNo framework is illustrated in Figure 2 (Middle). Initially, we extract the whole series embedding, which is then processed through N LiNo blocks to forecast future values of the time series. In this subsection, we will explain the whole series embedding, Li block, and No block, step by step.

Whole series embedding. Following iTransformer (Liu et al., 2024b), we first map time series data $X \in \mathbb{R}^{C \times T}$ from the original space to a new space to get $X_{embed} \in \mathbb{R}^{C \times D}$ using a simple linear projection, where D denotes the dimension of the layer. Such a design can better preserve the unique patterns of each variate.

Li block. The fixed window size of the MOV and learnable 1D convolution kernel (LD), and the non-learnability of the exponential smoothing function (ESF), prevent them from fully extracting all linear patterns. So we introduce a learnable autoregressive model (AR) with a full receptive field to replace them, where MOV, LD, and ESF are its subsets.

The structure of Li Block is shown in Figure 2 (right). Given its input feature $H_i \in \mathbb{R}^{C \times D}$ where $H_0 = X_{embed}$, we get i-th linear pattern $L_i \in \mathbb{R}^{C \times D}$ by:

$$\hat{L}_i[c,d] = \phi_i[c,1] * H_i[c,1] + \phi_i[c,2] * H_i[c,2]$$
$$+ \cdots + \phi_i[c,d] * H_i[c,d] + \beta_i[c], \qquad (2)$$
$$L_i = \textbf{Dropout}(\hat{L}_i).$$

Here, $\phi_i \in \mathbb{R}^{C \times D}$ represents the autoregressive coefficients, $\beta_i \in \mathbb{R}^C$ denotes bias term. The whole process of extracting the linear part of the input feature can be easily deployed in a convolution fashion by setting the weight of the convolution kernel to ϕ_i, and the weight of bias to β_i. Before applying the convolution (AR model), we pad the input feature $\mathbf{H}_i$ before convolution to make sure H_i and L_i have the same scale. The padded input feature $\hat{H}_i$ becomes,

$$\hat{H}_i[:,t] = \begin{cases} H_i[:,t-D], & \text{for } t \geq D \\ 0, & \text{for } t < D \end{cases}. \qquad (3)$$

We perform convolutions on each channel independently across the last dimension of $\hat{H}_i$. Following this, we apply dropout for generalization. The linear prediction $P_i^{li} \in \mathbb{R}^{C \times F}$ for this level is obtained by mapping the extracted linear component L_i. Subsequently, we pass $R_i^L = H_i - L_i$ to the next stage for nonlinear pattern modeling.

No block.   Typical nonlinear time series characteristics include temporal variations, frequency information, inter-series dependencies, etc. While all of these factors are crucial for precise forecasting, current nonlinear models can only address one (Wu et al., 2023; Nie et al., 2023; Zhang et al., 2022a; Piao et al., 2024) or two (Liu et al., 2024b; Li et al., 2023b; Chen et al., 2023) of these aspects. Therefore, we designed a No block that simultaneously handles all these characteristics.

As in Figure 2 (left), given a feature $R_i^L \in \mathbb{R}^{C \times D}$, both temporal variation patterns and frequency information are accessible through linear projection. Hence, we start by applying a linear projection in the time domain to obtain temporal variation patterns $N_i^T \in \mathbb{R}^{C \times D}$ in a classical manner. Correspondingly, we apply a linear projection in the frequency domain, which is transformed from R_i^L using the Fast Fourier Transform (FFT), following FITS (Xu et al., 2024). After that, the frequency domain representation is converted back, using the Inverse Fast Fourier Transform (IFFT) to obtain frequency information patterns $N_i^F \in \mathbb{R}^{C \times D}$. To leverage the complementary strengths of both domains, features extracted from both the time and frequency domains are fused and activated by: $N_i^{TF} = \textbf{Tanh}(N_i^T + N_i^F)$.

To model inter-series dependencies, we first normalize N_i^{TF} across the channel dimension using a softmax function, as in Figure 2 (upper left). We then compute a weighted mean by multiplying the softmax weights with N_i^{TF} and summing over the channel dimension. This weighted mean is repeated to match and concatenate with N_i^{TF}. The concatenated result is passed through an MLP to obtain inter-series dependencies information N_i^C.

To integrate temporal variations, frequency information, and inter-series dependencies, we first apply Layer Normalization to the sum of N_i^{TF} and N_i^C, resulting in N_i^{TFC}. A subsequent MLP is applied, and the result is added back to N_i^{TFC}, followed by a final Layer Normalization to produce the overall nonlinear pattern N_i. The nonlinear prediction $P_i^{no} \in \mathbb{R}^{C \times F}$ for this level is then obtained by mapping the extracted nonlinear part N_i. Finally, $R_i^N = R_i^L - N_i$ is passed to the next LiNo block, where $H_{i+1} = R_i^N$.

RevIN and forecasting results.   We used RevIN (Kim et al., 2022) to counter the distribution problem following iTransformer(Liu et al., 2024b). The input first performs an Instance Normalization (Ulyanov, 2016) before being embedded. The final output is reversed using the Mean and Standard Deviation of Instance Normalization. The final prediction result is aggregated from multi-level by:

$$\hat{Y} = \sum_{i=1}^{N}(P_i^{li}) + \sum_{i=1}^{N}(P_i^{no}). \qquad (4)$$

Table 1: Multivariate forecasting results with prediction lengths $F \in \{12, 24, 36, 48\}$ for PEMS dataset while $F \in \{96, 192, 336, 720\}$ for others with fixed lookback window $T = 96$. Results are averaged from all prediction lengths. *Avg* means further averaged by subsets. Full result is left in Appendix E.1 due to space limit.

Models	LiNo (Ours)		iTransformer (2024b)		RLinear (2023a)		PatchTST (2023)		TSMixer (2023)		Crossformer (2023)		TiDE (2023)		TimesNet (2023)		DLinear (2023)		FEDformer (2022b)		Autoformer (2021)	
Metric	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETT (Avg)	0.368	0.387	0.383	0.399	0.380	0.392	0.381	0.397	0.388	0.402	0.685	0.578	0.482	0.470	0.391	0.404	0.442	0.444	0.408	0.428	0.465	0.459
ECL	0.164	0.260	0.178	0.270	0.219	0.298	0.205	0.290	0.186	0.287	0.244	0.334	0.251	0.344	0.192	0.295	0.212	0.300	0.214	0.327	0.227	0.338
Exchange	0.350	0.398	0.360	0.403	0.378	0.417	0.367	0.404	0.376	0.414	0.940	0.707	0.370	0.413	0.416	0.443	0.354	0.414	0.519	0.429	0.613	0.539
Traffic	0.465	0.296	0.428	0.282	0.626	0.378	0.481	0.304	0.522	0.357	0.550	0.304	0.760	0.473	0.620	0.336	0.625	0.383	0.610	0.376	0.628	0.379
Weather	0.241	0.270	0.258	0.279	0.272	0.291	0.259	0.281	0.256	0.279	0.259	0.315	0.271	0.320	0.259	0.287	0.265	0.317	0.309	0.360	0.338	0.382
Solar-Energy	0.230	0.270	0.233	0.262	0.369	0.356	0.270	0.307	0.260	0.297	0.641	0.639	0.347	0.417	0.301	0.319	0.330	0.401	0.291	0.381	0.885	0.711
PEMS03	0.096	0.197	0.113	0.221	0.495	0.472	0.119	0.233	0.180	0.291	0.169	0.281	0.326	0.419	0.147	0.248	0.278	0.375	0.213	0.327	0.667	0.601
PEMS04	0.098	0.203	0.111	0.221	0.526	0.491	0.103	0.215	0.195	0.307	0.209	0.314	0.353	0.437	0.129	0.241	0.295	0.388	0.231	0.337	0.610	0.590
PEMS07	0.088	0.181	0.101	0.204	0.504	0.478	0.112	0.217	0.211	0.303	0.235	0.315	0.380	0.440	0.124	0.225	0.329	0.395	0.165	0.283	0.367	0.451
PEMS08	0.138	0.217	0.150	0.226	0.529	0.487	0.165	0.261	0.280	0.321	0.268	0.307	0.441	0.464	0.193	0.271	0.379	0.416	0.286	0.358	0.814	0.659
1st Count	9	8	1	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

4 EXPERIMENTS

Datasets. To thoroughly evaluate the performance of our proposed LiNo, we conduct extensive experiments on 13 widely used, real-world datasets including ETT (4 subsets) (Zhou et al., 2022a), Traffic, Exchange, Electricity(ECL), Weather (Wu et al., 2021), Solar-Energy(Solar) (Lai et al., 2018) and PEMS (4 subsets) (Liu et al., 2022a). Detailed descriptions of the datasets can be found in Appendix A. We select both univariate and multivariate time series forecasting tasks, ensuring a comprehensive assessment.

Experimental setting. All the experiments are conducted on a single NVIDIA GeForce RTX 4090 with 24G VRAM. The mean squared error (MSE) loss function is utilized for model optimization. We use the ADAM optimizer with an early stop parameter $patience = 6$. To foster reproducibility, we make our code, training scripts, and some visualization examples available in this **Anonymous Repository**[1]. Full implementation details and other information are in Appendix B.1.

4.1 MULTIVARIATE TIME SERIES FORECASTING RESULTS

Compared methods and benchmarks. We extensively compare the recent Linear-based or MLP-based methods, including DLinear (Zeng et al., 2023), TSMixer (Chen et al., 2023), TiDE (Das et al., 2023), RLinear (Li et al., 2023a). We also consider Transformer-based methods including FEDformer (Zhou et al., 2022b), Autoformer (Wu et al., 2021), PatchTST (Nie et al., 2023), Crossformer (Zhang & Yan, 2023), iTransformer (Liu et al., 2024b) and a CNN-based method TimesNet (Wu et al., 2023). These models represent the latest advancements in multivariate time series forecasting and encompass all mainstream prediction model types. The multivariate time series forecasting benchmarks follow the setting in iTransformer (Liu et al., 2024b). The lookback window is set to $T = 96$ for all datasets. We set the prediction horizon to $F \in \{12, 24, 48, 96\}$ for PEMS dataset and $F \in \{96, 192, 336, 720\}$ for others. Performance comparison among different methods is conducted based on two primary evaluation metrics: Mean Squared Error (MSE) and Mean Absolute Error (MAE). The results of TSMixer are reproduced following **Time Series Library** (Wang et al., 2024b) and other results are taken from iTransformer (Liu et al., 2024b).

Result analysis. As shown in Table 1, LiNo performed remarkably across 10 benchmark datasets. It achieved first place in **9 out of 10** datasets in MSE and **8** datasets in MAE, underscoring its leading position in multivariate time series forecasting tasks. LiNo successfully reduced the MSE metric by **3.41%** compared to the previous state-of-the-art method, **iTransformer**, across all 10 datasets. Notably, the PEMS datasets (*PEMS03:* 358 *variates, PEMS04:* 307 *variates, PEMS07:* 883 *variates, PEMS08:* 170 *variates*) and the ECL dataset (321 *variates*) present notorious challenges to

---
[1] https://anonymous.4open.science/r/LiNo-8225/

Table 2: Univariate forecasting results with prediction lengths $F \in \{96, 192, 336, 720\}$ and fixed lookback length $T = 96$ for all datasets. Results are averaged from all prediction lengths. Full result is left in Appendix E.2 due to space limit.

Models	LiNo (Ours)		MICN (2023)		FEDformer (2022b)		Autoformer (2021)		Informer (2022a)		LogTrans (2019)	
Metric	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETTm1	**0.053**	**0.172**	0.064	0.185	0.069	0.202	0.081	0.221	0.281	0.441	0.231	0.382
ETTm2	**0.118**	**0.255**	0.131	0.266	0.119	0.262	0.130	0.271	0.175	0.320	0.130	0.277
ETTh1	**0.074**	**0.209**	0.092	0.233	0.111	0.257	0.105	0.252	0.199	0.377	0.345	0.513
ETTh2	**0.180**	**0.332**	0.252	0.390	0.206	0.350	0.218	0.364	0.243	0.400	0.252	0.408
Traffic	**0.143**	**0.222**	0.165	0.246	0.219	0.323	0.261	0.365	0.309	0.388	0.355	0.404
Weather	**0.0016**	**0.030**	0.0030	0.040	0.0055	0.058	0.0083	0.070	0.0033	0.044	0.0058	0.057
1st Count	**6**	**6**	0	0	0	0	0	0	0	0	0	0

multivariate time series forecasting models due to their high dimensionality and complex nonlinearity. LiNo demonstrated its superiority in nonlinear pattern extraction by achieving a substantial relative decrease of **11.89%** in average MSE on the four PEMS-relevant benchmarks. On the ECL dataset, LiNo decreased the average MSE from **0.178** to **0.164**, representing a significant reduction of about **7.87%**.

Previous research suggests that simple linear models can outperform complex deep neural networks in certain scenarios (Zeng et al., 2023; Li et al., 2023a). For instance, in scenarios where the dataset displays clear nonlinear patterns, nonlinear models like iTransformer excel. However, on the ETT datasets (four subsets), **RLinear**, which consists of a linear layer combined with ReVIN (Kim et al., 2022), easily surpassed all previous sophisticated deep models. We argue that this is because most of these models focus solely on either linear or nonlinear patterns, neglecting the other, leading to inconsistent performance across different scenarios. In contrast, LiNo performs outstandingly across various scenarios, demonstrating the importance of a balanced approach to handling both linear and nonlinear patterns.

4.2 Univariate Time Series Forecasting Results

Compared methods and benchmarks. The models and results used for comparing univariate time series forecasting performance were collected from MICN (Wang et al., 2023), including MICN (Wang et al., 2023), FEDformer (Zhou et al., 2022b), Autoformer (Wu et al., 2021), Informer (Zhou et al., 2022a), LogTrans (Li et al., 2019). We follow the setting in MICN (Liu et al., 2024b) where the lookback window length is set to $T = 96$ and the prediction horizon to $F \in \{96, 192, 336, 720\}$ for all datasets.

Result analysis. Table 2 demonstrates the top-notch performance of LiNo in univariate time series forecasting tasks, achieving the best predictive results across all 6 datasets. On six datasets, LiNo reduced the MSE metric by **19.37%** and the MAE by **10.28%** compared to the previous SOTA method, MICN. Notably, on the Weather, ETTh2, and Traffic datasets, the MSE decreased by **47.11%**, **28.64%**, and **12.97%**, respectively, marking a significant improvement. The consistent superior advancement in both univariate and multivariate time series forecasting demonstrates the wide applicability of LiNo across various scenarios.

4.3 LiNo Analysis

Ablation study on LiNo components. To verify the effectiveness of LiNo components, we conducted ablation studies by removing components (w/o) on 7 multivariate time series forecasting benchmarks with a lookback window of $T = 96$ and prediction lengths $F \in \{96, 720\}$. The results are presented in Table 3. Every design in LiNo is crucial. Removing the No block results in significant performance degradation, with an MSE increase of up to **71.82%**. Similarly, the absence of the Li block leads to a **10.00%** rise in MSE, underscoring the importance of modeling both linear and nonlinear patterns. Further ablation of the No block reveals that temporal variation and frequency information extraction are essential. The absence of inter-series dependencies modeling results in a **15.91%** increase in MSE, highlighting its critical importance.

Table 3: Ablations on LiNo. 'w/o' means remove this design. 'TE' stands for temporal variations extraction, 'FE' strands for frequency information extraction, and 'CD' means the channel mixing step for inter-series dependencies modeling.

Dataset		LiNo		w/o Li Block		w/o No Block		w/o TE		w/o FE		w/o CD	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ECL	96	0.138	0.233	0.149	0.242	0.186	0.267	0.143	0.241	0.140	0.237	0.154	0.248
	720	0.191	0.290	0.210	0.300	0.245	0.320	0.197	0.293	0.196	0.294	0.223	0.311
Weather	96	0.154	0.199	0.211	0.300	0.162	0.206	0.158	0.204	0.159	0.204	0.164	0.209
	720	0.343	0.342	0.355	0.348	0.342	0.338	0.347	0.344	0.345	0.343	0.347	0.345
ETTm2	96	0.171	0.254	0.177	0.260	0.180	0.261	0.173	0.256	0.173	0.255	0.175	0.257
	720	0.395	0.393	0.399	0.396	0.409	0.400	0.399	0.396	0.397	0.395	0.391	0.392
ETTh2	96	0.292	0.340	0.295	0.344	0.301	0.348	0.294	0.342	0.294	0.341	0.291	0.340
	720	0.422	0.441	0.416	0.436	0.429	0.446	0.424	0.442	0.426	0.443	0.424	0.442
PEMS04	12	0.069	0.169	0.083	0.186	0.121	0.232	0.070	0.173	0.070	0.171	0.083	0.186
	96	0.137	0.247	0.278	0.359	1.016	0.762	0.149	0.261	0.146	0.259	0.296	0.349
PEMS08	12	0.070	0.166	0.076	0.176	0.119	0.230	0.075	0.180	0.074	0.176	0.085	0.189
	96	0.247	0.283	0.359	0.359	1.075	0.771	0.258	0.299	0.253	0.292	0.431	0.384
Solar-Energy	96	0.200	0.250	0.238	0.310	0.338	0.258	0.203	0.257	0.204	0.258	0.226	0.271
	720	0.250	0.283	0.251	0.395	0.369	0.292	0.260	0.296	0.267	0.297	0.277	0.297
avg-promote		0	0	-10.00%	-6.48%	-71.82%	-35.97%	-2.27%	-2.52%	-2.27%	-1.80%	-15.91%	-8.27%

Table 4: Impact of the number of LiNo blocks (layers) N on the model's performance. The task is **input-96-predict-96** for PEMS04&08, and **input-96-predict-720** for others. We set $N \in \{1, 2, 3, 4\}$. The best results are bold in red.

Number of LiNo blocks		ETTh1		ETTh2		ECL		Weather		Solar		PEMS04		PEMS08	
Value \Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
N	1	0.472	0.466	0.427	0.446	0.197	0.295	0.346	0.344	0.268	0.299	0.152	0.262	0.267	0.308
	2	0.471	0.466	**0.421**	**0.440**	**0.191**	**0.290**	**0.343**	**0.342**	**0.250**	**0.283**	0.145	0.256	**0.247**	**0.283**
	3	**0.459**	**0.456**	0.423	0.442	0.192	0.292	0.346	0.344	0.255	0.285	0.143	0.250	0.258	0.296
	4	0.468	0.463	0.424	0.442	0.194	0.293	0.347	0.345	0.257	0.286	**0.137**	**0.247**	0.258	0.296

Table 5: Further ablation study on the No Block. 'Temporal' means only extracting temporal variations (without introducing nonlinearity), 'Frequency' strands for frequency information extraction (without introducing nonlinearity), and 'TF' means these two patterns are captured simultaneously. The nonlinearity of the No Block is introduced by adding **ReLU** or **Tanh** activation function.

Models		Temporal		Frequency		TF		ReLU		Tanh	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETTh1	96	0.385	0.398	0.383	0.393	0.383	**0.392**	0.384	0.398	**0.375**	0.394
	720	0.487	0.475	0.482	0.469	0.478	0.467	0.488	0.477	**0.464**	**0.458**
ETTm1	96	0.341	0.369	0.342	0.369	0.338	0.366	0.328	0.365	**0.322**	**0.359**
	720	0.481	0.447	0.479	0.445	0.474	**0.439**	0.478	0.445	**0.465**	0.442
ECL	96	0.186	0.268	0.187	0.267	0.183	0.263	0.154	0.248	**0.150**	**0.243**
	720	0.245	0.320	0.245	0.320	0.241	0.317	0.223	0.311	**0.221**	**0.308**
Weather	96	0.165	0.209	0.165	0.208	**0.162**	**0.206**	0.162	0.208	0.163	0.209
	720	0.344	0.344	0.345	0.343	**0.342**	**0.338**	0.345	0.345	0.343	0.339

Further ablation on No Block. Considering that in real-world scenarios, nonlinear temporal variations and frequency information are more prevalent than inter-series dependencies in most cases, we conducted further ablation studies. Specifically, without considering inter-series dependencies, we simplified the No block to retain only the Temporal&Frequency Extraction component (**TF_Extraction**) shown in Figure 2 (left), and performed additional ablation experiments.

Combining Temporal and Frequency projections enhances expressiveness, improving the model's ability to learn complex patterns. **Tanh** provides a smooth, symmetric activation function that better captures the complex dependencies in both time and frequency domains, therefore delivering a better performance than the more commonly used **ReLU**, as in Table 5.

Sensitivity to the number of LiNo blocks. We investigate the impact of the number of LiNo blocks (layers) N on the model's performance, as shown in Table 4. The best forecasting results for each dataset are generally achieved when $N > 1$, indicating the necessity of deeper RRD. The variation in optimal N across datasets suggests that LiNo can flexibly adapt to different RRD requirements.

Table 6: Ablation study of different No block choice and different model design.

(a) Ablation study of different No block choice. '→ iTransformer' means replacing the proposed No block with iTransformer. Same to '→ TSMixer'. The input sequence length is set to $T = 96$ for all tasks.

(b) To compare the performance of different forecasting model designs, we choose **iTransformer** as the backbone and sequentially employ 'Raw', 'Mu', and **LiNo**. The input sequence length is set to $T = 96$.

Models		Ori LiNo		→ iTransformer		→ TSMixer	
Metric		MSE	MAE	MSE	MAE	MSE	MAE
ETTm2	96	**0.171**	**0.254**	0.174	0.259	0.173	0.256
	192	**0.237**	**0.298**	0.238	0.299	0.239	0.301
	336	**0.296**	**0.336**	0.302	0.340	0.304	0.343
	720	**0.395**	**0.393**	0.402	0.398	0.406	0.402
	Avg	**0.275**	**0.320**	0.279	0.324	0.281	0.326
ECL	96	**0.138**	**0.233**	0.141	0.239	0.145	0.249
	192	**0.155**	**0.250**	0.163	0.254	0.164	0.263
	336	**0.171**	**0.267**	0.175	0.271	0.187	0.285
	720	**0.191**	**0.290**	0.201	0.295	0.228	0.320
	Avg	**0.164**	**0.260**	0.170	0.265	0.181	0.279
Weather	96	**0.154**	**0.199**	0.156	0.201	0.157	0.203
	192	**0.205**	**0.248**	0.206	0.248	0.206	0.250
	336	**0.262**	**0.290**	0.264	0.291	0.267	0.295
	720	**0.343**	**0.342**	0.345	0.343	0.349	0.347
	Avg	**0.241**	**0.270**	0.243	0.271	0.245	0.274

Models		LiNo		Mu		Raw	
Metric		MSE	MAE	MSE	MAE	MSE	MAE
ETTm2	96	**0.174**	**0.259**	0.179	0.264	0.184	0.268
	192	**0.238**	**0.299**	0.243	0.304	0.247	0.307
	336	**0.302**	**0.340**	0.307	0.345	0.311	0.348
	720	**0.402**	**0.398**	0.406	0.400	0.408	0.402
	Promote	**-2.96%**	**-2.19%**	-1.30%	-0.91%	0	0
ECL	96	**0.141**	**0.239**	0.154	0.246	0.153	0.245
	192	**0.163**	**0.254**	0.167	0.259	0.166	0.257
	336	**0.175**	**0.271**	0.183	0.276	0.183	0.275
	720	**0.201**	**0.295**	0.220	0.309	0.224	0.310
	Promote	**-6.34%**	**-2.58%**	-0.28%	0.28%	0	0
Weather	96	**0.156**	**0.201**	0.174	0.214	0.178	0.217
	192	**0.206**	**0.248**	0.223	0.257	0.224	0.258
	336	**0.264**	**0.291**	0.278	0.298	0.281	0.299
	720	**0.345**	**0.343**	0.355	0.350	0.358	0.352
	Promote	**-6.72%**	**-3.82%**	-1.06%	-0.62%	0	0

Superiority of the proposed No block. Extracting nonlinear patterns, such as inter-series dependencies, temporal variations, and frequency information, is crucial for accurate predictions. To demonstrate the competence of the proposed No block, we sequentially replaced it with two renowned nonlinear time series forecasting models: **iTransformer** and **TSMixer**. As shown in Table 6 (a), our proposed No block consistently outperforms other nonlinear pattern extractors. It delivers superior performance across ETTm2 (7 variates), Weather (21 variates), and ECL (321 variates), showcasing its remarkable ability to extract nonlinear patterns.

Further analysis of LiNo is provided in Appendix C.

4.4 ANALYSIS OF DIFFERENT FORECASTING MODEL DESIGNS

Forecasting performance comparison. We use **iTransformer**, a leading transformer-based time series forecasting model, as the backbone. We evaluate three model designs: 'Raw' (classical design), 'Mu' (recursive splitting of representations for prediction, design used in N-BEATS (Oreshkin et al., 2020)), and 'LiNo' (our proposed framework with further recursive splitting into linear and nonlinear patterns). The forecasting performance in Table 6 (b) demonstrates the effectiveness of the LiNo framework. Compared to 'Raw', 'Mu' reduces the MSE on ETTm2, ECL, and Weather by 1.3%, 0.28%, and 1.06%, respectively. LiNo further reduces the MSE by 2.96%, 6.34%, and 6.72%. These results indicate that while 'Mu' improves forecasting performance, it remains suboptimal due to the entanglement of linear and nonlinear predictions. LiNo effectively separates these patterns, achieving more accurate results.

Noise robustness. To investigate the robustness of different forecasting model designs to noise, we conducted experiments using **iTransformer** as the backbone. Given an input multivariate time series signal $X \in \mathbb{R}^{B \times T \times N}$, we added Gaussian noise to obtain: $\hat{X} = X + \alpha \cdot \text{noise}$, where $\alpha \in \{0\%, 25\%, 50\%, 75\%, 100\%\}$ is the noise intensity coefficient, and noise $\in \mathbb{R}^{B \times T \times N}$ is Gaussian noise with mean 0 and standard deviation 1. The noisy input $\hat{X}$ was used during training. A more robust forecasting model will be less affected by this noise.

Figure 3: Multivariate forecasting performance of three different model designs using **iTransformer** as backbone under different noise levels across datasets of ECL, ETTm2, and Weather.

Figure 4: Visualization of multivariate forecasting result (***last channel/variate***) of the proposed **LiNo** on ETTh1 and ECL datasets. We set the number of LiNo blocks (layers) to $N = 3$. The task is multivariate time series forecasting with input $T = 96$ and target $F = 96$. 'LP' denotes Linear prediction, and 'NP' stands for Nonlinear prediction. LP i or NP i ($i \in \{1, 2, 3\}$) is the linear or nonlinear prediction of i-th layer (level).

Our LiNo design consistently outperforms the 'Mu' and 'Raw' models across various noise levels, demonstrating superior robustness and reliability in forecasting, as shown in Figure 3. This result supports our hypothesis that separating linear and nonlinear patterns enhances model robustness.

Visualization of linear and nonlinear predictions. We visualize LiNo's forecasting results on the ETTh1 and ECL datasets in Figure 4. The Li block primarily captures linear patterns such as long-term trends, while the No block effectively captures nonlinear signals like fluctuations and seasonality. The forecasting results for ECL and ETTh1 reveal three distinct linear modes and three different nonlinear patterns, enhancing the interpretability of time series forecasting and aiding in understanding the underlying data dynamics. Additional visualization results of LiNo can be found in Appendix D.

5 CONCLUSION

The commonly used seasonal and trend decomposition (STD) in previous methods still rely on flawed linear pattern extractors. Their lack of separating the nonlinear component from residual and shallow-level decomposition severely hinders its modeling capability. This work advances them by incorporating a more general linear extraction model and introducing a novel and powerful nonlinear extraction model into RRD. By performing RRD at a deeper and more nuanced level, we achieve a more refined decomposition, leading to more accurate and robust forecasting results. The proposed No block excels in capturing nonlinear features. Experiments across multiple benchmarks demonstrated LiNo's superior performance in both univariate and multivariate forecasting tasks, offering improved accuracy and stability. These findings could offer opportunities to design more robust and precise forecasting models.

REFERENCES

RK Agrawal and Ratnadip Adhikari. An introductory study on time series modeling and forecasting. *arXiv preprint arXiv:1302.6613*, 2013. URL https://arxiv.org/abs/1302.6613.

Md Atik Ahamed and Qiang Cheng. Timemachine: A time series is worth 4 mambas for long-term forecasting. *arXiv preprint arXiv:2403.09898*, 2024. URL https://arxiv.org/abs/2403.09898.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(8):1798–1828, 2013.

Yuxuan Bian, Xuan Ju, Jiangtong Li, Zhijian Xu, Dawei Cheng, and Qiang Xu. Multi-patch prediction: Adapting llms for time series representation learning. In *Proceedings of the Forty-first International Conference on Machine Learning (ICML)*, 2024. URL https://arxiv.org/abs/2402.04852v2.

Cristian Challu, Kin G Olivares, Boris N Oreshkin, Federico Garza Ramirez, Max Mergenthaler Canseco, and Artur Dubrawski. Nhits: Neural hierarchical interpolation for time series forecasting. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pp. 6989–6997, 2023.

Chris Chatfield and Haipeng Xing. *The analysis of time series: an introduction with R*. Chapman and hall/CRC, 2019.

Jialin Chen, Jan Eric Lenssen, Aosong Feng, Weihua Hu, Matthias Fey, Leandros Tassiulas, Jure Leskovec, and Rex Ying. From similarity to superiority: Channel clustering for time series forecasting. *arXiv preprint arXiv:2404.01340*, 2024. URL https://arxiv.org/abs/2404.01340.

Si-An Chen, Chun-Liang Li, Sercan O Arik, Nathanael Christian Yoder, and Tomas Pfister. Tsmixer: An all-mlp architecture for time series forecasting. *Transactions on Machine Learning Research*, 2023. ISSN 2835-8856. URL https://openreview.net/forum?id=wbpxTuXgm0.

Fatoumata Dama and Christine Sinoquet. Analysis and modeling to forecast in time series: A systematic review. *arXiv preprint arXiv:2104.00164*, 2021. URL https://arxiv.org/abs/2104.00164.

Abhimanyu Das, Weihao Kong, Andrew Leach, Shaan K Mathur, Rajat Sen, and Rose Yu. Long-term forecasting with tide: Time-series dense encoder. *Transactions on Machine Learning Research*, 2023. ISSN 2835-8856. URL https://openreview.net/forum?id=pCbC3aQB5W.

Luo Donghao and Wang Xue. Moderntcn: A modern pure convolution structure for general time series analysis. In *Proceedings of the Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=vpJMJerXHU.

Dazhao Du, Bing Su, and Zhewei Wei. Preformer: Predictive transformer with multi-scale segment-wise correlations for long-term time series forecasting. In *ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2023.

Jeffrey L. Elman. Finding structure in time. *Cognitive Science*, pp. 179–211, 1990. doi: 10.1207/s15516709cog1402_1. URL http://dx.doi.org/10.1207/s15516709cog1402_1.

Nate Gruver, Marc Finzi, Shikai Qiu, and Andrew G Wilson. Large language models are zero-shot time series forecasters. *Advances in Neural Information Processing Systems*, 36, 2024.

Norden E Huang, Zheng Shen, Steven R Long, Manli C Wu, Hsing H Shih, Quanan Zheng, Nai-Chyuan Yen, Chi Chao Tung, and Henry H Liu. The empirical mode decomposition and the hilbert spectrum for nonlinear and non-stationary time series analysis. *Proceedings of the Royal Society of London. Series A: mathematical, physical and engineering sciences*, 454(1971):903–995, 1998.

Romain Ilbert, Ambroise Odonnat, Vasilii Feofanov, Aladin Virmaux, Giuseppe Paolo, Themis Palpanas, and Ievgen Redko. SAMformer: Unlocking the potential of transformers in time series forecasting with sharpness-aware minimization and channel-wise attention. In *Forty-first International Conference on Machine Learning*, 2024. URL https://openreview.net/forum?id=8kLzL5QBh2.

Ming Jin, Shiyu Wang, Lintao Ma, Zhixuan Chu, James Y. Zhang, Xiaoming Shi, Pin-Yu Chen, Yuxuan Liang, Yuan-Fang Li, Shirui Pan, and Qingsong Wen. Time-LLM: Time series forecasting by reprogramming large language models. In *Proceedings of the Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=Unb5CVPtae.

Taesung Kim, Jinhee Kim, Yunwon Tae, Cheonbok Park, Jang-Ho Choi, and Jaegul Choo. Reversible instance normalization for accurate time-series forecasting against distribution shift. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=cGDAkQo1C0p.

Nikita Kitaev, Lukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkgNKkHtvB.

Guokun Lai, Wei-Cheng Chang, Yiming Yang, and Hanxiao Liu. Modeling long-and short-term temporal patterns with deep neural networks. In *Proceedings of the 41st International ACM SIGIR Conference on Research & Development in Information Retrieval*, pp. 95–104, 2018.

Shiyang Li, Xiaoyong Jin, Yao Xuan, Xiyou Zhou, Wenhu Chen, Yu-Xiang Wang, and Xifeng Yan. Enhancing the locality and breaking the memory bottleneck of transformer on time series forecasting. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32, pp. n/a. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/6775a0635c302542da2c32aa19d86be0-Paper.pdf.

Zhe Li, Shiyi Qi, Yiduo Li, and Zenglin Xu. Revisiting long-term time series forecasting: An investigation on linear mapping. *arXiv preprint arXiv:2305.10721*, 2023a.

Zhe Li, Zhongwen Rao, Lujia Pan, and Zenglin Xu. Mts-mixers: Multivariate time series forecasting via factorized temporal and channel mixing. *arXiv preprint arXiv:2302.04501*, 2023b. URL https://arxiv.org/abs/2302.04501.

Bryan Lim and Stefan Zohren. Time series forecasting with deep learning: A survey. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, pp. 20200209, 2021. doi: 10.1098/rsta.2020.0209. URL http://dx.doi.org/10.1098/rsta.2020.0209.

Shengsheng Lin, Weiwei Lin, Wentai Wu, Feiyu Zhao, Ruichao Mo, and Haotong Zhang. Segrnn: Segment recurrent neural network for long-term time series forecasting. *arXiv preprint arXiv:2308.11200*, 2023. URL https://arxiv.org/abs/2308.11200.

Shengsheng Lin, Weiwei Lin, Wentai Wu, Haojun Chen, and Junjie Yang. Sparsetsf: Modeling long-term time series forecasting with 1k parameters. In *Proceedings of the Forty-first International Conference on Machine Learning (ICML)*, 2024.

Juncheng Liu, Chenghao Liu, Gerald Woo, Yiwei Wang, Bryan Hooi, Caiming Xiong, and Doyen Sahoo. Unitst: Effectively modeling inter-series and intra-series dependencies for multivariate time series forecasting. *arXiv preprint arXiv:2406.04975*, 2024a. URL https://arxiv.org/abs/2406.04975.

Minhao Liu, Ailing Zeng, Muxi Chen, Zhijian Xu, Qiuxia Lai, Lingna Ma, and Qiang Xu. Scinet: Time series modeling and forecasting with sample convolution and interaction. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022a. URL https://openreview.net/forum?id=AyajSjTAzmg.

Shizhan Liu, Hang Yu, Cong Liao, Jianguo Li, Weiyao Lin, Alex X. Liu, and Schahram Dustdar. Pyraformer: Low-complexity pyramidal attention for long-range time series modeling and forecasting. In *International Conference on Learning Representations*, 2022b. URL `https://openreview.net/forum?id=0EXmFzUn5I`.

Yong Liu, Haixu Wu, Jianmin Wang, and Mingsheng Long. Non-stationary transformers: Exploring the stationarity in time series forecasting. In *Advances in Neural Information Processing Systems*, 2022c. URL `https://openreview.net/forum?id=ucNDIDRNjjv`.

Yong Liu, Chenyu Li, Jianmin Wang, and Mingsheng Long. Koopa: Learning non-stationary time series dynamics with koopman predictors. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=A4zzxu82a7`.

Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, and Mingsheng Long. itransformer: Inverted transformers are effective for time series forecasting. In *Proceedings of the Twelfth International Conference on Learning Representations*, 2024b. URL `https://openreview.net/forum?id=JePfAI8fah`.

Yong Liu, Guo Qin, Xiangdong Huang, Jianmin Wang, and Mingsheng Long. Autotimes: Autoregressive time series forecasters via large language models. *arXiv preprint arXiv:2402.02370*, 2024c.

William T Ng, K Siu, Albert C Cheung, and Michael K Ng. Expressing multivariate time series as graphs with time series attention transformer. *arXiv preprint arXiv:2208.09300*, 2022. URL `https://arxiv.org/abs/2208.09300`.

Yuqi Nie, Nam H Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers. In *Proceedings of the Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=Jbdc0vTOcol`.

Boris N. Oreshkin, Dmitri Carpov, Nicolas Chapados, and Yoshua Bengio. N-beats: Neural basis expansion analysis for interpretable time series forecasting. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=r1ecqn4YwB`.

Zijie Pan, Yushan Jiang, Sahil Garg, Anderson Schneider, Yuriy Nevmyvaka, and Dongjin Song. s^2 ip-llm: Semantic space informed prompt learning with llm for time series forecasting. In *Forty-first International Conference on Machine Learning*, 2024.

Xihao Piao, Zheng Chen, Taichi Murayama, Yasuko Matsubara, and Yasushi Sakurai. Fredformer: Frequency debiased transformer for time series forecasting. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '24, 2024.

Gabriel Rilling, Patrick Flandrin, and Paulo Goncalves. On empirical mode decomposition and its algorithms. In *IEEE-EURASIP Workshop on Nonlinear Signal and Image Processing*, volume 3, pp. 8–11. IEEE, 2003.

Zezhi Shao, Zhao Zhang, Fei Wang, Wei Wei, and Yongjun Xu. Spatial-temporal identity: A simple yet effective baseline for multivariate time series forecasting. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, pp. 4454–4458, 2022.

James H Stock and Mark W Watson. A comparison of linear and nonlinear univariate models for forecasting macroeconomic time series, 1998.

Naftali Tishby and Noga Zaslavsky. Deep learning and the information bottleneck principle. In *2015 ieee information theory workshop (itw)*, pp. 1–5. IEEE, 2015.

William Toner and Luke Nicholas Darlow. An analysis of linear time series forecasting models. In *Proceedings of the Forty-first International Conference on Machine Learning (ICML)*, 2024. URL `https://openreview.net/forum?id=xl82CcbYaT`.

José F. Torres, Dalil Hadjout, Abderrazak Sebaa, Francisco Martínez-Álvarez, and Alicia Troncoso. Deep learning for time series forecasting: A survey. *Big Data*, pp. 3–21, 2021. doi: 10.1089/big. 2020.0159. URL `http://dx.doi.org/10.1089/big.2020.0159`.

D Ulyanov. Instance normalization: The missing ingredient for fast stylization. *arXiv preprint arXiv:1607.08022*, 2016. URL `https://arxiv.org/abs/1607.08022`.

Huiqiang Wang, Jian Peng, Feihu Huang, Jince Wang, Junhui Chen, and Yifei Xiao. MICN: Multi-scale local and global context modeling for long-term series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=zt53IDUR1U`.

Shiyu Wang, Haixu Wu, Xiaoming Shi, Tengge Hu, Huakun Luo, Lintao Ma, James Y Zhang, and JUN ZHOU. Timemixer: Decomposable multiscale mixing for time series forecasting. In *International Conference on Learning Representations (ICLR)*, 2024a.

Yuxuan Wang, Haixu Wu, Jiaxiang Dong, Yong Liu, Mingsheng Long, and Jianmin Wang. Deep time series models: A comprehensive survey and benchmark. *arXiv preprint arXiv:2407.13278*, 2024b. URL `https://arxiv.org/abs/2407.13278`.

Zihan Wang, Fanheng Kong, Shi Feng, Ming Wang, Han Zhao, Daling Wang, and Yifei Zhang. Is mamba effective for time series forecasting? *arXiv preprint arXiv:2403.11144*, 2024c.

Gerald Woo, Chenghao Liu, Doyen Sahoo, Akshat Kumar, and Steven C. H. Hoi. Etsformer: Exponential smoothing transformers for time-series forecasting. *arXiv preprint arXiv:2202.01381*, 2022. URL `https://arxiv.org/abs/2202.01381`.

Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 22419–22430. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper_files/paper/2021/file/bcc0d400288793e8bdcd7c19a8ac0c2b-Paper.pdf`.

Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. TimesNet: Temporal 2d-variation modeling for general time series analysis. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=ju_Uqw384Oq`.

Zhijian Xu, Ailing Zeng, and Qiang Xu. Fits: Modeling time series with 10k parameters. In *Proceedings of the Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=bWcnvZ3qMb`.

Kun Yi, Qi Zhang, Wei Fan, Hui He, Liang Hu, Pengyang Wang, Ning An, Longbing Cao, and Zhendong Niu. FourierGNN: Rethinking multivariate time series forecasting from a pure graph perspective. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=bGs1qWQ1Fx`.

Guoqi Yu, Jing Zou, Xiaowei Hu, Angelica I Aviles-Rivero, Jing Qin, and Shujun Wang. Revitalizing multivariate time series forecasting: Learnable decomposition with inter-series dependencies and intra-series variations modeling. In *Proceedings of the Forty-first International Conference on Machine Learning (ICML)*, 2024. URL `https://openreview.net/forum?id=87CYNyCGOo`.

Ailing Zeng, Muxi Chen, Lei Zhang, and Qiang Xu. Are transformers effective for time series forecasting? In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pp. 11121–11128, 2023. URL `https://ojs.aaai.org/index.php/AAAI/article/view/26317/26089`.

Tianping Zhang, Yizhuo Zhang, Wei Cao, Jiang Bian, Xiaohan Yi, Shun Zheng, and Jian Li. Less is more: Fast multivariate time series forecasting with light sampling-oriented mlp structures. *arXiv preprint arXiv:2207.01186*, 2022a. URL `https://arxiv.org/abs/2207.01186`.

Xiyuan Zhang, Jin Xiaoyong, Karthick Gopalswamy, Gaurav Gupta, Youngsuk Park, Xingjian Shi, Hao Wang, Danielle C Maddix, Yuyang Wang, UcSan Diego, AwsAi Labs, and Aws Aws. First de-trend then attend: Rethinking attention for time-series forecasting. *arXiv preprint arXiv:2212.08151*, 2022b. URL `https://arxiv.org/abs/2212.08151`.

Yunhao Zhang and Junchi Yan. Crossformer: Transformer utilizing cross-dimension dependency for multivariate time series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=vSVLM2j9eie`.

Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35:11106–11115, 2022a. doi: 10.1609/aaai.v35i12.17325. URL `http://dx.doi.org/10.1609/aaai.v35i12.17325`.

Tian Zhou, Ziqing Ma, Qingsong Wen, Xue Wang, Liang Sun, and Rong Jin. Fedformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *Proceedings of the 39th International Conference on Machine Learning (ICML 2022)*, 2022b.

A DATASETS DESCRIPTION

Table 7: Detailed dataset descriptions. *Channels* denotes the number of channels in each dataset. *Dataset Split* denotes the total number of time points in (Train, Validation, Test) split respectively. *Prediction Length* denotes the future time points to be predicted, and four prediction settings are included in each dataset. *Granularity* denotes the sampling interval of time points.

Dataset	Channels	Prediction Length	Dataset Split	Granularity	Domain
ETTh1, ETTh2	7	{96, 192, 336, 720}	(8545, 2881, 2881)	Hourly	Electricity
ETTm1, ETTm2	7	{96, 192, 336, 720}	(34465, 11521, 11521)	15min	Electricity
Exchange	8	{96, 192, 336, 720}	(5120, 665, 1422)	Daily	Economy
Weather	21	{96, 192, 336, 720}	(36792, 5271, 10540)	10min	Weather
ECL	321	{96, 192, 336, 720}	(18317, 2633, 5261)	Hourly	Electricity
Traffic	862	{96, 192, 336, 720}	(12185, 1757, 3509)	Hourly	Transportation
Solar-Energy	137	{96, 192, 336, 720}	(36601, 5161, 10417)	10min	Energy
PEMS03	358	{12, 24, 48, 96}	(15617,5135,5135)	5min	Transportation
PEMS04	307	{12, 24, 48, 96}	(10172,3375,281)	5min	Transportation
PEMS07	883	{12, 24, 48, 96}	(16911,5622,468)	5min	Transportation
PEMS08	170	{12, 24, 48, 96}	(10690,3548,265)	5min	Transportation

We elaborate on the datasets employed in this study with the following details.

1. **ETT (Electricity Transformer Temperature)** Zhou et al. (2022a) [2] comprises two hourly-level datasets (ETTh) and two 15-minute-level datasets (ETTm). Each dataset contains seven oil and load features of electricity transformers from July 2016 to July 2018.

2. **Exchange** (Wu et al., 2021) [3] collects the panel data of daily exchange rates from 8 countries from 1990 to 2016.

3. **Traffic** (Wu et al., 2021) [4] describes the road occupancy rates. It contains the hourly data recorded by the sensors of San Francisco freeways from 2015 to 2016.

4. **Electricity** (Wu et al., 2021) [5] collects the hourly electricity consumption of 321 clients from 2012 to 2014.

5. **Weather** (Wu et al., 2021) [6] includes 21 indicators of weather, such as air temperature, and humidity. Its data is recorded every 10 min for 2020 in Germany.

6. **Solar-Energy** Lai et al. (2018) [7] records the solar power production of 137 PV plants in 2006, which is sampled every 10 minutes.

7. **PEMS** (Liu et al., 2022a) [8] contains public traffic network data in California collected by 5-minute windows.

We follow the same data processing and train-validation-test set split protocol used in iTransformer (Liu et al., 2024b), where the train, validation, and test datasets are strictly divided according to chronological order to make sure there are no data leakage issues. We fix the length of the lookback series as $T = 96$ for all datasets, and the prediction length $F \in \{12, 24, 48, 96\}$ for PEMS datasets, and $F \in \{96, 192, 336, 720\}$ for others. Other details of these datasets is concluded in Table 7.

---

[2]https://github.com/zhouhaoyi/ETDataset
[3]https://github.com/thuml/iTransformer
[4]http://pems.dot.ca.gov
[5]https://archive.ics.uci.edu/ml/datasets/ElectricityLoadDiagrams20112014
[6]https://www.bgc-jena.mpg.de/wetter/
[7]https://github.com/thuml/iTransformer
[8]https://pems.dot.ca.gov/

B IMPLEMENT DETAILS

B.1 EXPERIMENT DETAILS

To foster reproducibility, we make our code, training scripts, and some visualization examples available in this **Anonymous Repository**[9]. All the experiments are conducted on a single NVIDIA GeForce RTX 4090 with 24G VRAM. The mean squared error (MSE) loss function is utilized for model optimization. We use the ADAM optimizer with an early stop parameter $patience = 6$. We explore the number of LiNo blocks $N \in \{1, 2, 3, 4\}$, dropout ratio $dp \in \{0.0, 0.2, 0.5\}$, and the dimension of layers $dim \in \{256, 512\}$. The $learning\ rate \in \{1e-3, 1e-4, 1e-5\}$ and $batch\ size \in \{32, 64, 128, 256\}$ are adjusted based on the size and dimensionality of the dataset, as well as the specific conditions of our experimental setup. All the compared multivariate forecasting baseline models that we reproduced are implemented based on the benchmark of **Time series Lab** (Wang et al., 2024b) Repository, which is fairly built on the configurations provided by each model's original paper or official code.

Performance comparison among different methods is conducted based on two primary evaluation metrics: Mean Squared Error (MSE) and Mean Absolute Error (MAE). The formula is below: **Mean Squared Error (MSE)**:

$$\text{MSE} = \frac{1}{F} \sum_{i=1}^{F} (\mathbf{Y}_i - \hat{\mathbf{Y}}_i)^2. \tag{5}$$

Mean Absolute Error (MAE):

$$\text{MAE} = \frac{1}{F} \sum_{i=1}^{F} |\mathbf{Y}_i - \hat{\mathbf{Y}}_i|. \tag{6}$$

where $\mathbf{Y}, \hat{\mathbf{Y}} \in \mathbb{R}^{F \times C}$ are the ground truth and prediction results of the future with F time points and C channels. $\mathbf{Y}_i$ denotes the i-th future time point.

C FURTHER MODEL ANALYSIS

C.1 MODEL ROBUSTNESS

Table 8: Error Bar ($Mean \pm Std$) of LiNo's multivariate forecasting result on ETTh2, ETTm2, Weather, PEMS04, PEMS08. We set lookback window $T = 96$, and prediction length $F \in \{12, 24, 48, 96\}$ for PEMS04 and PEMS08, and $F \in \{96, 192, 336, 720\}$ for others. Mean and standard deviation were obtained on 5 runs with different random seeds.

Models	ETTh2		ETTm2		Weather		PEMS04		PEMS08	
Metric	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
96/12	0.293 ± 0.0017	0.341 ± 0.0012	0.172 ± 0.0004	0.254 ± 0.0005	0.156 ± 0.0013	0.201 ± 0.0013	0.069 ± 0.0002	0.168 ± 0.0009	0.071 ± 0.0004	0.169 ± 0.0026
192/24	0.377 ± 0.0015	0.392 ± 0.0008	0.238 ± 0.0006	0.298 ± 0.0005	0.206 ± 0.0021	0.248 ± 0.0019	0.081 ± 0.0015	0.186 ± 0.0031	0.094 ± 0.0011	0.191 ± 0.0027
336/48	0.417 ± 0.0009	0.426 ± 0.0005	0.297 ± 0.0005	0.336 ± 0.0004	0.265 ± 0.0020	0.291 ± 0.0017	0.104 ± 0.0027	0.214 ± 0.0036	0.139 ± 0.0036	0.227 ± 0.0064
720/96	0.422 ± 0.0007	0.440 ± 0.0007	0.395 ± 0.0011	0.393 ± 0.0009	0.343 ± 0.0016	0.342 ± 0.0012	0.139 ± 0.0021	0.247 ± 0.0031	0.254 ± 0.0079	0.296 ± 0.0091

We provide LiNo's Error Bar ($Mean \pm Std$) on several representative datasets in Table 8. LiNo demonstrated a relatively lower Error Bar across results with different random seeds, indicating consistent performance, high stability, and considerable generalization ability.

C.2 MODEL EFFICIENCY

We evaluated the **parameter count**, and the **inference time** of four cutting-edge transformer-based multivariate time series forecasting models: **iTransformer**, **Crossformer**, **PatchTST**, and **FED-former**. Results can be found in Table 9. Although LiNo introduces slightly more trainable parameters compared to iTransformer well-known for its simple and efficient design, its inference speed and prediction performance are significantly superior to iTransformer.

---

[9]https://anonymous.4open.science/r/LiNo-8225/

Table 9: Model efficiency analysis. We evaluated the **parameter count**, and the **inference time** (average of 5 runs on a single NVIDIA 4090 24GB GPU) with $batch\_size = 1$ on **ETTh1** and **ECL** dataset. We set the dimension of layer $dim \in \{256, 512\}$, and the number of network layers $N = 2$. The task is **input-96-forecast-720**. * means 'former.' **Para** means 'Parameter count(M).' **Time** means 'inference time(ms).'

Datasets/Models	dim	LiNo		PatchTST		Cross*		iTrans*		FED*	
		Param	Time	Para	Time	Para	Time	Para	Time	Para	Time
ETTh1	256	1.59	**143.81**	3.27	251.00	8.19	399.00	**1.27**	177.67	3.43	303.556
	512	4.82	**145.68**	8.64	266.66	32.11	445.74	**4.63**	190.92	13.68	345.736
Electricity	256	1.75	**151.33**	3.27	322.53	13.66	432.40	**1.27**	192.12	4.24	347.634
	512	5.14	**152.24**	8.64	411.96	43.04	507.54	**4.63**	249.60	15.29	398.599

Figure 5: Multivariate forecasting performance improves with the increase of lookback window $T \in \{48, 96, 192, 336, 720\}$ and a fixed prediction length $F = 720$. Notably, LiNo consistently and stably enhances its forecasting performance as the lookback window size increases.

C.3 INCREASING LOOKBACK LENGTH

It is generally expected that increasing the input length will enhance forecasting performance by incorporating more information (Zeng et al., 2023). This improvement is typically observed in linear forecasts, supported by statistical methods (Liu et al., 2023) that utilize extended historical data. Figure 5 evaluates the performance of LiNo and other prestigious baselines. LiNo effectively leverages longer lookback windows, showing a positive correlation between predictive performance and input length. It significantly outperforms other baselines on the Weather and ECL datasets and achieves comparable results on the ETTm2 dataset.

D VISUALIZATION

D.1 VISUALIZATION OF LINO'S FORECASTING RESULTS

To provide insights that help readers better understand the working mechanism of LiNo and to intuitively grasp the effects of advanced 'Recursive Residual Decomposition' (RRD), we present visualizations of LiNo's forecasting results (***Last channel/variate***) across 13 multivariate forecasting benchmarks. We set the input length $T = 96$, prediction length $F = 96$, and number of LiNo blocks (layers) $N = 3$. 'LP' denotes Linear prediction, and 'NP' stands for Nonlinear prediction. LP i or NP i ($i \in \{1, 2, 3\}$) is the linear or nonlinear prediction of i-th layer (level). Results are in Figure 6– 18.

D.2 VISUALIZATION OF WEIGHT OF LI BLOCKS AND NO BLOCKS

We present visualizations of the weight of Li blocks and No blocks obtained across 13 multivariate forecasting benchmarks to help better understand the proposed LiNo. We set the input length $T = 96$, prediction length $F = 96$, and number of LiNo blocks (layers) $N = 3$. Results are in Figure 19– 31.

The method used for getting the weight follows the approach outlined in **Analysis of linear model** (Toner & Darlow, 2024). Plotting the learned matrices as in Figure 19 requires us to first convert each trained model into the form $f(\vec{x}) = A\vec{x} + \vec{b}$. To do this we note that $f(\vec{0}) = A\vec{0} + \vec{b} = \vec{b}$. Thus, the bias can be found by passing the zero vector into the trained model. We can determine A

in a similar manner. Let $\vec{e_i}$ denote the i-th coordinate vector, that is $\vec{e_i}$ is the vector which is 1 at position i and zero elsewhere. Then $f(\vec{e_i}) = A\vec{e_i} + \vec{b} = A_{.,i} + \vec{b}$ where $A_{.,i}$ is the i-th column of A. Hence, given that we have already computed the bias term, we may derive A simply by passing through each coordinate vector $\vec{e_i}$ and subtracting $\vec{b}$. Then, we repeat this process separately to each Li block and No block to get their weight, since they each output a forecasting result.

Take the ETTh1 dataset as an example, we observe in Figure 7 that each block (Li or No block) produces significantly different weights. This indicates that each block focuses on different patterns. The three No blocks all generate weights with noticeable periodicity, while the three Li blocks' weights are more concentrated on the most recent points in the input series. These interesting findings help us better understand how neural networks behave when extracting features from time series.

E   FULL RESULTS

E.1   FULL RESULTS OF MULTIVARIATE FORECASTING BENCHMARK

The full multivariate forecasting results are provided in Table 11 and Table 12 due to the space limitation of the main text. The proposed model achieves comprehensive state-of-the-art in real-world multivariate time series forecasting applications.

E.2   FULL RESULTS OF UNIVARIATE FORECASTING BENCHMARK

Table 13 provides the full univariate forecasting results to save space in the main text. LiNo surpasses previous state-of-the-art MICN (Wang et al., 2023) by a large, earning its prominent place in univariate time series forecasting tasks.

F   COMPARISON BETWEEN LINO AND N-BEATS

Table 10: Multivariate forecasting results with prediction lengths $F \in \{96, 192, 336, 720\}$ and fixed lookback winodw $T = 96$ for all datasets. The Results of N-BEATS and N-HiTS are taken from (Challu et al., 2023).

Models		**LiNo**		N-HiTS		N-BEATS	
Metric		MSE	MAE	MSE	MAE	MSE	MAE
ETTm2	96	**0.171**	**0.254**	0.176	0.255	0.184	0.263
	192	**0.237**	**0.298**	0.245	0.305	0.273	0.337
	336	**0.296**	**0.336**	0.295	0.346	0.309	0.355
	720	**0.395**	**0.393**	0.401	0.413	0.411	0.425
Promote		**-6.63%**	**-7.17%**	-5.10%	-4.42%	0	0
ECL	96	**0.138**	**0.233**	0.147	0.249	0.145	0.247
	192	**0.155**	**0.250**	0.167	0.269	0.180	0.283
	336	**0.171**	**0.267**	0.186	0.290	0.200	0.308
	720	**0.191**	**0.290**	0.243	0.340	0.266	0.362
Promote		**-17.19%**	**-13.33%**	-6.07%	-4.33%	0	0
Weather	96	**0.154**	0.199	0.158	0.195	0.167	0.203
	192	**0.205**	0.248	0.211	0.247	0.229	0.261
	336	**0.262**	0.290	0.274	0.300	0.287	0.304
	720	**0.343**	0.342	0.351	0.353	0.368	0.359
Promote		**-8.28%**	**-4.26%**	-5.42%	-2.84%	0	0

LiNo significantly outperforms N-BEATS (Oreshkin et al., 2020) and its successor, N-HiTS (Challu et al., 2023), across the ETTm2, ECL, and Weather datasets. This demonstrates that, compared to using Recursive Residual Decomposition (RRD) to refine the final prediction based on residual errors from previous predictions (as proposed in N-BEATS), employing RRD to capture more nuanced linear and nonlinear patterns (as in this work) is a better choice.

Figure 6: Visualization of LiNo's multivariate forecasting result on ECL dataset. 'LP' denotes Linear prediction, and 'NP' stands for Nonlinear prediction. LP i or NP i ($i \in \{1, 2, 3\}$) is the linear or nonlinear prediction of i-th layer (level). Same to followed figures.

Figure 7: Visualization of LiNo's multivariate forecasting result on ETTh1 dataset.

Figure 8: Visualization of LiNo's multivariate forecasting result on ETTh2 dataset.

Figure 9: Visualization of LiNo's multivariate forecasting result on ETTm1 dataset.

Figure 10: Visualization of LiNo's multivariate forecasting result on ETTm2 dataset.

Figure 11: Visualization of LiNo's multivariate forecasting result on Exchange dataset.

Figure 12: Visualization of LiNo's multivariate forecasting result on PEMS03 dataset.

Figure 13: Visualization of LiNo's multivariate forecasting result on PEMS04 dataset.

Figure 14: Visualization of LiNo's multivariate forecasting result on PEMS07 dataset.

Figure 15: Visualization of LiNo's multivariate forecasting result on PEMS08 dataset.

Figure 16: Visualization of LiNo's multivariate forecasting result on Solar dataset.

Figure 17: Visualization of LiNo's multivariate forecasting result on Traffic dataset.

Figure 18: Visualization of LiNo's multivariate forecasting result on Weather dataset.

Figure 19: Visualization of LiNo's weight on ECL dataset.

Figure 20: Visualization of LiNo's weight on ETTh1 dataset.

Figure 21: Visualization of LiNo's weight on ETTh2 dataset.

Figure 22: Visualization of LiNo's weight on ETTm1 dataset.

Figure 23: Visualization of LiNo's weight on ETTm2 dataset.

Figure 24: Visualization of LiNo's weight on Exchange dataset.

Figure 25: Visualization of LiNo's weight on PEMS03 dataset.

Figure 26: Visualization of LiNo's weight on PEMS04 dataset.

Figure 27: Visualization of LiNo's weight on PEMS07 dataset.

Figure 28: Visualization of LiNo's weight on PEMS08 dataset.

Figure 29: Visualization of LiNo's weight on Solar dataset.

Figure 30: Visualization of LiNo's weight on Traffic dataset.

Figure 31: Visualization of LiNo's weight on Weather dataset.

Table 11: Full results of the long-term forecasting task. The input sequence length is set to $T = 96$ for all baselines. *Avg* means the average results from all four prediction lengths.

Models		LiNo (Ours)		iTransformer (2024b)		Rlinear (2023a)		TSMixer (2023)		PatchTST (2023)		Crossformer (2023)		TiDE (2023)		TimesNet (2023)		DLinear (2023)		FEDformer (2022b)		Autoformer (2021)	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETTm1	96	0.322	0.361	0.334	0.368	0.355	0.376	0.323	0.363	0.329	0.367	0.404	0.426	0.364	0.387	0.338	0.375	0.345	0.372	0.379	0.419	0.505	0.475
	192	0.365	0.383	0.377	0.391	0.391	0.392	0.376	0.392	0.367	0.385	0.450	0.451	0.398	0.404	0.374	0.387	0.380	0.389	0.426	0.441	0.553	0.496
	336	0.401	0.408	0.426	0.420	0.424	0.415	0.407	0.413	0.399	0.410	0.532	0.515	0.428	0.425	0.410	0.411	0.413	0.413	0.445	0.459	0.621	0.537
	720	0.469	0.447	0.491	0.459	0.487	0.450	0.485	0.459	0.454	0.439	0.666	0.589	0.487	0.461	0.478	0.450	0.474	0.453	0.543	0.490	0.671	0.561
	Avg	0.389	0.400	0.407	0.410	0.414	0.407	0.398	0.407	0.387	0.400	0.513	0.496	0.419	0.419	0.400	0.406	0.403	0.407	0.448	0.452	0.588	0.517
ETTm2	96	0.171	0.254	0.180	0.264	0.182	0.265	0.182	0.266	0.175	0.259	0.287	0.366	0.207	0.305	0.187	0.267	0.193	0.292	0.203	0.287	0.255	0.339
	192	0.237	0.298	0.250	0.309	0.246	0.304	0.249	0.309	0.241	0.302	0.414	0.492	0.290	0.364	0.249	0.309	0.284	0.362	0.269	0.328	0.281	0.340
	336	0.296	0.336	0.311	0.348	0.307	0.342	0.309	0.347	0.305	0.343	0.597	0.542	0.377	0.422	0.321	0.351	0.369	0.427	0.325	0.366	0.339	0.372
	720	0.395	0.393	0.412	0.407	0.407	0.398	0.416	0.408	0.402	0.400	1.730	1.042	0.588	0.524	0.408	0.403	0.554	0.522	0.421	0.415	0.433	0.432
	Avg	0.275	0.320	0.288	0.332	0.286	0.327	0.289	0.333	0.281	0.326	0.757	0.610	0.358	0.404	0.291	0.333	0.350	0.401	0.305	0.349	0.327	0.371
ETTh1	96	0.378	0.395	0.386	0.405	0.386	0.395	0.401	0.412	0.414	0.419	0.423	0.448	0.479	0.464	0.384	0.402	0.386	0.400	0.376	0.419	0.449	0.459
	192	0.423	0.423	0.441	0.436	0.437	0.424	0.452	0.442	0.460	0.445	0.471	0.474	0.525	0.492	0.436	0.429	0.437	0.432	0.420	0.448	0.500	0.482
	336	0.455	0.438	0.487	0.458	0.479	0.446	0.492	0.463	0.501	0.466	0.570	0.546	0.565	0.515	0.491	0.469	0.481	0.459	0.459	0.465	0.521	0.496
	720	0.459	0.456	0.503	0.491	0.481	0.470	0.507	0.490	0.500	0.488	0.653	0.621	0.594	0.558	0.521	0.500	0.519	0.516	0.506	0.507	0.514	0.512
	Avg	0.429	0.428	0.454	0.447	0.446	0.434	0.463	0.452	0.469	0.454	0.529	0.522	0.541	0.507	0.458	0.450	0.456	0.452	0.440	0.460	0.496	0.487
ETTh2	96	0.292	0.340	0.297	0.349	0.288	0.338	0.319	0.361	0.302	0.348	0.745	0.584	0.400	0.440	0.340	0.374	0.333	0.387	0.358	0.397	0.346	0.388
	192	0.375	0.391	0.380	0.400	0.374	0.390	0.402	0.410	0.388	0.400	0.877	0.656	0.528	0.509	0.402	0.414	0.477	0.476	0.429	0.439	0.456	0.452
	336	0.418	0.426	0.428	0.432	0.415	0.426	0.444	0.446	0.426	0.433	1.043	0.731	0.643	0.571	0.452	0.452	0.594	0.541	0.496	0.487	0.482	0.486
	720	0.422	0.441	0.427	0.445	0.420	0.440	0.441	0.450	0.431	0.446	1.104	0.763	0.874	0.679	0.462	0.468	0.831	0.657	0.463	0.474	0.515	0.511
	Avg	0.377	0.400	0.383	0.407	0.374	0.398	0.401	0.417	0.387	0.407	0.942	0.684	0.611	0.550	0.414	0.427	0.559	0.515	0.437	0.449	0.450	0.459
ECL	96	0.138	0.233	0.148	0.240	0.201	0.281	0.157	0.260	0.181	0.270	0.219	0.314	0.237	0.329	0.168	0.272	0.197	0.282	0.193	0.308	0.201	0.317
	192	0.155	0.250	0.162	0.253	0.201	0.283	0.173	0.274	0.188	0.274	0.231	0.322	0.236	0.330	0.184	0.289	0.196	0.285	0.201	0.315	0.222	0.334
	336	0.171	0.267	0.178	0.269	0.215	0.298	0.192	0.295	0.204	0.293	0.246	0.337	0.249	0.344	0.198	0.300	0.209	0.301	0.214	0.329	0.231	0.338
	720	0.191	0.290	0.225	0.317	0.257	0.331	0.223	0.318	0.246	0.324	0.280	0.363	0.284	0.373	0.220	0.320	0.245	0.333	0.246	0.355	0.254	0.361
	Avg	0.164	0.260	0.178	0.270	0.219	0.298	0.186	0.287	0.205	0.290	0.244	0.334	0.251	0.344	0.192	0.295	0.212	0.300	0.214	0.327	0.227	0.338
Exchange	96	0.084	0.203	0.086	0.206	0.093	0.217	0.089	0.211	0.088	0.205	0.256	0.367	0.094	0.218	0.107	0.234	0.088	0.218	0.148	0.278	0.197	0.323
	192	0.176	0.298	0.177	0.299	0.184	0.307	0.177	0.302	0.176	0.299	0.470	0.509	0.184	0.307	0.226	0.344	0.176	0.315	0.271	0.315	0.300	0.369
	336	0.316	0.409	0.331	0.417	0.351	0.432	0.327	0.415	0.301	0.397	1.268	0.883	0.349	0.431	0.367	0.448	0.313	0.427	0.460	0.427	0.509	0.524
	720	0.823	0.682	0.847	0.691	0.886	0.714	0.912	0.727	0.901	0.714	1.767	1.068	0.852	0.698	0.964	0.746	0.839	0.695	1.195	0.695	1.447	0.941
	Avg	0.350	0.398	0.360	0.403	0.378	0.417	0.376	0.414	0.367	0.404	0.940	0.707	0.370	0.413	0.416	0.443	0.354	0.414	0.519	0.429	0.613	0.539
Traffic	96	0.429	0.276	0.395	0.268	0.649	0.389	0.493	0.336	0.462	0.295	0.522	0.290	0.805	0.493	0.593	0.321	0.650	0.396	0.587	0.366	0.613	0.388
	192	0.450	0.289	0.417	0.276	0.601	0.366	0.497	0.351	0.466	0.296	0.530	0.293	0.756	0.474	0.617	0.336	0.598	0.370	0.604	0.373	0.616	0.382
	336	0.468	0.297	0.433	0.283	0.609	0.369	0.528	0.361	0.482	0.304	0.558	0.305	0.762	0.477	0.629	0.336	0.605	0.373	0.621	0.383	0.622	0.337
	720	0.514	0.320	0.467	0.302	0.647	0.387	0.569	0.380	0.514	0.322	0.589	0.328	0.719	0.449	0.640	0.350	0.645	0.394	0.626	0.382	0.660	0.408
	Avg	0.465	0.296	0.428	0.282	0.626	0.378	0.522	0.357	0.481	0.304	0.550	0.304	0.760	0.473	0.620	0.336	0.625	0.383	0.610	0.376	0.628	0.379
Weather	96	0.154	0.199	0.174	0.214	0.192	0.232	0.166	0.210	0.177	0.218	0.158	0.230	0.202	0.261	0.172	0.220	0.196	0.255	0.217	0.296	0.266	0.336
	192	0.205	0.248	0.221	0.254	0.240	0.271	0.215	0.256	0.225	0.259	0.206	0.277	0.242	0.298	0.219	0.261	0.237	0.296	0.276	0.336	0.307	0.367
	336	0.262	0.290	0.278	0.296	0.292	0.307	0.287	0.300	0.278	0.297	0.272	0.335	0.287	0.335	0.280	0.306	0.283	0.335	0.339	0.380	0.359	0.395
	720	0.343	0.342	0.358	0.347	0.364	0.353	0.355	0.348	0.354	0.348	0.398	0.418	0.351	0.386	0.365	0.359	0.345	0.381	0.403	0.428	0.419	0.428
	Avg	0.241	0.270	0.258	0.278	0.272	0.291	0.256	0.279	0.259	0.281	0.259	0.315	0.271	0.320	0.259	0.287	0.265	0.317	0.309	0.360	0.338	0.382
Solar-Energy	96	0.200	0.250	0.203	0.237	0.322	0.339	0.221	0.275	0.234	0.286	0.310	0.331	0.312	0.399	0.250	0.292	0.290	0.378	0.242	0.342	0.884	0.711
	192	0.225	0.265	0.233	0.261	0.359	0.356	0.268	0.306	0.267	0.310	0.734	0.725	0.339	0.416	0.296	0.318	0.320	0.398	0.285	0.380	0.834	0.692
	336	0.243	0.283	0.248	0.273	0.397	0.369	0.272	0.294	0.290	0.315	0.750	0.735	0.368	0.430	0.319	0.330	0.353	0.415	0.282	0.376	0.941	0.723
	720	0.250	0.283	0.249	0.275	0.397	0.356	0.281	0.313	0.289	0.317	0.769	0.765	0.370	0.425	0.338	0.337	0.356	0.413	0.357	0.427	0.882	0.717
	Avg	0.230	0.270	0.233	0.262	0.369	0.356	0.260	0.297	0.270	0.307	0.641	0.639	0.347	0.417	0.301	0.319	0.330	0.401	0.291	0.381	0.885	0.711
1st Count		28	29	6	10	5	4	0	0	4	2	0	0	0	0	0	0	0	0	2	0	0	0

Table 12: Full results of the PEMS forecasting task. The input length is set to $T = 96$ for all baselines. *Avg* means the average results from all four prediction lengths.

Models		LiNo (Ours)		iTransformer (2024b)		Rlinear (2023a)		TSMixer (2023)		PatchTST (2023)		Crossformer (2023)		TiDE (2023)		TimesNet (2023)		DLinear (2023)		FEDformer (2022b)		Autoformer (2021)	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
PEMS03	12	**0.061**	**0.163**	0.071	0.174	0.126	0.236	0.075	0.186	0.099	0.216	0.090	0.203	0.178	0.305	0.085	0.192	0.122	0.243	0.126	0.251	0.272	0.385
	24	**0.077**	**0.181**	0.093	0.201	0.246	0.334	0.095	0.210	0.142	0.259	0.121	0.240	0.257	0.371	0.118	0.223	0.201	0.317	0.149	0.275	0.334	0.440
	48	**0.113**	**0.217**	0.125	0.236	0.551	0.529	0.121	0.240	0.211	0.319	0.202	0.317	0.379	0.463	0.155	0.260	0.333	0.425	0.227	0.348	1.032	0.782
	96	**0.132**	**0.225**	0.164	0.275	1.057	0.787	0.184	0.295	0.269	0.370	0.262	0.367	0.490	0.539	0.228	0.317	0.457	0.515	0.348	0.434	1.031	0.796
	Avg	**0.096**	**0.197**	0.113	0.221	0.495	0.472	0.119	0.233	0.180	0.291	0.169	0.281	0.326	0.419	0.147	0.248	0.278	0.375	0.213	0.327	0.667	0.601
PEMS04	12	**0.069**	**0.169**	0.078	0.183	0.138	0.252	0.079	0.188	0.105	0.224	0.098	0.218	0.219	0.340	0.087	0.195	0.148	0.272	0.138	0.262	0.424	0.491
	24	**0.081**	**0.184**	0.095	0.205	0.258	0.348	0.089	0.201	0.153	0.275	0.131	0.256	0.292	0.398	0.103	0.215	0.224	0.340	0.177	0.293	0.459	0.509
	48	**0.103**	**0.212**	0.120	0.233	0.572	0.544	0.111	0.222	0.229	0.339	0.205	0.326	0.409	0.478	0.136	0.250	0.355	0.437	0.270	0.368	0.646	0.610
	96	0.137	**0.247**	0.150	0.262	1.137	0.820	**0.133**	0.247	0.291	0.389	0.402	0.457	0.492	0.532	0.190	0.303	0.452	0.504	0.341	0.427	0.912	0.748
	Avg	**0.098**	**0.203**	0.111	0.221	0.526	0.491	0.103	0.215	0.195	0.307	0.209	0.314	0.353	0.437	0.129	0.241	0.295	0.388	0.231	0.337	0.610	0.590
PEMS07	12	**0.055**	**0.146**	0.067	0.165	0.118	0.235	0.073	0.181	0.095	0.207	0.094	0.200	0.173	0.304	0.082	0.181	0.115	0.242	0.109	0.225	0.199	0.336
	24	**0.070**	**0.162**	0.088	0.190	0.242	0.341	0.090	0.199	0.150	0.262	0.139	0.247	0.271	0.383	0.101	0.204	0.210	0.329	0.125	0.244	0.323	0.420
	48	**0.095**	**0.189**	0.110	0.215	0.562	0.541	0.124	0.231	0.253	0.340	0.311	0.369	0.446	0.495	0.134	0.238	0.398	0.458	0.165	0.288	0.390	0.470
	96	**0.132**	**0.225**	0.139	0.245	1.096	0.795	0.163	0.255	0.346	0.404	0.396	0.442	0.628	0.577	0.181	0.279	0.594	0.533	0.262	0.376	0.554	0.578
	Avg	**0.088**	**0.181**	0.101	0.204	0.504	0.478	0.112	0.217	0.211	0.303	0.235	0.315	0.380	0.440	0.124	0.225	0.329	0.395	0.165	0.283	0.367	0.451
PEMS08	12	**0.070**	**0.166**	0.079	0.182	0.133	0.247	0.083	0.189	0.168	0.232	0.165	0.214	0.227	0.343	0.112	0.212	0.154	0.276	0.173	0.273	0.436	0.485
	24	**0.093**	**0.190**	0.115	0.219	0.249	0.343	0.117	0.226	0.224	0.281	0.215	0.260	0.318	0.409	0.141	0.238	0.248	0.353	0.210	0.301	0.467	0.502
	48	**0.140**	**0.227**	0.186	0.235	0.596	0.544	0.196	0.299	0.321	0.354	0.315	0.355	0.497	0.510	0.198	0.283	0.440	0.470	0.320	0.394	0.966	0.733
	96	0.247	0.283	**0.221**	**0.267**	1.166	0.814	0.266	0.331	0.408	0.417	0.377	0.397	0.721	0.592	0.320	0.351	0.674	0.565	0.442	0.465	1.385	0.915
	Avg	**0.138**	**0.217**	0.150	0.226	0.529	0.487	0.165	0.261	0.280	0.321	0.268	0.307	0.441	0.464	0.193	0.271	0.379	0.416	0.286	0.358	0.814	0.659
1st Count		**18**	**19**	1	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Table 13: Full univariate forecasting results with prediction lengths $F \in \{96, 192, 336, 720\}$ and fixed lookback winodw $T = 96$ for all datasets.

Models		LiNo (Ours)		MICN (2023)		FEDformer (2022b)		Autoformer (2021)		Informer (2022a)		LogTrans (2019)	
Metric		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
ETTm1	96	**0.029**	**0.126**	0.033	0.134	0.033	0.140	0.056	0.183	0.109	0.277	0.049	0.171
	192	**0.044**	**0.160**	0.048	0.164	0.058	0.186	0.081	0.216	0.151	0.310	0.157	0.317
	336	**0.058**	**0.185**	0.079	0.210	0.084	0.231	0.076	0.218	0.427	0.591	0.289	0.459
	720	**0.081**	**0.217**	0.096	0.233	0.102	0.250	0.110	0.267	0.438	0.586	0.430	0.579
	Avg	**0.053**	**0.172**	0.064	0.185	0.069	0.202	0.081	0.221	0.281	0.441	0.231	0.382
ETTm2	96	0.066	0.185	**0.059**	**0.176**	0.067	0.198	0.065	0.189	0.088	0.225	0.075	0.208
	192	**0.100**	0.235	0.100	**0.234**	0.102	0.245	0.118	0.256	0.132	0.283	0.129	0.275
	336	**0.130**	**0.273**	0.153	0.301	0.130	0.279	0.154	0.305	0.180	0.336	0.154	0.302
	720	**0.176**	**0.328**	0.210	0.354	0.178	0.325	0.182	0.335	0.300	0.435	0.160	0.321
	Avg	**0.118**	**0.255**	0.131	0.266	0.119	0.262	0.130	0.271	0.175	0.320	0.130	0.277
ETTh1	96	**0.056**	**0.180**	0.058	0.186	0.079	0.215	0.071	0.206	0.193	0.377	0.283	0.468
	192	**0.071**	**0.203**	0.079	0.210	0.104	0.245	0.114	0.262	0.217	0.395	0.234	0.409
	336	**0.085**	**0.228**	0.092	0.237	0.119	0.270	0.107	0.258	0.202	0.381	0.386	0.546
	720	**0.082**	**0.226**	0.138	0.298	0.142	0.299	0.126	0.283	0.183	0.355	0.475	0.628
	Avg	**0.074**	**0.209**	0.092	0.233	0.111	0.257	0.105	0.252	0.199	0.377	0.345	0.513
ETTh2	96	**0.127**	0.273	0.155	0.300	0.128	**0.271**	0.153	0.306	0.213	0.373	0.217	0.379
	192	0.176	0.326	**0.169**	**0.316**	0.185	0.330	0.204	0.351	0.227	0.387	0.281	0.429
	336	**0.203**	**0.359**	0.238	0.384	0.231	0.378	0.246	0.389	0.242	0.401	0.293	0.437
	720	**0.214**	**0.371**	0.447	0.561	0.278	0.420	0.268	0.409	0.291	0.439	0.218	0.387
	Avg	**0.180**	**0.332**	0.252	0.390	0.206	0.350	0.218	0.364	0.243	0.400	0.252	0.408
Traffic	96	**0.138**	**0.214**	0.158	0.241	0.207	0.312	0.246	0.346	0.257	0.353	0.226	0.317
	192	**0.134**	**0.214**	0.154	0.236	0.205	0.312	0.266	0.370	0.299	0.376	0.314	0.408
	336	**0.142**	**0.223**	0.165	0.243	0.219	0.323	0.263	0.371	0.312	0.387	0.387	0.453
	720	**0.160**	**0.238**	0.182	0.264	0.244	0.344	0.269	0.372	0.366	0.436	0.491	0.437
	Avg	**0.143**	**0.222**	0.165	0.246	0.219	0.323	0.261	0.365	0.309	0.388	0.355	0.404
Weather	96	**0.0012**	**0.026**	0.0029	0.039	0.0062	0.062	0.0110	0.081	0.0038	0.044	0.0046	0.052
	192	**0.0015**	**0.029**	0.0021	0.034	0.0060	0.062	0.0075	0.067	0.0023	0.040	0.0056	0.060
	336	**0.0016**	**0.029**	0.0023	0.034	0.0041	0.050	0.0063	0.062	0.0041	0.049	0.0060	0.054
	720	**0.0021**	**0.035**	0.0048	0.054	0.0055	0.059	0.0085	0.070	0.0031	0.042	0.0071	0.063
	Avg	**0.0016**	**0.030**	0.0030	0.040	0.0055	0.058	0.0083	0.070	0.0033	0.044	0.0058	0.057
1st Count		**28**	**25**	2	3	0	2	0	0	0	0	0	0