Graph Inverse Reinforcement Learning from Diverse Videos

Figure 1: **GraphIRL.** We propose an approach for performing inverse reinforcement learning from diverse third-person videos via graph abstraction. Based on our learned reward functions, we successfully train image-based policies in simulation and deploy them on a real robot.

Abstract

Research on Inverse Reinforcement Learning (IRL) from third-person videos has shown encouraging results on removing the need for manual reward design for robotic tasks. However, most prior works are still limited by training from a relatively restricted domain of videos. In this paper, we argue that the true potential of third-person IRL lies in increasing the diversity of videos for better scaling. To learn a reward function from diverse videos, we propose to perform graph abstraction on the videos followed by temporal matching in the graph space to measure the task progress. Our insight is that a task can be described by entity interactions that form a graph, and this graph abstraction can help remove irrelevant information such as textures, resulting in more robust reward functions. We evaluate our approach, *GraphIRL*, on cross-embodiment learning in X-MAGICAL and learning from human demonstrations for real-robot manipulation. We show significant improvements in robustness to diverse video demonstrations over previous approaches, and even achieve better results than manual reward design on a real robot pushing task. Videos are available at `https://graphirl.github.io/`.

1 Introduction

Deep Reinforcement Learning (RL) is a powerful general-purpose framework for learning behavior policies from high-dimensional interaction data, and has led to a multitude of impressive feats

in application areas such as game-playing [29] and robotics [24, 2]. Through interaction with an unknown environment, RL agents iteratively improve their policy by learning to maximize a reward signal, which has the potential to be used in lieu of hand-crafted control policies. However, the performance of policies learned by RL is found to be highly dependent on the careful specification of task-specific reward functions and, as a result, crafting a good reward function may require significant domain knowledge and technical expertise.

As an alternative to manual design of reward functions, *inverse RL* (IRL) has emerged as a promising paradigm for policy learning. By framing the reward specification as a learning problem, operators can specify a reward function based on video examples. While *imitation learning* typically requires demonstrations from a first-person perspective, IRL can in principle learn a reward function, *i.e.*, a measure of task progression, from *any* perspective, including third-person videos of humans performing a task. This has positive implications for data collection, since it is often far easier for humans to capture demonstrations in third-person.

Although IRL from third-person videos is appealing because of its perceived flexibility, learning a good reward function from raw video data comes with a variety of challenges. This is perhaps unsurprising, considering the visual and functional diversity that such data contains. For example, the task of pushing an object across a table may require different motions depending on the embodiment of the agent. A recent method for cross-embodiment IRL, dubbed XIRL [56], learns to capture task progression from videos in a self-supervised manner by enforcing temporal cycle-consistency constraints. While XIRL can in principle consume any video demonstration, we observe that its ability to learn task progression degrades substantially when the visual appearance of the video demonstrations do not match that of the target environment for RL. Therefore, it is natural to ask the question: *can we learn to imitate others from (a limited number of) diverse third-person videos?*

In this work, we demonstrate that it is indeed possible. Our key insight is that, while videos may be of great visual diversity, their underlying scene structure and agent-object interactions can be abstracted via a graph representation. Specifically, instead of directly using images, we extract object bounding boxes from each frame using an off-the-shelf detector, and construct a graph abstraction where each object is represented as a node in the graph. Often – in robotics tasks – the spatial location of an object by itself may not convey the full picture of the task at hand. For instance, to understand a task like *Peg in Box* (shown in Figure 1), we need to also take into account how the agent *interacts* with the object. Therefore, we propose to employ *Interaction Networks* [7] on our graph representation to explicitly model interactions between entities. To train our model, we follow [56, 9] and apply a temporal cycle consistency loss, which (in our framework) yields task-specific yet embodiment- and domain-agnostic feature representations.

We validate our method empirically on a set of simulated cross-domain cross-embodiment tasks from X-MAGICAL [56], as well as three vision-based robotic manipulation tasks. To do so, we collect a diverse set of demonstrations that vary in visual appearance, embodiment, object categories, and scene configuration; X-MAGICAL demonstrations are collected in simulation, whereas our manipulation demonstrations consist of real-world videos of humans performing tasks. We find our method to outperform a set of strong baselines when learning from visually diverse demonstrations, while simultaneously matching their performance in absence of diversity. Further, we demonstrate that vision-based policies trained with our learned reward perform tasks with greater precision than human-designed reward functions, and successfully transfer to a real robot setup with only approximate correspondence to the simulation environment. Thus, our proposed framework completes the cycle of learning rewards from real-world human demonstrations, learning a policy in simulation using learned rewards, and finally deployment of the learned policy on physical hardware.

2   Related Work

Learning from demonstration. Conventional imitation learning methods require access to expert demonstrations comprised of observations and corresponding ground-truth actions for every time step [32, 5, 3, 36], for which kinesthetic teaching or teleoperation are the primary modes of data collection in robotics. To scale up learning, video demonstrations are recorded with human operating the same gripper that the robot used, which also allows direct behaviro cloning [43, 55]. More recently, researchers have developed methods that instead infer actions from data via a learned forward [31] or inverse [45, 35] dynamics model. However, this approach still makes the implicit assumption

Figure 2: **Overview.** We extract object bounding boxes from video sequences using an off-the-shelf detector, and construct a graph abstraction of the scene. We model graph-abstracted object interactions using *Interaction Networks* [7], and learn a reward function by aligning video embeddings temporally. We then train image-based RL policies using our learned reward function, and deploy on a real robot.

that imitator and demonstrator share a common observation and action space, and are therefore not directly applicable to the cross-domain cross-embodiment problem setting that we consider.

Inverse RL. To address the aforementioned limitations, inverse RL has been proposed [30, 1, 19, 12, 6, 46] and it has recently emerged as a promising paradigm for cross-embodiment imitation in particular [39, 21, 49, 23, 8, 11, 34, 56, 4]. For example, Schmeckpeper et al. [39] proposes a method for integrating video demonstrations without corresponding actions into off-policy RL algorithms via a latent inverse dynamics model and heuristic reward assignment, and Zakka et al. [56] (XIRL) learns a reward function from video demonstrations using temporal cycle-consistency and trains an RL agent to maximize the learned rewards. In practice, however, inverse RL methods such as XIRL are found to require limited visual diversity in demonstrations. Our work extends XIRL to the setting of diverse videos by introducing a graph abstraction that models agent-object and object-object interactions while still enforcing temporal cycle-consistency.

Object-centric representations. have been proposed in many forms at the intersection of computer vision and robotics. For example, object-centric scene graphs can be constructed for integrated task and motion planning [10, 44, 57], navigation [14, 51], relational inference [50, 25],dynamics modeling [7, 48, 28, 53, 33**?**], model predictive control [38, 26, 54], grasping [**? ?**] or visual imitation learning [**? ?** 42]. Similar to our work, Sieb et al. [42] propose to abstract video demonstrations as object-centric graphs for the problem of single-video cross-embodiment imitation, and act by minimizing the difference between the demonstration graph and a graph constructed from observations captured at each step. As such, their method is limited to same-domain visual trajectory following, whereas we learn a general alignment function for cross-domain cross-embodiment imitation and leverage *Interaction Networks* [7] for modeling graph-abstracted spatial interactions rather than relying on heuristics.

3   Our Approach

In this section, we describe our main contribution, which is a self-supervised method for learning a reward function directly from a set of diverse third-person video demonstrations by applying temporal matching on graph abstractions. Our Graph Inverse Reinforcement Learning (GraphIRL) framework, shown in Figure 2, consists of building an object-centric graph abstraction of the video demonstrations and then learn an embedding space that captures task progression by exploiting the temporal cue

102 in the videos. This embedding space is then used to construct a *domain invariant* and *embodiment*
103 *invariant* reward function which can be used to train any standard reinforcement learning algorithm.

104 **Problem Formulation.** Given a task T, our approach takes a dataset of video demonstrations
105 $D = \{V_1, V_2, \ldots, V_n\}$. Each video consists of image frames $\{I_1^i, I_2^i, \ldots, I_k^i\}$ where i denotes the
106 video frame index and k denotes the total number of frames in V_i. Given D, our goal is to learn a
107 reward function that can be used to solve the task T for any robotic environment. Notably, we do *not*
108 assume access to any action information of the expert demonstrations, and our approach does *not*
109 require objects or embodiments in the target environment to share appearance with demonstrations.

3.1 Representation Learning

111 To learn task-specific representations in a self-supervised manner, we take inspiration from Dwibedi
112 et al. [9] and employ a temporal cycle consistency loss. However, instead of directly using images,
113 we propose a novel object-centric graph representation, which allows us to learn an embedding space
114 that not only captures task-specific features, but depends *solely* on the spatial configuration of objects
115 and their interactions. We here detail each component of our approach to representation learning.

116 **Object-Centric Representation.** Given video frames $\{I_1^i, I_2^i, \ldots, I_k^i\}$, we first extract object bound-
117 ing boxes from each frame using an off-the-shelf detector. Given N bounding boxes for an image, we
118 represent each bounding box as a $4 + m$ dimensional vector $o_j = \{x_1, y_1, x_2, y_2, d_1, d_2, \ldots, d_m\}$,
119 where the first 4 dimensions represent the leftmost and rightmost corners of the bounding box, and
120 the remaining m dimensions encode distances between the centroids of the objects. For each frame
121 I_j^i we extract an object-centric representation $I_j'^i = \{o_1, o_2, \ldots, o_m\}$ such that we can represent our
122 dataset of demonstrations as $D' = \{V_1', V_2', \ldots, V_n'\}$ where V_i' is the sequence of bounding boxes
123 corresponding to video V_i. Subsequent sections describe how we learn representations given D'.

124 **Spatial Interaction Encoder.** Taking inspiration from recent approaches on modeling physical
125 object dynamics [7, 48], we propose a *Spatial Interaction Encoder Network* to explicitly model
126 object-object interactions. Specifically, given a sequence V_i' from D', we model each element I'
127 as a graph, $G = (O, R)$, where O is the set of objects $\{o_1, o_2, \ldots, o_m\}$, m is the total number of
128 objects in I', and R denotes the relationship between objects (*i.e.*, whether two objects interact with
129 each other). For simplicity, all objects are connected with all other objects in the graph such that
130 $R = \{(i, j) \mid i \neq j \land i \leq m \land j \leq m\}$. We use a fully-connected graph because this makes the least
131 assumption about the problem and task specific object interaction structure could then be learned
132 directly from the data. We compose an object embedding for each of $o_i \in O$ by combining *self* and
133 *interactional* representations as follows:

$$f_o(o_i) = \phi_{\text{agg}}(f_s + f_{\text{in}}) \quad \text{with} \quad f_s(o_i) = \phi_s(o), \quad f_{\text{in}}(o_i) = \sum_{j=1}^{m} \phi_{\text{in}}((o_i, o_j)) \mid (i, j) \in \mathbb{R}, \quad (1)$$

134 where $f_s(o_i)$ represents the *self* or independent representation of an object, f_{in} represents the
135 *interactional* representation, *i.e.*, how it interacts with other objects in the scene, f_o is the final object
136 embedding, and $(,)$ represents concatenation. Here, the encoders ϕ_s, ϕ_{in} and ϕ_{agg} denote Multi layer
137 Perceptron (MLP) networks respectively. We emphasize that the expression for $f_{\text{in}}(\cdot)$ implies that
138 the object embedding $f_o(.)$ depends on *all* other objects in the scene; this term allows us to model
139 relationships of an object with the others. The final output from the spatial interaction encoder $\psi(\cdot)$
140 for object representation I' is the mean of all object encodings:

$$\psi(I') = \frac{1}{m} \sum_{i}^{m} f(o_i). \quad (2)$$

141 The spatial interaction encoder is then optimized using the temporal alignment loss introduced next.

142 **Temporal Alignment Loss**. Taking inspiration from prior works on video representation learning
143 [9, 18, 27, 47, 16], we employ the task of temporal alignment for learning task-specific representations.
144 Given a pair of videos, the task of self-supervised alignment implicitly assumes that there exists true
145 semantic correspondence between the two sequences, *i.e.*, both videos share a common semantic
146 space. These works have shown that optimizing for alignment leads to representations that could
147 be used for tasks that require understanding task progression such as action-classification. This is
148 because in order to solve for alignment, a learning model has to learn features that are (1) common
149 across most videos and (2) exhibit temporal ordering. For a sufficiently large dataset with single task,

the most common visual features would be distinct phases of a task that appear in all videos and if the task has small permutations, these distinct features would also exhibit temporal order. In such scenarios, the representations learned by optimizing for alignment are *task-specific* and invariant to changes in viewpoints, appearances and actor embodiments.

In this work, we employ Temporal Cycle Consistency (TCC) [9] loss to learn temporal alignment. TCC optimizes for alignment by learning an embedding space that maximizes one-to-one nearest neighbour mappings between sequences. This is achieved through a loss that maximizes for cycle-consistent nearest neighbours given a pair of video sequences. In our case, the cycle consistency is applied on the *graph abstraction* instead of image features as done in the aforementioned video alignment methods. Specifically, given D', we sample a pair of bounding box sequences $V_i' = \{I_1'^i, \ldots, I_{m_i}'^i\}$ and $V_j' = \{I'^j_1, \ldots, I_{m_j}'^j\}$ and extract embeddings by applying the spatial interaction encoder defined in Equation 2. Thus, we obtain the encoded features $S_i = \{\psi(I_1'^i), \ldots, \psi(I_{m_i}'^i)\}$ and $S_j = \{\psi(I_1'^j), \ldots, \psi(I_{m_j}'^j)\}$. For the nth element in S_i, we first compute its nearest neighbour, υ_{ij}^n, in S_j and then compute the probability that it cycles-back to the kth frame in S_i as:

$$\beta_{ijn}^k = \frac{e^{-||\upsilon_{ij}^n - S_i^k||^2}}{\sum_k^{m_j} e^{-||\upsilon_{ij}^n - S_i^k||^2}} \, , \upsilon_{ij}^n = \sum_k^{m_j} \alpha_k s_j^k \, , \alpha_k = \frac{e^{-||S_i^n - S_j^k||^2}}{\sum_k^{m_j} e^{-||S_i^n - S_j^k||^2}} \, . \tag{3}$$

The cycle consistency loss for nth element can be computed as $L_n^{ij} = (\mu_{ij}^n - n)^2$, where $\mu_{ij}^n = \sum_k^{mi} \beta_{ijn}^k k$ is the expected value of frame index n as we cycle back. The overall TCC loss is then defined by summing over all pairs of sequence embeddings (S_i, S_j) in the data, *i.e.*, $L_{ij}^n = \sum_{ijn} L_{ij}^n$.

3.2 Reinforcement Learning

We learn a task-specific embedding space by optimizing for temporal alignment. In this section, we define how to go from this embedding space to a reward function that measures task progression. For constructing the reward function, we leverage the insight from Zakka et al. [56] that in a task-specific embedding space, we can use euclidean distance as a notion of task progression, *i.e.*, frames far apart in the embedding space will be far apart in terms of task progression and vice versa. We therefore choose to define our reward function as

$$r(o) = -\frac{1}{c}||\psi(o) - g||^2 \, , \quad \text{with} \quad g = \sum_{i=1}^n \psi(I_{m_i}'^i) \, , \tag{4}$$

where o is the current observation, ψ is the Spatial Interaction Encoder Network from Section 3, g is the representative goal frame, m_i is the length of sequence V'^i and c is a scaling factor. The scaling factor c is computed as the average distance between the first and final observation of all the training videos in the learned embedding space. Note, that the range of the learned reward is $(-\infty, 0]$. Defining the reward function in this way gives us a dense reward because as the observed state gets closer and closer to the goal, the reward starts going down and approaches zero when the goal and current observation are close in embedding space. After constructing the learned reward, we can use it to train any standard RL algorithm. We note that, unlike previous approaches [39, 56], our method does not use *any* environment reward to improve performance, and instead relies *solely* on the learned reward, which our experiments demonstrate is sufficient for solving diverse robotic manipulation tasks.

4 Experiments

In this section, we demonstrate how our approach uses diverse video demonstrations to learn a reward function that generalizes to unseen domains. In particular, we are interested in answering the questions: (1) How do vision-based methods for IRL perform when learning from demonstrations that exhibit *domain shift*? and (2) is our approach capable of learning a stronger reward signal under this challenging setting? To that end, we first conduct experiments X-MAGICAL benchmark [56]. We then evaluate our approach on multiple robot manipulation tasks using a diverse set of demonstrations.

Implementation Details. All MLPs defined in Equation 2 have 2 layers followed by a ReLU activation, and the embedding layer outputs features of size 128 in all experiments. For training, we

Figure 3: **Overview of X-MAGICAL task variants.** We consider two environment variants and four embodiments for our simulated sweeping task experiments. Our work assesses the performance of IRL algorithms in both the *Diverse* and *Standard* environments across all four embodiments in the *Same-Embodiment* and *Cross-Embodiment settings*.

Figure 4: **Cross-Embodiment Cross-Environment.** Success rates of our method *GraphIRL* and baselines on *(top)* Standard Environment Pretraining → Diverse Environment RL and *(bottom)* Diverse Environment Pretraining → Standard Environment RL. All reported numbers are averaged over 5 seeds. Our approach performs favorably when compared to other baselines on both settings.

use ADAM [22] optimizer with a learning rate of 10^{-5}. We use Soft Actor-Critic (SAC) [15] as backbone RL algorithm for all methods. For experiments on X-MAGICAL, we follow Zakka et al. [56] and learn a state-based policy; RL training is performed for 500k steps for all embodiments. For robotic manipulation experiments, we learn a multi-view image-based SAC policy [20]. We train RL agent for 300k, 800k and 700k steps for *Reach*, *Push* and *Peg in Box* respectively. For fair comparison, we only change the learned reward function across methods and keep the RL setup identical. The success rates presented for all our experiments are averaged over 50 episodes. Refer to Appendix B for further implementation details.

Baselines. We compare against multiple vision-based approaches that learn rewards in a self-supervised manner: **(1) XIRL** [56] that learns a reward function by applying the TCC [9] loss on demonstration video sequences, **(2) TCN** [40] which is a self-supervised contrastive method for video representation learning that optimizes for temporally disentangled representations, and **(3) LIFS** [13] that learns an invariant feature space using a dynamic time warping-based contrastive loss. Lastly, we also compare against the manually designed **(4) Environment Rewards** from Jangir et al. [20]. The environment reward baseline is an oracle method since it is a dense reward and is carefully designed for the task under consideration. For vision-based baselines, we use a ResNet-18 encoder pretrained on ImageNet [37] classification. We use the hyperparameters, data augmentation schemes and network architectures provided in Zakka et al. [56] for all vision-based baselines. Please refer to Appendix E.1 for description of environment rewards and Zakka et al. [56] for details on the vision-based baselines.

4.1 Experimental Setup

We conduct experiments under two settings: the *Sweep-to-Goal* task from X-MAGICAL [56], and robotic manipulation tasks with an xArm robot both in simulation and on a real robot setup. We describe our experimental setup under these two settings in the following.

Figure 5: **Robotic Manipulation.** Success rates of our method *GraphIRL* and baselines on the tasks of *Reach*, *Push* and *Peg in Box*. All results are averaged over 5 seeds. We observe significant gains in performance specially over vision-based baselines due to large *domain-gap*

X-MAGICAL. We choose to extend X-MAGICAL [56], a 2D simulation environment for cross-embodiment imitation learning. On this benchmark, we consider a multi-object sweeping task, where the agent must push three objects towards a static goal region. We utilize two variants of the X-MAGICAL benchmark, which we denote as *Standard* (original) and *Diverse* (ours) environments, shown in Figure 3. *Standard* only randomizes the position of objects, whereas *Diverse* also randomizes visual appearance. We consider a set of four unique embodiments {*gripper, short-stick, medium-stick, long-stick*}. In particular, we conduct experiments in the *cross-environment* and *cross-embodiment setting* where we learn a reward function in the *Standard* environment on 3 held-out embodiments and do RL in the *Diverse* environment on 1 target embodiment, or vice-versa. This provides an additional layer of difficulty for the RL agent as visual randomizations show the brittleness of vision-based IRL methods. Refer to Appendix C for more details on performed randomizations.

Robotic Manipulation. Figure 1 shows initial and success configurations for each of the three task that we consider: **(1) Reach** in which the agent needs to reach a goal (red disc) with its end-effector, **(2) Push** in which the goal is to push a cube to a goal position, and **(3) Peg in Box** where the goal is to put a peg tied to the robot's end-effector inside a box. The last task is particularly difficult because it requires geometric 3D understanding of the objects. Further, a very specific trajectory is required to avoid collision with the box and complete the task. We collect a total of 256 and 162 video demonstrations for *Reach* and *Peg in Box*, respectively, and use 198 videos provided from Schmeckpeper et al. [39] for *Push*. The videos consist of human actors performing the same tasks but with a number of diverse objects and goal markers, as well as varied positions of objects. Unlike the data collected by Schmeckpeper et al. [39], we do not fix the goal position in our demonstrations. In order to detect objects in our training demonstrations, we use a trained model from Shan et al. [41]. The model is trained on a large-scale dataset collected from YouTube and can detect hands and objects in an image.; refer to Appendix E.2 for more details on data collection. Additionally, we do not require the demonstrations to resemble the robotic environment in terms of appearance or distribution of goal location. We use an xArm robot as our robot platform and capture image observations using a static third-person RGB camera in our real setup; details in Appendix G.

4.2 Results

X-MAGICAL. Results for the *cross-embodiment and cross-environment* setting are shown in Figure 4. When trained on *Standard*, our method performs significantly better than vision-based baselines (*e.g.*, 0.58 GraphIRL for gripper vs 0.35 for XIRL and 0.99 GraphIRL for longstick vs 0.56 XIRL). We conjecture that vision-based baselines struggle with visual variations in the environment, which our method is unaffected by due to its graph abstraction. Additionally, when trained on *diverse* environment, GraphIRL outperforms 3 out of 4 embodiments.

Robotic manipulation in simulation. In this section, we answer the core question of our work: *can we learn to imitate others from diverse third-person videos?* In particular, we collect human demonstrations for manipulation tasks as explained in Section 4.1 and learn a reward function as explained in Section 3. This is a challenging setting because as shown in Figure 1, the collected data and robotic environments belong to different domains and do not share any appearance characteristics. Further, unlike previous works [39, 56], we do not use any environment reward as an additional supervision to the reinforcement learning agent. Figure 5 presents our results. For the **Reach** task, GraphIRL and environment reward are able to achieve a success rate of 1.0, while other baseline

Real	XIRL	Env. Reward	GraphIRL (Ours)
Push	0.27	0.47	**0.60**
Reach	0.26	**0.93**	0.86
Peg in Box	0.06	**0.60**	0.53

Table 1: **Real robot experiments.** Success rate on robot manipulation tasks on physical hardware. We evaluate each method for 15 trials using a fixed set of goal and start state configurations. Best results are in **bold**.

Figure 6: Impact of reducing number of demonstrations. Results averaged over 5 seeds. For experiments with 100% demonstrations, we use 256, 198 and 162 videos for *Reach*, *Push* and *Peg in Box* respectively.

methods are substantially behind GraphIRL (e.g. 0.477 XIRL and 0.155 TCN). The poor performance of vision-based baselines could be attributed to substantial visual domain shift. Due to domain shift, the learned rewards for these baselines produce low rewards for successful episodes, please refer to Appendix A for a more detailed qualitative analysis. In the **Push** setting, we find that vision-based baseline methods still perform poorly. Similar to **Reach**, XIRL performs the best out of the vision-based baselines with a success rate of 0.187, and GraphIRL performs better than environment reward (e.g. 0.832 GraphIRL vs 0.512 Environment Reward). We find that for *Push*, the learned reward gives a much higher reward when the object gets very close to the goal as compared to the environment reward which is linearly proportional to negative distance between goal and object therefore the RL agent ends up learning a more precise policy when trained with the learned reward. This result shows clear advantage of our method as we are able to outperform a hand-designed reward function without using any task specific information. The **Peg in Box** task is rigorous to solve since it requires 3-d reasoning and a precise reward function. Here, while all vision-based methods fail, our GraphIRL method is able to solve the task with a success rate comparable to that achieved with the hand-designed environment reward. Overall, our GraphIRL method is able to solve 2D and 3D reasoning tasks with a real-robot without a hand-designed reward function or access to 3D scene information.

Real robot experiments. Finally, we deploy the learned policies on a real robot. For each experiment, we conduct 15 trials per method and report the average success rate. Results are shown in Table 1. Interestingly, we find that GraphIRL outperforms XIRL in all three tasks on the real robot setup (e.g. 0.26 XIRL vs 0.86 GraphIRL on *Reach* and 0.27 XIRL vs 0.60 GraphIRL on *Push*), and on *Push*, GraphIRL performs better than the environment reward specifically designed for the task (e.g. 0.47 Environment Reward vs 0.6 GraphIRL) which is in line with our findings in simulation.

4.3 Ablations

Impact of Modelling Spatial Interactions. We study the impact of modeling object-object spatial interactions using Spatial Interaction Encoder Network described in Section 3.1. Specifically, we replace our proposed encoder component with an Multi-Layer Perceptron (MLP) by concatenating representations of all objects into a single vector and then feeding it to a 3-layer MLP network. We denote this approach as *MLP* and the Spatial Interaction Encoder Network based approach

Variant	Success Rate
MLP	$0.61_{\pm 0.116}$
IN	$0.804_{\pm 0.054}$

Table 2: Impact of modelling object-object interaction on *Push* task. **MLP:** Multi-layer perceptron and **IN:** Spatial Interaction Network Encoder. Results over 5 seeds.

as *IN*. Results in Table 2. We observe that modeling object interactions leads to a 20% improvement in the RL success rate (i.e. 0.61 for MLP vs 0.804 for Interaction Networks).

Impact of Decreasing Number of Demonstration Videos. Results in Figure 6. We find that our approach is very data efficient and is capable of learning meaningful rewards even from a small number of videos. It achieves decent RL success rate with only 10% of total videos used (e.g. 72% for Push and 57.83% for Peg in Box). However, adding more video demonstrations generally leads to improved performance as expected.

5 Conclusions and Limitations

Conclusion. We demonstrate the effectiveness of our proposed method, *GraphIRL*, in a number of IRL settings with diverse third-person demonstrations. In particular, we show that our method successfully learns reward functions from human demonstrations with diverse objects and scene configurations, that we are able to train image-based policies in simulation using our learned rewards, and that policies trained with our learned rewards are more successful than both prior work and manually designed reward functions on a real robot. We also hereby commit to release our complete code and data to the public.

Limitations. while our method relaxes the requirements for human demonstrations, collecting the demonstrations still requires human labor; and although our results indicate that we can learn from relatively few videos, eliminating human labor entirely remains an open problem. Moreover, our approach assumes access to object bounding boxes. This implies that our method's performance is dependent on the performance of the object detector. Fortunately, 2d object detectors have become very reliable as we show in our experiments, we are able to use an off-the-shelf object detector to extract the bounding boxes without having to perform any manual labeling. Furthermore, the proposed graph abstraction allows us to solve tasks despite the large domain gap but it has some potential disadvantages too. In particular, we lose fine grained information such as object poses and precise object interactions which could be useful for complex tasks such as medical procedures. However, we conjecture that 2D images might also not be sufficient for such a task since inferring accurate object pose, 3D geometric information from a 2D image itself is a challenging problem. Finally, there are some forms of reward that cannot be learned using our approach. Specifically, we may not be able to learn rewards where a penalty is imposed for certain actions or rewards for tasks where the progress towards task completion cannot be defined at all by object configuration.

References

[1] Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *ICML*, 2004.

[2] OpenAI Marcin Andrychowicz, Bowen Baker, Maciek Chociej, R. Józefowicz, Bob McGrew, Jakub W. Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, S. Sidor, Joshua Tobin, P. Welinder, Lilian Weng, and Wojciech Zaremba. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39:20 – 3, 2020.

[3] Brenna Argall, Sonia Chernova, Manuela Veloso, and Brett Browning. A survey of robot learning from demonstration. *Robotics and Autonomous Systems*, 57:469–483, 05 2009.

[4] Sridhar Pandian Arunachalam, Sneha Silwal, Ben Evans, and Lerrel Pinto. Dexterous imitation made easy: A learning-based framework for efficient dexterous manipulation. *arXiv preprint arXiv:2203.13251*, 2022.

[5] Christopher G. Atkeson and Stefan Schaal. Robot learning from demonstration. In *ICML*, 1997.

[6] Yusuf Aytar, Tobias Pfaff, David Budden, Thomas Paine, Ziyu Wang, and Nando de Freitas. Playing hard exploration games by watching youtube. In *NIPS*, 2018.

[7] Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, et al. Interaction networks for learning about objects, relations and physics. *Advances in neural information processing systems*, 29, 2016.

[8] Annie S Chen, Suraj Nair, and Chelsea Finn. Learning generalizable robotic reward functions from" in-the-wild" human videos. *arXiv preprint arXiv:2103.16817*, 2021.

[9] Debidatta Dwibedi, Yusuf Aytar, Jonathan Tompson, Pierre Sermanet, and Andrew Zisserman. Temporal cycle-consistency learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1801–1810, 2019.

[10] Georgios Fainekos, Antoine Girard, Hadas Kress-Gazit, and George J. Pappas. Temporal logic motion planning for dynamic robots. *Autom.*, 45:343–352, 2009.

[11] Arnaud Fickinger, Samuel Cohen, Stuart Russell, and Brandon Amos. Cross-domain imitation learning via optimal transport. *arXiv preprint arXiv:2110.03684*, 2021.

[12] Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv*, 2017.

[13] Abhishek Gupta, Coline Devin, YuXuan Liu, Pieter Abbeel, and Sergey Levine. Learning invariant feature spaces to transfer skills with reinforcement learning. *arXiv preprint arXiv:1703.02949*, 2017.

[14] Saurabh Gupta, Varun Tolani, James Davidson, Sergey Levine, Rahul Sukthankar, and Jitendra Malik. Cognitive mapping and planning for visual navigation. *International Journal of Computer Vision*, 128:1311–1330, 2019.

[15] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement, 2018.

[16] Isma Hadji, Konstantinos G Derpanis, and Allan D Jepson. Representation learning via global temporal alignment and cycle-consistency. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11068–11077, 2021.

[17] Nicklas Hansen, Hao Su, and Xiaolong Wang. Stabilizing deep q-learning with convnets and vision transformers under data augmentation. *Advances in Neural Information Processing Systems*, 34:3680–3693, 2021.

[18] Sanjay Haresh, Sateesh Kumar, Huseyin Coskun, Shahram N Syed, Andrey Konin, Zeeshan Zia, and Quoc-Huy Tran. Learning by aligning videos in time. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5548–5558, 2021.

[19] Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *NeurIPS*, 2016.

[20] Rishabh Jangir, Nicklas Hansen, Sambaran Ghosal, Mohit Jain, and Xiaolong Wang. Look closer: Bridging egocentric and third-person views with transformers for robotic manipulation. *IEEE Robotics and Automation Letters*, 2022.

[21] Jun Jin, Laura Petrich, Zichen Zhang, Masood Dehghan, and Martin Jagersand. Visual geometric skill inference by watching human demonstration. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 8985–8991. IEEE, 2020.

[22] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[23] Youngwoon Lee, Andrew Szot, Shao-Hua Sun, and Joseph J Lim. Generalizable imitation learning from observation via inferring goal proximity. *Advances in Neural Information Processing Systems*, 34, 2021.

[24] Sergey Levine, P. Pastor, A. Krizhevsky, and Deirdre Quillen. Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *The International Journal of Robotics Research*, 37:421 – 436, 2018.

[25] Yikang Li, Wanli Ouyang, Bolei Zhou, Kun Wang, and Xiaogang Wang. Scene graph generation from objects, phrases and region captions. *2017 IEEE International Conference on Computer Vision (ICCV)*, pages 1270–1279, 2017.

[26] Yunzhu Li, Hao He, Jiajun Wu, Dina Katabi, and Antonio Torralba. Learning compositional koopman operators for model-based control. *arXiv preprint arXiv:1910.08264*, 2019.

[27] Weizhe Liu, Bugra Tekin, Huseyin Coskun, Vibhav Vineet, Pascal Fua, and Marc Pollefeys. Learning to align sequential actions in the wild. *arXiv preprint arXiv:2111.09301*, 2021.

[28] Joanna Materzynska, Tete Xiao, Roei Herzig, Huijuan Xu, Xiaolong Wang, and Trevor Darrell. Something-else: Compositional action recognition with spatial-temporal interaction networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1049–1059, 2020.

[29] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charlie Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

[30] Andrew Y Ng, Stuart J Russell, et al. Algorithms for inverse reinforcement learning. In *ICML*, 2000.

[31] Deepak Pathak, Parsa Mahmoudieh, Guanghao Luo, Pulkit Agrawal, Dian Chen, Yide Shentu, Evan Shelhamer, Jitendra Malik, Alexei A. Efros, and Trevor Darrell. Zero-shot visual imitation. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pages 2131–21313, 2018.

[32] Dean A. Pomerleau. Alvinn: An autonomous land vehicle in a neural network. In D. Touretzky, editor, *Advances in Neural Information Processing Systems*, volume 1. Morgan-Kaufmann, 1988.

[33] Haozhi Qi, Xiaolong Wang, Deepak Pathak, Yi Ma, and Jitendra Malik. Learning long-term visual dynamics with region proposal interaction networks. In *ICLR*, 2021.

[34] Yuzhe Qin, Yueh-Hua Wu, Shaowei Liu, Hanwen Jiang, Ruihan Yang, Yang Fu, and Xiaolong Wang. Dexmv: Imitation learning for dexterous manipulation from human videos. *arXiv preprint arXiv:2108.05877*, 2021.

[35] Ilija Radosavovic, Xiaolong Wang, Lerrel Pinto, and Jitendra Malik. State-only imitation learning for dexterous manipulation. *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 7865–7871, 2021.

[36] Harish Ravichandar, Athanasios S. Polydoros, Sonia Chernova, and Aude Billard. Recent advances in robot learning from demonstration. *Annual Review of Control, Robotics, and Autonomous Systems*, 3(1):297–330, 2020.

[37] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

[38] Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin Riedmiller, Raia Hadsell, and Peter Battaglia. Graph networks as learnable physics engines for inference and control. In *International Conference on Machine Learning*, pages 4470–4479. PMLR, 2018.

[39] Karl Schmeckpeper, Oleh Rybkin, Kostas Daniilidis, Sergey Levine, and Chelsea Finn. Reinforcement learning with videos: Combining offline observations with interaction. *arXiv preprint arXiv:2011.06507*, 2020.

[40] Pierre Sermanet, Corey Lynch, Yevgen Chebotar, Jasmine Hsu, Eric Jang, Stefan Schaal, Sergey Levine, and Google Brain. Time-contrastive networks: Self-supervised learning from video. In *2018 IEEE international conference on robotics and automation (ICRA)*, pages 1134–1141. IEEE, 2018.

[41] Dandan Shan, Jiaqi Geng, Michelle Shu, and David F Fouhey. Understanding human hands in contact at internet scale. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9869–9878, 2020.

[42] Maximilian Sieb, Zhou Xian, Audrey Huang, Oliver Kroemer, and Katerina Fragkiadaki. Graph-structured visual imitation. In *Conference on Robot Learning*, pages 979–989. PMLR, 2020.

[43] Shuran Song, Andy Zeng, Johnny Lee, and Thomas Funkhouser. Grasping in the wild: Learning 6dof closed-loop grasping from low-cost demonstrations. *Robotics and Automation Letters*, 2020.

[44] Siddharth Srivastava, Eugene Fang, Lorenzo Riano, Rohan Chitnis, Stuart Russell, and Pieter Abbeel. Combined task and motion planning through an extensible planner-independent interface layer. In *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pages 639–646, 2014.

[45] Faraz Torabi, Garrett Warnell, and Peter Stone. Behavioral cloning from observation. *ArXiv*, abs/1805.01954, 2018.

[46] Faraz Torabi, Garrett Warnell, and Peter Stone. Generative adversarial imitation from observation. *arXiv*, 2018.

[47] Junyan Wang, Yang Long, Maurice Pagnucco, and Yang Song. Dynamic graph warping transformer for video alignment. 2020.

[48] Nicholas Watters, Daniel Zoran, Theophane Weber, Peter Battaglia, Razvan Pascanu, and Andrea Tacchetti. Visual interaction networks: Learning a physics simulator from video. *Advances in neural information processing systems*, 30, 2017.

[49] Haoyu Xiong, Quanzhou Li, Yun-Chun Chen, Homanga Bharadhwaj, Samarth Sinha, and Animesh Garg. Learning by watching: Physical imitation of manipulation skills from human videos. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 7827–7834. IEEE, 2021.

[50] Danfei Xu, Yuke Zhu, Christopher Bongsoo Choy, and Li Fei-Fei. Scene graph generation by iterative message passing. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3097–3106, 2017.

[51] Wei Yang, X. Wang, Ali Farhadi, Abhinav Kumar Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. *ArXiv*, abs/1810.06543, 2019.

[52] Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations*, 2020.

[53] Yufei Ye, Maneesh Singh, Abhinav Gupta, and Shubham Tulsiani. Compositional video prediction. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10353–10362, 2019.

[54] Yufei Ye, Dhiraj Gandhi, Abhinav Gupta, and Shubham Tulsiani. Object-centric forward modeling for model predictive control. In *Conference on Robot Learning*, pages 100–109. PMLR, 2020.

[55] Sarah Young, Dhiraj Gandhi, Shubham Tulsiani, Abhinav Gupta, Pieter Abbeel, and Lerrel Pinto. Visual imitation made easy. *arXiv*, 2020.

[56] Kevin Zakka, Andy Zeng, Pete Florence, Jonathan Tompson, Jeannette Bohg, and Debidatta Dwibedi. Xirl: Cross-embodiment inverse reinforcement learning. In *Conference on Robot Learning*, pages 537–546. PMLR, 2022.

[57] Yifeng Zhu, Jonathan Tremblay, Stan Birchfield, and Yuke Zhu. Hierarchical planning for long-horizon manipulation with geometric and symbolic scene graphs. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6541–6548. IEEE, 2021.