ROBUST MULTI-AGENT REINFORCEMENT LEARNING DRIVEN BY CORRELATED EQUILIBRIUM

ABSTRACT

In this paper we deal with robust cooperative multi-agent reinforcement learning (CMARL). While CMARL has many potential applications, only a trained policy that is robust enough can be confidently deployed in real world. Existing works on robust MARL mainly apply vanilla adversarial training in centralized training and decentralized execution paradigm. We, however, find that if a CMARL environment contains an adversarial agent, the performance of decentralized equilibrium might perform significantly poor for achieving such adversarial robustness. To tackle this issue, we suggest that *when execution* the non-adversarial agents must jointly make the decision to improve the robustness, therefore solving *correlated equilibrium* instead. We theoretically demonstrate the superiority of correlated equilibrium over the decentralized one in adversarial MARL settings. Therefore, to achieve robust CMARL, we introduce novel strategies to encourage agents to learn correlated equilibrium while maximally preserving the convenience of the decentralized execution. The global variables with mutual information are proposed to help agents learn robust policies with MARL algorithms. The experimental results show that our method can dramatically boost performance on the SMAC environments.

1 INTRODUCTION

Recently, reinforcement learning (RL) has achieved remarkable success in many practical sequential decision problems, such as Go (Silver et al., 2017), chess (Silver et al., 2018), real-time strategy games (Vinyals et al., 2019), etc. In real-world, many sequential decision problems involve more than one decision maker (i.e. multi-agent), such as auto-driving, traffic light control and network routing. Cooperative multi-agent reinforcement learning (CMARL) is a key framework to solve these practical problems. Existing MARL methods for cooperative environments include policy-based methods, e.g. MADDPG (Lowe et al., 2017), COMA (Foerster et al., 2017), and value-based methods, e.g. VDN (Sunehag et al., 2018), QMIX (Rashid et al., 2018), QTRAN (Son et al., 2019). However, before we actually apply CMARL's policy into real world applications, a question must be asked: are these learned policies safe or robust to be deployed? What will happen if some agents made mistakes or behaved adversarially against other agents? It will be most likely that the entire team might fail to achieve their goal or perform extremely poorly. (Lin et al., 2020) demonstrates the unrobustness in CMARL environment, where a learnt adversarial of one agent can hugely decrease the team's performance.

Therefore, in practice, we expect to have a multi-agent team policy in a fully cooperative environment that is robust when some agent(s) make some mistakes and even behave adversarially. To the best of knowledge, very few existing works on this issue mainly use vanilla adversarial training strategy. Klima et al. (2018) considered a two-agent cooperative case, in order to make the policy robust, agents become competitive with a certain probability during training. Li et al. (2019) provided a robust MADDPG approach called M3DDPG, where each agent optimizes its policy based on other agents' influenced sub-optimal actions.

Most state-of-the-art MARL algorithms utilize *centralized training and decentralized execution* (CTDE) routine, since this setting is common in real world cases. The robust MARL method M3DDPG also followed the CTDE setting. However, existing works on team mini-max normal form or extensive form games show that if the environment contains an adversarial agent, then the

decentralized equilibrium from CTDE routine can be significantly worse than the correlated equilibrium. We furthermore extend this finding into stochastic team mini-max games. Inspired by this important observation, if we can urge agents to *learn a correlated equilibrium* (i.e. the non-adversarial agents jointly make the decision when execution), then we may achieve better performance than those following CTDE in robust MARL setting.

In this work, we achieve the robust MARL via solving correlated equilibrium motivated by the latent variable model, where the introduction of a latent variable across all agents could help agents jointly make their decisions. Our contributions can be summarized as follows.

- We demonstrate that in stochastic team mini-max games, the decentralized equilibrium can be arbitrarily worse than correlated one, and the gap can be significantly larger than in normal or extensive form games.
- With this result, we point out that learning correlated equilibrium is indeed necessary in robust MARL.
- We propose a simple strategy to urge agents to learn correlated equilibrium, and show that this method can yield significant performance improvements over vanilla adversarial training.

2 RELATED WORKS

Robust RL The robustness in RL involves the perturbations occurring in different cases, such as state or observation, environment, action or policy, opponent's policy, etc. **1)** For the robustness to state or observation perturbation, most works focused on adversarial attacks of image state/observation. Pattanaik et al. (2018) used gradient-based attack on image state, and vanilla adversarial training was adopted to obtain robust policy; Fischer et al. (2019) first trained a normal policy, and distilled it on adversarial states to achieve robustness; Ferdowsi et al. (2018) applied adversarial training to autonomous driving tasks that interfered agent's input sensors based on environment, and then conducted adversarial training; **2)** For the robustness to environment, robust Markov decision process (MDP) could be used to formulate this problem. Many works (e.g. Wiesemann et al. (2013); Lim et al. (2013)) have studied this model and provided both theoretical analysis and algorithmic design. In deep RL scenario, Rajeswaran et al. (2016) used Monte Carlo approach to train agent, while Abdullah et al. (2019); Hou et al. (2020) adopted adversarial training to obtain a robust agent to all environments within a Wasserstein ball. Mankowitz et al. (2019) conducted adversarial training in MPO algorithm to optimize the performance in the worst performance environment. **3)** To be against the perturbation of action or policy, Tessler et al. (2019); Gu et al. (2018); Vinitsky et al. (2020) considered the case that agent's action may be influenced by another action, and conducted adversarial training. **4)** For the robustness to opponent, Pinto et al. (2017); Ma et al. (2018) focused on the case that agent's reward may be influenced by another agent, and adversarial training was implemented to solve the two-agent game to obtain a robust agent.

Correlated Equilibrium Correlated equilibrium is a more general equilibrium in game theory compared to Nash equilibrium. In a cooperative task, if the team agents jointly make decisions together, then the optimal team policy is correlated equilibrium. Correlated equilibrium is widely studied in game theory (e.g. Hart & Mas-Colell (2001; 2000); Neyman (1997)). In team mini-max game, solving the team's correlated equilibrium in normal form game is straightforward (just treat the team as a single agent); Celli & Gatti (2017); Zhang & An (2020); Farina et al. (2018) proposed various algorithms to solve correlated equilibrium in extensive formal games. In deep RL scenario, Celli et al. (2019) applied vanilla hidden variable model to solve correlated equilibrium in simple repetitive environments, while information loss with hidden variable model was used in Chen et al. (2019) to solve correlated equilibrium in normal multi-agent environment.

3 ROBUST MARL

3.1 PROBLEM STATEMENT

A typical cooperative MARL problem can be formulated as a stochastic Markov game $(\mathcal{S}, \{\mathcal{A}_i\}_{i=1}^n, r, P)$, where $\mathcal{S}$ denotes the state space, $\{\mathcal{A}_i\}$ is i-th agent's action space. The en-

vironment starts at state s_0 based on some initial distribution p_0. At each time step t, agents select a joint action $\mathbf{a}_t \in \times_{i=1}^n \mathcal{A}_i$ based on some policy $\pi_{team}(\mathbf{a}_t|s_t)$, and receive reward $r(s_t, \mathbf{a}_t)$. The environment will transfer to a new state $s_{t+1} \sim P(\cdot|s_t, \mathbf{a}_t)$. The goal is to maximize agents' expected accumulated reward,

$$\max_{\pi_{team}} \mathbb{E}_{s_0 \sim p_0, \mathbf{a}_t \sim \pi_{team}, s_{t+1} \sim P} \left[\sum_t r(s_t, \mathbf{a}_t) \right]. \tag{1}$$

Most state-of-the-art MARL algorithms utilize CTDE routine, since this setting is common in real world cases. In this setting, each agent selects its own action independently. If the environment is fully observable, then at each timestep t, each agent selects an action $a_{it} \in \mathcal{A}_i$ based on some policy $\pi_i(a_{it}|s_t)$, and if the environment is partially observable, then at each timestep t, each agent will receive an observation o_{it} based on s_t, and select action based on policy $\pi_i(a_{it}|o_{it})$. And the goal becomes

$$\max_{\pi_{1:n}} \mathbb{E}_{s_0 \sim p_0, a_{1:n,t} \sim \pi_{1:n}, s_{t+1} \sim P} \left[\sum_t r(s_t, a_{1:n,t}) \right]. \tag{2}$$

In robust MARL, the goal can be different up to different requirements of robustness. The goal of this work is to obtain a multi-agent team policy in a fully cooperative environment that is robust when some agent(s) make some mistakes or even execute adversarially. That is, we aim to learn a policy located at a flat maximum. The general multi-agent robust RL can be formulated as a multi-player mini-max optimization problem,

$$\max_{\pi_{team}} \min_{\pi_{mis}} \mathbb{E}_{s_0 \sim p_0, \mathbf{a}_t \sim \pi_{mis}, s_{t+1} \sim P} \left[\sum_t r(s_t, \mathbf{a}_t) \right] \qquad \text{s.t. } D(\pi_{mis}||\pi_{team}) \leq \varepsilon \tag{3}$$

where π_{mis} is the mistaken policy that these agents actually perform. D is some kind of distance measure that can be specified later for different tasks. This mini-max optimization problem guarantees that we can achieve a policy located at a flat maximum, and it will not behave significantly poor when some agent(s) make small mistakes under the constraint $D(\pi_{mis}||\pi_{team}) \leq \varepsilon$.

However, the general multi-agent robust RL problem is almost impossible to solve, because both the inner min and outer max loop involves multiple players. This means that both the inner and outer loop require solving a multi-agent RL problem, and the outer loop is dependent on the inner one. In this work, we only consider a special simplified case. This case aims to find a policy that is robust when only one agent behaves adversarially, as formulated below.

$$\text{Fixed } i \text{ or } \forall i, \max_{\pi_{1:n}} \min_{\pi_{i,mis}} \mathbb{E}_{s_0 \sim p_0, a_{it} \sim \pi_{i,mis}, a_{-i,t} \sim \pi_{-i}, s_{t+1} \sim P} \left[\sum_t r(s_t, a_{1:n,t}) \right]$$
$$\text{s.t. } D(\pi_{i,mis}||\pi_i) \leq \varepsilon \tag{4}$$

where $\{-i\}$ means all except i.

In this paper, we instantiate this case into QMIX algorithm and evaluate on SMAC environment (Samvelyan et al., 2019).

3.2 VANILLA ADVERSARIAL TRAINING

The robustness formulation itself is a mini-max optimization problem. However, even though we simplify the general optimization problem into the case described in Eq.(4), it is still hard to solve. This is because the inner loop is still a MDP, and to make the optimization problem easier to solve, we further simplify it.

The inner minimization means that, we want the agent(s) to make some mistakes to lower the team's reward as much as possible, and the mistakes should not be too large. We use policies that have this property and are easier to obtain as the approximation of the solution for the inner optimization.

In QMIX, an agent i's worst action is the one that minimizes its Q_i function (since in QMIX $\frac{\partial Q_{tot}}{\partial Q_i} \geq 0$, lower Q_i will lead to lower Q_{tot}). Thus, if we want the agent to lower the team's reward while

not making too large mistakes, we can let it perform its worst action with certain low probability as the specification of the constraint in Eq. (4), i.e.

$$a_{i,mis} = \begin{cases} \arg \max_a Q_i(s,a) & \text{with prob. } 1 - \varepsilon \\ \arg \min_a Q_i(s,a) & \text{with prob. } \varepsilon \end{cases} \qquad (5)$$

Based on these simplification, we can apply vanilla adversarial training to obtain a robust policy. The detailed algorithm framework 2 is described in Appendix A.1 . The performance of vanilla adversarial training will be considered as a baseline.

4 ROBUST MARL WITH CORRELATED EQUILIBRIUM

4.1 ROBUST MARL REQUIRES CORRELATED EQUILIBRIUM

In this part, we will show that with naive adversarial training in a centralized training and decentralized execution fashion, the learned policy might be sub-optimal in adversarial settings, thus requiring a correlated equilibrium.

In typical MARL settings, if the environment is fully cooperative, then the algorithms with centralized training and decentralized execution (e.g. QMIX/MADDPG/COMA, etc) can achieve state-of-the-art performance in certain environments. This indicates that at least for these environments, correlation in execution is not necessary. Furthermore, Lauer & Riedmiller (2000) proved that decentralized executed policy can achieve optimal performance for fully observable and fully cooperative RL.

However, in the robust MARL setting, some agent(s) become adversarial, indicating that the environment is not fully cooperative now. So the question is: whether the correlation in execution is necessary in adversarial scenario?

For the settings of Eq. (4), the problems actually become a team mini-max game. The works on team mini-max normal form or extensive form games (von Stengel & Koller, 1997; Basilico et al., 2016; Celli & Gatti, 2017), pointed out that the decentralized equilibrium can be significantly worse than correlated equilibrium at least for some games. In normal form team mini-max game, Basilico et al. (2016) proved that the gap between correlated and decentralized equilibrium is at most $O(m^{n-2})$, where n is the number of agents (includes the adversarial) and m is each agent's number of action. And the bound is tight.

We denote $\mathbb{E}_{cor}$ as the team's expected reward under their optimal correlated policy, and $\mathbb{E}_{dec}$ as that in their optimal decentralized policy. In MARL, agents play a stochastic game. Since a repeated normal form game is a special case of stochastic games, so $\frac{\mathbb{E}_{cor}}{\mathbb{E}_{dec}}$ can be at least m^{n-2} in stochastic games. Moreover, we find that this gap can be even larger in stochastic games than that in normal form games, because stochastic game is a sequential game, and agents' previous actions can influence the future state and therefore affect the future reward.

Proposition 1. $\frac{\mathbb{E}_{cor}}{\mathbb{E}_{dec}}$ *can be much larger than m^{n-2} in stochastic games.*

Proof. Consider this example: $\mathcal{S} = \{S_1, S_2\}$, initial state is S_1. Agents $1 \cdots n - 1$ is a team, n is adversary. $\mathcal{A}_i = \{1, \cdots, m\}$, $i = 1 \cdots n$. Discount factor $\gamma < 1$. The team's reward function $r(S_1, \mathbf{a}) = 0, \forall \mathbf{a}. \ r(S_2, \mathbf{a}) = \begin{cases} 1 & a_1 = \cdots = a_n \\ 0 & \text{otherwise} \end{cases}$. Deterministic state transition function $T(S_1, \mathbf{a}) = \begin{cases} S_2 & a_1 = \cdots = a_n \\ S_1 & \text{otherwise} \end{cases}; T(S_2, \mathbf{a}) = \begin{cases} \text{Game ends} & a_1 = a_2 = \cdots = a_n \\ S_2 & \text{otherwise} \end{cases}$.

In each state, the team's optimal correlated policy is to perform correlated action $\{1, \cdots, 1\}, \cdots, \{m, \cdots, m\}$ with equal probability $\frac{1}{m}$. Because if the team perform any of these actions with probability less than $\frac{1}{m}$, the adversary will perform that action, which will reduce the team's reward.

However, if the team plays in a decentralized way, then each agent's optimal policy is to perform each m actions with equal probability $\frac{1}{m}$.

We can prove that in this example, $\frac{\mathbb{E}_{cor}}{\mathbb{E}_{dec}} \geq m^{2n-4}(1-r)^2$. The detailed derivation can be found in Appendix A.2. □

In fact, the gap between correlated and decentralized equilibrium in stochastic team mini-max game can be arbitrarily larger than normal form game, elaborated in the following proposition. The detailed derivation can be found in Appendix A.2.

Proposition 2. $\forall$ *fixed* $k \in \mathbb{Z}_+$, *there exists a stochastic game in which* $\frac{\mathbb{E}_{cor}}{\mathbb{E}_{dec}} \geq O(m^{k(n-2)})$.

Therefore, in robust MARL settings, CTDE algorithms may no longer achieve optimal performance. To achieve better robustness in adversarial settings, we need to design some methods that can urge agents to learn correlated equilibrium .

4.2 LEARNING CORRELATED EQUILIBRIUM

In this work, we propose a novel approach to learn correlated equilibrium for robust MARL agents: using global random variable with mutual information.

This method is inspired by the idea of InfoGAN (Chen et al., 2016). The idea is to add a global random variable z as an extra input of the Q network, i.e. changing $Q_i(o_{it}, a_{it})$ to $Q_i(o_{it}, z_t, a_{it})$). Although the global random variable itself is meaningless, agents may learn to perform correlated equilibrium based on its value. The intuition is that, taking the example in Proposition 1, if we add a global random variable z sampled from $[0, 1]$ uniformly at each timestep, then each agent might learn to perform action 1 when $z \in \left[0, \frac{1}{m}\right)$, perform action 2 when $z \in \left[\frac{1}{m}, \frac{2}{m}\right)$, and so on. Therefore, the overall policy is the optimal correlated policy of the team.

The following proposition is straight forward using the definition of correlated equilibrium. We also give a simple derivation in Appendix A.2.

Proposition 3. *For a fully observable, finite discrete action MARL environment, if all agents receive a global continuous random variable z, then there exists a deterministic policy $\mu_i(s, z) : \mathcal{S} \times \mathbb{R} \to \mathcal{A}_i, i \in \{1, \cdots, n\}$ equivalent to the team's optimal correlated (stochastic) policy $\pi^*(a_1, \cdots, a_n | s)$.*

We now summarize two advantages of the proposed global random variable method for learning correlation equilibrium in robust MARL settings.

- We can allow agents to perform correlated equilibrium while maximally preserving the property of CTDE. Since the global latent variable is independent of states, the only elements that agents need to share is a random number generator and a random seed. This can be done before the game starts, and agents can still perform "decentralized" policy during the game.

- In MDP or fully observable fully cooperative correlated multi-agent MDP, one can prove that there must exist an optimal deterministic policy (Puterman, 2014), and therefore deterministic policy algorithm can learn optimal policy. However, this property will not hold if the the multi-agent MDP is not fully cooperative, the optimal correlated policy in the example in Proposition 1 must be stochastic. This will prevent deterministic policy algorithms from learning optimal correlated policy directly. But when agents shares a global random variable, deterministic policy approaches will be possible to learn a policy that is equivalent to the optimal correlated policy.

To avoid the ignorance of the global random variable's information for each agent, we propose to maximize the mutual information between the random variable and the agent's action $I(z_t; a_{it})$, and therefore agents must use the information from z. Also, to avoid solving the posterior $P(z|a)$ directly, the variational lower bound is derived as an approximate objective, like InfoGAN and Barber & Agakov (2003):

$$I(z, a) \geq \mathbb{E}_{z,a} \left[\log \frac{q(z|a)}{p(z)} \right] = \mathbb{E}_{z,a} \left[\log q(z|a) \right] + H(z). \tag{6}$$

where $q(z|a)$ is the variational approximation of $P(z|a)$.

Unlike InfoGAN using latent variables c to model the information that is irrelevant of generator source z (width, italic), in reinforcement learning with latent variable, we prefer applying the latent variables to model the correlated policy that is related to current observations. Thus, instead of simply utilizing $I(z_t; a_{it})$, it's better to use the conditional mutual information $I(z_t; a_{it}|o_{it})$.

A similar variational lower bound can also be derived to approximate this conditional mutual information:

$$
\begin{aligned}
I(z, a|o) = \mathbb{E}_{z,a,o} \left[\log \frac{p(z|a,o)}{p(z|o)} \right] &= \mathbb{E}_{z,a,o} \left[\log \frac{q(z|a,o)}{p(z|o)} \right] + \mathbb{E}_{a,o}[D_{KL}(p(z|a,o)||q(z|a,o))] \\
&\geq \mathbb{E}_{z,a,o} \left[\log \frac{q(z|a,o)}{p(z|o)} \right] = \mathbb{E}_{z,a,o} \left[\log q(z|a,o) \right] + H(z) \quad \text{(Since } p(z|o) = p(z))
\end{aligned}
\tag{7}
$$

Since the entropy term $H(z)$ is a constant, thus ignored, we can define $\mathcal{L}_I = -\sum_{i=1}^{n} \mathbb{E}_{o_i,a_i \sim \mathcal{D}, z \sim p(z)} \left[\log q\left(z \mid a_i, o_i\right) \right]$, and use $\mathcal{L}_{tot} = \mathcal{L}_{RL} + \lambda_I \mathcal{L}_I$ as the overall loss function. In experiments, we follow InfoGAN's idea, configure variational approximation $q(z|\cdot)$ as a Gaussian distribution, and apply a neural network to output its mean and variance. Algorithm 1 describes the overall training procedure.

Algorithm 1: Overall training procedure

Initialize replay buffer $\mathcal{D} = \emptyset$
for *each epoch* **do**
    for *sampling loop* **do**
        Obtain current s_t or $\mathbf{o}_t$.
        Sample z_t using some distribution.
        Rollout action $\mathbf{a}_t$ (using ε-greedy or other method, with $Q_i(s_t, z_t, a_{it})$ or
          $Q_i(o_{it}, z_t, a_{it})$).
        Select i and rollout the mistaken action $a_{it,mis}$ using Eq. 5. Let
          $\mathbf{a}_{t,mis} = (a_{1t} \cdots a_{i-1,t}, a_{it,mis}, a_{i+1,t} \cdots a_n)$
        Perform action $\mathbf{a}_{t,mis}$ and get r_t, s_{t+1} or $\mathbf{o}_{t+1}$.
        Store transition $(s_t, z_t, \mathbf{a}_{t,mis}, r_t, s_{t+1})$ or $(s_t, \mathbf{o}_t, z_t, \mathbf{a}_{t,mis}, r_t, s_{t+1}, \mathbf{o}_{t+1})$ to $\mathcal{D}$.
    end
    for *training loop* **do**
        Sample a minibatch $\mathcal{M}$ from replay buffer $\mathcal{D}$.
        Compute QMIX loss $\mathcal{L}_{TD}$.
        Compute overall loss $\mathcal{L}_{tot} = \mathcal{L}_{TD} + \lambda_I \mathcal{L}_I$ with $\mathcal{L}_I$ described above.
        Perform a update step of QMIX with loss $\mathcal{L}_{tot}$.
    end
end

Comparison with existing works. Both Chen et al. (2019) and Kim et al. (2020) involves the idea of global random variable and mutual information. The main difference between our method and theirs can be summarized as follows.

- In our work, we formulate the global random variable as certain common knowledge to be shared between agents, and do not need to specify its distribution as Chen et al. (2019) ($p_z(z)$ in Theorem 2.2), since any continuous random variable is qualified.

- Kim et al. (2020) used the mutual information between each pair of agent's policy $I\left(\pi^i\left(\cdot \mid s_t\right); \pi^j\left(\cdot \mid s_t\right)\right)$ to encourage agent to coordinate. However, not all agents in CMARL environment needs to correlated so much. For example, in SMAC, maybe heterogeneous agents with different roles do not need be correlated in a strong sense. Therefore, we suggest to employ conditional mutual information $I(z; a|s)$ (or $I(z; a|o)$) to encourage agents to use information from z, and allow agents to learn the correlated method themselves. Chen et al. (2019) proposed similar mutual information settings, but since they formulated $p_z(z)$, then the mutual information $I\left(z; \boldsymbol{\pi}^S(\boldsymbol{a}, z \mid s)\right)$ over joint distribution was used.

- Both of these two works aim to improve coordination in standard MARL tasks, while we focus on solving robust CMARL.

5 EXPERIMENTS

We test our method with QMIX algorithm in SMAC (Samvelyan et al., 2019) environment. We follow the experiment settings in QMIX (Rashid et al., 2018), including all the hyper-parameter settings and the performance evaluation method (evaluate every 10K timesteps with 32 games). The only difference is we train and evaluate with agents' mistaken action as in Eq. (5). We test two robust settings like Eq. (4), including: 1) only one fixed agent will make mistakes; 2) all agents can randomly make mistakes, but in each timestep at most one agent can make mistakes.

Map and Agent Selection To evaluate our method, we select the maps and agents such that the original QMIX can achieve good performance in non-robust settings, but its policy is not robust with the selected agents.

By examining several maps about QMIX's performance and robustness, we choose four maps to evaluate our method: 8m, 2s3z, 3m, 3s5z. The detailed information can be found in Appendix A.3. In all the evaluations, we choose $\varepsilon = 0.3$ for 3m, and $\varepsilon = 0.5$ for other 3 maps.

We evaluate the "random agent" case in all except 3s5z maps. Because in 3s5z map, normal policy will still obtain 68% of winning rate when a random agent has 50% probability to select its worst action. For the "fixed agent" case, since many agents in these maps are homogeneous, we only select some representative agents for evaluation. The selection criteria is mainly based on the robustness of the normal QMIX policy, and the detailed information can be found in Appendix A.3. We evaluate a total of 9 different agent settings.

In the training, we use a 3-dimensional independent uniform distribution $U(0, 1)$ as global variable, and set MI loss coefficient $\lambda_I = 0.1$.

Adversarial Testing Results In this part we compare 4 different settings: **n**ormal **p**olicy (train without adversarial but test with adversarial), **v**anilla **a**dversarial training (baseline), adversarial training with **g**lobal **v**ariable but without mutual information loss, adversarial training with **g**lobal variable and **m**utual information loss. In the whole section, we use the following abbreviations to indicate these four settings: NP, VA, GV, GM.

We run each experiment 5 times like QMIX does, and report the 25% and 75% as the upper and lower error bar. The mean winning rate during training is shown in Figure 1. We also plot the mean winning rate of the last few steps (in dotted line), and the performance of NP is plotted as black dotted line. The plots show that by adding global variable and mutual information loss, the performance of GM in most settings is better than VA and GV in average. The performance of GV is sometimes but not always better than VA. The reason might be that, without mutual information loss, agents will become easier to ignore global variable's information. Additional experimental results can be found in Appendix A.4.

In adversarial settings, the testing variance is larger than normal settings. So in order to evaluate the performance more accurately, we select the high checkpoint of each run within the error bar, and test it with 1000 episodes. Also, we test the model with different percentages of adversarial rate. The results are depicted in Figure 2, and further show that training with global variable and mutual information can lead to a better adversarial testing performance. The raw data can be found in Appendix A.5 in Table 1.

Random Testing Results Apart from testing the adversarial agents, we also test scenarios that agent makes non-adversarial mistakes, i.e. agent plays random action with certain probability: $a_{mis} = \begin{cases} \arg\max_a Q(s, a) & \text{with prob. } 1 - \varepsilon \\ \text{Random choice from } \mathcal{A} & \text{with prob. } \varepsilon \end{cases}$. We use the same ε as above.

The results are depicted in Figure 3, which show that training with global variable and mutual information can lead to a slightly better random testing performance. The raw data can be found in Appendix A.5 in Table 2.

Figure 1: Test winning rate v.s. training steps for different maps and adversarial agents

Figure 2: Adversarial testing results with different adversarial rates.

Figure 3: Random testing results with different random rates.

6 CONCLUSION AND DISCUSSIONS

In this work, we focused on robust CMARL when one agent in the team makes mistakes or even behave adversarially. We found that in team mini-max stochastic games, the performance of decentralized equilibrium can be significantly worse than correlated equilibrium. Thus in order to achieve a better robust CMARL performance, we propose a method which uses global variables with mutual information to help agents learn correlated equilibrium. The experimental results show that this method can achieve better performance compared to vanilla adversarial training.

Robust CMARL is a important research direction, as it will directly determine whether we can safely deploy CMARL into practical problems. To the best of our knowledge, this research direction is still in the early stage. In this work, we just provide a simple method to solve the robust CMARL problem. Several future directions can be explored. The experiments of this work show that in some settings, the robust policy will slightly decrease the non-robust performance. So one possible future work is to balance the performance and robustness. Besides, we only focus on the robustness of one agent. In reality, perhaps all agents can have a certain probability to make mistakes. So another possible future work is to find some ways to solve the more complex robust CMARL problem, i.e. Eq. (3).

REFERENCES

Mohammed Amin Abdullah, Hang Ren, Haitham Bou Ammar, Vladimir Milenkovic, Rui Luo, Mingtian Zhang, and Jun Wang. Wasserstein robust reinforcement learning. *arXiv preprint arXiv:1907.13196*, 2019.

David Barber and Felix V Agakov. The im algorithm: a variational approach to information maximization. In *Advances in neural information processing systems*, pp. None, 2003.

Nicola Basilico, Andrea Celli, Giuseppe De Nittis, and Nicola Gatti. Team-maxmin equilibrium: efficiency bounds and algorithms. *arXiv preprint arXiv:1611.06134*, 2016.

Andrea Celli and Nicola Gatti. Computational results for extensive-form adversarial team games. *arXiv preprint arXiv:1711.06930*, 2017.

Andrea Celli, Marco Ciccone, Raffaele Bongo, and Nicola Gatti. Coordination in adversarial sequential team games via multi-agent deep reinforcement learning. *arXiv preprint arXiv:1912.07712*, 2019.

Liheng Chen, Hongyi Guo, Haifeng Zhang, Fei Fang, Yaoming Zhu, Ming Zhou, Weinan Zhang, Qing Wang, and Yong Yu. Signal instructed coordination in team competition. *arXiv preprint arXiv:1909.04224*, 2019.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in neural information processing systems*, pp. 2172–2180, 2016.

Gabriele Farina, Andrea Celli, Nicola Gatti, and Tuomas Sandholm. Ex ante coordination and collusion in zero-sum multi-player extensive-form games. In *Advances in Neural Information Processing Systems*, pp. 9638–9648, 2018.

Aidin Ferdowsi, Ursula Challita, Walid Saad, and Narayan B Mandayam. Robust deep reinforcement learning for security and safety in autonomous vehicle systems. In *2018 21st International Conference on Intelligent Transportation Systems (ITSC)*, pp. 307–312. IEEE, 2018.

Marc Fischer, Matthew Mirman, and Martin Vechev. Online robustness training for deep reinforcement learning. *arXiv preprint arXiv:1911.00887*, 2019.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. *arXiv preprint arXiv:1705.08926*, 2017.

Zhaoyuan Gu, Zhenzhong Jia, and Howie Choset. Adversary a3c for robust reinforcement learning, 2018. URL https://openreview.net/forum?id=SJvrXqvaZ.

Sergiu Hart and Andreu Mas-Colell. A simple adaptive procedure leading to correlated equilibrium. *Econometrica*, 68(5):1127–1150, 2000.

Sergiu Hart and Andreu Mas-Colell. A reinforcement procedure leading to correlated equilibrium. In *Economics Essays*, pp. 181–200. Springer, 2001.

Linfang Hou, Liang Pang, Xin Hong, Yanyan Lan, Zhiming Ma, and Dawei Yin. Robust reinforcement learning with wasserstein constraint, 2020. URL https://openreview.net/forum?id=HkeeITEYDr.

Woojun Kim, Whiyoung Jung, Myungsik Cho, and Youngchul Sung. A maximum mutual information framework for multi-agent reinforcement learning. *arXiv preprint arXiv:2006.02732*, 2020.

Richard Klima, Daan Bloembergen, Michael Kaisers, and Karl Tuyls. Learning robust policies when losing control. In *Adaptive and Learning Agents workshop at AAMAS*, 2018.

Martin Lauer and Martin Riedmiller. An algorithm for distributed reinforcement learning in cooperative multi-agent systems. In *In Proceedings of the Seventeenth International Conference on Machine Learning*. Citeseer, 2000.

Shihui Li, Yi Wu, Xinyue Cui, Honghua Dong, Fei Fang, and Stuart Russell. Robust multi-agent reinforcement learning via minimax deep deterministic policy gradient. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4213–4220, 2019.

Shiau Hong Lim, Huan Xu, and Shie Mannor. Reinforcement learning in robust markov decision processes. In *Advances in Neural Information Processing Systems*, pp. 701–709, 2013.

Jieyu Lin, Kristina Dzeparoska, Sai Qian Zhang, Alberto Leon-Garcia, and Nicolas Papernot. On the robustness of cooperative multi-agent reinforcement learning. *arXiv preprint arXiv:2003.03722*, 2020.

Ryan Lowe, Yi I Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in neural information processing systems*, pp. 6379–6390, 2017.

Xiaobai Ma, Katherine Driggs-Campbell, and Mykel J Kochenderfer. Improved robustness and safety for autonomous vehicle control with adversarial reinforcement learning. In *2018 IEEE Intelligent Vehicles Symposium (IV)*, pp. 1665–1671. IEEE, 2018.

Daniel J Mankowitz, Nir Levine, Rae Jeong, Abbas Abdolmaleki, Jost Tobias Springenberg, Timothy Mann, Todd Hester, and Martin Riedmiller. Robust reinforcement learning for continuous control with model misspecification. *arXiv preprint arXiv:1906.07516*, 2019.

Abraham Neyman. Correlated equilibrium and potential games. *International Journal of Game Theory*, 26(2):223–227, 1997.

Anay Pattanaik, Zhenyi Tang, Shuijing Liu, Gautham Bommannan, and Girish Chowdhary. Robust deep reinforcement learning with adversarial attacks. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pp. 2040–2042. International Foundation for Autonomous Agents and Multiagent Systems, 2018.

Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2817–2826. JMLR. org, 2017.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. Epopt: Learning robust neural network policies using model ensembles. *arXiv preprint arXiv:1610.01283*, 2016.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder De Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. *arXiv preprint arXiv:1803.11485*, 2018.

Mikayel Samvelyan, Tabish Rashid, Christian Schroeder de Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. *arXiv preprint arXiv:1902.04043*, 2019.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Earl Hostallero, and Yung Yi. Qtran: Learning to factorize with transformation for cooperative multi-agent reinforcement learning. *arXiv preprint arXiv:1905.05408*, 2019.

Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinícius Flores Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *AAMAS*, pp. 2085–2087, 2018.

Chen Tessler, Yonathan Efroni, and Shie Mannor. Action robust reinforcement learning and applications in continuous control. *arXiv preprint arXiv:1901.09184*, 2019.

Eugene Vinitsky, Yuqing Du, Kanaad Parvate, Kathy Jang, Pieter Abbeel, and Alexandre Bayen. Robust reinforcement learning using adversarial populations. *arXiv preprint arXiv:2008.01825*, 2020.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Bernhard von Stengel and Daphne Koller. Team-maxmin equilibria. *Games and Economic Behavior*, 21(1-2):309–321, 1997.

Wolfram Wiesemann, Daniel Kuhn, and Berç Rustem. Robust markov decision processes. *Mathematics of Operations Research*, 38(1):153–183, 2013.

Youzhi Zhang and Bo An. Computing team-maxmin equilibria in zero-sum multiplayer extensive-form games. In *AAAI*, pp. 2318–2325, 2020.

A APPENDIX

A.1 VANILLA ADVERSARIAL TRAINING FRAMEWORK

Algorithm 2: Vanilla adversarial training framework

Initialize replay buffer $\mathcal{D} = \emptyset$
for *each epoch* **do**
  for *sampling loop* **do**
    Obtain current s_t or $\mathbf{o}_t$, and rollout action $\mathbf{a}_t$ (using ε-greedy or other method).
    Select i and rollout the mistaken action $a_{it,mis}$ using Eq. 5. Let
      $\mathbf{a}_{t,mis} = (a_{1t} \cdots a_{i-1,t}, a_{it,mis}, a_{i+1,t} \cdots a_n)$
    Perform action $\mathbf{a}_{t,mis}$ and get r_t, s_{t+1} or $\mathbf{o}_{t+1}$.
    Store transition $(s_t, \mathbf{a}_{t,mis}, r_t, s_{t+1})$ or $(s_t, \mathbf{o}_t, \mathbf{a}_{t,mis}, r_t, s_{t+1}, \mathbf{o}_{t+1})$ to $\mathcal{D}$.
  end
  for *training loop* **do**
    Sample a minibatch $\mathcal{M}$ from replay buffer $\mathcal{D}$.
    Compute QMIX loss $\mathcal{L}_{TD}$.
    Perform a update step of QMIX with loss $\mathcal{L}_{TD}$.
  end
end

A.2 DERIVATION OF PROPOSITIONS

Detailed derivation of Proposition 1 In correlated equilibrium, every step in S_1 has $\frac{1}{m}$ probability to transfer to S_2, and every step in S_2 has $\frac{1}{m}$ probability to get reward. If current state is S_2, then the expected reward is:

$$\frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \gamma \left(\frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \gamma \left(\frac{1}{m} \cdot 1 + \left(1 - \frac{1}{m}\right) \gamma (\cdots)\right)\right)$$

$$= \frac{1}{m} \left(1 + \left(\left(1 - \frac{1}{m}\right)\gamma\right) + \left(\left(1 - \frac{1}{m}\right)\gamma\right)^2 + \cdots\right)$$

$$= \frac{1}{1 - \left(\left(1 - \frac{1}{m}\right)\gamma\right)} \frac{1}{m} \overset{def}{=} k$$

So the overall expected reward of the correlated equilibrium is:

$$\mathbb{E}_{cor} = \frac{1}{m} \cdot \gamma k + \left(1 - \frac{1}{m}\right) \gamma \left(\frac{1}{m} \cdot \gamma k + \left(1 - \frac{1}{m}\right) \gamma \left(\frac{1}{m} \cdot \gamma k + \left(1 - \frac{1}{m}\right) \gamma (\cdots)\right)\right)$$

$$= \frac{1}{1 - \left(\left(1 - \frac{1}{m}\right)\gamma\right)} \frac{\gamma k}{m} = \frac{1}{1 - \left(\left(1 - \frac{1}{m}\right)\gamma\right)} \frac{\gamma \frac{1}{1-\left(\left(1-\frac{1}{m}\right)\gamma\right)} \frac{1}{m}}{m}$$

In decentralized equilibrium, every step in S_1 has $\frac{1}{m^{n-1}}$ probability to transfer to S_2, and every step in S_2 has $\frac{1}{m^{n-1}}$ probability to get reward. Similarly:

$$\mathbb{E}_{dec} = \frac{1}{1 - \left(\left(1 - \frac{1}{m^{n-1}}\right)\gamma\right)} \frac{\gamma \frac{1}{1-\left(\left(1-\frac{1}{m^{n-1}}\right)\gamma\right)} \frac{1}{m^{n-1}}}{m^{n-1}}$$

Therefore:

$$\frac{\mathbb{E}_{cor}}{\mathbb{E}_{dec}} = \left(\frac{m^{n-1}(1-\gamma) + \gamma}{m(1-\gamma) + \gamma}\right)^2 \geq \left(\frac{m^{n-1}(1-\gamma)}{m(1-\gamma) + m\gamma}\right)^2 = m^{2n-4}(1-\gamma)^2$$

Detailed derivation of Proposition 2 Consider the k step game with k states $S_1, \cdots, S_k$. Agents and action spaces are the same as Proposition 1. The discount factor is γ. $r(s, \mathbf{a}) = 0, s \in \{S_1, \cdots, S_{k-1}\}, \forall \mathbf{a}$; $r(S_k, \mathbf{a}) = \begin{cases} 1 & a_1 = a_2 = \cdots = a_n \\ 0 & \text{otherwise} \end{cases}$. That is, the team can only receive reward in the last step, which is a common case in RL environments. The deterministic state transition function is $T(S_i, \mathbf{a}) = \begin{cases} S_{i+1} & a_1 = a_2 = \cdots = a_n \\ S_i & \text{otherwise} \end{cases}$, $i = 1 \cdots k$, where S_{k+1} denotes the game ending.

Let's prove that $\frac{\mathbb{E}_{cor,k}}{\mathbb{E}_{dec,k}} \geq m^{k(n-2)}(1-\gamma)^k$.

Proposition 1 shows that $\frac{\mathbb{E}_{cor,2}}{\mathbb{E}_{dec,2}} \geq m^{2(n-2)}(1-\gamma)^2$. Now suppose $\frac{\mathbb{E}_{cor,i}}{\mathbb{E}_{dec,i}} \geq m^{i(n-2)}(1-\gamma)^i$, by using similar derivation in Proposition 1, we can get

$$\mathbb{E}_{cor,i+1} = \frac{1}{1 - \left(\left(1 - \frac{1}{m}\right)\gamma\right)} \frac{\gamma \mathbb{E}_{cor,i}}{m}$$

$$\mathbb{E}_{dec,i+1} = \frac{1}{1 - \left(\left(1 - \frac{1}{m^{n-1}}\right)\gamma\right)} \frac{\gamma \mathbb{E}_{dec,i}}{m^{n-1}}$$

So,

$$\frac{\mathbb{E}_{cor,i+1}}{\mathbb{E}_{dec,i+1}} = \frac{m^{n-1}(1-\gamma) + \gamma}{m(1-\gamma) + \gamma} \frac{\mathbb{E}_{cor,i}}{\mathbb{E}_{dec,i}} \geq \frac{m^{n-1}(1-\gamma)}{m(1-\gamma) + m\gamma} \frac{\mathbb{E}_{cor,i}}{\mathbb{E}_{dec,i}}$$

$$= m^{n-2}(1-\gamma) \frac{\mathbb{E}_{cor,i}}{\mathbb{E}_{dec,i}} \geq m^{(i+1)(n-2)}(1-\gamma)^{i+1}$$

Derivation of Proposition 3 Given state s, since the action space is discrete, suppose each agent has m actions, then we can list all possible joint actions $a_1 \cdots a_n$ in a sequence $\{\mathbf{a}_k\}_{k=1}^{m^n}$. Consider the optimal correlated policy $\pi^*(a_1, \cdots, a_n | s)$. Let $p_k = \pi^*(\mathbf{a}_k | s)$, $k = 1 \cdots m^n$.

Let Z be the value range of z. Since z is a continuous random variable, we can divide the support set of Z into m^n disjoint subset $\{Z_k\}_{k=1}^{m^n}$, which satisfies $P(z \in Z_k) = p_k$.

Next, let each agent performs the following deterministic policy:

$$\mu_i(s, z) = (\mathbf{a}_k)_i \text{ if } z \in Z_k$$

That is, agent i performs action $(\mathbf{a}_k)_i$ if $z \in Z_k$. All agents will perform joint action $\mathbf{a}_k$ if $z \in Z_k$, and the team will perform joint action $\mathbf{a}_k$ with probability $P(z \in Z_k) = p_k$. This is exactly the optimal correlated policy.

A.3 SMAC MAP AND AGENT SELECTION

In SMAC environment, not all maps are suitable for evaluating out method. Because:

- In some map(s), QMIX's performance is not good in non-robust settings (e.g. 3s5z_vs_3s6z, 6h_vs_8z, 27m_vs_30m, corridor). These results can be found in SMAC paper (Samvelyan et al., 2019))

- In some map(s), the policy trained by QMIX in non-robust settings is already robust with most agents (e.g. so_many_banelines, 3s_vs_{3,4,5}z, 1c3s5z except agent Colossi, MMM).

- In some hard map(s), it may be difficult for agents to achieve robust policy. (e.g. 8m_vs_9m or 10m_vs_11m, our team already has less agents than the enemy; 1c3s5z agent Colossi, Colossi is a large agent, thus if it makes mistakes, other small agents are hard to make up.)

Since big map may more likely be robust when only one agent makes mistakes, we decide to focus on small maps. By examining several maps about QMIX's performance and robustness, we choose four maps to evaluate our method: 8m, 2s3z, 3m, 3s5z.

Since many agents in these maps are homogeneous, we only select some representative agents to evaluate.

- 3m map: All agents are homogeneous. We select the agent that is the least robust one in normal QMIX policy: agent 2. (The test winning rates of normal QMIX policy with 1000 episodes are 18.9%, 21.2%, **17.6%** respectively, when agent 0, 1, 2 has 30% probability to select the worst action.)

- 8m map: All agents are homogeneous. Since this map has more agents than 3m, we select the most robust agent and the least robust agent in normal QMIX policy: agent 4 and agent 6. (The test winning rate of normal QMIX policy with 1000 episodes are 2.3%, 3.4%, 5.4%, 10.3%, **1.9%**, 7.3%, **14.4%**, 7.1% respectively, when agent 0, 1, 2, 3, 4, 5, 6, 7 has 50% probability to select the worst action.)

- 3s5z map: During training we found that this map is difficult to train. We have to train more steps to make it converge, and the training process is slow. Therefore we only evaluate the least robust agent in normal QMIX policy: agent 3. (The test winning rate of normal QMIX policy with 1000 episodes are 27.5%, 31.5%, 80.5%, **9%**, 9.5%, 14.5%, 18%, 22.5% respectively, when agent 0, 1, 2, 3, 4, 5, 6, 7 has 50% probability to select the worst action.)

- 2s3z map: During training we found that this map is a bit difficult to train. We want to only evaluate the least robust agent in normal QMIX policy. But in this map, agent 2 and agent 4 are almost the same robust, so we evaluate both of them. (The test winning rate of normal QMIX policy with 1000 episodes are 6.1%, 8.1%, **5.7%**, 6.4%, **5.7%** respectively, when agent 0, 1, 2, 3, 4 has 50% probability to select the worst action.)

A.4 ADDITIONAL EXPERIMENT RESULTS

In this section, we present the additional experimental results, including the mean winning rate during training (Figure 4a), the adversarial testing results (Figure 4b), and the random testing results (Figure 4c).

The results shows that, the performance of GM is better than VA and GV in most settings, except for 2s3z's random agent, in which GV is better than VA but GM is similar to GV.

A.5 SMAC EVALUATION TABLES

The mean testing winning rates of adversarial testing results are shown in Table 1. The mean testing winning rates of random testing results are shown in Table 2.

(a) Training Curves   (b) Adversarial Testing Results   (c) Random Testing Results

Figure 4: Random Testing Results

Table 1: Adversarial Testing Results

			0%	10%	20%	30%	40%	50%
8m Map	Agent 4	NP	87.6	72.1	47.1	22.0	8.6	1.9
		VA	96.4	94.6	89.5	78.8	65.7	53.8
		GV	97.9	96.7	93.3	85.0	71.3	59.6
		GM	99.3	98.7	96.7	90.2	79.1	68.2
	Agent 6	NP	87.6	79.7	67.0	53.3	31.2	14.4
		VA	95.4	93.1	87.2	74.8	59.4	50.2
		GV	92.7	90.8	84.6	74.9	62.7	52.1
		GM	98.0	96.0	91.5	84.0	73.7	63.6
	Random Agent	NP	87.6	80.4	68.7	60.1	47.0	36.9
		VA	90.2	87.9	82.8	69.4	69.6	59.4
		GV	94.6	94.1	90.9	85.3	77.9	67.7
		GM	99.4	98.7	97.1	93.1	88.8	79.6
2s3z Map	Agent 2	NP	97.5	92.7	75.0	50.8	21.4	5.7
		VA	82.8	85.1	85.0	86.6	82.5	78.5
		GV	89.4	92.0	92.9	91.4	86.0	79.4
		GM	97.6	98.0	97.3	96.0	93.9	90.5
	Agent 4	NP	97.5	85.7	65.0	39.1	20.9	5.7
		VA	68.6	70.7	72.7	72.2	64.9	53.9
		GV	92.0	91.4	88.2	81.9	71.3	58.5
		GM	93.4	93.0	92.5	90.2	81.6	72.6
	Random Agent	NP	97.5	94.7	87.9	77.9	63.5	45.6
		VA	89.9	90.0	88.1	82.1	74.5	60.9
		GV	96.8	97.4	94.1	89.4	80.6	69.6
		GM	91.6	93.1	91.4	87.5	81.1	67.5
3s5z Map	Agent 3	NP	94.4	90.7	78.7	56.5	28.6	9.0
		VA	78.8	76.7	71.6	66.2	56.8	45.7
		GV	79.4	67.9	68.3	66.2	60.6	51.3
		GM	88.9	88.1	87.2	83.4	78.9	73.5
3m Map	Agent 2	NP	96.1	78.2	40.8	17.6	-	-
		VA	95.2	81.0	58.8	32.3	-	-
		GV	90.2	77.0	57.2	34.8	-	-
		GM	96.7	86.1	64.7	42.6	-	-
	Random Agent	NP	96.1	80.6	56.3	32.8	-	-
		VA	96.1	86.0	68.0	44.4	-	-
		GV	97.1	86.1	67.2	44.2	-	-
		GM	97.8	90.6	72.6	51.0	-	-

Table 2: Random Testing Results

			0%	10%	20%	30%	40%	50%
8m Map	Agent 4	NP	87.6	85.3	77.5	65.8	54.4	43.9
		VA	96.4	96.4	94.5	93.3	89.8	84.7
		GV	97.9	97.4	97.6	96.3	94.8	93.1
		GM	99.4	99.4	98.9	98.3	97.1	94.8
	Agent 6	NP	87.6	87.2	85.5	83.8	83.1	75.8
		VA	95.8	94.5	93.5	91.2	87.5	83.9
		GV	92.7	93.0	91.7	90.2	87.9	81.5
		GM	98.0	96.9	96.4	94.7	93.8	90.5
	Random Agent	NP	87.6	83.3	81.7	80.0	74.0	71.0
		VA	90.2	89.6	88.8	87.2	84.7	83.6
		GV	94.6	94.8	94.1	94.1	93.0	91.3
		GM	99.4	99.2	98.9	98.5	97.9	97.0
2s3z Map	Agent 2	NP	97.5	96.0	89.3	78.4	58.6	40.5
		VA	82.8	85.5	84.2	86.1	86.0	85.8
		GV	89.4	90.6	91.8	90.1	92.3	90.5
		GM	97.6	97.4	97.7	97.6	97.4	96.7
	Agent 4	NP	97.5	94.4	86.1	78.4	66.3	52.6
		VA	68.6	68.3	68.6	68.6	68.9	69.7
		GV	92.0	85.1	86.1	81.8	79.5	76.7
		GM	93.4	92.8	92.9	92.6	91.7	91.1
	Random Agent	NP	97.5	96.1	93.6	90.5	86.4	81.6
		VA	89.9	89.7	89.4	88.3	85.5	82.5
		GV	96.8	97.3	95.8	94.6	93.0	89.8
		GM	91.6	93.0	91.9	90.8	89.8	87.9
3s5z Map	Agent 3	NP	94.4	92.9	86.0	79.6	68.5	57.7
		VA	78.8	76.2	76.3	73.6	69.4	65.7
		GV	79.4	66.1	64.9	65.6	63.3	62.4
		GM	88.9	89.7	88.0	87.6	86.3	83.8
3m Map	Agent 2	NP	96.1	90.3	79.7	65.0	-	-
		VA	95.2	91.0	81.9	74.7	-	-
		GV	90.2	85.9	80.5	71.5	-	-
		GM	96.7	94.3	88.2	79.1	-	-
	Random Agent	NP	96.1	92.2	84.6	74.1	-	-
		VA	96.1	92.3	87.1	80.4	-	-
		GV	97.1	94.1	87.6	81.6	-	-
		GM	97.8	96.1	91.0	87.7	-	-