Enforcing Predictive Invariance across Structured Biomedical Domains

Abstract

Many biochemical applications such as molecular property prediction require models to generalize beyond their training domains (environments). Moreover, natural environments in these tasks are structured, defined by complex descriptors such as molecular scaffolds or protein families. Therefore, most environments are either never seen during training, or contain only a single training example. To address these challenges, we propose a new regret minimization (RGM) algorithm and its extension for structured environments. RGM builds from invariant risk minimization (IRM) by recasting simultaneous optimality condition in terms of predictive regret, finding a representation that enables the predictor to compete against an oracle with hindsight access to held-out environments. The structured extension adaptively highlights variation due to complex environments via specialized domain perturbations. We evaluate our method on multiple applications: molecular property prediction, protein homology and stability prediction and show that RGM significantly outperforms previous state-of-the-art baselines.

1 Introduction

In many biomedical applications, training data is necessarily limited or otherwise heterogeneous. It is therefore important to ensure that model predictions derived from such data generalize substantially beyond where the training samples lie. For instance, in molecule property prediction (Wu et al., 2018), models are often evaluated under scaffold split, which introduces structural separation between the chemical spaces of training and test compounds. In protein homology detection (Rao et al., 2019), the split is driven by protein superfamily where entire evolutionary groups are held out from the training set, forcing models to generalize across larger evolutionary gaps.

The key technical challenge is to be able to estimate models that can generalize beyond their training data. The ability to generalize implies a notion of invariance to the differences between the available training data and where predictions are sought. A recently proposed approach known as invariant risk minimization (IRM) (Arjovsky et al., 2019) seeks to find predictors that are simultaneously optimal across different such scenarios (called environments). Indeed, one can apply IRM with environments corresponding to molecules sharing the same scaffold (Bemis & Murcko, 1996) or proteins from the same family (El-Gebali et al., 2019) (see Figure 1). However, this is challenging since, for example, scaffolds are structured objects and can often uniquely identify each example in the training set. It is not helpful to create single-example environments as the model would see any variation from one example to another as scaffold variation.

In this paper, we propose a *regret minimization* algorithm to handle both standard and structured environments. The basic idea is to simulate unseen environments by using part of the training set as held-out environments E_e. We quantify generalization in terms of regret — the difference between the losses of two auxiliary predictors trained with and without examples in E_e. This imposes a stronger constraint on ϕ and avoids some undesired representations admitted by IRM. For the structured environments like molecular scaffolds, we simulate unseen environments by perturbing the representation ϕ. The perturbation is defined as the gradient of an auxiliary scaffold classifier with respect to ϕ. The difference between the original and perturbed representation highlights the scaffold variation to the model. Its associated regret measures how well a predictor trained without perturbation generalizes to the perturbed examples. The goal is to characterize the scaffold variation without explicitly creating an environment for every possible scaffold.

Figure 1: *Left*: Data generation process for molecule property prediction. Training and test environments are generated by controlling the scaffold variable. *Middle*: Scaffold is a subgraph of a molecular graph with its side chains removed. *Right*: In a toxicity prediction task (Wu et al., 2018), there are 1600 scaffold environments with 75% of them having a single example.

Our methods are evaluated on real-world datasets such as molecule property prediction and protein classification. We compare our model against multiple baselines including IRM, MLDG (Li et al., 2018a) and CrossGrad (Shankar et al., 2018). On the QM9 dataset (Ramakrishnan et al., 2014), we outperform the best baseline by a wide margin across multiple properties (41.7 v.s 52.3 average MAE) under an extrapolation evaluation. On a protein stability dataset (Rocklin et al., 2017), we achieve new state-of-the-art results compared to Rao et al. (2019) (0.79 v.s. 0.73 spearman's ρ).

2 RELATED WORK

Generalization challenges in biomedical applications The challenges of generalization have been extensively documented in this area. For instance, Yang et al. (2019); Rao et al. (2019); Hou et al. (2018) have demonstrated that state-of-the-art models exhibit significant drop in performance when tested under scaffold or protein family split. De facto, the scaffold split and its variants (Feinberg et al., 2018) are used so commonly in cheminformatics as they emulate temporal evaluation adopted in pharmaceutical industry. Therefore, the ability to generalize to new scaffold or protein family environments is the key for practical usage of these models. Moreover, input objects in these domains are typically structured — e.g., molecules are represented by graphs (Duvenaud et al., 2015; Dai et al., 2016; Gilmer et al., 2017). This characteristic introduces unique challenges with respect to the environment definition for IRM style algorithms.

Invariance Prior work has sought generalization by enforcing an appropriate invariance constraint over learned representations. For instance, domain adversarial network (DANN) (Ganin et al., 2016; Zhao et al., 2018) enforces the latent representation $Z = \phi(X)$ to have the same distribution across different environments E (i.e, $Z \perp E$). However, this forces predicted label distribution $P(Y|Z)$ to be the same across all the environments (Zhao et al., 2019). Long et al. (2018); Li et al. (2018c); Combes et al. (2020) extends the invariance criterion by conditioning on the label in order to address the label shift issue of DANN. Invariant risk minimization (IRM) (Arjovsky et al., 2019) seeks a different notion of invariance. Instead of aligning distributions of Z, IRM requires that the predictor f operating on $Z = \phi(X)$ is simultaneously optimal across different environments. The associated independence is $Y \perp E \mid Z$. Various work (Krueger et al., 2020; Chang et al., 2020) has sought to extend IRM. We focus on the structured setting, where most of the environments can uniquely specify X in the training set. As a result, E would act similarly to X. In the extreme case, the IRM principle reduces to $Y \perp X \mid Z$, which is not the desired invariance criterion. We propose to address this issue by introducing domain perturbation to adaptively highlight the structured variation.

Domain generalization These methods seek to learn models that generalize to new domains (Muandet et al., 2013; Ghifary et al., 2015; Motiian et al., 2017; Li et al., 2017; 2018b). Domain generalization methods can be roughly divided into three categories: *domain adversarial training* (Ganin et al., 2016; Tzeng et al., 2017; Long et al., 2018), *meta-learning* (Li et al., 2018a; Balaji et al., 2018; Li et al., 2019a;b; Dou et al., 2019) and *domain augmentation* (Shankar et al., 2018; Volpi et al., 2018). Our method resembles meta-learning based methods in that we create held-out environments to simulate domain shift during training. However, our objective seeks to reduce the regret between predictors trained with or without access to the held-out environments.

Existing domain generalization benchmarks assume that each domain contains sufficient amounts of data. We focus on a different setting where most of the environments contain only few (or single)

examples since they are defined by structured descriptors. This setting often arises in chemical and biological applications (see Figure 1). Similar to data augmentation method in Shankar et al. (2018), our structured RGM also creates perturbed examples based on domain-guided perturbations. However, our method operates over learned representations since our inputs are discrete. Moreover, the perturbed examples are only used to regularize the feature extractor ϕ via the regret term.

3 REGRET MINIMIZATION

To introduce our method, we start with a standard setting where the training set $\mathcal{D}$ is comprised of n environments $\mathcal{E} = \{E_1, \cdots, E_n\}$ (Arjovsky et al., 2019). Each environment E_i consists of examples (x, y) randomly drawn from some distribution $\mathcal{P}_i$. Assuming that new environments we may encounter at test time exhibit similar variability as the training environments, our goal is to train a model that generalizes to such new environments E_{test}. Suppose our model consists of two components $f \circ \phi$, where the predictor f operates on the feature extractor ϕ. Let $\mathcal{L}^e(f \circ \phi) = \sum_{(x,y) \in E_e} \ell(y, f(\phi(x)))$ be its empirical loss in environment E_e and $\mathcal{L}(f \circ \phi) = \sum_e \mathcal{L}^e(f \circ \phi)$. IRM learns ϕ and f such that f is simultaneously optimal in all training environments:

$$\min_{\phi, f} \mathcal{L}(f \circ \phi) \qquad \text{s.t.} \quad \forall e : f \in \arg\min_h \mathcal{L}^e(h \circ \phi) \tag{1}$$

One possible way to solve this objective is through Lagrangian relaxation:

$$\min_{\phi, f} \mathcal{L}(f \circ \phi) + \sum_e \lambda_e \big(\mathcal{L}^e(f \circ \phi) - \min_h \mathcal{L}^e(h \circ \phi)\big) \tag{2}$$

The regularizer $\mathcal{L}^e(f \circ \phi) - \min_h \mathcal{L}^e(h \circ \phi)$ measures the performance gap between f and the best predictor $\hat{h} \in F_e(\phi) = \arg\min_h \mathcal{L}^e(h \circ \phi)$ specific to environment E_e. Note that both f and $\hat{h}$ are trained and evaluated on examples from environment E_e. This motivates us to replace the regularizer with a predictive regret. Specifically, for each environment E_e, we define the associated regret $\mathcal{R}^e(\phi)$ as the difference between the losses of two auxiliary predictors trained *with* and *without* access to examples $(x, y) \in E_e$:

$$\mathcal{R}^e(\phi) = \mathcal{L}^e(f_{-e} \circ \phi) - \min_{h \in \mathcal{F}} \mathcal{L}^e(h \circ \phi) = \mathcal{L}^e(f_{-e} \circ \phi) - \mathcal{L}^e(f_e \circ \phi) \tag{3}$$

where the two auxiliary predictors are obtained from (assuming $\mathcal{F}$ is bounded and closed):

$$f_e \in F_e(\phi) = \arg\min_{h \in \mathcal{F}} \mathcal{L}^e(h \circ \phi) \qquad f_{-e} \in F_{-e}(\phi) = \arg\min_{h \in \mathcal{F}} \sum_{k \neq e} \mathcal{L}^k(h \circ \phi) \tag{4}$$

The *oracle predictor* f_e is trained on environment E_e, while f_{-e} uses the rest of the environments $\mathcal{E} \backslash \{E_e\}$ for training but is tested on E_e. Note that $\mathcal{R}^e(\phi)$ does not depend on the predictor f we are seeking to estimate; it is a function of the representation ϕ as well as the two auxiliary predictors f_{-e} and f_e. For notational simplicity, we have omitted $R^e(\phi)$'s dependence on f_{-e} and f_e. Since both predictors are evaluated on the same set of training examples in E_e, we immediately have

Proposition 1. *The regret $\mathcal{R}^e(\phi)$ is always non-negative for any representation ϕ.*

The proof is straightforward since f_e is the minimizer of $\mathcal{L}^e(f' \circ \phi)$ and both f_e and f_{-e} are drawn from the same parametric family $\mathcal{F}$. The overall regret $\mathcal{R}(\phi) = \sum_e \mathcal{R}^e(\phi)$ expresses our stated goal of finding a representation ϕ that generalizes to each held-out environment. Our regret minimization (RGM) objective then balances the empirical loss against the regret, finding ϕ and f that minimize:

$$\mathcal{L}_{\text{RGM}} = \mathcal{L}(f \circ \phi) + \lambda \sum_e \mathcal{R}^e(\phi) \tag{5}$$

3.1 COMPARISON WITH IRM

Compared to IRM, the proposed RGM objective imposes a stronger constraint on ϕ since f_{-e} is not trained on E_e. To show this formally, let $F_e(\phi), F_{-e}(\phi)$ be the set of optimal predictors in E_e and $\mathcal{E} \backslash \{E_e\}$ respectively as defined in Eq.(4). Since $\mathcal{R}^e(\phi) = 0 \Leftrightarrow f_{-e} \in F_e(\phi)$ and f_{-e} is chosen arbitrarily from $F_{-e}(\phi)$, the constrained form of the RGM objective can be stated as

$$\min_{\phi, f} \mathcal{L}(f \circ \phi) \qquad \text{s.t.} \quad \forall e : F_{-e}(\phi) \subseteq F_e(\phi) \tag{6}$$

Figure 2: *Left*: In the backward pass, the gradient of $\mathcal{L}^e(f_e \circ \phi)$ goes through a gradient reversal layer (Ganin et al., 2016) which negates the gradient during back-propagation. *Right*: An example where environments are generated by different translations of X_1. For the identity mapping $\phi(X) = (X_1, X_2)$, there exists a predictor f_{IRM} which is simultaneously optimal in all environments. In contrast, ϕ is not feasible under RGM because there is a linear classifier $h \in F_{-2}(\phi)$ but $h \notin F_2(\phi)$.

The analogous IRM constraints are $f \in \cap_e F_e(\phi)$ and $\cap_e F_e(\phi) \neq \emptyset$. Suppose both IRM and RGM constraints are feasible and let $\mathcal{L}^*_{\text{IRM}}, \mathcal{L}^*_{\text{RGM}}$ be their optimal loss respectively. Consider the set of optimal features under both objectives:

$$\Phi_{\text{IRM}} = \{\phi \mid \min_{f \in \cap_e F_e(\phi)} \mathcal{L}(f \circ \phi) = \mathcal{L}^*_{\text{IRM}}, \cap_e F_e(\phi) \neq \emptyset\} \tag{7}$$

$$\Phi_{\text{RGM}} = \{\phi \mid \min_{f \in \mathcal{F}} \mathcal{L}(f \circ \phi) = \mathcal{L}^*_{\text{RGM}}, \forall e : F_{-e}(\phi) \subseteq F_e(\phi)\} \tag{8}$$

Proposition 2. *Assuming two environments, if $\mathcal{L}^*_{\text{RGM}} = \mathcal{L}^*_{\text{IRM}}$, then $\Phi_{\text{RGM}} \subseteq \Phi_{\text{IRM}}$. The converse $\Phi_{\text{IRM}} \subseteq \Phi_{\text{RGM}}$ does not hold in general.*

While limited to two environments, the proposition suggests that RGM imposes stronger constraints on ϕ. Figure 2 shows a counterexample illustrating that $\Phi_{\text{IRM}} \not\subseteq \Phi_{\text{RGM}}$. Suppose there are two environments generated by translation of X_1 and the true hypothesis is $\mathbb{I}[X_2 > 0]$. The identity mapping $\phi(X) = (X_1, X_2)$ is not translation invariant, but $\phi \in \Phi_{\text{IRM}}$ because there exists a predictor f_{IRM} that is simultaneously optimal in all environments. On the other hand, ϕ is not feasible under RGM because there is a linear classifier $h \in F_{-2}(\phi)$ that is optimal in E_1 but suboptimal in E_2, violating the RGM constraint $F_{-2}(\phi) \subseteq F_2(\phi)$. Thus $\phi \notin \Phi_{\text{RGM}}$.

To see why it would be helpful to add a stronger constraint on ϕ, consider the following data generation process where the environment e can be inferred from x alone:

$$p(x, y, e) = p(e)p(x|e)p(y|x, e); \qquad p(y|x, e) = p(y|x, e(x)) \tag{9}$$

For molecules and proteins, this assumption is often valid because the environment labels (scaffolds, protein families) typically depend on x only. We call ϕ *label-preserving* if it retains all the information about the label: $p(y|\phi(x)) = p(y|x, e)$. Such representation may not generalize to new environments given the dependence on e through ϕ. However, we can show that for any label-preserving ϕ, its associated ERM optimal predictor also satisfies the IRM constraints:

Proposition 3. *For any label-preserving ϕ with $p(y|\phi(x)) = p(y|x, e)$, its associated ERM optimal predictor f^* satisfies the IRM constraint. Moreover, if $\phi \in \Phi_{\text{IRM}}$, $f^* \circ \phi$ is optimal under IRM.*

While IRM constraints are vacuous for any label-preserving ϕ, this is not necessarily the case with RGM constraints. Consider, for example, the counterexample in Figure 2. The identity mapping $\phi(X) = (X_1, X_2)$ is label-preserving since it retains all the input information. However, ϕ is infeasible under RGM.

3.2 STRUCTURED ENVIRONMENTS

Now let us consider a more challenging setting, where we have another set of environments defined via structured descriptors besides the standard environments $\{E_1, \cdots, E_n\}$. Formally, the structured environments comes in the form $\mathcal{D} = \{(x_i, y_i, s_i)\}$, where s_i is a structured environment descriptor of (x, y). For instance, in molecule property prediction, s_i is defined as a Murcko scaffold (i.e., subgraph) of molecule x_i. It is hard to turn the scaffolds into standard environments because scaffolds

Figure 3: a) Structured RGM: we introduce additional oracle predictors $\tilde{f}_e$ for the perturbed inputs; b) In molecule tasks, the scaffold classifier g is trained by negative sampling.

are structured descriptors and they often uniquely identify each molecule in the training set (Figure 1). Creating single-example environments is not helpful as the model would see any change from one example to another as scaffold variation.

Alternatively, we can describe scaffold variation by perturbation in the representation ϕ. The idea is to create a perturbed instance $\tilde{x}_i$ for each example (x_i, y_i, s_i) so that the difference between x_i and $\tilde{x}_i$ highlights how scaffold information has changed in the representation. Specifically, the perturbation $\delta(x_i)$ is defined through a parametric scaffold classifier g built on top of the representation ϕ.[1] The associated scaffold classification loss is $\ell(s_i, g(\phi(x_i)))$. Given that our inputs are discrete, we define the perturbation δ as the gradient with respect to the continuous representation ϕ:

$$\phi(\tilde{x}_i) := \phi(x_i) + \delta(x_i) = \phi(x_i) + \alpha \nabla_z \ell(s_i, g(z))|_{z=\phi(x_i)} \tag{10}$$

where α is a step size parameter. The perturbation is specifically designed to contain less information about the scaffold s_i, and we require that the model should not be affected by this variation in the representation. Since these perturbations introduce additional simulated test scenarios that we wish to generalize to, we propose to regularize our model also based on regret associated with perturbed inputs. Similar to Eq.(3), the regret corresponding to perturbed inputs is defined as

$$\mathcal{R}^e(\phi + \delta) = \mathcal{L}^e(f_{-e} \circ (\phi + \delta)) - \min_h \mathcal{L}^e(h \circ (\phi + \delta)) \tag{11}$$

$$\mathcal{L}^e(h \circ (\phi + \delta)) = \sum_{(x_i, y_i) \in E_e} \ell\big(y_i, h(\phi(x_i) + \delta(x_i))\big) \tag{12}$$

which introduces a new oracle predictor $\tilde{f}_e = \arg\min_h \mathcal{L}^e(h \circ (\phi + \delta))$ for each environment E_e (see Figure 3a). Note that f_{-e} is the same auxiliary predictor as before. It minimizes a separate objective $\mathcal{L}^{-e}(f_{-e} \circ \phi)$, which does *not* include the perturbed examples.

The structured RGM objective $\mathcal{L}_{\text{SRGM}}$ augments the basic RGM with additional regret terms as well as the scaffold classification loss $\mathcal{L}_g(g \circ \phi)$:

$$\mathcal{L}_{\text{SRGM}} = \mathcal{L}(f \circ \phi) + \lambda_g \mathcal{L}_g(g \circ \phi) + \lambda \sum_e \sum_{\psi \in \{0, \delta\}} \mathcal{R}^e(\phi + \psi) \tag{13}$$

$$\mathcal{L}_g(g \circ \phi) = \sum_{(x, y, s) \in \mathcal{D}} \ell\big(s, g(\phi(x))\big) \tag{14}$$

The forward pass of SRGM is shown in Algorithm 1. Since s is a structured object with a large number of possible values, we train the classifier g with negative sampling (Figure 3b). Note that ϕ is also updated to partially optimize $\mathcal{L}_g$. This is necessary to ensure that the scaffold classifier operating on ϕ has enough information to introduce a reasonable gradient perturbation $\delta(x)$. This trade-off keeps some scaffold information in ϕ while ensuring, via the associated regret terms, that this information is not strongly relied upon. The effect of this design choice is studied in the appendix.

3.3 OPTIMIZATION

The standard RGM objective in Eq.(5) can be viewed as finding a stationary point of a multi-player game between f, ϕ as well as the auxiliary predictors $\{f_{-e}\}$ and $\{f_e\}$. Our predictor f and representation ϕ find their best response strategies by minimizing

$$\min_{f, \phi} \left\{ \mathcal{L}(f \circ \phi) + \lambda \sum_e \left(\mathcal{L}^e(f_{-e} \circ \phi) - \mathcal{L}^e(f_e \circ \phi) \right) \right\} \tag{15}$$

---

[1]Our method is introduced using scaffolds as examples. It can be applied to other structured environments like protein families by simply replacing the scaffold classifier with a protein family classifier.

Algorithm 1 Structured RGM: Forward Pass

1: Sample two minibatches B_e from environment E_e
2: **for** each environment $E_e \in \mathcal{E}$ **do**
3:      Compute scaffold classification loss $\mathcal{L}_g(g \circ \phi)$ over B_e.
4:      Construct perturbed examples $\tilde{B}_e$ via gradient perturbation (see Eq.(10)) .
5:      Compute empirical loss $\mathcal{L}(f \circ \phi)$ on B_e.
6:      Compute auxiliary predictor loss $\mathcal{L}^{-e}(f_{-e} \circ \phi)$ on B_{-e}.
7:      Compute oracle predictor losses $\mathcal{L}^e(f_e \circ \phi)$ and $\mathcal{L}(\tilde{f}_e \circ \phi, \tilde{E}_e)$ on B_e and $\tilde{B}_e$.
8:      Compute regret terms $\mathcal{R}^e(\phi), \mathcal{R}^e(\phi + \delta)$ on B_e and $\tilde{B}_e$.
9: **end for**

---

while the auxiliary predictors minimize

$$\min_{f_{-e}} \mathcal{L}^{-e}(f_{-e} \circ \phi) \quad \text{and} \quad \min_{f_e} \mathcal{L}^e(f_e \circ \phi) \quad \forall e \tag{16}$$

This multi-player game can be optimized by stochastic gradient descent. Since f_e and ϕ optimizes $\mathcal{L}^e(f_e \circ \phi)$ in opposite directions, we introduce a gradient reversal layer (Ganin et al., 2016) between ϕ and f_e. This allows us to update all the players in a single forward-backward pass (see Figure 2). In each step, we simultaneously update all the players by

$$f \leftarrow f - \eta \nabla_f \mathcal{L}(f \circ \phi) \qquad\qquad \phi \leftarrow \phi - \eta \nabla_\phi \mathcal{L}(f \circ \phi) - \eta \lambda \sum_e \nabla_\phi \mathcal{R}^e(\phi)$$

$$f_{-e} \leftarrow f_{-e} - \eta \nabla \mathcal{L}^{-e}(f_{-e} \circ \phi) \qquad f_e \leftarrow f_e - \eta \nabla \mathcal{L}^e(f_e \circ \phi) \quad \forall e$$

where $\mathcal{L}^{-e}(f_{-e} \circ \phi) = \sum_{k \neq e} \mathcal{L}^k(f_{-e} \circ \phi)$. In each step, we sample minibatches $B_1, \cdots, B_n$ from each environment $E_1, \cdots, E_n$. The loss $\mathcal{L}(f \circ \phi)$ is computed over all the minibatches $\bigcup_k B_k$, while $\mathcal{L}^{-e}(f_{-e} \circ \phi)$ is computed over minibatches $B_{-e} = \bigcup_{k \neq e} B_k$. The regret term $R^e(\phi)$ is evaluated based on examples in B_e only.

For structured RGM, its optimization rule is analogous to RGM, with additional gradient updates for the oracle predictors $\tilde{f}_e$ and scaffold classifier g (see Appendix A.4). While the perturbation δ is defined on the basis of ϕ and g, we do not include the dependence during back-propagation as incorporating this higher order gradient does not improve our empirical results.

4 EXPERIMENTS

Our methods (RGM and SRGM) are evaluated on real-world applications such as molecular property prediction, protein homology and stability prediction. Our baselines include:

- Standard empirical risk minimization (ERM) trained on aggregated environments;
- Domain adversarial training methods including DANN (Ganin et al., 2016) and CDAN (Long et al., 2018), which seek to learn domain-invariant features;
- IRM (Arjovsky et al., 2019) requiring the model to be simultaneously optimal in all environments;
- MLDG (Li et al., 2018a), a meta-learning method which simulates domain shift by dividing training environments into meta-training and meta-testing;
- CrossGrad (Shankar et al., 2018) which augments the training set with domain-guided perturbations of inputs. Since our inputs are discrete, we perform perturbation on the representation instead.

4.1 MOLECULAR PROPERTY PREDICTION

Data The training data consists of $\{(x_i, y_i, s_i)\}$, where x_i is a molecular graph, y_i is its property and s_i is its scaffold. We adopt four datasets from the MoleculeNet benchmark (Wu et al., 2018):

- QM9 is a regression dataset of 134K compounds with 12 properties related to quantum chemistry. We split the dataset based on number of atoms: our training set contains molecules with no more than 7 atoms; our validation and test set consist of molecules with 8 and 9 atoms respectively. This setup is much harder than random split as it requires models to extrapolate to new chemical space.

Table 1: Mean absolute error (MAE) on the QM9 dataset. Models are trained on molecules with no more than 7 atoms and tested on molecules with 9 atoms. Due to space limit, we only show standard deviation for the top three methods in subscripts. We highlight the best method in each setup.

	Categorical environments						Scaffold environments	
Property	ERM	DANN	CDAN	IRM	MLDG	RGM	CrossGrad	SRGM
mu	0.658	0.655	0.655	0.690	**0.654**	$0.656_{(.004)}$	$0.664_{(.001)}$	$0.666_{(.005)}$
alpha	13.08	13.17	13.19	13.16	14.13	$\mathbf{12.99}_{(.028)}$	$12.79_{(.379)}$	$\mathbf{11.54}_{(.777)}$
HOMO	0.008	0.008	0.008	0.009	0.008	$0.008_{(.000)}$	$0.008_{(.000)}$	$0.009_{(.000)}$
LUMO	0.011	0.011	0.011	0.011	0.011	$\mathbf{0.010}_{(.000)}$	$0.011_{(.000)}$	$0.013_{(.000)}$
gap	0.014	0.013	0.014	0.015	0.014	$\mathbf{0.012}_{(.001)}$	$0.014_{(.001)}$	$0.016_{(.001)}$
R2	352.8	355.7	357.3	368.6	381.2	$\mathbf{328.4}_{(11.2)}$	$351.7_{(11.0)}$	$\mathbf{279.9}_{(29.6)}$
ZPVE	0.025	0.024	0.025	0.025	0.026	$\mathbf{0.022}_{(.000)}$	$0.024_{(.001)}$	$\mathbf{0.019}_{(.001)}$
Cv	5.336	5.351	5.369	5.327	5.756	$\mathbf{4.860}_{(.228)}$	$5.235_{(.176)}$	$\mathbf{3.909}_{(.420)}$
U0	67.18	67.57	67.34	67.67	71.83	$\mathbf{60.25}_{(2.62)}$	$63.82_{(1.82)}$	$\mathbf{51.32}_{(4.51)}$
U	66.67	67.00	67.24	68.55	71.60	$\mathbf{58.74}_{(2.51)}$	$64.30_{(1.47)}$	$\mathbf{51.54}_{(5.09)}$
H	67.00	67.39	67.27	68.23	71.47	$\mathbf{59.72}_{(2.23)}$	$64.39_{(2.19)}$	$\mathbf{50.17}_{(2.56)}$
G	65.92	65.95	66.02	68.16	70.70	$\mathbf{59.40}_{(2.12)}$	$64.63_{(1.12)}$	$\mathbf{51.23}_{(6.13)}$

- HIV, Tox21 and BBBP are three classification datasets related to medicinal chemistry. The three datasets contains 36K, 7K and 2K molecules respectively. The training and test sets are built by scaffold splitting. To measure extrapolation, we sort the scaffolds by their molecular weight and put the top 10% largest scaffolds in the test set. The training set contains 80% of the smallest scaffolds and the rest 10% scaffolds form the validation set (details in the appendix).

Setup The training set consists of multiple environments based on the Murcko scaffold (Bemis & Murcko, 1996). Since most of our baselines cannot utilize structural information of the environments (i.e., scaffolds), we consider two evaluation setup for fair comparison:

- *Categorical environments*: We cluster all the training environments into two environments E_0, E_1. For QM9, E_1 contains molecules with 7 atoms. For other datasets, E_1 contains the top 25% largest scaffolds. Under this setup, DANN, CDAN, IRM and MLDG are comparable with RGM.

- *Scaffold environments*: We compare SRGM with CrossGrad in this setup. Both methods utilizes scaffold information via gradient perturbation from a scaffold classifier g.

Following Wu et al. (2018), we report mean absolute error (MAE) for QM9 and AUROC for the HIV, Tox21 and BBBP. All the results are averaged across five independent runs.

Model The molecule encoder ϕ is a graph convolutional network (Yang et al., 2019) which translates a molecular graph into a continuous vector. The predictor f is a two-layer MLP that takes $\phi(x)$ as input and predicts the label. The scaffold classifier g is also a two-layer MLP trained by negative sampling since scaffold is a combinatorial object with a large number of possible values. Specifically, for a given molecule x with scaffold $u(x)$, we randomly sample K other molecules and take their associated scaffolds $\{u_k\}$ as negative classes. Details of model architecture and hyper-parameters are discussed in the appendix.

Results Our results on the QM9 dataset are shown in Table 1. In the categorical setup, RGM outperforms all the baselines (except for property mu), with significant improvement on six properties (R2, Cv, U0, U, H, G) with 7-10% relative error reduction. In the scaffold setup, SRGM outperforms all the baselines on eight properties (out of 12). While CrossGrad utilizes scaffold information, its performance is worse than RGM in general. Compared to RGM, SRGM shows significant error reduction (10-20%) on seven properties (alpha, R2, Cv, U0, U, H, G). This validates the advantage of exploiting structures of the environments (scaffolds).

Results on the classification datasets are shown in Table 2. In the categorical setup, RGM performs similarly to other baselines (within one standard deviation). In the scaffold setup, SRGM shows clear improvement on all three datasets, with a significant accuracy increase in the HIV dataset (0.735 v.s. 0.644). This further confirms the importance of exploiting the structure of domain shift.

	HIV	Tox21	BBBP	HOMO	stability
ERM	$0.614_{(.031)}$	$0.690_{(.008)}$	$0.895_{(.008)}$	20.9%	0.736
DANN	$0.624_{(.023)}$	$0.680_{(.005)}$	$0.896_{(.002)}$	22.3%	0.770
CDAN	$0.613_{(.055)}$	$0.682_{(.004)}$	$0.896_{(.005)}$	21.9%	0.750
IRM	$0.637_{(.043)}$	$0.686_{(.003)}$	$0.896_{(.009)}$	21.0%	0.723
MLDG	$0.639_{(.057)}$	$0.686_{(.009)}$	$0.896_{(.003)}$	22.0%	0.754
RGM	$0.644_{(.028)}$	$0.685_{(.004)}$	$0.895_{(.007)}$	**23.4%**	**0.787**
CrossGrad	$0.708_{(.035)}$	$0.694_{(.006)}$	$0.902_{(.002)}$	20.9%	0.662
SRGM	$\mathbf{0.735}_{(.015)}$	$\mathbf{0.701}_{(.003)}$	$\mathbf{0.911}_{(.003)}$	**23.8%**	**0.793**

Figure 4 & Table 2: *Left*: Ablation study on QM9 with various levels of domain shift. Models are trained on three different sets: molecules with less than 8, 7 and 6 atoms (increasing domain shift). *Right*: Results on molecule and protein datasets. CrossGrad and SRGM operate on the structured environments (scaffolds or topology), while RGM and others operate on categorical environments.

Ablation study We conduct additional experiments to study the performance of RGM/SRGM with respect to the severity of domain shift. Fixing the test set to molecules with 9 atoms, we construct three progressively harder training sets: molecules with no more than 8, 7 and 6 atoms. We report the MAE ratio (averaged over 12 properties) between SRGM/RGM/CrossGrad and ERM. As shown in Figure 4, SRGM consistently outperforms CrossGrad and RGM across different setups.

4.2 Protein Modeling

Data The dataset consists of pairs $\{(x_i, y_i, s_i)\}$, where x_i is a protein represented as sequence of amino acid characters and y_i denotes its property. We consider two datasets used in Rao et al. (2019):

- *Homology prediction* (HOMO) (Fox et al., 2013): The dataset consists of 12K for training, 736 for validation and 718 for testing, which are split by protein superfamilies (evolutionary groups). This requires models to generalize across large evolutionary gaps. There are 1823 protein superfamilies in total, with around 1200 of them having less than 10 instances in the training set.
- *Stability prediction* (Rocklin et al., 2017): The dataset has 54K for training, 2.4K for validation and 13K for testing. The train set contains proteins sampled broadly across sequence space, while the test set contains Hamming distance-1 neighbors of most stable proteins. The dataset contains 1218 topology groups, with around 1200 of them having no more than two instances.

Setup Each environment s_i corresponds to a protein superfamily or topology. Since most environments contain very few examples, we cluster them into two environments E_0, E_1. For the homology task, E_1 contains all superfamilies with less than 10 proteins and $E_0 = E - E_1$. For the stability task, we sort the topology groups by their frequency and divide them evenly into E_0 and E_1. SRGM and CrossGrad use gradient perturbation from a protein superfamily/topology classifier g, while RGM and other baselines are trained on the clustered environments E_0, E_1.

Model Our protein encoder ϕ is a pre-trained BERT model (Rao et al., 2019). The predictor f is a linear function that takes $\phi(x)$ as input and predicts its fold label or stability score. The superfamily and topology classifier g is a two-layer MLP. The hyperparameters are listed in the appendix.

Results Following Rao et al. (2019), we report the top-1 accuracy for homology prediction and Spearman ranking correlation ρ for stability prediction. Our ERM baseline matches their Transformer performance. Both RGM and SRGM outperforms all the baselines in both tasks (homology: 23.8% v.s. 22.3%; stability: 0.793 v.s. 0.770). The difference between RGM and SRGM is relatively smaller compared to the molecule domain.

5 Conclusion

In this paper, we propose regret minimization for generalization across structured biomedical domains such as molecular scaffolds or protein families. We seek to find a representation that enables the predictor to compete against an oracle with hindsight access to unseen domains. Our method significantly outperforms all baselines on real-world biomedical tasks.

REFERENCES

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Yogesh Balaji, Swami Sankaranarayanan, and Rama Chellappa. Metareg: Towards domain generalization using meta-regularization. In *Advances in Neural Information Processing Systems*, pp. 998–1008, 2018.

Guy W Bemis and Mark A Murcko. The properties of known drugs. 1. molecular frameworks. *Journal of medicinal chemistry*, 39(15):2887–2893, 1996.

Shiyu Chang, Yang Zhang, Mo Yu, and Tommi S Jaakkola. Invariant rationalization. *arXiv preprint arXiv:2003.09772*, 2020.

Remi Tachet des Combes, Han Zhao, Yu-Xiang Wang, and Geoff Gordon. Domain adaptation with conditional distribution matching and generalized label shift. *arXiv preprint arXiv:2003.04475*, 2020.

Hanjun Dai, Bo Dai, and Le Song. Discriminative embeddings of latent variable models for structured data. In *International Conference on Machine Learning*, pp. 2702–2711, 2016.

Qi Dou, Daniel Coelho de Castro, Konstantinos Kamnitsas, and Ben Glocker. Domain generalization via model-agnostic learning of semantic features. In *Advances in Neural Information Processing Systems*, pp. 6447–6458, 2019.

David K Duvenaud, Dougal Maclaurin, Jorge Iparraguirre, Rafael Bombarell, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P Adams. Convolutional networks on graphs for learning molecular fingerprints. In *Advances in neural information processing systems*, pp. 2224–2232, 2015.

Sara El-Gebali, Jaina Mistry, Alex Bateman, Sean R Eddy, Aurélien Luciani, Simon C Potter, Matloob Qureshi, Lorna J Richardson, Gustavo A Salazar, Alfredo Smart, Erik L L Sonnhammer, Layla Hirsh, Lisanna Paladin, Damiano Piovesan, Silvio C E Tosatto, and Robert D Finn. The Pfam protein families database in 2019. *Nucleic Acids Research*, 47(D1):D427–D432, 2019. ISSN 0305-1048. doi: 10.1093/nar/gky995. URL https://academic.oup.com/nar/article/47/D1/D427/5144153.

Evan N Feinberg, Debnil Sur, Zhenqin Wu, Brooke E Husic, Huanghao Mai, Yang Li, Saisai Sun, Jianyi Yang, Bharath Ramsundar, and Vijay S Pande. Potentialnet for molecular property prediction. *ACS central science*, 4(11):1520–1530, 2018.

Naomi K Fox, Steven E Brenner, and John-Marc Chandonia. Scope: Structural classification of proteins—extended, integrating scop and astral data and classification of new structures. *Nucleic acids research*, 42(D1):D304–D309, 2013.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Muhammad Ghifary, W Bastiaan Kleijn, Mengjie Zhang, and David Balduzzi. Domain generalization for object recognition with multi-task autoencoders. In *Proceedings of the IEEE international conference on computer vision*, pp. 2551–2559, 2015.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. *arXiv preprint arXiv:1704.01212*, 2017.

Jie Hou, Badri Adhikari, and Jianlin Cheng. Deepsf: deep convolutional neural network for mapping protein sequences to folds. *Bioinformatics*, 34(8):1295–1303, 2018.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). *arXiv preprint arXiv:2003.00688*, 2020.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Deeper, broader and artier domain generalization. In *Proceedings of the IEEE international conference on computer vision*, pp. 5542–5550, 2017.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Learning to generalize: Meta-learning for domain generalization. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018a.

Da Li, Jianshu Zhang, Yongxin Yang, Cong Liu, Yi-Zhe Song, and Timothy M Hospedales. Episodic training for domain generalization. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1446–1455, 2019a.

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5400–5409, 2018b.

Ya Li, Xinmei Tian, Mingming Gong, Yajing Liu, Tongliang Liu, Kun Zhang, and Dacheng Tao. Deep domain generalization via conditional invariant adversarial networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 624–639, 2018c.

Yiying Li, Yongxin Yang, Wei Zhou, and Timothy M Hospedales. Feature-critic networks for heterogeneous domain generalization. *arXiv preprint arXiv:1901.11448*, 2019b.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I Jordan. Conditional adversarial domain adaptation. In *Advances in Neural Information Processing Systems*, pp. 1640–1650, 2018.

Saeid Motiian, Marco Piccirilli, Donald A Adjeroh, and Gianfranco Doretto. Unified deep supervised domain adaptation and generalization. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 5715–5725, 2017.

Krikamol Muandet, David Balduzzi, and Bernhard Schölkopf. Domain generalization via invariant feature representation. In *International Conference on Machine Learning*, pp. 10–18, 2013.

Raghunathan Ramakrishnan, Pavlo O Dral, Matthias Rupp, and O Anatole Von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific data*, 1(1):1–7, 2014.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Xi Chen, John Canny, Pieter Abbeel, and Yun S Song. Evaluating protein transfer learning with tape. In *Advances in Neural Information Processing Systems*, 2019.

Gabriel J Rocklin, Tamuka M Chidyausiku, Inna Goreshnik, Alex Ford, Scott Houliston, Alexander Lemak, Lauren Carter, Rashmi Ravichandran, Vikram K Mulligan, Aaron Chevalier, et al. Global analysis of protein folding using massively parallel design, synthesis, and testing. *Science*, 357 (6347):168–175, 2017.

Shiv Shankar, Vihari Piratla, Soumen Chakrabarti, Siddhartha Chaudhuri, Preethi Jyothi, and Sunita Sarawagi. Generalizing across domains via cross-gradient training. *arXiv preprint arXiv:1804.10745*, 2018.

Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7167–7176, 2017.

Riccardo Volpi, Hongseok Namkoong, Ozan Sener, John C Duchi, Vittorio Murino, and Silvio Savarese. Generalizing to unseen domains via adversarial data augmentation. In *Advances in Neural Information Processing Systems*, pp. 5334–5344, 2018.

Zhenqin Wu, Bharath Ramsundar, Evan N Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S Pappu, Karl Leswing, and Vijay Pande. Moleculenet: a benchmark for molecular machine learning. *Chemical science*, 9(2):513–530, 2018.

Kevin Yang, Kyle Swanson, Wengong Jin, Connor Coley, Philipp Eiden, Hua Gao, Angel Guzman-Perez, Timothy Hopper, Brian Kelley, Miriam Mathea, et al. Analyzing learned molecular representations for property prediction. *Journal of chemical information and modeling*, 59(8): 3370–3388, 2019.

Han Zhao, Shanghang Zhang, Guanhang Wu, José MF Moura, Joao P Costeira, and Geoffrey J Gordon. Adversarial multiple source domain adaptation. In *Advances in neural information processing systems*, pp. 8559–8570, 2018.

Han Zhao, Remi Tachet des Combes, Kun Zhang, and Geoffrey J Gordon. On learning invariant representation for domain adaptation. *arXiv preprint arXiv:1901.09453*, 2019.

A TECHNICAL DETAILS

A.1 PROOF OF PROPOSITION 1

Note that $\mathcal{L}^e(f \circ \phi)$ is defined on a set of fixed examples in E_e. Since $f_e \in \arg\min_{f' \in \mathcal{F}} \mathcal{L}^e(f' \circ \phi)$ and f_e, f_{-e} are in the same parametric family $\mathcal{F}$, we have $\mathcal{R}^e(\phi) = \mathcal{L}^e(f_{-e} \circ \phi) - \mathcal{L}^e(f_e \circ \phi) \geq 0$.

A.2 PROOF OF PROPOSITION 2

Proof. Consider any representation $\phi^* \in \Phi_{\mathrm{RGM}}$. When there are only two environments $\{E_1, E_2\}$, we have $F_{-2}(\phi^*) = F_1(\phi^*)$ and $F_{-1}(\phi^*) = F_2(\phi^*)$ by definition. Thus the RGM constraint implies

$$F_2(\phi^*) = F_{-1}(\phi^*) \subseteq F_1(\phi^*) \qquad F_1(\phi^*) = F_{-2}(\phi^*) \subseteq F_2(\phi^*)$$

Therefore $F_1(\phi^*) = F_2(\phi^*)$. Since the loss function is non-negative and $\mathcal{F}$ is bounded and closed, $F_1(\phi^*) \neq \emptyset$. Thus, $\cap_e F_e(\phi^*) = F_1(\phi^*) \neq \emptyset$. Now consider any $f \in \cap_e F_e(\phi^*)$. By definition,

$$\forall e : \mathcal{L}^e(f \circ \phi^*) \leq \min_{h \in \mathcal{F}} \mathcal{L}^e(h \circ \phi^*)$$

By summing the above inequality over all environments, we have

$$\sum_e \mathcal{L}^e(f \circ \phi^*) \leq \sum_e \min_{h \in \mathcal{F}} \mathcal{L}^e(h \circ \phi^*) \leq \min_{h \in \mathcal{F}} \sum_e \mathcal{L}^e(h \circ \phi^*)$$

Since $\sum_e \mathcal{L}^e(f \circ \phi^*) = \mathcal{L}(f \circ \phi^*)$, the above inequality implies

$$\mathcal{L}(f \circ \phi^*) \leq \min_{h \in \mathcal{F}} \mathcal{L}(h \circ \phi^*) = \mathcal{L}^*_{\mathrm{RGM}} = \mathcal{L}^*_{\mathrm{IRM}}$$

Thus, $f \circ \phi^*$ is an optimal solution under IRM and $\phi^* \in \Phi_{\mathrm{IRM}}$. $\qquad \square$

A.3 PROOF OF PROPOSITION 3

Proof. Let us recall our assumption of the data generation process:

$$p(x, y, e) = p(e)p(x|e)p(y|x, e); \qquad p(y|x, e) = p(y|x, e(x))$$

Under this assumption, we can rephrase the IRM objective as

$$\min_{f, \phi} \quad \mathbb{E}_e \mathbb{E}_{x|e} \mathbb{E}_{y|x, e} \ell(y, f(\phi(x))) \tag{17}$$

$$\text{s.t.} \quad \mathbb{E}_{x|e} \mathbb{E}_{y|x, e} \ell(y, f(\phi(x))) \leq \min_{f_e} \mathbb{E}_{x|e} \mathbb{E}_{y|x, e} \ell(y, f_e(\phi(x))) \quad \forall e \tag{18}$$

Given any label-preserving representation $\phi(x)$, its ERM optimal predictor is

$$f^*(\phi(x)) = \arg\min_f \mathbb{E}_{y|\phi(x)} \ell(y, f(\phi(x))) \tag{19}$$

To see that f^* is ERM optimal, consider

$$\min_f \mathbb{E}_e \mathbb{E}_{x|e} \mathbb{E}_{y|x, e} \ell(y, f(\phi(x))) \quad \geq \quad \mathbb{E}_e \mathbb{E}_{x|e} \min_f \mathbb{E}_{y|x, e} \ell(y, f(\phi(x))) \tag{20}$$

$$= \quad \mathbb{E}_e \mathbb{E}_{x|e} \min_f \mathbb{E}_{y|\phi(x)} \ell(y, f(\phi(x))) \tag{21}$$

$$= \quad \mathbb{E}_e \mathbb{E}_{x|e} \mathbb{E}_{y|\phi(x)} \ell(y, f^*(\phi(x))) \tag{22}$$

where Eq.(21) holds because $\phi(x)$ is label-preserving. Note that f^* satisfies the IRM constraint because it is simultaneously optimal across all environments:

$$\forall e : \min_{f_e} \mathbb{E}_{x|e} \mathbb{E}_{y|x, e} \ell(y, f_e(\phi(x))) \quad \geq \quad \mathbb{E}_{x|e} \min_{f_e} \mathbb{E}_{y|x, e} \ell(y, f_e(\phi(x))) \tag{23}$$

$$= \quad \mathbb{E}_{x|e} \min_f \mathbb{E}_{y|\phi(x)} \ell(y, f(\phi(x))) \tag{24}$$

$$= \quad \mathbb{E}_{x|e} \mathbb{E}_{y|\phi(x)} \ell(y, f^*(\phi(x))) \tag{25}$$

Moreover, if $\phi \in \Phi_{\mathrm{IRM}}$ is an optimal representation, $f^* \circ \phi$ is an optimal solution of IRM. $\qquad \square$

Table 3: Dataset statistics

	QM9	HIV	Tox21	BBBP	Homology	Stability
Training	4K	25243	6427	1580	12.3K	54K
Validation	18K	6352	568	206	736	2.4K
Testing	113K	3959	839	256	718	13K

A.4 STRUCTURED RGM UPDATE RULE

Since $\tilde{f}_e$ and ϕ optimizes $\mathcal{L}(\tilde{f}_e \circ \phi, \tilde{E}_e)$ in different directions, we also introduce a gradient reversal layer between ϕ and $\tilde{f}_e$. The SRGM update rule is the following:

$$\phi \leftarrow \phi - \eta \nabla_\phi \mathcal{L}(f \circ \phi) - \eta \lambda_g \nabla_\phi \mathcal{L}_g(g \circ \phi) - \eta \lambda \sum_e \sum_{\psi \in \{0,\delta\}} \nabla_\phi \mathcal{R}^e(\phi + \psi)$$

$$f \leftarrow f - \eta \nabla_f \mathcal{L}(f \circ \phi) \qquad g \leftarrow g - \eta \nabla_g \mathcal{L}_g(g \circ \phi)$$

$$f_e \leftarrow f_e - \eta \nabla \mathcal{L}^e(f_e \circ \phi) \qquad \tilde{f}_e \leftarrow \tilde{f}_e - \eta \nabla \mathcal{L}(\tilde{f}_e \circ (\phi + \delta)) \quad \forall e$$

$$f_{-e} \leftarrow f_{-e} - \eta \nabla \mathcal{L}^{-e}(f_{-e} \circ \phi) \quad \forall e$$

B EXPERIMENTAL DETAILS

B.1 MOLECULAR PROPERTY PREDICTION

Data The four property prediction datasets are provided in the supplementary material, along with the training/validation/test splits. The size of each training environment, validation and test set are listed in Table 3. The QM9, Tox21 and BBBP dataset are downloaded from Wu et al. (2018). The HIV dataset is downloaded from the original source with EC50 measurements.[2] The positive class is defined as molecules with EC50 less than 1μM.

For the QM9 ablation study, we consider three training sets $\mathcal{D}_8, \mathcal{D}_7, \mathcal{D}_6$: molecules with no more than 8, 7 and 6 atoms (increasing domain shift). When training on $\mathcal{D}_8$, we sample 20K compounds from those with 9 atoms as our validation set and the rest for testing. This is less ideal for domain generalization evaluation since we want the validation and test set to come from different domains.

Model Hyperparameters For the feature extractor ϕ, we adopt the GCN implementation from Yang et al. (2019). We use their default hyperparameters across all the datasets and baselines. Specifically, the GCN contains three convolution layers with hidden dimension 300. The predictor f is a two-layer MLP with hidden dimenion 300 and ReLU activation. The model is trained with Adam optimizer for 30 epochs with batch size 50 and learning rate η linearly annealed from 10^{-3} to 10^{-4}.

For RGM, we explore $\lambda \in \{0.01, 0.1\}$ for each dataset. For SRGM, we explore $\lambda_g \in \{0.1, 1\}$ for the classification datasets while $\lambda_g \in \{0.01, 0.1\}$ for the QM9 dataset as $\lambda_g = 1$ causes gradient explosion. For DANN and CDAN, its hyperparameter is the weight of the adversarial domain classifier $\lambda_d \in \{0.1, 1\}$. For MLDG, its hyperparameter is $\beta \in \{0.1, 1\}$. Its inner optimization also uses Adam optimizer with default learning rate $\alpha = 10^{-3}$. For IRM, its hyperparameter is the weight of its gradient penalty term $\gamma \in \{0.1, 1\}$. The suggested value $\gamma = 100$ results in severe gradient explosion problem. For CrossGrad, its hyperparameter is the weight of the domain classifier $\lambda_d \in \{0.1, 1\}$.

Scaffold Classification The scaffold classifier is trained by negative sampling since scaffolds are structured objects. Specifically, for each molecule x_i in a minibatch B, the negative samples are the scaffolds $\{s_k\}$ of other molecules in the minibatch. The probability that x_i is mapped to its correct scaffold s_i is then defined as

$$p(s_i \mid x_i, B) = \frac{\exp\{g(\phi(x_i))^\top g(\phi(s_i))\}}{\sum_{k \in B} \exp\{g(\phi(x_i))^\top g(\phi(s_k))\}} \tag{26}$$

---

[2] https://wiki.nci.nih.gov/download/attachments/158204006/aids_ec50_may04.txt?version=1&modificationDate=1378736563000&api=v2

Figure 5: Ablation study of SRGM. *Left*: SRGM performs better than SRGM-detach which does not update ϕ to optimize the scaffold classification loss $\mathcal{L}_g$. *Right*: SRGM performs better than when the scaffold classifier is a MLP instead of a linear layer.

The scaffold classification loss is $-\sum_i \log p(s_i \mid x_i, B)$ for a minibatch B. We choose the classifier g to be a two-layer MLP with hidden dimension 300 and ReLU activation. As shown in Figure 5, the two-layer MLP performs better than a simple linear function across multiple tasks.

B.2 PROTEIN MODELING

Data The homology and stability dataset are downloaded from Rao et al. (2019). The size of each training environment, validation and test set are listed in Table 3.

Model hyperparameters For both tasks, our protein encoder is a pre-trained BERT (Rao et al., 2019). The predictor is a linear layer and the superfamily/topology classifier is a two-layer MLP whose hidden layer dimension is 768. The model is fine-tuned with an Adam optimizer with learning rate 10^{-4} and linear warm up schedule. The batch size is 16 and 20 for the homology and stability task. For RGM and SRGM, we explore $\lambda \in \{0.01, 0.1\}$ and $\lambda_g \in \{0.1, 1\}$ respectively. For the other baselines, please refer to section B.1.

B.3 ADDITIONAL ABLATION STUDY

In section 3.2, we mentioned that the feature extractor ϕ is updated to optimize the scaffold classification loss $\mathcal{L}_g$. To study the effect of this design choice, we experiment with a variant of SRGM called SRGM-detach, in which ϕ is not updated to optimize the scaffold classification loss. As shown in Figure 5, the performance of SRGM-detach is worse than SRGM in general. This is because the scaffold classifier performs much better in SRGM and the gradient $\delta(x)$ clearly corresponds to the change of scaffold information.