Asymmetric Temperature Scaling Makes Larger Networks Teach Well Again

Abstract

Knowledge Distillation (KD) aims at transferring the knowledge of a well-performed neural network (the *teacher*) to a weaker one (the *student*). A peculiar phenomenon is that a more accurate model doesn't necessarily teach better, and temperature adjustment can neither alleviate the mismatched capacity. To explain this, we decompose the efficacy of KD into three parts: *correct guidance*, *smooth regularization*, and *class discriminability*. The last term describes the distinctness of *wrong class probabilities* that the teacher provides in KD. Complex teachers tend to be over-confident and traditional temperature scaling limits the efficacy of *class discriminability*, resulting in less discriminative wrong class probabilities. Therefore, we propose *Asymmetric Temperature Scaling (ATS)*, which separately applies a higher/lower temperature to the correct/wrong class. ATS enlarges the variance of wrong class probabilities in the teacher's label and makes the students grasp the absolute affinities of wrong classes to the target class as discriminative as possible. Both theoretical analysis and extensive experimental results demonstrate the effectiveness of ATS.

1   Introduction

Although large-scale deep neural networks have achieved overwhelming successes in many real-world applications [22, 11, 60], the vast capacity hinders them from being deployed on portable devices with limited computation and storage resources [3]. Some efficient architectures, e.g., MobileNets [14, 37] and ShuffleNets [59, 29], have been proposed for lightweight deployment, while their performances are usually constrained. Fortunately, knowledge distillation (KD) [46, 13] could transfer the knowledge of a more complex and well-performed network (i.e., the *teacher*) to them.

The original KD [13] forces the student to mimic the teacher's behavior via minimizing the Kullback-Leibler (KL) divergence between their output probabilities. Recent studies generalize KD to various types of knowledge [36, 57, 17, 12, 33, 1, 34, 44, 52, 27, 54, 45, 50, 26, 23] or various distillation schemes [61, 2, 58, 20]. An intuitive sense after the proposal of KD [13] is that larger teachers could teach students better because their accuracies are higher. A recent work [6] first points out that the teacher accuracy is a poor predictor of the student's performance. That is, more accurate neural networks don't necessarily teach better. Until now, this phenomenon is still counter-intuitive [51], surprising [31], and unexplored [24]. Different from some existing empirical studies and theoretical analysis [40, 18, 30, 35, 55, 63, 6, 28, 15], we investigate the miraculous phenomenon in detail and aim to answer the following questions: *What's the real reason that more complex teachers can't teach well? Is it really impossible to make larger teachers teach better through simple operations, such as temperature scaling?*

To answer the first question, we focus on analyzing the distinctness of wrong class probabilities that a teacher provides in KD. We decompose the teacher's label into three parts (see Sect. 4.1): (I)

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: **Left**: Decomposition of a teacher's label. The first class is the target. As temperature increases, *correct guidance* is weaker, *smooth regularization* is stronger, while *class discriminability* (measured by the variance of wrong class probabilities) will first increase and then decrease. **Right**: Larger/Smaller teachers' logits are consistent in relative class affinities, i.e., logit values of the four wrong classes are in the same order of magnitude. However, larger teachers are over-confident and give a larger target logit or smaller *inherent variance*, leading to a smaller *derived variance* under traditional temperature scaling, i.e., less distinct wrong class probabilities after softmax.

Correct Guidance: the correct class's probability; (II) *Smooth Regularization*: the average probability of wrong classes; (III) *Class Discriminability*: the variance of wrong class probabilities (defined as *derived variance*). The commonly utilized temperature scaling could control the efficacy of these three terms (the left of Fig. 1). More complex teachers are over-confident and assign a larger score for the correct class or less varied scores for the wrong classes. If we use a uniform temperature to scale their logits, the *class discriminability* of the larger teacher is less effective (theoretically analyzed in Sect. 4.2), i.e., the probabilities of wrong classes are less distinct (the right of Fig. 1).

As to the second question, we focus on enlarging the variance of wrong class probabilities (i.e., *derived variance*) that a teacher provides to make the distillation process more discriminative. To specifically enhance the distinctness of wrong class probabilities, we separately apply a higher/lower temperature to the correct/wrong class's logit instead of a uniform temperature (see Sect. 4.3). We name our method *Asymmetric Temperature Scaling (ATS)*, and abundant experimental studies verify that utilizing this simple operation could make larger teachers teach well again.

2   Related Works

KD with Larger Teacher: Although KD has been a general technique for knowledge transfer in various applications [13, 61, 42, 25], could any student learn from any teacher? [6] first studies the KD's dependence on student and teacher architectures. They find that larger models do not often make better teachers and propose the *early-stopped teacher* as a solution. [31] introduces a multi-step KD process, employing an intermediate-sized network (the *teacher assistant*) to bridge the capacity gap. [51] formulates KD as a multi-task learning problem with several knowledge transfer losses. The transfer loss will be utilized only when its gradient direction is consistent with the cross-entropy loss. [10, 24] define the knowledge gap as *residual*, which is utilized to teach the *residual student*, and then they take the ensemble of the student and residual student for inference. These works attribute the worse teaching performance to capacity mismatch, i.e., weaker students can't completely mimic the excellent teachers. However, they don't explain this peculiar phenomenon in detail.

Understanding of KD: Quite a few works focus on understanding the advantages of KD from a principled perspective. [28] unifies KD and privileged information into *generalized distillation*. [35, 18] utilize gradient flow and neural tangent kernel to analyze the convergence property of KD under deep linear networks and infinitely wide networks. [5] explains KD via quantifying the task-relevant and task-irrelevant visual concepts. [7] casts KD as a semiparametric inference problem and proposes corresponding enhancements. Our work is more related to KD decompositions. [9] treats the teacher's correct/wrong outputs differently, respectively explaining them as importance weighting and class similarities. [40] further decomposes the "dark knowledge" into universal knowledge, domain knowledge, and gradient rescaling. [30] establishes a bias-variance tradeoff to quantify the

divergence of a teacher with the *Bayes teacher*. [63] utilizes bias-variance decomposition to analyze KD and discovers *regularization samples* that could increase bias and decrease variance. Our work is also related to Label smoothing (LS). [55] points out that the regularization effect in KD is similar to LS. [32] finds that training a teacher with LS could degrade its teaching quality, and attributes this to the fact that LS erases *relative information* between teacher logits. Recently, [38] further studies this problem and proposes a metric to measure the degree of erased information quantitatively. Our work also decomposes KD into several effects to study why more complex teachers can't teach well. Detailed relatedness to these works is presented in Sect. 4.1.

3 Background

We consider a C-class classification problem with $\mathcal{Y} = [C] = \{1, 2, \cdots, C\}$. Given a neural network and a sample pair $(\mathbf{x}, y)$, we could obtain the "logits" as $\mathbf{f}(\mathbf{x}) \in \mathbb{R}^C$. We denote the softmax function with temperature τ as $\mathrm{SF}(\cdot; \tau)$, i.e., $\mathbf{p}_c(\tau) = \exp\left(\mathbf{f}_c(\mathbf{x})/\tau\right)/Z(\tau)$ and $Z(\tau) = \sum_{j=1}^{C} \exp\left(\mathbf{f}_j(\mathbf{x})/\tau\right)$, where $\mathbf{p}(\tau)$ is the softened probability vector that a network outputs and c is the index of class. Later, we may omit the dependence on $\mathbf{x}$ and τ if without any ambiguity. We use $\mathbf{f}_y$ and $\mathbf{p}_y$ to denote the *correct class*'s logit and probability, while we use $\mathbf{g}$ and $\mathbf{q}$ to represent the vector of *wrong classes*' logits and probabilities, i.e., $\mathbf{g} = [\mathbf{f}_c]_{c \neq y}$ and $\mathbf{q} = [\mathbf{p}_c]_{c \neq y}$.

The most standard KD [13] contains two stages of training. The first stage trains complex teachers, and then the second stage transfers the knowledge from teachers to a smaller student via minimizing the KL divergence between softened probabilities. Usually, the loss function during the second stage (i.e., the student's learning objective) is a combination of cross-entropy loss and distillation loss:

$$\ell = \underbrace{-(1 - \lambda) \log \mathbf{p}_y^S(1)}_{\text{CE Loss}} \underbrace{-\lambda\tau^2 \sum_{c=1}^{C} \mathbf{p}_c^T(\tau) \log \mathbf{p}_c^S(\tau)}_{\text{KD Loss}}, \tag{1}$$

where the upper script "T"/"S" denotes "Teacher"/"Student" respectively. Commonly, a default temperature of 1 is utilized for the CE loss, and the student could also take a temperature of 1 for the KD loss, e.g., $\mathbf{p}_c^S(\tau = 1)$ [13, 31, 45, 44].

Suppose we have two teachers, denoted as T_{large} and T_{small}, and the larger teacher performs better on both training and test data. If we use them to teach the same student S, we could find that the student's performance is worse when mimicking the larger teacher's outputs. Adjusting the temperature could neither make the larger teacher teach well. The details of this phenomenon could be found in [6, 31] and Fig. 9. Obviously, $\mathbf{p}^{T_{\text{large}}}$ could differ a lot from $\mathbf{p}^{T_{\text{small}}}$, which is the only difference in the loss function when teaching the student. Hence, we focus on analyzing *what probability distributions are tended to be provided by teachers with different capacities*.

4 Proposed Methods

This section first decomposes KD into three parts and defines several quantitative metrics. Then, we present theoretical analysis to demonstrate why larger networks can't teach well. Finally, we propose a more appropriate temperature scaling approach as an alternative.

4.1 KD Decomposition

We omit the coefficient of $\lambda\tau^2$ in Eq. 1, and define $e\left(\mathbf{q}^T(\tau)\right) = \frac{1}{C-1} \sum_{j=1, j \neq y}^{C} \mathbf{p}_j^T(\tau)$, where $\mathbf{q}^T(\tau) = [\mathbf{p}_c^T(\tau)]_{c \neq y}$. Then, we have the following decomposition:

$$\ell_{\text{kd}} = \underbrace{-\mathbf{p}_y^T(\tau) \log \mathbf{p}_y^S(\tau)}_{\text{Correct Guidance}} \underbrace{- \sum_{c \neq y} e\left(\mathbf{q}^T(\tau)\right) \log \mathbf{p}_c^S(\tau)}_{\text{Smooth Regularization}} \underbrace{- \sum_{c \neq y} \left(\mathbf{p}_c^T(\tau) - e\left(\mathbf{q}^T(\tau)\right)\right) \log \mathbf{p}_c^S(\tau)}_{\text{Class Discriminability}}. \tag{2}$$

(I) Correct Guidance: this term guarantees correctness during teaching. The decomposition in [9] also contains this term, which is explained as importance weighting. This term works similarly to the cross-entropy loss, which could be dealt with separately when applying temperature scaling.

112 **(II) Smooth Regularization**: some previous works [55, 62, 63] attribute the success of KD to the
113 efficacy of regularization and study its relation to label smoothing (LS). The combination of this term
114 with *correct guidance* works similarly to LS. Notably, $e_{j\neq y}\left(\mathbf{p}_j^T(\tau)\right)$ differs across samples, implying
115 that the strength of smoothing is instance-specific, which is similar to the analysis in [62].

116 **(III) Class Discriminability**: this term tells the student the affinity of wrong classes to the correct
117 class. Transferring the knowledge of class similarities to students has been the mainstream guess of
118 the "dark knowledge" in KD [13, 38]. Ideally, a good teacher should be as discriminating as possible
119 in telling students which classes are more related to the correct class.

120 Illustrations of the decomposition are presented in the left of Fig. 1. Obviously, an appropriate
121 temperature should simultaneously contain the efficacy of the three terms, e.g., the shaded row in
122 Fig. 1. A too high or too low temperature could lead to smaller *class discriminability*, making the
123 guidance less different among wrong classes, which weakens the distillation performance in practical.
124 Among these three terms, we advocate that *class discriminability* is more fundamental in KD and
125 present more discussions in Appendix A (verified in Fig. 2 and Fig. 3).

126 To measure these three terms quantitatively, we use the *target class probability* (i.e., $\mathbf{p}_y$), the *average*
127 *of wrong class probabilities* (i.e., $e(\mathbf{q}) = \frac{1}{C-1}\sum_{j\neq y}\mathbf{p}_j$), and the *variance of wrong class probabilities*
128 (i.e., $v(\mathbf{q}) = \frac{1}{C-1}\sum_{j\neq y}\left(\mathbf{p}_j - e(\mathbf{q})\right)^2$) as estimators. $e(\cdot)$ and $v(\cdot)$ calculates the mean and variance
129 of the elements in a vector. In some cases, we use the standard deviation as an estimator for the
130 third term, i.e., $\sigma[\mathbf{q}] = v^{1/2}(\mathbf{q})$. Because the latter two terms are calculated after applying softmax
131 to the complete logit vector, we define them as *Derived Average (DA)* and *Derived Variance (DV)*,
132 respectively. In experiments, we calculate these metrics for all training samples and sometimes report
133 the average or standard deviation across these samples.

4.2 Theoretical Analysis

135 We analyze the mean and variance of the softened probability vector, i.e., the teacher's label $\mathbf{p}^T(\tau)$
136 used in KD. We defer the proofs of Lemma 4.1 and Proposition 4.3, 4.4 to Appendix B.

137 **Lemma 4.1** (Variance of Softened Probabilities)**.** *Given a logit vector* $\mathbf{f} \in \mathbb{R}^C$ *and the softened*
138 *probability vector* $\mathbf{p} = SF(\mathbf{f};\tau), \tau \in (0,\infty)$, $v(\mathbf{p})$ *monotonically decreases as* τ *increases.*

139 As τ increases, $\mathbf{p}(\tau)$ becomes more uniform, i.e., it's entropy increases. However, we especially
140 focus on the wrong classes, where the mean and variance are more intuitive to calculate and analyze.

141 **Assumption 4.2.** The target logit is higher than other classes' logits, i.e., $\mathbf{f}_y \geq \mathbf{f}_c, \forall c \neq y$.

142 Assumption 4.2 is rational because well-performed teachers could almost achieve a higher accuracy
143 (e.g., >95%) on the training set, and most training samples meet this requirement.

144 **Proposition 4.3.** *Under Assumption 4.2,* $\mathbf{p}_y$ *monotonically decreases as* τ *increases, and* $e(\mathbf{q})$
145 *monotonically increases as* τ *increases. As* $\tau \to \infty$, $e(\mathbf{q}) \to 1/C$.

146 Proposition 4.3 implies that increasing temperature could lead to a higher *derived average* (empirically
147 see Fig. 7) and strengthen the *smooth regularization* term in Eq. 2.

148 Before we analyze the *class discriminability* term, we define $\tilde{\mathbf{q}}(\tau)$ as the result of applying softmax
149 *only to the wrong logits* with temperature τ, i.e., $\tilde{\mathbf{q}}(\tau) = \mathrm{SF}(\mathbf{g};\tau)$. For the element index c' of $\mathbf{q}$, we
150 have

$$\tilde{\mathbf{q}}_{c'}(\tau) = \exp(\mathbf{g}_{c'}/\tau)/\sum_j \exp(\mathbf{g}_j/\tau). \tag{3}$$

151 Notably, $\tilde{\mathbf{q}}$ differs from $\mathbf{q}$ a lot. Specifically, the former satisfies $\sum_{c'}\tilde{\mathbf{q}}_{c'} = 1$, while the summation of
152 the latter is $\sum_{c\neq y}\mathbf{p}_c = 1 - \mathbf{p}_y$. The former does not depend on the correct class's logit while the latter
153 does. We name $v(\tilde{\mathbf{q}})$ *Inherent Variance (IV)* because it only depends on wrong classes' logits.

154 **Proposition 4.4** (Derived Variance vs. Inherent Variance)**.** *The derived variance is determined by*
155 *the square of derived average and the inherent variance via:*

$$\underbrace{v(\mathbf{q})}_{DV} = (C-1)^2 \underbrace{e^2[\mathbf{q}]}_{DA^2} \underbrace{v(\tilde{\mathbf{q}})}_{IV}. \tag{4}$$

156 With τ increases, $e(\mathbf{q})$ increases (Proposition 4.3) while $v(\tilde{\mathbf{q}})$ decreases (Lemma 4.1), and hence, it
157 is not so easy to judge the specific monotonicity of $v(\mathbf{q})$ w.r.t. τ. Empirically, we observe that the

158 *derived variance* first increases and then decreases (see Fig. 7), which conforms to the change of the
159 *class discriminability* as illustrated in Fig. 1.

160 We could use Proposition 4.4 to clearly analyze why larger teacher networks can't teach well. Before
161 this, we present another two properties and a corollary without detailed proof.

162 *Remark* 4.5. Fixing $\mathbf{g}$ and τ, a higher target logit $\mathbf{f}_y$ leads to a higher $\mathbf{p}_y$, i.e., a smaller *derived*
163 *average* $e(\mathbf{q})$.

164 *Remark* 4.6. Fixing τ, less varied wrong logits $\mathbf{g}$ leads to less varied $\tilde{\mathbf{q}}$, i.e., a smaller *inherent*
165 *variance* $v(\tilde{\mathbf{q}})$.

166 **Corollary 4.7.** *Suppose we have two teachers T_1 and T_2, and their logit vectors for a same sample*
167 *are $\mathbf{f}^{T_1}$ and $\mathbf{f}^{T_2}$.*

168 • *If $\mathbf{f}_y^{T_1} \geq \mathbf{f}_y^{T_2}$ while $\mathbf{g}^{T_1}$ and $\mathbf{g}^{T_2}$ are nearly the same, then $\mathbf{p}_y^{T_1} \geq \mathbf{p}_y^{T_2}$ (Remark 4.5) while*
169 $v(\tilde{\mathbf{q}}^{T_1}) \approx v(\tilde{\mathbf{q}}^{T_2})$. *Hence, $v(\mathbf{q}^{T_1}) \leq v(\mathbf{q}^{T_2})$.*

170 • *If $\mathbf{f}_y^{T_1} \approx \mathbf{f}_y^{T_2}$ while $v(\mathbf{g}^{T_1}) \leq v(\mathbf{g}^{T_2})$, then $\mathbf{p}_y^{T_1} \approx \mathbf{p}_y^{T_2}$ while $v(\tilde{\mathbf{q}}^{T_1}) \leq v(\tilde{\mathbf{q}}^{T_2})$ (Remark 4.6).*
171 *Hence, $v(\mathbf{q}^{T_1}) \leq v(\mathbf{q}^{T_2})$.*

172 This corollary explains why a larger teacher can't teach better. Because the larger teacher tends to be
173 over-confident, the target logit $\mathbf{f}_y$ may be larger or the variance of wrong logits $v(\mathbf{g})$ may be smaller.
174 These are illustrated in Fig. 1 and empirically verified in Fig. 4. Then the *derived variance* $v(\mathbf{q})$ may
175 be smaller, limiting the efficacy of *class discriminability* in Eq. 2. Empirical results are in Fig. 7.

176 Notably, we focus on analyzing the variance of wrong class probabilities instead of all classes.
177 Maximizing the variance of all classes' probabilities does not mean maximizing the variance of
178 wrong classes'. For example, although a very low temperature can maximize the variance of all
179 classes' probabilities, the generated teacher's label is one-hot that shows no distinctness between
180 wrong classes. In other words, the effectiveness of KD should be more related to the distinctness
181 between wrong classes rather than all classes. However, traditional temperature scaling applies a
182 uniform temperature for all classes, which cannot separately handle the wrong classes.

183 ## 4.3 Asymmetric Temperature Scaling

184 We conclude the above analysis: *if a larger teacher makes an over-confident prediction, the wrong*
185 *class probabilities it provides could be not discriminative enough.* Utilizing a uniform temperature
186 could not enlarge the *derived variance* as much as possible with the interference of the target class's
187 logit (see the middle of Fig. 7). Thanks to the decomposition in Eq. 2, the *correct guidance* term
188 works similarly to the cross-entropy loss and allows us to deal with it separately. Hence, we propose
189 a novel temperature scaling approach:

$$\mathbf{p}_c(\tau_1, \tau_2) = \exp\left(\mathbf{f}_c/\tau_c\right) / \sum_{j \in [C]} \exp\left(\mathbf{f}_j/\tau_j\right), \qquad \tau_i = \mathcal{I}\{i = y\}\tau_1 + \mathcal{I}\{i \neq y\}\tau_2, \forall i \in [C], \quad (5)$$

190 where we take $\tau_1 > \tau_2 > 0$. This approach is named *Asymmetric Temperature Scaling (ATS)* because
191 we apply different temperatures to the logits of correct and wrong classes. According to Eq. 4, ATS
192 could bring such benefits when the teacher is over-confident:

193 • If the teacher outputs a larger logit $\mathbf{f}_y$ for the correct class, a relatively larger τ_1 could
194 decrease it to a reasonable magnitude, i.e., decreasing $\mathbf{p}_y$ and increasing $e(\mathbf{q})$, and finally
195 increasing the *derived variance* $v(\mathbf{q})$;

196 • If the teacher outputs less varied logits $\mathbf{g}$ for wrong classes, a relatively smaller temperature
197 τ_2 could make them more diverse, i.e., increasing $v(\tilde{\mathbf{q}})$, finally increasing the *derived*
198 *variance* $v(\mathbf{q})$.

199 ATS is more flexible in enlarging the *derived variance* (see the right of Fig. 7), i.e., it could generate
200 more discriminative distillation guidance during teaching. Take the demo in Fig. 1 as an example, the
201 smaller and larger teacher captures the same relative class affinities, e.g., they both know that the
202 fourth/fifth class (shaded cells) is the most/least relevant to the target class. However, with a uniform
203 temperature 4.0, the smaller teacher provides probabilities $(0.073, 0.060)$ for these two classes,
204 while over-confident larger teachers provide $(0.040, 0.033)$ or $(0.074, 0.067)$. Clearly, the absolute
205 affinities of the larger teachers are not so discriminative as the smaller teacher's. Utilizing ATS, we

Figure 2: Student's test accuracies without KD ("NoKD"), with KD ("-KD"), and only with the first two terms in Eq. 2 ("-ILS"). "ST"/"LT" refers to "small/large teacher".

Figure 3: Correlations of *smooth regularization* (measured by *derived average*) and *class discriminability* (measured by *derived variance*) w.r.t. KD improvement ratio.

could respectively apply $(\tau_1 = 4.67, \tau_2 = 4.0)$ or $(\tau_1 = 4.0, \tau_2 = 2.0)$ to the over-confident teacher's logits, generating the same probability vector as the smaller teacher's. ATS utilizes two temperatures and creates the wiggle room to make the distribution over wrong classes more discriminative.

5   Experiments

We use CIFAR-10/CIFAR-100 [21], TinyImageNet [43], CUB [47], Stanford Dogs [19], and Google Speech Commands [48] as the datasets. For teacher networks, we use different versions of ResNet [11], WideResNet [56], ResNeXt [49]. For student networks, we use VGG [39], ShuffleNetV1/V2 [59, 29], AlexNet [22], MobileNetV2 [37], and DSCNN [60]. Details are in Appendix C.

5.1   Observations

Class discriminability matters a lot in KD and correlates with the KD improvement. To show the importance of *class discriminability* in KD, we omit the distinctness of wrong class probabilities during distillation. Specifically, we only keep the first two terms in Eq. 2, which works similarly to the instance-specific label smoothing (abbreviated as "ILS"). Fig. 2 shows students' performances on CIFAR-100. Without the third term in Eq. 2, both small teachers ("ST") and larger teachers ("LT") teach worse significantly. Then, we investigate the correlations of KD performance improvement (i.e., the test accuracy change ratio with KD w.r.t. without KD) with *smooth regularization* and *class discriminability* under 270 pairs of "(teacher, student, temperature)". Details are in Appendix C.4. Fig. 3 plots the scatters, where dots show pairs whose improvement is higher than 2%. Clearly, teachers with a larger *derived variance* tend to guide better. *These observations show the rationality of the proposed KD decomposition and imply that enhancing derived variance is beneficial.*

Larger teachers provide a larger target logit or less varied wrong logits. We first compare the logit distributions provided by larger and smaller teachers on the training set. Fig. 4 plots the histograms (200 bins) of the target logit (i.e., $\mathbf{f}_y$) and the standard deviation of wrong logits (i.e., $\sigma[\mathbf{g}]$). The left and right, respectively, show the results on CIFAR-100 and CIFAR-10. Clearly, the first column shows that ResNet110 tends to generate a larger target logit (i.e., $\mathbb{E}_{\mathbf{x}}[\mathbf{f}_y] \approx 15.0$) than ResNet14 (i.e., $\mathbb{E}_{\mathbf{x}}[\mathbf{f}_y] \approx 10.0$). On CIFAR-10, the smallest $\mathbf{f}_y$ given by WRN28-8 is larger than WRN28-1. Furthermore, WRN28-8 gives smaller variance (the fourth column), i.e., smaller *inherent variance*. *These reveal specific manifestations of complex networks' over-confidence.*

Larger and smaller teachers have similar inherent variance while different derived variance under traditional temperature scaling. We use $\tau = 1.0$ to soften the *complete logits* and *only the wrong class logits*, respectively, and then show the mean and standard deviation of *derived variance* and *inherent variance* across training samples in Fig. 5. Although the larger models' *inherent variance* is smaller, the difference between RNX29-4-4d and RNX29-64-4d is only up to $1.3\times$. However, the *derived variance* differs a lot, where the smaller teacher's variance is approximately $9.7\times$ as the larger teacher's. These observations imply that *traditional temperature scaling could seriously decrease the derived variance of larger teachers though they have appreciable inherent variance*.

Complex teachers know approximately the same as smaller teachers on relative class affinities. Only if the relative magnitudes of the wrong class probabilities are correct, it is valid to enlarge the discrimination between them. Otherwise, if a teacher himself misunderstands the knowledge's principles, it will be counterproductive to reinforce this knowledge to students. Given two teachers

Figure 4: The distributions of the *target logit* ($\mathbf{f}_y$) and the *standard deviation of wrong logits* ($\sigma[\mathbf{g}]$) of the 50K training samples on CIFAR-10/100. Rows show networks with various capacity.

Figure 5: The *derived variance* and *inherent variance* on CIFAR-100 using ResNeXt. Each bar shows the mean and standard deviation across 50K training samples. The x-axis shows networks with various capacity.

Figure 6: Several metrics among teachers with various capacities on CIFAR-10. The first three metrics are related to the relative magnitudes of teachers' label, while distillation distance is related to the absolute magnitudes.

Figure 7: The change of *derived average* ($e(\mathbf{q})$) and *derived variance* ($v(\mathbf{q})$) as τ increases from 0.1 to 10.0 on CIFAR-10. The third one shows the results of ResNet110 with the proposed ATS. *DV* under TS is limited while ATS enlarges it.

T_1 and T_2, we first calculate the *Spearman correlation* between $\mathbf{p}^{T_1}$ and $\mathbf{p}^{T_2}$. Second, the set overlap between the top-5 predictions is calculated, i.e., $|\mathcal{C}^{T_1} \cap \mathcal{C}^{T_2}|/|\mathcal{C}^{T_1} \cup \mathcal{C}^{T_2}|$. $\mathcal{C}$ denotes the set of top-5 predicted classes. Third, we calculate Kendall's τ between $\mathbf{p}^{T_1}$ and $\mathbf{p}^{T_2}$, which directly shows the rank correlation of two teachers. These metrics only depend on classes' relative magnitudes. The results are in Fig. 6. Excitingly, these metrics among teachers with different capacities do not vary a lot, and the Spearman correlations are almost all larger than 0.85. According to the interpretation of Kendall's τ [8, 53], if the smaller teacher predicts that class i is more related to the target class than that of class j, then the larger teacher has a probability of $(0.75 + 1)/2 = 0.875$ to give the same relative affinity. As a comparison, we also calculate the distillation distance defined in [15], which utilizes L1 distance and depends on the absolute magnitudes of probabilities. Using this metric, the distance increases quickly as the capacity gap increases. These observations demonstrate that *teachers know approximately the same about relative class affinities while their absolute values differ significantly under traditional temperature scaling*.

The proposed ATS could enlarge the derived variance of larger teachers. The above analysis verifies that the over-confident teachers experience lower *derived variance* under traditional temperature scaling although they grasp the relative class affinities well. For an intuitive visualization, we plot the probabilities for a randomly sampled instance whose correct class is $y = 1$ from CIFAR-100. The top two rows in Fig. 8 show the results of RNX29-4-4d and RNX29-64-4d under traditional temperature scaling (TS), where the latter really experiences a smaller *derived variance*. Using ATS could enhance the *derived variance* as shown at the bottom row (the bars are more jagged). Then, we study the change of *derived average* (DA) and *derived variance* (DV) as temperature increases. Given a τ, we obtain the DA and DV for all training samples via softmax and then calculate the average. For ATS, we use $\tau_1 = 1.25\tau$ and $\tau_2 = 0.75\tau$. The curves are shown in Fig. 7. According to Proposition 4.3, $e(\mathbf{q})$ increases as τ increases, which enhances the efficacy of *smooth regularization*. Notably, this term changes nearly the same between teachers with various capacities. However, the *derived variance* $v(\mathbf{q})$ differs a lot. Empirically, $v(\mathbf{q})$ first increases and then decreases, and the maximal of the larger teacher's DV is smaller, which verifies the Corollary 4.7. Because *derived variance* corresponds to the efficacy of *class discriminability*, this shows why larger teachers can't teach well. Using the proposed ATS could enhance the *derived variance*, which equivalently improves the efficacy of *class discriminability* in KD. We conclude that *traditional temperature scaling leads to*

Figure 8: Probability vector visualization of a randomly selected training sample from CIFAR-100. The target class is $y = 1$. The bottom row shows applying ATS to the larger teacher.

Figure 9: Distillation results via TS (solid curves) and ATS (dashed curves) on CIFAR-100. The x-axis of each figure shows teachers with various capacities.

Table 1: Comparisons with SOTA methods on CIFAR-100. ResNet110, WRN28-8, and RNX29-64-4d are teachers. VGG8, SFV1, and MV2 are students. The area in gray shows the results of the ensemble. "KD+ATS" and "KD+ATS+Ens" are our methods.

Teacher	ResNet110 (74.09)			WRN28-8 (79.73)			RNX29-64-4d (79.91)			Avg
Student	VGG8	SFV1	MV2	VGG8	SFV1	MV2	VGG8	SFV1	MV2	
NoKD	69.92	70.04	64.75	69.92	70.04	64.75	69.92	70.04	64.75	68.24
ST-KD	72.30	73.22	66.56	71.85	72.85	**66.52**	71.61	72.18	65.82	70.32
KD	71.35	71.86	65.49	70.46	70.87	64.97	71.13	71.80	64.99	69.21
ESKD	71.88	72.02	65.92	71.13	71.32	65.09	71.09	71.27	64.83	69.39
TAKD	**72.71**	72.86	66.98	71.20	71.62	65.11	71.46	71.44	65.36	69.86
SCKD	70.38	70.61	64.59	70.83	70.52	65.19	70.33	70.92	64.86	68.69
KD+ATS	72.31	**73.44**	67.18	72.72	73.58	66.47	72.93	73.03	66.80	**70.94**
Ens	72.77	73.61	67.76	72.77	73.61	67.76	72.77	73.61	67.76	71.38
ResKD	73.89	**76.03**	69.00	73.84	**75.14**	67.69	74.64	75.43	68.10	72.64
KD+ATS+Ens	**74.86**	75.05	**69.50**	**74.60**	75.04	**68.79**	75.34	75.47	69.82	**73.16**

distillation labels with less discriminative information among wrong class probabilities; our proposed ATS could enhance the discrimination among wrong classes and benefit the distillation process.

5.2 Performances

ATS makes larger teachers teach well again. Previous studies find that more accurate teachers can't necessarily teach well [6, 31]. As shown in Fig. 9, although we tune temperatures in $\{1.0, 2.0, 4.0, 8.0, 12.0, 16.0\}$, larger teachers still teach worse under traditional temperature scaling (the solid curves). However, using ATS (the dashed curves) could make larger teachers teach well or better again. The details are in Appendix C.4.

ATS surpasses previous methods with advanced techniques. We compare with SOTA methods and list the results on CIFAR-100, TinyImageNet, CUB, and Dogs in Tab. 1 and Tab. 2. Details of compared methods are in Appendix C.3. The last column of these tables shows the average performance of corresponding rows. The larger teacher could slightly improve the students' performances via traditional KD, i.e., $68.24\% \rightarrow 69.21\%$ and $57.94 \rightarrow 58.89\%$. However, using a smaller teacher (the row of "ST-KD") could obtain about 2% improvement on average, i.e., $68.24\% \rightarrow 70.32\%$ and $57.94\% \rightarrow 59.77\%$. This again verifies that larger teachers really teach worse on various datasets. Taking advantage of the *early-stopped teacher* (ESKD), the *teacher assistant* (TAKD), and the *student customized teacher* (SCKD) only improves the larger teacher slightly, e.g., $69.21\% \rightarrow 69.86\%$ and $58.89\% \rightarrow 59.04\%$. These results do not even surpass the small teacher. ResKD improves the students' performances a lot via introducing the *residual student* and taking the two students' ensemble, which surpasses the ensemble performances of two separately trained students under different initializations (the "Ens" row). For a fair comparison, we also test the performances of

Table 2: Comparisons with SOTA methods on TinyImageNet, CUB, and Stanford Dogs. WRN50-2 and RNX101-32-8d are teachers. AlexNet, SFV2, and MV2 are students.

	TinyImageNet			CUB			Stanford Dogs			Avg
Teacher	WRN50-2 (66.28)			RNX101-32-8d (79.50)			RNX101-32-8d (73.98)			
Student	ANet	SFV2	MV2	ANet	SFV2	MV2	ANet	SFV2	MV2	
NoKD	34.62	45.79	52.03	55.66	71.24	74.49	50.20	68.72	68.67	57.94
ST-KD	36.16	49.59	52.93	56.39	72.15	76.80	51.95	69.92	72.06	59.77
KD	35.83	48.48	52.33	55.10	71.89	76.45	50.22	68.48	71.25	58.89
ESKD	34.97	48.34	52.15	55.64	72.15	76.87	50.39	69.02	71.56	59.01
TAKD	36.20	48.71	52.44	54.82	71.53	76.25	50.36	68.94	70.61	58.87
SCKD	36.16	48.76	51.83	56.78	71.99	75.13	51.78	68.80	70.13	59.04
KD+ATS	**37.42**	**50.03**	**54.11**	**58.32**	**73.15**	**77.83**	**52.96**	**70.92**	**73.16**	**60.88**
Ens	39.37	50.69	56.40	59.84	74.43	77.47	54.04	71.65	72.53	61.82
ResKD	38.66	51.93	57.32	**62.60**	75.29	76.27	54.68	70.73	72.85	62.26
KD+ATS+Ens	**40.42**	**52.14**	**58.47**	62.00	**76.26**	**78.97**	**55.69**	**73.22**	**74.67**	**63.54**

Figure 10: Ablation studies on asymmetric temperatures on CIFAR-100 and TinyImageNet (τ_1, τ_2 in Eq. 5).

Figure 11: Ablation studies on the weighting of KD loss and CE loss on CIFAR-100 (λ in Eq. 1).

our methods via repeating the "KD+ATS" two times and making predictions via the ensemble. The results are almost 1% higher than ResKD. Results on CIFAR-10 and speech data are in Appendix D.

Ablation Studies One might argue that the validity of ATS is due to the tuning from a larger hyper-parameter space. We vary τ_1 from 1.0 to 6.0, τ_2 from 1.0 to 5.0, and record the performances in Fig. 10. Obviously, setting $\tau_1 > \tau_2$ could be better, and especially, we recommend the setting of $\tau_2 \in [\tau_1 - 2, \tau_1 - 1]$. Although we introduce one more hyper-parameter, ATS is simple to implement and surpasses SOTA methods that take advanced techniques. We achieve the goal of only utilizing simple operations to make larger teachers teach well again. Then, we study the trade off of the KD loss and CE loss under different λ. The results of "WRN28-8 → MV2" on CIFAR-100 (Fig. 11) verifies that ATS could improve the performances under various λ. We also compare ATS with other types of KD under various scenes, and the results are in Appendix D.3.

6 Conclusion

We study the miraculous phenomenon in KD that a more accurate model doesn't necessarily teach better. The proposed KD decomposition attributes the success of a better teacher to three factors, including *correct guidance*, *smooth regularization*, and *class discriminability*. Through theoretical analysis, over-confident teachers could not release their potential abilities of the *class discriminability* under traditional temperature scaling. As a simple yet effective solution, we propose *Asymmetric Temperature Scaling (ATS)* to enhance the *derived variance* of larger teachers, making their distillation labels more discriminative when teaching students. Extensive experimental results verify the superiorities of our proposed methods.

7 Broader Impact

We focus on the variance of wrong class probabilities to analyze why larger teachers cannot teach well and hope that our research could bring a new perspective to the KD field. Our work has no potential negative societal impacts.

References

[1] Sungsoo Ahn, Shell Xu Hu, Andreas C. Damianou, Neil D. Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 9163–9171, 2019.

[2] Rohan Anil, Gabriel Pereyra, Alexandre Passos, Róbert Ormándi, George E. Dahl, and Geoffrey E. Hinton. Large scale distributed neural network training through online distillation. In *The 6th International Conference on Learning Representations*, 2018.

[3] Cristian Bucila, Rich Caruana, and Alexandru Niculescu-Mizil. Model compression. In *Proceedings of the Twelfth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 535–541, 2006.

[4] Pengguang Chen, Shu Liu, Hengshuang Zhao, and Jiaya Jia. Distilling knowledge via knowledge review. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 5008–5017, 2021.

[5] Xu Cheng, Zhefan Rao, Yilan Chen, and Quanshi Zhang. Explaining knowledge distillation by quantifying the knowledge. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12922–12932, 2020.

[6] Jang Hyun Cho and Bharath Hariharan. On the efficacy of knowledge distillation. In *IEEE/CVF International Conference on Computer Vision*, pages 4793–4801, 2019.

[7] Tri Dao, Govinda M. Kamath, Vasilis Syrgkanis, and Lester Mackey. Knowledge distillation as semiparametric inference. In *The 9th International Conference on Learning Representations*, 2021.

[8] Ronald Fagin, Ravi Kumar, and D. Sivakumar. Comparing top k lists. *SIAM Journal on Discrete Mathematics*, 17(1):134–160, 2003.

[9] Tommaso Furlanello, Zachary Chase Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born-again neural networks. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pages 1602–1611, 2018.

[10] Mengya Gao, Yujun Wang, and Liang Wan. Residual error based knowledge distillation. *Neurocomputing*, 433:154–161, 2021.

[11] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[12] Byeongho Heo, Minsik Lee, Sangdoo Yun, and Jin Young Choi. Knowledge transfer via distillation of activation boundaries formed by hidden neurons. In *The Thirty-Third AAAI Conference on Artificial Intelligence*, pages 3779–3787, 2019.

[13] Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. *CoRR*, abs/1503.02531, 2015.

[14] Andrew G. Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *CoRR*, abs/1704.04861, 2017.

[15] Daniel Hsu, Ziwei Ji, Matus Telgarsky, and Lan Wang. Generalization bounds via distillation. In *The 9th International Conference on Learning Representations*, 2021.

[16] Zhen Huang, Xu Shen, Jun Xing, Tongliang Liu, Xinmei Tian, Houqiang Li, Bing Deng, Jianqiang Huang, and Xian-Sheng Hua. Revisiting knowledge distillation: An inheritance and exploration framework. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 3579–3588, 2021.

[17] Zehao Huang and Naiyan Wang. Like what you like: Knowledge distill via neuron selectivity transfer. *CoRR*, abs/1707.01219, 2017.

[18] Guangda Ji and Zhanxing Zhu. Knowledge distillation in wide neural networks: Risk bound, data efficiency and imperfect teacher. In *Advances in Neural Information Processing Systems 33*, 2020.

[19] Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Fei fei Li. Novel dataset for fine-grained image categorization. In *First Workshop on Fine-Grained Visual Categorization, CVPR (2011)*.

[20] Kyungyul Kim, ByeongMoon Ji, Doyoung Yoon, and Sangheum Hwang. Self-knowledge distillation with progressive refinement of targets. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 6567–6576, 2021.

[21] Alex Krizhevsky. Learning multiple layers of features from tiny images. 2012.

[22] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems 25*, pages 1106–1114, 2012.

[23] Xuhong Li, Yves Grandvalet, and Franck Davoine. Explicit inductive bias for transfer learning with convolutional networks. In *Proceedings of the 35th International Conference on Machine Learning*, pages 2830–2839, 2018.

[24] Xuewei Li, Songyuan Li, Bourahla Omar, Fei Wu, and Xi Li. Reskd: Residual-guided knowledge distillation. *IEEE Transactions on Image Processing*, 30:4735–4746, 2021.

[25] Ruofan Liang, Tianlin Li, Longfei Li, Jing Wang, and Quanshi Zhang. Knowledge consistency between neural networks and beyond. In *The 8th International Conference on Learning Representations*, 2020.

[26] Junjie Liu, Dongchao Wen, Hongxing Gao, Wei Tao, Tse-Wei Chen, Kinya Osa, and Masami Kato. Knowledge representing: Efficient, sparse representation of prior knowledge for knowledge distillation. In *IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 638–646, 2019.

[27] Yufan Liu, Jiajiong Cao, Bing Li, Chunfeng Yuan, Weiming Hu, Yangxi Li, and Yunqiang Duan. Knowledge distillation via instance relationship graph. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 7096–7104, 2019.

[28] David Lopez-Paz, Léon Bottou, Bernhard Schölkopf, and Vladimir Vapnik. Unifying distillation and privileged information. In *The 4th International Conference on Learning Representations*, 2016.

[29] Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet V2: practical guidelines for efficient CNN architecture design. In *Computer Vision - ECCV 2018 - 15th European Conference*, pages 122–138, 2018.

[30] Aditya Krishna Menon, Ankit Singh Rawat, Sashank J. Reddi, Seungyeon Kim, and Sanjiv Kumar. A statistical perspective on distillation. In *Proceedings of the 38th International Conference on Machine Learning*, pages 7632–7642, 2021.

[31] Seyed-Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. Improved knowledge distillation via teacher assistant. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence*, pages 5191–5198, 2020.

[32] Rafael Müller, Simon Kornblith, and Geoffrey E. Hinton. When does label smoothing help? In *Advances in Neural Information Processing Systems 32*, pages 4696–4705, 2019.

[33] Nikolaos Passalis and Anastasios Tefas. Learning deep representations with probabilistic knowledge transfer. In *Computer Vision - ECCV 2018 - 15th European Conference*, volume 11215, pages 283–299, 2018.

[34] Baoyun Peng, Xiao Jin, Dongsheng Li, Shunfeng Zhou, Yichao Wu, Jiaheng Liu, Zhaoning Zhang, and Yu Liu. Correlation congruence for knowledge distillation. In *2019 IEEE/CVF International Conference on Computer Vision*, pages 5006–5015, 2019.

[35] Mary Phuong and Christoph Lampert. Towards understanding knowledge distillation. In *Proceedings of the 36th International Conference on Machine Learning*, pages 5142–5151, 2019.

[36] Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. In *The 3rd International Conference on Learning Representations*, 2015.

[37] Mark Sandler, Andrew G. Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *2018 IEEE Conference on Computer Vision and Pattern Recognition*, pages 4510–4520, 2018.

[38] Zhiqiang Shen, Zechun Liu, Dejia Xu, Zitian Chen, Kwang-Ting Cheng, and Marios Savvides. Is label smoothing truly incompatible with knowledge distillation: An empirical study. In *The 9th International Conference on Learning Representations*, 2021.

[39] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *3rd International Conference on Learning Representations*, 2015.

[40] Jiaxi Tang, Rakesh Shivanna, Zhe Zhao, Dong Lin, Anima Singh, Ed H. Chi, and Sagar Jain. Understanding and improving knowledge distillation. *CoRR*, abs/2002.03532, 2020.

[41] Raphael Tang and Jimmy Lin. Deep residual learning for small-footprint keyword spotting. In *IEEE International Conference on Acoustics, Speech and Signal Processing*, pages 5484–5488, 2018.

[42] Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In *The 5th International Conference on Learning Representations*, 2017.

[43] Amirhossein Tavanaei. Embedded encoder-decoder in convolutional networks towards explainable AI. *CoRR*, abs/2007.06712, 2020.

[44] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. In *The 8th International Conference on Learning Representations*, 2020.

[45] Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *2019 IEEE/CVF International Conference on Computer Vision*, pages 1365–1374, 2019.

[46] Gregor Urban, Krzysztof J. Geras, Samira Ebrahimi Kahou, Özlem Aslan, Shengjie Wang, Abdelrahman Mohamed, Matthai Philipose, Matthew Richardson, and Rich Caruana. Do deep convolutional nets really need to be deep and convolutional? In *The 5th International Conference on Learning Representations*, 2017.

[47] C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical report, 2011.

[48] Pete Warden. Speech commands: A dataset for limited-vocabulary speech recognition. *CoRR*, abs/1804.03209, 2018.

[49] Saining Xie, Ross B. Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 5987–5995, 2017.

[50] Han-Jia Ye, Su Lu, and De-Chuan Zhan. Distilling cross-task knowledge via relationship matching. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12393–12402, 2020.

[51] Yi Wang Yichen Zhu. Student customized knowledge distillation: Bridging the gap between student and teacher. In *IEEE/CVF International Conference on Computer Vision*, 2021.

[52] Junho Yim, Donggyu Joo, Ji-Hoon Bae, and Junmo Kim. A gift from knowledge distillation: Fast optimization, network minimization and transfer learning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition*, pages 7130–7138, 2017.

[53] Kaichao You, Yong Liu, Jianmin Wang, and Mingsheng Long. Logme: Practical assessment of pre-trained models for transfer learning. In *Proceedings of the 38th International Conference on Machine Learning*, pages 12133–12143, 2021.

[54] Lu Yu, Vacit Oguz Yazici, Xialei Liu, Joost van de Weijer, Yongmei Cheng, and Arnau Ramisa. Learning metrics from teachers: Compact networks for image embedding. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 2907–2916, 2019.

[55] Li Yuan, Francis E. H. Tay, Guilin Li, Tao Wang, and Jiashi Feng. Revisiting knowledge distillation via label smoothing regularization. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3902–3910, 2020.

[56] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *Proceedings of the British Machine Vision Conference*, 2016.

[57] Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. In *The 5th International Conference on Learning Representations*, 2017.

[58] Linfeng Zhang, Jiebo Song, Anni Gao, Jingwei Chen, Chenglong Bao, and Kaisheng Ma. Be your own teacher: Improve the performance of convolutional neural networks via self distillation. In *2019 IEEE/CVF International Conference on Computer Vision*, pages 3712–3721, 2019.

[59] Xiangyu Zhang, Xinyu Zhou, Mengxiao Lin, and Jian Sun. Shufflenet: An extremely efficient convolutional neural network for mobile devices. In *2018 IEEE Conference on Computer Vision and Pattern Recognition*, pages 6848–6856, 2018.

[60] Yundong Zhang, Naveen Suda, Liangzhen Lai, and Vikas Chandra. Hello edge: Keyword spotting on microcontrollers. *CoRR*, abs/1711.07128, 2017.

[61] Ying Zhang, Tao Xiang, Timothy M. Hospedales, and Huchuan Lu. Deep mutual learning. In *2018 IEEE Conference on Computer Vision and Pattern Recognition*, pages 4320–4328, 2018.

[62] Zhilu Zhang and Mert R. Sabuncu. Self-distillation as instance-specific label smoothing. In *Advances in Neural Information Processing Systems 33*, 2020.

[63] Helong Zhou, Liangchen Song, Jiajie Chen, Ye Zhou, Guoli Wang, Junsong Yuan, and Qian Zhang. Rethinking soft labels for knowledge distillation: A bias-variance tradeoff perspective. In *The 9th International Conference on Learning Representations*, 2021.