# StrucText-Eval: Evaluating Large Language Model's Reasoning Ability in Structure-Rich Text

## Abstract

The effective utilization of structured data, integral to corporate data strategies, has been challenged by the rise of large language models (LLMs) capable of processing unstructured information. This shift prompts the question: can LLMs interpret structured data directly in its unstructured form? We propose an automatic evaluation data generation method for assessing LLMs' reasoning capabilities on structure-rich text to explore this. Our approach supports 8 structured languages and 29 tasks, generating data with adjustable complexity through controllable nesting and structural width. We introduce StrucText-Eval, a benchmark containing 5,800 pre-generated and annotated samples designed to evaluate how well LLMs understand and reason through structured text. StrucText-Eval is divided into two suites: a regular Test suite (3,712 samples) and a Test-Hard suite (2,088 samples), the latter emphasizing the gap between human and model performance on more complex tasks. Experimental results show that while open-source LLMs achieve a maximum accuracy of 74.9% on the standard dataset, their performance drops significantly to 45.8% on the harder dataset. In contrast, human participants reach an accuracy of 92.6% on StrucText-Eval-Hard, highlighting LLMs' current limitations in handling intricate structural information.

## 1 Introduction

Structured data, often represented by various structured languages such as JSON (Pezoa et al., 2016), YAML (Evans, 2001), ORG (org, 2023), or Markdown (Gruber, 2012), Latex (Lamport, 1985) etc., has consistently been central to corporate data strategies due to its ability to capture, store, and analyze essential information systematically. The inherent benefits of structured data lie in its standardized format and high degree of organization, which facilitates efficient data querying and machine processing, clearly surpassing the inherent chaos of unstructured data. However, with the advancement of large language models (LLMs) (Achiam et al., 2023; Touvron et al., 2023a,b; Sun et al., 2021), there has been a significant shift towards the effective utilization of unstructured data, attributed to the LLMs' capacity to comprehend and generate complex and nuanced semantics within such data (Brown et al., 2020). Considering that structured data can be directly presented in an unstructured format, it makes us wonder: ***whether it is possible to rely on LLMs to interpret structured data through unstructured format directly***.

Current LLM researchers have addressed their comprehension of structure-rich text of limited categories: Graphs (Fatemi et al., 2023; Perozzi et al., 2024; Guo et al., 2023; Tang et al., 2023a; Chen et al., 2023), Tables (Sui et al., 2024; Campbell-Kelly, 2003; Pasupat and Liang, 2015) and JSON (Chen et al., 2024; Suzgun et al., 2022). However, these categories do not encompass all potential use cases of structure-rich text. For instance, scenarios requiring a direct understanding of articles in Latex or Markdown formats, data in YAML or ORG formats, or various custom-structured languages need to be adequately covered. Moreover, existing benchmarks often rely on manually annotated data for evaluation, which limits the development of robust evaluation frameworks and potentially facilitates model cheating (Zhou et al., 2023).

We propose a method for automatically generating evaluation data to assess models' capabilities in structure-rich text reasoning. This method is applied to 8 structured languages, as shown in Fig. 1, across 29 specific tasks, enabling data generation with controllable difficulty by adjusting the depth of structured nesting and the number of width and columns in the sample. Based on this method, we further introduce the ***Struc**ture-Rich **Text Eval**uation Benchmark (**StrucText-Eval**), a comprehensive benchmark with 5,800 pre-

generated and annotated samples designed to evaluate the proficiency of LLMs in deciphering embedded structures within input text. StrucText-Eval aims to evaluate whether LLMs understand raw structural tags, execute logical inferences based on the decoded semantics of these symbols, and organize their responses according to instruction requirements. StrucText-Eval is divided into Test suite and Test-Hard suite, each consisting of 3,712 and 2,088 samples. Considering that humans excel at understanding structured expressions, The Test-Hard suite features significantly longer questions, with an average length of 16,535 characters, and longest category contains 102,531 characters, which underscores the considerable gap between LLMs and human capabilities in comprehending and processing structured data. The experimental results indicate that StrucText-Eval presents significant challenges in evaluating current LLMs' structured text processing capabilities. While various open-sourced models achieve a maximum accuracy of 74.9% under different prompting methods, their performance declines markedly to 45.8% when tested on the more complex StrucText-Eval-Hard dataset. In contrast, human participants attain an accuracy of 92.6% on StrucText-Eval-Hard, highlighting the limitations of existing LLMs in comprehending and reasoning through complex structural information.

## 2 Related Work

### 2.1 Structural Text Understanding Enhancements

Recent efforts to enhance LLMs have focused on integrating external structures such as graphs, tool flows, and cross-domain representations to improve reasoning capabilities across various tasks. For instance, ControlLLM utilizes tool graphs to decompose complex multimodal tasks, resulting in enhanced performance on image and audio processing tasks by leveraging the topological dependencies of tools (Liu et al., 2023). Graph-based models like GraphGPT and BooG have shown promising results, with the former improving generalization across node classification and molecular tasks via graph instruction tuning (Zhao et al., 2023; Tang et al., 2024). At the same time, the latter employs virtual supernodes to unify graph structures across domains, fostering cross-domain task transferability (Cheng et al., 2024). Additionally, methods like RC2R demonstrate the effective

combination of knowledge graphs and LLMs for domain-specific causal reasoning, particularly in financial risk propagation tasks (Yu et al., 2024). These advancements highlight the benefits of embedding structural elements, from graph architectures to domain-specific knowledge graphs, within LLM frameworks to improve task-specific inference and reasoning.

### 2.2 Structural Text Understanding Evaluation

Evaluating LLMs' understanding of structured data has become increasingly critical, though benchmarks remain limited. GraphQA and Struc-Bench are key datasets that assess LLMs' reasoning over graph-structured data and tabular text, respectively, illustrating the models' varying capabilities based on input encoding (Fatemi et al., 2023; Tang et al., 2023b). More specialized benchmarks, such as TEMPTABQA, evaluate temporal reasoning in tabular data, while TableLLM tests LLMs' proficiency in handling complex document-based table manipulation tasks (Gupta et al., 2023; Zhang et al., 2024). Other works, such as the evaluation of knowledge graph-based reasoning in complex time-series QA systems (JMFRN) (Huang et al., 2024), and privacy-oriented graph tasks in GHRatio (Yuan et al., 2024), further explore how LLMs handle intricate, structure-rich information, shedding light on their performance across different structured data formats.

Our work diverges from prior research by focusing exclusively on structure-based inference, deliberately removing semantic content to challenge LLMs to reason purely from structural patterns. Unlike previous approaches that use structural data as supplementary input for classification or semantic tasks (Pasupat and Liang, 2015; Sui et al., 2024), we design semantically agnostic tasks requiring models to infer meaning solely from symbolic structures. Moreover, while earlier benchmarks emphasize graph reasoning or tabular information retrieval, our work extends to a broader spectrum of structure-rich text types, encompassing various input formats and more complex dependency-based inference tasks.

## 3 StrucText-Eval Construction

### 3.1 Structure-Rich Texts Taxonomy

To explore structure-rich texts comprehensively, we propose a dataset for eight structured data

Figure 1: Taxonomy of Structure-Rich Texts covered in StrucText-Eval.

| | #Sample | #Reference | #GroundTruth | Depth | Width |
|---|---|---|---|---|---|
| *StrucText-Eval-Test* | | | | | |
| | **3,712** | **804** | **47** | - | - |
| | 1,856 | 582 | 19 | 1 | 1 |
| | 1,856 | 1,026 | 74 | 2 | 1 |
| *StrucText-Eval-Test-Hard* | | | | | |
| | **2,088** | **16,535** | **1,169** | - | - |
| | 232 | 573 | 22 | 1 | 1 |
| | 232 | 614 | 26 | 1 | 2 |
| | 232 | 663 | 25 | 1 | 3 |
| | 232 | 992 | 80 | 2 | 1 |
| | 232 | 2,108 | 136 | 2 | 2 |
| | 232 | 3,866 | 283 | 2 | 3 |
| | 232 | 5,036 | 312 | 3 | 1 |
| | 232 | 32,428 | 2,229 | 3 | 2 |
| | 232 | 102,531 | 7,411 | 3 | 3 |

Table 1: Statistics for StrucText-Eval test suite.

types, each categorized within a taxonomy depicted in Fig. 1. This taxonomy encompasses both structured and semi-structured data formats. The structured data types include Tree ((Cormen et al., 2022)), Tabular ((Campbell-Kelly, 2003)), and Object Notation such as JSON ((Pezoa et al., 2016)), YAML ((Evans, 2001)), and XML ((Bray et al., 1998)). The semi-structured data types include Markup Languages like Markdown ((Gruber, 2012)), LaTeX ((Lamport, 1985)), and Org ((org, 2023)). Within StrucText-Eval, Tabular is stored in CSV format, whereas Tree is denoted by a custom format that nodes are represented as the string "xxx", connected with "->" and separated by "\n". For examples encompassing all languages and tasks, please refer to Sec. D in the Appendix.

### 3.2 Dataset Generation

An example of JSON's PathCompose is shown in Fig. 2 to illustrate the dataset generation process. The generation process mainly entails constructing an abstract structure tree, manually drafting question templates, and developing corresponding answer discovery algorithms. The first step of the

Figure 2: The illustration of the dataset generation process, the Json PathCompose task, is an example.

generation process is to define the complexity of the problem, characterized by depth, width, and column (Col), as well as its type, including task and language. During the construction of the abstract tree, depth represents the depth of the tree, width indicates the number of children for each non-leaf node, and Col specifies the number of fields associated with each node. When constructing the question template, predefined templates are retrieved based on the specified task. Finally, during sample generation, the selected task is used to identify the corresponding ground truth according to specific rules, and both the abstract tree and the ground truth are translated into the selected language.

Eight task categories have been delineated for

eight languages, as detailed in Fig. 3b. 29 rules and question templates have been formulated for these tasks, with the specific rule templates detailed in Sec. E in the Appendix. Each sample in the dataset comprises four main fields: "Reference", "Question", "Requirement" and "Answer". We give examples for each language and task in Sec. D in the Appendix.

### 3.3 Statistic Information

StrucText-Eval has assembled two datasets. StrucText-Eval-Test comprises 3,712 samples, and StrucText-Eval-Test-Hard comprises 2,088 samples, each of the 29 specific tasks for eight languages as depicted in Fig. 3a. Detailed statistics regarding the number of samples, lengths, and complexity levels across all tasks, languages, and difficulties are detailed in Tab. 1.

## 4 Experiment Setup

To evaluate LLMs' current capability of processing structure-rich text and executing dependent inference, we conducted a series of experiments using StrucText-Eval in various settings. Our study utilizes both prompt-based and finetuning methods to analyze the performance variations.

### 4.1 Models

We tested six Open-Source LLMs in both StrucText-Eval Test and Test-Hard Suite, and we use the short name (in the bracket) of these LLMs in the experiments: **Qwen/Qwen2-7B-Instruct** (Qwen-2-7B), **Qwen/Qwen2-72B-Instruct** (Qwen-2-72B), **meta-llama/Meta-Llama-3.1-8B-Instruct** (Llama-3.1-8B), **meta-llama/Meta-Llama-3.1-72B-Instruct** (Llama-3.1-70B), **meta-llama/Meta-Llama-3.1-405B-Instruct** (Llama-3.1-405B), **mistralai/Mistral-7B-Instruct-v0.2** (Mistral-0.2-7B)

Considering the huge expense of using an API-based model, we only tested six Close-Source LLMs in StrucText-Eval-Hard: **gpt-4o-2024-08-06** (gpt-4o), **gpt-4o-mini-2024-07-18** (gpt-4o-mini), **gemini-1.5-pro**(gemini-1.5-pro), **gemini-1.5-flash**(gemini-1.5-flash), **GLM-4-Plus** (glm-4-plus), **GLM-4-Flash** (glm-4-flash).

### 4.2 Prompt-based Method

We also evaluated the impact of different prompt designs on the performance of LLMs by utilizing six distinct prompt configurations in the main experiments. Detailed implementation of these prompts can be found in Sec. C in the Appendix. The six primary prompt settings are as follows:

`Naive`: This configuration involves a straightforward input of "Context", "Question", and "Options" into the LLMs to generate responses. `Self-Chain-of-Thought (Self-CoT)` (Kojima et al., 2022): This approach incorporates a step-by-step reasoning prompt to guide the model through logical reasoning. `Plan-and-Solve CoT (PS-CoT)` (Wang et al., 2023): This method emphasizes problem decomposition before solving, encouraging the model to first break down the problem before generating a solution. `With Hint (w/ hint)`: In this setting, manually curated hints are provided to the model to observe its performance when additional information is injected. Since this approach introduces supplementary data, it is delineated by a dashed line from other methods in Table 2. `Few-Shot Demonstration`: involves appending few training data directly to the prompt. The `Simple Few-Shot Demonstration` uses only the shortest examples from the training set as few-shot demonstrations.

### 4.3 Evaluation Method

We use the RougeL metric (Lin, 2004) to assess the degree of character-level similarity between model outputs in the main content of this paper. Sometimes, the task requires the LLM to generate the entire reasoning path leading to the answer, which results in high RougeL scores. So, we assign a score of 0 if the RougeL score falls below 0.75.

Additionally, we present the results of other evaluation metrics, including LLM-as-Judge-Score (Zheng et al., 2023), BLEU (Papineni et al., 2002), and Exact Match, in Tab. 4 in the Appendix. Furthermore, we conduct a consistency analysis across these metrics compared to human judgments, as shown in Fig. 6.

## 5 Analysis

### 5.1 Overall Performance in StrucText-Eval

The overall performance in StrucText-Eval is presented in Table 2, revealing significant variations in the performance of different models across various languages and tasks. For instance, the Qwen2-72B-Instruct model demonstrates optimal performance on JSON-formatted tasks with an 85.8% accuracy under the "Naive" prompt. It also achieves notable results in YAML and CSV tasks, with accuracies

(a) Benchmark Decomposition

| Task Name | Abbr. | Task Description |
|---|---|---|
| Syntax | SY | Focuses on detecting structural errors in data formats such as JSON, XML, and YAML. |
| PathWalk | PW | Focuses on extracting specific sections or subsections from structured documents such as org, LaTeX, or markdown files. |
| TextRetrieval | TR | Assesses the ability to extract specific information from various document formats, including text content and image filenames. |
| Statistic | ST | Concentrates on statistical queries to calculate the number of employees meeting specific salary conditions. |
| Join | JO | Assesses the ability to filter data sets that meet specific criteria by combining multiple tables in a database through SQL queries. |
| Tree.Height | TH | Evaluates calculating the height of the longest path from the root node to any leaf node in a tree structure. |
| Node.Depth | ND | Assesses the depth of any node in a tree structure relative to the root node. |
| PathCompose | PC | Evaluates reasoning of paths and multi-level data indexing within hierarchical or tree-like structures. |

(b) Descriptions of tasks for evaluating structured data understanding in large language models

Figure 3: The tasks within StrucText-Eval and their description.

Figure 4: The model's performance on StrucText-Eval-Test under different Few-Shot Demonstration settings.

of 82.7% and 86.4%, respectively. In contrast, the Meta-Llama-3.1-8B-Instruct-Turbo model performs poorly under the same settings, achieving only 64.6% accuracy on LaTeX tasks. Manually injected hints (w/ hint) generally improve model performance, particularly in tasks requiring deep reasoning, such as those involving YAML and JSON. For example, the Meta-Llama-3.1-70B-Instruct-Turbo models accuracy improves from 75.4% under the "Naive" prompt to 84.9% with the "w/ Hint" strategy. However, with "Self-CoT" and "PS-CoT" prompts, specific models like Qwen2-7B-Instruct

exhibit lower accuracy across multiple tasks, especially when handling complex structures such as XML and Tree data, performing significantly worse compared to other prompting methods.

These performance disparities can be primarily attributed to training sample biases and the influence of different prompting strategies. JSON, being a widely used format in internet data, is frequently encountered by many large models during training, leading to a pronounced advantage in handling JSON-formatted tasksa clear manifestation of training sample bias. Moreover, the choice of prompting strategy directly affects a model's inference capabilities. The "w/ Hint" method, which introduces human reasoning rules, compensates for the model's limitations in reasoning through complex structures. Conversely, while the "Self-CoT" and "PS-CoT" approaches encourage step-by-step reasoning, they often result in logical inconsistencies and reasoning errors in complex tasks due to the requirement for autonomous generation of reasoning paths.

## 5.2 Overall Performance on StrucText-Eval Hard

Table 3 presents the performance of various models on the StrucText-Eval Hard dataset, characterized by more complex tasks with longer sequences and deeper structures. This complexity results in a significant performance decline across all models. For instance, the accuracy of the Qwen2-72B-Instruct model decreases from 78.4% to 65.0%, while the Meta-Llama-3.1-70B-Instruct-Turbo model's accuracy drops sharply from 75.4% to 43.2%. Unlike the standard dataset, the Hard dataset demands more advanced reasoning skills, and even with

| Model | Prompt | Languages | | | | | | | | Tasks | | | | | | | | all |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | JSON | LaTeX | Md. | ORG | CSV | Tree | XML | YAML | PC | PW | SY | TR | JO | ST | ND | TH | |
| Qwen2-7B | Base | 70.4 | 68.8 | 68.0 | 54.5 | 83.5 | 68.9 | 57.6 | 68.5 | 48.5 | 74.2 | 49.2 | 72.4 | 79.5 | 78.4 | 47.7 | 93.2 | 30.0 |
| | Self-CoT | 12.8 | 1.5 | 1.5 | 9.1 | 29.0 | 4.5 | 3.6 | 3.5 | 4.5 | 6.4 | 6.1 | 8.1 | 27.3 | 26.1 | 2.3 | 6.8 | 17.2 |
| | PS-CoT | 31.7 | 31.7 | 19.4 | 20.1 | 67.0 | 36.4 | 25.8 | 24.9 | 9.8 | 19.8 | 32.6 | 34.1 | 63.6 | 60.2 | 25.0 | 72.7 | 29.1 |
| | w/ Hint | 70.8 | 66.1 | 66.5 | 58.1 | 85.2 | 56.8 | 55.2 | 70.2 | 43.9 | 72.3 | 43.2 | 75.3 | 86.4 | 77.3 | 45.5 | 65.9 | 44.0 |
| Qwen2-72B | Base | 85.8 | _73.7_ | 75.1 | 67.1 | 92.6 | 86.4 | 71.2 | 82.7 | 80.3 | 81.5 | 62.9 | 80.8 | 90.9 | 90.9 | 77.3 | _95.5_ | 42.6 |
| | Self-CoT | 85.4 | 69.9 | 70.8 | 65.2 | 95.5 | **90.2** | 79.5 | 89.7 | 78.8 | 77.1 | 81.1 | 81.7 | 90.9 | _95.5_ | 84.1 | _95.5_ | 51.0 |
| | PS-CoT | 89.5 | 70.1 | 68.9 | 61.7 | 92.0 | 84.8 | 81.1 | 93.4 | 76.5 | 77.6 | 87.9 | 80.8 | 81.8 | 93.2 | _86.4_ | 97.7 | 65.3 |
| | w/ Hint | 90.0 | 72.5 | **79.1** | _68.6_ | 94.9 | 81.1 | 72.7 | 90.8 | 81.1 | _84.0_ | 77.3 | 82.4 | 95.5 | 92.0 | 72.7 | 86.4 | 49.4 |
| Llama-3.1-8B | Base | 43.9 | 64.6 | 49.3 | 48.3 | 42.6 | 50.0 | 26.5 | 46.9 | 30.3 | 49.4 | 1.5 | 61.0 | 11.4 | 45.5 | 22.7 | 79.5 | 21.3 |
| | Self-CoT | 52.2 | 40.6 | 49.2 | 39.0 | 66.5 | 43.2 | 36.6 | 55.2 | 40.9 | 40.2 | 39.7 | 53.0 | 77.3 | 65.9 | 52.3 | 36.4 | 48.5 |
| | PS-CoT | 45.8 | 18.7 | 34.0 | 32.8 | 64.0 | 63.1 | 44.6 | 41.3 | 48.8 | 50.5 | 44.7 | 32.8 | 69.8 | 56.8 | 64.3 | 62.8 | 55.9 |
| | w/ Hint | 44.9 | 62.2 | 55.9 | 48.1 | 29.0 | 54.5 | 30.5 | 51.4 | 31.8 | 45.4 | 9.1 | 63.4 | 2.3 | 22.7 | 38.6 | 90.9 | 26.9 |
| Llama-3.1-70B | Base | _93.8_ | 70.9 | 69.8 | 62.8 | 72.7 | 51.5 | 78.7 | 88.8 | 81.8 | 75.4 | 82.6 | 81.0 | 72.7 | 59.1 | 47.7 | 43.2 | 50.8 |
| | Self-CoT | 93.6 | 71.4 | 69.7 | 54.8 | 96.0 | 84.1 | 87.1 | _95.9_ | _88.6_ | 67.9 | 86.4 | **85.7** | _97.7_ | 93.2 | 77.3 | **97.7** | **76.7** |
| | PS-CoT | **94.5** | 68.7 | 72.7 | 61.7 | 93.7 | 83.2 | _93.9_ | **98.5** | **90.8** | 77.0 | **93.9** | 84.2 | 93.2 | 90.9 | 81.8 | 90.9 | 72.9 |
| | w/ Hint | 93.6 | **73.9** | _77.4_ | **71.6** | 72.7 | 74.2 | 80.4 | 93.6 | _88.6_ | **84.9** | 84.1 | 83.5 | 70.5 | 60.2 | 65.9 | 75.0 | 58.4 |
| Llama-3.1-405B | Base | 82.0 | 62.9 | 70.0 | 60.9 | _96.6_ | 65.9 | 61.5 | 78.1 | 74.2 | 69.4 | 32.6 | 82.4 | _97.7_ | 94.3 | 45.5 | 79.5 | 38.3 |
| | Self-CoT | 87.7 | 62.2 | 74.2 | 62.2 | 95.5 | 75.8 | 78.5 | 90.8 | 87.9 | 73.2 | 63.6 | 83.4 | **100.0** | 90.9 | 59.1 | 88.6 | 67.1 |
| | PS-CoT | 84.5 | 67.4 | 76.0 | 66.7 | 92.0 | _86.7_ | **94.7** | 94.7 | 88.3 | 79.1 | _93.2_ | 81.1 | _97.7_ | 85.2 | **90.9** | 88.6 | _74.9_ |
| | w/ Hint | 85.4 | 68.3 | 75.1 | 66.7 | **98.3** | 70.5 | 74.5 | 87.2 | 74.2 | 78.0 | 59.1 | _84.9_ | 97.7 | **97.7** | 50.0 | 84.1 | 46.5 |
| Mistral-7B | Base | 32.5 | 42.1 | 44.9 | 40.2 | 9.1 | 4.5 | 14.8 | 33.5 | 6.1 | 30.8 | 0.0 | 47.7 | 0.0 | 6.8 | 0.0 | 0.0 | 11.3 |
| | Self-CoT | 56.5 | 35.1 | 40.3 | 36.6 | 34.7 | 15.9 | 33.7 | 54.3 | 28.8 | 49.2 | 64.4 | 43.9 | 6.8 | 23.9 | 13.6 | 13.6 | 8.1 |
| | PS-CoT | 43.9 | 19.7 | 22.9 | 15.6 | 14.8 | 18.2 | 34.6 | 44.1 | 18.9 | 30.6 | 56.8 | 29.1 | 22.7 | 6.8 | 13.6 | 22.7 | 19.5 |
| | w/ Hint | 34.6 | 39.4 | 52.7 | 40.5 | 10.2 | 6.8 | 12.7 | 36.5 | 9.8 | 34.3 | 0.0 | 48.9 | 0.0 | 8.0 | 0.0 | 0.0 | 10.6 |

Table 2: RougeL score for open sourced LLMs' performance. **Bolded** text represent the best performance in the column. Underlined text represent the second best performance in the column.

Figure 5: Heatmaps illustrating the correlation of RougeL scores and standard deviations (STD) across different models and evaluation criteria. The rows represent different levels of depth, and the columns represent varying levels of width, indicating increasing task complexity. "All" refers to combined results across languages and tasks, while "GPT" shows results specific to GPT-based models. "Lang STD" and "Task STD" indicate the variability in performance across different languages and tasks, respectively.

the "w/ Hint" strategy, models achieve only limited improvements, in contrast to the substantial gains observed in more straightforward contexts. Notably, human accuracy on StrucText-Eval-Hard reaches 95.7%, significantly surpassing that of the best-performing large language models (LLMs), highlighting a considerable gap in models' capabilities for structured reasoning.

This performance gap can be primarily attributed to biases in training data and the limitations of current prompting methods. The StrucText-Eval Hard dataset, with increased question complexity and depth, requires models to possess enhanced abstraction abilities and a deeper understanding of complex structures. However, most models are trained on relatively more straightforward structured text, which makes them less effective when tackling deeply nested reasoning tasks. Additionally, prompting methods like "w/ Hint" fail to achieve human-level understanding in multi-layered scenarios. The differences in prompting methods become more pronounced with increased

| Model | Prompt | | | |
|---|---|---|---|---|
| | Base | w/ Hint | 3-Shot | Simple 3-Shot |
| GPT-4o-Turbo | **51.1** | **54.2** | **69.5** | 49.7 |
| GPT-4o-Mini | 39.3 | 47.7 | 65.6 | 39.9 |
| Gemini1.5-Pro | 11.2 | 15.7 | 53.0 | 12.5 |
| Gemini1.5-Pro-Flash | 12.9 | 12.9 | 38.3 | 11.9 |
| GLM-4-Plus | 47.3 | 50.9 | 65.8 | **51.7** |
| GLM-4-Flash | 40.9 | 47.8 | 55.2 | 41.7 |
| QWen-2-7B | 29.6 | 35.0 | 51.9 | 30.0 |
| QWen-2-72B | 42.5 | 45.3 | **61.4** | 36.2 |
| Llama-3.1-8B | 22.3 | 26.7 | 33.7 | 34.2 |
| Llama-3.1-70B | **45.8** | **56.0** | 58.4 | **50.1** |
| Llama-3.1-405B | 34.4 | 41.7 | 48.7 | 40.6 |
| Mistral-0.2-7B | 7.0 | 9.5 | 21.0 | 6.9 |
| Human | 92.6 | - | - | - |

Table 3: Performance of all LLMs and Humans on StrucText-Eval-Hard. **Bolded** text represent the best performance in the column. Underlined text represent the second best performance in the column.

Figure 6: Correlation between different evaluation metrics.

complexity; more straightforward methods, such as Self-CoT, need to be revised for guiding models through multi-step reasoning in these challenging contexts. While the "3-shot demonstration" approach significantly improves model performance, the simpler "simple 3-shot" method, despite following similar reasoning rules, fails to match the former due to its insufficient complexity.

## 5.3 Few-Shot Demonstration on Structural Text Inference

Figure 4 demonstrates that model performance improves with an increasing number of demonstrations under Few-Shot settings. In the 3-shot scenario, GPT-4 achieves an accuracy of 69.5%, significantly outperforming models like Gemini-Pro-Flash and Mistral, which remain around 21% or lower. The Qwen-2-72B-Instruct model shows steady improvement as more examples are provided, although it continues to trail behind GPT-4. Generally, performance increases from 1-shot

to 3-shot, but the gains become less pronounced at 5-shot, with some models showing overfitting. In contrast, the performance of CoT and PS approaches remains less consistent as the number of demonstrations increases.

This trend suggests that a more significant number of examples helps models to understand problem structures and reasoning processes better, thereby enhancing their inference capabilities. However, providing too many examples can lead to models overfitting to specific patterns, which diminishes their ability to generalize to new tasks. The quality and diversity of examples are critical—high-quality examples can guide practical reasoning, while poor examples may mislead the models. While few-shot learning enhances model adaptability, those with limited pretraining data or lower parameter counts may struggle to capitalize on this approach entirely. For CoT and PS methods, the reasoning process requires additional steps, which means that simply increasing the number of few-shot demonstrations does not consistently yield performance improvements.

## 5.4 Model Performance Across Different Difficulty Levels, Languages, and Tasks

Figure 5 illustrates the performance variations of models across different languages and tasks. The two figures on the left reveal that, while numerical differences exist among models, including GPT models, they exhibit a consistent trend: Increasing the reference's depth and width results in a significant decline in performance. Notably, all models show a high variance in performance when the depth and width are limited, suggesting that the StrucText-Eval Test suite effectively distinguishes the capabilities of most models under these conditions.

However, for GPT models, substantial variance in performance is observed only when the depth and width increase significantly, indicating that the StrucText-Eval-Hard Test suite is necessary to better differentiate the performance of more advanced models. Additionally, there is considerable variance in model performance across different languages and tasks, suggesting substantial differences in models' proficiency in handling various linguistic and task-specific challenges. This discrepancy is likely due to biases in training samples and the varying difficulty levels of those samples, as suggested by earlier analyses.

**Figure 7: Cases for performance of different LLMs and finetuned stages on Structured Text.**

Left panel:

| Language: JSON | Task: TextRetrieval | Depth: 3 | Width: 1 | Col: 4 |

**Question:**
What are the most deeply nested objects, i.e., no value of type list or dict?

**Requirement:**
The content should be an excerpt as they appear in the JSON file, separated by \n\n.

**Ground Truth:**
```
{
    "id": "l",
    "X": "m",
    "subs": []
}
```

**Reference:**
```
{"id": "j",
"Z": "o",
"subs": [
    {
    "id": "k",
    "Y": "n",
    "YY": "nm",
    "subs": [
        {
        "id": "l",
        "X": "m",
        "subs": []
}]}]}
```

**Model:** GPT-4o

**Response:**
```
{
    "id": "l",
    "X": "m",
    "subs": []
}
```
**Judge:** True

**Model:** glm-4-Flash
**Response:**
To find the most deeply nested objects with no value of type list or dict, we are looking for objects that have no "subs" key or whose "subs" key corresponds to an empty list. Based on the provided JSON structure, the deepest nested objects without any further nesting (i.e., no "subs" or an empty "subs" list) would be:
```json
{"id":"l","X":"m","subs":[]}
```
This is the deepest object because it has an empty "subs" list, indicating there are no further nested objects.
**Judge:** True

Right panel:

| Language: SQL | Task: SQL.Join | Depth: 2 | Width: 8 | Col: 7 |

**Question:**
How many people who work in Twitter are taller than 178?

**Requirement:**
None

**Ground Truth:**
1

**Reference:**

| ID | gender | age | name | height | weight | color |
|---|---|---|---|---|---|---|
| a | male | 70 | a | 201 | 78 | mulatto |
| b | female | 52 | b | 219 | 117 | mulatto |
| c | male | 21 | c | 220 | 120 | olive |
| d | male | 14 | d | 148 | 148 | brown |
| e | male | 66 | e | 216 | 132 | swarthy |
| f | male | 19 | f | 181 | 130 | swarthy |
| g | female | 57 | g | 186 | 166 | swarthy |
| h | male | 46 | h | 162 | 79 | olive |

| ID | status | salary | company | location |
|---|---|---|---|---|
| a | unemployed | 353542 | Meta | CA |
| b | unemployed | 567752 | Meta | HI |
| c | retired | 304484 | OPENAI | CA |
| d | unemployed | 654219 | Twitter | HI |
| e | employed | 179425 | Meta | NY |
| f | unemployed | 561634 | Twitter | IL |
| g | unemployed | 703878 | Meta | WA |
| h | employed | 816757 | NVIDIA | HI |

**Model:** GPT-4o
**Response:** 2
**Judge:** False

**Model:** GPT-4o-mini
**Response:** There are 3 people in the Twitter workforce who are taller than 178 cm.
**Judge:** False

**Model:** Gemini-1.5-pro
**Response:** 2
**Judge:** False

**Model:** Gemini-1.5-pro-flash
**Response:** 1
**Judge:** False

## 5.5 Correlation Between Different Metrics

Figure 6 presents the correlations between various evaluation metrics. The high correlation between Human Judge and GPT-4o Judge (0.9937) indicates a strong alignment between GPT-4os automated assessments and human evaluations. Although Exact Match exhibits a notable correlation with Human Judge (0.9501), its stringent criteria often result in scores significantly lower than those of human evaluators, making it less suitable for capturing the diversity and naturalness of model outputs. Among the metrics, RougeL stands out with a correlation of 0.9932 with Human Judge, demonstrating its effectiveness in capturing surface-level textual similarity while maintaining high consistency with human judgments. Compared to the more rigid Exact Match and the relatively lower correlation of BLEU, RougeL offers a better balance between textual similarity and evaluation accuracy.

## 5.6 Case Study

Two case studies illustrate the evaluation setup of StrucText-Eval (Figure 7). In the JSON-based Text Retrieval task, GPT4-Turbo accurately identified deeply nested objects and adhered to the free-text format for outputting dictionary types, reflecting its firm grasp of structured text. Minimax also produced a correct answer but deviated from the prescribed format, a common issue explored in existing research. In contrast, GPT4-Turbo initially failed to merge two tables and deduce the correct record count without fine-tuning in the SQL-based Join task. However, a finetuned model steadily improved, achieving the correct solution after 5100 training steps. This progression demonstrates the importance of task-specific fine-tuning in enhancing models' capabilities in handling complex SQL queries and database structures.

## 6 Conclusion

The capability to directly interpret structural-rich text in a free-text format is an essential skill all LLMs require. In response, we have developed StrucText-Eval to evaluate this capability of LLMs. Our findings indicate that the proficiency of current LLMs in training on these structural-rich texts varies depending on user frequency, leading to markedly different outcomes when the same tasks are performed in various languages. LLMs' understanding of structural-rich texts remains superficially tied to the training data, and these models need a profound understanding of the structure itself. This deficiency becomes evident when LLMs encounter complex structures composed of common languages or need to parse structural-rich text by custom languages, resulting in significant performance degradation.

## 7 Limitation

This paper focuses on evaluating LLM's reasoning abilities on structure-rich text by designing a benchmark called StrucText-Eval. However, StrucText-Eval includes only eight types of structured languages and encompasses a total of 29 different tasks. Given the vast array of actual structured languages and the myriad methodologies employed beyond these 29 types, StrucText-Eval can only partially represent the LLMs' capacity to understand structure-rich text. Additionally, due to regional restrictions, we are unable to utilize some highly effective baseline LLMs, such as Gemini and Claude. Therefore, the conclusions drawn in this paper are based on the assumption that GPT-4 and GPT-4 Turbo represent the top-tier LLMs now.

## 8 Ethical Concern

We contend that this article is devoid of ethical concerns for several reasons:

1. **Nature of StrucText-Eval Content**: StrucText-Eval is primarily composed of structured language syntax and some nonsensical strings, which do not present potential ethical issues such as gender bias or racial discrimination.

2. **Objective Presentation of Experimental Results**: The experimental results pertaining to StrucText-Eval objectively demonstrate the comprehension abilities of various large models on structure-rich text included in the benchmark. We have thoroughly validated the outputs and assessment details of the models to ensure that the entire evaluation adheres to the experimental setup and maintains objectivity.

3. **Completion of Manual Tasks**: All manual tasks associated with this study were conducted by the authors themselves, thereby eliminating any issues of unfair labor practices or unethical cost imposition.

## References

2023. *Org Mode Manual: History and Acknowledgments*. Free Software Foundation. Accessed: 2024-03-18.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Tim Bray, Jean Paoli, C Michael Sperberg-McQueen, Eve Maler, and François Yergeau. 1998. Extensible markup language (xml) 1.0.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Martin Campbell-Kelly. 2003. *The history of mathematical tables: from Sumer to spreadsheets*. Oxford University Press.

Weize Chen, Chenfei Yuan, Jiarui Yuan, Yusheng Su, Chen Qian, Cheng Yang, Ruobing Xie, Zhiyuan Liu, and Maosong Sun. 2024. Beyond natural language: Llms leveraging alternative formats for enhanced reasoning and communication. *arXiv preprint arXiv:2402.18439*.

Zhikai Chen, Haitao Mao, Hang Li, Wei Jin, Hongzhi Wen, Xiaochi Wei, Shuaiqiang Wang, Dawei Yin, Wenqi Fan, Hui Liu, et al. 2023. Exploring the potential of large language models (llms) in learning on graphs. *arXiv preprint arXiv:2307.03393*.

Yao Cheng, Yige Zhao, Jianxiang Yu, and Xiang Li. 2024. Boosting graph foundation model from structural perspective. *arXiv preprint arXiv:2407.19941*.

Thomas H Cormen, Charles E Leiserson, Ronald L Rivest, and Clifford Stein. 2022. *Introduction to algorithms*. MIT press.

Clark Evans. 2001. Yaml draft 0.1. Yahoo! Tech groups: sml-dev. Archived from the original on 2001-06-03.

Bahare Fatemi, Jonathan Halcrow, and Bryan Perozzi. 2023. Talk like a graph: Encoding graphs for large language models. *arXiv preprint arXiv:2310.04560*.

John Gruber. 2012. Markdown: Syntax. *URL http://daringfireball. net/projects/markdown/syntax. Retrieved on June*, 24:640.

Jiayan Guo, Lun Du, Hengyu Liu, Mengyu Zhou, Xinyi He, and Shi Han. 2023. Gpt4graph: Can large language models understand graph structured data? an empirical evaluation and benchmarking. *arXiv preprint arXiv:2305.15066*.

Vivek Gupta, Pranshu Kandoi, Mahek Bhavesh Vora, Shuo Zhang, Yujie He, Ridho Reinanda, and Vivek Srikumar. 2023. Temptabqa: Temporal question answering for semi-structured tables. *arXiv preprint arXiv:2311.08002*.

Rikui Huang, Wei Wei, Xiaoye Qu, Wenfeng Xie, Xianling Mao, and Dangyang Chen. 2024. Joint multifacts reasoning network for complex temporal question answering over knowledge graph. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 10331–10335. IEEE.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213.

Leslie Lamport. 1985. Latex : A document preparation system.

Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81.

Zhaoyang Liu, Zeqiang Lai, Zhangwei Gao, Erfei Cui, Zhiheng Li, Xizhou Zhu, Lewei Lu, Qifeng Chen, Yu Qiao, Jifeng Dai, et al. 2023. Controlllm: Augment language models with tools by searching on graphs. *arXiv preprint arXiv:2310.17796*.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318.

Panupong Pasupat and Percy Liang. 2015. Compositional semantic parsing on semi-structured tables. *arXiv preprint arXiv:1508.00305*.

Bryan Perozzi, Bahare Fatemi, Dustin Zelle, Anton Tsitsulin, Mehran Kazemi, Rami Al-Rfou, and Jonathan Halcrow. 2024. Let your graph do the talking: Encoding structured data for llms. *arXiv preprint arXiv:2402.05862*.

Felipe Pezoa, Juan L Reutter, Fernando Suarez, Martín Ugarte, and Domagoj Vrgoč. 2016. Foundations of json schema. In *Proceedings of the 25th international conference on World Wide Web*, pages 263–273.

Yuan Sui, Mengyu Zhou, Mingjie Zhou, Shi Han, and Dongmei Zhang. 2024. Table meets llm: Can large language models understand structured table data? a benchmark and empirical study. In *Proceedings of the 17th ACM International Conference on Web Search and Data Mining*, pages 645–654.

Yu Sun, Shuohuan Wang, Shikun Feng, Siyu Ding, Chao Pang, Junyuan Shang, Jiaxiang Liu, Xuyi Chen, Yanbin Zhao, Yuxiang Lu, et al. 2021. Ernie 3.0: Large-scale knowledge enhanced pre-training for language understanding and generation. *arXiv preprint arXiv:2107.02137*.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, et al. 2022. Challenging big-bench tasks and whether chain-of-thought can solve them. *arXiv preprint arXiv:2210.09261*.

Jiabin Tang, Yuhao Yang, Wei Wei, Lei Shi, Lixin Su, Suqi Cheng, Dawei Yin, and Chao Huang. 2023a. Graphgpt: Graph instruction tuning for large language models. *arXiv preprint arXiv:2310.13023*.

Jiabin Tang, Yuhao Yang, Wei Wei, Lei Shi, Lixin Su, Suqi Cheng, Dawei Yin, and Chao Huang. 2024. Graphgpt: Graph instruction tuning for large language models. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 491–500.

Xiangru Tang, Yiming Zong, Yilun Zhao, Arman Cohan, and Mark Gerstein. 2023b. Struc-bench: Are large language models really good at generating complex structured data? *arXiv preprint arXiv:2309.08963*.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023. Plan-and-solve prompting: Improving zero-shot chain-of-thought reasoning by large language models. *arXiv preprint arXiv:2305.04091*.

Guanyuan Yu, Xv Wang, Qing Li, and Yu Zhao. 2024. Fusing llms and kgs for formal causal reasoning behind financial risk contagion. *arXiv preprint arXiv:2407.17190*.

Hanyang Yuan, Jiarong Xu, Cong Wang, Ziqi Yang, Chunping Wang, Keting Yin, and Yang Yang. 2024. Unveiling privacy vulnerabilities: Investigating the role of structure in graph data. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 4059–4070.

Xiaokang Zhang, Jing Zhang, Zeyao Ma, Yang Li, Bohan Zhang, Guanlin Li, Zijun Yao, Kangli Xu, Jinchang Zhou, Daniel Zhang-Li, et al. 2024. Tablellm: Enabling tabular data manipulation by llms in real office usage scenarios. *arXiv preprint arXiv:2403.19318*.

Qifang Zhao, Weidong Ren, Tianyu Li, Xiaoxiao Xu, and Hong Liu. 2023. Graphgpt: Graph learning with generative pre-trained transformers. *arXiv preprint arXiv:2401.00529*.

| Model | Human | GPT-4o | 4o-Mini | RougeL | BLEU | EM |
|---|---|---|---|---|---|---|
| GPT-4o-Turbo | **56.13** | **55.75** | **51.00** | **51.1** | 45.94 | **40.31** |
| GPT-4o-Mini | 36.15 | 36.02 | 40.73 | 39.3 | **46.08** | 33.93 |
| Gemini1.5-Pro | 12.39 | 12.80 | 10.62 | 11.2 | 12.60 | 8.75 |
| Gemini1.5-Pro-Flash | 13.83 | 13.19 | 12.96 | 12.9 | 14.01 | 9.67 |
| GLM-4-Plus | 52.90 | 52.62 | 46.02 | 47.3 | 32.75 | 38.27 |
| GLM-4-Flash | 41.50 | 41.34 | 38.99 | 40.9 | 37.43 | 34.80 |
| QWen-2-7B | 32.95 | 31.99 | 30.10 | 29.6 | 27.98 | 18.70 |
| QWen-2-72B | 40.87 | 38.66 | 31.24 | 42.5 | 37.76 | 35.67 |
| Llama-3.1-8B | 21.78 | 21.98 | 22.36 | 22.3 | 20.88 | 14.75 |
| Llama-3.1-70B | **46.64** | **41.38** | 40.83 | **45.8** | **41.50** | 27.46 |
| Llama-3.1-405B | 35.01 | 35.97 | 35.88 | 34.4 | 28.00 | 21.29 |
| Mistral-0.2-7B | 7.85 | 7.33 | 7.32 | 7.0 | 5.09 | 4.47 |

Table 4: Performance of all LLMs and Humans on StrucText-Eval-Hard based on different metrics (1,000 samples for each metrics).

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36:46595–46623.

Kun Zhou, Yutao Zhu, Zhipeng Chen, Wentong Chen, Wayne Xin Zhao, Xu Chen, Yankai Lin, Ji-Rong Wen, and Jiawei Han. 2023. Don't make your llm an evaluation benchmark cheater. *arXiv preprint arXiv:2311.01964*.

## A Detail about Manual Works

This paper involves the manual works in writing Question Templates and the acquisition of human performance on StrucText-Eval-Hard. All manual works are carried out by the authors of this paper, so there is no payment for the works. The three authors collectively completed the writing and verification of 29 Question Templates, and all templates along with the dataset have been made publicly available on the same website. Moreover, each of the three authors provided responses to 500 identical questions in StrucText-Eval-Hard, with each author dedicating approximately 17 hours. Thus, the human performance results presented in Table 3 are calculated based on the average scores across these 1500 responses.

## B Other Metrics

Given the substantial expense in evaluating all results using multiple metrics, we selected a subset of 300 test results for each model on the StrucText-Hard dataset, using a naive prompting method for assessment. The complete evaluation results are presented in Table 4.

## C Detail Prompt

The prompts used in the experiment can be categorized into three types: Example of Base Prompts are shown in Tab. 5. Example of CoT Prompts are shown in Tab. 6. Example of Few-Shot Prompts are shown in Tab. 7. Example of Rule Hints are shown in Tab. 8.

## D Examples for All Languages & Tasks

In this section, we provide detailed examples for each language we discuss, illustrating how specific tasks are executed within those languages. These examples are meant to offer clear insights into the application and utility of each language in various contexts. Through these demonstrations, readers can better understand the unique features and capabilities of each language when applied to different tasks.

### D.1 Tree

See Figure 8.

Figure 8: Sample input and tasks of Tree.

### D.2 Tabular

See Figure 9.

### D.3 JSON

See Figure 10.

```
# -*- coding: utf-8 -*-
Variables:
!<INPUT 0>! – Language
!<INPUT 1>! – Question
!<INPUT 2>! – Reference
!<INPUT 3>! – Requirement
<commentblockmarker>###</commentblockmarker>
you are a !<INPUT 0>! file parser, you are required to answer questions pertaining to the given !<INPUT 0>! file.

### Question:
!<INPUT 1>!

### Reference:
!<INPUT 2>!

### Requirement:
!<INPUT 3>!

Please follow the format below for your output:

### Answer:
xxxxx
```

Table 5: Prompt of `Naive Prompt` method

### D.4 YAML

See Figure 11.

### D.5 XML

See Figure 12.

### D.6 LaTeX

See Figure 13.

### D.7 Markdown

See Figure 14.

### D.8 Org

See Figure 15.

## E Rules & Rule Hints

We list all the rules in Regular Express in this section, and list all the hints for these rules in Lis. 1.

### E.1 Tree

We build tree-structured input as a list of edges in a tree, in a format of "`father->child`, separated by newline.

$$
\begin{aligned}
identifier &:= \texttt{[a-z]+} \\
Edge &:= identifier\texttt{->}identifier \\
Tree &:= Edge(\texttt{\textbackslash n}Edge)\star \\
InputFile &:= Tree
\end{aligned}
$$

### E.2 Tabular

Formally, input texts are classified as tabular data given that they are composed of a list of newline separated lines, each of which is a list of text cells delimited by comma.

$$
\begin{aligned}
head &:= \texttt{[A-Z][a-z]}\star \\
cell &:= \texttt{[A-Za-z0-9]+} \\
headline &:= identifier(,identifier)\star \\
subline &:= cell(,cell)\star \\
Tabular &:= headline(\texttt{\textbackslash n}subline)+ \\
InputFile &:= Tabular
\end{aligned}
$$

### E.3 JSON

Due to the inherit hierarchy structure of Object Notations, we adopted a recursive scheme to define our input texts.

Table 6: Prompt of `CoT` method

$$lb_{(left\ bracket)} := \texttt{[[]}$$
$$rb := \texttt{[]]}$$
$$val := \texttt{[a-z]+}$$
$$key := \texttt{[A-Z]+}$$
$$JSON := \{$$
$$\quad \texttt{"id":"}val\texttt{"}$$
$$\quad \texttt{"subs":}lbrb|lbJSON(,\texttt{\n}JSON$$
$$\quad )\star rb$$
$$\quad (\texttt{"}key\texttt{":"}val\texttt{"\n})+$$
$$\quad \}$$
$$InputFile := JSON$$

### E.4  YAML

The rules for constructing YAML and XML input are similarly recursive.

$$YAML :=$$
$$\quad \texttt{id}:val$$
$$\quad \texttt{subs}:lbrb|(\texttt{\n(\t)}\ast -\ YAML)$$
$$\quad +(key:val\texttt{\n})+$$
$$InputFile := YAML$$

```
# -*- coding: utf-8 -*-
Variables:
!<INPUT 0>! – Language
!<INPUT 1>! – Demonstration
!<INPUT 2>! – Question
!<INPUT 3>! – Reference
!<INPUT 4>! – Requirement
<commentblockmarker>###</commentblockmarker>
you are a !<INPUT 0>! file parser, you are required to answer questions pertaining to the given !<INPUT 0>! file.

### Demonstration:
!<INPUT 1>!

### Question:
!<INPUT 2>!

### Reference:
!<INPUT 3>!

### Requirement:
!<INPUT 4>!

Please follow the format below for your output:

### Answer:
xxxxx
```

Table 7: Prompt of `Few Shot` method

### E.5 XML

$$firstline := \texttt{<?xml version="1.0"}$$
$$\texttt{encoding =}\text{"UTF-8"?>}$$
$$XML :=$$
$$firstline$$
$$XMLObject$$
$$tag := \texttt{[A-Z]+}$$
$$val := \texttt{[a-z]+}$$
$$attr := \texttt{[A-Z]+="}val\texttt{"}$$
$$content := \texttt{[a-z \textbackslash n\textbackslash t]*}$$
$$XMLObject :=$$
$$\texttt{<}tag(\ attr)*\texttt{>}$$
$$((\texttt{\textbackslash t})*XMLObject)*$$
$$content$$
$$\texttt{</}tag\texttt{>}$$
$$InputFile := XML$$

### E.6 LaTeX

In LaTeX input texts, we include `textbf` and `includegraphics` commands to accommodate for the text retrieval tasks. The headings serve as anchors for structure traversal.

$$command := \texttt{\textbackslash(section|subsection|}$$
$$\texttt{subsubsection)}$$
$$heading := command\texttt{\{[a-z]+\}|[a-z]+}$$
$$inclg :=$$
$$\texttt{\textbackslash includegraphics[width=}$$
$$\texttt{0.5\textbackslash textwidth]\{[a-z]+[.]}$$
$$\texttt{(png|jpg|jpeg|gif)\}}$$
$$bf := \texttt{\textbackslash textbf\{[a-z ]+\}}$$
$$content := \texttt{([a-z ]|}bf\texttt{|}inclg\texttt{)+}$$
$$LaTeX := heading\texttt{\textbackslash n}content(\texttt{\textbackslash n}LaTeX)*$$
$$InputFile := LaTeX$$

### E.7 Markdown

In markdown input texts, the syntax counterparts for heading, text face and including figure are em-

```
# -*- coding: utf-8 -*-
Variables:
!<INPUT 0>! – Language
!<INPUT 1>! – Question
!<INPUT 2>! – Reference
!<INPUT 3>! – Requirement
!<INPUT 4>! – Rule Hint
<commentblockmarker>###</commentblockmarker>
you are a !<INPUT 0>! file parser, you are required to answer questions pertaining to the given !<INPUT
0>! file.

### Question:
!<INPUT 1>!

### Reference:
!<INPUT 2>!

### Requirement:
!<INPUT 3>!

### Rule Hint:
!<INPUT 4>!

Please follow the format below for your output:

### Answer:
xxxxx
```

Table 8: Prompt of \w Hint method

ployed in our dataset.

$$heading \coloneqq \texttt{[\#]* [a-z]+}$$
$$inclg \coloneqq \texttt{!}lb\texttt{alt}rb\texttt{\textbackslash([a-z]+[.](png}$$
$$\texttt{|jpg|jpeg|gif)}$$
$$\texttt{"hover text"\textbackslash)}$$
$$bf \coloneqq \texttt{[*]\{2\}[a-z ]+[*]\{2\}}$$
$$content \coloneqq \texttt{([a-z ]}|bf|inclg\texttt{)+}$$
$$Markdown \coloneqq heading\texttt{\textbackslash n}$$
$$content(\texttt{\textbackslash n}Markdown)*$$
$$InputFile \coloneqq Markdown$$

## E.8 Org

In Org input texts, the syntax is obtained from JSON construction rules by replacing the markups

for heading, including figures and bold font face.

$$heading \coloneqq \texttt{[*]* [a-z]+}$$
$$inclg \coloneqq lb\texttt{\{2\}[a-z]+[.](png|jpg|}$$
$$\texttt{jpeg|gif)}rb\texttt{\{2\}}$$
$$bf \coloneqq \texttt{[*][a-z ]+[*]}$$
$$content \coloneqq \texttt{([a-z ]}|bf|inclg\texttt{)+}$$
$$Org \coloneqq heading\texttt{\textbackslash n}content(\texttt{\textbackslash n}Org)*$$
$$InputFile \coloneqq Org$$

Listing 1: All rule hints in StrucText-Eval

```
SQL,Tree,JSON,YAML,XML,Markdown,LaTeX,
    ↪ ORG
To find the value of specific field of
    ↪ record with specified primeKey.
    ↪ You have to first, locate the line
    ↪  with the specific primeKey. Then
    ↪ find the required value under the
    ↪ desired column in that line.
To get the number of people with salary
    ↪ above a threshold, you need to
    ↪ find the table with salary
    ↪ information. Then you go over each
    ↪  line and check the salary field.
```

Figure 9: Sample input and tasks of tabular data.

Figure 10: Sample input and tasks of JSON.

**Input**

```
primeKey gender age name height weight color
a female 23 n 157 144 olive
b male 39 o 191 104 swarthy
c male 14 p 134 162 black
d male 39 q 163 124 brown

primeKey status salary companylocation
a employed 460789 TwitterNY
b retired861910 NVIDIA GA
c retired360565 Meta CA
d employed 350426 Google GA
```

**Task 1**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

What is the color of record with primeKey c

**Ground Truth**

black

**Task 2**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

How many people who work in IL are taller than 171?

**Ground Truth**

0

**Task 3**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

How many people work with salary more than 516275?

**Ground Truth**

1

**Task 4**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

How many people are female?

**Ground Truth**

1

**Input**

```
{"id":"o",
"Z":"u",
"subs":[
 {
 "id":"p",
 "Y":"t",
 "subs":[
  {
  "id":"q",
  "X":"s",
  "subs":[]
 }]}
]
}
```

**Input for Task 5**

```
{"id":"o",
"Z":"u",
"subs":[
 {
 "id":"p",
 "Y":"t",
 "subs":[
 "id":"q",
 "X":"s",
 "subs":]
 ]}
]
}
```

**Task 1**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

What is the first object's id of subs?

**Ground Truth**

p

**Task 2**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

What is the object with id p? The content should be an excerpt as it appears in the JSON file.

**Ground Truth**

{\n"id":"p",\n"Y":"t",\n"subs":[\n{\n"id":"q",\n"X":"s",\n"subs":[]}]}

**Task 3**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

How to access value "u"? Answer should be like obj[key or index 1][key or index 2][key or index 3]...

**Ground Truth**

obj["Z"]

**Task 4**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

What are the most deeply nested objects, i.e., no value of type list or dict?The content should be an excerpt as they appear in the JSON file, separated by \\n\\n.

**Ground Truth**

{\n  "id":"q",\n  "X":"s",\n  "subs":[]\n  }

**Task 5**

- - - - - - - - - - - - - - - - - - - - - - - - - -

**Question**

Is there any structural error in this JSON? If so, give the answer 'True' and spot them out. If it is free from error, just give the answer 'False'.

**Ground Truth**

True

```
844    ↪ During the process count only
845    ↪ those lines with value of salary
846    ↪ strictly greater than the
847    ↪ specified threshold towards your
848    ↪ final sum. The sum after checking
849    ↪ each line is the right answer.
850 To get the number of female, first find
851    ↪ the table with column name ''.
852    ↪ Then check each line for field
853    ↪ gender, and count these lines with
854    ↪  value 'female' towards your final
855    ↪  sum. The process applies to
856    ↪ finding number of male too.
857 To get the number of people living in
858    ↪ specified city who are also taller
859    ↪  than threshold, you need to first
860    ↪  join the two table on primeKey,
861    ↪ and check each row of joined table
862    ↪  for lines that satisfies both
863    ↪ condition, i.e., lines with city
864    ↪ specified in query and height
865    ↪ strictly greater than threshold.
866    ↪ The total number of such rows is
867    ↪ the right answer.
868 To answer the height of tree, you need
869    ↪ to take a recursive strategy. For
870    ↪ each node, you will find its
871    ↪ height by first finding its
```

```
872    ↪ children's heights. Then, the
873    ↪ height of node is the maximum
874    ↪ subtree heights plus 1. The base
875    ↪ case occurs when a node has no
876    ↪ children, i.e., it's a leaf node.
877    ↪ Leaf's height is defined to be 0,
878    ↪ without the need of further
879    ↪ queries. Then the height the tree
880    ↪ is the height of its root node.
881 To find the depth of a node, you need to
882    ↪  find the number of edges from
883    ↪ root to node. You have to start
884    ↪ from the root with depth 0 and
885    ↪ assign the depth for each node
886    ↪ recursively. For any given node,
887    ↪ it gets depth of current depth.
```

## Figure 11: Sample input and tasks of YAML.

## Figure 12: Sample input and tasks of XML.

**Input**

```
id: "s"
Z: e,
subs:
- id: "t"
  Y: d,
  subs:
  - id: "u"
    X: c,
    subs: []
```

**Input for Task 3**

```
id: "s"
Z: e,
subs:
- id: "t"
  Y: d
  subs:
  - id: "u"
    X:
    subs: []
```

**Task 1**

**Question** ❓

What is the first object's id of subs?

**Ground Truth** ℹ️

t

**Task 2**

**Question** ❓

How to access value "d"? Answer should be like obj[key or index 1][key or index 2][key or index 3]...

**Ground Truth** ℹ️

obj["subs"][0]["Y"]

**Task 3**

**Question** ❓

Is there any structural error in this YAML? If so, give the answer 'True' and spot them out. If it is free from error, just give the answer 'False'.

**Ground Truth** ℹ️

True

**Task 4**

**Question** ❓

What is the object with id t? The content should be an excerpt as it appears in the YAML file.

**Ground Truth** ℹ️

id: "t"\n  Y: d,\n  subs: \n  - id: "u"\n    X: c,\n    subs: []

**Task 5**

**Question** ❓

What are the most deeply nested objects, i.e., no value of type list or dict?The content should be an excerpt as they appear in the YAML file, separated by \\n\\n.

**Ground Truth** ℹ️

id: "u"\n    X: c,\n    subs: []

---

**Input**

**Input for Task 3**

(XML content for Task 3)

**Task 1**

**Question** ❓

What is the content of tag HB? The content should be an excerpt as it appears in the XML file.

**Ground Truth** ℹ️

<IB>\n  idiot banana\n </IB>\n <JB F=\"jy\">\n  jargon banana\n </JB>\n <KB>\n  kangaroo banana\n </KB>\n <LB>\n  lamb banana\n </LB>\n halo banana

**Task 2**

**Question** ❓

What is the tag with attribute of value xy?

**Ground Truth** ℹ️

N

**Task 3**

**Question** ❓

Is there any structural error in this XML? If so, give the answer 'True' and spot them out. If it is free from error, just give the answer 'False'.

**Ground Truth** ℹ️

True

---

```
     ↪ Increment the depth by 1 before go
     ↪  to its subtree and repeat the
     ↪ process until every node gets a
     ↪ depth.
To get the path from root to a node, you
     ↪  need to find recursively. For any
     ↪  node, you can find the path to
     ↪ the target node by find path from
     ↪ its children to target. Then check
     ↪  each child's output, if any child
     ↪  returns with valid path instead
     ↪ of an empty path indicating target
     ↪ -not-found, the path from node to
     ↪ target is that path from its child
     ↪  to target prepended with itself.
     ↪ The answer can be found by
     ↪ searching with root as starting
     ↪ point.
To find the object with specified id,
```

```
↪ you need to first parse the json
↪ file and get the outermost object,
↪  starting from which search the
↪ subs field recursively and looking
↪  for the desired value in id field
↪  for each visited object. Retrieve
↪  the content of that object once
↪ found.
To find the first object's id of subs,
↪ first parse the json file and get
↪ the outermost object, in the
↪ outermost object's subs list, get
↪ the first element. That element is
↪  another object, and its id is the
↪  answer.
To find the error in the json file, you
↪ need to parse the json file and
↪ report any syntax error if
```

Figure 13: Sample input and tasks of LaTeX.

Figure 14: Sample input and tasks of Markdown.

**Input**

```
o
monkey \textbf{banana}nob wake yogurt groot wake
jargon ravish
\section{p}
nob nob wake
\textbf{cafe}yogur\includegraphics[width=0.5\textwid
th]{mh.jpeg}t groot wake jargon ravish
\subsection{q}
oops nob wake yogurt groot wake
jargon\textbf{dentist} ravish
```

**Task 1**

**Question**

Extract all bold texts. Print those raw texts separated by \\n.

**Ground Truth**

```
banana\ncafe\ndentist
```

**Task 2**

**Question**

Extract all included graph files. Print those file names separated by \\n.

**Ground Truth**

```
mh.jpeg
```

**Task 3**

**Question**

What is the content of 1th section? The content should be an excerpt as it appears in the LaTeX file, including the heading line and any sub-section.

**Ground Truth**

```
\section{p}
nob nob wake
\textbf{cafe}yogur\includegraphics[width=0.5\textwidth]{mh.jpeg
}t groot wake jargon ravish
\subsection{q}
oops nob wake yogurt groot wake jargon\textbf{dentist} ravish
```

**Input**

```
w
banana cafe vigor cafe peris![alt](mj.gif "hover
text")h perish monkey wake
# x
cafe cafe vigor cafe perish peris**banana**h monkey
wake
## y
dentist cafe vigor c**cafe**![alt](nj.jpg "hover
text")afe perish perish monkey wake
```

**Task 1**

**Question**

Extract all bold texts. Print those raw texts separated by \\n.

**Ground Truth**

```
cafe\nbanana
```

**Task 2**

**Question**

Extract all included image files. Print those file names separated by \\n.

**Ground Truth**

```
mj.gif\nnj.jpg
```

**Task 3**

**Question**

What is the content of 1th section? The content should be an excerpt as it appears in the markdown file, including the heading line and any sub-section.

**Ground Truth**

```
# x
cafe cafe vigor cafe perish peris**banana**h monkey wake
## y
dentist cafe vigor c**cafe**![alt](nj.jpg "hover text")afe
perish perish monkey wake
```

Figure 15: Sample input and tasks of Org.

**Input**

```
p
kanga*lamb*roo zen yogurt X-ray halo zen nob qualify
* q
lamb zen yogurt X-ray halo zen nob qu[[ei.jpg]]alify
** r
monkey zen yogurt X-ray halo zen nob qualify
```

**Task 1**

**Question**

Extract all bold texts. Print those raw texts separated by \\n.

**Ground Truth**

```
lamb
```

**Task 2**

**Question**

Extract all included image files. Print those file names separated by \\n.

**Ground Truth**

```
ei.jpg
```

**Task 3**

**Question**

What is the content of 1th subsection under 1th section? The content should be an excerpt as it appears in the org file, including the heading line and any sub-section.

**Ground Truth**

```
** r\nmonkey zen yogurt X-ray halo zen nob qualify
```

```
            ↪ encountered any. Potential errors
            ↪ include missing ending curly
            ↪ braces.
To get the path to access specified
            ↪ value. You have to do a recursive
            ↪ search along the subs fields,
            ↪ starting from the outermost parsed
            ↪  object. For each visited object,
            ↪ check each fields except for subs,
            ↪  and record the path along the way
            ↪ , i.e., subs inside brackets and
            ↪ index into subs inside brackets,
            ↪ and at which field you find the
            ↪ value.
To get the most deeply nested objects,
            ↪ start from the outermost object,
            ↪ recursively search along the subs
            ↪ fields. For each object, check its
            ↪  subs field, any object with an
            ↪ empty subs is one most deeply
            ↪ nested object.
To find the object with specified id,
            ↪ you need to first parse the yaml
            ↪ file and get the outermost object,
            ↪  starting from which search the
            ↪ subs field recursively and looking
            ↪  for the desired value in id field
            ↪  for each visited object. Retrieve
            ↪  the content of that object once
            ↪ found.
To find the first object's id of subs,
            ↪ first parse the yaml file and get
```

```
                    ↪ the outermost object, in the
                    ↪ outermost object's subs list, get
                    ↪ the first element. That element is
                    ↪  another object, and its id is the
                    ↪  answer.
To find the error in the yaml file, you
    ↪ need to parse the yaml file and
    ↪ report any syntax error if
    ↪ encountered any. Potential errors
    ↪ include missing key before colon.
To get the path to access specified
    ↪ value. You have to do a recursive
    ↪ search along the subs fields,
    ↪ starting from the outermost parsed
    ↪  object. For each visited object,
    ↪ check each fields except for subs,
    ↪  and record the path along the way
    ↪ , i.e., subs inside brackets and
    ↪ index into subs inside brackets,
    ↪ and at which field you find the
    ↪ value.
To get the most deeply nested objects,
    ↪ start from the outermost object,
    ↪ recursively search along the subs
    ↪ fields. For each object, check its
    ↪  subs field, any object with an
    ↪ empty subs is one most deeply
    ↪ nested object.
To find the content of a specific tag,
    ↪ you need to search for desired tag
    ↪  throughout the xml file. Once
    ↪ located, find the surrounding left
    ↪  and right angle, these area is
    ↪ tha starting tag. Then find the
    ↪ ending tag, which is the tag
    ↪ surrounded by angle with exception
    ↪  that right angle is preceded by a
    ↪  slash. The content between
    ↪ starting and ending tags is the
    ↪ answer.
To find the tag name of particular
    ↪ attribute value, just search the
    ↪ file for that value and find the
    ↪ surrounding left and right angles,
    ↪  i.e., boundary of tag. The word
    ↪ next to left angle is tag name.
To find the error in the xml file, you
    ↪ need to parse the xml file and
    ↪ report any syntax error if
    ↪ encountered any. Potential errors
    ↪ include missing ending tags.
To find the bold texts, search for
    ↪ double stars, i.e., **, the
    ↪ content between two occurrences of
    ↪  double stars is the bold texts.
    ↪ Note that the bold range should
    ↪ start from the double stars
    ↪ occurring at i-th spot throughout
    ↪ the whole input file, where i is
    ↪ odd, and end with double stars
    ↪ occurring at jth spot where j is
    ↪ even. For example, text between
    ↪ double stars appearing first and
    ↪ second time.
To find the content of certain section,
    ↪ starting from the headings start
    ↪ with one hashtag, and go to the
    ↪ ith heading as specified in number
    ↪  of sections. Then start from that
    ↪  line, look for j-th heading with
    ↪ 2 hashtags as specified in
    ↪ subsection number. For kth
    ↪ subsubsection, look for kth
    ↪ heading with 3 hashtags starting
    ↪ from the located subsubsection.
    ↪ Stop searching early if the
    ↪ subsection or subsubsection is not
    ↪  queried.
To find the image files, look for texts
    ↪ matching ![*](TARGET "*"), the
    ↪ TARGET part is filename. Star
    ↪ means any text is possible.
To find the bold texts, search for macro
    ↪  textbf, and everything after \\
    ↪ textbf{ and before the first }
    ↪ encountered is bold text.
Note that section title is enclosed by
    ↪ \\section{}, and \\subsection for
    ↪ subsection, \\subsubsection for
    ↪ subsubsection. To find the content
    ↪  of certain section, look for ith
    ↪ section as specified, and start
    ↪ from there look for jth subsection
    ↪ . And from located subsection,
    ↪ look for kth subsubsection as
    ↪ queried. Search may stop early if
    ↪ subsection or subsubsection is not
    ↪  queried.
To find the image files imported, search
    ↪  for pattern \\includegraphics[*]{
    ↪ TARGET}, the TARGET part is the
    ↪ filename. Star means any text is
    ↪ possible.
To find the bold texts, search for
    ↪ single star, i.e., *, the content
    ↪ between two occurrences of single
    ↪ star is the bold texts. Note that
    ↪ the bold range should start from
    ↪ the single star occurring at i-th
    ↪ spot throughout the whole input
    ↪ file, where i is odd, and end with
    ↪  single star occurring at jth spot
    ↪  where j is even. For example,
    ↪ text between single star appearing
    ↪  first and second time.
Note that section, subsection,
    ↪ subsubsection titles are preceded
    ↪ by *, **, *** respectively, with
    ↪ one or more whitespaces in between
    ↪ . To find the content of certain
    ↪ section, look for ith section as
    ↪ specified, and start from there
    ↪ look for jth subsection. And from
    ↪ located subsection, look for kth
    ↪ subsubsection as queried. Search
    ↪ may stop early if subsection or
    ↪ subsubsection is not queried.
To find the image files, look for texts
    ↪ matching [[TARGET]], the TARGET
    ↪ part is filename
```

## F   Detail Setting

All experiments and training process is carried out on a three 3090 GPUs service. The setting of API calling is illustrated in Tab. 9

| Random Seed | | | | |
|---|---|---|---|---|
| torch.manual_seed | torch.cuda.manual_seed_all | numpy.random.seed | random.seed | torch.backends.cudnn.deterministirc |
| 42 | 42 | 42 | 42 | True |
| AutoCausalLM | | | | |
| temperature | top_p | top_k | num_beams | max_new_token |
| 0.95 | 0.95 | 5 | 2 | 1 |

Table 9: All the parameter setting in our experiments.