DISAMBIGUATING SYMBOLIC EXPRESSIONS IN INFORMAL DOCUMENTS

ABSTRACT

We propose the task of *disambiguating* symbolic expressions in informal STEM documents in the form of LaTeX files – that is, determining their precise semantics and abstract syntax tree – as a neural machine translation task. We discuss the distinct challenges involved and present a dataset with roughly 33,000 entries. We evaluated several baseline models on this dataset, which failed to yield even syntactically valid LaTeX before overfitting. Consequently, we describe a methodology using a *transformer* language model pre-trained on sources obtained from `arxiv.org`, which yields promising results despite the small size of the dataset. We evaluate our model using a plurality of dedicated techniques, taking syntax and semantics of symbolic expressions into account.

1 INTRODUCTION

Despite huge advancements in machine learning, the task of a understanding informal reasoning is still beyond current methods. In fact, it became commonplace that humans annotate informal documents containing reasoning in many domains, e.g. law Libal & Steen (2020). Reasoning is most visible in mathematical documents and software specification and as such in the last decades, the formalization of mathematical knowledge, and the verification of formal proofs, has become increasingly popular. By now, dozens of interactive and automated theorem prover systems are available, each providing libraries with up to hundreds of thousands of formalizations of mathematical definitions, theorems, and their proofs written by human mathematicians Harrison et al. (2014).

While formal methods are still primarily used by computer scientists (e.g. to verify software and hardware, as well as in program synthesis), by now they have also drawn the interest of an increasing number of research mathematicians – primarily thanks to famous problems such as Kepler's conjecture Hales et al. (2017) or the classification theorem for finite simple groups Solomon (1995), which have successfully been verified using theorem prover systems.

However, while *some* mathematicians have begun actively adapting formal methods for their work, there is a prohibitively large discrepancy between the way new mathematical results are developed, presented and published in mathematical practice, and the way they are formalized and implemented in formal systems Kaliszyk & Rabe (2020): Most theorem proving systems implement a fixed *logical foundation* (such as variants of set theory or various kinds of type theories), a surface syntax in which a user declares new definitions and statements in terms of the underlying foundations, and either a tactic language or a language for expressing *proof terms* (usually on basis of the Curry-Howard-correspondence in a typed λ-calculus) that allow for declaring proofs. Consequently, the process of formalizing new content in a formal system resembles *programming* much more than it does developing informal proofs.

This discrepancy results in severe challenges for traditional mathematicians: Formal systems are difficult to learn and use, even if one is well acquainted with the (informal) mathematics involved. They require learning dedicated formal languages resembling programming languages, declaring content on a level of detail that is prohibitive for beginners even for "obvious" conclusions, and their libraries are difficult to grasp without already being familiar with the system's language, conventions and functionalities. Due to the required level of detail, knowledge of the existing libraries is crucial when formalizing new content. Furthermore, many "intuitively valid" arguments can not be easily expressed in terms of a logical foundation in the first place, and knowing how to deal with those requires familiarity with the logical foundation involved and lots of practice.

Consequently, the utility of formalizing mathematical results can be too easily (and too often *is*) dismissed in light of the additional time and work required for non-experts. This is despite the fact that many services available for formal mathematics are already enabled by *semi*-formal (or *flexiformal*) representations, such as semantic annotations in natural language texts, or formal representations containing opaque informal expressions (see e.g. Kohlhase (2013); Lange (2011a); Iancu (2017); Kohlhase et al. (2017a); Corneli & Schubotz (2017); Dehaye et al. (2016)). Therefore, we need to invest into methods for bridging the gap between informal mathematical practice and (semi-)formal mathematics. One way to do so is to investigate *autoformalization*, the task of (semi-automatically) converting existing informal mathematical presentations to (increasingly) formal representations.

Notably, these issues extend beyond pure mathematics to other STEM (science, technology, engineering and math) fields, where the formal verification (or lack thereof) of results can have direct real-world implications – examples include an infamous and costly error in the floating-point unit of Intel processors Harrison (2003) and several human failures to adequately convert between SI and imperial units, most famously in NASA's Mars orbiter Grossman. In fact, the former has already established formal verification as a vital tool in hardware design Harrison (2003).

Two observations motivate the research presented here:

1. The vast majority of STEM researchers can be assumed to be comfortable with using LaTeX; any integration of formal methods in a LaTeX development environment (e.g. via new packages or IDE integration) would consequently lower the entry barrier significantly.

2. the task of going from purely informal mathematical texts to fully formal representations of the contained knowledge is best done via a separation of concerns, by focussing on individual subtasks (such as disambiguating symbolic expressions, natural language parsing and translating to a formal foundation) using dedicated tools for each.

In this paper, we discuss specifically the task of *disambiguating* symbolic expressions – i.e. associating all symbols in an expression with their precise semantics – in LaTeX documents as a machine learning task, using sTEX semantically annotated LaTeX Kohlhase (2008). The contributions are threefold:

1. We discuss the details of disambiguating symbolic expressions in informal STEM documents as a neural machine translation task, 2. we present a new dataset specifically for this task, based on the existing SMGLoM library of sTEX macros (see Subsection 2.2), and 3. we present a methodology (using transformer language models) that allows us to achieve positive results on our dataset. We previously evaluated several baseline NMT models (such as Luong et al. (2017); Vaswani et al. (2017) and a plain character-based sequence-to-sequence model), which all failed to yield meaningful results due to our dataset being considerably smaller than is required for traditional NMT models.[1]

2 Preliminaries

By *disambiguating*, we mean the task of transforming a sequence of symbols (representing a mathematical formula) into an *abstract syntax tree* and associating each leaf in the tree with a unique identifier specifying the precise semantics of the corresponding symbol.

While this might superficially seem an easy task, closer consideration shows that even obvious seeming statements such as "$a + b$" can in fact correspond to a multitude of possible disambiguations: a and b can be variables or previously defined constants, whereas $+$ can represent e.g. addition on multiple different number spaces, generic ring or vectorspace operations, or string concatenation. In order to adequately disambiguate expressions generically, it is therefore necessary to take the context in which the expression occurs into account.

In this paper, we consider informal documents in LaTeX specifically, which we will disambiguate with the sTEX package, using semantic identifiers provided by the *SMGloM* library. This eventually enables various formal knowledge management services (such as type/proof checking) provided by the MMT system.

---

[1] All code and data relevant to this paper is available at `https://u.pcloud.link/publink/show?code=XZDXlqkZvNTaiDsAOzjVxyxeaCFwI8YCMsDV`.

This link will be replaced by one to a git repository after the anonymity period has ended.

2.1 sTeX

Kohlhase proposed sTeX Kohlhase (2008), a package for annotating LaTeX documents with structural and formal semantics which is today used by multiple groups formalizing mathematics in various systems. In particular, sTeX is based on OMDoc Kohlhase (2006), an extension of OpenMath Buswell et al. (2004) which is foundation-agnostic in the sense that it does not favor a specific foundation (such as type or set theories) over any other. This approach is consequently best suited for semantifying informal documents, where foundations are often unspecified, left implicit or switched fluently. For example, category theoretic and set theoretic formulations are often used interchangeably in algebraic settings, whereas type theories are generally favored for computational aspects and formal systems.

Figure 1 shows example sTeX macros and their usage in various stages. Relevant for this paper is primarily the `\symdef` command, which introduces a new mathematical concept (e.g. `\nattimes` in Figure 1). It takes as arguments a macro name (e.g. `nattimes`), a symbolic notation (last argument) and optionally an OMDoc-name (e.g. `multiplication`), arity (e.g. `[1]`, which may be flexary) and notational precedence (e.g. `p=600`, for automatic bracketing). It generates a unique identifier for the concept being declared (based on the provided OMDoc-name), and a new LaTeX macro (e.g. `\nattimes`) for referring to the symbol. Alternative notational variants for symbols can be introduced via `\symvariant`, which are used as options to the macro (e.g. `\nattimes[cdot]`).

In addition to being valid LaTeX compilable via `pdflatex`, sTeX-documents can be transformed to OMDoc using the LaTeXML-software Ginev et al. (2011), yielding a formally disambiguated representation of the document and in particular the symbolic expressions therein on the basis of the macros provided by `\symdef`s. LaTeXML also heuristically attempts to disambiguate non-sTeX-symbols, e.g. by considering "=" and "+" as infix notations for generic equality and addition operators, respectively.

2.2 SMGLoM

The *SMGloM* Kohlhase (2014), *semantic multilingual glossary of mathematics*) is a library of hundreds of sTeX-modules containing mathematical concepts and definitions. It is separated into *signature modules* (using the `modsig`-environment, see Figure 1) containing only symbol declarations, and *natural language modules* (using the `mhmodnl`-environment, here exemplary for English) that serve as dictionary entries for these, in which the semantics of the symbols are described in a semi-formal manner. The second row of Figure 1 shows an SMGLoM entry.

2.3 Mmt

sTeX itself is integrated, and shares an underlying OMDoc ontology, with the Mmt system Rabe & Kohlhase (2013); Horozal et al. (2012); Rabe (2017) – a foundation-independent meta-framework and API for knowledge management services. This integration makes the generic services provided by Mmt– e.g. type checking, library management/browsing, translation – available to informal mathematical texts. Using *alignments* Müller (2019); Müller et al. (2017), OMDoc-expressions can be translated between different libraries, languages and foundations. This allows for e.g. translating (originally) sTeX-content to a typed setting in order to e.g. check expressions and run type inference.

Additionally, several theorem prover libraries have been translated to OMDoc and integrated in the Mmt system, e.g. Kohlhase et al. (2017b); Müller et al. (2019) (for a detailed overview, see Müller (2019) and Kohlhase & Rabe (2020)). Extending these integrations to enable exporting from Mmt as well (and in conjunction with natural language processing), this could enable verifying informal mathematics imported via sTeX using external state-of-the-art theorem prover systems.

3 State of the Art

Various papers over the last years have – explicitly or implicitly – attempted to extract formal information from informal documents using machine learning. These fall into two categories:

Firstly, there are projects that attempt to fully formalize informal mathematical documents using machine learning techniques, using the surface language of some theorem prover system directly as a target. In Kaliszyk et al. (2017b; 2015; 2014), the Flyspeck project Hales et al. (2017) – the

| sTeX declarations (signature module) | ```
\begin{modsig}{natarith}
 ...
 \symdef[name=multiplication]{nattimesOp}{\*}
 \symvariant{nattimesOp}{cdot}{\mathop\cdot}
 \symdef[assocarg=1,name=multiplication]
   {nattimes}[1]{\assoc[p=600]{\nattimesOp}{#1}}
 \symvariant{nattimes}[1]{cdot}
   {\assoc[p=600]{\nattimesOp[cdot]}{#1}}
... \end{modsig}
``` |
| --- | --- |
| sTeX references (natural language module) | ```
\begin{mhmodnl}{natarith}{en}
 ...
 \begin{definition}
  \Defi{multiplication} $\nattimesOp[cdot]$
  computes the \defi{product} $\nattimes[cdot]
   {a,b}$ (also written as $\nattimes{a,b}$ or
  $\nattimes[x]{a,b}$) of \trefiis[naturalnumbers]
   {natural}{number} $a$ and $b$. It is defined
  by the equations $\eq{\nattimes[cdot]{x,0},0}$
  and $\eq{\nattimes[cdot]{x,\natsucc{y}},
   \natplus{x,\nattimes[cdot]{x,y}}}$.
 \end{definition}
... \end{mhmodnl}
``` |
| PDF output (for the natural language module) | **Definition.** Multiplication $\cdot$ computes the product $a \cdot b$ (also written as ab or $a \times b$) of natural numbers a and b. It is defined by the equations $x \cdot 0 = 0$ and $x \cdot S(y) = x + x \cdot y$. |
| OMDoc | ```
<OMA>
  <OMS cd="smglom:mv?equal" name="equal"/>
  <OMA>
    <OMS cd="smglom:arithmetics?natarith"
      name="multiplication"/>
    <OMV name="x"/>
    <OMI>0</OMI>
  </OMA>
  <OMI>0</OMI>
</OMA>
``` |

Figure 1: An sTeX Example: The OMDoc corresponds to the symbolic expression $x \cdot 0 = 0$

formalization of Kepler's theorem – was used as a basis for a parallel dataset in order to translate from informal mathematics to HOL Light Harrison (1996) syntax. Kaliszyk et al. (2017a); Wang et al. (2018; 2020) target the Mizar language Mizar instead, using the *Journal of Formalized Mathematics* JFM as data – an informal representation of the formal *Mizar Mathematical Library* Bancerek et al. (2018). While these projects achieved impressive results given the ambitious nature of the task, their success rate is naturally limited by the involved models having to solve several tasks at once (see second observation in Section 1). Additionally, by going to a fully formal language immediately, the result does not preserve the narrative presentation of the input document, effectively losing (for us) valuable information in the process.

Secondly, various projects have aimed to *solve* informally presented mathematical problems of various kinds. These include Arai et al. (2014); Matsuzaki et al. (2014; 2017; 2018) on pre-university math problems, Saxton et al. (2019) and Lample & Charton (2019) on high-school level equations, Gan & Yu (2017) and Seo et al. (2015) on geometric problems, and Huang et al. (2018) and Wang et al. (2017) on solving typical high-school word problems. While this naturally entails disambiguating symbolic expressions, all these projects reduce their domain of applicability to specific areas where all occurring formal symbols are syntactically unambiguous – primarily common arithmetic operations, functions and relations on real numbers – such that disambiguation reduces to simple parsing.

4 sTeX-Annotating with Machine Learning as an NMT Task

Disambiguating plain LaTeX math expressions via sTeX annotations amounts to a translation problem, for which NMT models have been proven to be quite effective, even beyond natural language

translations Clark et al. (2020). In fact, several projects have attempted to fully auto-formalize informal mathematics by translating LaTeX documents to the surface language of a formal system (e.g. Mizar in Kaliszyk et al. (2017a); Wang et al. (2018), HOL Light in Kaliszyk et al. (2017b; 2015; 2014)), with positive results. The function we want to learn is the following:

Definition 4.1. *(Disambiguation Task) Let $\mathcal{L}$ be a set of LaTeX fragments (i.e. strings), which we assume are syntactically valid LaTeX in some suitable document context.*

A symbolic expression is (for our purposes, simplified) any substring s of some $S \in L$ such that s is interpreted by the TeX-engine in math mode – e.g., if it is delimited by $\$$, $\$\$$ or $\backslash$ $[$ and $\backslash$ $]$ respectively.

We call $S \in \mathcal{L}$ fully disambiguated, if every symbolic expression occurring in S only consists of:

1. variable names *(e.g.* `n` *or* `\mathcal{G}`, *provided they do not represent specific, definite mathematical objects),*

2. *sTeX macros introduced via a* `\symdef` *declaration in the SGLoM, or*

3. non-semantic *commands or characters, such as additional spaces/tabs/linebreaks, purely aesthetic spacing or kerning commands, unnecessary parentheses or clarifying comments (e.g. in under- or overbraces).*

Let $\mathcal{L}_{sTeX} \subset \mathcal{L}$ the subset of fully disambiguated LaTeX fragments. Conversely, let $\mathcal{L}_{LaTeX} \subset \mathcal{L}$ be the set of LaTeX fragments that do not contain any sTeX macros[2].

Clearly, for any $S \in \mathcal{L}$, there is some $LaTeX(S) \subset \mathcal{L}_{LaTeX}$ such that S and any $S' \in LaTeX(S)$ represent the same symbolic presentation – i.e. they generate the same output on `pdflatex`.

Conversely, we assume that for any $S \in \mathcal{L}$ there is a set $sTeX(S) \subset \mathcal{L}_{sTeX}$ such that 1. $LaTeX(S) = LaTeX(S')$ for all $S' \in sTeX(S)$ (i.e. they have the same symbolic presentation) and 2. all $S' \in sTeX(S)$ capture the intended semantics of S - i.e. the author of S, were they to know the SMGLoM library sufficiently well, would agree that S' is a correctly fully disambiguated variant of S.

Our goal is to learn a function $f : \mathcal{L} \to \mathcal{L}$ such that for any $S \in \mathcal{L}$ we have $f(S) \in sTeX(S)$.

There are several aspects which distinguish a LaTeX-to-sTeX translation from similar translation tasks which significantly affect the applicability of existing tools and hence our methodology. First, Unlike the most popular formal systems, there is no large library of formalizations for the translation target. The primary library (i.e. SMGLoM) provides relatively few symbols and hence can only cover a small part of informal documents even in theory. Consequently, a translation mechanism should be able to adapt to additions to the SMGLoM-library, even more so than with other formal systems that usually have a sufficiently large (and relatively stable) core library covering a decent part of mathematics. Additionally, apart from some rudimentary concepts such as logical connectives or basic arithmetic functions, the SMGLoM library *references* the majority of symbols only once (in the corresponding dictionary entry). This is unlike most other formal systems, where all symbols need to be typed or defined formally when being declared, which naturally leads to a significant number of references to previously declared symbols. The only other publically available sTeX library (MiKoMH; consisting of lecture notes) is heavily biased towards subjects in computer science, covering only a small part of SMGLoM-entries, and often introducing local `\symdef`s.

This leaves us with only a small dataset that does not represent well the general distribution we would like to learn. Second, translation is only relevant for specific fragments of an input text, namely the symbolic expressions; for the surrounding natural language texts, translation should be the identity. Nevertheless, surrounding text usually contains critical information for disambiguation; e.g. without the surrounding context, it is impossible to disambiguate an expression $a + b$, since the symbol "+" could refer to any of dozens of addition operations.

Finally, depending on perspective, the domain language is a proper subset of the target language; or rather (since we want to avoid ambiguous expressions in sTeX) domain and target language share both a basic grammar as well as a large amount of vocabulary (namely $\mathcal{L}_{LaTeX} \cap \mathcal{L}_{sTeX}$) which e.g. subsumes natural English. For the domain language, large datasets are easily obtainable.

---

[2]Note that $\mathcal{L}_{LaTeX}$ and $\mathcal{L}_{sTeX}$ are not disjoint

5 DATASETS

We, therefore, have two datasets of sTeX-content:

1. The SMGLoM[3], which introduces precisely those macros that we want to be learned by an NMT-model, but references most of them only once, and
2. The MiKoMH[4]-repository of lecture notes, which is heavily biased towards computer science topics.

To obtain a parallel corpus for supervised learning, we take the individual LaTeX-files in those repositories and do the following:

1. We separate the documents into small fragments of (on average) 500 character lengths, which we will call *sentences* in the sequel. Symbolic expressions occur preferably at the end of a sentence, based on the assumption that preceding text provides a more meaningful context. Sentences that do not contain symbolic expressions are ignored.
2. In each sentence $S = S_{\text{sTeX}} \in \mathcal{L}_{\text{sTeX}}$, we perform some standardization function which e.g. removes non-semantic macros and ensures that macro arguments are always braced, in order to minimize author bias,
3. We extract all symbolic expressions $(m_{\text{sTeX},i})_{i \leq n_S}$ in S and expand all sTeX macros in them, resulting in $(m_{\text{LaTeX},i})_{i \leq n_S}$ (where n_S is the number of symbolic expressions in S). Analogously, we expand all sTeX macros in S itself, yielding $S_{\text{LaTeX}} \in \mathcal{L}_{\text{LaTeX}}$.

Each entry in our dataset then consists of a 4-tuple $(S_{\text{LaTeX}}, S_{\text{sTeX}}, (m_{\text{LaTeX},i})_{i \leq n_S}, (m_{\text{sTeX},i})_{i \leq n_S})$. In total, we obtain 911 entries from SMGLoM and 9200 entries from MiKoMH.

Synthesizing Training Data   In order to augment our datasets for supervised learning, we opted to exploit the MMT integration to synthesize additional training data.

For that, we aligned SMGLoM symbols with declarations in a strongly typed MMT archive; namely the *Math-in-the-Middle (MitM)* library Müller (2019). This allows us to randomly generate well-typed (and hence syntactically well-formed) terms in a typed setting, translate these along alignments to sTeX expressions and subsequently generate surrounding verbalizations.

The generating algorithm takes as input a set of symbols Sym (e.g. all MitM-symbols for which an alignment to SMGLoM exists) and a starting symbol $s \in$ Sym (e.g. `nattimes`; binary multiplication on natural numbers). It returns a random well-typed formal expression t which is guaranteed to contain s. Afterwards, it is *verbalized* as an sTeX sentence using natural language fragments (a detailled description of the algorithm is given in Appendix A).

The synthesized sTeX sentences are then treated as above to augment our parallel training corpus.

As an **evaluation dataset**, we developed sTeX documents based on selected fragments of introductory sections from mathematics lecture notes; primarily containing basics such as set operations, number spaces, examples for proofs by induction, basic combinatorics and definitions of common algebraic structures, containing 161 symbolic expressions in total. Of the ≈ 100 SMGLoM symbols used therein, 92 were aligned with corresponding symbols in the MitM library and used as input symbols for synthesizing sentences; with 250 sentences per starting symbol (as to not drown out the non-synthesized sentences), yielding 23,000 additional sentences.

Unlike the training datasets, the evaluation document was translated to plain LaTeX manually using the PDF as a reference, in order to avoid possible spurious patterns in automatically expanded sTeX.

6 METHODOLOGY

Initial experiments using standard, dedicated NMT models with full sentences as input/output quickly proved to be ineffective due to the size of the training corpus, which was too small to cause these

---

[3] `https://gl.mathhub.info/smglom`
[4] `https://gl.mathhub.info/MiKoMH`

models to even generate syntactically correct LaTeX (e.g. knowing to balance pairs of brackets) before overfitting on the training data.

Transformer language models (e.g. Devlin et al. (2018); Liu et al. (2019); Radford (2018); Radford et al. (2019); Clark et al. (2020)) allow us to leverage huge available corpora of plain LaTeX documents to train a model to "understand" both basic LaTeX syntax and mathematical terminology. Using those, we consequently do not need to rely on our small dataset for this base-level understanding. We can then approach learning sTEX annotations as a downstream task on a pre-trained transformer model. Consequently, we pre-trained a GPT2 Radford et al. (2019) model on a large portion of available LaTeX sources of scientific papers from the preprint repository `arxiv.org` (6,673,950 entries of length 1,024 tokens). The model was trained *from scratch* in order to use a dedicated tokenizer trained on LaTeX directly (byte-level tokenizer; vocabulary size 32,000) rather than natural language alone.

In order to leverage the pretrained model for both source and target language[5], we subsequently opted to fine-tune the GPT2-model on inputs of the form

$$S_{\text{LaTeX}} \; \texttt{} \; m_{\text{LaTeX}} \; \texttt{} \; m_{\text{sTEX}} \; \texttt{},$$

where `` a single-token separator.[6] For example, for Figure 1 the training data contains fragments (normalized) such as:

```
Multiplication $\cdot$ computes the product $a\cdot b$ (also written as
        $ab$ or $a\times b$) of natural numbers $a$ and $b$.
             $a\cdot b$  $\nattimes[cdot]{a,b}$ 
```

We then use text generation on inputs of the form $S_{\text{LaTeX}} \; \texttt{} \; m_{\text{LaTeX}} \; \texttt{}$ for translating and stop generating after encountering ``.

By using one entry per symbolic expression, we obtain a dataset of 121,368 examples. The GPT2-model was finetuned on these for five epochs, resulting in an average training loss of 0.04 and yielding promising results on the evaluation set (see below). This approach has the following advantages:

1. It allows for using large datasets of generic LaTeX documents to learn basic syntactic rules and semantics of mathematical expressions beyond our small sTEX datasets.

2. We conjecture that this approach makes the model less sensitive to spurious patterns in the synthesized part of our dataset.

3. Adding new symbols to the SMGLoM and aligning them to (new or existent) symbols in the MitM library allows for immediately synthesizing training data, obviating the need to first obtain large amounts of data *using* the new symbol before the model can learn to use it.

4. The mere pretrained GPT2 model can be trained on *additional* downstream tasks, e.g. introducing macros for referencing mathematical concepts in natural language fragments.

7 Evaluation and Results

The traditional evaluation metrics (loss during evaluation, perplexity, BLEU) are somewhat difficult and/or meaningless to apply in our situation, since 1. the returned tokens and provided label tokens might differ in semantically irrelevant ways (e.g. `$a+b$` vs. `$a + b$`), and 2. loss/perplexity would be evaluated during a forward pass in a next token prediction task on a token-by-token basis, which would retroactively "correct" errors in prediction that would otherwise yield completely wrong result.

Consequently, we opted for a plurality of evaluation strategies. Let S_F the returned sentence of our model on an input S_{LaTeX} with correct label S_{sTEX}. Then on our evaluation set we get

1. $S_F \in \mathcal{L}$ for 96.9% of inputs

2. $S_{\text{LaTeX}} \in \text{LaTeX}(S_F)$ for 64.0% of inputs,

3. $S_F \in \mathcal{L}_{\text{sTEX}}$ for 60.2% of inputs, and

4. $S_F = S_{\text{sTEX}}$ for 47.2% of inputs.

---

[5]Initial experiment with the pretrained model as encoder component only showed improvements over randomly initialized encoder-decoder-models, but ultimately proved unsuitable still due to the small dataset size.

[6]inspired by `http://jalammar.github.io/illustrated-gpt2/#part-3-beyond-language-modeling`

In comparison, using traditional NMT models auch as Luong et al. (2017); Vaswani et al. (2017) we effectively obtained 0% success rates for all of the above. Additional evaluation techniques exploiting the MMT integration are described in Appendix B.

S_{LaTeX}:	`\mathbb{N}=\{0,1,2,3,\ldots\}`
S_{sTeX}:	`\eq{\NaturalNumbers,\setdots{0,1,2,3}}`
S_F:	`\NaturalNumbers=\set{0,1,2,3}`
S_{LaTeX}:	`(A \subseteq B)\Leftrightarrow(\forall x\in A. x\in B)`
S_{sTeX}:	`\biimpl{\sseteq{A}{B}}{\foral{\inset{x}{A}}{\inset{x}{B}}}`
S_F:	`\biimpl{\sseteq{A}{B}}{\foral{x}{A}\inset{x}{B}}}`
S_{LaTeX}:	`\mathcal{P}(A):=\{x|x\subseteq A\}`
S_{sTeX}:	`\defeq{\powerset{A}}{\setst{x}{\sseteq{x}{A}}}`
S_F:	`\defeq{\powerset{A}}{\bsetst{x}{x}{\sset{x}{x} A}}`
S_{LaTeX}:	`1+2+3+4+5=(5\cdot6)/2=15`
S_{sTeX}:	`\eq{\natplus{1,2,3,4,5},\natdiv[slash]{\nattimes[cdot]`
`{5,6}}{2},15}`
S_F:	`\natplus{1,2,3,4,5}=\natdiv[slash]{\natplus{\nattimes[cdot]`
`{5,6},4,5}}{2}=15`

Figure 2: Example Inputs and Outputs from our Evaluation Set

Figure 2 shows a few examples where our model "failed" in interesting ways. As the first and fourth examples show, the model seems to consistently fail to replace "=" by the intended macro `\eq` – a failure that LaTeXML can recover when converting to OMDOC, but also regularly occurs in the training data. Similarly, `\ldots` often leads to wrong translations: The first example shows that the model simply dropped `\ldots`, using a generic set constructor macro `\set` rather than `\setdots`, the one specifically intended for sets ending in ellipses.

In the second example, the model seems to introduce a nonsensical additional argument for the `\foral` macro. Notably, the expression $\forall x \in A.P$ can also be achieved using the dedicated macro `\foralS{x}{A}{P}`. Seemingly, the model chose the macro `\foral`, and the arguments for the `\foralS` macro, yielding a wrong translation that generates a wrong pdf output, while being "semantically almost correct".

In the third example, the model confuses the macro `\setst` (for set comprehension) with a more complex macro `\bsetst` (for set comprehension with a complex pattern on the left side). Additionally, it confuses `\sseteq` (for inclusive subsets $x \subseteq A$) with `\sset` (for generic subsets $x \subset A$), duplicating the first argument and moving the *intended* argument `A` outside the scope of the macro.

Example four is interesting in that the model correctly identifies the arithmetic operations as those on the natural numbers, but spuriously inserts an additive term `\natplus{...,4,5}`; this is likely an artifact from the left-hand side of the equation. Interestingly, these kinds of artifacts occur more than ones in our evaluation set.

8 CONCLUSION

We have proposed the task of disambiguating symbolic expressions in informal STEM documents, and defined this task formally. This allows for annotating informal documents semantically, and further processing them using tools that support such annotated documents (e.g. MMT). We discussed the specificity of this task and what separates this task from other NMT problems. We developed a dataset for this task and presented an approach that yields promising results, especially in light of the size of the dataset. In particular, the presented approach points to the efficacy of using transformer models pretrained on generic LaTeX documents.

In the future, we plan to combine the proposed symbolic disambiguation approach with an auto-formalization framework. This way we aim to achieve better results for end-to-end formalization of informal mathematical documents. Furthermore, more promising results for the currently proposed task could be obtained by reintegrating the proposed models into an encoder-decoder NMT model.

REFERENCES

Noriko H. Arai, Takuya Matsuzaki, Hidenao Iwane, and Hirokazu Anai. Mathematics by machine. In *Proceedings of the 39th International Symposium on Symbolic and Algebraic Computation*, ISSAC '14, pp. 1–8, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2501-1. doi: 10.1145/2608628. 2627488. URL http://doi.acm.org/10.1145/2608628.2627488.

Grzegorz Bancerek, Czeslaw Bylinski, Adam Grabowski, Artur Kornilowicz, Roman Matuszewski, Adam Naumowicz, and Karol Pak. The role of the mizar mathematical library for interactive proof development in mizar. *J. Autom. Reasoning*, 61(1-4):9–32, 2018. doi: 10.1007/s10817-017-9440-6. URL https://doi.org/10.1007/s10817-017-9440-6.

S. Buswell, O. Caprotti, D. Carlisle, M. Dewar, M. Gaetano, and M. Kohlhase. The Open Math Standard, Version 2.0. Technical report, The Open Math Society, 2004. See http://www.openmath.org/standard/om20.

Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. ELECTRA: pre-training text encoders as discriminators rather than generators. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=r1xMH1BtvB.

Joe Corneli and Moritz Schubotz. math.wikipedia.org: A vision for a collaborative semi-formal, language independent math(s) encyclopedia. In *AITP 2017. The Second Conference on Artificial Intelligence and Theorem Proving*, pp. 28–31. 2017.

Paul-Olivier Dehaye, Mihnea Iancu, Michael Kohlhase, Alexander Konovalov, Samuel Lelièvre, Dennis Müller, Markus Pfeiffer, Florian Rabe, Nicolas M. Thiéry, and Tom Wiesing. Interoperability in the OpenDreamKit project: The math-in-the-middle approach. In Michael Kohlhase, Moa Johansson, Bruce Miller, Leonardo de Moura, and Frank Tompa (eds.), *Intelligent Computer Mathematics 2016*, number 9791 in LNAI. Springer, 2016. ISBN 978-3-319-08434-3. URL https://github.com/OpenDreamKit/OpenDreamKit/blob/master/WP6/CICM2016/published.pdf.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018. URL http://arxiv.org/abs/1810.04805.

Wenbin Gan and Xinguo Yu. Automatic understanding and formalization of natural language geometry problems using syntax-semantics models. 2017. doi: 10.24507/ijicic.14.01.83. URL http://www.ijicic.org/ijicic-140106.pdf.

Herman Geuvers, Matthew England, Osman Hasan, Florian Rabe, and Olaf Teschke (eds.). *Intelligent Computer Mathematics*, number 10383 in LNAI, 2017. Springer. ISBN 978-3-319-62074-9. doi: 10.1007/978-3-319-62075-6.

Deyan Ginev, Heinrich Stamerjohanns, Bruce R. Miller, and Michael Kohlhase. The latexml daemon: Editable math on the collaborative web. In James H. Davenport, William M. Farmer, Josef Urban, and Florian Rabe (eds.), *Intelligent Computer Mathematics - 18th Symposium, Calculemus 2011, and 10th International Conference, MKM 2011, Bertinoro, Italy, July 18-23, 2011. Proceedings*, volume 6824 of *Lecture Notes in Computer Science*, pp. 292–294. Springer, 2011. doi: 10.1007/978-3-642-22673-1_25. URL https://doi.org/10.1007/978-3-642-22673-1_25.

Lisa Grossman. Metric math mistake muffed mars meteorology mission. https://www.wired.com/2010/11/1110mars-climate-observer-report/.

Thomas C. Hales, Mark Adams, Gertrud Bauer, Dat Tat Dang, John Harrison, Truong Le Hoang, Cezary Kaliszyk, Victor Magron, Sean McLaughlin, Thang Tat Nguyen, Truong Quang Nguyen, Tobias Nipkow, Steven Obua, Joseph Pleso, Jason M. Rute, Alexey Solovyev, An Hoai Thi Ta, Trung Nam Tran, Diep Thi Trieu, Josef Urban, Ky Khac Vu, and Roland Zumkeller. A formal proof of the Kepler conjecture. *Forum of Mathematics, Pi*, 5, 2017. doi: 10.1017/fmp.2017.1.

J. Harrison. HOL Light: A Tutorial Introduction. In *Proceedings of the First International Conference on Formal Methods in Computer-Aided Design*, pp. 265–269. Springer, 1996.

J. Harrison. Formal verification at Intel. In *18th Annual IEEE Symposium of Logic in Computer Science, 2003. Proceedings.*, pp. 45–54, June 2003. doi: 10.1109/LICS.2003.1210044.

John Harrison, Josef Urban, and Freek Wiedijk. History of interactive theorem proving. In Jörg H. Siekmann (ed.), *Computational Logic*, volume 9 of *Handbook of the History of Logic*, pp. 135–214. Elsevier, 2014. doi: 10.1016/B978-0-444-51624-4.50004-6. URL https://doi.org/10.1016/B978-0-444-51624-4.50004-6.

F. Horozal, M. Kohlhase, and F. Rabe. Extending MKM Formats at the Statement Level. In J. Campbell, J. Carette, G. Dos Reis, J. Jeuring, P. Sojka, V. Sorge, and M. Wenzel (eds.), *Intelligent Computer Mathematics*, pp. 64–79. Springer, 2012.

Danqing Huang, Jing Liu, Chin-Yew Lin, and Jian Yin. Neural math word problem solver with reinforcement learning. In *Proceedings of the 27th International Conference on Computational Linguistics*, pp. 213–223, Santa Fe, New Mexico, USA, August 2018. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/C18-1018.

Mihnea Iancu. *Towards Flexiformal Mathematics*. PhD thesis, Jacobs University, Bremen, Germany, 2017. URL https://opus.jacobs-university.de/frontdoor/index/index/docId/721.

JFM. Journal of formalized mathematics. http://www.mizar.org/JFM.

Cezary Kaliszyk and Florian Rabe. A survey of languages for formalizing mathematics, 2020. URL https://arxiv.org/abs/2005.12876.

Cezary Kaliszyk, Josef Urban, Jiří Vyskočil, and Herman Geuvers. Developing corpus-based translation methods between informal and formal mathematics: Project description. In Stephen M. Watt, James H. Davenport, Alan P. Sexton, Petr Sojka, and Josef Urban (eds.), *Intelligent Computer Mathematics*, pp. 435–439, Cham, 2014. Springer International Publishing. ISBN 978-3-319-08434-3.

Cezary Kaliszyk, Josef Urban, and Jiří Vyskočil. Learning to parse on aligned corpora (rough diamond). In Christian Urban and Xingyuan Zhang (eds.), *Interactive Theorem Proving*, pp. 227–233, Cham, 2015. Springer International Publishing. ISBN 978-3-319-22102-1.

Cezary Kaliszyk, Josef Urban, and Jirí Vyskocil. System description: Statistical parsing of informalized Mizar formulas. 2017a. doi: 10.1109/synasc.2017.00036.

Cezary Kaliszyk, Josef Urban, and Jiří Vyskočil. Automating formalization by statistical and semantic parsing of mathematics. In Mauricio Ayala-Rincón and César A. Muñoz (eds.), *Interactive Theorem Proving*, pp. 12–27, Cham, 2017b. Springer International Publishing. ISBN 978-3-319-66107-0.

M. Kohlhase. *OMDoc: An Open Markup Format for Mathematical Documents (Version 1.2)*. Number 4180 in Lecture Notes in Artificial Intelligence. Springer, 2006.

M. Kohlhase. Using LaTeX as a Semantic Markup Format. *Mathematics in Computer Science*, 2(2): 279–304, 2008.

Michael Kohlhase. The flexiformalist manifesto. In Andrei Voronkov, Viorel Negru, Tetsuo Ida, Tudor Jebelean, Dana Petcu, Stephen M. Watt, and Daniela Zaharie (eds.), *14th International Workshop on Symbolic and Numeric Algorithms for Scientific Computing (SYNASC 2012)*, pp. 30–36, Timisoara, Romania, 2013. IEEE Press. ISBN 978-1-4673-5026-6. URL http://kwarc.info/kohlhase/papers/synasc13.pdf.

Michael Kohlhase. A data model and encoding for a semantic, multilingual terminology of mathematics. In Stephan Watt, James Davenport, Alan Sexton, Petr Sojka, and Josef Urban (eds.), *Intelligent Computer Mathematics 2014*, number 8543 in LNCS, pp. 169–183. Springer, 2014. ISBN 978-3-319-08433-6. URL http://kwarc.info/kohlhase/papers/cicm14-smglom.pdf.

Michael Kohlhase and Florian Rabe. Experiences from exporting major proof assistant libraries. 2020. URL https://kwarc.info/people/frabe/Research/KR_oafexp_20.pdf.

Michael Kohlhase, Thomas Koprucki, Dennis Müller, and Karsten Tabelow. Mathematical models as research data via flexiformal theory graphs. In Geuvers et al. (2017). ISBN 978-3-319-62074-9. doi: 10.1007/978-3-319-62075-6. URL http://kwarc.info/kohlhase/papers/cicm17-models.pdf.

Michael Kohlhase, Dennis Müller, Sam Owre, and Florian Rabe. Making PVS accessible to generic services by interpretation in a universal format. In Mauricio Ayala-Rincón and César A. Muñoz (eds.), *Interactive Theorem Proving*, volume 10499 of *LNCS*. Springer, 2017b. ISBN 978-3-319-66107-0. URL http://kwarc.info/kohlhase/submit/itp17-pvs.pdf.

Guillaume Lample and François Charton. Deep learning for symbolic mathematics, 2019.

Christoph Lange. *Enabling Collaboration on Semiformal Mathematical Knowledge by Semantic Web Integration*. PhD thesis, Jacobs University Bremen, 2011a. URL https://svn.kwarc.info/repos/swim/doc/phd/phd.pdf. Also available as a book Lange (2011b).

Christoph Lange. *Enabling Collaboration on Semiformal Mathematical Knowledge by Semantic Web Integration*. Number 11 in Studies on the Semantic Web. AKA Verlag and IOS Press, Heidelberg and Amsterdam, 2011b. ISBN 978-1-60750-840-3. URL http://www.semantic-web-studies.net.

Tomer Libal and Alexander Steen. Towards an executable methodology for the formalization of legal texts. In Mehdi Dastani, Huimin Dong, and Leon van der Torre (eds.), *Logic and Argumentation - Third International Conference, CLAR 2020, Hangzhou, China, April 6-9, 2020, Proceedings*, volume 12061 of *Lecture Notes in Computer Science*, pp. 151–165. Springer, 2020. doi: 10.1007/978-3-030-44638-3_10. URL https://doi.org/10.1007/978-3-030-44638-3_10.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692, 2019. URL http://arxiv.org/abs/1907.11692.

Minh-Thang Luong, Eugene Brevdo, and Rui Zhao. Neural machine translation (seq2seq) tutorial. *https://github.com/tensorflow/nmt*, 2017.

Takuya Matsuzaki, Hidenao Iwane, Hirokazu Anai, and Noriko H. Arai. The most uncreative examinee: A first step toward wide coverage natural language math problem solving. In *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, AAAI'14, pp. 1098–1104. AAAI Press, 2014. URL http://dl.acm.org/citation.cfm?id=2893873.2894044.

Takuya Matsuzaki, Takumi Ito, Hidenao Iwane, Hirokazu Anai, and Noriko H. Arai. Semantic parsing of pre-university math problems. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2131–2141, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1195. URL https://www.aclweb.org/anthology/P17-1195.

Takuya Matsuzaki, Hidenao Iwane, Munehiro Kobayashi, Yiyang Zhan, Ryoya Fukasaku, Jumma Kudo, Hirokazu Anai, and Noriko H. Arai. Can an a.i. win a medal in the mathematical olympiad? - benchmarking mechanized mathematics on pre-university problems. *AI Commun.*, 31:251–266, 2018.

Mizar. Mizar. http://www.mizar.org, 1973–2006. URL http://www.mizar.org.

Dennis Müller. *Mathematical Knowledge Management Across Formal Libraries*. PhD thesis, Informatics, FAU Erlangen-Nürnberg, 10 2019. URL https://kwarc.info/people/dmueller/pubs/thesis.pdf.

Dennis Müller, Thibault Gauthier, Cezary Kaliszyk, Michael Kohlhase, and Florian Rabe. Classification of alignments between concepts of formal mathematical systems. In Geuvers et al. (2017). ISBN 978-3-319-62074-9. doi: 10.1007/978-3-319-62075-6. URL http://kwarc.info/kohlhase/papers/cicm17-alignments.pdf.

Dennis Müller, Florian Rabe, and Claudio Sacerdoti Coen. The Coq Library as a Theory Graph. accepted at CICM 2019, 2019.

F. Rabe and M. Kohlhase. A Scalable Module System. *Information and Computation*, 230(1):1–54, 2013.

Florian Rabe. How to Identify, Translate, and Combine Logics? *Journal of Logic and Computation*, 27(6):1753–1798, 2017.

Alec Radford. Improving language understanding by generative pre-training. 2018. URL `https://www.semanticscholar.org/paper/Improving-Language-Understanding-by-Generative-Radford/cd18800a0fe0b668a1cc19f2ec95b5003d0a5035`.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.

David Saxton, Edward Grefenstette, Felix Hill, and Pushmeet Kohli. Analysing mathematical reasoning abilities of neural models. *CoRR*, abs/1904.01557, 2019. URL `http://arxiv.org/abs/1904.01557`.

Minjoon Seo, Hannaneh Hajishirzi, Ali Farhadi, Oren Etzioni, and Clint Malcolm. Solving geometry problems: Combining text and diagram interpretation. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 1466–1476, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1171. URL `https://www.aclweb.org/anthology/D15-1171`.

Ron Solomon. On finite simple groups and their classification. *Notices of the AMS*, pp. 231–239, February 1995.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *CoRR*, abs/1706.03762, 2017. URL `http://arxiv.org/abs/1706.03762`.

Qingxiang Wang, Cezary Kaliszyk, and Josef Urban. First experiments with neural translation of informal to formal mathematics. *CoRR*, abs/1805.06502, 2018. URL `http://arxiv.org/abs/1805.06502`.

Qingxiang Wang, Chad E. Brown, Cezary Kaliszyk, and Josef Urban. Exploration of neural machine translation in autoformalization of mathematics in Mizar. In Jasmin Blanchette and Catalin Hritcu (eds.), *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs, CPP 2020, New Orleans, LA, USA, January 20-21, 2020*, pp. 85–98. ACM, 2020. doi: 10.1145/3372885.3373827. URL `https://doi.org/10.1145/3372885.3373827`.

Yan Wang, Xiaojiang Liu, and Shuming Shi. Deep neural solver for math word problems. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 845–854, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1088. URL `https://www.aclweb.org/anthology/D17-1088`.