On Robust Multiclass Learnability

Abstract

This work analyzes the robust learning problem in the multiclass setting. Under the framework of Probably Approximately Correct (PAC) learning, we first show that the graph dimension and the Natarajan dimension, which characterize the standard multiclass learnability, are no longer applicable in robust learning problem. We then generalize these notions to the robust learning setting, denoted as the adversarial graph dimension (AG-dimension) and the adversarial Natarajan dimension (AN-dimension). Upper and lower bounds of the sample complexity of robust multiclass learning are rigorously derived based on the AG-dimension and AN-dimension, respectively. Moreover, we calculate the AG-dimension and AN-dimension of the class of linear multiclass predictors, and show that the graph (Natarajan) dimension is of the same order as the AG(AN)-dimension. Finally, we prove that the AG-dimension and AN-dimension are not equivalent.

1 Introduction

Learning models that are robust to adversarial perturbations has attracted significant research attention in recent years. Notably, prior work on this subject has largely studied the theory of robust learnability in the context of binary supervised learning. However, many important problems require classification into a great number of target classes. For example, in image object recognition and language models building[1, 2], the number of classes scales as the number of possible objects or the dictionary size respectively. It is thus of both practical and theoretical interest to generalize the robust binary learning theory to the robust multiclass setting.

In the standard multiclass learning setting, the finiteness of the Natarajan dimension or graph dimension [3] (both of which are generalized from the VC-dimension [4]) is necessary and sufficient to ensure learnability [5]. Recent work has shown that the finiteness of the VC-dimension is neither sufficient nor necessary for (proper) robust binary classification [6]. Inspired by [6], this paper demonstrates that the Natarajan/graph dimension can no longer characterize robust learnability in the multiclass problem. Meanwhile, some questions naturally arise: In multiclass setting, how can robust learning be ensured? And what is necessary for robust learning?

To answer these questions, we generalize the corrupted hypothesis classes [7], which arise from standard hypothesis classes in the binary setting in the presence of an adversary, and use them to reduce the robust learning problem to a non-robust one. By considering the graph dimension and Natarajan dimension of the corrupted hypothesis classes—which are defined as the adversarial graph dimension (AG-dimension) and adversarial Natarajan dimension (AN-dimension) respectively—we derive the upper and lower bounds of sample complexity of the robust multiclass learning problem. We then analyze the AG-dimension and the AN-dimension of linear multiclass predictor class, showing that the AG(AN)-dimension and the graph (Natarajan) dimension are of the same order.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Since it is proven that the graph dimension and the Natarajan dimension are equivalent when the target class is finite [5], is it possible to use the AG-dimension and AN-dimension to bound each other? Our work suggests that the equivalent relationship does not hold, which is illustrated by constructing a hypothesis class with finite AN-dimension but not robustly learnable.

1.1 Overview of techniques

Our Theorems 3 and 5, stating that the finiteness of graph dimension is not sufficient and the finiteness of Natarajan dimension is not necessary for robust learning, respectively, are demonstrated by constructing counter examples. The arguments follow closely the proofs of analogous results but generalize the constructions and analyzes to match the definition of graph/Natarajan dimension in the multiclass setting.

Our main results, namely Theorems 4 and 6, are high probability bounds of sample complexity that are sufficient/necessary for robust PAC learning, respectively. Compared to standard PAC learning, robust PAC learning is mainly different in the definition of loss function, which considers the maximum of 0-1 loss over a perturbation set. Thus to prove these bounds, we need to design a way that takes the disturbance set into account to control the adversarial risk in a high probability. [7] presents the notion of corrupted hypothesis class and use it to derive an upper bound for binary robust learning by considering the VC-dimension of the corrupted hypothesis class. This approach shed some light on our work. However, generalizing to multiclass setting in this way faces some difficulties, since there are quite a few definitions that can be generalized to multiclass setting, e.g. corrupted hypothesis class, shattering coefficient and VC-dimension in the context of adversarial setting. To make it more natural, we define the corrupted hypothesis class in multiclass setting, which does not involve fixed label patterns, and then study the graph/Natarajan dimension of a corrupted hypothesis class. For clarity, we analytically abstract these definitions as the AG/AN-dimension of hypothesis class, making it get rid of the notion of corrupted hypothesis class. There are some beneficial efforts by defining in this way: one is to intuitively correspond the graph/Natarajan dimension to the AG/AN-dimension, as well as the bounds derived by these notions. Another benefit is to make it possible to transfer common multiclass proof techniques to adversarial setting, namely constructing auxiliary binary classification problems and using them to control the risk we focus on.

Theorems 7 and 8 give bounds of AG/AN-dimension for linear multiclass predictors $\mathcal{H}_\Psi$. To show these results, we need to prove two non-trivial bounds, namely the upper bound of AG-dimension and the lower bound of AN-dimension. For the upper bound, we gain our construction idea from [8], which calculates the graph dimension of multiclass SVM. Yet their proof make use of Sauer's Lemma [9], which is only applicable for standard setting. To fill this gap, we present Lemma 2 - the generalization of Sauer's Lemma in adversarial setting - showing that the growth function in the context of adversarial and multiclass setting, which is defined very finely, also increases polynomially as the number of samples $m > d_G^{\mathcal{U}} + 1$, where $d_G^{\mathcal{U}}$ is the AG-dimension of some hypothesis class. As for the lower bound, we claim that for linear classifiers, its AN-dimension equals to its Natarajan dimension. We demonstrate this by geometric analysis, which makes use of the linearity of predictors in $\mathcal{H}_\Psi$.

We prove Theorem 9 by constructing a novel counter example to show the finiteness of AN-dimension is not sufficient for robust multiclass learning, which reveals that the AG-dimension and AN-dimension are not equivalent.

1.2 Related work

[10, 11, 12, 13] focus on the robust binary classification problem. [3] characterize the multiclass learnability in non-robust setting. [14, 5, 15] define a large family of notions of dimensions, all of which generalize the VC-dimension and may be used to estimate the sample complexity of multiclass classification. [8] calculate the graph dimension and the Natarajan dimension of linear multiclass predictor class. [16] upper bounds the adversarial risk of linear multiclass classifiers based on Rademacher complexity, which cannot directly derive bounds of sample complexity of general robust

multiclass learning problems. The theory on robust multiclass learnability for general hypothesis class is less explored. This work takes some steps towards solving this problem.

2 Preliminaries

This section introduces some basic notations and concepts used throughout the present study.

In the remainder of this article, $\mathbb{R}, \mathbb{N}, \mathbb{R}^+$ and $\mathbb{R}^d$ represent the sets of real numbers, natural numbers, non-negative real numbers and d-dimensional vectors over $\mathbb{R}$, respectively. We denote the set $\{1, \ldots, n\}$ (for $n \in \mathbb{N}$) by $[n]$. If A and B are sets, we use B^A to denote the collection of all mappings from A to B and 2^A to denote the power set of A, that is the collection of all subsets of A. Let $C = \{c_1, \ldots, c_m\} \subset \mathcal{X}$ and $C' \subset C$ be a subset of C, then $I_{C'} \in [m]$ denotes the index set of C'. Let $\mathcal{H}$ be a class of functions defined in $\mathcal{X}$, then $\mathcal{H}|_C$ represents the restriction of $\mathcal{H}$ to C, that is $\mathcal{H}_C = \{(h(c_1), \ldots, h(c_m)) : h \in \mathcal{H}\}$. We denote the indicator function by $\mathbb{1}(\text{event})$, that is 1 if an event happens and 0 otherwise. Finally, $\|\cdot\|_p$ represents the ℓ_p norm.

The *robust learning* problem is formalized as follows. Let $\mathcal{X} = \mathbb{R}^d$ be the instance space and $\mathcal{Y} = \{1, \ldots, k\}$ be the label space. For an unknown distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$[1] and a hypothesis class $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$, the goal of robust learning is to find a function $f \in \mathcal{H}$, based on n labeled training samples $S = \{(x_i, y_i)\}_{i=1}^n$ drawn independent and identically distributed (i.i.d.) from $\mathcal{D}$, such that under a small perturbation $\mathcal{U} : \mathcal{X} \to 2^{\mathcal{X}}$, the *adversarial risk*

$$R_{\mathcal{U}}(f; \mathcal{D}) \triangleq \mathbb{E}_{(x,y) \sim \mathcal{D}} \left[\sup_{x' \in \mathcal{U}(x)} l(f(x'), y) \right]$$

is minimal for the 0-1 loss $l(\hat{y}, y) \triangleq \mathbb{1}(\hat{y} \neq y)$.

The perturbation $\mathcal{U}(x)$ is required to be nonempty, so some choice of x' is always available. One choice for the perturbation is the p-norm ball ($p \geq 1$) with a small radius r, i.e. $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \leq r\}$. Selecting $r = 0$ gives the *identity perturbation*: $\mathcal{I}(x) \triangleq \{x\}$. Note that in this case, the problem is reduced to a standard learning problem, and $R_{\mathcal{I}}(f; \mathcal{D})$ is called the *standard risk* of f over $\mathcal{D}$.

The mechanism of finding a function is called a *learning algorithm*. In this paper, we focus on *proper* learning algorithms, that is, learning algorithms will always pick a function from $\mathcal{H}$. Formally, a learning algorithm is a function $\mathcal{A} : \cup_{n=0}^{\infty} (\mathcal{X} \to \mathcal{Y})^n \to \mathcal{H}$. A common choice of robust learning algorithm is to learn through *adversarial empirical risk minimization* or AERM for short:

$$\hat{f} \in \text{AERM}_{\mathcal{U}}(\mathcal{H}; S) \triangleq \underset{f \in \mathcal{H}}{\arg \min} \, R_{\mathcal{U}}(f; \hat{\mathcal{D}}_n),$$

where $\hat{\mathcal{D}}_n$ is the *empirical distribution* generated by S, i.e. for $(x, y) \sim \hat{\mathcal{D}}_n$, (x, y) is equal to (x_i, y_i) with probability $1/n$ for each $i \in \{1, \ldots, n\}$.

Learning algorithms like AERM do not always produce a function that achieves the optimal adversarial risk, because a training set consisting of finite samples is not always sufficiently informative to represent $\mathcal{D}$. Thus, we introduce the definition of robust probably approximately correct (PAC) learnability, in the realizable and agnostic setting [7, 6]:

Definition 1 (Agnostic Robust PAC Learnability). *Under perturbation $\mathcal{U}$, a hypothesis class $\mathcal{H}$ is robustly PAC learnable in the agnostic setting if there is a function $m_{\mathcal{H}, \mathcal{U}}^{ag} : (0, 1)^2 \to \mathbb{N}$ and a learning algorithm $\mathcal{A} : \cup_{n=0}^{\infty} (\mathcal{X} \times \mathcal{Y})^n \to \mathcal{H}$ with the following property. For every $\epsilon, \delta \in (0, 1)$ and every distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$, let $S = \{(x_i, y_i)\}_{i=1}^n$ be n samples i.i.d generated by $\mathcal{D}$ s.t. $n > m_{\mathcal{H}, \mathcal{U}}^{ag}(\epsilon, \delta)$. Then with probability at least $1 - \delta$,*

$$R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \leq \min_{f \in \mathcal{H}} R_{\mathcal{U}}(f; \mathcal{D}) + \epsilon.$$

The function $m_{\mathcal{H}, \mathcal{U}}^{ag}$ is defined as the sample complexity of learning $\mathcal{H}$ under perturbation $\mathcal{U}$ in the agnostic setting.

---

[1]Formally, there is a sigma algebra $\mathcal{F} \subset 2^{\mathcal{X} \times \mathcal{Y}}$ of events and $\mathcal{D}$ is a probability measure on $(\mathcal{X} \times \mathcal{Y}, \mathcal{F})$.

125 **Definition 2** (Realizable Robust PAC Learnability). *Under perturbation $\mathcal{U}$, a hypothesis class $\mathcal{H}$*
126 *is robustly PAC learnable in the realizable setting if there is a function $m^{re}_{\mathcal{H},\mathcal{U}} : (0,1)^2 \to \mathbb{N}$ and a*
127 *learning algorithm $\mathcal{A} : \cup_{n=0}^{\infty}(\mathcal{X} \times \mathcal{Y})^n \to \mathcal{H}$ with the following property. For every $\epsilon, \delta \in (0,1)$*
128 *and every distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$, let $S = \{(x_i, y_i)\}_{i=1}^n$ be n samples i.i.d generated by $\mathcal{D}$ s.t.*
129 *$n > m^{re}_{\mathcal{H},\mathcal{U}}(\epsilon, \delta)$. Then with probability at least $1 - \delta$,*

$$R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \le \epsilon.$$

130 *The function $m^{re}_{\mathcal{H},\mathcal{U}}$ is defined as the sample complexity of learning $\mathcal{H}$ under perturbation $\mathcal{U}$ in the*
131 *realizable setting.*

132 These definitions agree with the standard PAC learnability when $\mathcal{U} = \mathcal{I}$, which has been widely
133 studied in both *binary* ($k = 2$) and *multiclass* ($k > 2$) setting. We recall the known result regarding
134 the sample complexity of binary learning. Recall the definition of the Vapnik-Chervonenkis dimension
135 (VC-dimension) [4]:

136 **Definition 3** (VC-dimension). *Let $\mathcal{H} \subset \{0,1\}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that S*
137 *is shattered by $\mathcal{H}$ if $\mathcal{H}|_S = \{0,1\}^S$. The VC-dimension of $\mathcal{H}$, denoted by $\mathrm{VC}\,(\mathcal{H})$, is the maximal*
138 *cardinality of a set that is shattered by $\mathcal{H}$.*

139 The following theorem, based on the VC-dimension, characterizes the sample complexity of learning
140 *binary* hypothesis classes.

141 **Theorem 1** ([4] and [17]). *There are absolute constants $C_1, C_2 > 0$ such that for every $\mathcal{H} \subset \{0,1\}^{\mathcal{X}}$,*

$$C_1\left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon}\right) \le m^{re}_{\mathcal{H},\mathcal{I}}(\epsilon, \delta) \le C_2\left(\frac{\mathrm{VC}\,(\mathcal{H})\ln\frac{1}{\epsilon} + \ln\frac{1}{\delta}}{\epsilon}\right),$$

142 *and*

$$C_1\left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right) \le m^{ag}_{\mathcal{H},\mathcal{I}}(\epsilon, \delta) \le C_2\left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right).$$

143 It is natural to seek a generalization of the VC-dimension to hypothesis classes of non-binary functions.
144 We recall two generalizations, both introduced by [3]:

Definition 4 (Graph dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$*
G-shatters S if there exists an $f : S \to \mathcal{Y}$ such that for every $T \subset S$, there is a $g \in \mathcal{H}$ such that

$$\forall x \in T, g(x) = f(x), \quad \text{and} \quad \forall x \in S \backslash T, g(x) \neq f(x).$$

145 *The graph dimension of $\mathcal{H}$, denoted by $d_G(\mathcal{H})$, is the maximal cardinality of a set that is G-shattered*
146 *by $\mathcal{H}$.*

Definition 5 (Natarajan dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say*
that $\mathcal{H}$ N-shatters S if there exists $f_1, f_2 : S \to \mathcal{Y}$ such that $\forall x \in S, f_1(x) \neq f_2(x)$, and for every
$T \subset S$, there is a $g \in \mathcal{H}$ such that

$$\forall x \in T, g(x) = f_1(x), \quad \text{and} \quad \forall x \in S \backslash T, g(x) = f_2(x).$$

147 *The Natarajan dimension of $\mathcal{H}$, denoted by $d_N(\mathcal{H})$, is the maximal cardinality of a set that is*
148 *N-shattered by $\mathcal{H}$.*

149 Both the graph dimension and the Natarajan dimension coincide with the VC-dimension for $k = 2$.
150 Based on these notions, the following theorem provides the upper and lower bounds of sample
151 complexity of standard multiclass learning:

152 **Theorem 2** ([3] and [5]). *There are absolute constants $C_1, C_2 > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$C_1\left(\frac{d_N(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon}\right) \le m^{re}_{\mathcal{H},\mathcal{I}}(\epsilon, \delta) \le C_2\left(\frac{d_G(\mathcal{H})\ln\frac{1}{\epsilon} + \ln\frac{1}{\delta}}{\epsilon}\right),$$

153 *and*

$$C_1\left(\frac{d_N(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right) \le m^{ag}_{\mathcal{H},\mathcal{I}}(\epsilon, \delta) \le C_2\left(\frac{d_G(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right).$$

3 AG-dimension and upper bounds for robust multiclass learning

We start by showing that finite graph dimension is not sufficient for robust multiclass learnability. We then introduce the notion of corrupted hypotheses, presented by [7]. By computing the graph dimension of these hypotheses, which is defined as adversarial graph dimension, we can upper bound the sample complexity of robust multiclass learning problem in both realizable and agnostic settings.

3.1 Finite graph dimension is not sufficient for robust multiclass learning

Theorem 2 shows that the finiteness of the graph dimension is a sufficient condition for multiclass learnability in non-robust setting. While in adversarial setting, for hypothesis classes with finite graph dimension, one cannot ensure the robust PAC learnability of $\mathcal{H}$, even if $d_G(\mathcal{H}) = 1$.

Theorem 3. *There exists a hypothesis class $\mathcal{H}$ with $d_G(\mathcal{H}) = 1$ and an adversary $\mathcal{U}$ such that $\mathcal{H}$ is not robustly PAC learnable with respect to $\mathcal{U}$.*

The argument follows closely a proof of an analogous result by [6] for binary robust learning. The proof is presented in Appendix.

3.2 Adversarial graph dimension

Consider a given hypothesis $f : \mathcal{X} \to \mathcal{Y}$. A labeled adversarial sample $(\tilde{x}, y)$ is classified correctly if $\tilde{x} \in f^{-1}(y)$. A labeled example (x, y) is classified correctly if $\mathcal{U}(x) \subset f^{-1}(y)$. Following [7], let $\tilde{\mathcal{Y}} = \mathcal{Y} \cup \{\perp\}$, where $\perp$ is the special "always wrong" output, i.e. $l(y, \perp) = l(\perp, y) = 1$ for every $y \in \tilde{\mathcal{Y}}$. We define the mapping $\kappa_{\mathcal{U}} : \mathcal{Y}^{\mathcal{X}} \to \tilde{\mathcal{Y}}^{\mathcal{X}}$:

$$\kappa_{\mathcal{U}}(f)(x) = \begin{cases} y, & \mathcal{U}(x) \subset f^{-1}(y), \\ \perp, & \text{otherwise.} \end{cases} \tag{1}$$

The corrupted set of hypotheses induced by perturbation $\mathcal{U}$ is then defined by $\tilde{\mathcal{H}} = \{\kappa_{\mathcal{U}}(f) : f \in \mathcal{H}\}$.

Lemma 1 (Lemma 2 in [7]). *For any perturbation $\mathcal{U}$ and distribution $\mathcal{D}$, $R_{\mathcal{U}}(f; \mathcal{D}) = R_{\mathcal{I}}(\kappa_{\mathcal{U}}(f); \mathcal{D})$.*

This lemma bridges the equivalence between robustly learning $\mathcal{H}$ and learning $\tilde{\mathcal{H}}$ without adversary, which enables us to use standard techniques to bound the sample complexity. Intuitively, we can derive a sufficient condition by considering the graph dimension of $\tilde{\mathcal{H}}$, which can be equivalently formalized as follows:

Definition 6 (Adversarial Graph Dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$ adversarially G-shatters S if there exists an $f : \mathcal{X} \to \mathcal{Y}$ such that for every $T \subset S$, there is a $g \in \mathcal{H}$ such that*

$$\forall x \in T, \forall x' \in \mathcal{U}(x), g(x') = f(x)$$

and

$$\forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), g(x') \neq f(x).$$

The adversarial graph dimension (AG-dimension) of $\mathcal{H}$, denoted by $d_G^{\mathcal{U}}(\mathcal{H})$, is the maximal cardinality of a set that is adversarially G-shattered by $\mathcal{H}$.

Proposition 1. *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $\tilde{\mathcal{H}}$ be the corrupted set of hypotheses induced by perturbation $\mathcal{U}$. Then we have*

$$d_G(\tilde{\mathcal{H}}) = d_G^{\mathcal{U}}(\mathcal{H}).$$

The proof is presented in Appendix.

Intuitively, by combining the above proposition with Lemma 1 and Theorem 2, we can upper bound the sample complexity of robust multiclass learning. Formally:

Theorem 4. *There are absolute constants $C > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$m_{\mathcal{H}, \mathcal{U}}^{re}(\epsilon, \delta) \leq C\left(\frac{d_G^{\mathcal{U}}(\mathcal{H})\ln(\frac{1}{\epsilon}) + \ln(\frac{1}{\delta})}{\epsilon}\right), \quad \text{and} \quad m_{\mathcal{H}, \mathcal{U}}^{ag}(\epsilon, \delta) \leq C\left(\frac{d_G^{\mathcal{U}}(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon^2}\right).$$

Proof. Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class with $d_G^{\mathcal{U}}(\mathcal{H}) = d$. For every $f \in \mathcal{H}$, define $\bar{f} : \mathcal{X} \times \mathcal{Y} \to \{0, 1\}$ by setting $\bar{f}(x, y) = 1$ if and only if $f(x') = y$ for all $x' \in \mathcal{U}(x)$. Note that according to our construction, we have

$$\mathbb{P}_{(x,y)\sim\mathcal{D}}[\bar{f}(x, y) \neq 1] = \mathbb{E}_{(x,y)\sim\mathcal{D}}\left[\sup_{x'\in\mathcal{U}(x)} \mathbb{1}(f(x') \neq y)\right]. \tag{2}$$

In the realizable case, let $\bar{\mathcal{H}} = \{\bar{f} : f \in \mathcal{H}\}$. From the definition, we can see that $\text{VC}(\bar{\mathcal{H}}) = d_G^{\mathcal{U}}(\mathcal{H})$. By Theorem 1, there exists $C > 0$ such that when we draw $m > C(\frac{d}{\epsilon}\ln(\frac{1}{\epsilon}) + \frac{1}{\epsilon}\ln(\frac{1}{\delta}))$ samples i.i.d. from some distribution $\mathcal{D}$ on $\mathcal{X} \times \mathcal{Y}$, then with probability at least $1 - \delta$ we have $\mathbb{P}_{(x,y)\sim\mathcal{D}}[\bar{f}(x, y) \neq 1] \leq \epsilon$. Plugging 2 into this inequality, we complete the proof for the realizable case and it is similar for the agnostic case. $\square$

4 AN-dimension and lower bounds for robust multiclass learning

In this section, we discuss the necessary conditions for robust multiclass learnability.

4.1 Finite Natarajan dimension is not necessary for robust multiclass learning

We first show that the finiteness of ordinary Natarajan dimension is also not necessary for robust multiclass learnability.

Theorem 5. *There exist $\mathcal{H}, \mathcal{U}$ such that $d_N(\mathcal{H}) = \infty$ but $\mathcal{H}$ is robustly PAC learnable under $\mathcal{U}$, i.e. $m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon, \delta) < \infty$.*

The proof follows the construction from [6], which shows that finite VC-dimension is not necessary for robust binary learnability. We leave the proof details to Appendix.

4.2 Adversarial Natarajan dimension

Following the idea of generalizing the graph dimension to the AG-dimension, for a given hypothesis class $\mathcal{H}$, one can consider the Natarajan dimension of its corrupted hypothesis class to lower bound the sample complexity of robust learnability. However, there are several natural but different ways in which the notion of N-shattering can be generalized: that is, we can either let f_2 that witnesses $\tilde{\mathcal{H}}$ N-shattering S take the value " $\perp$ " or not. Both notions derive a necessary condition for robust learnability. In this work, we choose the stronger notion, i.e. we need the entire perturbation sets to be N-shattered by $\mathcal{H}$.

Definition 7 (Adversarial Natarajan Dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$ adversarially N-shatters S if there exist $f_1, f_2 : \mathcal{X} \to \mathcal{Y}$ such that $\forall y \in S, f_1(y) \neq f_2(y)$, and for every $T \subset S$, there is a $g \in \mathcal{H}$ such that*

$$\forall x \in T, \forall x' \in \mathcal{U}(x), g(x') = f_1(x)$$

and

$$\forall x \in S \backslash T, \forall x' \in \mathcal{U}(x), g(x') = f_2(x).$$

The adversarial Natarajan dimension (AN-dimension) of $\mathcal{H}$, denoted by $d_N^{\mathcal{U}}(\mathcal{H})$, is the maximal cardinality of a set that is adversarially N-shattered by $\mathcal{H}$.

Based on this definition, we present that:

Theorem 6. *There are absolute constants $C > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$m_{\mathcal{H},\mathcal{U}}^{re}(\epsilon, \delta) \geq C\left(\frac{d_N^{\mathcal{U}}(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon}\right), \quad and \quad m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon, \delta) \geq C\left(\frac{d_N^{\mathcal{U}}(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon^2}\right).$$

Proof. Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class such that $d_N^{\mathcal{U}}(\mathcal{H}) = d$, and let $\mathcal{H}_d = \{0, 1\}^{[d]}$ be the family of all mappings from $[d]$ to $\{0, 1\}$. We want to show that for every learning algorithm $\mathcal{A}$ for

$\mathcal{H}$ and every $\epsilon, \delta \in (0, 1)$, there exists a learning algorithm $\bar{\mathcal{A}}$ satisfying: if there exists a function $m_{\mathcal{A}, \mathcal{U}}^{re} : (0, 1)^2 \to \mathbb{N}$ such that when $\mathcal{A}$ witnesses $m > m_{\mathcal{A}, \mathcal{U}}^{re}(\epsilon, \delta)$ samples (denoted as S) drawn i.i.d from some distribution $\mathcal{D}$, $\mathbb{P}[R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \le \epsilon] > 1 - \delta$. Then when $\bar{\mathcal{A}}$ witnesses m samples (denoted as S') drawn i.i.d from some distribution $\mathcal{D}'$ on $[d] \times \{0, 1\}$, $\mathbb{P}[R_{\mathcal{I}}(\bar{\mathcal{A}}(S'); \mathcal{D}') \le \epsilon] > 1 - \delta$ holds. By this claim, we have $m_{\bar{\mathcal{A}}, \mathcal{I}}^{re} \le m_{\mathcal{A}, \mathcal{U}}^{re}$, thus $m_{\mathcal{H}_d, \mathcal{I}}^{re} \le m_{\mathcal{H}, \mathcal{U}}^{re}$. Note that $\mathrm{VC}\,(\mathcal{H}_d) = d$, so by Theorem 1 we have $m_{\mathcal{H}, \mathcal{U}}^{re}(\epsilon, \delta) \ge C(\frac{d + \ln(1/\delta)}{\epsilon})$ for some constant $C > 0$ (independent of $\mathcal{H}$), and similarly for the agnostic case.

We now prove the claim. Let $\{s_1, \ldots, s_d\} \subset \mathcal{X}$ be a set and let f_0, f_1 be functions that witness the adversarial N-shattering of $\mathcal{H}$. Given a sample set $S' \triangleq \{(x_i, y_i)\}_{i=1}^m \subset [d] \times \{0, 1\}$, let $g = \mathcal{A}(\{s_{x_i}, f_{y_i}(s_{x_i})\}_{i=1}^m)$. Consider the learning algorithm $\bar{\mathcal{A}} : \cup_{n=0}^{\infty} ([d] \times \{0, 1\})^n \to \mathcal{H}_d$:

$$\bar{\mathcal{A}}(S')(j) = \begin{cases} 1, & g(s_j') = f_1(s_j), \forall s_j' \in \mathcal{U}(s_j), \\ 0, & \text{otherwise.} \end{cases}$$

Denote $\bar{\mathcal{A}}(S')$ by f. By the definition of adversarial N-shattering, it can be derived that $f(j) = 0$ if and only if $g(s_j') = f_2(s_j), \forall s_j' \in \mathcal{U}(s_j)$. By the construction we have

$$\mathbb{E}_{(j, y) \sim \mathcal{D}'}[\mathbb{1}(f(j) \ne y)] = \mathbb{E}_{(j, y) \sim \mathcal{D}'}[\sup_{s_j' \in \mathcal{U}(s_j)} \mathbb{1}(g(s_j') \ne f_y(s_j))] = \mathbb{E}_{(x, y) \sim \hat{\mathcal{D}}_m'} R_{\mathcal{U}}(g; \hat{\mathcal{D}}_m'),$$

where $\hat{\mathcal{D}}_m'$ is defined by $\mathbb{P}_{\hat{\mathcal{D}}_m'}(X = s_j, Y = f_y(s_j)) = \mathbb{P}_{\mathcal{D}'}(J = j, B = y)$. $\qquad \square$

5   The AG/AN-dimension of linear multiclass predictors

In this section, we calculate the AG-dimension and AN-dimension for linear multiclass predictors under bounded l_p perturbation, motivated by the binary results of [7] and the non-adversarial results of [8]. Recall the definition of linear multiclass predictors. Let $\Psi : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}^{dk}$ be a class-sensitive feature mapping [18]:

$$\Psi(x, y) = [\underbrace{0, \ldots, 0}_{\in \mathbb{R}^{(y-1)d}}, \underbrace{x^{(1)}, \ldots, x^{(d)}}_{\in \mathbb{R}^d}, \underbrace{0, \ldots, 0}_{\in \mathbb{R}^{(k-y)d}}],$$

where $x^{(i)}$ represents the i^{th} coordinate of x. The class of linear multiclass predictors is defined as

$$\mathcal{H}_{\Psi} = \{x \mapsto \arg\max_{i \in \mathcal{Y}} \langle w, \Psi(x, i) \rangle : w \in \mathbb{R}^{dk}\}. \tag{3}$$

We cite that the graph dimension and Natarajan dimension of $\mathcal{H}_{\Psi}$ is given by $(d - 1)(k - 1) \le d_N(\mathcal{H}_{\Psi}) \le d_G(\mathcal{H}_{\Psi}) \le O(dk \ln(dk))$ [8]. We then present the theorems, showing that the AG-dimension and AN-dimension also satisfy this bound.

We start by calculating the AN-dimension of $\mathcal{H}_{\Psi}$. Specifically, one can show that the AN-dimension of $\mathcal{H}_{\Psi}$ equals to the standard Natarajan dimension of $\mathcal{H}_{\Psi}$.

Theorem 7. *Let $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \le r\}$ for some $r \in \mathbb{R}^+$ and $p \in \mathbb{R}^+ \cup \{\infty\}$, and let $\mathcal{H}_{\Psi}$ be as defined in 3. Then, the AN-dimension of $\mathcal{H}_{\Psi}$ satisfies $d_N^{\mathcal{U}}(\mathcal{H}_{\Psi}) = d_N(\mathcal{H}_{\Psi})$.*

Proof. Since adversarial N-shattering implies N-shattering, we have $d_N^{\mathcal{U}}(\mathcal{H}_{\Psi}) \le d_N(\mathcal{H}_{\Psi})$. To prove the inverse inequality, it should be noted that the classifiers in $\mathcal{H}_{\Psi}$ are linear, hence if $\mathcal{H}_{\Psi}$ N-shatters S, it also N-shatters the set with some $x \in S$ replaced by $\forall x' \in l_x$, where l_x is the half-line which terminates at 0 and goes through x. For those $x \in S$ that cannot be adversarially N-shattered by $\mathcal{H}_{\Psi}$, we can always find some $x' \in l_x$ such that $\mathcal{U}(x')$ does not cross the decision boundary of g_T that witnesses the N-shattering for all $T \in S$. $\qquad \square$

Note that the Natarajan dimension of $\mathcal{H}_{\Psi}$ satisfies $(d - 1)(k - 1) \le d_N(\mathcal{H}_{\Psi}) \le dk$ (Corollary 29.8 in [19]). Combine this result with Theorem 7, we have:

Corollary 1. *Under the conditions of Theorem 7, $(d - 1)(k - 1) \le d_N^{\mathcal{U}}(\mathcal{H}_{\Psi}) \le dk$.*

250 Next, we present the AG-dimension of $\mathcal{H}_\Psi$:

Theorem 8. *Let* $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \le r\}$ *for some* $r \in \mathbb{R}^+$ *and* $p \in \mathbb{R}^+ \cup \{\infty\}$, *and let* $\mathcal{H}_\Psi$ *be as defined in 3. Then, the AG-dimension of* $\mathcal{H}_\Psi$ *satisfies*

$$(d-1)(k-1) \le d_G^{\mathcal{U}}(\mathcal{H}_\Psi) \le O(dk \ln(dk)).$$

251 To prove this result, we first present a lemma, which can be viewed as the generalization of Sauer's
252 Lemma [9] in the adversarial setting. We first define the restriction of a corrupted class. Let $\tilde{\mathcal{H}}$ be
253 the corrupted hypothesis class induced by $\mathcal{U}$. Let $S = \{x_1, \ldots, x_m\} \subset \mathcal{X}$. Fix a $f \in \mathcal{Y}^S$, for each
254 $h \in \mathcal{H}$, define $h_f : S \to \{0, 1\}$ such that $h_f(x_i) = 1$ if and only if $\kappa_{\mathcal{U}}(h)(x_i) = f(x_i), i \in [m]$.
255 Define $\mathcal{H}_f = \{h_f : h \in \mathcal{H}\}$. The restriction of $\tilde{\mathcal{H}}$ to S is defined by:

$$\tilde{\mathcal{H}}|_S = \mathcal{H}_{f*}|_S, \quad \text{where } f^* = \underset{f \in \mathcal{Y}^S}{\arg\max} \left| \mathcal{H}_f|_S \right|.$$

Lemma 2. *Let* $\mathcal{U}$ *be an adversary and* $\mathcal{H}$ *be a hypothesis class with* $d_G^{\mathcal{U}}(\mathcal{H}) \le d_G < \infty$. *Let* $\tilde{\mathcal{H}}$ *be the corrupted hypothesis class induced by* $\mathcal{U}$. *Let* $S = \{x_1, \ldots, x_m\} \subset \mathcal{X}$. *Then, for all* $m > d_G + 1$ *we have*

$$|\tilde{\mathcal{H}}|_S| \le \left(\frac{em}{d_G}\right)^{d_G}.$$

256 *Proof.* By Sauer's Lemma [9] and the fact that $\text{VC}(\mathcal{H}_f) \le d_G^{\mathcal{U}}(\mathcal{H})$ for all $f \in \mathcal{Y}^S$. $\qquad\square$

257 We now prove Theorem 8. The construction idea follows the proof of the non-adversarial results in
258 [8].

Proof of Theorem 8: The lower bound follows from Theorem 7 and the fact that $d_G^{\mathcal{U}}(\mathcal{H}) \ge d_N^{\mathcal{U}}(\mathcal{H})$
260 for all $\mathcal{H}$. To upper bound $d_G := d_G^{\mathcal{U}}(\mathcal{H})$, let $S = (x_1, \ldots, x_{d_G}) \in \mathbb{R}^d$ be a set which is adversarially
261 G-shattered by $\mathcal{H}_\Psi$, and let $f : S \to \mathcal{Y}$ be a function that witnesses the shattering. For every
262 $(i, j) \in [d_G] \times [k]$, define $z_{i,j} = \Psi(x_i, f(x_i)) - \Psi(x_i, j)$. Denote $Z = \{z_{i,j} | (i, j) \in [d_G] \times [k]\}$.
263 We now show that there exists a injective mapping from subsets of S to $\mathcal{W}_f^{dk}|_Z$, where $\mathcal{W}^{dk}$ is the
264 class of halfspace classifiers over $\mathbb{R}^{dk}$.

265 For each $T \subset S$, by the definition of adversarial G-shattering, $\exists h_T \in \mathcal{H}_\Psi$ such that

$$\forall x \in T, \forall x' \in \mathcal{U}(x), h_T(x') = f(x), \quad \text{and} \quad \forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), h_T(x') \ne f(x). \quad (4)$$

266 Let $w_T \in \mathbb{R}^{dk}$ be the vector defines h_T, 4 implies

$$\forall x \in T, \forall x' \in \mathcal{U}(x), \forall j \in [k], \langle w_T, \Psi(x', f(x)) \rangle \ge \langle w_T, \Psi(x', j) \rangle,$$

267 and

$$\forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), \exists j \in [k], \langle w_T, \Psi(x', f(x)) \rangle < \langle w_T, \Psi(x', j) \rangle. \quad (5)$$

It can be easily derived from 5 that $\forall i \in I_{S \backslash T}, \exists j \in [k], \exists z' \in \mathcal{V}(z_{i,j})$ s.t. $\langle w_T, z' \rangle < 0$, where $\mathcal{V}$ is
the p-norm ball in $\mathbb{R}^{dk}$ with radius r. And from 5 we can assume w.l.o.g that $\forall i \in I_T, \forall j \in [k], \forall z' \in \mathcal{V}(z_{i,j}), \langle w_T, z' \rangle \ge 0$. This is because if there exists some $z' \in \mathcal{V}(z)$ s.t. $\langle w_T, z' \rangle < 0$, notice that
$z' = \mathcal{V}(c') + z_{i,j}$ for some bounded c', we can replace x_i by some x_i' without destroying the adversarial
G-shattering (see the trick used in proof of Theorem 7), to ensure $\langle w_T, \Psi(x_i', f(x_i)) - \Psi(x_i', j) \rangle > \langle w_T, c \rangle, \forall c \in \mathcal{V}(0)$. Consequently, for every $T \in S$ we obtain a label pattern $P_T : [d_G] \times [k] \to \{0, 1\}$:

$$P_T(z_{i,j}) = \mathbb{1}(\min_{z' \in \mathcal{V}(z_{i,j})} \langle w_T, z' \rangle \ge 0).$$

268 It satisfies that $\forall i \in I_T, j \in [k], P_S(i, j) = 1$ and $\forall i \in I_{S \backslash T}, \exists j \in [k], P_T(i, j) = 0$, which implies
269 $P_T \ne P_{T'}$ for $T \ne T'$. And by definition P_T is connected with a unique element in $\mathcal{W}_f^{dk}|_Z$, which
270 completes the proof of our claim.

Note that the AG-dimension of halfspace classifier class with respect to $\mathcal{U}$ coincides with the definition of adversarial VC-dimension in [7]. Thus it satisfies that $d_G^{\mathcal{U}}(\mathcal{W}^{dk}) = dk + 1$ by Theorem 2 in [7]. Consequently, we have

$$|2^S| = 2^{d_G} \leq \left|\mathcal{W}_f^{dk}|_Z\right| \leq \left|\widetilde{\mathcal{W}^{dk}}|_Z\right| \overset{(i)}{\leq} \left(\frac{e|Z|}{d_G^{\mathcal{U}}(\mathcal{W}^{dk})}\right)^{d_G^{\mathcal{U}}(\mathcal{W}^{dk})} \leq (kd_G)^{dk+1},$$

where we have used Lemma 2 in step (i). We conclude that $d_G \leq O(dk \ln dk)$. $\qquad\square$

6   AG-dimension and AN-dimension are not equivalent

In previous sections, we have shown that the finiteness of the AN-dimension is a necessary condition for robust learnability, and the finiteness of the AG-dimension is a sufficient condition for robust learnability. Furthermore, we analyze these definitions on the linear multiclass predictor class, finding that the AG-dimension (AN-dimension) matches the order of the graph dimension (Natarajan dimension) for this class. The following question therefore naturally arises: are these two quantities equivalent? In [5], it is proven that for every hypotheses class $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,

$$d_N(\mathcal{H}) \leq d_G(\mathcal{H}) \leq 4.67 \log_2(k)d_N(\mathcal{H}). \qquad (6)$$

That is, in standard learning setting, if $k \leq \infty$ then the definition of the Natarajan dimension and the graph dimension are indeed equivalent, hence both the Natarajan dimension and graph dimension can characterize the standard learnability of a hypothesis class. However, in the adversarial setting ($\mathcal{U} \neq \mathcal{I}$), the generalized definitions derived above cannot bound each other. To show this, we claim that finite AN-dimension is not sufficient for robust learnability.

Theorem 9. *There exist $\mathcal{H},\mathcal{U}$ such that $d_N^{\mathcal{U}}(\mathcal{H}) = 0$ but $\mathcal{H}$ is not robustly PAC learnable under $\mathcal{U}$, i.e. $m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon, \delta) = \infty$.*

Proof. Let $\mathcal{U}$ be the 2-norm ball: $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_2 \leq r\}$ for all $x \in \mathcal{X}$ and some $r > 0$. We construct $\mathcal{H}$ as follow. Pick a sequence $\{x_i\}_{i=1}^{\infty} \subset \mathcal{X}$ such that for any $i \neq j, \mathcal{U}(x_i) \cap \mathcal{U}(x_j) = \emptyset$. Let $f : \mathcal{X} \to \mathcal{Y}$ be a function satisfying: there exists $z_i \in \mathcal{U}(x_i) \backslash x_i$ such that $f(z_i) \neq f(x_i)$ for each $i \in \mathbb{N}$. For each sequence $b = \{b_i\}_{i=1}^{\infty} \subset \{0, 1\}$, define $h_b : \mathcal{X} \to \mathcal{Y}$:

$$h_b(x) = \begin{cases} f(x_i), & x \in \mathcal{U}(x_i)\backslash z_i, \quad i \in \mathbb{N}, \\ f(x_i), & x = z_i \text{ and } b_i = 1, \\ f(z_i), & x = z_i \text{ and } b_i = 0, \\ 1, & \text{otherwise.} \end{cases}$$

Let $\mathcal{H} = \{h_b : b \text{ is a sequence in } \{0, 1\}\}$. Using the same approach employed in the proof of Lemma 3, for any learning rule $\mathcal{A} : (\mathcal{X} \times \mathcal{Y})^* \to \mathcal{H}$, there exists a distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$ such that there exists a function $f^* \in \mathcal{H}$ with $R_{\mathcal{U}}(f^*; \mathcal{D}) = 0$, and with probability of at least $1/7$ over the choice of $S \sim \mathcal{D}^m$ we have that $R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \geq 1/8$, by considering the distribution family $\mathfrak{D}$ containing distributions that are uniform over $2m$ points in $\{(x_1, f(x_1)), \ldots, (x_{3m}, f(x_{3m}))\}$. We complete the proof by noting that $d_N^{\mathcal{U}}(\mathcal{H}) = 0$, since there is no single r-ball that is adversarially N-shattered by $\mathcal{H}$. $\qquad\square$

7   Conclusion

In this work, we show that the graph/Natarajan dimension cannot characterize robust multiclass learnability. And we construct the concepts of AG-dimension and AN-dimension to upper bound and lower bound the sample complexity of robust multiclass learning. We further analyze the AG/AN-dimension of linear multiclass predictors. Finally, we prove that AG-dimension and AN-dimension are not equivalent. However, it is not yet clear whether finite AG-dimension is also necessary for robust multiclass learning. Establishing a complexity measure that characterizes robust learnability still remains an open question.

References

[1] Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE SP*, pages 39–57, 2017.

[2] Nicholas Carlini and David A. Wagner. Audio adversarial examples: Targeted attacks on speech-to-text. In *IEEE SP*, pages 1–7, 2018.

[3] B. K. Natarajan. On learning sets and functions. *Machine Learning*, 4:67–97, 1989.

[4] Vladimir Naumovich Vapni. *The Nature of Statistical Learning Theory*. Springer, 1995.

[5] Shai Ben-David, Nicolò Cesa-Bianchi, David Haussler, and Philip M. Long. Characterizations of learnability for classes of {0, ..., n}-valued functions. *Journal of Computer and System Sciences*, 50(1):74–86, 1995.

[6] Omar Montasser, Steve Hanneke, and Nathan Srebro. VC classes are adversarially robustly learnable, but only improperly. In *COLT*, volume 99, pages 2512–2530, 2019.

[7] Daniel Cullina, Arjun Nitin Bhagoji, and Prateek Mittal. Pac-learning in the presence of adversaries. In *NeurIPS*, pages 228–239, 2018.

[8] Amit Daniely, Sivan Sabato, and Shai Shalev-Shwartz. Multiclass learning approaches: A theoretical comparison with implications. In *NeurIPS*, pages 494–502, 2012.

[9] Norbert Sauer. On the density of families of sets. *Journal of Combinatorial Theory, Series A*, 13(1):145–147, 1972.

[10] Justin Khim and Po-Ling Loh. Adversarial risk bounds for binary classification via function transformation. *CoRR*, abs/1810.09519, 2018.

[11] Robi Bhattacharjee, Somesh Jha, and Kamalika Chaudhuri. Sample complexity of robust linear classification on separated data. In *ICML*, volume 139 of *Proceedings of Machine Learning Research*, pages 884–893, 2021.

[12] Arjun Nitin Bhagoji, Daniel Cullina, and Prateek Mittal. Lower bounds on adversarial robustness from optimal transport. In *NeurIPS*, pages 7496–7508, 2019.

[13] Dimitrios I. Diochnos, Saeed Mahloujifar, and Mohammad Mahmoody. Lower bounds for adversarially robust PAC learning under evasion and hybrid attacks. In *ICMLA*, pages 717–722, 2020.

[14] Nicolò Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games*. Cambridge University Press, 2006.

[15] David Haussler and Philip M. Long. A generalization of sauer's lemma. *Journal of Combinatorial Theory, Series A*, 71(2):219–240, 1995.

[16] Dong Yin, Kannan Ramchandran, and Peter L. Bartlett. Rademacher complexity for adversarially robust generalization. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pages 7085–7094, 2019.

[17] Peter L. Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3:463–482, 2002.

[18] Koby Crammer and Yoram Singer. On the algorithmic implementation of multiclass kernel-based vector machines. *Journal of Machine Learning Research*, 2:265–292, 2001.

[19] Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning - From Theory to Algorithms*. Cambridge University Press, 2014.