On Robust Multiclass Learnability

Abstract

This work analyzes the robust learning problem in the multiclass setting. Under the framework of Probably Approximately Correct (PAC) learning, we first show that the graph dimension and the Natarajan dimension, which characterize the standard multiclass learnability, are no longer applicable in robust learning problem. We then generalize these notions to the robust learning setting, denoted as the adversarial graph dimension (AG-dimension) and the adversarial Natarajan dimension (AN-dimension). Upper and lower bounds of the sample complexity of robust multiclass learning are rigorously derived based on the AG-dimension and AN-dimension, respectively. Moreover, we calculate the AG-dimension and AN-dimension of the class of linear multiclass predictors, and show that the graph (Natarajan) dimension is of the same order as the AG(AN)-dimension. Finally, we prove that the AG-dimension and AN-dimension are not equivalent.

1 Introduction

Learning models that are robust to adversarial perturbations has attracted significant research attention in recent years. Notably, prior work on this subject has largely studied the theory of robust learnability in the context of binary supervised learning. However, many important problems require classification into a great number of target classes. For example, in image object recognition and language models building[1, 2], the number of classes scales as the number of possible objects or the dictionary size respectively. It is thus of both practical and theoretical interest to generalize the robust binary learning theory to the robust multiclass setting.

In the standard multiclass learning setting, the finiteness of the Natarajan dimension or graph dimension [3] (both of which are generalized from the VC-dimension [4]) is necessary and sufficient to ensure learnability [5]. Recent work has shown that the finiteness of the VC-dimension is neither sufficient nor necessary for (proper) robust binary classification [6]. Inspired by [6], this paper demonstrates that the Natarajan/graph dimension can no longer characterize robust learnability in the multiclass problem. Meanwhile, some questions naturally arise: In multiclass setting, how can robust learning be ensured? And what is necessary for robust learning?

To answer these questions, we generalize the corrupted hypothesis classes [7], which arise from standard hypothesis classes in the binary setting in the presence of an adversary, and use them to reduce the robust learning problem to a non-robust one. By considering the graph dimension and Natarajan dimension of the corrupted hypothesis classes—which are defined as the adversarial graph dimension (AG-dimension) and adversarial Natarajan dimension (AN-dimension) respectively—we derive the upper and lower bounds of sample complexity of the robust multiclass learning problem. We then analyze the AG-dimension and the AN-dimension of linear multiclass predictor class, showing that the AG(AN)-dimension and the graph (Natarajan) dimension are of the same order.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Since it is proven that the graph dimension and the Natarajan dimension are equivalent when the target class is finite [5], is it possible to use the AG-dimension and AN-dimension to bound each other? Our work suggests that the equivalent relationship does not hold, which is illustrated by constructing a hypothesis class with finite AN-dimension but not robustly learnable.

Related work. [8, 9, 10, 11] focus on the robust binary classification problem. [3] characterize the multiclass learnability in non-robust setting. [12, 5, 13] define a large family of notions of dimensions, all of which generalize the VC-dimension and may be used to estimate the sample complexity of multiclass classification. [14] calculate the graph dimension and the Natarajan dimension of linear multiclass predictor class. [15] upper bounds the adversarial risk of linear multiclass classifiers based on Rademacher complexity, which cannot directly derive bounds on sample complexity of general robust multiclass learning problems. The theory on robust multiclass learnability for general hypothesis class is less explored. This work takes some steps towards solving this problem.

2 Preliminaries

This section introduces some basic notations and concepts used throughout the present study.

In the remainder of this article, $\mathbb{R}, \mathbb{N}, \mathbb{R}^+$ and $\mathbb{R}^d$ represent the sets of real numbers, natural numbers, non-negative real numbers and d-dimensional vectors over $\mathbb{R}$, respectively. We denote the set $\{1, \ldots, n\}$ (for $n \in \mathbb{N}$) by $[n]$. If A and B are sets, we use B^A to denote the collection of all mappings from A to B and 2^A to denote the power set of A, that is the collection of all subsets of A. Let $C = \{c_1, \ldots, c_m\} \subset \mathcal{X}$ and $C' \subset C$ be a subset of C, then $I_{C'} \in [m]$ denotes the index set of C'. Let $\mathcal{H}$ be a class of functions defined in $\mathcal{X}$, then $\mathcal{H}|_C$ represents the restriction of $\mathcal{H}$ to C, that is $\mathcal{H}_C = \{(h(c_1), \ldots, h(c_m)) : h \in \mathcal{H}\}$. We denote the indicator function by $\mathbb{1}(\text{event})$, that is 1 if an event happens and 0 otherwise. Finally, $\|\cdot\|_p$ represents the ℓ_p norm.

The *robust learning* problem is formalized as follows. Let $\mathcal{X} = \mathbb{R}^d$ be the instance space and $\mathcal{Y} = \{1, \ldots, k\}$ be the label space. For an unknown distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$[1] and a hypothesis class $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$, the goal of robust learning is to find a function $f \in \mathcal{H}$, based on n labeled training samples $S = \{(x_i, y_i)\}_{i=1}^n$ drawn independent and identically distributed (i.i.d.) from $\mathcal{D}$, such that under a small perturbation $\mathcal{U} : \mathcal{X} \to 2^{\mathcal{X}}$, the *adversarial risk*

$$R_{\mathcal{U}}(f; \mathcal{D}) \triangleq \mathbb{E}_{(x,y) \sim \mathcal{D}} \left[\sup_{x' \in \mathcal{U}(x)} l(f(x'), y) \right]$$

is minimal for the 0-1 loss $l(\hat{y}, y) \triangleq \mathbb{1}(\hat{y} \neq y)$.

The perturbation $\mathcal{U}(x)$ is required to be nonempty, so some choice of x' is always available. One choice for the perturbation is the p-norm ball ($p \geq 1$) with a small radius r, i.e. $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \leq r\}$. Selecting $r = 0$ gives the *identity perturbation*: $\mathcal{I}(x) \triangleq \{x\}$. Note that in this case, the problem is reduced to a standard learning problem, and $R_{\mathcal{I}}(f; \mathcal{D})$ is called the *standard risk* of f over $\mathcal{D}$.

The mechanism of finding a function is called a *learning algorithm*. In this paper, we focus on *proper* learning algorithms, that is, learning algorithms will always pick a function from $\mathcal{H}$. Formally, a learning algorithm is a function $\mathcal{A} : \cup_{n=0}^{\infty} (\mathcal{X} \to \mathcal{Y})^n \to \mathcal{H}$. A common choice of robust learning algorithm is to learn through *adversarial empirical risk minimization* or AERM for short:

$$\hat{f} \in \text{AERM}_{\mathcal{U}}(\mathcal{H}; S) \triangleq \underset{f \in \mathcal{H}}{\arg\min}\, R_{\mathcal{U}}(f; \hat{\mathcal{D}}_n),$$

where $\hat{\mathcal{D}}_n$ is the *empirical distribution* generated by S, i.e. for $(x, y) \sim \hat{\mathcal{D}}_n$, (x, y) is equal to (x_i, y_i) with probability $1/n$ for each $i \in \{1, \ldots, n\}$.

Learning algorithms like AERM do not always produce a function that achieves the optimal adversarial risk, because a training set consisting of finite samples is not always sufficiently informative

---

[1]Formally, there is a sigma algebra $\mathcal{F} \subset 2^{\mathcal{X} \times \mathcal{Y}}$ of events and $\mathcal{D}$ is a probability measure on $(\mathcal{X} \times \mathcal{Y}, \mathcal{F})$.

to represent $\mathcal{D}$. Thus, we introduce the definition of robust probably approximately correct (PAC) learnability, in the realizable and agnostic setting [7, 6]:

Definition 1 (Agnostic Robust PAC Learnability). *Under perturbation $\mathcal{U}$, a hypothesis class $\mathcal{H}$ is robustly PAC learnable in the agnostic setting if there is a function $m_{\mathcal{H},\mathcal{U}}^{ag} : (0,1)^2 \to \mathbb{N}$ and a learning algorithm $\mathcal{A} : \cup_{n=0}^{\infty}(\mathcal{X} \times \mathcal{Y})^n \to \mathcal{H}$ with the following property. For every $\epsilon, \delta \in (0,1)$ and every distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$, let $S = \{(x_i, y_i)\}_{i=1}^{n}$ be n samples i.i.d generated by $\mathcal{D}$ s.t. $n > m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon, \delta)$. Then with probability at least $1 - \delta$,*

$$R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \leq \min_{f \in \mathcal{H}} R_{\mathcal{U}}(f; \mathcal{D}) + \epsilon.$$

The function $m_{\mathcal{H},\mathcal{U}}^{ag}$ is defined as the sample complexity of learning $\mathcal{H}$ under perturbation $\mathcal{U}$ in the agnostic setting.

Definition 2 (Realizable Robust PAC Learnability). *Under perturbation $\mathcal{U}$, a hypothesis class $\mathcal{H}$ is robustly PAC learnable in the realizable setting if there is a function $m_{\mathcal{H},\mathcal{U}}^{re} : (0,1)^2 \to \mathbb{N}$ and a learning algorithm $\mathcal{A} : \cup_{n=0}^{\infty}(\mathcal{X} \times \mathcal{Y})^n \to \mathcal{H}$ with the following property. For every $\epsilon, \delta \in (0,1)$ and every distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$, let $S = \{(x_i, y_i)\}_{i=1}^{n}$ be n samples i.i.d generated by $\mathcal{D}$ s.t. $n > m_{\mathcal{H},\mathcal{U}}^{re}(\epsilon, \delta)$. Then with probability at least $1 - \delta$,*

$$R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \leq \epsilon.$$

The function $m_{\mathcal{H},\mathcal{U}}^{re}$ is defined as the sample complexity of learning $\mathcal{H}$ under perturbation $\mathcal{U}$ in the realizable setting.

These definitions agree with the standard PAC learnability when $\mathcal{U} = \mathcal{I}$, which has been widely studied in both *binary* ($k = 2$) and *multiclass* ($k > 2$) setting. We recall the known result regarding the sample complexity of binary learning. Recall the definition of the Vapnik-Chervonenkis dimension (VC-dimension) [4]:

Definition 3 (VC-dimension). *Let $\mathcal{H} \subset \{0,1\}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that S is shattered by $\mathcal{H}$ if $\mathcal{H}|_S = \{0,1\}^S$. The VC-dimension of $\mathcal{H}$, denoted by $\mathrm{VC}\,(\mathcal{H})$, is the maximal cardinality of a set that is shattered by $\mathcal{H}$.*

The following theorem, based on the VC-dimension, characterizes the sample complexity of learning *binary* hypothesis classes.

Theorem 1 ([4] and [16]). *There are absolute constants $C_1, C_2 > 0$ such that for every $\mathcal{H} \subset \{0,1\}^{\mathcal{X}}$,*

$$C_1 \left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln \frac{1}{\delta}}{\epsilon} \right) \leq m_{\mathcal{H},\mathcal{I}}^{re}(\epsilon, \delta) \leq C_2 \left(\frac{\mathrm{VC}\,(\mathcal{H}) \ln \frac{1}{\epsilon} + \ln \frac{1}{\delta}}{\epsilon} \right),$$

and

$$C_1 \left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln \frac{1}{\delta}}{\epsilon^2} \right) \leq m_{\mathcal{H},\mathcal{I}}^{ag}(\epsilon, \delta) \leq C_2 \left(\frac{\mathrm{VC}\,(\mathcal{H}) + \ln \frac{1}{\delta}}{\epsilon^2} \right).$$

It is natural to seek a generalization of the VC-dimension to hypothesis classes of non-binary functions. We recall two generalizations, both introduced by [3]:

Definition 4 (Graph dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$ G-shatters S if there exists an $f : S \to \mathcal{Y}$ such that for every $T \subset S$, there is a $g \in \mathcal{H}$ such that*

$$\forall x \in T, g(x) = f(x), \quad \text{and} \quad \forall x \in S \backslash T, g(x) \neq f(x).$$

The graph dimension of $\mathcal{H}$, denoted by $d_G(\mathcal{H})$, is the maximal cardinality of a set that is G-shattered by $\mathcal{H}$.

Definition 5 (Natarajan dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$ N-shatters S if there exists $f_1, f_2 : S \to \mathcal{Y}$ such that $\forall x \in S, f_1(x) \neq f_2(x)$, and for every $T \subset S$, there is a $g \in \mathcal{H}$ such that*

$$\forall x \in T, g(x) = f_1(x), \quad \text{and} \quad \forall x \in S \backslash T, g(x) = f_2(x).$$

The Natarajan dimension of $\mathcal{H}$, denoted by $d_N(\mathcal{H})$, is the maximal cardinality of a set that is N-shattered by $\mathcal{H}$.

110 Both the graph dimension and the Natarajan dimension coincide with the VC-dimension for $k = 2$.
111 Based on these notions, the following theorem provides the upper and lower bounds of sample
112 complexity of standard multiclass learning:

113 **Theorem 2** ([3] and [5])**.** *There are absolute constants $C_1, C_2 > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$C_1\left(\frac{d_N(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon}\right) \le m^{re}_{\mathcal{H},\mathcal{I}}(\epsilon,\delta) \le C_2\left(\frac{d_G(\mathcal{H})\ln\frac{1}{\epsilon} + \ln\frac{1}{\delta}}{\epsilon}\right),$$

114 *and*

$$C_1\left(\frac{d_N(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right) \le m^{ag}_{\mathcal{H},\mathcal{I}}(\epsilon,\delta) \le C_2\left(\frac{d_G(\mathcal{H}) + \ln\frac{1}{\delta}}{\epsilon^2}\right).$$

115 3 AG-dimension and upper bounds for robust multiclass learning

116 We start by showing that finite graph dimension is not sufficient for robust multiclass learnability.
117 We then introduce the notion of corrupted hypotheses, presented by [7]. By computing the graph
118 dimension of these hypotheses, which is defined as adversarial graph dimension, we can upper bound
119 the sample complexity of robust multiclass learning problem in both realizable and agnostic settings.

120 3.1 Finite graph dimension is not sufficient for robust multiclass learning

121 Theorem 2 shows that the finiteness of the graph dimension is a sufficient condition for multiclass
122 learnability in non-robust setting. While in adversarial setting, for hypothesis classes with finite graph
123 dimension, one cannot ensure the robust PAC learnability of $\mathcal{H}$, even if $d_G(\mathcal{H}) = 1$.

124 **Theorem 3.** *There exists a hypothesis class $\mathcal{H}$ with $d_G(\mathcal{H}) = 1$ and an adversary $\mathcal{U}$ such that $\mathcal{H}$ is*
125 *not robustly PAC learnable with respect to $\mathcal{U}$.*

126 To prove this theorem, We first present a lemma, which is generalized from Lemma 3 in [6].

127 **Lemma 1.** *Let $m \in \mathbb{N}$. Then, there exists a hypothesis class $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ such that for any learning rule*
128 $\mathcal{A} : (\mathcal{X} \times \mathcal{Y})^* \to \mathcal{H}$, *there exists a distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$ such that:*

129 *1. There exists a function $f^* \in \mathcal{H}$ with $R_{\mathcal{U}}(f^*; \mathcal{D}) = 0$.*

130 *2. With probability of at least $1/7$ over the choice of $S \sim \mathcal{D}^m$ we have that $R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \ge 1/8$.*

131 The proof of this lemma is presented in Appendix. We now proceed with the proof of Theorem 3.

132 *Proof of Theorem 3:* The argument follows closely a proof of an analogous result by [6] for binary
133 robust learning, but generalizes the constructions and analyzes to match the definition of graph
134 dimension in the multiclass setting. For each $m \in \mathbb{N}$, let $X_m = \{x_1^{(m)}, \ldots, x_{3m}^{(m)}\}$ be a set that
135 contains $3m$ distinct points in $\mathcal{X}$ subject to $\forall x_i, x_j \in \cup_{m=1}^{\infty} X_m$, if $x_i \ne x_j$, then $\mathcal{U}(x_i) \cap \mathcal{U}(x_j) = \emptyset$.
136 And we construct $\mathcal{H}_m$ on X_m as follows. For each $b \in \{0, 1\}^{3m}$, we construct a set $\mathcal{Z}_b$: Initialize
137 $\mathcal{Z}_b = \emptyset$, for each $i \in [3m]$, if $b_i = 1$ then pick a point $z \in \mathcal{U}(x_i^{(m)})$ such that $z \notin \mathcal{Z}_{b'}$ for each
138 $b' \ne b$, and add it to $\mathcal{Z}_b$. Let $h_b : \mathcal{X} \to \mathcal{Y}$ be a hypothesis such that $h_b(x) = 1$ if and only if $x \notin \mathcal{Z}_b$
139 and $x \notin X_{m'}$ for $m' \ne m$. Furthermore, for fixed $m \in \mathbb{N}$ and $x \in X_{m'}$ s.t. $m' \ne m$, we need all h_b
140 map x into a same label $y_x (\ne 1)$, where y_x is consistent for all m. That is,

$$h_b(x) = \begin{cases} \neg 1, & x \in Z_b, \\ y_x(\ne 1), & \exists m' \ne m, x \in X_{m'}, \\ 1, & \text{otherwise,} \end{cases}$$

where $\neg 1$ is some label that is not equal to 1. Then define

$$\mathcal{H}_m = \{h_b : b \in \{0, 1\}^{3m}, \sum_{i=1}^{3m} b_i = m\}.$$

141 Let $\mathcal{H} = \cup_{m=1}^{\infty} \mathcal{H}_m$. We claim that $d_G(\mathcal{H}) \le 1$. That is, if pick two points $x_1, x_2 \in \mathcal{X}$ such that
142 $x_1 \ne x_2$, $\mathcal{H}$ cannot G-shatters $\{x_1, x_2\}$. since for all $h \in \mathcal{H}$ and $x \in \mathcal{X}$, there are at most two

cases of $h(x)$, one of which is 1. Hence the only $f : \{x_1, x_2\} \to S$ in Definition 4 that needs to be considered is $f(x_1) = f(x_2) = 1$. There are six cases to consider:

(1) There exists $m \in \mathbb{N}$ such that $z_1, z_2 \in X_m$. Then $\forall h_b \in \mathcal{H}_m, x_1, x_2 \notin Z_b$ by the construction of Z_b. Hence $h_b(x_1) = h_b(x_2) = 1$. And $\forall h \in \mathcal{H}_{m'}$ for $m' \neq m$, we have $h(x_1) = y_{x_1} \neq 1, h(x_2) = y_{x_2} \neq 1$. So we only obtain labelings $(1, 1)$ and $(\neg 1, \neg 1)$.

(2) There exists $m \in \mathbb{N}$ such that $x_1, x_2 \in \mathcal{U}(X_m) \backslash X_m$. There are two sub-cases to consider. (i) $\exists b$ s.t. $h_b \in \mathcal{H}_m$ and $x_1, x_2 \in Z_b$, then we have $h_b(x_1) \neq 1$ and $h_b(x_2) \neq 1$. For the remaining $h \in \mathcal{H}$ we have $h(x_1) = h(x_2) = 1$. So we only obtain labelings $(1, 1)$ and $(\neg 1, \neg 1)$ in this sub-case. (ii) For the remaining sub-cases, labeling $(\neg 1, \neg 1)$ cannot be obtained since $x_1, x_2 \notin X_m$ for all m and there is no b such that x_1, x_2 are in Z_b in the same time.

(3) $x_1 \in X_m$ and $x_2 \in X_{m'}$ for $m \neq m'$. In this case, we have $h(x_1) = 1, h(x_2) \neq 1$ for $h \in \mathcal{H}_m$, and $h(x_1) \neq 1, h(x_2) = 1$ for $h \in \mathcal{H}_{m'}$. For those predictors that are in neither $\mathcal{H}_m$ nor $\mathcal{H}_{m'}$, we have $h(x_1) \neq 1, h(x_2) \neq 1$. Hence we cannot label both points x_1 and x_2 with $(1, 1)$.

(4) $x_1 \in X_m$ and $x_2 \in \mathcal{U}(X_{m'}) \backslash X_{m'}$ for $m \neq m'$. Observe that $h(x_1) = 1$ if and only if $h \in \mathcal{H}_m$. But for all $h \in \mathcal{H}_m, h$ always labels x_2 with 1. Hence labeling $(1, \neg 1)$ cannot be obtained.

(5) $x_1 \in \mathcal{U}(X_m) \backslash X_m$ and $x_2 \in \mathcal{U}(X_{m'}) \backslash X_{m'}$ for $m \neq m'$. Similar to the discussion above, for all $h \in \mathcal{H}$, either $h(x_1) = 1$ or $h(x_2) = 1$. So we cannot obtain labeling $(\neg 1, \neg 1)$.

(6) The remaining cases, i.e. $x_1, x_2 \notin \mathcal{U}(X_m)$ for all $m \in \mathbb{N}$. In this case we can only obtain labeling $(1, 1)$ since for all $h \in \mathcal{H}$, we have $h(x_1) = h(x_2) = 1$.

The arguments above show that $d_G(\mathcal{H}) \leq 1$. It remains to show $\mathcal{H}$ is not robustly PAC learnable. By Lemma 1, it follows that for any learning rule $\mathcal{A} : (\mathcal{X} \times \mathcal{Y})^* \to \mathcal{H}$ and for any $m \in \mathbb{N}$, there exists a distribution $\mathcal{D}$ over $X_m \times \mathcal{Y}$ where there exists a predictor $h^* \in \mathcal{H}$ with $R_{\mathcal{U}}(h^*; \mathcal{D}) = 0$, but with probability at least $1/7$ over $S \sim \mathcal{D}^m, R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) > 1/8$ if $\mathcal{A}(S) \in \mathcal{H}_m$. Classifiers in $\mathcal{H}_{m'}$ where $m' \neq m$ are also non-robust since they make mistakes on points in X_m. This concludes that $\mathcal{H}$ is not robustly PAC learnable, which completes the proof. $\qquad\square$

3.2 Adversarial graph dimension

Consider a given hypothesis $f : \mathcal{X} \to \mathcal{Y}$. A labeled adversarial sample $(\tilde{x}, y)$ is classified correctly if $\tilde{x} \in f^{-1}(y)$. A labeled example (x, y) is classified correctly if $\mathcal{U}(x) \subset f^{-1}(y)$. Following [7], let $\tilde{\mathcal{Y}} = \mathcal{Y} \cup \{\bot\}$, where $\bot$ is the special "always wrong" output, i.e. $l(y, \bot) = l(\bot, y) = 1$ for every $y \in \tilde{\mathcal{Y}}$. We define the mapping $\kappa_{\mathcal{U}} : \mathcal{Y}^{\mathcal{X}} \to \tilde{\mathcal{Y}}^{\mathcal{X}}$:

$$\kappa_{\mathcal{U}}(f)(x) = \begin{cases} y, & \mathcal{U}(x) \subset f^{-1}(y), \\ \bot, & \text{otherwise.} \end{cases} \tag{1}$$

The corrupted set of hypotheses induced by perturbation $\mathcal{U}$ is then defined by $\tilde{\mathcal{H}} = \{\kappa_{\mathcal{U}}(f) : f \in \mathcal{H}\}$.

Lemma 2 (Lemma 2 in [7]). *For any perturbation $\mathcal{U}$ and distribution $\mathcal{D}$, $R_{\mathcal{U}}(f; \mathcal{D}) = R_{\mathcal{I}}(\kappa_{\mathcal{U}}(f); \mathcal{D})$.*

This lemma bridges the equivalence between robustly learning $\mathcal{H}$ and learning $\tilde{\mathcal{H}}$ without adversary, which enables us to use standard techniques to bound the sample complexity. Intuitively, we can derive a sufficient condition by considering the graph dimension of $\tilde{\mathcal{H}}$, which can be equivalently formalized as follows:

Definition 6 (Adversarial Graph Dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$. We say that $\mathcal{H}$ adversarially G-shatters S if there exists an $f : \mathcal{X} \to \mathcal{Y}$ such that for every $T \subset S$, there is a $g \in \mathcal{H}$ such that*

$$\forall x \in T, \forall x' \in \mathcal{U}(x), g(x') = f(x)$$

and

$$\forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), g(x') \neq f(x).$$

The adversarial graph dimension (AG-dimension) of $\mathcal{H}$, denoted by $d_G^{\mathcal{U}}(\mathcal{H})$, is the maximal cardinality of a set that is adversarially G-shattered by $\mathcal{H}$.

Proposition 1. *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $\tilde{\mathcal{H}}$ be the corrupted set of hypotheses induced by perturbation $\mathcal{U}$. Then we have*

$$d_G(\tilde{\mathcal{H}}) = d_G^{\mathcal{U}}(\mathcal{H}).$$

183 The proof is presented in Appendix.

184 Intuitively, by combining the above proposition with Lemma 2 and Theorem 2, we can upper bound
185 the sample complexity of robust multiclass learning. Formally:

Theorem 4. *There are absolute constants $C > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$m_{\mathcal{H},\mathcal{U}}^{re}(\epsilon,\delta) \leq C\left(\frac{d_G^{\mathcal{U}}(\mathcal{H})\ln(\frac{1}{\epsilon}) + \ln(\frac{1}{\delta})}{\epsilon}\right), \quad and \quad m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon,\delta) \leq C\left(\frac{d_G^{\mathcal{U}}(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon^2}\right).$$

186 *Proof.* Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class with $d_G^{\mathcal{U}}(\mathcal{H}) = d$. For every $f \in \mathcal{H}$, define $\bar{f} : \mathcal{X} \times \mathcal{Y} \to$
187 $\{0,1\}$ by setting $\bar{f}(x,y) = 1$ if and only if $f(x') = y$ for all $x' \in \mathcal{U}(x)$. Note that according to our
188 construction, we have

$$\mathbb{P}_{(x,y)\sim\mathcal{D}}[\bar{f}(x,y) \neq 1] = \mathbb{E}_{(x,y)\sim\mathcal{D}}\left[\sup_{x'\in\mathcal{U}(x)} \mathbb{1}(f(x') \neq y)\right]. \tag{2}$$

189 In the realizable case, let $\bar{\mathcal{H}} = \{\bar{f} : f \in \mathcal{H}\}$. From the definition, we can see that $\text{VC}(\bar{\mathcal{H}}) = d_G^{\mathcal{U}}(\mathcal{H})$.
190 By Theorem 1, there exists $C > 0$ such that when we draw $m > C(\frac{d}{\epsilon}\ln(\frac{1}{\epsilon}) + \frac{1}{\epsilon}\ln(\frac{1}{\delta}))$ samples i.i.d.
191 from some distribution $\mathcal{D}$ on $\mathcal{X} \times \mathcal{Y}$, then with probability at least $1 - \delta$ we have $\mathbb{P}_{(x,y)\sim\mathcal{D}}[\bar{f}(x,y) \neq$
192 $1] \leq \epsilon$. Plugging 2 into this inequality, we complete the proof for the realizable case and it is similar
193 for the agnostic case. $\square$

4   AN-dimension and lower bounds for robust multiclass learning

195 In this section, we discuss the necessary conditions for robust multiclass learnability.

4.1   Finite Natarajan dimension is not necessary for robust multiclass learning

197 We first show that the finiteness of ordinary Natarajan dimension is also not necessary for robust
198 multiclass learnability.

Theorem 5. *There exist $\mathcal{H}, \mathcal{U}$ such that $d_N(\mathcal{H}) = \infty$ but $\mathcal{H}$ is robustly PAC learnable under $\mathcal{U}$, i.e.*
200 $m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon,\delta) < \infty$.

201 The proof follows the construction from [6], which shows that finite VC-dimension is not necessary
202 for robust binary learnability. We leave the proof details to Appendix.

4.2   Adversarial Natarajan dimension

204 Following the idea of generalizing the graph dimension to the AG-dimension, for a given hypothesis
205 class $\mathcal{H}$, one can consider the Natarajan dimension of its corrupted hypothesis class to lower bound
206 the sample complexity of robust learnability. However, there are several natural but different ways
207 in which the notion of N-shattering can be generalized: that is, we can either let f_2 that witnesses
208 $\tilde{\mathcal{H}}$ N-shattering S take the value " $\perp$ " or not. Both notions derive a necessary condition for robust
209 learnability. In this work, we choose the stronger notion, i.e. we need the entire perturbation sets to
210 be N-shattered by $\mathcal{H}$.

Definition 7 (Adversarial Natarajan Dimension). *Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class and let $S \subset \mathcal{X}$.*
We say that $\mathcal{H}$ adversarially N-shatters S if there exist $f_1, f_2 : \mathcal{X} \to \mathcal{Y}$ such that $\forall y \in S, f_1(y) \neq$
$f_2(y)$, and for every $T \subset S$, there is a $g \in \mathcal{H}$ such that

$$\forall x \in T, \forall x' \in \mathcal{U}(x), g(x') = f_1(x)$$

and

$$\forall x \in S\backslash T, \forall x' \in \mathcal{U}(x), g(x') = f_2(x).$$

211 *The adversarial Natarajan dimension (AN-dimension) of $\mathcal{H}$, denoted by $d_N^{\mathcal{U}}(\mathcal{H})$, is the maximal*
212 *cardinality of a set that is adversarially N-shattered by $\mathcal{H}$.*

213 Based on this definition, we present that:

Theorem 6. *There are absolute constants $C > 0$ such that for every $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,*

$$m^{re}_{\mathcal{H},\mathcal{U}}(\epsilon,\delta) \geq C\left(\frac{d^{\mathcal{U}}_N(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon}\right), \quad and \quad m^{ag}_{\mathcal{H},\mathcal{U}}(\epsilon,\delta) \geq C\left(\frac{d^{\mathcal{U}}_N(\mathcal{H}) + \ln(\frac{1}{\delta})}{\epsilon^2}\right).$$

214 *Proof.* Let $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$ be a hypothesis class such that $d^{\mathcal{U}}_N(\mathcal{H}) = d$, and let $\mathcal{H}_d = \{0,1\}^{[d]}$ be the
215 family of all mappings from $[d]$ to $\{0,1\}$. We want to show that for every learning algorithm $\mathcal{A}$ for
216 $\mathcal{H}$ and every $\epsilon,\delta \in (0,1)$, there exists a learning algorithm $\bar{\mathcal{A}}$ satisfying: if there exists a function
217 $m^{re}_{\mathcal{A},\mathcal{U}} : (0,1)^2 \to \mathbb{N}$ such that when $\mathcal{A}$ witnesses $m > m^{re}_{\mathcal{A},\mathcal{U}}(\epsilon,\delta)$ samples (denoted as S) drawn
218 i.i.d from some distribution $\mathcal{D}, \mathbb{P}[R_{\mathcal{U}}(\mathcal{A}(S);\mathcal{D}) \leq \epsilon] > 1 - \delta$. Then when $\bar{\mathcal{A}}$ witnesses m samples
219 (denoted as S') drawn i.i.d from some distribution $\mathcal{D}'$ on $[d] \times \{0,1\}, \mathbb{P}[R_{\mathcal{I}}(\bar{\mathcal{A}}(S');\mathcal{D}') \leq \epsilon] > 1-\delta$
220 holds. By this claim, we have $m^{re}_{\bar{\mathcal{A}},\mathcal{I}} \leq m^{re}_{\mathcal{A},\mathcal{U}}$, thus $m^{re}_{\mathcal{H}_d,\mathcal{I}} \leq m^{re}_{\mathcal{H},\mathcal{U}}$. Note that VC $(\mathcal{H}_d) = d$, so by
221 Theorem 1 we have $m^{re}_{\mathcal{H},\mathcal{U}}(\epsilon,\delta) \geq C(\frac{d+\ln(1/\delta)}{\epsilon})$ for some constant $C > 0$ (independent of $\mathcal{H}$), and
222 similarly for the agnostic case.

223 We now prove the claim. Let $\{s_1,\ldots,s_d\} \subset \mathcal{X}$ be a set and let f_0, f_1 be functions that witness
224 the adversarial N-shattering of $\mathcal{H}$. Given a sample set $S' \triangleq \{(x_i,y_i)\}^m_{i=1} \subset [d] \times \{0,1\}$, let $g = $
225 $\mathcal{A}(\{s_{x_i}, f_{y_i}(s_{x_i})\}^m_{i=1})$. Consider the learning algorithm $\bar{\mathcal{A}} : \cup^{\infty}_{n=0}([d] \times \{0,1\})^n \to \mathcal{H}_d$:

$$\bar{\mathcal{A}}(S')(j) = \begin{cases} 1, & g(s'_j) = f_1(s_j), \forall s'_j \in \mathcal{U}(s_j), \\ 0, & \text{otherwise.} \end{cases}$$

226 Denote $\bar{\mathcal{A}}(S')$ by f. By the definition of adversarial N-shattering, it can be derived that $f(j) = 0$ if
227 and only if $g(s'_j) = f_2(s_j), \forall s'_j \in \mathcal{U}(s_j)$. By the construction we have

$$\mathbb{E}_{(j,y)\sim\mathcal{D}'}[\mathbb{1}(f(j) \neq y)] = \mathbb{E}_{(j,y)\sim\mathcal{D}'}[\sup_{s'_j\in\mathcal{U}(s_j)}\mathbb{1}(g(s'_j) \neq f_y(s_j))] = \mathbb{E}_{(x,y)\sim\hat{\mathcal{D}}'_m}R_{\mathcal{U}}(g;\hat{\mathcal{D}}'_m),$$

228 where $\hat{\mathcal{D}}'_m$ is defined by $\mathbb{P}_{\hat{\mathcal{D}}'_m}(X = s_j, Y = f_y(s_j)) = \mathbb{P}_{\mathcal{D}'}(J = j, B = y)$. □

5   The AG/AN-dimension of linear multiclass predictors

230 In this section, we calculate the AG-dimension and AN-dimension for linear multiclass predictors
231 under bounded l_p perturbation, motivated by the binary results of [7] and the non-adversarial results of
232 [14]. Recall the definition of linear multiclass predictors. Let $\Psi : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}^{dk}$ be a class-sensitive
233 feature mapping [17]:

$$\Psi(x,y) = [\underbrace{0,\ldots,0}_{\in\mathbb{R}^{(y-1)d}}, \underbrace{x^{(1)},\ldots,x^{(d)}}_{\in\mathbb{R}^d}, \underbrace{0,\ldots,0}_{\in\mathbb{R}^{(k-y)d}}],$$

234 where $x^{(i)}$ represents the i^{th} coordinate of x. The class of linear multiclass predictors is defined as

$$\mathcal{H}_{\Psi} = \{x \mapsto \arg\max_{i\in\mathcal{Y}}\langle w, \Psi(x,i)\rangle : w \in \mathbb{R}^{dk}\}. \tag{3}$$

235 We cite that the graph dimension and Natarajan dimension of $\mathcal{H}_{\Psi}$ is given by $(d-1)(k-1) \leq$
236 $d_N(\mathcal{H}_{\Psi}) \leq d_G(\mathcal{H}_{\Psi}) \leq O(dk\ln(dk))$ [14]. We then present the theorems, showing that the AG-
237 dimension and AN-dimension also satisfy this bound.

238 **Theorem 7.** *Let $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \leq r\}$ for some $r \in \mathbb{R}^+$ and $p \in \mathbb{R}^+ \cup \{\infty\}$, and let*
239 *$\mathcal{H}_{\Psi}$ be as defined in 3. Then, the AN-dimension of $\mathcal{H}_{\Psi}$ satisfies $d^{\mathcal{U}}_N(\mathcal{H}_{\Psi}) = d_N(\mathcal{H}_{\Psi})$.*

240 *Proof.* Since adversarial N-shattering implies N-shattering, we have $d^{\mathcal{U}}_N(\mathcal{H}_{\Psi}) \leq d_N(\mathcal{H}_{\Psi})$. To prove
241 the inverse inequality, it should be noted that the classifiers in $\mathcal{H}_{\Psi}$ are linear, hence if $\mathcal{H}_{\Psi}$ N-shatters
242 S, it also N-shatters the set with some $x \in S$ replaced by $\forall x' \in l_x$, where l_x is the half-line which
243 terminates at 0 and goes through x. For those $x \in S$ that cannot be adversarially N-shattered by $\mathcal{H}_{\Psi}$,
244 we can always find some $x' \in l_x$ such that $\mathcal{U}(x')$ does not cross the decision boundary of g_T that
245 witnesses the N-shattering for all $T \in S$. □

246 **Corollary 1.** *Under the conditions of Theorem 7, $(d-1)(k-1) \leq d_N^{\mathcal{U}}(\mathcal{H}_\Psi) \leq dk$.*

247 *Proof.* Combine Theorem 7 and $(d-1)(k-1) \leq d_N(\mathcal{H}_\Psi) \leq dk$ (Corollary 29.8 in [18]). □

Theorem 8. *Let $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_p \leq r\}$ for some $r \in \mathbb{R}^+$ and $p \in \mathbb{R}^+ \cup \{\infty\}$, and let $\mathcal{H}_\Psi$ be as defined in 3. Then, the AG-dimension of $\mathcal{H}_\Psi$ satisfies*

$$(d-1)(k-1) \leq d_G^{\mathcal{U}}(\mathcal{H}_\Psi) \leq O(dk \ln(dk)).$$

248 To prove this result, we first present a lemma, which can be viewed as the generalization of Sauer's
249 Lemma [19] in the adversarial setting. We first define the restriction of a corrupted class. Let $\tilde{\mathcal{H}}$ be
250 the corrupted hypothesis class induced by $\mathcal{U}$. Let $S = \{x_1, \ldots, x_m\} \subset \mathcal{X}$. Fix a $f \in \mathcal{Y}^S$, for each
251 $h \in \mathcal{H}$, define $h_f : S \to \{0,1\}$ such that $h_f(x_i) = 1$ if and only if $\kappa_{\mathcal{U}}(h)(x_i) = f(x_i), i \in [m]$.
252 Define $\mathcal{H}_f = \{h_f : h \in \mathcal{H}\}$. The restriction of $\tilde{\mathcal{H}}$ to S is defined by:

$$\tilde{\mathcal{H}}|_S = \mathcal{H}_{f*}|_S, \quad \text{where } f^* = \arg\max_{f \in \mathcal{Y}^S} \left| \mathcal{H}_f|_S \right|.$$

Lemma 3. *Let $\mathcal{U}$ be an adversary and $\mathcal{H}$ be a hypothesis class with $d_G^{\mathcal{U}}(\mathcal{H}) \leq d_G < \infty$. Let $\tilde{\mathcal{H}}$ be the corrupted hypothesis class induced by $\mathcal{U}$. Let $S = \{x_1, \ldots, x_m\} \subset \mathcal{X}$. Then, for all $m > d_G + 1$ we have*

$$|\tilde{\mathcal{H}}|_S| \leq \left(\frac{em}{d_G} \right)^{d_G}.$$

253 *Proof.* By Sauer's Lemma [19] and the fact that $\text{VC}(\mathcal{H}_f) \leq d_G^{\mathcal{U}}(\mathcal{H})$ for all $f \in \mathcal{Y}^S$. □

254 We now prove Theorem 8. The construction idea follows the proof of non-adversarial results in [14].

255 *Proof of Theorem 8:* The lower bound follows from Theorem 7 and the fact that $d_G^{\mathcal{U}}(\mathcal{H}) \geq d_N^{\mathcal{U}}(\mathcal{H})$
256 for all $\mathcal{H}$. To upper bound $d_G := d_G^{\mathcal{U}}(\mathcal{H})$, let $S = (x_1, \ldots, x_{d_G}) \in \mathbb{R}^d$ be a set which is adversarially
257 G-shattered by $\mathcal{H}_\Psi$, and let $f : S \to \mathcal{Y}$ be a function that witnesses the shattering. For every
258 $(i,j) \in [d_G] \times [k]$, define $z_{i,j} = \Psi(x_i, f(x_i)) - \Psi(x_i, j)$. Denote $Z = \{z_{i,j}|(i,j) \in [d_G] \times [k]\}$.
259 We now show that there exists a injective mapping from subsets of S to $\mathcal{W}_f^{dk}|_Z$, where $\mathcal{W}^{dk}$ is the
260 class of halfspace classifiers over $\mathbb{R}^{dk}$.

261 For each $T \subset S$, by the definition of adversarial G-shattering, $\exists h_T \in \mathcal{H}_\Psi$ such that

$$\forall x \in T, \forall x' \in \mathcal{U}(x), h_T(x') = f(x), \quad \text{and} \quad \forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), h_T(x') \neq f(x). \quad (4)$$

262 Let $w_T \in \mathbb{R}^{dk}$ be the vector defines h_T, 4 implies

$$\forall x \in T, \forall x' \in \mathcal{U}(x), \forall j \in [k], \langle w_T, \Psi(x', f(x)) \rangle \geq \langle w_T, \Psi(x', j) \rangle,$$

263 and

$$\forall x \in S \backslash T, \exists x' \in \mathcal{U}(x), \exists j \in [k], \langle w_T, \Psi(x', f(x)) \rangle < \langle w_T, \Psi(x', j) \rangle. \quad (5)$$

It can be easily derived from 5 that $\forall i \in I_{S \backslash T}, \exists j \in [k], \exists z' \in \mathcal{V}(z_{i,j})$ s.t. $\langle w_T, z' \rangle < 0$, where $\mathcal{V}$ is
the p-norm ball in $\mathbb{R}^{dk}$ with radius r. And from 5 we can assume w.l.o.g that $\forall i \in I_T, \forall j \in [k], \forall z' \in \mathcal{V}(z_{i,j}), \langle w_T, z' \rangle \geq 0$. This is because if there exists some $z' \in \mathcal{V}(z)$ s.t. $\langle w_T, z' \rangle < 0$, notice that
$z' = \mathcal{V}(c') + z_{i,j}$ for some bounded c', we can replace x_i by some x_i' without destroying the adversarial
G-shattering (see the trick used in proof of Theorem 7), to ensure $\langle w_T, \Psi(x_i', f(x_i)) - \Psi(x_i', j) \rangle > \langle w_T, c \rangle, \forall c \in \mathcal{V}(0)$. Consequently, for every $T \in S$ we obtain a label pattern $P_T : [d_G] \times [k] \to \{0,1\}$:

$$P_T(z_{i,j}) = \mathbb{1}(\min_{z' \in \mathcal{V}(z_{i,j})} \langle w_T, z' \rangle \geq 0).$$

264 It satisfies that $\forall i \in I_T, j \in [k], P_S(i,j) = 1$ and $\forall i \in I_{S \backslash T}, \exists j \in [k], P_T(i,j) = 0$, which implies
265 $P_T \neq P_{T'}$ for $T \neq T'$. And by definition P_T is connected with a unique element in $\mathcal{W}_f^{dk}|_Z$, which
266 completes the proof of our claim.

Note that the AG-dimension of halfspace classifier class with respect to $\mathcal{U}$ coincides with the definition of adversarial VC-dimension in [7]. Thus it satisfies that $d_G^{\mathcal{U}}(\mathcal{W}^{dk}) = dk + 1$ by Theorem 2 in [7]. Consequently, we have

$$|2^S| = 2^{d_G} \leq \left| \mathcal{W}_f^{dk} |_Z \right| \leq \left| \widetilde{\mathcal{W}^{dk}} |_Z \right| \overset{(i)}{\leq} \left(\frac{e|Z|}{d_G^{\mathcal{U}}(\mathcal{W}^{dk})} \right)^{d_G^{\mathcal{U}}(\mathcal{W}^{dk})} \leq (kd_G)^{dk+1},$$

where we have used Lemma 3 in step (i). We conclude that $d_G \leq O(dk \ln dk)$. $\qquad\square$

6 AG-dimension and AN-dimension are not equivalent

In previous sections, we have shown that the finiteness of the AN-dimension is a necessary condition for robust learnability, and the finiteness of the AG-dimension is a sufficient condition for robust learnability. Furthermore, we analyze these definitions on the linear multiclass predictor class, finding that the AG-dimension (AN-dimension) matches the order of the graph dimension (Natarajan dimension) for this class. The following question therefore naturally arises: are these two quantities equivalent? In [5], it is proven that for every hypotheses class $\mathcal{H} \subset \mathcal{Y}^{\mathcal{X}}$,

$$d_N(\mathcal{H}) \leq d_G(\mathcal{H}) \leq 4.67 \log_2(k) d_N(\mathcal{H}). \tag{6}$$

That is, in standard learning setting, if $k \leq \infty$ then the definition of the Natarajan dimension and the graph dimension are indeed equivalent, hence both the Natarajan dimension and graph dimension can characterize the standard learnability of a hypothesis class. However, in the adversarial setting ($\mathcal{U} \neq \mathcal{I}$), the generalized definitions derived above cannot bound each other. To show this, we claim that finite AN-dimension is not sufficient for robust learnability.

Theorem 9. *There exist $\mathcal{H}, \mathcal{U}$ such that $d_N^{\mathcal{U}}(\mathcal{H}) = 0$ but $\mathcal{H}$ is not robustly PAC learnable under $\mathcal{U}$, i.e. $m_{\mathcal{H},\mathcal{U}}^{ag}(\epsilon, \delta) = \infty$.*

Proof. Let $\mathcal{U}$ be the 2-norm ball: $\mathcal{U}(x) = \{z \in \mathcal{X} : \|z - x\|_2 \leq r\}$ for all $x \in \mathcal{X}$ and some $r > 0$. We construct $\mathcal{H}$ as follow. Pick a sequence $\{x_i\}_{i=1}^{\infty} \subset \mathcal{X}$ such that for any $i \neq j, \mathcal{U}(x_i) \cap \mathcal{U}(x_j) = \emptyset$. Let $f : \mathcal{X} \to \mathcal{Y}$ be a function satisfying: there exists $z_i \in \mathcal{U}(x_i) \backslash x_i$ such that $f(z_i) \neq f(x_i)$ for each $i \in \mathbb{N}$. For each sequence $b = \{b_i\}_{i=1}^{\infty} \subset \{0, 1\}$, define $h_b : \mathcal{X} \to \mathcal{Y}$:

$$h_b(x) = \begin{cases} f(x_i), & x \in \mathcal{U}(x_i) \backslash z_i, \quad i \in \mathbb{N}, \\ f(x_i), & x = z_i \text{ and } b_i = 1, \\ f(z_i), & x = z_i \text{ and } b_i = 0, \\ 1, & \text{otherwise.} \end{cases}$$

Let $\mathcal{H} = \{h_b : b \text{ is a sequence in } \{0, 1\}\}$. Using the same approach employed in the proof of Lemma 1, for any learning rule $\mathcal{A} : (\mathcal{X} \times \mathcal{Y})^* \to \mathcal{H}$, there exists a distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$ such that there exists a function $f^* \in \mathcal{H}$ with $R_{\mathcal{U}}(f^*; \mathcal{D}) = 0$, and with probability of at least $1/7$ over the choice of $S \sim \mathcal{D}^m$ we have that $R_{\mathcal{U}}(\mathcal{A}(S); \mathcal{D}) \geq 1/8$, by considering the distribution family $\mathfrak{D}$ containing distributions that are uniform over $2m$ points in $\{(x_1, f(x_1)), \ldots, (x_{3m}, f(x_{3m}))\}$. We complete the proof by noting that $d_N^{\mathcal{U}}(\mathcal{H}) = 0$, since there is no single r-ball that is adversarially N-shattered by $\mathcal{H}$. $\qquad\square$

7 Discussion

In this work, we construct the concepts of AG-dimension and AN-dimension to upper bound and lower bound the sample complexity of robust multiclass learning, respectively. However, it is not yet clear whether finite AG-dimension is also necessary for robust multiclass learning. Establishing a complexity measure that characterizes robust learnability still remains an open question.

References

[1] Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE SP*, pages 39–57, 2017.

[2] Nicholas Carlini and David A. Wagner. Audio adversarial examples: Targeted attacks on speech-to-text. In *IEEE SP*, pages 1–7, 2018.

[3] B. K. Natarajan. On learning sets and functions. *Machine Learning*, 4:67–97, 1989.

[4] Vladimir Naumovich Vapni. *The Nature of Statistical Learning Theory*. Springer, 1995.

[5] Shai Ben-David, Nicolò Cesa-Bianchi, David Haussler, and Philip M. Long. Characterizations of learnability for classes of {0, ..., n}-valued functions. *Journal of Computer and System Sciences*, 50(1):74–86, 1995.

[6] Omar Montasser, Steve Hanneke, and Nathan Srebro. VC classes are adversarially robustly learnable, but only improperly. In *COLT*, volume 99, pages 2512–2530, 2019.

[7] Daniel Cullina, Arjun Nitin Bhagoji, and Prateek Mittal. Pac-learning in the presence of adversaries. In *NeurIPS*, pages 228–239, 2018.

[8] Justin Khim and Po-Ling Loh. Adversarial risk bounds for binary classification via function transformation. *CoRR*, abs/1810.09519, 2018.

[9] Robi Bhattacharjee, Somesh Jha, and Kamalika Chaudhuri. Sample complexity of robust linear classification on separated data. In *ICML*, volume 139 of *Proceedings of Machine Learning Research*, pages 884–893, 2021.

[10] Arjun Nitin Bhagoji, Daniel Cullina, and Prateek Mittal. Lower bounds on adversarial robustness from optimal transport. In *NeurIPS*, pages 7496–7508, 2019.

[11] Dimitrios I. Diochnos, Saeed Mahloujifar, and Mohammad Mahmoody. Lower bounds for adversarially robust PAC learning under evasion and hybrid attacks. In *ICMLA*, pages 717–722, 2020.

[12] Nicolò Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games*. Cambridge University Press, 2006.

[13] David Haussler and Philip M. Long. A generalization of sauer's lemma. *Journal of Combinatorial Theory, Series A*, 71(2):219–240, 1995.

[14] Amit Daniely, Sivan Sabato, and Shai Shalev-Shwartz. Multiclass learning approaches: A theoretical comparison with implications. In *NeurIPS*, pages 494–502, 2012.

[15] Dong Yin, Kannan Ramchandran, and Peter L. Bartlett. Rademacher complexity for adversarially robust generalization. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pages 7085–7094, 2019.

[16] Peter L. Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3:463–482, 2002.

[17] Koby Crammer and Yoram Singer. On the algorithmic implementation of multiclass kernel-based vector machines. *Journal of Machine Learning Research*, 2:265–292, 2001.

[18] Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning - From Theory to Algorithms*. Cambridge University Press, 2014.

[19] Norbert Sauer. On the density of families of sets. *Journal of Combinatorial Theory, Series A*, 13(1):145–147, 1972.