NOT ALL TASKS ARE BORN EQUAL: UNDERSTANDING ZERO-SHOT GENERALIZATION

ABSTRACT

Recent work has achieved remarkable zero-shot performance with multi-task prompted pretraining, but little has been understood. For the first time, we show that training on a small number of key tasks beats using all the training tasks, while removing these key tasks substantially hurts performance. We also find that these key tasks are mostly question answering (QA) tasks. We design a shuffle experiment to further show that training on these QA tasks leads to better cross-task generalization in multi-task learning under various training/test task splits. These novel findings combined deepen our understanding about zero-generalization— training on certain tasks such as QA encodes general knowledge transferable to a wide range of tasks, which explains the improved zero-shot performance in recent progress. In addition, to automate this procedure, we devise a method to identify and upsample key training tasks without observing the test tasks based on cross validation. Empirically, our approach achieves improved results across various model scales and tasks.[1]

1 INTRODUCTION

Recent work (Brown et al., 2020; Artetxe et al., 2021; Rae et al., 2021) has demonstrated the potential of leveraging pretrained language models (PLMs) to perform zero-shot generalization. Zero-shot generalization enables PLMs to adapt to a variety of natural language processing (NLP) tasks without relying on any annotated data, which opens the possibility towards generic systems.

Pretrained models, such as GPT-3 (Brown et al., 2020), BERT (Devlin et al., 2018) and T5 (Raffel et al., 2019), can perform zero-shot inference on unseen test tasks by leveraging natural language prompts and formulating NLP tasks into language modeling tasks. More recent advances (Wei et al., 2021; Sanh et al., 2021) performed **multi-task prompted training** on PLMs and further enhanced the zero-shot performance to a large extent. Despite the substantial progress, few works have studied how multi-task prompted training boosts the zero-shot performance. The lack of understanding hinders further improvement of the field.

To this end, we take a further step to understand multi-task training for zero-shot generalization (1) by selecting only a small number of dominating training tasks and performing multi-task training and (2) by studying the characteristics of tasks with general transfer ability. The results reveal several interesting findings — First of all, only a small number of training tasks dominate the performance of zero-shot generalization. In other words, using only these dominating training tasks to perform multi-task training leads to good results while removing these dominating tasks would drastically hurt the zero-shot performance. Secondly, not all tasks are born equal, and some tasks show general transfer ability by providing widely useful knowledge. Moreover, dominant tasks with general transfer ability can be automatically detected using pairwise generalization results.

In addition, based on the findings, we propose an improved method, **task reweighting** , which improves multi-task training for zero-shot generalization to a large extent. Task reweighting first automatically identifies a set of key training tasks based on cross validation without peeking forward any test tasks, and then performs reweighting by upsampling dominating tasks or downsampling non-critical tasks, as shown in Figure 2. In this way, we build a better mixture of multi-task training sets to highlight those dominant tasks with better general transfer ability. Experiments show that

---

[1]We will release our code upon acceptance.

task reweighting consistently outperforms the previous approach T0 (Sanh et al., 2021) across three different model scales and on test tasks of various types.

To sum up, our contributions are as follows.

1. We conduct experiments to understand and reveal how multi-task training for zero-shot generalization works—(1) Only a small number of training tasks dominate zero-shot generalization; (2) Some dominant tasks provide general transfer ability and can be detected using pairwise generalization results.

2. We devise a novel method, task reweighting , to improve zero-shot generalization by (1) first automatically identifying key training tasks based on cross validation without observing any test tasks, and (2) reweighting training tasks using upsampling and downsampling strategies.

3. Experiments show that our approach achieves new state-of-the-art results across various model scales and tasks.

2 RELATED WORK

2.1 ZERO-SHOT LEARNING IN NLP

Zero-Shot Learning denotes no data correlated with the test set is available during the training stage. The early definition of zero-shot learning referred to predicting samples with unseen classes, so traditional methods require prior information such as semantic knowledge (Zhang et al., 2019a) or knowledge graph (Chen et al., 2021) for an unseen class so that model can predict that class without training data. Meta-learning (Zhang et al., 2022) and reinforcement learning (Ye et al., 2020) methods are also used for zero-shot learning.

Nowadays, more work focuses on the setting of predicting samples with unseen tasks, supported by the development and prevalence of pre-trained language models (PLMs), as well as multi-task training. McCann et al. (2018) unifies NLP tasks into QA-format to perform multi-task learning. Liu et al. (2019) designs a multi-task deep neural network for natural language understanding tasks. Aghajanyan et al. (2021) designs an intermediate training stage between pretraining and finetuning using around 50 tasks. Most recently, with the combination of the above two approaches, T0 and FLAN (Sanh et al., 2021; Wei et al., 2021) have shown that explicit multi-task prompted training where all tasks are unified by the natural language prompts can vastly promote zero-shot task generalization. We stand on the shoulder of this new paradigm and devote ourselves to improving the recipe of multi-task prompted training by revealing the mechanism of generalization in Section 3 and further enhancing its performance in Section 4.

2.2 THE INTERPRETATION OF PROMPTED LEARNING

Nowadays, researchers have shown an increased interest in how the prompts help the model generalize to unseen tasks. Some researchers (Wei et al., 2021; Schick & Schütze, 2020; Mishra et al., 2022) suggest that the model learns to understand what they are doing through prompts. While some work (Webson & Pavlick, 2022; IV et al., 2022) challenges this assumption, revealing that sometimes we could get comparable performance without prompts or even wrong prompts.

T0 (Sanh et al., 2021) claims that they only empirically witness the transfer phenomenon, but it is unclear why it happens. We provide new insights into the reason for generalization. We challenge the idea that the model learns the task through instructions, based on the observation that deleting a small but important set of tasks will lead to transfer failure. We suggest that most generalization ability comes from dominant tasks, which could be divided into specific and general transfer abilities. We hope our discovery could promote the development of this field.

2.3 TRANSFER RELATIONSHIPS IN MULTI-TASK LEARNING

Based on the observation that transfer ability comes from dominant tasks, we would like to further improve the zero-shot performance by exploring the transfer relationships in multi-task learning. Some previous works learn transfer relationships in supervised multi-task training. Taskonomy (Zamir et al., 2018) builds a transfer structure of a series of computer vision tasks by training

task-specific encoders on each dataset and retraining the decoders on target datasets. Dwivedi & Roig (2019) and Song et al. (2019) obtain the transfer relationship based on the assumption that transferable task-specific models have similar representations or embeddings on the same data. Song et al. (2019) learns the embedding of each NLP task and tries to predict the transfer relationship between different datasets. ExT5 (Aribandi et al., 2021) learns the transferability by co-training the source task and target task and evaluate on the target task. UnifiedQA (Khashabi et al., 2020) explores the transferability between different QA tasks. The major challenge lies in that we could not get access to the test task at the training stage, thus hard to figure out in advance which training tasks can be more useful for unseen tasks. To address this challenge, we propose a reweighting method based on the transfer performance of pairwise training tasks, which will be discussed in Section 4.

2.4 DATA AUGMENTATION IN NLP

Data Augmentation is widely used in NLP to strengthen the robustness and diversity of the data distribution and promote the model performance. However, most of the approaches are conducted in word-level (Zhang et al., 2015; Wang & Yang, 2015; Wei & Zou, 2019) and sentence-level (Kafle et al., 2017; Hou et al., 2018; Khashabi et al., 2018; Zhang et al., 2018), or in other words, instance-level. In our paper, to naturally cater for the multi-task setting, we adopt a new perspective and design a cross-domain data augmentation which intersects each domain data with different kinds of tasks, which significantly improves the diversity of data distribution.

3 UNDERSTANDING ZERO-SHOT TASK GENERALIZATION

In this section, we focus on understanding how multi-task training contributes to the generalization on unseen tasks. By revealing the mechanism of task transfer, we provide some insights for further improvements of zero-shot performance.

3.1 DATA

We followed the setting of T0 (Sanh et al., 2021) and adopted the tasks therein. There are 38 training tasks across 8 task types, and 11 test tasks ranging from natural language inference (RTE (Candela et al., 2006), CB (De Marneffe et al., 2019), ANLI/R1-R3 (Nie et al., 2020)), coreference resolution (WSC (Levesque et al., 2012), Winogrande (Sakaguchi et al., 2020)), sentence completion (COPA (Roemmele et al., 2011), StoryCloze (Mostafazadeh et al., 2017), Hellaswag (Zellers et al., 2019)), to word disambiguation (WiC (Pilehvar & Camacho-Collados, 2018)). Both training and test sets are disjoint in task types, thus guaranteeing the zero-shot setting. We report the mean and median accuracy over multiple prompts for each test task.

3.2 A SMALL NUMBER OF KEY TASKS DOMINATE PERFORMANCE

Since there has been little agreement on where the excellent zero-shot generalization performance comes from, we would like to conduct experiments to explore its mechanism. Some researchers believe that the model understands the prompts through multi-task training (Wei et al., 2021; Schick & Schütze, 2020; Mishra et al., 2022), while we take an orthogonal perspective and hypothesize that there might be a few key tasks that are crucial for the zero-shot generalization performance. To verify this hypothesis, we first conduct an experiment by training one model using only a small number of tasks in the T0 training set, and evaluation is conducted on the normal T0 test set.

Experimental Settings For a straightforward verification of the above hypothesis, we manually select the top-8 tasks out of the 38 training tasks of T0. These selected tasks empirically demonstrate good generalization to the test tasks according to preliminary experiments. Specifically, each of the top-8 key tasks alone has shown appealing improvements on at least two test datasets (see Figure 1 for reference). The top-8 selected tasks are CosmosQA (Huang et al., 2019), Social IQA (Sap et al., 2019), PAWS (Zhang et al., 2019b), QuAIL (Rogers et al., 2020), WikiQA (Yang et al., 2015), QuaRTz (Tafjord et al., 2019), QASC (Khot et al., 2020), and ROPES (Lin et al., 2019).

For comparison, we experimented with three different variants by training a T5-Large model using only top-8 tasks ("Top-8 Only") and all but the top-8 tasks ("T0 Tasks w/o Top-8"), respectively.

| Train Tasks | Met. | Natural Language Inference | | | | | Sentence Completion | | | Co-Reference | | WSD. | Avg. |
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC	
All T0 Tasks	Mean	72.53	50.60	30.93	31.96	32.23	82.20	27.16	92.05	62.21	52.00	50.14	53.09
	Med.	74.01	57.14	30.40	31.60	31.75	83.00	27.60	91.77	62.98	52.33	50.00	54.87
Top-8 Only	Mean	**73.10**	**66.55**	**33.55**	32.46	**36.34**	**84.62**	**30.93**	**94.51**	**64.04**	**53.02**	**50.52**	**56.33**
	Med.	**74.91**	**71.42**	**33.10**	32.10	**36.42**	**84.50**	**30.96**	**94.76**	**65.38**	**52.96**	**50.16**	**56.97**
T0 Tasks w/o Top-8	Mean	60.47	44.17	30.68	**32.81**	32.87	67.07	26.46	68.81	51.83	51.29	50.92	47.03
	Med.	60.29	44.64	30.80	**33.00**	33.33	66.83	26.65	72.53	47.12	51.54	50.71	47.04

Table 1: Zero-shot performance of training with top-8 tasks (out of 38) on T5-Large. The top-8 tasks are CosmosQA, SocialIQA, PAWS, QuAIL, WikiQA, QuaRTz, QASC, and ROPES. "Top-8 Only" means using only the top-8 tasks. "T0 Tasks w/o Top-8" means using the T0 tasks with top-8 tasks removed. Results that are comparable to or outperform the T0 baseline are denoted in bold.

Results and Analysis From Table 1, we observe that training with only the top-8 tasks outperforms training with all tasks when tested on 11 test tasks, while training with all but the top-8 tasks drastically decreases performance.

These results demonstrate that the selected top-8 tasks play an important role in zero-shot generalization. Although there are 38 training tasks in total, a small number of tasks determine the zero-shot performance. It is generally agreed that training with more tasks should lead to better learning of prompts, but our experiments show that this is not the key reason for the performance improvement. It is the information contained in key tasks that contributes to zero-shot generalization. This result raises a further question whether the model learns to read, understand and react to instructions broadly from all tasks, or just benefit from several dominant tasks which have strong general transferability.

To sum up, based on the aforementioned results and analysis, we arrive at the following finding.

Finding 1. A few key tasks contribute to the zero-shot task generalization, and using the selected top-8 training tasks by post hoc test results can achieve better performance than all training tasks.

3.3 GENERAL TRANSFER AND SPECIFIC TRANSFER

First of all, we divide the transfer ability into specific transfer ability and general transfer ability according to the scope of target tasks.

Specific transfer ability means that the task can only provide special knowledge for a small set of tasks with certain kinds of patterns. A typical example is the sentiment analysis task, which help the sentiment analysis tasks of different domains a lot, but has little effect on other complex NLU tasks.

General transfer ability means that the task can provide knowledge that is required by most downstream tasks. The more it provides beyond the knowledge captured by the pretrained model, the better it will contribute to the overall transfer ability of the model. For example, adding question answering (QA) tasks will improve the performance on most of the downstream tasks, which could be because they provide valuable commonsense and reasoning.

After introducing the division of transfer ability, we raise two questions based on the experimental results shown in Section 3.2. (1) Do the key tasks embrace the ability of general transfer or specific transfer? (2) Can we reveal the common patterns or characteristics shared by the tasks with general transfer ability?

To answer these questions, we set up another experiment to study the pairwise transfer results between all pairs of tasks. Specifically, for any pair of task in the T0 collection, we train on one task and evaluate on the other. We expect to decouple the effects of multi-task learning and observe patterns to answer the above questions. Results are shown in Figure 1.

For the first question, we can see from the figure that most of the tasks selected in post hoc experiments bring improvements on a wide range of tasks, and thus have a certain degree of general transfer ability. This also indicates that key tasks can be possibly predicted by examining the pairwise transfer results.

For the second question, we can observe that the question answering (QA) tasks show strong transfer ability to other task families, while other task families do not. This indicates that some QA tasks may have some special properties, which may help us design more general transfer-capable tasks in the future. To explore the characteristics of these QA tasks, we take a closer look at them in the next section.

Figure 1: Pairwise transfer relationships. The entry at row i and column j denotes the average performance training on task i and evaluate on task j. For each entry, the value is the average scores of different prompts. (Accuracy if only Accuracy is calculated, and otherwise the mean of Accuracy and F1.) Only those prompts related to the original tasks are included for evaluation. We highlight those entries with high scores for each task.

3.4 NOT ALL TASKS ARE BORN EQUAL

Some QA Tasks Show General Transfer Ability We first conduct experiments to further verify the robustness of the general transfer ability of QA tasks. In other words, we are interested in knowing whether QA tasks always play a vital role in multi-task learning when combined with different splits of training and test tasks. Specifically, we randomly split the remaining task types for training and testing, and then compare the multi-task training results with and without those "key" tasks.

In detail, the whole process is shown below, repeated three times.

1. We select 8 key tasks (denoted as D_{key}) from extractive QA and multiple-choice QA and randomly split the remaining 10 task types into training (8 task types) and testing (2 task types).

2. Denote all tasks D (including all training tasks and test tasks in T0), and splited test tasks D_{test}. Randomly choose the same number of non-dominant tasks D_{rand}.

3. Training with $D - D_{test}$, $D - D_{test} - D_{key}$, $D - D_{test} - D_{rand}$ respectively, and evaluate on D_{test}.

Results are in Table 2. We can see that training without dominant tasks D_{key} achieves a lower average performance than without non-dominant tasks D_{rand}. One exception is the experiment 2, where most of the test sets are generation tasks, and it seems that no tasks can transfer to them well.

This observation further proves that dominant tasks play an important role not only in single-task transfer but also in multi-task learning, strengthening the conclusion that they provide some generally useful knowledge. Therefore, we reach the following finding.

ID	$D - D_{test}$	$D - D_{test} - D_{key}$	$D - D_{test} - D_{rand}$
0	54.97	52.98	53.16
1	44.03	35.09	44.95
2	17.64	17.81	17.42

Table 2: Impact of key tasks. We detect the impact of key tasks in multi-task training by randomly spliting the tasks for training and testing. We report the result on D_{test} by training on $D - D_{test}$, $D - D_{test} - D_{key}$, and $D - D_{test} - D_{rand}$. The process is repeated for three times.

Finding 2. Not all tasks are born equal, and some tasks such as question answering show general transfer ability both in the single-task and multi-task settings.

Why QA Tasks Show General Transfer Ability? Experiments show that some QA tasks account a lot for general transfer ability, but it remains unknown why it works. We suspect some QA tasks provide some knowledge that is not captured in the pretraining process. From the examples in Table 3, we can see that both CosmosQA and SocialIQA require some simple reasoning ability in the general domain, which is required for a wide range of NLP tasks. More importantly, it is difficult to learn this knowledge in the pretraining stage, so an additional supplement is necessary to make the model have good cognitive ability. As a result, those tasks show better general transfer ability. There may be some quantitative methods to evaluate the knowledge provided by these tasks. A possible solution is to design some probe tasks, as is done in Pruksachatkun et al. (2020), and we leave this for future work.

CosmosQA	**Context:** So , last day in Seattle , and my flight was at 1:30 . I got to chit chat with my old manager (more like a mentor) , and left Seattle feeling really good and inspired . .
Question: Why did I chit chat with my old manager ?
Answer: Because I enjoy talking to him .
SocialIQA	**Context:** Cameron decided to have a barbecue and gathered her friends together.
Question: How would Others feel as a result?
Answer: like attending
Wiki_Hop	**Question:** participant_of juan rossell
Answer: 1996 summer olympics
WiQA	**Paragraph Step Context:** ["Plants and animals long ago died", "They are buried under layers of soil", "Pressure builds over time", "The remains liquefy", "The carbon atoms rearrange to become a new substance."]
Question: suppose a smaller satellites is determined happens, how will it affect less remains liquefy. **Answer:** no effect

Table 3: Examples of part of the QA tasks. CosmosQA and SocialIQA both show excellect general transfer ability, while Wiki Hop QA and WiQA don't. The biggest difference between them is the knowledge domain.

Which Kinds of QA Tasks Work? Another important observation is that not all QA tasks show general transfer ability. CosmosQA, SocialIQA, and QuAIL show outstanding transfer ability, while some tasks such as Wiki_Hop, and WiQA do not. Through a careful examination of the datasets, we conjecture that it is mainly because of the domain type. Take an extreme case for instance, training on datasets full of math problems is not likely to provide general transfer ability to other tasks. All of CosmosQA, SocialIQA, and QuAIL require commonsense knowledge that is useful in the general domain. However, the Wiki_Hop dataset urges the model to remember specific knowledge that is mainly required for knowledge contests.

So far, we have analyzed phenomena about the zero-shot task generalization ability. At the same time, three problems remain unsolved: (1) The test set cannot be seen in advance (2) We need to further distinguish which QA tasks are useful when a large number of QA tasks are provided (3) When the training set provided is changed, we need to distinguish new tasks with general transfer ability. For the above three reasons, we propose a general data-driven approach to identify tasks with general transfer capability.

4 AN IMPROVED METHOD: TASK REWEIGHTING

Figure 2: The pipeline of the improved multi-task prompted training recipe. We detect key tasks by examining the pairwise generalization results between training tasks. These key tasks are upsampled to form an optimized mixture of datasets.

4.1 METHOD

We have arrived at several findings in Section 3, revealing that (1) only a small number of training tasks dominate the performance of zero-shot generalization and (2) some key tasks with general transfer ability can be detected through pairwise generalization. Following the findings, we hypothesize that one of the key aspects of improving zero-shot performance is to appropriately adjust the weight of different training tasks, such that the model is trained with an optimized mixture of multi-task datasets. To this end, we devise a novel method, task reweighting , that first automatically identifies a set of key training tasks based on cross validation without observing any test tasks, and then re-weights the training tasks through upsampling or downsampling. Figure 2 shows an overview of our method.

Formally, we are given a set of training tasks $\mathcal{T} = \{t_i\}_i$ where t_i is a task, and a pretrained model $\mathcal{M}$. Each task is formulated as $t_i = \{x_{i,j}, y_{i,j}\}_j$, consisting of a prompted input $x_{i,j}$ and a prompted target $y_{i,j}$. Our goal is to assign appropriate weights $\{w_i\}_i$ for each training task, and use the optimized mixture of training tasks to train the model $\mathcal{M}$ in a multi-task manner such that it performs well on unseen test tasks.

Generally, our method consists of three major steps.

1. **Pre-detection of key tasks**. Identify key training tasks based on cross validation without relying on any test tasks. This can be viewed as a prior approximation to the post-hoc method in Section 3.2.
2. **Task reweighting**. Reweight different training tasks by upsampling key tasks or downsampling non-key tasks.
3. **Multi-task training**. Train a model using the reweighted mixture of multi-task datasets.

Pre-Detection of Key Tasks Without observing the test tasks, the main idea of our approach is to use cross validation within the training tasks. To identify the key tasks, we first train a model on each training task and evaluate it on all the training tasks. This results in a $N \times N$ (N is the number of training tasks) table, which is part of the results in Figure 1. Then we design a method to select key training tasks based on this $N \times N$ table. For each task pair A and B, let $f(A, B)$ be the performance of training on A and evaluating on B. We let $g(A, B) = 1$ if the following conditions are satisfied (and otherwise $g(A, B) = 0$):

1. A and B are of different task types.

2. The performance $f(A, B)$ is high enough:

$$f(A, B) \geq \max_{A' \neq B} f(A', B) - \text{TH}_1$$

and

$$f(A, B) \geq \text{mean}_{A' \neq B} f(A', B) + \text{TH}_2$$

Here TH_1 and TH_2 are two constants which control the tolerant distance between f(A, B) and maximum performance and average performance respectively. The value $g(A, B)$ indicates whether A is a high-performing training task for B. We constrain that A and B are of different types because we eventually target cross task generalization. We then aggregate $g(A) = \sum_B g(A, B)$ to represent how many times A is a high-performing training task for another task, and use the tasks with the largest $g(A)$ values as the key tasks. In our implementation, we apply thresholding on $g(A)$ to obtain the set of key tasks.

Task Reweighting by Upsampling or Downsampling After detecting the key tasks using only the training tasks, we propose a simple yet effective reweighting approach to optimize the mixture of multi-task data. We either perform upsampling or downsampling strategy. For upsampling, we upsample the key tasks by N_u times. For downsampling, we cap the number of samples to be N_d for each non-key tasks and use the original sample size for the key tasks. In our preliminary experiments, we found task reweighting more robust than using the key tasks only because it takes a softer approach to highlight the importance of key tasks while maintaining knowledge from other tasks.

Data Augmentation In the above sections, we have discussed an important discovery that certain tasks are crucial for zero-shot performance. However, some of these key tasks might be limited in terms of labeled data. Thus, we further propose a data augmentation method to create as many samples as possible for each task. Specifically, given tasks A and B, we apply the prompts of A to the data of B to obtain additional augmented data. In other words, we have more data from task B that are used to perform the task A. We use a trained T0 to predict the labels of the augmented samples, which is similar to self training. Note that data augmentation is optional and independent of task reweighting. We will do ablation study to investigate the effectiveness of this component.

Multi-Task Training Our training procedure is the same as T0. The only difference is that we employ an optimized mixture of datasets (and optionally with data augmentation).

4.2 EXPERIMENTAL SETUP

Following the same training and evaluation setting as T0 (Sanh et al., 2021), we finetune the T5 with language model adaptation (Raffel et al., 2019) on 38 training tasks, which has been discussed in detail in Section 3.1.

Based on our reweighting strategy, we set the pre-detection parameters as $TH_1 = 5$, $TH_2 = 10$, and then choose the datasets which are counted as the key tasks at least twice (i.e., all tasks A with $g(A) \geq 2$). Given each key task D with data size $|D|$, we duplicate D by 5 times ($N_u = 5$) for the upsampling strategy. For the downsampling strategy, we downsample each non-key task to $N_d = \min(50,000, |D|)$ samples.

4.3 RESULTS

Post-hoc v.s. Prior Detection of Key Tasks One vital part of our approach is the detection of key tasks, so we list the key tasks selected by post-hoc (i.e., observing the test tasks) and pre-detection methods in Table 4. There are five common tasks shared by the two methods, indicating that our approach can detect most of the key tasks. Moreover, our experiments show that even though the two sets of key tasks are not exactly matched, the results demonstrate that this does not affect performance.

Method	Key Tasks
Post-hoc	Cosmos QA, Social IQA, PAWS, Quail, WikiQA, QuaRTz, QASC, ROPES
Prior-detect	Cosmos QA, Adv./DBiDAF, Adv./DRoBERTa, QuaRTz, Social IQA, Hotpot QA, Adv./DBERT, ROPES, Quail

Table 4: Key Tasks selected by post-hoc and prior detection method. The underlined text represents the key tasks shared by both approaches.

Main Results We experiment with three scales: Large, XL, and XXL. We compare our proposed method with the original T0 reported in (Sanh et al., 2021) (T0 (†)) and our reproduced T0 (T0 (*)). Also, we present the results of task-reweighted T0, including T0 with upsampling key tasks (US-T0) and T0 with downsampling non-key tasks (US-T0). Besides, we display the performance of the task-reweighted T0 with augmented data, dubbed as US+DA-T0, DS+DA-T0 respectively. We summarize the following key observations from Table 5.

Model	Met.	Natural Language Inference					Sentence Completion			Co-Reference		WSD.	Avg.
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC	
T5-Large-LM-Adapt (770M)													
T0 (*)	Mean	72.53	50.60	30.93	31.96	32.23	82.20	27.16	92.05	62.21	52.00	50.14	53.09
	Med.	74.01	57.14	30.40	31.60	31.75	83.00	27.60	91.77	62.98	52.33	50.00	54.87
DS-T0	Mean	74.22	60.95	35.65	32.57	35.88	87.64	**28.29**	94.12	**63.75**	54.89	**51.60**	56.33
	Med.	75.45	66.07	36.00	32.40	36.50	87.50	**28.38**	94.01	64.42	55.33	51.41	57.04
DS+DA-T0	Mean	**80.72**	**71.90**	36.00	**34.80**	38.18	84.10	26.00	94.00	63.27	54.54	50.58	57.65
	Med.	**81.23**	**80.36**	36.40	**35.20**	39.33	85.21	26.06	94.39	63.94	54.38	50.31	58.80
US-T0	Mean	78.30	61.55	36.05	34.06	36.50	87.79	28.05	**94.97**	62.40	**55.52**	51.46	56.97
	Med.	79.00	69.60	36.10	33.90	36.75	89.00	28.14	**94.92**	64.42	**56.43**	50.39	58.06
US+DA-T0	Mean	80.69	70.95	**37.38**	34.20	**39.43**	**87.97**	26.73	93.71	63.27	55.58	51.47	**58.31**
	Med.	80.69	**80.35**	**38.00**	34.20	**40.33**	**89.29**	26.98	93.91	64.42	55.72	51.25	**59.56**
T5-XL-LM-Adapt (3B)													
T0 (†)	Mean	64.55	45.36	33.84	33.11	33.33	72.40	27.29	84.03	65.10	50.97	50.69	50.97
	Med.	64.08	50.00	33.65	33.40	33.33	74.92	27.51	85.09	64.42	50.51	50.39	51.57
T0 (*)	Mean	80.72	67.62	41.09	37.79	40.38	91.92	**32.03**	97.27	**65.96**	57.84	50.14	60.37
	Med.	80.14	75.00	42.80	39.20	41.75	92.00	**32.29**	97.22	**68.27**	58.41	50.00	61.62
DS-T0	Mean	83.21	73.33	44.38	38.84	43.72	94.17	31.21	**97.72**	64.42	62.67	52.01	62.34
	Med.	82.67	82.14	45.40	39.70	45.58	94.50	32.03	**97.70**	64.42	63.38	51.33	63.53
DS+DA-T0	Mean	**84.77**	74.40	43.25	**39.17**	43.22	**94.93**	27.01	97.65	**66.74**		53.09	62.39
	Med.	**84.66**	82.14	46.30	**39.70**	45.75	**95.00**	27.00	97.65	62.98	65.35	52.90	63.58
US-T0	Mean	82.41	69.38	43.20	38.40	40.72	93.55	30.30	97.25	61.41	60.56	**53.66**	60.99
	Med.	82.34	82.81	45.41	39.94	42.60	93.75	30.38	97.34	63.67	62.27	**52.66**	63.02
US+DA-T0	Mean	83.29	**75.83**	44.80	39.09	43.68	94.81	26.29	96.94	61.73	66.03	53.28	62.34
	Med.	84.48	**82.14**	**47.90**	39.90	47.25	94.50	26.17	97.06	64.90	65.11	52.98	63.85
T5-XXL-LM-Adapt (11B)													
T0 (†)	Mean	80.83	70.12	43.56	38.68	41.26	90.02	33.58	92.40	61.45	59.94	56.58	60.77
	Med.	81.23	78.57	44.70	39.40	42.42	90.79	33.65	94.71	64.42	60.46	57.21	62.51
T0 (*)	Mean	84.01	**72.26**	47.89	42.80	46.49	91.60	**35.27**	**98.15**	62.69	69.46	54.83	63.98
	Med.	85.02	**83.93**	49.00	44.00	48.58	95.00	**34.62**	**98.24**	66.35	70.24	52.35	66.12
Our Best	Mean	**85.56**	72.50	**48.28**	**43.81**	**47.62**	**95.18**	27.91	97.46	**67.02**	**71.41**	**56.29**	**64.82**
	Med.	**85.74**	82.14	**51.60**	**46.40**	**51.25**	**95.00**	27.71	97.54	**66.35**	**71.19**	**58.46**	**66.67**

Table 5: Zero-shot performance for our improved T0 and original T0 at three different scales. Results with † are reported by Sanh et al., and results with ⋆ are reproduced in our experiments. US-T0 means T0 with upsampling key tasks, DS-T0 means T0 with downsampling non-dominant tasks, and DS+DA-T0 / US+DA-T0 represents DS-T0 / US-T0 with augmented data.

1. Advantage of Task Reweighting. Our task-reweighted T0 with both upsampling and downsampling strategies (US-T0 and DS-T0) boosts the performance of reproduced T0. Specifically, DS-T0 outperforms T0 (*) by 3.2% at Large scale and 2.0% at XL scale, and US-T0 outperforms T0 (*) by 3.9% at Large scale and 0.6% at XL scale.

2. Advantage of Data Augmentation. Task-reweighted T0 achieves better performance with augmented data. Specifically, downsampling T0 (DS-T0) increases 1.3% with augmented data at Large scale and upsampling T0 (US-T0) increases 1.3% with augmented data at XL scale. And T0 with both task reweighting and augmented data achieves 0.8% gain with reproduced T0. It indicates that data augmentation can further strengthen the mixture of multi-task data.

3. Advantage of Our Implementation Framework. Our reproduced T0 result is better than the reported T0 (Sanh et al., 2021) by 9.4% at XL scale and 3.2% at XXL scale. [2]

5 CONCLUSIONS

This work studies the principles of zero-shot generalization through pairwise experiments, and reveals that a small number of training tasks dominate performance. We further divide the transfer relationship into specific transfer and general transfer, and find that adding those tasks with general transfer ability will contribute to the performance gain for most tasks. Moreover, those tasks with general transfer ability can be identified by examining the pairwise generalization results. Based on the findings, we propose the task reweighting method to improve the zero-shot performance. Extensive experiments demonstrate the effectiveness of our framework.

---

[2] The reason is unclear since T0 did not release the training code. We make sure to follow T0's setting and will release our code for reproduction.

6 REPRODUCIBILITY

We promise that our experiments are reproducible. We have clearly defined the data set, training framework and hyperparameters we used at the "experimental setup" part of each section (see Section 3.2 and Section 4.2 for more details). We also leave part of the training details and algorithm details in Appendix A. Last but not least, we will release our code upon acceptance.

REFERENCES

Armen Aghajanyan, Anchit Gupta, Akshat Shrivastava, Xilun Chen, Luke Zettlemoyer, and Sonal Gupta. Muppet: Massive multi-task representations with pre-finetuning. arXiv preprint arXiv:2101.11038, 2021.

Vamsi Aribandi, Yi Tay, Tal Schuster, Jinfeng Rao, Huaixiu Steven Zheng, Sanket Vaibhav Mehta, Honglei Zhuang, Vinh Q. Tran, Dara Bahri, Jianmo Ni, Jai Prakash Gupta, Kai Hui, Sebastian Ruder, and Donald Metzler. Ext5: Towards extreme multi-task scaling for transfer learning. CoRR, abs/2111.10952, 2021.

Mikel Artetxe, Shruti Bhosale, Naman Goyal, Todor Mihaylov, Myle Ott, Sam Shleifer, Xi Victoria Lin, Jingfei Du, Srinivasan Iyer, Ramakanth Pasunuru, et al. Efficient large scale language modeling with mixtures of experts. arXiv preprint arXiv:2112.10684, 2021.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. CoRR, abs/2005.14165, 2020.

Joaquin Quiñonero Candela, Ido Dagan, Bernardo Magnini, and Florence d'Alché-Buc (eds.). Machine Learning Challenges, Evaluating Predictive Uncertainty, Visual Object Classification and Recognizing Textual Entailment, First PASCAL Machine Learning Challenges Workshop, MLCW 2005, Southampton, UK, April 11-13, 2005, Revised Selected Papers, volume 3944 of Lecture Notes in Computer Science, 2006. Springer.

Qi Chen, Wei Wang, Kaizhu Huang, and Frans Coenen. Zero-shot text classification via knowledge graph embedding for social media data. IEEE Internet of Things Journal, 2021.

Marie-Catherine De Marneffe, Mandy Simons, and Judith Tonhauser. The commitmentbank: Investigating projection in naturally occurring discourse. In proceedings of Sinn und Bedeutung, volume 23, pp. 107–124, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. CoRR, abs/1810.04805, 2018.

Kshitij Dwivedi and Gemma Roig. Representation similarity analysis for efficient task taxonomy & transfer learning. In CVPR, pp. 12387–12396. Computer Vision Foundation / IEEE, 2019.

Yutai Hou, Yijia Liu, Wanxiang Che, and Ting Liu. Sequence-to-sequence data augmentation for dialogue language understanding. arXiv preprint arXiv:1807.01554, 2018.

Lifu Huang, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Cosmos QA: machine reading comprehension with contextual commonsense reasoning. In EMNLP/IJCNLP (1), pp. 2391–2401. Association for Computational Linguistics, 2019.

Robert L. Logan IV, Ivana Balazevic, Eric Wallace, Fabio Petroni, Sameer Singh, and Sebastian Riedel. Cutting down on prompts and parameters: Simple few-shot learning with language models. In ACL (Findings), pp. 2824–2835. Association for Computational Linguistics, 2022.

Kushal Kafle, Mohammed A Yousefhussien, and Christopher Kanan. Data augmentation for visual question answering. In INLG, pp. 198–202, 2017.

Daniel Khashabi, Snigdha Chaturvedi, Michael Roth, Shyam Upadhyay, and D. Roth. Looking beyond the surface: A challenge set for reading comprehension over multiple sentences. In NAACL-HLT, 2018.

Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. Unifiedqa: Crossing format boundaries with a single QA system. In EMNLP (Findings), volume EMNLP 2020 of Findings of ACL, pp. 1896–1907. Association for Computational Linguistics, 2020.

Tushar Khot, Peter Clark, Michal Guerquin, Peter Jansen, and Ashish Sabharwal. QASC: A dataset for question answering via sentence composition. In AAAI, pp. 8082–8090. AAAI Press, 2020.

Hector Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. In Thirteenth International Conference on the Principles of Knowledge Representation and Reasoning. Citeseer, 2012.

Kevin Lin, Oyvind Tafjord, Peter Clark, and Matt Gardner. Reasoning over paragraph effects in situations. In MRQA@EMNLP, pp. 58–62. Association for Computational Linguistics, 2019.

Xiaodong Liu, Pengcheng He, Weizhu Chen, and Jianfeng Gao. Multi-task deep neural networks for natural language understanding. arXiv preprint arXiv:1901.11504, 2019.

Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. The natural language decathlon: Multitask learning as question answering. arXiv preprint arXiv:1806.08730, 2018.

Swaroop Mishra, Daniel Khashabi, Chitta Baral, and Hannaneh Hajishirzi. Cross-task generalization via natural language crowdsourcing instructions. In ACL (1), pp. 3470–3487. Association for Computational Linguistics, 2022.

Nasrin Mostafazadeh, Michael Roth, Annie Louis, Nathanael Chambers, and James Allen. Lsdsem 2017 shared task: The story cloze test. In Proceedings of the 2nd Workshop on Linking Models of Lexical, Sentential and Discourse-level Semantics, pp. 46–51, 2017.

Yixin Nie, Adina Williams, Emily Dinan, Mohit Bansal, Jason Weston, and Douwe Kiela. Adversarial NLI: A new benchmark for natural language understanding. In ACL, pp. 4885–4901. Association for Computational Linguistics, 2020.

Mohammad Taher Pilehvar and José Camacho-Collados. Wic: 10, 000 example pairs for evaluating context-sensitive representations. CoRR, abs/1808.09121, 2018.

Yada Pruksachatkun, Jason Phang, Haokun Liu, Phu Mon Htut, Xiaoyi Zhang, Richard Yuanzhe Pang, Clara Vania, Katharina Kann, and Samuel R. Bowman. Intermediate-task transfer learning with pretrained models for natural language understanding: When and why does it work? CoRR, abs/2005.00628, 2020.

Jack W Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, et al. Scaling language models: Methods, analysis & insights from training gopher. arXiv preprint arXiv:2112.11446, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. CoRR, abs/1910.10683, 2019.

Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S Gordon. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In AAAI Spring Symposium: Logical Formalizations of Commonsense Reasoning, pp. 90–95, 2011.

Anna Rogers, Olga Kovaleva, Matthew Downey, and Anna Rumshisky. Getting closer to AI complete question answering: A set of prerequisite real tasks. In AAAI, pp. 8722–8731. AAAI Press, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. In AAAI, pp. 8732–8740. AAAI Press, 2020.

Victor Sanh, Albert Webson, Colin Raffel, Stephen H. Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, Manan Dey, M. Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal V. Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Févry, Jason Alan Fries, Ryan Teehan, Stella Biderman, Leo Gao, Tali Bers, Thomas Wolf, and Alexander M. Rush. Multitask prompted training enables zero-shot task generalization. CoRR, abs/2110.08207, 2021.

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan Le Bras, and Yejin Choi. Social iqa: Common-sense reasoning about social interactions. In EMNLP/IJCNLP (1), pp. 4462–4472. Association for Computational Linguistics, 2019.

Timo Schick and Hinrich Schütze. It's not just size that matters: Small language models are also few-shot learners. CoRR, abs/2009.07118, 2020.

Jie Song, Yixin Chen, Xinchao Wang, Chengchao Shen, and Mingli Song. Deep model transferability from attribution maps. In NeurIPS, pp. 6179–6189, 2019.

Oyvind Tafjord, Matt Gardner, Kevin Lin, and Peter Clark. Quartz: An open-domain dataset of qualitative relationship questions. In EMNLP/IJCNLP (1), pp. 5940–5945. Association for Computational Linguistics, 2019.

William Yang Wang and Diyi Yang. That's so annoying!!!: A lexical and frame-semantic embedding based data augmentation approach to automatic categorization of annoying behaviors using #petpeeve tweets. In EMNLP, pp. 2557–2563. The Association for Computational Linguistics, 2015.

Albert Webson and Ellie Pavlick. Do prompt-based models really understand the meaning of their prompts? In NAACL-HLT, pp. 2300–2344. Association for Computational Linguistics, 2022.

Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. Finetuned language models are zero-shot learners. CoRR, abs/2109.01652, 2021.

Jason W. Wei and Kai Zou. EDA: easy data augmentation techniques for boosting performance on text classification tasks. In EMNLP/IJCNLP (1), pp. 6381–6387. Association for Computational Linguistics, 2019.

Yi Yang, Wen-tau Yih, and Christopher Meek. Wikiqa: A challenge dataset for open-domain question answering. In EMNLP, pp. 2013–2018. The Association for Computational Linguistics, 2015.

Zhiquan Ye, Yuxia Geng, Jiaoyan Chen, Jingmin Chen, Xiaoxiao Xu, Suhang Zheng, Feng Wang, Jun Zhang, and Huajun Chen. Zero-shot text classification via reinforced self-training. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pp. 3014–3024, 2020.

Amir Roshan Zamir, Alexander Sax, William B. Shen, Leonidas J. Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In CVPR, pp. 3712–3722. Computer Vision Foundation / IEEE Computer Society, 2018.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? In ACL (1), pp. 4791–4800. Association for Computational Linguistics, 2019.

Jingqing Zhang, Piyawat Lertvittayakumjorn, and Yike Guo. Integrating semantic knowledge to tackle zero-shot text classification. arXiv preprint arXiv:1903.12626, 2019a.

Sheng Zhang, Xiaodong Liu, Jingjing Liu, Jianfeng Gao, Kevin Duh, and Benjamin Van Durme. Record: Bridging the gap between human and machine commonsense reading comprehension. ArXiv, abs/1810.12885, 2018.

Xiang Zhang, Junbo Jake Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In NIPS, pp. 649–657, 2015.

Yiwen Zhang, Caixia Yuan, Xiaojie Wang, Ziwei Bai, and Yongbin Liu. Learn to adapt for generalized zero-shot text classification. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 517–527, 2022.

Yuan Zhang, Jason Baldridge, and Luheng He. PAWS: paraphrase adversaries from word scrambling. In NAACL-HLT (1), pp. 1298–1308. Association for Computational Linguistics, 2019b.

A   EXPERIMENTAL DETAILS

A.1   HYPER-PARAMETERS SELECTION

For all the experiments, we adopt the ADAM optimizer and use a learning rate of 1e-4. Considering the amount of data, the batch size and training steps are different for different settings in our experiments. The hyper-parameters of our experiments are in Table 6.

Experiment	Batch Size	Steps
Single Task Transfer	512	1000
Top-3 Task Transfer	1024	2000
Top-8 Task Transfer	1024	10000
Full Dataset	1024	20000

Table 6: Training hyper-parameters for our experiments.

A.2   DATA AUGMENTATION DETAILS

We propose two algorithms for the domain-task intersection. The first one is based on a human-written taxonomy tree, and another relies on universal fields. We combine the two techniques and achieve a balance between quality and diversity.

Taxonomy Tree based Domain-Task Intersection To build a general taxonomy tree to cover as many prompts as possible, we take both task format and task content into consideration to develop a series of guidelines similar to a Decision Tree. Then, at the end of each branch, we intersect the source data lying in that branch with the related prompts belonging to that branch. In this way, we might produce a reasonable combination of the source data and prompt. For example, classification tasks like IMDB can also do tasks like title generation.

Universal Domain-Task Generation To further improve the diversity of the augmented data, we get rid of the man-made restriction and propose universal domain-task generation. In detail, we define the unified fields for data from all domains, which are utilized for various tasks. Obviously, each original domain data lacks certain kinds of fields, e.g., AG NEWS data only have two fields: category label and text. Therefore, we leverage the T0 to predict the missing fields in order to conduct different kinds of tasks using the prompts having already trained in T0. After that, we filter samples according to the confidence score (i.e., the probability output by the model).

B   FULL RESULTS

B.1   FULL RESULTS ON TOP-3 SUPPORT DATASETS

The results when training on the top-3 support datasets for each test task are in Table 7 and Table 8. We can see that the model trained on top-3 support datasets shows comparable results with the T0 baseline.

| Tasks | Met. | Natural Language Inference | | | | | Sentence Completion | | | Co-Reference | | WSD |
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC
T0	Mean	71.94	56.46	32.81	32.29	34.24	84.77	27.09	93.45	64.30	54.33	50.45
	Med.	71.88	60.94	32.32	31.64	34.05	85.54	26.92	93.23	65.23	54.38	50.31
RTE_KEY	Mean	**72.42**	54.17	32.08	31.87	34.22	69.41	28.37	82.43	**64.52**	51.78	50.67
	Med.	**73.47**	66.07	31.90	31.60	34.00	68.03	28.03	84.34	**63.46**	51.93	50.55
CB_KEY	Mean	56.86	**60.48**	**33.17**	32.94	34.98	**81.04**	28.48	93.34	44.81	54.57	51.79
	Med.	57.76	**69.64**	**32.80**	33.00	35.42	**83.00**	28.74	93.53	39.90	54.70	50.78
COPA_KEY	Mean	59.49	40.36	31.73	31.65	32.06	77.52	29.31	93.32	51.63	50.92	49.82
	Med.	59.39	42.86	31.10	32.20	32.50	83.00	29.22	93.37	54.81	51.07	50.00
Hella._KEY	Mean	63.10	49.05	32.93	**34.03**	**35.48**	81.61	**30.15**	**94.43**	47.79	51.55	49.88
	Med.	63.72	50.00	33.30	**33.90**	**36.25**	82.35	**29.91**	**94.60**	45.19	51.38	49.92
Story._KEY	Mean	59.49	40.36	31.73	31.65	32.06	77.52	29.31	93.32	51.63	50.92	49.82
	Med.	59.39	42.86	31.10	32.20	32.50	83.00	29.22	93.37	54.81	51.07	50.00
WSC_KEY	Mean	55.09	42.62	31.65	32.30	32.39	50.45	23.92	48.77	63.75	50.88	50.99
	Med.	54.33	46.43	31.70	32.50	32.33	49.50	23.97	48.69	63.46	50.75	50.78
Wino_KEY	Mean	62.45	59.76	31.67	33.76	34.84	64.57	26.11	66.65	48.75	**55.79**	51.68
	Med.	63.36	76.79	31.60	33.70	34.75	65.69	26.09	71.94	47.12	**55.80**	51.18

Table 7: Results of training on the top-3 support datasets for each task on T5-Large. The entry at row i and column j denotes the average accuracy training on the top-3 support datasets of task i and evaluate on task j. Mean denotes the mean performance on all prompts, and Med. denotes the median performance on all prompts. **Bold** denotes the best performance for each evaluation dataset.

| | Met. | Natural Language Inference | | | | | Sentence Completion | | | Co-Reference | | WSD |
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC
Baseline T0	Mean	80.80	67.26	43.80	38.90	42.20	93.11	30.40	97.80	63.90	61.80	52.30
	Med.	78.70	71.43	45.40	40.00	43.30	93.50	30.90	97.70	63.90	61.80	52.70
RTE_KEY	Mean	**79.63**	65.95	38.95	37.77	37.90	72.53	31.31	83.14	59.71	52.88	52.13
	Med.	**79.60**	71.43	38.90	38.00	37.92	71.96	31.31	84.02	59.13	53.04	52.51
CB_KEY	Mean	77.22	63.93	**41.25**	**38.86**	**40.62**	87.50	**35.43**	95.28	61.44	56.02	51.77
	Med.	76.53	69.64	**41.80**	**39.80**	**42.25**	87.00	**36.09**	95.24	62.98	55.56	52.12
ANLI1_KEY	Mean	77.00	60.59	40.73	37.84	39.13	87.07	33.45	96.80	63.37	54.51	51.05
	Med.	77.98	66.07	41.90	38.10	39.58	89.00	33.28	96.85	64.90	54.06	50.71
ANLI2_KEY	Mean	77.11	64.17	38.67	37.63	38.28	71.95	29.35	90.06	63.37	55.82	51.97
	Med.	77.26	67.86	39.10	37.90	37.92	71.38	29.23	92.41	62.50	56.43	52.19
ANLI3_KEY	Mean	58.84	63.93	37.02	36.19	37.72	67.14	25.68	76.24	42.79	58.63	51.77
	Med.	58.30	71.43	37.30	36.30	38.00	68.65	24.82	78.41	40.87	58.33	50.86
COPA_KEY	Mean	60.97	58.21	37.07	35.16	37.07	83.95	32.45	95.47	49.04	54.10	51.54
	Med.	63.36	60.71	38.30	35.10	38.58	88.00	32.71	95.40	49.52	53.59	51.33
Hella_KEY	Mean	69.42	65.36	38.85	37.20	38.50	**87.07**	33.66	**97.24**	50.38	55.44	51.03
	Med.	69.86	75.00	38.60	36.76	39.08	**91.00**	33.28	**97.27**	52.88	54.85	50.31
Story_KEY	Mean	69.42	65.36	38.85	37.20	38.50	**87.07**	33.66	**97.24**	50.38	55.44	51.03
	Med.	69.86	75.00	38.60	36.76	39.08	**91.00**	33.28	**97.27**	52.88	54.85	50.31
WSC_KEY	Mean	60.36	52.38	33.73	33.97	33.31	53.50	26.39	51.43	**63.75**	51.70	52.02
	Med.	59.93	51.79	33.50	34.00	33.33	54.00	26.28	51.36	**63.46**	51.62	51.96
Wino_KEY	Mean	66.21	**69.88**	34.95	35.17	27.73	75.27	25.37	67.48	50.58	**61.50**	50.20
	Med.	66.61	**75.00**	35.30	35.50	38.75	76.50	25.17	69.21	50.48	**61.88**	50.00
WiC_KEY	Mean	56.03	52.86	34.64	34.07	33.98	87.20	31.23	95.28	47.31	53.91	50.83
	Med.	56.68	57.14	34.70	34.10	33.75	91.50	31.41	95.40	47.60	52.49	50.24

Table 8: Zero-Shot results of training with the top-3 support tasks for each test task. The experiments are performed on T5-3B model. The entry at (row i, column j) denotes the performance of test task j evaluated on the model trained with task-i's top-3 support sets. The best result for each test task is denoted in bold.

B.2 FULL RESULTS EVALUATED ON HELD-OUT TEST DATASETS

Full results evaluated on held-out test datasets are in Table 9 and Table 10.

Task Names	Met.	Natural Language Inference					Sentence Completion			Co-Reference		WSD
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Wino.	Story.	Hella.	WSC	WiC
MRPC	Mean	49.96	47.74	33.12	33.21	32.94	53.9	50.4	48.06	23.39	61.92	50.13
	Med.	50.36	50.0	33.3	33.3	32.83	54.0	50.83	47.68	23.22	63.46	50.16
QQP	Mean	58.66	45.0	30.01	31.63	31.19	57.2	50.02	45.78	26.42	54.52	50.27
	Med.	59.03	48.21	28.4	31.3	30.17	56.0	50.12	45.54	26.77	63.46	50.16
PAWS	Mean	69.1	42.74	31.97	31.92	33.53	48.78	50.09	51.42	24.46	63.46	51.39
	Med.	70.4	44.64	32.1	32.0	33.42	48.0	50.12	51.9	24.34	62.5	51.33
Hotpot QA	Mean	57.11	39.4	33.55	34.41	33.17	44.02	51.57	46.82	24.95	59.71	50.38
	Med.	56.32	46.43	33.5	34.7	33.08	45.03	51.3	46.93	24.76	62.02	50.47
Wiki QA	Mean	63.18	47.26	29.99	30.88	33.14	53.74	49.72	48.84	22.79	59.52	51.3
	Med.	63.18	50.0	29.2	30.5	33.33	54.58	49.01	49.39	22.58	62.02	50.31
Adv./DBidaf	Mean	48.12	35.12	32.69	33.15	33.46	58.62	50.13	52.37	27.26	54.71	50.11
	Med.	47.29	42.86	33.2	33.3	33.5	58.0	50.04	51.52	27.91	61.54	50.0
Adv./DBERT	Mean	47.94	35.24	33.27	33.67	33.09	55.14	50.28	52.65	26.73	55.0	50.13
	Med.	47.29	50.0	33.3	33.3	33.0	55.5	50.2	51.58	27.37	62.5	50.08
Adv./DRoberTa	Mean	47.87	34.88	33.29	33.48	33.19	56.23	50.83	53.3	26.52	55.19	50.06
	Med.	47.29	50.0	33.3	33.3	33.0	56.01	50.91	52.75	26.54	63.46	50.0
DuoRC/Self.	Mean	54.58	40.12	32.55	33.33	32.73	48.92	50.2	46.25	26.03	47.98	48.64
	Med.	54.33	50.0	32.6	33.3	32.92	49.0	50.51	46.61	26.38	47.6	49.69
DuoRC/Para.	Mean	53.21	40.95	32.25	33.13	32.72	46.89	50.31	46.44	25.4	46.44	49.97
	Med.	52.89	46.43	32.9	33.2	32.67	46.58	50.2	46.66	25.73	44.23	50.0
ROPES	Mean	52.49	31.43	33.67	34.61	34.94	58.08	53.2	46.61	25.84	42.02	50.19
	Med.	52.71	32.14	33.9	35.0	34.67	56.62	53.43	46.34	25.95	36.54	50.0
Quoref	Mean	51.05	26.79	33.85	33.91	33.16	51.77	51.25	51.1	25.46	58.37	51.76
	med.	50.36	26.79	33.6	33.7	33.33	53.0	51.22	50.13	25.47	62.5	50.78
Cos_E	Mean	50.14	38.93	32.68	33.54	33.34	66.54	51.81	63.55	27.2	50.19	52.23
	Med.	50.72	41.07	33.0	33.3	33.42	67.0	52.41	62.27	27.17	51.44	52.66
Cosmos QA	Mean	52.71	43.33	33.06	33.41	33.32	77.72	50.56	91.18	31.44	49.71	49.31
	Med.	53.07	46.43	33.3	33.3	33.33	83.0	50.83	91.39	31.92	54.33	50.08
DREAM	Mean	54.08	41.19	32.35	33.05	33.14	72.65	50.66	82.06	26.44	48.08	51.13
	Med.	53.79	50.0	33.2	33.3	33.5	74.5	50.51	82.58	26.35	47.12	51.57
QASC	Mean	54.91	43.69	31.71	33.25	33.64	53.8	52.53	65.9	26.5	43.37	50.42
	Med.	53.07	41.07	32.8	33.3	33.42	56.0	51.93	68.52	26.34	37.98	50.24
QuAIL	Mean	54.55	52.38	32.65	32.75	33.49	72.79	51.03	87.09	27.52	40.67	49.87
	Med.	53.79	62.5	33.1	33.0	33.83	73.5	50.99	87.71	27.56	38.46	49.92
QuaRel	Mean	47.58	29.05	33.33	34.59	33.51	58.04	49.69	50.8	25.0	44.9	50.56
	Med.	46.75	35.71	33.4	34.6	33.42	58.5	49.72	51.04	25.13	44.23	50.55
QuaRTz	Mean	54.98	51.9	31.28	32.64	33.93	65.2	55.99	58.57	25.94	36.25	52.15
	Med.	54.87	55.36	31.1	32.2	34.08	66.33	56.04	57.24	25.9	36.06	51.72
SciQ	Mean	52.96	20.36	33.15	32.97	33.28	50.8	51.25	45.09	24.63	45.19	48.71
	Med.	52.71	8.93	33.3	33.3	33.5	50.0	51.3	45.06	24.62	37.02	48.98
Social IQA	Mean	66.17	52.62	31.33	33.47	34.39	70.99	51.65	80.89	28.25	47.02	51.32
	Med.	66.79	62.5	31.4	33.5	34.25	73.0	51.7	82.04	28.18	48.56	50.86
Wiki Hop	Mean	52.96	34.76	33.53	33.53	33.29	52.58	50.07	48.79	25.82	39.52	50.03
	Med.	52.71	41.07	33.4	33.4	33.42	53.0	50.04	49.01	25.96	36.54	50.0
WiQA	Mean	52.64	37.98	32.93	33.46	33.56	48.96	49.6	40.5	21.52	37.98	51.22
	Med.	52.71	41.07	33.3	33.4	33.58	49.5	49.64	39.34	20.61	36.54	50.94

Task Names	Met.	RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC
Amazon	Mean	53.65	49.05	32.47	32.89	33.38	55.48	49.72	48.61	24.36	41.25	51.3
	Med.	53.43	50.0	32.5	33.2	33.5	55.0	49.49	49.12	24.19	37.02	50.71
App Reviews	Mean	52.31	31.07	32.95	33.15	33.27	55.14	49.64	53.75	23.98	42.6	50.08
	Med.	52.71	41.07	33.3	33.3	33.33	54.5	49.64	54.25	23.86	36.54	50.0
IMDB	Mean	55.23	42.86	32.82	33.47	33.11	56.81	49.68	48.78	24.15	38.85	50.99
	Med.	54.51	41.07	32.8	33.4	33.33	56.0	49.41	49.01	24.18	36.54	50.47
Rotten Tomatoes	Mean	54.26	43.45	32.71	33.17	33.09	59.19	50.31	50.58	23.63	40.29	53.06
	Med.	53.79	48.21	32.8	33.4	33.0	60.21	50.2	52.81	23.21	41.35	53.13
Yelp	Mean	52.71	34.52	33.25	33.31	33.54	51.5	50.42	45.68	22.67	37.4	49.83
	Med.	52.71	41.07	33.4	33.4	33.58	52.5	50.43	45.7	22.01	36.54	49.92
Common Gen	Mean	47.4	37.5	33.38	33.27	33.31	53.47	49.57	49.3	26.32	61.92	50.03
	Med.	47.29	50.0	33.3	33.3	33.0	54.0	49.49	49.39	26.71	63.46	50.0
Wiki Bio	Mean	47.83	42.98	32.93	33.65	33.06	50.6	49.5	44.76	23.08	55.58	49.84
	Med.	47.29	46.43	33.3	33.3	33.08	50.5	49.57	45.0	22.57	62.02	50.0
CNN Daily Mail	Mean	48.27	40.48	32.85	33.8	33.09	46.69	49.27	51.82	25.77	56.63	50.02
	Med.	47.29	50.0	33.2	33.4	33.0	45.42	49.17	51.63	25.85	63.46	50.0
Gigaword	Mean	53.03	26.31	33.34	34.19	33.46	57.45	49.98	44.5	23.28	49.81	49.4
	Med.	53.61	25.0	33.6	34.2	33.58	57.5	50.28	44.9	23.0	46.15	49.61
MultiNews	Mean	51.52	26.9	32.66	33.03	33.19	45.62	49.17	48.03	24.17	52.88	49.86
	Med.	52.17	25.0	32.9	33.4	33.0	44.0	49.09	48.0	24.15	57.69	49.92
SamSum	Mean	47.69	27.98	33.63	32.87	32.89	51.55	50.99	46.89	25.31	52.69	50.39
	Med.	46.93	28.57	33.6	33.2	33.08	52.5	50.75	46.87	25.34	59.13	50.08
XSum	Mean	48.81	42.62	33.43	33.05	33.08	57.86	49.72	45.51	22.35	57.31	52.45
	Med.	48.19	50.0	33.3	33.2	33.17	58.0	49.57	45.7	22.13	60.58	52.35
AG News	Mean	53.5	34.05	32.95	33.66	33.72	54.01	50.01	51.35	23.54	38.27	51.05
	Med.	53.43	39.29	33.0	33.6	33.67	54.5	50.2	52.65	23.2	37.5	50.0
DBPedia	Mean	52.78	35.12	33.24	33.33	33.67	54.86	51.18	52.9	26.45	38.46	51.29
	Med.	53.43	41.07	33.1	33.4	33.67	53.5	51.14	52.86	26.17	36.54	51.1
TREC	Mean	51.52	43.57	33.15	33.06	32.77	55.17	50.02	52.53	25.55	55.38	50.38
	Med.	51.44	48.21	33.3	33.0	33.08	55.0	49.72	52.86	25.53	63.46	50.0

Table 9: Experiments on T5-large-lm-adapt. The entry at row i and column j denotes the average accuracy training on the top-3 support datasets of task i and evaluate on task j. Mean denotes the mean performance on all prompts, and Med. denotes the median performance on all prompts.

Task Names	Met.	Natural Language Inference					Sentence Completion			Co-Reference		WSD
		RTE	CB	ANLI1	ANLI2	ANLI3	COPA	Hella.	Story.	WSC	Wino.	WiC
MRPC	Mean	54.44	36.79	33.43	32.87	33.38	55.02	25.83	49.77	61.92	51.68	51.35
	Med.	53.97	37.5	33.6	32.3	33.17	56.0	25.62	49.92	62.5	51.78	50.47
QQP	Mean	60.87	46.43	31.07	32.16	31.72	58.23	26.23	47.4	54.23	50.53	50.13
	Med.	61.91	50.0	30.2	31.7	31.0	59.5	26.26	47.62	63.46	50.36	50.16
PAWS	Mean	74.33	60.6	35.68	34.91	35.44	56.65	27.09	55.0	61.63	50.75	51.21
	Med.	74.37	66.07	35.0	35.0	35.08	56.0	27.49	55.0	61.54	51.14	51.18
Hotpot QA	Mean	57.22	21.9	34.55	34.56	34.48	58.82	24.45	58.98	58.37	52.58	50.53
	Med.	55.6	10.71	34.3	35.0	34.25	60.71	24.2	58.69	59.62	52.17	50.24
Wiki QA	Mean	61.05	52.26	31.49	32.96	32.69	52.81	26.74	58.4	62.69	51.1	50.02
	Med.	60.83	51.79	31.0	32.7	32.58	52.5	26.89	58.47	63.46	51.14	50.0
Adv./DBidaf	Mean	48.52	47.14	32.95	33.6	33.35	56.35	26.49	52.68	56.15	52.17	50.02
	Med.	47.29	51.79	33.2	33.3	33.17	56.62	26.82	52.7	63.46	52.25	50.0
Adv./DBERT	Mean	48.81	37.62	33.27	33.25	33.46	60.58	26.45	54.86	55.38	51.89	49.91
	Med.	47.29	50.0	33.2	33.3	33.08	59.81	26.88	53.34	63.46	50.83	50.0
Adv./DRoBERTa	Mean	47.91	39.64	33.26	33.49	33.34	62.01	26.94	55.5	55.38	53.32	50.0

	Med.	47.29	50.0	33.3	33.3	33.0	62.75	27.39	54.36	63.46	53.59	50.0
DuoRC/Self.	Mean	57.11	43.45	32.83	33.35	33.51	55.66	26.71	45.79	44.13	52.49	50.0
	Med.	56.86	48.21	33.4	33.5	33.33	55.38	26.75	46.18	39.42	52.25	50.0
DuoRC/Para.	Mean	53.61	39.17	33.82	34.15	33.74	53.83	26.66	47.66	38.17	52.83	50.41
	Med.	53.25	41.07	33.5	33.9	33.5	54.5	27.01	46.93	37.02	52.33	50.24
ROPES	Mean	53.65	41.67	34.2	34.68	35.64	69.19	26.13	50.73	40.38	57.76	50.31
	Med.	53.43	41.07	33.7	33.8	35.25	67.65	26.27	50.88	37.98	58.25	50.0
Quoref	Mean	47.44	34.17	33.98	34.52	33.06	51.1	25.84	51.26	60.77	53.76	49.72
	Med.	47.29	41.07	33.8	33.7	33.08	52.5	25.71	51.58	63.46	53.59	50.0
Cos_E	Mean	52.45	38.21	33.65	32.91	33.53	66.72	28.35	51.36	38.56	53.69	50.89
	Med.	51.81	39.29	33.5	33.0	33.42	66.83	29.31	50.94	36.54	52.88	51.02
Cosmos QA	Mean	55.34	54.64	35.29	33.2	33.51	84.57	33.33	95.06	47.4	53.92	51.77
	Med.	56.68	53.57	35.4	33.3	33.75	85.5	33.34	95.03	44.71	53.75	52.27
DREAM	Mean	52.38	37.74	33.53	32.94	33.66	76.12	28.57	80.2	47.4	52.94	50.2
	Med.	52.17	41.07	33.6	32.5	33.5	77.5	28.23	80.22	48.08	53.67	50.0
QASC	Mean	56.43	37.38	34.87	34.72	34.99	63.88	27.38	75.62	38.56	54.54	50.78
	Med.	56.5	41.07	34.6	34.7	34.83	65.5	27.27	77.12	36.54	55.09	50.0
QuAIL	Mean	54.12	49.17	35.12	34.41	34.32	79.41	29.28	89.83	37.12	54.44	50.13
	Med.	53.61	46.43	33.8	34.1	34.08	83.0	29.31	89.85	36.54	55.64	49.76
QuaRel	Mean	52.45	31.43	33.06	33.42	33.46	60.95	27.85	50.33	43.08	50.36	47.96
	Med.	52.71	33.93	33.1	33.3	33.5	58.5	28.49	50.24	39.9	50.12	48.04
QuaRTz	Mean	57.36	63.69	31.81	32.83	34.17	68.2	24.74	53.96	43.94	57.06	49.34
	Med.	57.4	69.64	31.4	32.7	34.0	65.0	24.48	52.81	42.79	56.99	49.76
SciQ	Mean	53.18	25.95	32.98	33.31	33.86	56.69	24.15	48.67	37.4	51.76	50.99
	Med.	52.71	8.93	33.3	33.3	33.5	55.38	23.62	48.53	36.54	51.46	50.0
Social IQA	Mean	67.69	51.55	36.76	35.63	37.85	72.28	28.83	80.99	54.33	54.52	50.91
	Med.	70.94	58.93	36.8	36.0	37.92	72.96	29.3	83.48	58.65	54.93	51.33
Wiki Hop	Mean	52.45	29.52	33.43	33.55	33.62	56.01	26.05	56.79	37.31	51.78	50.22
	Med.	52.71	28.57	33.4	33.5	33.67	54.08	26.13	56.97	36.54	52.25	50.0
WiQA	Mean	53.68	42.74	34.51	34.69	36.19	56.24	22.8	45.12	36.63	53.42	50.71
	Med.	52.71	39.29	34.5	34.5	36.0	56.5	21.86	45.22	36.54	53.51	50.0
Amazon	Mean	51.95	46.9	33.74	33.85	34.72	55.83	25.45	47.25	52.5	50.28	49.87
	Med.	52.35	51.79	33.4	33.9	34.5	56.0	25.75	47.25	59.13	50.12	50.0
App Reviews	Mean	54.37	31.43	32.94	33.82	33.09	58.23	23.74	56.73	46.92	49.58	51.88
	Med.	54.87	35.71	33.2	33.4	33.0	58.17	23.17	56.97	41.83	49.41	50.86
IMDB	Mean	55.7	51.9	34.07	34.11	34.04	51.85	26.4	48.66	48.27	51.25	48.97
	Med.	56.14	58.93	33.4	33.5	33.75	52.0	26.79	49.01	49.04	51.46	48.75
Rotten Tomatoes	Mean	54.3	50.95	33.3	33.39	33.72	51.62	26.98	49.93	39.33	50.66	51.08
	Med.	54.33	51.79	33.3	33.4	33.58	52.04	27.24	50.08	39.42	50.83	50.39
Yelp	Mean	52.71	32.5	33.38	33.59	33.38	53.3	25.65	46.69	36.54	49.93	49.97
	Med.	52.71	39.29	33.4	33.4	33.5	54.0	25.82	46.77	36.54	50.28	50.0
Common Gen	Mean	48.12	36.55	33.47	33.72	33.49	50.77	26.09	50.82	58.85	49.77	49.92
	Med.	47.29	48.21	33.3	33.4	33.17	51.0	26.24	50.99	62.5	49.88	49.84
Wiki Bio	Mean	48.38	34.17	32.73	33.69	33.08	55.03	22.72	46.79	56.83	51.78	50.2
	Med.	48.01	37.5	32.9	33.5	33.42	54.5	22.36	47.73	61.54	51.46	50.16
CNN Daily Mail	Mean	48.88	42.38	33.15	33.54	33.08	51.22	28.44	54.16	57.5	50.32	50.02
	Med.	47.65	48.21	33.3	33.4	33.0	51.46	28.94	54.36	63.46	50.2	50.0
Gigaword	Mean	53.1	32.38	33.37	33.84	34.18	59.66	23.41	47.15	37.4	50.67	49.86
	Med.	52.71	35.71	33.4	33.6	34.33	60.0	22.95	47.3	36.54	50.36	49.84
MultiNews	Mean	48.66	41.19	32.99	33.36	32.97	52.9	23.94	48.94	51.63	51.21	50.64
	Med.	48.38	41.07	33.2	33.3	32.92	53.04	24.1	48.85	57.69	51.07	50.63

SamSum	Mean	47.11	33.21	31.99	32.73	32.18	53.41	24.0	51.69	50.48	50.59	51.68
	Med.	46.57	35.71	31.7	32.8	31.83	52.0	24.01	52.11	51.92	50.99	51.25
XSum	Mean	47.04	43.21	33.31	34.01	32.94	52.43	20.31	48.13	58.65	49.85	49.98
	Med.	47.47	50.0	33.4	33.8	33.08	52.96	19.06	47.89	63.46	50.04	50.08
AG News	Mean	52.24	47.98	33.41	33.07	33.38	59.38	25.64	47.4	41.92	50.32	50.2
	Med.	52.35	53.57	33.4	33.3	33.5	59.31	25.68	47.35	43.27	50.51	50.24
DBPedia	Mean	52.74	18.45	33.3	33.52	33.39	61.82	24.87	47.48	46.25	50.83	51.14
	Med.	52.89	8.93	33.4	33.4	33.42	63.0	25.61	47.46	49.52	50.91	51.33
TREC	Mean	53.1	38.69	33.37	33.35	33.42	61.73	27.12	51.46	36.83	49.69	50.06
	Med.	52.71	41.07	33.4	33.4	33.5	64.5	27.68	51.31	36.54	49.57	50.0

Table 10: Experiments on T5-xl-lm-adapt. The entry at row i and column j denotes the average accuracy training on the top-3 support datasets of task i and evaluate on task j. Mean denotes the mean performance on all prompts, and Med. denotes the median performance on all prompts.