Video Scene Graph Generation from Single-Frame Weak Supervision

Abstract

Video scene graph generation (VidSGG) aims to generate a sequence of graph-structure representations for the given video. However, all existing VidSGG methods are *fully-supervised*, *i.e.*, they need dense and costly manual annotations. In this paper, we propose the first *weakly-supervised* VidSGG task with only single-frame weak supervision: SF-VidSGG. By "weakly-supervised", we mean that SF-VidSGG relaxes the training supervision from two different levels: 1) It only provides single-frame annotations instead of all-frame annotations. 2) The single-frame ground-truth annotation is still a weak image SGG annotation, *i.e.*, an un-localized scene graph. To solve this new task, we also propose a novel Pseudo Label Assignment based method, dubbed as **PLA**. PLA is a two-stage method, which generates pseudo visual relation annotations for the given video at the first stage, and then trains a fully-supervised VidSGG model with these pseudo labels. Specifically, PLA consists of three modules: an object PLA module, a predicate PLA module, and a future predicate prediction (FPP) module. Firstly, in the object PLA, we localize all objects for every frame. Then, in the predicate PLA, we design two different teachers to assign pseudo predicate labels. Lastly, in the FPP module, we fusion these two predicate pseudo labels by the regularity of relation transition in videos. Extensive ablations and results on the benchmark Action Genome have demonstrated the effectiveness of our PLA.

1 Introduction

Scene graph (Johnson et al., 2015) is a type of visually-aligned graph-structured representation that summarizes all the object instances (*e.g.*, "person", "chair") as nodes and their pairwise visual relations (or predicates, *e.g.*, "sitting on") as directed edges. As a bridge to connect the vision and language modalities, scene graphs have been widely used in many different downstream visual-language tasks, such as visual captioning (Yang et al., 2019; 2020), grounding (Jing et al., 2020), question answering (Hudson & Manning, 2019), and retrieval (Johnson et al., 2015).

Early Scene Graph Generation (SGG) work mainly focuses on generating scene graphs for the given *image*, dubbed as **ImgSGG** (Xu et al., 2017; Zellers et al., 2018; Chen et al., 2019). However, due to its static nature, ImgSGG fails to represent numerous dynamic visual relations that take place over a period of time, such as "walking with" and "running away" (vs. static relation "standing"). Meanwhile, it is hard or impossible to identify these dynamic visual relations with only a single frame, because these visual relations can only be well classified by considering the temporal context. Therefore, another more meaningful but challenging video-based SGG task was proposed: **VidSGG** (Shang et al., 2017; 2019).

Since the complex and dense annotations of a scene graph (*cf.*, Figure 1(a)), fully-supervised SGG methods always require lots of manual annotations, and the case is even worse for video data. Meanwhile, several prior SGG works (Li et al., 2022a) have found that even carefully manually-annotated labels are still quite noisy, *i.e.*, the annotated positive labels may not be the best matched, and numerous negative labels are just missing annotated. Thus, a surge of recent ImgSGG work (Zareian et al., 2020; Zhong et al., 2021; Shi et al., 2021; Li et al., 2022c) start to generate scene graphs for images with only weak supervision. By "weak supervision", we mean that the annotations for model training are not complete localized scene graphs. For example, a typical type of weak supervision

is *unlocalized scene graphs*. As illustrated in Figure 1(b), an unlocalized scene graph only contains image-level object and relation categories without corresponding object bounding boxes (bboxes).

Although recent weakly-supervised ImgSGG has achieved good performance and received unprecedented attention, to the best our knowledge, there is no existing work about generating video scene graphs from weak supervision. To put forward the research on this critical topic, we propose the first weakly-supervised VidSGG task with single-frame weak supervision, called **SF-VidSGG**. Specifically, given an input video, SF-VidSGG aims to generate a localized scene graph for each frame in the video, but *the only supervision for training is an unlocalized scene graph for the middle frame of each training video*. As the example shown in Figure 1(c), the supervision is an unlocalized scene graph for the third frame. Obviously, SF-VidSGG task tries to relieve the intensive annotation issues from two levels: 1) Video-level: For each video, we only need single-frame annotations instead of all-frame annotations as the

Figure 1: **(a)** Localized scene graph: It consists of all object bboxes, object categories, and predicate categories. **(b)**: Unlocalized scene graph: It consists of object and predicate categories without object bboxes. **(c)** The supervision for SF-VidSGG, which only provides an unlocalized scene graph for the middle frame of the video.

fully-supervised setting (*i.e.*, reduce the number of annotated frames). 2) Frame-level: The single-frame annotation is an unlocalized scene graph (*i.e.*, avoid annotating object locations).

A straightforward solution for SF-VidSGG is: Using all the weakly annotated frames to train a weakly-supervised ImgSGG model first, and then detecting scene graphs on each frame with the ImgSGG model. Apparently, this naive ImgSGG-based method has overlooked the temporal context in the video data. To this end, we propose a novel Pseudo Label Assignment strategy **PLA**, which can serve as the first baseline for SF-VidSGG. Since PLA is agnostic to different VidSGG architectures, it can be easily incorporated into any advanced VidSGG model. Specifically, PLA decouples the problem into two steps: The first step is to assign a *pseudo* localized scene graph for every frame in the video, and the second step is to train a fully-supervised VidSGG model by the pseudo localized scene graphs. PLA consists of three modules: object pseudo label assignment module (Obj-PLA), relation pseudo label assignment module (Rel-PLA), and future predicate prediction module (FPP). In the Obj-PLA module, we detect object region proposals for all the frames. In the Rel-PLA module, we propose two relation pseudo label assignment teachers and they generate two different pseudo labels for each frame. In the FPP module, we determine adapted weights to fuse these labels from two different teachers. To effectively obtain optimal adapted weights for fusing different teacher knowledge, the FPP module exploits the temporal context based on the relation transition in videos. The relation transition means how the predicates change between the same subject-object pairs in different frames.

In summary, we make three main technique contributions in this paper:

1. We propose the first weakly-supervised VidSGG task. Compared to its fully-supervised counterpart, we try to mitigate the intensive annotations from both video-level and frame-level.

2. We propose a novel method PLA for SF-VidSGG. It utilizes two teachers to assign pseudo label for unlabeled data and refines the pseudo labels from both teachers by knowledge distillation.

3. We propose a future predicate prediction module that leverages temporal dependencies in video.

2 RELATED WORK

Image Scene Graph Generation (ImgSGG). ImgSGG aims to generate semantic graph structures — scene graphs — as the representation of images. In each scene graph, every node represents an object instance and every edge represents a visual relation between two objects. Early ImgSGG methods always directly predict all pairwise visual relations (Lu et al., 2016; Zhang et al., 2017). Later, ImgSGG methods mainly focus on designing different context encoding architectures, such

as message passing (Xu et al., 2017; Li et al., 2017), recurrent network (Zellers et al., 2018), tree-structure model (Tang et al., 2019), agent communication (Chen et al., 2019), and Transformer-based models (Lu et al., 2021). Recently, a surge of ImgSGG work starts to explore the long-tailed issue in predicate or triplet classification. Existing methods for debiased SGG can be roughly devided to four types: class-aware re-sampling (Li et al., 2021; Desai et al., 2021), loss re-weighting (Lin et al., 2017; Yan et al., 2020; Knyazev et al., 2020), biased-model-based (Tang et al., 2020; Chiou et al., 2021; Yu et al., 2020) and noisy label correction (Li et al., 2022a;b).

Video Scene Graph Generation (VidSGG). Beyond static images, VidSGG aims to detect dynamic visual relations in the videos. Compared to ImgSGG, VidSGG is more challenging because they need to consider the spatio-temporal context in adjacent frames. Based on the formats of relation triplet annotations, existing VidSGG work can be categorized into two groups: 1) **Tracklet-based**: Each graph node is an object tracklet in a video clip (Shang et al., 2017; 2019) or the whole video (Liu et al., 2020; Gao et al., 2021; 2022). 2) **Frame-based**: Each graph node is an object bbox as in ImgSGG, but these visual relation triplets are dynamic in the whole video sequence (Ji et al., 2020; Feng et al., 2021; Cong et al., 2021; Li et al., 2022d). In this paper, we follow the frame-based VidSGG setting, and propose the first weakly-supervised VidSGG setting and model.

Weakly-Supervised ImgSGG. A ground-truth visual relation triplet annotation consists of two object locations, their object categories, and pairwise visual relations. Thus, it is extremely labor-intensive to obtain large-scale fully-annotated scene graph benchmarks. To reduce the labeling costs, several ImgSGG work proposed to generate scene graphs under weak supervision. Currently, there are two main types of weak supervision for ImgSGG: 1) **Unlocalized Scene Graphs** (Zareian et al., 2020; Shi et al., 2021; Li et al., 2022c): It only consists of image-level labels that describe the object and visual relation categories without object locations. 2) **Aligned Captions** (Shi et al., 2021; Ye & Kovashka, 2021): It provides an entailment caption for the given image. In this paper, we only utilize an unlocalized scene graph of a middle frame as the supervision for VidSGG.

Knowledge Distillation (KD). KD is first used for model compression (Hinton et al., 2015). Then, KD becomes a prevalent method to transfer knowledge from a (larger) teacher model to a (smaller) student model. Benefiting from the soft targets generated by teacher models, the student model can even outperform their teachers through appropriate training strategies (Zhang et al., 2018; Furlanello et al., 2018). However, these traditional KD methods are single-teacher. To reduce the limitation of the data diversity and single-teacher knowledge, recent work tries to distill knowledge from multiple teachers. The idea of multi-teacher KD has been widely applied to numerous vision tasks, *i.e.*, object detection (Chen et al., 2017; Wang et al., 2019), visual question answering (Niu & Zhang, 2021; Chen et al., 2022) and ImgSGG (Li et al., 2022c). In this paper, we propose two relation pseudo label assignment teachers and use multi-teacher KD to fuse knowledge of multi-teachers.

3 PROPOSED APPROACH

Task Definition. In this paper, we propose a new VidSGG task: *weakly-supervised VidSGG with single-frame weak supervision* (SF-VidSGG). Specifically, given an input video $V = \{I^1, ..., I^T\}$ with T frames, SF-VidSGG aims to generate a scene graph G^t for each frame I^t, and then stack them along the time axis to obtain the final video scene graph $\mathcal{G} = \{G^1, ..., G^T\}$, where $G^t = (\mathcal{N}^t, \mathcal{E}^t)$, $\mathcal{N}^t$ and $\mathcal{E}^t$ denote the set of graph nodes and edges in G^t, respectively. In the training stage, we only use the weakly-supervision as mentioned in Sec. 1, *i.e.*, the only supervision for SF-VidSGG is an unlocalized scene graph for a middle frame of the video V, denoted as $\widetilde{G}^m = (\widetilde{\mathcal{N}}^m, \widetilde{\mathcal{E}}^m)$, and I^m is the only frame in the video with annotation.

3.1 MODEL OVERVIEW

To tackle the SF-VidSGG task, we propose a novel framework: Pseudo Label Assignment (**PLA**). The whole pipeline of PLA is illustrated in Figure 2. Specifically, it consists of three components: *object pseudo label assignment* (Obj-PLA) module, *relation pseudo label assignment* (Rel-PLA) module, and *future predicate prediction* (FPP) module. In the Obj-PLA, we detect object region proposals for all the frames. For the frame with weak annotation, we further complete its unlocalized scene graph $\widetilde{G}$ to obtain a pseudo localized scene graph G_{pseudo}. In the Rel-PLA, we propose two relation pseudo label assignment teachers: model-based and model-free. The model-based

Figure 2: A overview of PLA. Here we show how to assign pseudo label for one unannotated frame I^t as an example. PLA consists of three module: (a) **Obj-PLA** detects pseudo object bounding boxes and assigns pseudo category labels to them. (b) **Rel-PLA** proposes two teachers to assign pseudo relation annotations (G^t_{soft} and G^t_{hard}). (c) **FPP** first calculates a adapted weight by G^t_{soft} of all frames in the video, then calculates the final pseudo relation annotations (G^t_{final}) by the weighted sum. Finally, we train a fully supervised VidSGG model by G^t_{final}.

teacher assigns "soft" predicate pseudo labels $\mathcal{P}_{\text{soft}}$ by an ImgSGG model, while the model-free teacher assigns "hard" predicate pseudo labels $\mathcal{P}_{\text{hard}}$ by some heuristic rules. After $\mathcal{P}_{\text{soft}}$ and $\mathcal{P}_{\text{hard}}$ are assigned, the FPP module determines adapted weights to fuse $\mathcal{P}_{\text{soft}}$ and $\mathcal{P}_{\text{hard}}$ to obtain the final pseudo label $\mathcal{P}_{\text{final}}$. Finally, we train a fully-supervised VidSGG model by $\mathcal{P}_{\text{final}}$.

3.2 OBJECT PESUDO LABEL ASSIGNMENT (OBJ-PLA)

In this module, we aim to generate pseudo object category annotations for all frames. For each frame I^t in input video, we first use an off-the-shelf detector to generate a set of proposal $\mathcal{O}^t$. Each proposal $o^t_i \in \mathcal{O}^t$ has a corresponding bounding box position b^t_i and an initial object category $\hat{c}^t_i$, *i.e.*, $o^t_i = (b^t_i, \hat{c}^t_i)$. Since the differences in object category ontology between the pretrained detector and VidSGG benchmarks, we then map the detected object categories to the object categories in the VidSGG dataset if there is overlapping between their synonyms in WordNet (Miller, 1995), *e.g.*, "woman" is mapped to "person", "pizza box" is mapped to "box".

For the annotated frame I^m, Obj-PLA has an additional step: matching these detected bounding boxes with entities in the unlocalized scene graph to obtain a pseudo localized scene graph. Here we use a category-based strategy: a bounding box and a entity will be matched if they have the same category. This strategy has a weakness that it cannot distinguish bounding boxes with the same object category. When the detector finds multiple bounding boxes with the same object category, we just randomly choose one of them to match. To solve this problem, Li et al. (2022c) utilizes pretrained VL models to calculate relevant scores between entities with bounding boxes. The final matches are decided by the object category labels and the relevant scores. We leave these advanced methods for the future work.

3.3 RELATION PESUDO LABEL ASSIGNMENT (REL-PLA)

After Obj-PLA, we obtain a pseudo localize scene graph for the annotated Frame and object bboxes for all other unannotated frames. In Rel-PLA, we design two strategies (teachers) to generate pseudo predicate labels for the unannotated frames.

Model-based Teacher. Model-based Teacher assigns "soft" predicate pseudo labels by an ImgSGG model. It first obtains pseudo localized scene graphs G_{pseudo} from the annotated frame set by Obj-PLA, then train a ImgSGG model by these scene graphs. After training, each un-annotated frame I^t is fed to the network to obtain $G^t_{\text{soft}} = M_{\text{img}}(I^t)$, the scene graph for I^t. Here we represent the predicate in G^t_{soft} by the category distribution of predicate, besides one-hot labels. Inspired by knowledge distillation, we believe that the soft pseudo label can preserve more information than the hard pseudo label (Hinton et al., 2015).

Model-free Teacher. Model-free teacher assigns "hard" pseudo prediacte labels by some heuristic rules. The first step is **object sequence matching**. We adopt the object category and the IoU to match the objects detected in the different frames. Two object o_i^t and o_j^{t+1} in adjacent frames can be matched if they have same object categories and $IoU(b_i^t, b_j^{t+1}) > \eta$, where η is the IoU matching threshold to filter objects. We *frame-by-framely* match objects from the middle frame to both ends. As shown in Figure 3, "book" and "towel" in I^{m+2} are not matched with any object in I^{m+1} because there is no object detected in I^{m+1} with category "book" and IoU of bounding boxes with category "towel" in I^{m+1} and I^{m+2} is lower than η. The second step is **relation propagation**. We simply propagate the predicate of a subject-object pair in the annotated frame to the same subject-object pair in the un-annotated frames.

Figure 3: Illustration of model-free teacher.

3.4 FUTURE PREDICATE PREDICTION (FPP) MODULE

Multi-Teacher Fusion Strategy. After obtaining $\mathcal{P}_{\text{soft}}$ and $\mathcal{P}_{\text{hard}}$ by two teachers, the simplest fusing strategy is treating each teacher equally and averaging the two pseudo labels. However, this strategy overlooks the noise in the model-based teacher. The model-based teacher sometimes assign wrong pseudo labels due to the incorrect predictions in model M_{img}. On the other hand, pseudo labels assigned by the model-free teacher can be seen as the default predictions because these labels have already appeared in the video. To some extent, the model-free teacher can be seen as a complement when the model-based teacher assign a wrong pseudo label. Therefore, a better strategy is assigning adaptive weights for $\mathcal{P}_{\text{soft}}$ and $\mathcal{P}_{\text{hard}}$ and then calculating the final pseudo labels by the weighted sum:

$$\mathcal{P}_{\text{final}}^i = w_{\text{soft}}^i * \mathcal{P}_{\text{soft}}^i + w_{\text{hard}}^i * \mathcal{P}_{\text{hard}}^i, \tag{1}$$

where w_{soft}^i and w_{hard}^i denotes the weights of the soft and hard predicate labels for video i, respectively. In the FPP module, we calculate w_{soft}^i and w_{hard}^i by regularity of relation transition.

Relation Transition. Relation transition means how the predicates change between the same subject-object pairs in different frames. Mi et al. (2021) has proved that relation transition has the temporal tendency, which means we can infer their relationship in the next frame through their relationship in the current frame for the same subject-object pair. As the example shown in Figure 4, we can found two main conclusions: 1) Relation transitions have some regular patterns, *e.g.*, for subject-object pair "people-chair", relation "leaning on " is mainly transferred to "sitting on", but hardly transferred to "lying on" and "standing on". 2) Relation transitions with different subject-object pairs have different regular patterns, *e.g.*, the statistical distributions for "people-chair" and "people-food" are different. Therefore, we can evaluate the quality of predicate pseudo labels by regularity of relation transition in video. Specifically, irregular relation transitions (*e.g.*, "leaning on" → "lying on" for "people-chair") are of low quality, then we assign low weights to them.

Proposed FPP. As shown in Figure 5, We take two steps to calculate weights w_{soft} and w_{hard}. 1) **Predicate prediction**: For each predicate p^t in I^t assigned by the model-based teacher, we predict $\hat{p}^{t+1}$ as the predicate that p^t will transition to in I^{t+1}. For each $\hat{p}^{t+1}$, we find its corresponding predicate p^{t+1} in I^{t+1} that actually assigned by the model-based teacher. 2) **Adapted weight assignment**: We first calculate KL-divergence between $\hat{p}^{t+1}$ and p^{t+1} as the inconsistency score. Then, we assign low weights to pseudo labels with high inconsistency scores and high weights to pseudo labels with low inconsistency scores. In the following, we detailed introduce these two steps.

Predicate Prediction. To predict the future predicates, we construct a relation transition matrix $T \in \mathbb{R}^{N_o * N_r * N_r}$, where N_o, N_r are the number of objects and relations in the dataset, respectively. The relation transition matrix indicates the statistical distribution of relation transition in the VidSGG dataset. Given a relation p^t in frame I^t with object category c_o, we predict the future predicate $\hat{p}^{t+1}$

Figure 4: Statistical distributions of relation transition in AG dataset.

Figure 5: Illustration of the FPP, which consists of two parts: predicate prediction and adapted weight assignment.

for the same subject-object pair in I^{t+1} as:

$$\hat{p}^{t+1} = p^t \times T[id(c_o)], \tag{2}$$

where $id(c_o)$ is the id of c_o in the vocabulary C_o^g. There is a small problem that $\hat{p}^{t+1}$ sometimes does not have its corresponding predicate p^{t+1} in frame I^{t+1} because the detector can not detect the subject-object pair. Similar to object sequence matching in the model-free teacher, we adopt the object category and the IoU to filter predicates without corresponding subject-object pair in the next frame. The set of $\hat{p}^{t+1}$ and p^{t+1} after filtering in the whole video are denoted as $\hat{\mathcal{P}}_{\text{filter}}$ and $\mathcal{P}_{\text{filter}}$, respectively.

Adapted Weight Assignment. We first calculate the inconsistency score by KL-divergence as below:

$$S_{\text{incon}} = \text{KL}(\hat{\mathcal{P}}_{\text{filter}}||\mathcal{P}_{\text{filter}}). \tag{3}$$

We then calculate the inconsistency score for $\mathcal{P}_{\text{soft}}$, denoted as $S_{\text{incon}}^{\text{soft}}$. A high inconsistency score indicates that these predicate pseudo labels do not satisfy the regularity of relation transition, so we should assign low weights to them. To the end, we define the function as:

$$w_{\text{soft}} = 2 - 2 * \text{Sigmoid}(S_{\text{incon}}^{\text{soft}}), \quad w_{\text{hard}} = 1 - w_{\text{soft}}. \tag{4}$$

3.5 TRAINING OBJECTIVES

FPP module. We assume that the relation transition matrix T in FPP module indicates the statistical distribution of relation transition in the VidSGG dataset. However, in the SF-VidSGG task, we can not count the distribution of relation transition directly because we only have single-frame weak supervision for each video. An alternative approach is generating pseudo labels by the model-based teacher and then learning the distribution of these pseudo labels. To accomplish this, we formulate the loss function as below to train the FPP module:

$$\mathcal{L}_{\text{FPP}} = \text{KL}(\hat{\mathcal{P}}_{\text{filter}}^{\text{soft}}||\mathcal{P}_{\text{filter}}^{\text{soft}}), \tag{5}$$

Student Model. We adopt the KL-divergence loss for training like most knowledge distillation methods, which can be formulated as follows:

$$\mathcal{L}_{\text{KD}} = \text{KL}(\mathcal{P}_{\text{pred}}||\mathcal{P}_{\text{final}}), \tag{6}$$

where $\mathcal{P}_{pred}$ denotes the output of the student model, and $\mathcal{P}_{final}$ denotes the predicate pseudo labels.

Finally, the total training loss of PLA is:

$$\mathcal{L} = \mathcal{L}_{\text{KD}} + \mathcal{L}_{\text{FPP}}. \tag{7}$$

4 EXPERIMENTS

4.1 EXPERIMENTAL SETTINGS

Datasets. We evaluated our method PLA on the challenging VidSGG benchmark: Action Genome (AG) (Ji et al., 2020). AG is a prevalent VidSGG dataset providing human-object relationships with

frame-level annotations. Specifically, AG consists of 9,201 videos, which annotated for 234,253 frames by 476,299 bounding boxes of 36 object categories and 1,715,568 instances of 25 relation categories. All relation categories in AG are split into three types: 3 attention relations, 6 spatial relations and 16 contact relations. Each subject-object pair has one attention relation but may has multiple spatial or contact relations. In our SF-VidSGG setting, we used the official splits as fully-supervised work, *i.e.*, 7,464 videos for training, 1,737 videos for testing. For each video in the training set, we only used the unlocalized scene graph of the middle frame as supervision.

Evaluation Metrics. Following the fully-supervised setting, we evaluated PLA on three different settings: 1) *Scene Graph Detection* (**SGDet**): Given a video, the model needs to detect the objects and predict predicate categories of object pairs for all frame. In SGDet, an object is considered to be successfully detected if the IoU between the predicted bbox and its ground-truth bbox is larger than 0.5. 2) *Scene Graph Classification* (**SGCls**): Given a video and object bboxes, the model needs to predict object and predicate categories for all frames. 3) *Predicate Classification* (**PredCls**): Given a video, object bboxes and object labels, the model needs to predict predicate categories for all frames. Since the ground-truth bboxes are not provided in SF-VidSGG, we only trained models under **SGDet** settings, then evaluated them under these three settings. We used Recall@K (**R@K**, K = [10,20,50]) as our evaluation metric, which measures the ratio of the ground-truth relation triplets among the top-K predicted relation triplets. Furthermore, we adopt two typical strategies to generate dynamic scene graphs: 1) **With Constraint**: It only allows each subject-object pair to have at most one predicate. 2) **No Constraint**: It allows each subject-object pair to have multiple predicates.

Implementation Details. In the Obj-PLA module, we used the pretrained VinVL (Li et al., 2020; Zhang et al., 2021) with backbone ResNeXt-152 C4 as the off-the-shelf detector. Specifically, it is pre-trained on multiple detection benchmarks, including COCO (Lin et al., 2014), OpenImages (Kuznetsova et al., 2020), Objects365 (Shao et al., 2019), and Visual Genome (Krishna et al., 2017). This detector is capable of detecting 1,594 general object categories. We kept objects which confidence is higher than 0.2 and extracted the 2048-D region features from the detector. In the Rel-PLA module, we modified STTran (Cong et al., 2021) to an ImgSGG model that process one frame at a time, denoted as STTran†. We used STTran† as the teacher model to assign pseudo soft labels in Rel-PLA. For the model-free teacher, we set the IOU matching threshold $\eta = 0.5$. In FPP module, we set the initial learning rate $1e^{-3}$. We used STTran as the student model, and followed the same training settings (*e.g.*, learning rate and batch size) of the original paper.

4.2 ABLATION STUDIES

In this section, we validated the effectiveness of our PLA by answering the following questions: **Q1**: How does each component in PLA contribute to the performance on the SF-VidSGG task? **Q2**: What is the upper-bound under our pseudo label assignment training paradigm? **Q3**: How do we choose hyperparameters in our model?

4.2.1 EFFECTIVENESS OF EACH COMPONENT (Q1)

Settings. To analyze the importance of each component in PLA, we implemented the straightforward model mentioned in Sec. 1 as the baseline model. It first obtained pseudo localized scene graphs G_{pseudo} from the annotated frame set by Obj-PLA, then trained a STTran† model by these scene graphs. The gray lines in Table 1 show the results of the baseline model (model A). We also trained the models with different components of PLA, which is shown in Table 1.

Effectiveness of Rel-PLA. Compared to the baseline model A, models with model-based teacher or model-free teacher (model B and model C) has a significant improvement. The experimental results demonstrate that by utilizing the unannotated frames in the video, model B and model C are able to outperform the baseline model A across almost all the metrics, only except for no constrained PredCls-R@50 of model B. Particularly, model B and model C have outperformed the baseline by 5.24% (15.07 *v.s.*14.32) and 2.58% (14.69 *v.s.*14.32) relatively in terms of R@10 with constraint criteria for SGDet, respectively. This is owing to that the two teachers have the ability to assign high-quality pseudo labels to the unannotated frames.

Table 1: Performance (%) on dataset Action Genome of models with different components of PLA. Model A is the baseline, B only uses model-based teacher, C only uses model-free teacher, D uses both teachers and treats them equally, E uses both teachers and set adapted weights by FPP module.

Task	Model	Components				With Constraint			No Constraint		
		Obj-PLA	Model-based	Model-free	FPP	R@10	R@20	R@50	R@10	R@20	R@50
SGDet	A	✓	✗	✗	✗	14.32	20.42	25.43	14.78	21.72	30.87
	B	✓	✓	✗	✗	14.99	21.11	26.12	15.46	22.56	**31.75**
	C	✓	✗	✓	✗	14.69	20.71	25.70	15.09	22.04	31.26
	D	✓	✓	✓	✗	15.11	21.16	26.03	15.57	22.56	31.60
	E	✓	✓	✓	✓	**15.39**	**21.44**	**26.24**	**15.83**	**22.83**	31.74
SGCls	A	✓	✗	✗	✗	35.19	35.80	35.80	44.25	51.76	55.80
	B	✓	✓	✗	✗	36.58	37.19	37.20	45.54	52.52	**56.46**
	C	✓	✗	✓	✗	35.70	36.32	36.32	45.44	52.82	56.07
	D	✓	✓	✓	✗	36.48	37.06	37.06	44.52	52.52	56.17
	E	✓	✓	✓	✓	**36.81**	**37.46**	**37.46**	**46.00**	**53.01**	56.42
PredCls	A	✓	✗	✗	✗	59.58	61.13	61.13	74.86	89.91	98.26
	B	✓	✓	✗	✗	61.23	62.79	62.79	76.08	89.91	97.92
	C	✓	✗	✓	✗	61.26	62.93	62.93	77.09	**91.99**	**99.00**
	D	✓	✓	✓	✗	61.19	62.69	62.70	76.51	90.82	98.46
	E	✓	✓	✓	✓	**61.64**	**63.25**	**63.25**	**77.20**	91.53	98.61

Table 2: Performance (%) for SGDet on AG of baseline, GTRel and PLA. GTRel can be treated as the upper-bound model.

Method	With Constraint			No Constraint		
	R@10	R@20	R@50	R@10	R@20	R@50
Baseline	14.32	20.56	25.73	14.72	21.93	30.87
PLA	15.39	21.44	26.24	15.83	22.83	31.74
GTRel	**16.10**	**22.38**	**27.33**	**16.73**	**24.02**	**33.40**

Table 3: Performance (%) for SGDet on AG of the model only uses model-free teacher with different IoU matching threshold η.

η	With Constraint			No Constraint		
	R@10	R@20	R@50	R@10	R@20	R@50
0.0	13.58	19.52	24.62	14.02	20.95	30.49
0.2	14.64	20.54	25.33	**15.11**	22.03	31.11
0.5	**14.69**	**20.71**	**25.70**	15.09	**22.04**	**31.26**

Effectiveness of FPP. As shown in Table 1, model D and model E are all use both teachers, but model E uses the FPP module to set adapted weights. We can observe that model E outperforms model D across all the metrics. Especially, model E has achieved about 2% relative improvement over model D on R@10 metric under the no constraint criteria for SGDet. The improvement proves that FFP has the ability to assign more accurate pseudo labels than the simple fixed weight strategy.

4.2.2 BEST CASE: GROUND-TRUTH UNLOCALIZED SCENE GRAPHS (Q2)

Settings. To address this question, we trained a model with the ground-truth unlocalized scene graph annotations of all frames as the upper-bound model, denoted as GTRel. More specifically, we first utilized the Obj-PLA module to generate pseudo localized scene graphs from the ground-truth unlocalized scene graphs. Then we used these pseudo localized scene graphs to train a VidSGG model. Here we fixed the off-shelf detector in Obj-PLA and the final student model, because PLA is agnostic to them. We compared baseline model, PLA and GTRel in Table 2.

Results. As shown in Table 1, we observe that GTRel significantly improves the performance over the baseline. Specifically, GTRel has outperformed the baseline by 13.19% (16.73 *v.s.* 14.72) relatively in terms of R@10 no constraint criteria for SGDet. We also demonstrate that PLA has ability to reduce the gap between the baseline model and GTRel. For example, GTRel improves by 12.43% (16.10 *v.s.* 14.32) relatively over baseline in terms of R@10 with constraint criteria for SGDet, but only improves by 4.61% (16.10 *v.s.* 15.39) relatively over PLA on same metric. These results show that PLA is able to reduce about half performance gap between the baseline model and the upper-bound model GTRel for the SF-VidSGG task.

4.2.3 ABLATION STUDY ON HYPERPARAMETER SETTINGS (Q3)

Settings. We analyzed the influence of the hyperparameter η, which denote the IoU matching threshold in Rel-PLA. We set different η for the model only uses model-free teacher (model C). All results are in Table 3. Particularly, when the threshold η is set to 0, we match the objects in different frames only by the object category without the IoU of the bounding boxes in adjacent frames.

Figure 6: Visualization results of pseudo labels assigned by: (a) ground-truth, (b) model-based teacher, (c) model-free teacher, (d) both teachers with fixed weights, (e) both teachers with adapted weights. (a) and (b) are hard labels (each node indicates a single relation), while (c) - (e) are soft labels (each node indicates a relation distribution). The green relations mean correct predictions, the yellow relations are wrong predictions that do not exist in the ground-truth.

Figure 7: Qualitative results for the statistical distributions of relation transition. In each subfigure, the left is the ground-truth result and the right is result of PLA.

Results. As shown in Table 3, we can observe that the model with $\eta = 0$ has a weak performance due to more wrong objects matching without IoU information. And the model with $\eta = 0.5$ slightly outperforms the model with $\eta = 0.2$. Therefore, we set $\eta = 0.5$ for all experiments.

4.3 QUALITATIVE RESULTS

Pseudo Label Visualization. Figure 6 shows a qualitative comparison of the pseudo labels generated by different variants of PLA. Results indicates that the adapted weights given by FPP module can generate more accurate pseudo labels than fixed weights. For example, relation in T^{m+1} ("not contacting") is different from that in T^m ("touching" and "sitting on"), so the model-free teacher give totally wrong relations ("touching" and "sitting on") and the model-based teacher predict an almost accurate relation (98% for "not contacting"). Compared to the fixed weight, the FPP module gives more weight to the model-based teacher, and generates more accurate pseudo labels.

Relation Transition Distribution Visualization. Figure 7 demonstrates the statistical distributions of relation transition counted by ground truth and learned by PLA. From Figure 7, we can observe that PLA can learn a distribution similar to the ground truth.

5 CONCLUSIONS

In this paper, we presented the first weakly-supervised VidSGG task with only single-frame weak supervision: SF-VidSGG. Unlike VidSGG, SF-VidSGG only require a weak annotaion without bounding box for one frame in each video. To the end, we proposed a novel and efficient method named PLA for SF-VidSGG, which based on pseudo label assignment for the video. We validated the effectiveness of each component of PLA through extensive experiments. In future work, we would like to explore weaker supervision in VidSGG or more accurate pseudo label assignment.

Ethics Statement

Video scene generation models can be utilized in unauthorized human monitoring and surveillance, which leads to some ethical and privacy issues. Apart from these general issues that already exist in the video scene graph generation task, our paper has no additional ethical issues.

Reproducibility Statement

PLA is mainly implemented based on the released code of STTran (Cong et al., 2021) and evaluated on the Action Genome (AG) (Ji et al., 2020) dataset, which is publicly available with a license that allows free usage for research purposes. We will also release our code of PLA.

REFERENCES

Guobin Chen, Wongun Choi, Xiang Yu, Tony Han, and Manmohan Chandraker. Learning efficient object detection models with knowledge distillation. *Advances in neural information processing systems*, 30, 2017.

Long Chen, Hanwang Zhang, Jun Xiao, Xiangnan He, Shiliang Pu, and Shih-Fu Chang. Counterfactual critic multi-agent training for scene graph generation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4613–4623, 2019.

Long Chen, Yuhang Zheng, and Jun Xiao. Rethinking data augmentation for robust visual question answering. *arXiv preprint arXiv:2207.08739*, 2022.

Meng-Jiun Chiou, Henghui Ding, Hanshu Yan, Changhu Wang, Roger Zimmermann, and Jiashi Feng. Recovering the unbiased scene graphs from the biased ones. In *Proceedings of the 29th ACM International Conference on Multimedia*, pp. 1581–1590, 2021.

Yuren Cong, Wentong Liao, Hanno Ackermann, Bodo Rosenhahn, and Michael Ying Yang. Spatial-temporal transformer for dynamic scene graph generation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16372–16382, 2021.

Alakh Desai, Tz-Ying Wu, Subarna Tripathi, and Nuno Vasconcelos. Learning of visual relations: The devil is in the tails. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15404–15413, 2021.

Shengyu Feng, Subarna Tripathi, Hesham Mostafa, Marcel Nassar, and Somdeb Majumdar. Exploiting long-term dependencies for generating dynamic scene graphs. *arXiv preprint arXiv:2112.09828*, 2021.

Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *International Conference on Machine Learning*, pp. 1607–1616. PMLR, 2018.

Kaifeng Gao, Long Chen, Yifeng Huang, and Jun Xiao. Video relation detection via tracklet based visual transformer. In *Proceedings of the 29th ACM International Conference on Multimedia*, pp. 4833–4837, 2021.

Kaifeng Gao, Long Chen, Yulei Niu, Jian Shao, and Jun Xiao. Classification-then-grounding: Reformulating video scene graphs as temporal bipartite graphs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 19497–19506, 2022.

Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2(7), 2015.

Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6700–6709, 2019.

Jingwei Ji, Ranjay Krishna, Li Fei-Fei, and Juan Carlos Niebles. Action genome: Actions as compositions of spatio-temporal scene graphs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10236–10247, 2020.

Chenchen Jing, Yuwei Wu, Mingtao Pei, Yao Hu, Yunde Jia, and Qi Wu. Visual-semantic graph matching for visual grounding. In *Proceedings of the 28th ACM International Conference on Multimedia*, pp. 4041–4050, 2020.

Justin Johnson, Ranjay Krishna, Michael Stark, Li-Jia Li, David Shamma, Michael Bernstein, and Li Fei-Fei. Image retrieval using scene graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3668–3678, 2015.

Boris Knyazev, Harm de Vries, Cătălina Cangea, Graham W Taylor, Aaron Courville, and Eugene Belilovsky. Graph density-aware losses for novel compositions in scene graph generation. *arXiv preprint arXiv:2005.08230*, 2020.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, et al. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 123(1):32–73, 2017.

Alina Kuznetsova, Hassan Rom, Neil Alldrin, Jasper Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Malloci, Alexander Kolesnikov, et al. The open images dataset v4. *International Journal of Computer Vision*, 128(7):1956–1981, 2020.

Lin Li, Long Chen, Yifeng Huang, Zhimeng Zhang, Songyang Zhang, and Jun Xiao. The devil is in the labels: Noisy label correction for robust scene graph generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18869–18878, 2022a.

Lin Li, Long Chen, Hanrong Shi, Wenxiao Wang, Jian Shao, Yi Yang, and Jun Xiao. Label semantic knowledge distillation for unbiased scene graph generation. *arXiv preprint arXiv:2208.03763*, 2022b.

Rongjie Li, Songyang Zhang, Bo Wan, and Xuming He. Bipartite graph network with adaptive message passing for unbiased scene graph generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11109–11119, 2021.

Xingchen Li, Long Chen, Wenbo Ma, Yi Yang, and Jun Xiao. Integrating object-aware and interaction-aware knowledge for weakly supervised scene graph generation. In *Proceedings of the 30th ACM international conference on Multimedia*, 2022c.

Xiujun Li, Xi Yin, Chunyuan Li, Xiaowei Hu, Pengchuan Zhang, Lei Zhang, Lijuan Wang, Houdong Hu, Li Dong, Furu Wei, Yejin Choi, and Jianfeng Gao. Oscar: Object-semantics aligned pre-training for vision-language tasks. *ECCV 2020*, 2020.

Yikang Li, Wanli Ouyang, Bolei Zhou, Kun Wang, and Xiaogang Wang. Scene graph generation from objects, phrases and region captions. In *Proceedings of the IEEE international conference on computer vision*, pp. 1261–1270, 2017.

Yiming Li, Xiaoshan Yang, and Changsheng Xu. Dynamic scene graph generation via anticipatory pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13874–13883, 2022d.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Chenchen Liu, Yang Jin, Kehan Xu, Guoqiang Gong, and Yadong Mu. Beyond short-term snippet: Video relation detection with spatio-temporal global context. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10840–10849, 2020.

Cewu Lu, Ranjay Krishna, Michael Bernstein, and Li Fei-Fei. Visual relationship detection with language priors. In *European conference on computer vision*, pp. 852–869. Springer, 2016.

Yichao Lu, Himanshu Rai, Jason Chang, Boris Knyazev, Guangwei Yu, Shashank Shekhar, Graham W Taylor, and Maksims Volkovs. Context-aware scene graph generation with seq2seq transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15931–15941, 2021.

Li Mi, Yangjun Ou, and Zhenzhong Chen. Visual relationship forecasting in videos. *arXiv preprint arXiv:2107.01181*, 2021.

George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11): 39–41, 1995.

Yulei Niu and Hanwang Zhang. Introspective distillation for robust question answering. *Advances in Neural Information Processing Systems*, 34:16292–16304, 2021.

Xindi Shang, Tongwei Ren, Jingfan Guo, Hanwang Zhang, and Tat-Seng Chua. Video visual relation detection. In *Proceedings of the 25th ACM international conference on Multimedia*, pp. 1300–1308, 2017.

Xindi Shang, Donglin Di, Junbin Xiao, Yu Cao, Xun Yang, and Tat-Seng Chua. Annotating objects and relations in user-generated videos. In *Proceedings of the 2019 on International Conference on Multimedia Retrieval*, pp. 279–287, 2019.

Shuai Shao, Zeming Li, Tianyuan Zhang, Chao Peng, Gang Yu, Xiangyu Zhang, Jing Li, and Jian Sun. Objects365: A large-scale, high-quality dataset for object detection. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 8430–8439, 2019.

Jing Shi, Yiwu Zhong, Ning Xu, Yin Li, and Chenliang Xu. A simple baseline for weakly-supervised scene graph generation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16393–16402, 2021.

Kaihua Tang, Hanwang Zhang, Baoyuan Wu, Wenhan Luo, and Wei Liu. Learning to compose dynamic tree structures for visual contexts. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6619–6628, 2019.

Kaihua Tang, Yulei Niu, Jianqiang Huang, Jiaxin Shi, and Hanwang Zhang. Unbiased scene graph generation from biased training. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 3716–3725, 2020.

Tao Wang, Li Yuan, Xiaopeng Zhang, and Jiashi Feng. Distilling object detectors with fine-grained feature imitation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4933–4942, 2019.

Danfei Xu, Yuke Zhu, Christopher B Choy, and Li Fei-Fei. Scene graph generation by iterative message passing. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5410–5419, 2017.

Shaotian Yan, Chen Shen, Zhongming Jin, Jianqiang Huang, Rongxin Jiang, Yaowu Chen, and Xian-Sheng Hua. Pcpl: Predicate-correlation perception learning for unbiased scene graph generation. In *Proceedings of the 28th ACM International Conference on Multimedia*, pp. 265–273, 2020.

Xu Yang, Kaihua Tang, Hanwang Zhang, and Jianfei Cai. Auto-encoding scene graphs for image captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10685–10694, 2019.

Xu Yang, Chongyang Gao, Hanwang Zhang, and Jianfei Cai. Hierarchical scene graph encoder-decoder for image paragraph captioning. In *Proceedings of the 28th ACM International Conference on Multimedia*, pp. 4181–4189, 2020.

Keren Ye and Adriana Kovashka. Linguistic structures as weak supervision for visual scene graph generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8289–8299, 2021.

Jing Yu, Yuan Chai, Yujing Wang, Yue Hu, and Qi Wu. Cogtree: Cognition tree loss for unbiased scene graph generation. *arXiv preprint arXiv:2009.07526*, 2020.

Alireza Zareian, Svebor Karaman, and Shih-Fu Chang. Weakly supervised visual semantic parsing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3736–3745, 2020.

Rowan Zellers, Mark Yatskar, Sam Thomson, and Yejin Choi. Neural motifs: Scene graph parsing with global context. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5831–5840, 2018.

Hanwang Zhang, Zawlin Kyaw, Shih-Fu Chang, and Tat-Seng Chua. Visual translation embedding network for visual relation detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5532–5540, 2017.

Pengchuan Zhang, Xiujun Li, Xiaowei Hu, Jianwei Yang, Lei Zhang, Lijuan Wang, Yejin Choi, and Jianfeng Gao. Vinvl: Making visual representations matter in vision-language models. *CVPR 2021*, 2021.

Ying Zhang, Tao Xiang, Timothy M Hospedales, and Huchuan Lu. Deep mutual learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4320–4328, 2018.

Yiwu Zhong, Jing Shi, Jianwei Yang, Chenliang Xu, and Yin Li. Learning to generate scene graph from natural language supervision. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1823–1834, 2021.