Subjective Code Preferences in Experts and Large Language Models

Abstract

Coding preferences are important for modern Large Language Models (LLMs) systems to adapt to programmers' personal needs. However, existing work mainly focuses on code correctness and overlooks subjective coding characteristics. In this work, we propose a typification of four subjective coding preference axes — complexity, commenting, modularity, and readability — motivated by common engineering habits and validated by 25 software engineers. We collect a dataset of approximately 3,000 paired Python code snippets reflecting these axes, annotated by 78 expert coders who rate their preferences on a Likert scale. Using this dataset, we study how LLMs handle subjective coding preferences. We prompt 13 LLMs to select preferences both through textual descriptions and code examples. We find systematic inconsistencies and positional bias. We then use the five most consistent models (i.e., those that are coherent in their choices between coding deeds and words) to re-annotate the dataset. Compared to humans, models show polarized Likert distributions and notable divergence in ratings, up to more than two points. A case study on GPT-5 further reveals reliance on external assumptions and brittle reasoning.[1]

1 Introduction

In recent years, LLMs have become broadly used as coding tools (Ferino et al., 2025). Their evaluation typically involves benchmarks targeting objective aspects like code correctness and security (Weyssow et al., 2024a; Liu et al., 2024). This, however, limits the evaluation to a "correct vs incorrect" answer paradigm, and does not tell us how LLMs behave when subjective coding preferences come into play. This is especially critical since LLMs can be inconsistent in opinion-based or value-related domains (Xu et al., 2025). Focusing only on objective criteria also contradicts the fundamental

definition of a *preference* (Brafman and Domshlak, 2009), which is a set of *alternative* choices, where a more desirable choice precedes a less desirable one. Assessing code quality criteria beyond correctness is necessary in expert coding domains, like software engineering, where code needs to be optimized across multiple criteria (Li and Chen, 2024a) influencing each other (Buse and Weimer, 2009; Tashtoush et al., 2023a).

In this work, we provide an extensive investigation of LLMs' behavior across subjective coding preferences (Figure 1). First, we introduce a set of coding preferences axes that are subjective (i.e., both preference values produce a working code) but can still be measured and shown from the previous work to be important for SW development (Tashtoush et al., 2023b; Souza et al., 2005): commenting, modularity, readability, and complexity. To validate our choices, we survey 25 experts from diverse coding domains, who confirm our axes are indeed subjective and important in real-world coding. We then generate a novel dataset of $\approx 3K$ paired Python snippets, where each snippet of a pair represents a different value on our preference axes (e.g. more vs less commented code to solve the same problem). This dataset is then fully annotated by 78 coding experts, using a Likert-6 scale to express their subjective preferences for each pair (e.g. Strongly/Slightly prefer snippet A over snippet B). Borderline annotations (slight preferences) are enriched by experts with textual rationale.

We use our generated dataset to analyze the behavior and alignment of 13 LLMs in two setups. First, we test if LLMs are consistent in expressing a utility at a textual level (e.g., "a more commented code") and code level (actual coding snippets of more or less commented code). All tested LLMs show severe inconsistency, choosing a specific textual preference, but then picking the opposite coding snippet. Most of the tested models also show

---

Figure 1: Overview of our dataset construction and experimental pipeline.

extreme positional bias, where the choices stay unaltered even if we swap the coding snippets.

Second, we let LLMs replicate our dataset annotation, and compare their preference distribution with that of experts: most models show misalignment, with polarized choices (predominantly choosing the extremes of our selection scale), compared to the more balanced one of our experts. GPT-5, the only exception, models the overall human distribution over our dataset quite well, but still shows severe divergence on a per-item basis. We also run a case study where we qualitatively inspect cases of disagreement between experts and GPT-5, showing reliance on external assumptions (metrics and criteria that are not relevant to the preference) and brittle reasoning, culminating in ignoring core knowledge necessary for a correct assessment.

To summarize, this paper provides the following three contributions (Figure 1):

1. A novel dataset of Python coding snippets showcasing subjective preferences, validated and annotated by expert SE (§3).

2. First assessment of LLM consistency on making subjective coding preferences, across natural language and code modality (§4).

3. Analysis of the alignment and behavior between LLMs and humans with respect to subjective coding preferences (§5).

2 Related Work

Coding Preferences Previous works related to LLMs' coding preferences (Weyssow et al., 2024a;

Liu et al., 2024) inspect objective criteria, such as security or correctness, marking the code in correct/incorrect (Liu et al., 2024; Weyssow et al., 2024a). These studies do not reflect the complexity of decisions and tradeoffs that a developer experiences, especially when moving from casual coders (like students) to professionals (like software engineers) (Dutta et al., 2025). This is also reflected in existing datasets like CodeUltraFeedback (Weyssow et al., 2024a), CodePrefBench (Liu et al., 2024), and OpenCodeInstruct (Ahmad et al., 2025), which focus on tuning LLMs for software development problems, but not on preference alignment. This results in LLMs developing towards code generation correctness and ignoring humans' priority for a more nuanced and complex approach to software development (Azeem et al., 2025).

Our work, on the contrary, proposes justified code characteristics that do not focus only on code correctness. Exploring various code utilities and what professionals prefer in a code besides correctness is a crucial focus for different aspects of software engineering. Some examples of the importance of this multi-criteria analysis include readability's enhancement of software maintainability (Buse and Weimer, 2010b; Tashtoush et al., 2023b), or development optimization across multiple objectives (Li and Chen, 2024b). We also note that, while there is previous research proposing integrated benchmarking to assess coding criteria beyond correctness (Zheng et al., 2024), it does not provide validation from the side of the end usersC(expert coders), which is presented in our study.

Human-LLM preferences comparison Being trained on vast amounts of natural language data, LLMs show similar decision heuristics to humans

in text generation (Suri et al., 2023), including pre-existing biases and conceptual behavior tendencies. However, this human-like pattern is not exhibited in controlled binary-choice experiments, where the decision-making requires broader narrative support (Jia et al., 2024). This leads to LLMs being more prone to hesitating and admitting their limits in the presence of a clear dislike (Li et al., 2024). Additionally, AI systems are argued to better maximize the satisfaction of preferences and uncover hidden contexts by integrating normative reasoning with machine learning (Zhi-Xuan et al., 2024). On this experiment, we enrich borderline preferences with textual rationale to gain a better, first-of-its-kind understanding of how humans and LLMs ground their choices with regard to decision-making in the coding domain.

LLM Alignment on Code and Natural Language Prompt-based inference has been shown to enhance LLMs' performance across a variety of coding tasks, mostly generation (Jain et al., 2021; Weyssow et al., 2024b) and testing (Kang et al., 2023; Lemieux et al., 2023). This includes Few-shot prompting (Song et al., 2022), and Chain-of-Thoughts reasoning (Wei et al., 2023). However, while LLMs are ideally expected to reliably judge whether a given code satisfies the requirements given in a natural language, they systematically fail in correctly performing such "description-to-code" evaluations stemming mainly from inherent biases and hallucinations within LLMs (Jin and Chen, 2025). There is no up-to-date proof of the positive contributions of these methodologies to LLMs' alignment between words and coding deeds. We address this in our study, by exploring different prompting setups.

3 Data

3.1 Coding Preferences

We define four coding preferences axes: commenting, complexity, modularity, and readability. Each axis is designed to be subjective but measurable. They do not affect the code correctness; instead, the choice for each preference is motivated by the individual professional experience of expert coders. For example, a more or less modular code does not necessarily affect the correctness of the code but might be more appropriate given the developers' preferences, project requirements, or standard protocols from industry.

Commenting Appropriate code commenting benefits code maintenance, and speeds up debugging. However, excessive or redundant comments can be detrimental. *'Commenting'* utility represents the extent to which a code snippet contains commented lines, including the code documentation (Rani et al., 2023).

Consider a code snippet $\mathcal{S}$, with $\mathcal{L}_{\text{total}}(\mathcal{S})$ total lines, and $\mathcal{L}_{\text{comment}}(\mathcal{S}) \subseteq \mathcal{L}_{\text{total}}(\mathcal{S})$ commented lines. The commenting score $CS(\mathcal{S})$ is:

$$\text{CS}(\mathcal{S}) = \frac{|\mathcal{L}_{\text{comment}}(\mathcal{S})|}{|\mathcal{L}_{\text{total}}(\mathcal{S})|}.$$

Modularity Code modularity refers to the practice of breaking down a large program into smaller, independent, and reusable units called modules. Making a correct and balanced use of this coding feature can improve code organization, re-usability, and maintainability. Modularity is typically measured by the number of separate modules and functions, divided by the total number of code lines (Hughes and Hogskola, 1999). Specifically, given a snippet $\mathcal{S}$, with $\mathcal{M}(\mathcal{S})$ distinct modules and functions, and $\mathcal{L}_{\text{total}}(\mathcal{S})$ lines of code, the modularity score of $\text{MS}(\mathcal{S})$ is:

$$\text{MS}(\mathcal{S}) = \frac{|\mathcal{M}(\mathcal{S})|}{|\mathcal{L}_{\text{total}}(\mathcal{S})|}.$$

Complexity The degree of complexity of a code can have a profound effect on maintainability, developer productivity, software quality, performance, and overall business cost. For this preference, we consider coding snippets with opposite complexity codes in terms of big O-notation (Sikka et al., 2019). Consider a program $\mathcal{P}$ with input size n, $T_{\mathcal{P}}(n)$ time complexity, and $S_{\mathcal{P}}(n)$ space complexity functions. The asymptotic complexity class of $\mathcal{P}$ is characterized by:

$$\mathcal{C}(\mathcal{P}) = (\mathcal{O}(T_{\mathcal{P}}(n)), \mathcal{O}(S_{\mathcal{P}}(n))),$$

Readability Code readability is a fundamental coding characteristic (Börstler et al., 2023; Wyrich et al., 2023) that defines developers' preferences and values in structuring their code. However, it is very subjective and experience-based, without an established unified measurement (Scalabrino et al., 2017). One definition of readability is linked to judging how easy a text is to understand (Buse and Weimer, 2010a), which can be represented in overt code features (e.g., average or maximal line length,

number of loops, etc.). On the other hand, discussions on this topic (Rosenberg et al., 1998; Chidamber and Kemerer, 1994; Oliveira et al., 2025) agree that following the coding standards, cyclomatic complexity, and code maintainability are also associated with the concept of readability.

We propose a consensus readability model combining overt code features and established notions of readability. More specifically, we train a multiple linear regression with code local factors as independent variables and scores acquired by three methods that to some extent reflect readability as dependent variables. Additional information can be found in the Figure 5 in the Appendix A. Thus, we acquire a code readability score that, combined with the complexity value, lets us evaluate the Readability/Complexity tradeoff.

Axes validation   The goal of our work is to investigate subjective preferences that matter in the real-world coding. Therefore, we validate our four axes through an online survey with experts (see details in Appendix B). We recruit 25 coders from Upwork[2] with background in backend development (28%), frontend development (24%), full-stack development (20%), machine learning engineering (16%), and other fields (12%). The majority (88%) codes for company projects, while the rest works on academic or freelance development. We ask the experts to rate, on a Likert-7 scale, the importance of our four preferences, and their dependency on personal coding habits, project constraints, and requirements (The full set of questions in the survey can be found in the Appendix C). From survey results (Figure 2) all metrics are confirmed as influenced by company/project requirements, and experts show average agreement on their importance in different software engineering environments. For readability, commenting, and modularity tradeoffs, the majority tend to choose either a lower or a higher degree of usage, while in terms of complexity, respondents opt for a balance.

3.2 Generating the Dataset

Next, we realize our preferences axes as a dataset $\mathcal{D}$ of paired code snippets

$$\mathcal{D} = \{(p, (s_1, d_1), (s_2, d_2))\},$$

where p is a programming problem description, s_i

---

[2]upwork.com

is a code snippet that solves p, and d_i is a structured description of s_i with respect to a specific evaluation metric ("e.g. minimal VS extensive commenting"). Each pair (s_1, s_2) represents alternative solutions to the same problem p, annotated by their corresponding metric-based characterizations (d_1, d_2).

Table 1: Dataset composition by preference axis.

Axis	Portion	Snippets pairs
Commenting	26%	765
Complexity	35%	1,030
Modularity	24%	706
Readability	15%	442
Total	**100%**	**2,944**

For Commenting and Modularity, we first extract source code snippets from existing Python programming datasets (Cassano et al., 2024; Muennighoff et al., 2024; Tarun, 2021; Kaggle, 2023). We select snippets that score low on our metrics (e.g.. for *Modularity*, we select only those samples that do not contain any modules, thus with $MS(\mathcal{S}) = 0$). Then, we prompt CodeGemma-7B (Team et al., 2024) to generate the opposite of the given snippet (as in, high-scoring), and manually review the resulting code (see Figure 8 in Appendix D). Finally, we check the generated snippets for correctness and executability by testing on executing code snippets with the same input and comparing the produced output. We obtain 86.12% and 99.8% matching stdout and stderror outputs, respectively. For Complexity and Readability, Coding pairs are acquired from open-access coding competitions repositories (The Algorithms — GitHub Organization, 2026; GeeksforGeeks, 2025) and are fully human-written; thus, no LLM is used for code generation. The final dataset contains 2944 coding pairs (statistics in Table 1).

Validating dataset variety   To inspect subjective preferences in clearly distinguishable scenarios, it is important that our dataset contains sufficiently different coding snippets for each pair. We verify this via a Wilcoxon paired t-test based on the level of commenting (t=55.22; mean-diff=0.260), modularity (t=73.98; mean-diff=0.086), and readability (t=20.57; mean-diff=0.098) . We obtain P-values $< 2.2e - 16$ for each preference type, proving significant differences (Figure 6 in Appendix A). For complexity, the paired t-test was not performed, as these samples are measured in big-O notation, so the benchmarking values are not numerical.

Figure 2: Responses from the experts' survey for each preference: aggregated values, along with context-specific importance (project, requirements, or habits). Appendix C contains the full questionnaire and Likert distribution.

Figure 3: Examples of an instance from our dataset. Given a Python problem (e.g., generating the Fibonacci numbers), we provide (1) two solution snippets varying across a preference axis (e.g., more or less commented); (2) preference annotation from human experts and LLMs.

3.3 Human Preference Annotation

To compare humans and LLMs, we collect human preferences annotations for our dataset. We hire experts from Prolific[3], with background in software engineering and a degree in computer science. We verify their ability to differentiate preferences via a qualification task: given 8 coding pairs, experts are asked to mark those with a hiher/lowel degree of commenting/modularity or are more or less computationally complex. Only annotators with 100% passing rate are accepted.

Preference annotation In the main task (example of the annotation UI in Appendix E, Figure 11), annotators are shown (1) a textual description of a Python problem; (2) two solutions (code snippets) solving it; (3) a clarification of the differences be-

tween them at the preference axis level (e.g. "Snippet A/B uses minimal/extensive commenting"); (4) a brief explanation of the axis (e.g. "Commenting refers to the commented of docstring lines..."). Experts choose their preference among the two snippets, based on their working experience, via a Likert-6 scale (0 = Strongly prefer snippet A; 5 = Strongly prefer snippet B). The median option was deliberately omitted to obtain distinguishable preferences between A and B. Final numeric preference annotation is done by 73 annotators, where 27 experts annotated ≈176 coding pairs each, and 46 annotated ≈89 coding pairs each. Each coding pair is annotated 3 times by different experts, and code pairs were presented in a randomized order. Figure 3 shows an instance example (including LLMs preferences, which we cover in §5).

---

[3]prolific.com

Rationale annotation Incorporating additional argumentation for preference data can help us uncover more advanced patterns in human and LLMs behaviour, as well as being useful in datasets like ours for preference alignment (Just et al., 2025; Liu et al., 2025a). Therefore, we collect rationale annotation for coding pairs with midpoint preference choice[4] (in this case, 2 and 3, as for *Slightly prefer A/B*). Existing work either adopts free-text rationale (Gabriel, 2020) or preset templates where the annotators fill in specific blanks (Zhi-Xuan et al., 2024). We adopt both methodologies for completeness. To filter out unreliable annotators who may offload rationale writing to LLMs, we adopt a mix of metric checks, manual inspection, and comparison with popular vendor LLMs (see Appendix F). Overall, we obtain rationale annotation from 26 experts over 514 coding snippets.

4 Evaluating LLMs' consistency over subjective preferences

As a first experiment, we assess if LLMs can effectively understand subjective preferences when explicitly expressing them. Given a Python problem z from our dataset, we ask the LLM to choose between two preference options x or y (e.g. extensive or minimal commenting), to solve it. We do this with x, y represented as both text and code. Ideally, we expect the model to be consistent (e.g., "extensive commenting", and the snippet with more comments). This tells us to what extent LLMs recognize the code realization of a textual preference.

We note that our annotators are expected to have this ability, given their work experience. Regardless of this, they also demonstrate it in our qualification task with an acceptance rate of 100% accuracy to proceed with the main annotation task. We also note that human coders, during their job, do not explicitly state a preference: they apply it implicitly. An expert AI assistant, on the other hand, should motivate its choices, and a developer may even state their own preference before, to condition them (e.g. "keep in mind I prefer more densely commented code").

We evaluate 13 LLMs (Appendix E) across four categories. As **baseline** models, we include Llama-3-8B-Instruct (Llama3-8B) and Llama-3-70B-Instruct (Llama3-70B) (Grattafiori et al.,

2024), DeepSeek-R1-Distill-Qwen-14B (DS-R1-14B), and Qwen3-8B and Qwen3-32B (Team, 2025). As **coding** models, we use StarCoder2-15B (Lozhkov et al., 2024), DeepSeek-Coder-33B-Base (DS-Coder-33B) (Guo et al., 2024), and Qwen3-Coder-30B-Instruct (Qwen3-Coder-30B) (Team, 2025). As **judge** models, we include Prometheus-13B (Kim et al., 2024) and DeepSeek-GRM-16B (DS-GRM-16B) (Liu et al., 2025b). Finally, we evaluate three **vendor** models: gpt-5-mini (GPT-5) (OpenAI, 2025), Claude-sonnet-4.5 (Claude-4.5) (Anthropic, 2025), and gemini-3-flash-preview (Gemini-3) (Google, 2025). We test three setups:

Baseline (BL): LLM is asked to specify the preferences in Session A, where the model selects a textual option, and Session B, where the model selects a code snippet. Session B is new and holds no memory of Session A.

One-chat (OC): Both choices are made in the same session, ruling out forgetting the textual explanation that can be possible in the *Baseline* setting.

Few-Shot (FS): We introduce 2 input-output examples of paired textual and coding preferences to the prompt.

The specific prompts can be found in Appendix D. Additionally, we re-run each setup by swapping the order of the two snippets to investigate positional bias. We calculate *Consistency Score* (CS) as the correspondence between preference text and code choices:

$$\text{CS} = P(Q_t, Q_c) \sim D\big(\text{LLM}(Q_t) = \text{LLM}(Q_c)\big)$$

where $P(Q_t, Q_c)$ denotes the joint preference over a text query Q_t and a code query Q_c, $\text{LLM}(\cdot)$ is the response of the language model to a given query, and $D(\cdot)$ is an indicator of agreement between the two responses. When we swap the snippets, we calculate *Swap Adjustment Score* (SAS), measuring LLMs' consistency when the order of preferences is shifted. This metric denotes the percentage of cases where the model chooses the same option both in the ordered and the shifted dataset. Thus, such cases, when the choice for the first setup is *A*, and the choice for the shifted setup is *B*, which represent the same unit:

$$\text{SAS} = \text{Pr}\big(\text{LLM}(Q_{\text{ordered}}) \neq \text{LLM}(Q_{\text{shifted}})\big)$$

---

[4]Each pair is re-annotated for rationale by its original annotator.

Open LLMs	BL		OC		FS	
	CS↑	SAS↑	CS↑	SAS↑	CS↑	SAS↑
Llama3-8B	0.35	0.14	0.36	0.15	0.67	0.48
Llama3-70B	0.68	0.55	0.67	0.63	0.72	0.63
Qwen3-8B	0.90	0.00	1.00	0.00	0.96	0.00
Qwen3-32B	0.80	0.20	1.00	0.00	0.81	0.00
DS-R1-14B	0.92	0.00	1.00	0.00	0.99	0.00
DS-Coder-33B	0.53	0.02	0.73	0.04	0.73	0.17
StarCoder2-15B	0.26	0.07	0.52	0.24	0.51	0.03
Qwen3-Coder-30B	0.50	0.40	0.57	0.44	0.63	0.53
Prometheus-13B	0.11	0.00	0.52	0.08	0.99	0.00
DS-GRM-16B	0.49	0.13	0.80	0.17	0.45	0.04

Vendor LLMs	BL		OC		FS	
	CS↑	SAS↑	CS↑	SAS↑	CS↑	SAS↑
GPT-5	0.25	0.63	0.21	0.61	0.29	0.65
Claude-4.5	0.27	0.35	0.15	0.57	0.18	0.25
Gemini-3	0.35	0.55	0.33	0.60	0.30	0.67

Table 2: LLMs' CS (↑) and SAS (↑) across different prompting approaches. We mark **best** and **worst** per column.

where Q_{ordered} and Q_{shifted} denote the query with the original and swapped snippet ordering, respectively, and $\Pr(\cdot)$ is the probability over the evaluated cases.

From results (Table 2), models consistently pick contradicting textual and code preferences. This is evident from the generally low CS values. When a very high CS appears, this is due to positional bias. For example, Qwen3-8B, Qwen3-32B, and DS-R1-14B reach $CS > 80$. However, once we swap the order of the snippets, the models do not change their choice, and SAS drops dramatically. Interestingly, CS and SAS show opposite trends in GPT-5 and Gemini-3, showing more positional consistency in their choices. We also note that OC and FS prompting do not improve the situation: some models benefit from it in terms of CS, but with little-to-no change in SAS.

5 Exploring Preference Behavior among LLMs and Humans

Next, we compare the distribution of preference values between humans and LLMs. To manage the computational and inference cost of our experiments, we select 3 open-weight and 2 vendor LLMs based on combined CS and SAS (Table 2). We choose Llama3-70B (baseline model); Qwen3-Coder-30B (coding model); DS-GRM-16B (judge model); Claude-4.5 and GPT-5 (vendor models). We prompt these models by replicating our human annotation setup (Section 3.3), meaning that LLMs are now expressing a preference on a 6-scale, given the two snippets and a description of the axis value.

Disagreement We first compute the distribution of human Likert rankings from Section 3.3. For each coding pair i, we define a per-item disagreement score a_i: for human annotators, it is the average pairwise absolute difference across all $\binom{n_i}{2}$ annotator pairs (j, k), where h_{ij} and h_{ik} are their respective Likert ratings; for an LLM, it is the absolute deviation of its response ℓ_i from the human median m_i. The overall Disagreement D is then the mean of a_i over all N coding pairs:

$$a_i = \begin{cases} \dfrac{1}{\binom{n_i}{2}} \displaystyle\sum_{1 \le j < k \le n_i} |h_{ij} - h_{ik}| & \text{for human annotation} \\ |\ell_i - m_i| & \text{for LLM annotation} \end{cases}$$

$$D = \frac{1}{N} \sum_{i=1}^{N} a_i$$

Via this metric, we compute D among humans, and between humans and LLMs. We also compute Jensen-Shannon Divergence (Lin, 2002) between humans and LLMs. We choose this measure over the others (such as KL divergence (Kullback and Leibler, 1951)) as it is symmetric and bounded, offering better interpretation of its values. This is in line with other works in the field (Go et al., 2023; Yang et al.).

Results from the distribution (Figure 4) and metrics (Table 3) reveal how critical it is to assess alignment via multiple metrics. GPT-5 achieves the lowest JSD scores, with a distribution of ratings closely mirroring the experts (except for commenting). However, it shows one of the highest D: despite producing realistic aggregate statistics, GPT-5 still frequently deviates from human judgement on individual examples. This indicates that a model can learn the "shape" of human opinions without learning what drives human decisions on specific cases. Llama3-70B shows the opposite failure mode: systematic distribution biases (JSD), but low D. This shows how a consistent directional bias can accidentally align with human medians. Generally, all open LLMs show extremely skewed distribution; DS-GRM-16B consistently shows the worst results for each metric, which could be attributed to it being the smallest model.

Qualitative analysis Subjectivity can be trivial for judgments on commenting and Modularity. Computational complexity, however, is rather objective. To understand the sources of disagreement

Figure 4: Distribution of preference choices among LLMs and humans.

Human VS	Commenting		Complexity		Modularity		Readability		Overall	
	D	JSD	D	JSD	D	JSD	D	JSD	D	JSD
Human	1.93	–	1.67	–	1.81	–	1.49	–	1.74	–
Llama3-70B	2.29	0.63	1.30	0.55	1.36	0.56	1.18	0.60	1.54	0.57
Qwen3-Coder-30B	1.85	0.51	1.09	0.38	1.05	0.54	1.02	0.36	1.25	0.39
DS-GRM-16B	1.64	0.70	1.92	0.71	1.95	0.73	2.12	0.74	1.89	0.72
GPT-5	2.31	0.26	1.71	0.12	1.79	0.12	1.56	0.04	1.85	0.12
Claude-4.5	1.71	0.58	1.45	0.21	1.46	0.37	1.29	0.26	1.49	0.28

Table 3: Per-metric disagreement ($D \downarrow$) and Jensen-Shannon divergence ($JSD \downarrow$) between annotator pairs. We mark **best** and **worst** values for both D and JSD across metrics.

along this axis, we perform a qualitative analysis of the experts' judgments compared to GPT-5, as it shows the strongest JSD (Table 3). We inspect 20 randomly selected code pairs with at least one human annotator disagreeing with GPT-5. First, we observe *reliance on external assumptions*: GPT-5 (alongside some experts) occasionally presumes additional contexts beyond the problem statement; for example, it favours code with better average case complexity, while experts may consider worst-case complexity (Appendix H, ID 1). Such hidden contexts of preferences can misdirect preference-learning (Siththaranjan and Laidlaw, 2024), and are of utmost importance in case of expert preferences. Similarly, GPT-5 sometimes relies on auxiliary metrics beyond complexity, like commenting, readability, pure-pythonic vs mixed-implementations, and usage of certain libraries such as Numpy (Appendix H, ID 2-4). This sometimes leads to choosing an inefficient implementation due to surface-level simplicity. Finally, we observe consistent *brittle reasoning* in GPT-5: its rationale (Appendix H, ID 5) relies on superficial characteristics of the code, or even blatantly ignores known algorithmic complexity bounds, echoing prior findings (Şahinuç et al., 2026).

6 Conclusions

In this work, we inspected the behaviour of LLMs over subjective coding preferences, which are critical in expert coding, and often overlooked by traditional benchmarking. We introduced a novel dataset of coding snippets, that are expert-annotated with subjective preferences. We then used our dataset to identify patterns of behavior and consistency in LLMs. We find that LLMs cannot consistently identify the realization of subjective preferences, and struggle in identifying the same preference value when it's presented as text or code. We also find severe positional bias, showing that even seemingly robust models just learned fixed selection patterns. Vendor models are less affected by positional bias, but still fall far from desirable consistency. Compared to experts, most tested models show extremely polarized distribution, opting almost exclusively for the extreme of the proposed scale. GPT-5 closely resembles the human distribution, but still suffers from consistent per-item divergence. Our qualitative study further reveals problematic patterns in how the model reasons.

We release our dataset to foster research in preference learning and expert coder models. Our dataset can be used to integrate coding preferences into human reinforcement strategies for further development of coding assistants that follow users' personal choices. Additionally, acquired annotations and rationales can serve as a source for extended linguistic and statistical analysis for deeper insights into how LLMs understand code.

7 Limitations

Preference Matching and Preference Aggregation We focus on four coding preference axes. We do understand, however, that subjective preferences may widen into many other axes we did not consider. Some examples of those from the related literature and results of our survey include code *maintainability* and *security*. We also acnkowledge that preference axes could aggregate in complex ways. Our current framework represents the single-principal alignment for an AI system to match one unique preference. We reserve the analysis of complex aggregation of multiple axes within single coding snippets for future work.

Programming Languages We limit our study to Python, excluding other programming language. This choice was motivated by the extensive set of Python resources available online; however, other programming languages should be considered in future developments of our research line.

Model choices The choice of our 13 LLMs is certainly limited, especially when it comes to the rapid development of new models, scales, and training approaches. In this work, we limited ourselves to those baseline, coding, judge, and vendor models that showed the strongest performance in popular coding benchmarks. This is a conscious choice that lets us analyze the models that end users may be more likely to use for coding, when it comes to both open and vendor LLMs. This was also necessary for us to keep a manageable computational requirement and experimental runtime: testing each model on $\approx$ 3000 paired snippets, in three prompting setups, plus the swapped case, imposed us to take this choice. The same logic made us narrow our selection in our second experiment, where we picked the 5 most consistent models. Additionally, this was motivated by the necessity of keeping the inference cost of vendor model within our budget (accounting also for the budge spent in human annotation).

Assumption of expert competence We consider our coding experts as the gold standard when it comes to real-world subjective preferences. However, we do not assume that our experts are always correct. We acknowledge that our qualification task, annotation setup, and sanity checks may be limited and not fully sufficient against all the challenges that come into the implicitly complex domain of subjective data annotation. We assume the trustworthiness of our expert based on our protocol, but also acknowledge that the convoluted nature of expert preference may need deeper analysis.

References

Wasi Uddin Ahmad, Aleksander Ficek, Mehrzad Samadi, Jocelyn Huang, Vahid Noroozi, Somshubra Majumdar, and Boris Ginsburg. 2025. Opencodeinstruct: A large-scale instruction tuning dataset for code llms. *Preprint*, arXiv:2504.04030.

Anthropic. 2025. Claude-sonnet-4.5. Large language model.

Samina Azeem, Muhammad Shumail Naveed, Muhammad Sajid, and Imran Ali. 2025. Ai vs. human programmers: Complexity and performance in code generation. *VAWKUM Transactions on Computer Sciences*, 13(1):201–216.

Ronen Brafman and Carmel Domshlak. 2009. Preference handling - an introductory tutorial. *AI Magazine*, 30(1):58.

Raymond Buse and Westley Weimer. 2010a. Learning a metric for code readability. *Software Engineering, IEEE Transactions on*, 36:546–558.

Raymond PL Buse and Westley R Weimer. 2009. Learning a metric for code readability. *IEEE Transactions on software engineering*, 36(4):546–558.

Raymond P.L. Buse and Westley R. Weimer. 2010b. Learning a metric for code readability. *IEEE Transactions on Software Engineering*, 36(4):546–558.

Jürgen Börstler, Kwabena Bennin, Sara Hooshangi, Johan Jeuring, Hieke Keuning, Carsten Kleiner, Bonnie Mackellar, Rodrigo Duran, Harald Störrle, Daniel Toll, and Jelle Assema. 2023. Developers talking about code quality. *Empirical Software Engineering*, 28.

Federico Cassano, Luisa Li, Akul Sethi, Noah Shinn, Abby Brennan-Jones, Jacob Ginesin, Edward Berman, George Chakhnashvili, Anton Lozhkov, Carolyn Jane Anderson, and Arjun Guha. 2024. Can it edit? evaluating the ability of large language models to follow code editing instructions. *Preprint*, arXiv:2312.12450.

S.R. Chidamber and C.F. Kemerer. 1994. A metrics suite for object oriented design. *IEEE Transactions on Software Engineering*, 20(6):476–493.

Subhabrata Dutta, Timo Kaufmann, Goran Glavaš, Ivan Habernal, Kristian Kersting, Frauke Kreuter, Mira Mezini, Iryna Gurevych, Eyke Hüllermeier, and Hinrich Schuetze. 2025. Problem solving through human-ai preference-based cooperation. *Preprint*, arXiv:2408.07461.

Samuel Ferino, Rashina Hoda, John Grundy, and Christoph Treude. 2025. Novice developers' perspectives on adopting llms for software development: A systematic literature review. *Preprint*, arXiv:2503.07556.

Iason Gabriel. 2020. Artificial intelligence, values, and alignment. *Minds and Machines*, 30(3):411–437.

GeeksforGeeks. 2025. Complete a2z reference for dsa concepts. Last updated: 26 Jul 2025.

Dongyoung Go, Tomasz Korbak, Germán Kruszewski, Jos Rozen, Nahyeon Ryu, and Marc Dymetman. 2023. Aligning language models with preferences through f-divergence minimization. In *Proceedings of the 40th International Conference on Machine Learning*, pages 11546–11583.

Google. 2025. Gemini-3-flash. Large language model.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Daya Guo, Qihao Zhu, Dejian Yang, Zhenda Xie, Kai Dong, Wentao Zhang, Guanting Chen, Xiao Bi, Y. Wu, Y. K. Li, Fuli Luo, Yingfei Xiong, and Wenfeng Liang. 2024. Deepseek-coder: When the large language model meets programming – the rise of code intelligence. *Preprint*, arXiv:2401.14196.

John Hughes and Chalmers Hogskola. 1999. Why functional programming matters.

Naman Jain, Skanda Vaidyanath, Arun Iyer, Nagarajan Natarajan, Suresh Parthasarathy, Sriram Rajamani, and Rahul Sharma. 2021. Jigsaw: Large language models meet program synthesis. *Preprint*, arXiv:2112.02969.

Jingru Jia, Zehua Yuan, Junhao Pan, Paul E. McNamara, and Deming Chen. 2024. Decision-making behavior evaluation framework for llms under uncertain context. *Preprint*, arXiv:2406.05972.

Haolin Jin and Huaming Chen. 2025. Uncovering systematic failures of llms in verifying code against natural language specifications. *Preprint*, arXiv:2508.12358.

Hoang Anh Just, Ming Jin, Anit Sahu, Huy Phan, and Ruoxi Jia. 2025. Data-centric human preference with rationales for direct preference alignment. *Preprint*, arXiv:2407.14477.

Kaggle. 2023. Leetcode solutions and content kpis. https://www.kaggle.com/datasets/jacobhds/leetcode-solutions-and-content-kpis.

Sungmin Kang, Juyeon Yoon, and Shin Yoo. 2023. Large language models are few-shot testers: Exploring llm-based general bug reproduction. *Preprint*, arXiv:2209.11515.

Seungone Kim, Juyoung Suk, Shayne Longpre, Bill Yuchen Lin, Jamin Shin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. 2024. Prometheus 2: An open source language model specialized in evaluating other language models. *Preprint*, arXiv:2405.01535.

Solomon Kullback and Richard A Leibler. 1951. On information and sufficiency. *The annals of mathematical statistics*, 22(1):79–86.

Caroline Lemieux, Jeevana Priya Inala, Shuvendu K. Lahiri, and Siddhartha Sen. 2023. Codamosa: Escaping coverage plateaus in test generation with pre-trained large language models. In *Proceedings of the 45th International Conference on Software Engineering*, ICSE '23, page 919–931. IEEE Press.

Junlong Li, Fan Zhou, Shichao Sun, Yikai Zhang, Hai Zhao, and Pengfei Liu. 2024. Dissecting human and llm preferences. *Preprint*, arXiv:2402.11296.

Miqing Li and Tao Chen. 2024a. Methodology and guidelines for evaluating multi-objective search-based software engineering. In *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering*, pages 707–709.

Miqing Li and Tao Chen. 2024b. Methodology and guidelines for evaluating multi-objective search-based software engineering. In *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering*, FSE 2024, page 707–709, New York, NY, USA. Association for Computing Machinery.

Jianhua Lin. 2002. Divergence measures based on the shannon entropy. *IEEE Transactions on Information theory*, 37(1):145–151.

Hanbing Liu, Haoyang Li, Xiaokang Zhang, Ruotong Chen, Haiyong Xu, Tian Tian, Qi Qi, and Jing Zhang. 2025a. Uncovering the impact of chain-of-thought reasoning for direct preference optimization: Lessons from text-to-sql. *Preprint*, arXiv:2502.11656.

Jiawei Liu, Thanh Nguyen, Mingyue Shang, Hantian Ding, Xiaopeng Li, Yu Yu, Varun Kumar, and Zijian Wang. 2024. Learning code preference via synthetic evolution. *Preprint*, arXiv:2410.03837.

Zijun Liu, Peiyi Wang, Runxin Xu, Shirong Ma, Chong Ruan, Peng Li, Yang Liu, and Yu Wu. 2025b. Inference-time scaling for generalist reward modeling. *Preprint*, arXiv:2504.02495.

Anton Lozhkov, Raymond Li, Loubna Ben Allal, Federico Cassano, Joel Lamy-Poirier, Nouamane Tazi, Ao Tang, Dmytro Pykhtar, Jiawei Liu, Yuxiang Wei, Tianyang Liu, Max Tian, Denis Kocetkov, Arthur Zucker, Younes Belkada, Zijian Wang, Qian Liu, Dmitry Abulkhanov, Indraneil Paul, and 47 others. 2024. Starcoder 2 and the stack v2: The next generation. *Preprint*, arXiv:2402.19173.

Paakhi Maheshwari. 2024. Code snippets: Insights and readability. https://www.kaggle.com/datasets/paakhim10/code-snippets-insights-and-readability. Accessed: 2026-03-16.

Niklas Muennighoff, Qian Liu, Armel Zebaze, Qinkai Zheng, Binyuan Hui, Terry Yue Zhuo, Swayam Singh, Xiangru Tang, Leandro von Werra, and Shayne Longpre. 2024. Octopack: Instruction tuning code large language models. *Preprint*, arXiv:2308.07124.

Delano Oliveira, Reydne Santos, Benedito de Oliveira, Martin Monperrus, Fernando Castor, and Fernanda Madeiral. 2025. Understanding code understandability

improvements in code reviews. *IEEE Transactions on Software Engineering*, 51(1):14–37.

OpenAI. 2025. Gpt-5 mini. Large language model.

Pooja Rani, Arianna Blasi, Nataliia Stulova, Sebastiano Panichella, Alessandra Gorla, and Oscar Nierstrasz. 2023. A decade of code comment quality assessment: A systematic literature review. *Journal of Systems and Software*, 195:111515.

L. Rosenberg, T. Hammer, and J. Shaw. 1998. Software metrics and reliability. In *Proceedings of the IEEE International Symposium on Software Reliability Engineering*. IEEE.

Simone Scalabrino, Gabriele Bavota, Christopher Vendome, Mario Linares-Vásquez, Denys Poshyvanyk, and Rocco Oliveto. 2017. Automatically assessing code understandability: How far are we? pages 417–427.

Jagriti Sikka, Kushal Satya, Yaman Kumar, Shagun Uppal, Rajiv Ratn Shah, and Roger Zimmermann. 2019. Learning based methods for code runtime complexity prediction. *Preprint*, arXiv:1911.01155.

Anand Siththaranjan and Cassidy Laidlaw. 2024. Distributional preference learning: Understanding and accounting for hidden context in rlhf. In *International Conference on Learning Representations (ICLR)*.

Yisheng Song, Ting Wang, Subrota K Mondal, and Jyoti Prakash Sahoo. 2022. A comprehensive survey of few-shot learning: Evolution, applications, challenges, and opportunities. *Preprint*, arXiv:2205.06743.

Sergio Souza, Nicolas Anquetil, and Káthia Oliveira. 2005. A study of the documentation essential to software maintenance.

Gaurav Suri, Lily R. Slater, Ali Ziaee, and Morgan Nguyen. 2023. Do large language models show decision heuristics similar to humans? a case study using gpt-3.5. *Preprint*, arXiv:2305.04400.

I. Tarun. 2021. Python code instructions 18k dataset. https://huggingface.co/datasets/iamtarun/python_code_instructions_18k_alpaca.

Yahya Tashtoush, Noor Abu-El-Rub, Omar Darwish, Shorouq Al-Eidi, Dirar Darweesh, and Ola Karajeh. 2023a. A notional understanding of the relationship between code readability and software complexity. *Information*, 14(2):81.

Yahya Tashtoush, Noor Abu-El-Rub, Omar Darwish, Shorouq Al-Eidi, Dirar Darweesh, and Ola Karajeh. 2023b. A notional understanding of the relationship between code readability and software complexity. *Information*, 14(2).

CodeGemma Team, Heri Zhao, Jeffrey Hui, Joshua Howland, Nam Nguyen, Siqi Zuo, Andrea Hu, Christopher A. Choquette-Choo, Jingyue Shen, Joe Kelley, Kshitij Bansal, Luke Vilnis, Mateo Wirth, Paul Michel, Peter Choy, Pratik Joshi, Ravin Kumar, Sarmad Hashmi, Shubham Agrawal, and 8 others. 2024. Codegemma: Open code models based on gemma. *Preprint*, arXiv:2406.11409.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

The Algorithms — GitHub Organization. 2026. Open source resource for learning data structures algorithms and their implementation in any programming language.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2023. Chain-of-thought prompting elicits reasoning in large language models. *Preprint*, arXiv:2201.11903.

Martin Weyssow, Aton Kamanda, Xin Zhou, and Houari Sahraoui. 2024a. Codeultrafeedback: An llm-as-a-judge dataset for aligning large language models to coding preferences. *Preprint*, arXiv:2403.09032.

Martin Weyssow, Xin Zhou, Kisub Kim, David Lo, and Houari Sahraoui. 2024b. Exploring parameter-efficient fine-tuning techniques for code generation with large language models. *Preprint*, arXiv:2308.10462.

Marvin Wyrich, Justus Bogner, and Stefan Wagner. 2023. 40 years of designing code comprehension experiments: A systematic mapping study. *ACM Comput. Surv.*, 56(4).

Ruoxi Xu, Hongyu Lin, Xianpei Han, Jia Zheng, Weixiang Zhou, Le Sun, and Yingfei Sun. 2025. Large language models often say one thing and do another. *Preprint*, arXiv:2503.07003.

Chaoqi Wang Yibo Jiang Chenghao Yang, Han Liu, and Yuxin Chen. Beyond reverse kl: Generalizing direct preference optimization with diverse diver-gence constraints.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.

Jiasheng Zheng, Boxi Cao, Zhengzhao Ma, Ruotong Pan, Hongyu Lin, Yaojie Lu, Xianpei Han, and Le Sun. 2024. Beyond correctness: Benchmarking multi-dimensional code generation for large language models. *Preprint*, arXiv:2407.11470.

Tan Zhi-Xuan, Micah Carroll, Matija Franklin, and Hal Ashton. 2024. Beyond preferences in ai alignment. *Philosophical Studies*, 182(7):1813–1863.

Furkan Şahinuç, Subhabrata Dutta, and Iryna Gurevych. 2026. Reward modeling for scientific writing evaluation. *Preprint*, arXiv:2601.11374.

A Additional information on coding metrics

Although there is no single objective criteria for readability, discussions on this topic agree on the following characteristics that are usually associated with how easy code is to understand: (1) Following coding standards, linters, pep8, etc.; (2) Cyclomatic complexity, which is a way of evaluating the code based on a built graph and number of nodes, edges

Figure 5: Readability Model Pipeline.

Figure 6: Distribution of code metrics differentiating Code_A and Code_B.

and connected components; (3) Code maintainability, including above-mentioned cyclomatic complexity as well as relations between operators and operands; (4) Subjective human perception of how code looks which is based on local factors. These are the surface features that aim to capture human notions of readability and include such traits as number of comments, average line length, and loop count. We propose creating a combined readability model (Figure 5) that, on one hand, contains overt code features, and, on the other hand, represents the established concepts of readability. For this purpose, a multiple linear regression is used with code local factors as independent variables and scores acquired by three methods that to some extent reflect readability as dependent variables on this data (Maheshwari, 2024). We then obtain weights for each of the local features, which allow us to reproduce readability metric on any code snippet of any programming language.

B Ethics Statement

In this section, we briefly discuss the ethical aspects of our experiments.

Ethical Review Before starting our experiments, we consulted our Institution for ethical pre-assessment. Since we do not collect any demographics and personal information about the participants, and crowdworkers do not disclose any data that could identify them, our experiment was confirmed to be ethically compliant without further procedures.

Data Consent For both recruitment processes done in this study, the survey and the main annotation task, we provided instructions explaining how the collected data would be used, the goal of the study, and ways to contact the study executors directly. Participants who wanted to take part in our experiments were required to give us explicit agreement before proceeding.

Workload and pay We estimated a maximum time for completing the expert survey of 30 min, and set an hourly rate per participant of 22€.

For the numeric preference annotation, we first conducted a pilot study, where we determined the average completion time as one hour for ~90 coding pairs. For the qualification task, which consisted of annotating 8 coding pairs, the required time per participant was 15 min and the hourly rate was 28€. For the full-scale annotation task, the hourly rate per annotator was set to 14€.

For the rationale preference annotation, participants are paid approximately 15€/hour, and the estimated (from the pilot study) workload is 6 coding pairs per hour.

Additional information on the recruited experts Other general information about participants of the *survey* includes:

1. 44% have 4-6 years of working experience; 28% have 7-9 years; 20% have 1-3 years; and 8% have 10+ years.

2. 48% spend approximately 3-5 hours a day on working with code; 44% spend 5-8 hours a day; 8% spend 1-3 hours.

C Survey Coding Styles of Software Engineers

> **Part 1: General information about experience and current work**

> **Q1.** How many years of working experience do you have as a developer?

Response options:

(a) 1-3 years
(b) 4-6 years
(c) 7-9 years
(d) 10+ years

> **Q2.** What is your main specialisation?

Response options:

☐ Back-end
☐ Front-end
☐ Full Stack
☐ QA/testing
☐ ML engineering
☐ Other: _______________

> **Q3.** What are the main applications of your code?

Response options:

(a) Company projects
(b) Academic projects

> **Q4.** How many hours a day do you spend on working with code on average?

Response options:

(a) 1-3 hours
(b) 3-5 hours
(c) 5-8 hours

> **Part 2: Coding Comments**

Instructions:

You will be asked to rate several coding factors based on how relevant they are in your daily work and your personal experience. For your convenience and clearness, each coding factor is provided with a short definition.

"Coding comments" refer to the commented or docstring lines in code that usually explain what the code does

Example case: some code might contain a high number of comments explaining each step, while another way to implement the same code is with a moderate use of comments in the exceptional cases.

> **Q1.** To what extent do you agree with the following statement regarding the use of coding comments?
> 1. Using different degree of comments in code (i.e. low or high) depends on the habits of a particular developer
> 2. In my daily coding activity I personally choose different degree of comments (i.e. low or high) depending on the specific project/task
> 3. Using different degree of comments in code depends on the requirements and/or computational limitations of the specific project
> 4. Using different degree of comments in code (i.e. low or high) doesn't depend on the habits of a particular developer

Response options: 1 = Strongly disagree, 2 = Disagree, 3 = Somewhat disagree, 4 = Neutral, 5 = Somewhat agree, 6 = Agree, 7 = Strongly agree.

> **Q2.** Please mark here how you usually balance degree of comments in your code

Response options:

(a) I always use minimal commenting
(b) I mostly use minimal commenting
(c) I equally use minimal and extensive commenting
(d) I mostly use extensive commenting
(e) I always use extensive commenting

> **Q3.** Feel free to share any other thoughts about this coding characteristic (coding comments)

Response options: Open-ended text.

> **Part 3: Coding Modularity**

Instructions:

You will be asked to rate several coding factors based on how relevant they are in your daily work and your personal experience. For your convenience and clearness, each coding factor is provided with a short definition.

"Modularity" refers to the higher or lower usage of smaller self-contained modules (functions and classes)

Example case: some code might contain higher number of smaller self-contained modules, while another way to implement the same scripts is to write monolithic code

> **Q1.** To what extent do you agree with the following statement regarding the use of coding modularity?
> 1. Modularity in code depends on the requirements and/or computational limitations of the specific project
> 2. Modularity in code doesn't depend on the habits of a particular developer
> 3. In my daily coding activity I personally choose different degree of modularity depending on the specific project/task
> 4. Modularity in code depends on the habits of a particular developer

Response options: 1 = Strongly disagree, 2 = Disagree, 3 = Somewhat disagree, 4 = Neutral, 5 = Somewhat agree, 6 = Agree, 7 = Strongly agree.

> **Q2.** Please mark here how you usually balance modularity in your code

Response options:

(a) I always write monolithic code
(b) I mostly write monolithic code
(c) I equally write monolithic code and code that contains higher number of smaller modules
(d) I mostly write code that contains higher number of smaller modules
(e) I always write code that contains higher number of smaller modules

> **Q3.** Feel free to share any other thoughts about this coding characteristic (modularity)

Response options: Open-ended text.

> **Part 4: Code Complexity**

Instructions:

You will be asked to rate several coding factors based on how relevant they are in your daily work and your personal experience. For your convenience and clarity, each coding factor is provided with a short definition.

"Complexity" refers to the balance between computational resources and the amount of time taken by the code to run.

Example case: some code might be very quick to execute but requires a lot of memory, while another way to implement the same code is to save memory and sacrifice the running time

> **Q1.** To what extent do you agree with the following statement regarding the use of coding complexity?
> 1. Complexity in code depends on the habits of a particular developer
> 2. Complexity in code depends on the requirements and/or computational limitations of the specific project
> 3. In my daily coding activity I personally make decisions regarding code complexity depending on the specific project/task
> 4. In my daily coding activity my decisions regarding code complexity don't depend on the specific project/task

Response options: 1 = Strongly disagree, 2 = Disagree, 3 = Somewhat disagree, 4 = Neutral, 5 = Somewhat agree, 6 = Agree, 7 = Strongly agree.

> **Q2.** Please mark here how you usually balance complexity in your code

Response options:

(a) I always minimize computational resources and sacrifice speed of code execution
(b) I mostly minimize computational resources and sacrifice speed of code execution
(c) I equally balance computational resources and speed of code execution
(d) I mostly minimize speed of code execution and sacrifice computational resources
(e) I always minimize speed of code execution and sacrifice computational resources

Q3. Feel free to share any other thoughts about this coding characteristic (complexity)

Response options: Open-ended text.

Part 5: Code Readability

Instructions:

You will be asked to rate several coding factors based on how relevant they are in your daily work and your personal experience. For your convenience and clearness, each coding factor is provided with a short definition.

"Readability" refers to how easy code is to understand, "readability-complexity trade-off" implies the balance between how readable a code is and the computational costs to run it

Example case: some very optimised code might be very hard to read without deep understanding of the underlying framework, while another way to implement the same code is to sacrifice computational costs for better code readability

Q1. To what extent do you agree with the following statement regarding the use of coding readability-complexity trade-off?
1. Choices regarding coding readability-complexity trade-off depend on the requirements and/or computational limitations of the specific project
2. In my daily coding activity I personally make decisions regarding readability-complexity trade-off depending on the specific project/task
3. Choices regarding coding readability-complexity trade-off don't depend on the requirements and/or computational limitations of the specific project
4. Choices regarding coding readability-complexity trade-off depends on the habits of a particular developer

Response options: 1 = Strongly disagree, 2 = Disagree, 3 = Somewhat disagree, 4 = Neutral, 5 = Somewhat agree, 6 = Agree, 7 = Strongly agree.

Q2. Please mark here how you usually balance readability-complexity trade-off in your code

Response options:

(a) I always sacrifice computational resources for a more readable code
(b) I mostly sacrifice computational resources for a more readable code
(c) I equally balance computational resources and how readable code is
(d) I mostly sacrifice how readable code is and minimize computational resources
(e) I always sacrifice how readable code is and minimize computational resources

Q3. Feel free to share any other thoughts about this coding characteristic (readability-efficiency trade-off)

Response options: Open-ended text.

Part 6: Conclusion

Q1. What are the other coding factors that you're considering important at your daily work?

Response options: Open-ended text.

Q2. What are the other trade-offs in your daily coding decisions that you face? (i.e. produce memory-efficient code but sacrifice time of execution)

Response options: Open-ended text.

Q3. Please share any other thoughts or feedback about different coding styles and choices that developers come across to

Response options: Open-ended text.

D Prompts

We report the prompts we used in our experiments in Figures 7 to 10.

```
The following two options represent solutions of the same Python
problem z.Which of these two options would you prefer?

Option A: x

Option B: y

Please respond with only A or B.
```

Figure 7: Prompt template to investigate LLMs' coding preferences. x and y are realized either as textual descriptions or code snippets solving a Python problem z.

```
Here is a code snippet $CODE that solves the following Python
problem: $PROBLEM. This code scores very low on $PREFERENCE.

Write the opposite of this code solution for the stated
problem so that your version will score high on $PREFERENCE

Here is the explanation of $PREFERENCE: $EXPLANATION
```

Figure 8: CodeGemma-7B Code Generation Prompt.

```
The following two options represent solutions of the same Python
problem z.Which of these two options would you prefer?

Option A: x

Option B: y

Please respond with only A or B.

Here are some examples:

1) Option A $CODE: x_code; Option B $CODE: y_code; Response:
x_code. Option A $TEXT: x_text; Option B $TEXT: y_text; Response:
x_text.

2) Option A $CODE: x_code; Option B $CODE: y_code; Response:
y_code. Option A $TEXT: x_text; Option B $TEXT: y_text; Response:
y_text.
```

Figure 9: Few-Shot Example Prompt.

E   Annotation Interface

This section demonstrates an example of UI interface for the main annotation task as it was displayed to participants (Figure 11).

```
$PROBLEM_TITLE

$PROBLEM_EXPLANATION

Which  of  these  two  codes  would  you  most  likely  choose  in
a daily work as software engineer?

Preference  (0  =  strongly  prefer  A,  5  =  strongly  prefer
B)

$PREFERENCE_EXPLANATION

Option A: $TEXT_A; $CODE_A

Option B: $TEXT_B; $CODE_B
```

Figure 10: Prompt for Human-like Preference Annotation.

F   Sanity checks

Rationale annotation sanity check   Before acquiring rationale from experts, we conduct a short probing rationale annotation study to understand the potential risks and limits for this kind of experimental setup. We contacted 4 experts who had already done the numeric annotation task, and asked them to ground their previous choices in the written form (2 coding pairs per each annotator). We compare the obtained answers with the responses from ChatGPT and Gemini by BertScore (Zhang et al., 2019), as well as review them manually, to eliminate the use of LLMs for this round of annotation. This verification showed that both open-ended questions and a template can serve as a reliable source for collecting human rationales. In addition, we apply a combination of metrics on the sequences of numeric annotations for each participant to exclude lazy workers or participants whose previous annotations have been done mechanically. Those metrics include: entropy, switch rate (how often an annotator changes their label), switch symmetry (whether the annotator switches symmetrically and does random left-right clicking), percentage of using two midpoint labels together and separately, and frequency of the most repeated annotation sequence. We use the following thresholds for each metric: entropy < 1.43; switch rate $< 80\%$; switch symmetry < 0.375; usage of each midpoint label separately $< 23\%$; usage of mid-

Fibonacci

This script is intended to design a recursive function to generate Fibonacci numbers using Python. Which of these two codes would you most likely choose in your daily work?

"Commenting" refers to the commented or docstring lines in code that usually explain what the code does

Option A

Use extensive commenting

Option B

Use minimal commenting

Figure 11: A full example of the expert preference annotation interface.

point labels together $< 41\%$.

G Experimental Setup

The experimental setup for pairwise and 6-scale preference setting uses a fixed random seed across Python, NumPy, and PyTorch, and enables deterministic CUDA behavior to ensure reproducibility. For some models of larger size (e.g., Llama3-70B, Qwen3-32B, and DS-Coder-33B), inference is run with 8-bit quantization. We use greedy decoding (`do_sample=False`) for deterministic token selection. The remaining settings, such as left padding and a maximum of new generated tokens, are standard implementation choices motivated by enforcing either binary-choice or N-token generation output. In some cases, `max_new_tokens` hyperparameter was heuristically increased to avoid truncated outputs and ensure the model produced a complete decision.

H Examples for Qualitative analysis

ID 1. Text_A: More computationally complex code

Text_B: Less computationally complex code

Annotator_Score_1: 1

Annotator_Score_2: 3

Annotator_Score_3: 1

GPT5_Score: 0

Ann_Comments_1:

Ann_Comments_2: I would choose Option B due to its greater efficiency and lower time complexity. While this function wouldn't most likely be used many times, by adding a large input on Option A the code would run recursively too many times, wasting time and resources.

Ann_Comments_3:

GPT5_Comments: I picked 0 (strongly prefer A) because Code A is minimal, self-contained, and directly returns the gcd with very little implementation overhead, making it easy to read, verify, and use for typical small-to-moderate integers. Although the subtraction form can be asymptotically worse than the division-based/extended variant, Code B does extra work to produce

Bezout coefficients and has more branching/sign handling (higher constant overhead), so unless you specifically need the coefficients or must handle very large numbers, the simpler implementation is preferable in the time/resources tradeoff for common use.

Problem: This Python code solves the algorithmic problem of GCD that involves computing the greatest common divisor of two integers using Euclid's algorithm and returning the result.

ID 2. Text_A: More computationally complex code

Text_B: Less computationally complex code

Annotator_Score_1: 2

Annotator_Score_2: 3

Annotator_Score_3: 5

GPT5_Score: 5

Ann_Comments_1: Even if more complex, the comments are much more precise. If the algorithm works, and especially is a known algorithm, then its okay to use it anywhere, as long as it is commented properly like in option B.

Ann_Comments_2: Option B shows the characteristics of dynamic programming: it uses overlapping subproblems and optimal substructures. It stores the dynamic programming parts in the dp array. It ends with a reconstructing step in the while loop where the string is again put together.

On the other hand, Option A does not reconstruct the string, nor is it dynamic programming. It is, as the first comment says, just a naive recursive implementation without any memoization. This makes it heavily computationally intense (exponentially).

However, option B is not perfect since it lacks online commenting that helps to explain the steps (overlapping subproblems, optimal substructures, reconstruction).

Ann_Comments_3:

GPT5_Comments: I picked 5 (strongly prefer B) because the dynamic-programming implementation runs in O(mn) time and is practical for real inputs, whereas the naive recursive version is exponential and infeasible except for tiny strings. Code B also reconstructs the subsequence and handles edge cases cleanly (at the cost of O(mn) memory), making it far superior in the time/resources tradeoff.

Problem: This Python code solves the algorithmic problem of LCS that involves computing the longest common subsequence of two strings with dynamic programming and reconstructing the subsequence.

ID 3. Text_A: More computationally complex code

Text_B: Less computationally complex code

Annotator_Score_1: 0

Annotator_Score_2: 2

Annotator_Score_3: 2

GPT5_Score: 0

Ann_Comments_1:

Ann_Comments_2: I would choose Option B because it implements Euclid's algorithm in a much simpler and more readable recursive form while maintaining optimal time complexity. Option A is more verbose and harder to maintain, even though it computes additional coefficients (extended GCD). In daily work, clarity and simplicity are usually preferable when only the GCD value is required.

Ann_Comments_3:

GPT5_Comments: I picked 0 (strongly prefer A) because Code A implements the plain Euclidean gcd with a single modulo recursion and minimal overhead, giving the fastest, simplest solution for just the GCD. Code B is an extended-GCD routine that maintains many extra variables and performs additional arithmetic to compute Bezout coefficients, so it does more work (and is more error-prone and harder to read) when only the gcd is required.

Problem: This Python code solves the algorithmic problem of GCD that involves computing the greatest common divisor of two

integers using Euclid's algorithm and returning the result.

ID 4. Text_A: More computationally complex code

Text_B: Less computationally complex code

Annotator_Score_1: 3

Annotator_Score_2: 2

Annotator_Score_3: 1

GPT5_Score: 0

Ann_Comments_1: I would slightly prefer Option B. The dynamic programming approach efficiently computes the maximum value without generating all possible combinations, which makes it much faster for larger numbers of items. While Option A is conceptually simple, it quickly becomes impractical as the number of items grows, so Option B is more suitable for daily work where performance matters.

Ann_Comments_2:

Ann_Comments_3:

GPT5_Comments: I chose 0 (strongly prefer A) because Code A directly returns both the optimal value and the explicit item selection (best_combination), making it a complete, easy-to-verify solution, whereas the provided DP (Code B) only returns the maximum value and omits reconstruction of which items achieve it. Also, although brute-force is exponential, it is simple, uses built-in combinatorics (good for small n), and avoids the potentially large $O(n \cdot \text{capacity})$ time/space cost and implementation pitfalls of the DP when capacity is huge or item reconstruction is required.

Problem: This Python code solves the algorithmic problem of Knapsack that involves selecting items to maximize value under a weight/capacity constraint using dynamic programming and returning both value and chosen items.

ID 5. Text_A: More computationally complex code

Text_B: Less computationally complex code

Annotator_Score_1: 1

Annotator_Score_2: 3

Annotator_Score_3: 1

GPT5_Score: 0

Ann_Comments_1:

Ann_Comments_2: I would slightly prefer Option A. It uses a recursive merge sort approach, which has a predictable $O(n \log n)$ time complexity, making it more efficient for larger lists compared to bubble sort. Although the recursion and merging logic is a bit more complex, it's generally more suitable for handling bigger datasets in daily work.

Ann_Comments_3:

GPT5_Comments: I picked 0 (strongly prefer A) because this bubble_sort is simple, in-place, and has low per-operation overhead with an early-exit optimization (best case $O(n)$), making it predictable and lightweight for typical small-to-moderate inputs. The provided merge_sort implementation is actually inefficient in practice — it repeatedly slices lists, uses pop(0) ($O(n)$ per pop), and concatenates lists, which induces extra copies and can degrade to much worse than the ideal $O(n \log n)$ behavior and use more memory, so its real-world time/space cost can exceed the bubble sort shown.

Problem: This Python code solves the algorithmic problem of Sorting Algorithm by ordering elements according to a key and stability rules, discussing time/space complexity and worst-case behavior.