PHYSICS-INFORMED DEEP LEARNING OF INCOMPRESSIBLE FLUID DYNAMICS

ABSTRACT

Fast and stable fluid simulations are an essential prerequisite for applications ranging from computer-generated imagery to computer-aided design in research and development. Solving the partial differential equations governed by the dynamics of incompressible fluids, however, is a challenging task and traditional numerical approximation schemes come at high computational costs. Recent deep learning based approaches promise vast speed-ups but either do not generalize to new domain geometries or rely on complex pipelines that outsource major parts of the fluid simulation to traditional methods.

In this work, we propose a novel unsupervised training framework that allows powerful convolutional neural networks to learn the entire update step of mapping a fluid state from time-point t to a subsequent state at time $t + dt$. For this purpose, we introduce a physics-informed loss function that penalizes residuals of the incompressible Navier-Stokes equations on a staggered grid. This greatly simplifies the pipeline to train and evaluate neural fluid models. After training, the framework yields models that are capable of fast fluid simulations and can handle various fluid phenomena including the Magnus effect and Kármán vortex streets. We present an interactive real-time demo and show that trained models can generalize to new domain geometries unseen during training. Moreover, the trained neural networks offer a differentiable update step to advance the fluid simulation in time and, thus, can be used as efficient differentiable fluid solvers. This can be exploited for optimal control tasks as we demonstrate in a proof-of-concept experiment. Our models significantly outperform a recent differentiable fluid solver in terms of computational speed and accuracy.

1 INTRODUCTION

Simulating the behavior of fluids by solving the incompressible Navier-Stokes equations is of great importance for a wide range of applications and accurate as well as fast fluid simulations are a long-standing research goal. On top of simulating the behavior of fluids, several applications such as sensitivity analysis of fluids or gradient-based control algorithms rely on differentiable fluid simulators that allow to propagate gradients throughout the simulation (Holl et al. (2020)).

Recent advances in deep learning aim for fluid simulations that combine accuracy and speed. Kim et al. (2019) present a framework to learn parameterized fluid simulations and allow to interpolate efficiently in between such simulations. However, their work does not generalize to new domain geometries that lay outside the training data. Kim & Lee (2020) train a RNN-GAN that produces turbulent flow fields within a pipe domain, but do not show generalization results beyond pipe domains. Xie et al. (2018) introduce a tempoGAN to perform temporally consistent superresolution of smoke simulations. This allows to produce plausible high-resolution smoke-density fields for arbitrary low-resolution inputs, but in our case, the fluid model should output a complete fluid state description consisting of a velocity and a pressure field. Tompson et al. (2017) present how a Helmholtz projection step can be learned to accelerate Eulerian fluid simulations. This method generalizes to new domain geometries, but a particle tracer is needed to deal with the advection term of the Navier-Stokes equations. Furthermore, as Eulerian fluids do not model viscosity, effects like e.g. the Magnus effect or Kármán vortex streets cannot be simulated. Geneva & Zabaras (2020) propose a physics-informed framework to learn the entire update step for the Burgers equations in

1D and 2D, but no generalization results for new domain geometries are demonstrated. All of the aforementioned methods rely on the availability of vast amounts of data from fluid-solvers such as FEniCS, OpenFOAM or Mantaflow. Most of these methods do not generalize well or outsource a major part of the fluid simulation to traditional methods such as low-resolution fluid solvers or a particle tracer.

In this work, we propose a novel unsupervised training framework that does not require any simulated fluid-data (neither as ground truth data, nor to train an adversarial network, nor to initialize frames for a physics-informed loss). It allows CNNs to learn the entire update-step of mapping a fluid domain from time-point t to $t + dt$ without having to rely on low resolution fluid-solvers or a particle-tracer. In fact, we will demonstrate that a physics-informed loss function combined with a simple strategy to recycle fluid-data generated by the neural network at training time suffices to teach CNNs fluid dynamics on increasingly realistic statistics of fluid states. This drastically simplifies the training pipeline. Fluid simulations get efficiently unrolled in time by recurrently applying the trained model on a fluid state. Furthermore, the fluid models include viscous friction and handle effects such as the Magnus effect and Kármán vortex streets. On top of that, we show by means of a gradient-based optimal control example how backpropagation through time can be used to differentiate the fluid simulation. Code and pretrained models are supplied in the supplementary material.

2 RELATED WORK

In literature, several different approaches can be found that aim to approximate the dynamics of PDEs in general and fluids in particular with efficient, learning-based surrogate models.

Lagrangian methods such as smoothed particle hydrodynamcs (SPH) Gingold & Monaghan (1977) handle fluids from the perspective of many individual particles that move with the velocity field. Following this approach, learning-based methods using regression forests by Ladický et al. (2015), graph neural networks by Mrowca et al. (2018); Li et al. (2019) and continuous convolutions by Ummenhofer et al. (2020) have been developed. In addition, Smooth Particle Networks (SP-Nets) by Schenck & Fox (2018) allow for differentiable fluid simulations within the Lagrangian frame of reference. These Lagrangian methods are particularly suitable when a fluid domain exhibits large, dynamic surfaces (e.g. waves or droplets). However, to simulate the dynamics within a fluid domain accurately, *Eulerian methods*, that treat the Navier-Stokes equations in a fixed frame of reference, are usually better suited.

Continuous Eulerian methods allow for mesh-free solutions by mapping domain coordinates (e.g. x,y,t) directly onto field values (e.g. velocity $\vec{v}$ / pressure p) (Sirignano & Spiliopoulos (2018); Grohs et al. (2018); Khoo et al. (2019)). Recent applications focused on flow through porous media (Zhu & Zabaras (2018); Zhu et al. (2019); Tripathy & Bilionis (2018)), fluid modeling (Yang et al. (2016); Raissi et al. (2018)), turbulence modeling (Geneva & Zabaras (2019); Ling et al. (2016)) and modeling of molecular dynamics (Schöberl et al. (2019)). Training is usually based on physics-constrained loss functions that penalize residuals of the underlying PDEs. Similar to our approach, Raissi et al. (2019) uses vector potentials to obtain continuous divergence-free velocity fields to approximate the incompressible Navier-Stokes equations. Continuous methods return smooth, accurate results and can overcome the curse of dimensionality of discrete techniques in high-dimensional PDEs (Grohs et al. (2018)). However, these networks are trained on a specific domain and cannot generalize to new environments or be used in interactive scenarios.

Discrete Eulerian methods, on the other hand, aim to solve the underlying PDEs on a grid and early work dates back to Harlow & Welch (1965) and Stam (1999). Accelerating such traditional works with deep learning techniques is a major field of research and all of the methods mentioned in the introduction fall into this category. Further methods include the approach by Thuerey et al. (2019) to learn solutions of the Reynolds-averaged Navier-Stokes equations for airfoil flows, but requires large amounts of training data and does not generalize beyond airfoil flows. In the work by Um et al. (2020), a correction step is learned that brings solutions of a low-resolution differentiable fluid solver closer to solutions of a high-resolution fluid simulation. However, generalization results for new domain geometries were not presented.

3 METHOD

In this section, we briefly review the incompressible Navier-Stokes equations, which are to be solved by the neural network. Then, we explain how the Helmholtz decomposition can be exploited to ensure incompressibility within the fluid domain. Furthermore, we provide details of our discrete spatio-temporal fluid representation and introduce the fluid model. Afterwards, we formulate a physics-informed loss function based on residuals of the Navier-Stokes equations and introduce a pressure regularization term in case of very high Reynolds numbers. Finally, we explain the unsupervised training strategy.

3.1 INCOMPRESSIBLE NAVIER-STOKES EQUATIONS

Most fluids can be modeled very accurately with the incompressible Navier-Stokes equations - a set of non-linear equations that describe the interplay of a velocity field $\vec{v}$ and a pressure field p within a fluid domain Ω:

$$\nabla \cdot \vec{v} = 0 \qquad\qquad\qquad\qquad \text{incompressibility on } \Omega \qquad (1)$$

$$\rho \dot{\vec{v}} = \rho \left(\frac{\partial \vec{v}}{\partial t} + (\vec{v} \cdot \nabla) \vec{v} \right) = -\nabla p + \mu \Delta \vec{v} + \vec{f} \qquad \text{conservation of momentum on } \Omega \qquad (2)$$

Here, ρ describes the fluid density and μ the viscosity. Equation 1 states that the fluid is incompressible and thus $\vec{v}$ is divergence-free. Equation 2 states that the change in momentum of fluid particles must correspond to the sum of forces that arise from the pressure gradient, viscous friction and external forces. In our case, external forces on the fluid (such as e.g. gravity) can be neglected, so we set $\vec{f} = 0$.

These incompressible Navier-Stokes equations shall be solved by a CNN given initial conditions $\vec{v}^0$ and p^0 at the beginning of the simulation and Dirichlet boundary conditions which constrain the velocity field at the domain boundary $\partial\Omega$:

$$\vec{v} = \vec{v}_d \qquad\qquad \text{Dirichlet boundary condition on } \partial\Omega \qquad (3)$$

3.2 HELMHOLTZ DECOMPOSITION

A common method to ensure incompressibility of a fluid (see Equation 1) is to project the flow field onto the divergence-free part of its Helmholtz decomposition. The Helmholtz theorem states that every vector field $\vec{v}$ can be decomposed into a curl-free part (∇q) and a divergence-free part ($\nabla \times \vec{a}$):

$$\vec{v} = \nabla q + \nabla \times \vec{a} \qquad (4)$$

Note, that $\nabla \times (\nabla q) = \vec{0}$ and $\nabla \cdot (\nabla \times \vec{a}) = 0$. The Helmholtz projection consists of solving the Poisson problem $\nabla \cdot \vec{v} = \Delta q$ for q, followed by substracting ∇q from the original flow field. However, solving the Poisson equation on arbitrary domains comes at high computational costs for classical methods and one has to rely e.g. on conjugate gradient methods to approximate its solution.

Here, we propose a different approach and directly try to learn a vector potential $\vec{a}$ with $\vec{v} = \nabla \times \vec{a}$. This ensures that the network outputs a divergence-free velocity field within the domain Ω and automatically solves Equation 1. In this work, we consider 2D fluid simulations, so only the z-component of $\vec{a}$, a_z, is of interest since v_z and all derivatives with respect to the z-axis are zero:

$$\nabla \times \vec{a} = \begin{pmatrix} \partial_y a_z - \partial_z a_y \\ \partial_z a_x - \partial_x a_z \\ \partial_x a_y - \partial_y a_x \end{pmatrix} = \begin{pmatrix} \partial_y a_z \\ -\partial_x a_z \\ 0 \end{pmatrix} = \begin{pmatrix} v_x \\ v_y \\ 0 \end{pmatrix} = \vec{v} \qquad (5)$$

3.3 DISCRETE SPATIO-TEMPORAL FLUID REPRESENTATION

Marker-And-Cell (MAC) grid To solve the Navier-Stokes equations, we represent the relation between a_z, v_x, v_y, p on a 2D staggered marker-and-cell (MAC) grid (see Figure 1a). Therefore, we discretise time and space as follows:

$$\vec{a}(x,y,t) = \begin{pmatrix} 0 \\ 0 \\ (a_z)_{i,j}^t \end{pmatrix} ; \ \vec{v}(x,y,t) = \begin{pmatrix} (v_x)_{i,j}^t \\ (v_y)_{i,j}^t \end{pmatrix} ; \ p(x,y,t) = p_{i,j}^t \tag{6}$$

Obtaining gradient, divergence, Laplace and curl operations on this grid with finite differences is straight forward and can be efficiently implemented with convolutions (see appendix A).

(a) Layout of Staggered Marker-And-Cell (MAC) grid in 2D.

(b) Diagram of the fluid model. By recurrently applying the model on the fluid state (p^t and a^t), we can unroll the fluid simulation in time.

Figure 1: MAC grid and diagram of the fluid model.

Explicit, Implicit, Implicit-Explicit (IMEX) time integration methods The discretization of the time domain is needed to deal with the time-derivative of the velocity field $\frac{\partial \vec{v}}{\partial t}$ in Equation 2, which becomes:

$$\rho \left(\frac{\vec{v}^{t+dt} - \vec{v}^t}{dt} + \left(\vec{v}^{t'} \cdot \nabla \right) \vec{v}^{t'} \right) = -\nabla p^{t+dt} + \mu \Delta \vec{v}^{t'} + \vec{f} \tag{7}$$

The goal is to take as large as possible timesteps dt while maintaining stable and accurate solutions. Stability and accuracy largely depend on the definition of $v^{t'}$. In literature, choosing $v^{t'} = v^t$ is often referred to as explicit integration methods and frequently leads to unstable behavior. Choosing $v^{t'} = v^{t+dt}$ is usually associated with implicit integration methods and gives stable solutions at the cost of numerical dissipation. Implicit-Explicit (IMEX) methods, which set $v^{t'} = (v^t + v^{t+dt})/2$ are a compromise between both methods and considered to be more accurate but less stable than implicit methods.

3.4 FLUID MODEL

We represent the fluid dynamics by a recurrent model that maps the fluid state $p^t, \vec{a}^t$ for timestep t and the domain description $\Omega^{t+dt}, \vec{v}_d^{t+dt}$ to the fluid state $p^{t+dt}, \vec{a}^{t+dt}$ of the next timestep. Here, p^t describes the pressure field and $\vec{a}^t$ describes the vector potential of $\vec{v}^t$. For $t = 0$, we consider initial states $p^0 = 0$ and $\vec{a}^0 = \vec{0}$, however, other initial conditions could be considered as well. Ω^{t+dt} is a binary mask that contains the domain geometry and is 1 for the fluid domain and 0 everywhere else. For the boundary of the domain, we simply take the inverse of Ω: $\partial\Omega = 1 - \Omega$. $\vec{v}_d^{t+dt}$ represents the Dirichlet boundary conditions and contains a velocity field that must be matched by $\vec{v}^{t+dt}$ at the domain boundaries. Figure 1b shows a diagram of the fluid model. First, $\left(p^t, \vec{a}^t, \Omega^{t+dt}, \vec{v}_d^{t+dt}\right)$ are taken to derive a slightly more meaningful feature representation that comprises $\left(p^t, a^t, \nabla \times a^t, \Omega^{t+dt}, \partial\Omega^{t+dt}, \Omega^{t+dt} \cdot \nabla \times a^t, \Omega^{t+dt} \cdot p^t, \partial\Omega^{t+dt} \cdot \vec{v}_d^{t+dt}\right)$. These features can be very efficiently computed with convolutions and are then fed into a U-Net (Ronneberger et al. (2015)) with a reduced number of channels (the exact network configuration can be found in appendix B). The mean of the U-Net output is set to 0 in order to keep p and $\vec{a}$ well defined and prevent drifting offset values. Finally, the output is added to p^t and $\vec{a}^t$ to obtain the updated fluid state p^{t+dt} and $\vec{a}^{t+dt}$.

3.5 PHYSICS-CONSTRAINED LOSS FUNCTION

Using the residuals of the Navier-Stokes equations (Equations 1 and 2), we can formulate the following loss terms on Ω and $\partial\Omega$:

$$L_d = \|\nabla \cdot \vec{v}\|^2 \qquad\qquad \text{divergence loss on } \Omega \qquad (8)$$

$$L_p = \left\|\rho\left(\frac{\partial\vec{v}}{\partial t} + (\vec{v}\cdot\nabla)\vec{v}\right) + \nabla p - \mu\Delta\vec{v} - \vec{f}\right\|^2 \qquad \text{momentum loss on } \Omega \qquad (9)$$

$$L_b = \|\vec{v} - \vec{v}_d\|^2 \qquad\qquad \text{boundary loss on } \partial\Omega \qquad (10)$$

Combining the described loss terms, we obtain the following loss function:

$$L = \alpha L_d + \beta L_p + \gamma L_b \qquad (11)$$

where α, β, γ are hyperparameters that weight the contributions of the different loss terms. Note that if we use a vector potential $\vec{v} = \nabla \times \vec{a}$, $L_d = 0$ is automatically fulfilled and we can set $\alpha = 0$. This loss function can be computed very efficiently with convolutions in $O(N)$ (where N = number of grid cells), whereas solving the Navier-Stokes equations explicitly would be computationally a lot more expensive. For detailed descriptions regarding the fully discretized loss-function, we refer to appendix A.

3.6 PRESSURE REGULARIZATION

In the special case of very high Reynolds numbers (see Equation 13) and inviscid flows, training becomes unstable as viscous friction cannot dissipate enough energy out of the system anymore. This leads to unrealistic gradients in $\vec{v}$ and p.

For such cases, we introduce an additional regularization term for the loss function (11) that can be traded off with L_p to stabilize training:

$$L_r = \|\nabla p\|^2 \qquad (12)$$

The intuition behind this regularization term is, that we want to penalize unrealistically high energies in the pressure field.

3.7 TRAINING STRATEGY

Training starts with initializing a pool $\{\Omega_k^0, (v_d)_k^0, (a_z)_k^0, p_k^0\}$ of randomized domains Ω_k^0 and boundary conditions $(v_d)_k^0$ as well as initial conditions for the vector potential and pressure fields that we both set to zero ($(a_z)_k^0 = 0$ and $p_k^0 = 0$). The resolution of our training domains is 100x300 grid cells and example-domains of the training pool are shown in appendix C. Note that our training pool does not rely on any previously simulated fluid-data.

At each training step, a random mini-batch $\{\Omega_k^t, (v_d)_k^t, (a_z)_k^t, p_k^t\}_{\{k\in\text{minibatch}\}}$ is drawn from the pool and fed into the neural network which is designed to predict the velocity ($\vec{v}_k^{t+dt} = \nabla \times \vec{a}_k^{t+dt}$) and pressure ($p_k^{t+dt}$) fields of the next time step. Based on a physics-informed loss-function (Equation 11), we update the weights of the network using the Adam optimizer (Kingma & Ba (2015)). At the end of each training step, the pool is updated by replacing the old vector potential and pressure fields $(a_z)_k^t, p_k^t$ by the newly predicted ones $(a_z)_k^{t+dt}, p_k^{t+dt}$. This recycling strategy fills the training pool with more and more realistic fluid states as the model becomes better at simulating fluid dynamics.

From time to time, old environments of the training pool are replaced by new randomized environments and the vector potential as well as the pressure fields are reset to 0. This increases the variance of the training pool and helps the neural network to learn "cold starts" from $\vec{0}$-velocity and 0-pressure fields.

Besides the fluid model described above, which we denote as $\vec{a}$-Net in the following, we also trained an ablation model, $\vec{v}$-Net, that directly learns to predict the velocity field without a vector potential. For the implementation of both models, we used the popular machine learning framework Pytorch

and trained the models on a NVidia GeForce RTX 2080 Ti. Training converged after about 1 day. The hyperparameters in the loss-function for the $\vec{a}$-Net were $\beta = 1$ and $\gamma = 20$. The reason for choosing a higher weight for the loss term L_b than for L_p was the observation, that errors in L_b can lead to unrealistic flows leaking through boundaries. For the ablation study ($\vec{v}$-Net), we used $\alpha = 100, \beta = 1, \gamma = 0.001$. Here, we had to choose a very high weight for L_d to ensure incompressibility of the fluid, otherwise unrealistic source and sink effects start to appear. For L_b, on the other hand, we used a very low weight as the boundary conditions can be trivially learned by the $\vec{v}$-Net. We used these parameter settings for all experiments.

4 Results

To evaluate the potential of our method, we assess its ability to re-produce physical effects such as Kármán vortex streets and the Magnus effect. In addition, we demonstrate its generalization capability and real-time performance. Finally, we test the fluid models quantitatively.

4.1 Qualitative Evaluation

Qualitative analysis of wake dynamics   The Reynolds number is a dimensionless quantity closely related to qualitative effects in fluid dynamics such as the wake dynamics behind an obstacle. It is defined by:

$$Re = \frac{\rho \, \|\vec{v}\| \, D}{\mu} \tag{13}$$

Here, ρ is the fluid density, $\|\vec{v}\|$ is the fluid speed, D is the diameter of the obstacle, and μ is the viscosity. (We use the units of the grid).

We retrained models for different values of μ and ρ to compare the fluid behavior for a wide range of Reynolds numbers. Figure 2 shows, that the trained models are able to predict the wake dynamics behind an obstacle in good accordance with qualitative expectations from fluid dynamics. As a rule of thumb, for $Re \ll 1$, the flow becomes time-reversible. This can be noticed in Figure 2a by the symmetry of the flow before and after the obstacle and the nearly constant pressure gradient within the pipe. Starting from $Re \approx 10$, the flow is still laminar but a static wake is forming behind the obstacle (see Figure 2b). For Reynolds numbers $Re >\approx 90$, Kármán vortex streets start to appear (see Figure 2c). A Kármán vortex street consists of clock and counterclockwise spinning vortices that are generated at the obstacle and then start moving in a regularly oscillating pattern with the flow. For very large Reynolds numbers or inviscid flows, the flow field becomes turbulent, which can be recognized by the irregular patterns behind the obstacle in Fig 2d.

(a) Re=0.6, $\mu = 5, \rho = 0.2$ **(b)** Re=30, $\mu = 0.5, \rho = 1$

(c) Re=600, $\mu = 0.1, \rho = 4$ **(d)** Re$\rightarrow \infty$, $\mu = 0, \rho = 1$
(obtained with regularization on ∇p)

Figure 2: After training, our models are able to show correct wake flow dynamics for a wide range of different Reynolds numbers. ($D = 30, \|\vec{v}\| = 0.5$). Streamlines indicate flow direction, linewidth indicates speed and colors represent the pressure field (blue: low pressure / yellow: high pressure).

(a) Magnus effect on a clock-wise turning cylinder. **(b)** Generalization example: Note that the fluid model has never been confronted with wing-profiles during training.

Figure 3: Our models feature the Magnus effect and generalize to new fluid domains. Further examples are presented in appendix D and the video.

Magnus effect   The Magnus effect appears when a flow interacts with a rotating body. It is widely known e.g. in sports such as soccer or tennis where spin is used to deflect the path of a ball. The reason for the deflection stems from a low pressure field where the surface of the object moves along flow direction and a high pressure field where the object surface moves against the flow. Figure 3a shows, that our models are able to reproduce the Magnus effect around a rotating cylinder.

Analysis of generalization capability   We also tested the networks capability to generalize to objects not seen during training. Figure 3b shows the networks capability to meet boundary conditions of an airfoil and return a plausible pressure field that produces lift (see low pressure on top of wing). Note that in contrast to the approach by Thuerey et al. (2019), which learns simplified, time-averaged solutions of the Navier-Stokes equations, our method is able to simulate the full incompressible Navier-Stokes equations for an airfoil without relying on any ground truth data or having seen airfoil-geometries during training. Further generalization examples are provided in appendix D.

Real-time capability   Since progressing the simulation by a timestep consists merely of one forward pass through a convolutional neural network, it can be easily parallelized and achieved at comparably low computational costs. This enables for example interactive real-time simulations. We implemented a demo that allows to interact with a fluid by moving obstacles, rotating spheres and changing the flow speed within a pipe (see video in supplementary material and source code). Our method runs at 250 timesteps per second on a 100x300 grid. In the respective experiments, we used a NVidia GeForce RTX 2080 Ti consuming about 860 MB of GPU memory.

4.2 QUANTITATIVE EVALUATION

Quantitative comparison of different fluid solvers is challenging, as their performance is highly dependent on factors like the geometry of the domain, fluid parameters such as viscosity or density, flow speed or the timestep of the integrator. As benchmarks for fluid simulations on MAC grids are not yet available, we built a simple toy domain on a 100 x 100 grid which simulates a flow around an obstacle within a pipe (more details are provided in appendix E). We compare our method ($\vec{a}$-Net) against the recently released, open source, differentiable fluid simulator PhiFlow by Holl et al. (2020) and provide an ablation study ($\vec{v}$-Net) that does not make use of the Helmholtz decomposition but directly works on the velocity field $\vec{v}$.

First, we compared the computational speed on a CPU and GPU by looking at the number of timesteps that the different methods could integrate per second (see Table 1). The $\vec{v}$-Net as well as the $\vec{a}$-Net are significantly faster than PhiFlow (11x on CPU and 40x on GPU) as they do not rely on an iterative conjugate gradient solver but instead use a single forward pass through a convolutional neural network that can be easily parallelized on a GPU. To provide a fair comparison on L_d, we set the velocity field at the boundaries equal to $\vec{v}_d$. This enables us to compute L_d for the $\vec{a}$-Net architecture on the domain boundaries which would otherwise have zero divergence everywhere. For $dt = 4$, we outperformed Phiflow by several orders of magnitude. For both, L_d and L_p, the $\vec{a}$-Net architecture significantly outperformed the more naive $\vec{v}$-Net approach. Furthermore, we investigated the evolution of L_p and L_d for the $\vec{a}$-Net over time (see Figure 4). As the fluid state is initialized with $a_z = 0$ and $p = 0$, the $\vec{a}$-Net has to perform a cold-start which is the reason for high

L_p and L_d during the first circa 70 steps. Afterwards, the $\vec{a}$-Net continues an accurate and stable fluid simulation.

Method	CPU [TPS]	GPU [TPS]	L_d	L_p
PhiFlow	7	-	6.2e-4	-
$\vec{v}$-Net (ours)	82	311	8.66e-7	4.87e-5
$\vec{a}$-Net (ours)	82	311	**5.44e-7**	**1.56e-5**

Table 1: Quantitative comparison of timesteps per second (TPS) on CPU / GPU as well as divergence loss and momentum loss for differentiable fluid solvers on a 100x100 grid for timesteps of size $dt = 4$.

Figure 4: Long term stability of fluid simulations performed by the $\vec{a}$-Net

4.3 Optimal Control of Vortex Shedding Frequency

In this section, we present a proof-of-concept experiment to show the effectiveness of backpropagating gradients through time in order to obtain differentiable fluid simulations with our previously trained fluid models. For this purpose, we consider an application scenario that aims at controlling the shedding frequency of a Kármán vortex street by changing the flow speed within a pipe. Therefore, we measure the y-component of the velocity field $v_y(t)$ behind an obstacle (see white box in Figure 5a) over time and adjust the inflow / outflow boundary conditions in $\vec{v}_d$ such that $E[|V_y(f)|^2] = \hat{f}$. Here, $\hat{f}$ is the target frequency and $V_y(f)$ is the frequency spectrum of $v_y(t)$ that can be efficiently computed using the fast Fourier transform (see Figure 5b). To optimize $\vec{v}_d$, we define a Loss function $L = (E[|V_y(f)|^2] - \hat{f})^2$ and compute the gradients $\frac{\partial L}{\partial \vec{v}_d}$ with a standard automatic differentiation library (Pytorch). This is possible since all parts of the loss function including the fluid simulation and the fast Fourier transform are differentiable. The update steps of $\vec{v}_d$ are done using the ADAM-optimizer and converge after approximately 70 iterations (see Figure 5c). We want to emphasize that differentiable fluid simulations are limited to scenarios with low Reynolds numbers as in the presence of turbulences, chaotic behavior will lead to exploding gradients.

(a) control setup   (b) frequency distribution   (c) optimization curve

Figure 5: The frequency of vortex streets can be controlled using our differentiable fluid models.

5 Discussion and Outlook

In this work, we present an unsupervised learning scheme for the incompressible Navier-Stokes equations and introduce a fluid model that uses a vector potential to output divergence-free velocity fields. Qualitative results of our trained fluid models are in good accordance with expectations from fluid dynamics for a wide range of Reynolds numbers and generalize to unknown fluid domains. Quantitative assessment showed superior performance in terms of accuracy and speed compared to Phiflow and a naive approach that directly predicts the velocity field. We present a real-time demo and demonstrate how differentiability can be used in a proof-of-concept fluid control scenario. We believe that our fluid models can significantly speed up more sophisticated fluid control pipelines such as described by Holl et al. (2020).

First experiments of extending this approach to 3D deliver encouraging results and are topic of future research. Furthermore, on top of Dirichlet boundary conditions, Neumann boundary conditions and multi-phase domains could be incorporated in future fluid models as well.

REFERENCES

Nicholas Geneva and Nicholas Zabaras. Quantifying model form uncertainty in reynolds-averaged turbulence models with bayesian deep neural networks. *Journal of Computational Physics*, 383: 125 – 147, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.01.021. URL `http://www.sciencedirect.com/science/article/pii/S0021999119300464`.

Nicholas Geneva and Nicholas Zabaras. Modeling the dynamics of pde systems with physics-constrained deep auto-regressive networks. *Journal of Computational Physics*, 403:109056, 2020.

Robert A. Gingold and Joseph J. Monaghan. Smoothed particle hydrodynamics: theory and application to non-spherical stars. *Monthly notices of the royal astronomical society*, 181(3): 375–389, 1977.

Philipp Grohs, Fabian Hornung, Arnulf Jentzen, and Philippe Von Wurstemberger. A proof that artificial neural networks overcome the curse of dimensionality in the numerical approximation of black-scholes partial differential equations. *arXiv preprint arXiv:1809.02362*, 2018.

Francis H. Harlow and J. Eddie Welch. Numerical calculation of time-dependent viscous incompressible flow of fluid with free surface. *The physics of fluids*, 8(12):2182–2189, 1965.

Philipp Holl, Vladlen Koltun, and Nils Thuerey. Learning to control pdes with differentiable physics. *ICLR*, 2020.

Yuehaw Khoo, Jianfeng Lu, and Lexing Ying. Solving for high-dimensional committor functions using artificial neural networks. *Research in the Mathematical Sciences*, 6(1):1, 2019.

Byungsoo Kim, Vinicius C. Azevedo, Nils Thuerey, Theodore Kim, Markus Gross, and Barbara Solenthaler. Deep fluids: A generative network for parameterized fluid simulations. In *Computer Graphics Forum*, volume 38, pp. 59–70. Wiley Online Library, 2019.

Junhyuk Kim and Changhoon Lee. Deep unsupervised learning of turbulence for inflow generation at various reynolds numbers. *Journal of Computational Physics*, 406:109216, 2020. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.109216. URL `http://www.sciencedirect.com/science/article/pii/S0021999119309210`.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

L'ubor Ladický, SoHyeon Jeong, Barbara Solenthaler, Marc Pollefeys, and Markus Gross. Data-driven fluid simulations using regression forests. *ACM Trans. Graph.*, 34(6), October 2015. ISSN 0730-0301. doi: 10.1145/2816795.2818129. URL `https://doi.org/10.1145/2816795.2818129`.

Yunzhu Li, Jiajun Wu, Russ Tedrake, Joshua B Tenenbaum, and Antonio Torralba. Learning particle dynamics for manipulating rigid bodies, deformable objects, and fluids. In *ICLR*, 2019.

Julia Ling, Andrew Kurzawski, and Jeremy Templeton. Reynolds averaged turbulence modelling using deep neural networks with embedded invariance. *Journal of Fluid Mechanics*, 807:155–166, 2016.

Damian Mrowca, Chengxu Zhuang, Elias Wang, Nick Haber, Li Fei-Fei, Joshua B. Tenenbaum, and Daniel L. K. Yamins. Flexible neural representation for physics prediction. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 8813–8824, Red Hook, NY, USA, 2018. Curran Associates Inc.

Maziar Raissi, Alireza Yazdani, and George Em Karniadakis. Hidden fluid mechanics: A navier-stokes informed deep learning framework for assimilating flow visualization data. *arXiv preprint arXiv:1808.04327*, 2018.

Maziar Raissi, P. Perdikaris, and George Em Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686 – 707, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2018.10.045. URL http://www.sciencedirect.com/science/article/pii/S0021999118307125.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Connor Schenck and Dieter Fox. Spnets: Differentiable fluid dynamics for deep neural networks. In *Conference on Robot Learning*, pp. 317–335, 2018.

Markus Schöberl, Nicholas Zabaras, and Phaedon-Stelios Koutsourelakis. Predictive collective variable discovery with deep bayesian models. *The Journal of Chemical Physics*, 150(2):024109, 2019. doi: 10.1063/1.5058063. URL https://doi.org/10.1063/1.5058063.

Justin Sirignano and Konstantinos Spiliopoulos. Dgm: A deep learning algorithm for solving partial differential equations. *Journal of Computational Physics*, 375:1339 – 1364, 2018. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2018.08.029. URL http://www.sciencedirect.com/science/article/pii/S0021999118305527.

Jos Stam. Stable fluids. In *Proceedings of the 26th annual conference on Computer graphics and interactive techniques*, pp. 121–128, 1999.

Nils Thuerey, Konstantin Weißenow, Lukas Prantl, and Xiangyu Hu. Deep learning methods for reynolds-averaged navier–stokes simulations of airfoil flows. *AIAA Journal*, pp. 1–12, 2019.

Jonathan Tompson, Kristofer Schlachter, Pablo Sprechmann, and Ken Perlin. Accelerating eulerian fluid simulation with convolutional networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 3424–3433. JMLR. org, 2017.

Rohit K. Tripathy and Ilias Bilionis. Deep uq: Learning deep neural network surrogate models for high dimensional uncertainty quantification. *Journal of Computational Physics*, 375:565 – 588, 2018. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2018.08.036. URL http://www.sciencedirect.com/science/article/pii/S0021999118305655.

Kiwon Um, Raymond Fei, Philipp Holl, Robert Brand, and Nils Thuerey. Solver-in-the-loop: Learning from differentiable physics to interact with iterative pde-solvers, 2020.

Benjamin Ummenhofer, Lukas Prantl, Nils Thuerey, and Vladlen Koltun. Lagrangian fluid simulation with continuous convolutions. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=B1lDoJSYDH.

You Xie, Erik Franz, Mengyu Chu, and Nils Thuerey. Tempogan: A temporally coherent, volumetric gan for super-resolution fluid flow. *ACM Trans. Graph.*, 37(4), July 2018. ISSN 0730-0301. doi: 10.1145/3197517.3201304. URL https://doi.org/10.1145/3197517.3201304.

Cheng Yang, Xubo Yang, and Xiangyun Xiao. Data-driven projection method in fluid simulation. *Computer Animation and Virtual Worlds*, 27(3-4):415–424, 2016. doi: 10.1002/cav.1695. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/cav.1695.

Yinhao Zhu and Nicholas Zabaras. Bayesian deep convolutional encoder–decoder networks for surrogate modeling and uncertainty quantification. *Journal of Computational Physics*, 366:415 – 447, 2018. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2018.04.018. URL http://www.sciencedirect.com/science/article/pii/S0021999118302341.

Yinhao Zhu, Nicholas Zabaras, Phaedon-Stelios Koutsourelakis, and Paris Perdikaris. Physics-constrained deep learning for high-dimensional surrogate modeling and uncertainty quantification without labeled data. *Journal of Computational Physics*, 394:56 – 81, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.05.024. URL http://www.sciencedirect.com/science/article/pii/S0021999119303559.

A PHYSICS-INFORMED LOSS ON A MAC GRID

As mentioned in Section 3.3 of the paper, our method relies on a staggered marker-and-cell grid representation for the vector potential as well as the velocity and pressure fields. In the following, we provide further details on how to apply this representation to learn incompressible fluid dynamics.

To calculate the velocity field $\vec{v} = \nabla \times \vec{a}$ of a vector potential $\vec{a}$ on a MAC grid in 2D, we have to compute the curl as follows:

$$
\begin{aligned}
(v_x)_{i,j} &= (a_z)_{i+1,j} - (a_z)_{i,j} \\
(v_y)_{i,j} &= (a_z)_{i,j} - (a_z)_{i,j+1}
\end{aligned}
\tag{14}
$$

If this vector potential is inserted into the divergence operator on a MAC grid, we can show that $\nabla \cdot \vec{v}_{i,j} = 0$ is indeed fulfilled:

$$
\nabla \cdot \vec{v}_{i,j} = (v_x)_{i,j+1} - (v_x)_{i,j} + (v_y)_{i+1,j} - (v_y)_{i,j}
\tag{15}
$$

$$
= \begin{aligned}[t]
&((a_z)_{i+1,j+1} - (a_z)_{i,j+1}) - ((a_z)_{i+1,j} - (a_z)_{i,j}) \\
&+ ((a_z)_{i+1,j} - (a_z)_{i+1,j+1}) - ((a_z)_{i,j} - (a_z)_{i,j+1})
\end{aligned}
\tag{16}
$$

$$
= 0
\tag{17}
$$

Thus, for the $\vec{a}$-Net, the incompressibility equation is automatically fulfilled and no further training on the divergence loss L_d is required. However, for the $\vec{v}$-Net, the residuals of the divergence are still of importance:

$$
(R_d)_{i,j}^{t+dt} = \nabla \cdot \vec{v}_{i,j}^{t+dt} (= 0 \text{ for } \vec{a}\text{-Net})
\tag{18}
$$

The residuals of the momentum equation in x-direction can be computed as follows:

$$
\begin{aligned}
(R_{p_x})_{i,j}^{t+dt} = \rho \Bigg(& \frac{(v_x)_{i,j}^{t+dt} - (v_x)_{i,j}^t}{dt} + (v_x)_{i,j}^{t'} \cdot \frac{(v_x)_{i,j+1}^{t'} - (v_x)_{i,j-1}^{t'}}{2} \\
& + \frac{\frac{(v_y)_{i,j-1}^{t'} + (v_y)_{i,j}^{t'}}{2} \cdot \left((v_x)_{i,j}^{t'} - (v_x)_{i-1,j}^{t'} \right) + \frac{(v_y)_{i+1,j-1}^{t'} + (v_y)_{i+1,j}^{t'}}{2} \cdot \left((v_x)_{i+1,j}^{t'} - (v_x)_{i,j}^{t'} \right)}{2} \Bigg) \\
& + \left(p_{i,j}^{t+dt} - p_{i,j-1}^{t+dt} \right) - \mu \cdot \Delta (v_x)_{i,j}^{t'}
\end{aligned}
\tag{19}
$$

Here, we use the following isotropic Laplace operator:

$$
\begin{aligned}
\Delta s_{i,j} = \frac{1}{4} (& 1 * s_{i-1,j-1} + 2 * s_{i-1,j} + 1 * s_{i-1,j+1} \\
& + 2 * s_{i,j-1} - 12 * s_{i,j} + 2 * s_{i,j+1} \\
& + 1 * s_{i+1,j-1} + 2 * s_{i+1,j} + 1 * s_{i+1,j+1})
\end{aligned}
\tag{20}
$$

The derivation of the advection term for R_{p_x} is a bit more complex since on a MAC grid, v_x and v_y are displaced by half a pixel in x-direction and y-direction. To obtain the residuals of the momentum equation in y-direction, $(R_{p_y})_{i,j}$, one has to take $(R_{p_x})_{i,j}$ and swap x and y and the indices respectively.

Now, the discretized loss terms can be written as follows:

$$
L_d^{t+dt} = \sum_{i,j} \Omega_{i,j}^{t+dt} ((R_d)_{i,j}^{t+dt})^2
\tag{21}
$$

$$
L_p^{t+dt} = \sum_{i,j} \Omega_{i,j}^{t+dt} \left(((R_{p_x})_{i,j}^{t+dt})^2 + ((R_{p_y})_{i,j}^{t+dt})^2 \right)
\tag{22}
$$

$$
L_b^{t+dt} = \sum_{i,j} \partial \Omega_{i,j}^{t+dt} \left\| \vec{v}_d^{t+dt} - \vec{v}^{t+dt} \right\|^2
\tag{23}
$$

Note, that all mentioned operations can be efficiently implemented with convolutions. To obtain the final velocities on a square grid, we project the velocity fields of the MAC grid back onto the $\vec{a}$-grid using linear interpolation:

$$\vec{v} = \frac{1}{2} \begin{pmatrix} (v_x)_{i-1,j} + (v_x)_{i,j} \\ (v_y)_{i,j-1} + (v_y)_{i,j} \end{pmatrix} \tag{24}$$

B NETWORK ARCHITECTURE

Our fluid model is based on the U-Net architecture (Ronneberger et al. (2015)) with a reduced number of channels (see Figure 6). As the pressure field and vector potential can have an arbitrary offset, we always normalize the mean of the pressure (Δp) and vector potential (Δa_z) to 0 to keep these fields well-defined and prevent drifting offset values.

Figure 6: U-Net architecture with reduced number of channels.

C EXAMPLES OF TRAINING DOMAINS

The domains we used for training consist of 100×300 grids. We used 3 different randomized domains as exemplary depicted in Figure 7. First, we have boxes with randomized height and width that float on randomized paths inspired by Brownian motion in a pipe with randomized flow speed. Second, we have the same setup but replaced the boxes by cylinders with randomized radii and angular velocities in order to learn the Magnus effect. Finally, we have a folded pipe system with randomized flow speed, that is randomly flipped along the x-axis.

D FURTHER EXAMPLES OF GENERALIZATION

Note that the network was only trained on very simple domain geometries as presented in appendix C. Still, as can be seen in Figure 8, the network is capable of generalizing to far more complicated domain geometries (e.g. shark, car). Figure 8c shows that it can generalize to multiple objects in the scene, although the training set contained at most one object per scene. And Figure 8d shows that we can alter the outer boundary conditions as well. For real-time simulations, please have a look at our source code and the supplementary video.

E QUANTITATIVE ANALYSIS: THE BENCHMARK PROBLEM

Figure 9 shows the domain Ω and v_d on a 100×100 grid which was used as the benchmark problem for quantitative analysis. The flow speed for the inlet and outlet was set to 0.5. The timestep of the integrator was set to $dt = 4$ and the viscosity and fluid density were set to $\mu = 0.1$ and $\rho = 4$ respectively.

Figure 7: The left column shows Ω (in white) / $\partial\Omega$ (in black) and the right column shows $\vec{v}_d$ for three examples of training domains. (Colors indicate the direction and magnitude of $\vec{v}_d$ as depicted in Figure 9a)

(a) Shark   **(b)** Car

(c) Smiley   **(d)** Smiley in cave

Figure 8: Our models generalize to various domain geometries, although being trained only on very simple shapes (see Figure 7)

(a)   **(b)**   **(c)**

Figure 9: The left column shows Ω (in white) / $\partial\Omega$ (in black) and the right column shows $\vec{v}_d$ for the benchmark problem. (Colors indicate the direction of $\vec{v}_d$ as depicted in Figure 9a)