ShapeCrafter: A Recursive Text-Conditioned 3D Shape Generation Model

Abstract

We present **ShapeCrafter**, a neural network for recursive text-conditioned 3D shape generation. Existing methods to generate text-conditioned 3D shapes consume an entire text prompt to generate a 3D shape in a single step. However, humans tend to describe shapes recursively—we may start with an initial description and progressively add details based on intermediate results. To capture this recursive process, we introduce a method to generate a 3D shape distribution, conditioned on an initial phrase, that gradually evolves as more phrases are added. Since existing datasets are insufficient for training this approach, we present **Text2Shape++**, a large dataset of 369K shape–text pairs that supports recursive shape generation. To capture local details that are often used to refine shape descriptions, we build on top of vector-quantized deep implicit functions that generate a distribution of high-quality shapes. Results show that our method can generate shapes consistent with text descriptions, and shapes evolve gradually as more phrases are added. Our method supports shape editing, extrapolation, and can enable new applications in human–machine collaboration for creative design.

1 Introduction

Humans are unique in the animal kingdom in the use of language to describe objects, scenes and events [9]. We use language not only to describe an object's physical and functional attributes, but also to qualify or modify those attribute descriptions. More specifically, we use (linguistic) *recursion* [7]—we may start with an initial description of an object, and progressively add phrases to describe it better or modify it. We use this ability extensively, for instance when describing an object over the phone. For the next generation of intelligent robots, computational creativity tools, and online shopping systems to be widely accessible, they need the capability to understand recursive natural language descriptions of objects.

Driven by recent progress in language modeling [11, 35, 3] and generative image modeling [21], there has been rapid progress in the problem of text-conditioned image generation [52, 42, 54, 55, 56]. For instance, methods such as DALL-E [37, 36] can generate photorealistic images from only text descriptions. This success in the 2D domain together with progress in 3D shape representations [31, 28, 30] has led to interest in text-conditioned *3D shape generation* [47, 38, 19]. However, extant methods have several shortcomings. First, these methods are limited to one-step shape generation and lack the ability to recursively modify or improve generated shapes [12]. Second, unlike in 2D images, there are no readily available large datasets of 3D shape–text pairs. Existing datasets are limited in size due to challenges in manually annotating 3D data and do not support recursive generation [5, 2]. Finally, current methods cannot capture local details that are commonly used in language descriptions.

In this paper, we address the above limitations and present a method for **recursive text-conditioned generation of 3D shapes**. Our method, **ShapeCrafter**, consists of a transformer-based [46] neural

Figure 1: **ShapeCrafter** is a method for recursive text-conditioned 3D shape generation. Given an initial phrase (`A chair`), it generates a shape distribution (4 samples shown in the leftmost column). As more phrases are added, the initial shape is refined (2 samples shown). We can handle long phrase sequences while continuously evolving an initial shape (shape editing for a fixed random seed). Our method also shows extrapolation capabilities (`legs are armrests`, bottom right).

network architecture that takes an initial text phrase (via BERT [11]) and generates a distribution of latent features over a 3D grid that can be sampled to obtain shapes consistent with the input. Our goal is to capture recursive phrase sequences common in language descriptions (see Figure 1)—as more informative words/phrases are added, our method produces more relevant shape distributions. To achieve this, we design a recursive network architecture that takes the latest phrase input in a sequence, and incorporates it with latent grid features from the previous step to generate refined shapes. The shape distributions produced by our method evolve gradually as more phrases are added, thus enabling new applications in human–machine collaboration for creative design.

To address the limited size of existing datasets, we introduce **Text2Shape++**, a dataset that contains **369K** *many-to-many* mappings of variable-length phrase sequences that map to the same shape. This dataset is derived from Text2Shape [5] that has 75K one-to-one text-shape pairs but no recursive phrase sequences. We introduce a method to transform (see Section 4.1) the Text2Shape dataset into variable-length phrase resulting in a significantly larger dataset. Finally, to learn high-quality shapes, we adopt vector-quantized deep implicit functions (P-VQ-VAE) [53, 30] to better represent local details and generate shape distributions rather than single shapes.

Experiments and results produced by ShapeCrafter demonstrate that we can generate and evolve high-quality 3D shape distributions that are consistent with the input text. As additional phrases are added to the sequence, the shapes gradually and continuously evolve while retaining shape details generated in the previous steps thus enabling **shape editing** functionality (see Figure 1). Our model can handle long phrase sequences that other methods cannot. Surprisingly, our model demonstrates the capability to extrapolate to novel inputs (*e.g.,* chair legs that look like armrests, see Figure 1 bottom right) unseen during training. Quantitative results show that our shape reconstruction quality is comparable to the state of the art, while our recursive shape generation and editing capabilities are state of the art. To sum up, our contributions are:

- **ShapeCrafter**, a neural network architecture that enables recursive text-conditioned generation of 3D shapes that continuously evolve as phrases are added.
- **Text2Shape++**, a new large dataset of **369K shape–text pairs** that can be used for recursive shape generation tasks.
- A model that captures local shape details corresponding to text descriptions and enables shape editing and extrapolation to novel text descriptions.

2 Related Work

In this brief review, we limit our discussion to work on 3D shape representations, 3D shape generation and manipulation. Text-conditioned 2D image generation [23, 37, 36] is outside of the scope of this review, please see [13, 16] for details.

3D Shape Representation and Generation: Existing work in 3D shape generation can be categorized based on their underlying representation of choice. Major choices include meshes [15, 51, 48, 14, 10], voxels [8, 25, 20, 5], point clouds [1, 24, 33, 49, 34, 39], neural fields/scene representation networks [29, 40], or deep implicit fields [31, 28, 6]. Meshes and point clouds are useful for simple shapes but struggle with complex details and topology resulting in lower quality results. Voxel grids take up a large amount of memory limiting details. Implicit fields including SDFs are more popular because they can capture fine-grained details, handle arbitrary topologies, and produce watertight meshes. Since many neural implicits encode the whole shape into a single latent code, they often suffer from "posterior collapse", where the latent space is not fully used, and latents get ignored by the decoder [37, 45]. To combat this, the feature volume can be divided into smaller cells [41, 32]. More recently, vector quantized deep implicit functions (VQ-DIF) [53, 30] have gained popularity. VQ-DIFs encode shape as a series of discrete 2-tuples representing feature of the shape, and their position and content. This allows separation of specific features and effective re-combination in a transformer-based architecture. We adopt this approach in our work due to its high generation quality.

Text-Conditioned 3D Shape Generation: Text-conditioned 3D shape synthesis is significantly more challenging than text-conditioned image synthesis due to a lack of large text-shape datasets. Therefore, current methods use large pre-trained image–language embeddings like CLIP [35]. CLIP-conditional shape generation methods [47, 38, 19] associate encoded CLIP text features and CLIP image features obtained by rendering 3D shapes. Alternatively, sequence-to-sequence models [5, 2, 30, 27] are used to match texts and shapes. Unlike our method, none of the above methods can support long phrase sequences, or recursive shape generation that controls local shape details.

Datasets: Training text-conditioned 3D shape generation models requires supervision in the form of text-shape pairs. Unlike in 2D, obtaining this labeled data is harder in 3D due to the complexity of creating text descriptions for large datasets like ShapeNet [4]. Nonetheless, Text2Shape [5] gathered such data for two object classes (chairs, tables) in ShapeNet. In total, they provide 75K pairs (30K for chairs, 40K for tables) which is still insufficient for training models that capture local detail. ShapeGlot [2] provides a (2D) shape discrimination dataset with 94K rendered triplets of which one is closest to a text description. None of these datasets support recursive shape learning. In our work, we provide a method to transform the Text2Shape dataset into a larger dataset of phrase sequence–shape pairs that supports recursive shape generation.

3 Background

We first introduce the fundamental technical details and justification for our choice of shape representation, text feature extraction, and auto-regressive shape generation.

Shape Representation: Neural implicit representations [31] have been shown to capture shapes of arbitrary topology using a global latent code. However, a single global latent code can result in poor local details, so we use grid-based representations [32] which also offer local shape details. In this paper, we use a vector-quantized feature embedding space which represents each shape as a probability distribution of possible tokens in a fix-sized code book.

For each shape X, a shape encoder $E_\phi(\cdot)$ encodes its T-SDF into a low dimensional 3D grid feature $E \in g^3 \times D$, where g is the resolution of the 3D grid, and D is the dimension of the 3D grid features. We define a discrete latent space which has K embedding vectors, where each of the vector has dimension D. For shape feature e_i at grid position i, a vector quantization operation $VQ(\cdot)$ is used to look up its the nearest neighbor e'_i in the discrete latent space. The feature put into the shape decoder $D_\phi(\cdot)$ is the 3D discrete latent feature grid $E' \in g^3 \times D$, with discrete features e'_i at grid locations i. Therefore, we have:

$$E = E_\phi(X), E' = VQ(E), X' = D_\phi(E'), \tag{1}$$

where X' is the reconstructed shape, and ϕ is the set of learnable parameters of the decoder. As a result, a shape X can be represented as a 3D latent feature index grid $Q \in g^3$, where the number q_i at each grid location corresponds to a discrete shape feature e'_i. To learn this, we use P-VQ-VAE [30], which extracts discrete latent features from a volumetric Truncated-Signed Distance Field (T-SDF). In our method, we empirically set $K = 512$, $D = 256$, and the 3D shape grid resolution is $g = 8$.

Text Feature Extraction: To extract semantic meaning from text input, we use BERT [11]. BERT is a bidirectional transformer pretrained on a large web-scale dataset that can be fine-tuned for different tasks. For each input test I, we use the first token in last layer of the $\mathbf{BERT_{BASE}}$ model as the text

feature embedding $B \in \mathbb{R}^{768}$. In order to have all grids in the 3D feature grid to gather some semantic information from text input, we use a multilayer perceptron $\Phi(\cdot)$ to project the text embedding feature into the same resolution as the 3D feature grid. We have:

$$C = \Phi(B), \Phi : \mathbb{R}^{786} \to \mathbb{R}^{g^3}, \tag{2}$$

where C denotes the projected text features.

Autoregressive Generation: Both the 3D latent feature index grid Q extracted using P-VQ-VAE and the projected text feature C extracted by BERT are in the shape of a 3D grid. Features within the grid are correlated with each other. Our goal is to build a generation model that learns the joint-distribution of the grid, while making the code in each grid dependent on previous phrase inputs.

To achieve this, we use a conditional autoregressive model for shape generation. Given grid-wise conditional feature $Z \in g^3 \times H$, where H is the dimension of the conditional feature (we set $H = 512$), the joint distribution of the 3D latent feature index grid Q and the conditional feature Z is formulated as $p(Q|Z) = \prod_{i=1}^{g^3} p(q_i|q_{<i}, Z)$. We use the simplified assumption [30], that this joint distribution is a product of the shape prior, coupled with independent conditional terms Z:

$$p(q_i|q_{<i}, Z) = \prod_{i=1}^{g^3} p_\theta(q_i|q_{<i}) \cdot p_\psi(q_i|Z). \tag{3}$$

4 Recursive Text-conditioned 3D Shape Generation

We now describe the details of how we achieve recursive text-conditioned shape generation. We first introduce our Text2Shape++ dataset in Section 4.1 since since the dataset design influences our technical approach. Next, we introduce the "shape set" feature representation we use for recursive generation in Section 4.2. We then introduce the inference procedure of our method in Section 4.3. Finally, we introduce our training strategy that enables recursive generation in Section 4.4.

4.1 Text2Shape++: Dataset to Support Recursive Shape Generation

Our goal is to generate 3D shapes recursively from phrase input enabling the gradual evolution of generated 3D shapes. Unfortunately, no existing dataset can support this problem since text–shape pairs are limited to single phrases. Therefore, we construct a new dataset, Text2Shape++, building upon the Text2Shape [5] dataset, which has text–shape pairs of chair and table categories from ShapeNet [4]. Text2Shape++ contains **369K text–shape pairs**, which to our knowlege is the largest such dataset. Each text prompt in the dataset is represented as a phrase sequence, and each phrase sequence corresponds to one or more shapes. On average, each phrase sequence corresponds to 16 phrases for chairs, and 25 phrases for tables.

Constructing Text2Shape++: Given each text prompt in the Text2Shape [5] dataset, we first split the text into sentences using a sentence splitter [18]. For each sentence, we use a constituency parser [22] to parse the sentence in to a constituency tree. There could be many phrase types in a constituency tree—we only consider 18 of them as valid phrase types that contain descriptions such as verbs, nouns, and adjectives. Meanwhile, we also mark the phrases that only contain stop-words (*e.g.,* it, there, . . .) as invalid. During the parsing procedure, if any of the children of current node is not a valid phrase, we stop parsing. Thus, a sentence is parsed into a constituency tree, where all the leaf nodes are valid phrases that contain useful information. For a parsed tree Y, we use depth-first search to get all of the leaf nodes in the tree $I = [i_1, i_2, ..., i_T]$, where T denotes the number of leaves. We use I_t to denote the concatenation of the 1^{st} to the t^{th} phrases, and we refer I_t as a phrase sequence.

To get shapes corresponding to phrase sequences, we calculate the similarity score of all the phrase sequences in our dataset with RoBERTa [26]. We consider two phrase sequences as *similar* if their similarity score is higher than certain threshold (we empirically chose 0.94). For each phrase sequence, its corresponded shapes include the original Text2Shape dataset pair, as well as shapes paired with its *similar* phrase sequences. Therefore, Text2Shape++ is a **many-to-many** text–shape correspondence dataset.

Figure 2: (Top) We take input text phrases and extract semantic features using BERT. These features are projected to a feature grid C_t which is concatenated with the latent feature code distribution Z_{t-1} from the previous time step. Residual blocks $\Psi(\cdot)$ output the feature grid distribution Z_t for the current time step. (2) During step t of inference, we combine C_t and Z_{t-1} to obtain Z_t which is sampled to produce 3D shapes.

4.2 Shape Set Feature Representation.

Since any phrase sequences in Text2Shape++ can have many shapes (*i.e.*, *shape set*) as their ground truth, we represent the shape set as a probability distribution of the discrete latent space rather a set of deterministic discrete latent feature codes. Recall that we use P-VQ-VAE [30] (see Section 3) to represent a 3D shape X as a 3D discrete latent feature index grid $Q \in g^3$. The discrete latent feature space has K latent features. Therefore, for a shape set that corresponds to a phrase sequence, it can be represented as a probability distribution of latent feature codes $Z \in g^3 \times K$.

Formally, each phrase sequence is provided with a shape set $\{X^j\}_{j=1}^M$ and their corresponded similarity scores $\{w^j\}_{j=1}^M$, where M indicates the number of shapes in the shape set. Given the shape X_j represented as a 3D discrete latent feature index grid Q_j, its probability distribution of latent feature codes Z is deterministic, which can be represented as $Z_{ik} = \mathbb{I}\{j = Q_i\}$, where i denotes grid at position i, and k denotes the k^{th} dimension. Given a shape set $\{X^j\}_{j=1}^M$, where each shape X_j is represented by a 3D discrete latent feature index grid Q_j, we represent the shape set as a probability distribution by simply weighting the probability of the all the shapes with their similarity score:

$$Z^{set} = \frac{\sum_{j=1}^M w^j * Z^j}{\sum_{j=1}^M w^j},\tag{4}$$

where Z^{set} is the shape representation of the shape set.

4.3 Recursive Shape Generation

We now describe the recursive inference procedure of ShapeCrafter which is also illustrated in Figure 2. ShapeCrafter uses probability distribution of latent feature codes Z (Section 4.2) as its shape/shape set representation. To achieve text-conditioning, the phrase input is used to change the probability distribution of the latent feature code Z. As more phrases are added, the probabilities become narrower resulting in more deterministic shapes.

At time step t, ShapeCrafter takes two inputs: text input i_t from the current phrase, and the probability distribution of the latent feature code from the previous time step Z_{t-1}. At the first time step, we set Z_0 to be $\frac{1}{K}$, where $K = 512$ for each cell. The $\mathbf{BERT}_{BASE}$ model (Section 3) extracts text features B_t and the multi-layer perception $\Phi(\cdot)$ project the feature to C, which has the same resolution as the 3D grid features. The text feature C is then concatenated with shape set feature Z_{t-1} along the

channel dimension. Several residual blocks $\Psi(\cdot)$ are used to infer the probability distribution of the latent feature code at time t, which could be formulated as:

$$Z_t = \Psi([Z_{t-1}, C]), \tag{5}$$

where $[\cdot]$ stands for concatenation operation. Please see the supplementary document for more details.

The inferred probability distribution Z_t includes information from both text and shape at the previous step. However, the features at each grid are only weakly correlated. Therefore, it is fed to the autoregressive generation model (Section 3) which generates the 3D discrete latent feature index grid Q. The VAE decoder D_ϕ introduced in Section 3 then decodes the index grid Q to a shape represented by a T-SDF.

At each recursive generation step, we want the generation model prioritize the distinct shape features from the current phrase at t. Therefore, we sort the sequence of the inputs at the autoregressive step by the difference of the probability distribution at two time steps. We then use a random transformer [43] to generate the index grid sequentially, which could be formulated as:

$$p_t(q_{b_i}|q_{b_{<i}}, Z) = \prod_{i=1}^{N} p_{t\theta}(q_{b_i}|q_{b_{<i}}) \cdot p_{t\Psi}(q_{b_i}|Z), \{b_i\}_{i=1}^{N} = argsort(\|Z_t - Z_{t-1}\|_2^2), \tag{6}$$

where $N = g^3$ is the number of grids, and $argsort(\cdot)$ is descending sort operation.

4.4 Training

Five components are involved in training ShapeCrafter: (1) P-VQ-VAE model for shape representation; (2) Auto-regressive model for shape generation; (3) Fine-tuning $\textbf{BERT}_{BASE}$ model for text feature extraction; (4) Text feature projection model Φ; and (5) Residuals blocks Ψ to extract the final distribution. We first follow the training strategy of AutoSDF [30] to train the P-VQ-VAE model and the autoregressive model. Then, we jointly train the $\textbf{BERT}_{BASE}$ model, the projection model , and the residual blocks. Text2Shape++ provides us the dataset to train these three components since it provides phrase sequences $I = [i_1, i_2, ..., i_T]$ and the corresponding shape sets $\{X_t^j\}_{j=1}^{M}$. At time step t, we feed in phrase i_t and the shape set probability distribution feature Z_{t-1} corresponding to I_{t-1}. Note that Z_{t-1} is taken from Text2Shape++. We receive as output the predicted shape set probability distribution feature $\hat{Z}_t$. Our loss function consists of reconstruction loss, vector quantization objective, and commitment loss as proposed by van den Oord et al. [44] For the reconstruction loss, we use cross-entropy loss with Z_t as the label. For the vector quantization objective, we randomly sample from the the distribution Z_t and acquire latent feature index Q_t as the target.

5 Experiments

In this section, we provide both quantitative and qualitative evaluation of ShapeCrafter on recursive text-conditioned shape generation task. Specifically, we focus on: (1) quantitative evaluation and comparison with AutoSDF [30] to assess the ability of ShapeCrafter to generate high-quality shapes that correspond to text input, (2) quantitative evaluation of the ability to handle long phrase sequences, (3) ablations to evaluate recursive generation in preserving shape details from previous steps. For consistency, we limit our experiments to the chair category, but we show results on the table category in the supplementary document.

Dataset: All our experiments use our Text2Shape++ dataset for training (20% held out for validation). For comparisons, we use full sentences from the Text2Shape datasets for validation.

Metrics: We use the following three metrics to evaluate text-shape correspondence and shape quality.

CLIP-Similarity (CLIP-S). This metric compares the text–shape correspondence quality among all the methods as measured by CLIP [35]. We first rendered the generated mesh into images from 20 different views. We then use the pretrained CLIP [35] text encoder and image encoder to extract the text feature and images features, and calculate the similarity between the text feature and all of the shape features. We use the maximum of the similarity score from the 20 view images as CLIP-Similarity. To normalize the clip-similarity score, we calculated the cosine similarity between rendered pictures of the Stanford bunny and the word "teapot", and used this score as a lower limit,

as it indicates the image and text are not at all alike. Then, we took the max cosine similarity score between pictures of the Stanford bunny and the word "bunny", and used it as the upper limit. Clip-similarity score of our tested results are obtained by normalizing cosine similarities between the upper and lower limits.

ShapeGlot-Confidence (ShapeGlot-C). The ShapeGlot-Confidence metric compares the text-shape correspondence between methods. A neural evaluator is trained as proposed in [2] to distinguish the target shape from distractors given the specified text. The trained neural evaluator achieves a 83% accuracy on this binary classification task with the Shapeglot[2] dataset. ShapeGlot-Confidence tells that, among the shapes generated by all of the methods, which one corresponded to the text the most. We use this as a proxy for a perceptual study.

FID. We use the Frechet Inception Distance (**FID**) metric [17] to evaluate the quality of the generated shapes. For shape feature extraction, we use the voxel encoder in [50] and train it on ShapeNet classification task[4].

5.1 Comparisons

We evaluate and compare the performance of ShapeCrafter on text-conditioned shape generation [30]. For this experiment, we use single step generation for AutoSDF using the entire prompt from the Text2Shape [5] test set (since

Table 1: AutoSDF and ShapeCrafter on text conditioned generation.

Metric	CLIP-S $\uparrow$	Shapeglot-C $\uparrow$	FID $\downarrow$
Mittal et al. [30]	48.92	0.46	18.45
ShapeCraft (Ours)	**52.43**	**0.53**	**16.36**

AutoSDF is not designed for recursive generation). Our model take the sentence as input and generate it recursively. Table 1 illustrates the performance of ShapeCrafter and AutoSDF[30] on this task. We outperform AutoSDF on CLIP-Similarity score and a Shapeglot-Confidence score, which means ShapeCrafter is able to generate shapes that are visually similar to the text input. For shape quality evaluation, our model has a lower FID score, indicating that we can capture details better. This experiment also shows that a recursive generation strategy is useful, compared to a single step strategy.

In Figure 3, we also compare the performance between AutoSDF[30] and ShapeCrafter qualitatively.

We visualize the shape generated by phrases from Text2Shape++. Clearly, comparing with AutoSDF, the generated results of ShapeCrafter is more sequentially consistent.

5.2 Phrase Sequence Length

Figure 3: Qualitative comparison with AutoSDF [30].

We are also interested in the ability of ShapeCrafter on generating text inputs of various lengths. We divide the texts inputs into three levels by the number of phrases they contain. All text inputs are categorized into three tiers: texts that contain $1-2$, $2-4$, and more than 4 phrases. Table 2 compares the performance of AutoSDF and ShapeCrafter on text inputs of various lengths. Overall, the results from these three metrics indicate that ShapeCrafter generates shapes that are more consistent with longer text inputs than AutoSDF without compromising generation quality. Specifically, for FID, the shape quality of AutoSDF decreases as the text input grows longer, while the shape quality of

ShapeCrafter remains stable. For CLIP-Similarity, the performance of ShapeCrafter is comparable with AutoSDF for shorter texts, and ShapeCrafter is better than AutoSDF at generating shapes that closely agree with medium-length and long texts. For Shapeglot-Confidence, AutoSDF performs better with shorter/medium-length text inputs, but ShapeCrafter performs better with longer inputs.

Table 2: AutoSDF and ShapeCrafter on recursive text-conditioned Generation.

# Phrases	[1, 2]			(2, 4]			(4, +∞)		
	CLIP-S ↑	Shapeglot-C ↑	FID ↓	CLIP-S ↑	Shapeglot-C ↑	FID ↓	CLIP-S ↑	Shapeglot-C ↑	FID ↓
Mittal et al.	**45.72**	0.44	18.13	45.27	0.42	20.33	55.77	0.44	22.47
ShapeCraft	**45.72**	**0.53**	**17.40**	**53.38**	**0.58**	**16.44**	**58.18**	**0.53**	**16.89**

5.3 Ablations / Recursive Text-conditioned Shape Generation

We also evaluate the performance of ShapeCrafter on recursive text-conditioned shape generation task qualitatively. Fig. 3 shows the shape generated at each time step. Shapes that rendered in the same color are generated from the same phrase sequences. This figure provides examples that demonstrate ShapeCrafter has the ability to generate shapes that are of high-quality. See row 2 instance 1 to 3, it shows The generation continuous in time-sequence. Instances 4 and 4 in row 2 shows that the model is able to generate from long phrase sequences. The model is able to change the overall structure of the shape, including part addition and removal, part replacement, and shape type changes. It's able to change the local details of the shape.

Our model is trained conditionally and inference recursively. To prove the effectiveness of the conditional training, we design a baseline without the conditional training part, and only generated shape features recursively with AutoSDF[30]. Specifically, at time step t, we multiply the probability generated from the text input, with the probability generated from the ran-

Table 3: Ablation studies on the effectiveness on: (1) conditional training and (2) the re-ordered random transformer sequence.

Metric	CLIP-Similarity ↑	FID ↓
w/o condition	49.53	20.22
w/o reorder	42.47	16.67
Ours	52.43	16.36

dom transformer at time step $t - 1$, and use the production as the conditional distribution of the random transformer at time step t. We refer this baseline as *w/o condition*. To prove the effectiveness of reordering the input sequence in the random transformer, we design another baseline that putting feature into the transformer in a random sequence. We refer this baseline as *w/o reorder*. The performance of these baselines are illustrated at Table. 3. The performance drops without these components, which proves the effectiveness of the design choices.

6 Conclusion

In this paper, we presented ShapeCrafter, a method for recursive text-conditioned 3D shape generation. Different from previous single-step methods, our focus is on generating 3D shape distributions that can be gradually evolved to capture semantics described in phrase sequences. We also presented a method to transform an existing dataset to support recursive shape generation tasks to produce a larger dataset called Text2Shape++ with 369K shape–text pairs. Results show that our method produces high-quality shapes while handling long phrase sequences, support shape editing, and extrapolates to shapes unseen during training.

Limitations: Our method has several notable limitations. First, ShapeCrafter is limited to shape generation only and cannot handle appearance attributes common in language descriptions. Limitations of the Text2Shape dataset extend to our method—we only support two shape categories: tables and chairs. Empirically, we observe that our method demonstrates elements of "part assembly", but cannot handle large-scale deformations. We believe that we have taken an step in the direction towards addressing the above challenges. From a **societal impact** perspective, more care is needed to ensure that our dataset represents diverse shape instances to avoid bias.

Figure 4: Qualitative results produced by ShapeCrafter. Each unique color shows results generated recursively from our model using the same seed to sample the shape distribution. Our method demonstrates consistent and gradual evolution of shape enabling us to simulate shape editing.

References

[1] Panos Achlioptas, Olga Diamanti, Ioannis Mitliagkas, and Leonidas J Guibas. Learning representations and generative models for 3d point clouds. *arXiv preprint arXiv:1707.02392*, 2017.

[2] Panos Achlioptas, Judy Fan, X.D. Robert Hawkins, D. Noah Goodman, and J. Leonidas Guibas. ShapeGlot: Learning language for shape differentiation. *CoRR*, abs/1905.02925, 2019.

[3] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[4] Angel X. Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. ShapeNet: An Information-Rich 3D Model Repository. Technical Report arXiv:1512.03012 [cs.GR], Stanford University — Princeton University — Toyota Technological Institute at Chicago, 2015.

[5] Kevin Chen, Christopher B Choy, Manolis Savva, Angel X Chang, Thomas Funkhouser, and Silvio Savarese. Text2shape: Generating shapes from natural language by learning joint embeddings. In *Asian conference on computer vision*, pages 100–116. Springer, 2018.

[6] Zhiqin Chen and Hao Zhang. Learning implicit fields for generative shape modeling. *Proceedings of IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[7] Noam Chomsky. Minimal recursion: exploring the prospects. In *Recursion: Complexity in cognition*, pages 1–15. Springer, 2014.

[8] Christopher B Choy, Danfei Xu, JunYoung Gwak, Kevin Chen, and Silvio Savarese. 3d-r2n2: A unified approach for single and multi-view 3d object reconstruction. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2016.

[9] Michael C Corballis. From hand to mouth. In *From Hand to Mouth*. Princeton University Press, 2020.

[10] Angela Dai and Matthias Nießner. Scan2mesh: From unstructured range scans to 3d meshes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5574–5583, 2019.

[11] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[12] Alaaeldin El-Nouby, Shikhar Sharma, Hannes Schulz, Devon Hjelm, Layla El Asri, Samira Ebrahimi Kahou, Yoshua Bengio, and Graham W Taylor. Keep drawing it: Iterative language-based image generation and editing. *arXiv preprint arXiv:1811.09845*, 2, 2018.

[13] Stanislav Frolov, Tobias Hinz, Federico Raue, Jörn Hees, and Andreas Dengel. Adversarial text-to-image synthesis: A review. *Neural Networks*, 144:187–209, 2021.

[14] Georgia Gkioxari, Jitendra Malik, and Justin Johnson. Mesh r-cnn. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9785–9795, 2019.

[15] Rana Hanocka, Amir Hertz, Noa Fish, Raja Giryes, Shachar Fleishman, and Daniel Cohen-Or. Meshcnn: a network with an edge. *ACM Transactions on Graphics (TOG)*, 38(4):1–12, 2019.

[16] Xiaodong He and Li Deng. Deep learning for image-to-text generation: A technical overview. *IEEE Signal Processing Magazine*, 34(6):109–116, 2017.

[17] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

[18] Matthew Honnibal and Mark Johnson. An improved non-monotonic transition system for dependency parsing. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 1373–1378, Lisbon, Portugal, September 2015. Association for Computational Linguistics.

[19] Ajay Jain, Ben Mildenhall, Jonathan T Barron, Pieter Abbeel, and Ben Poole. Zero-shot text-guided object generation with dream fields. *arXiv preprint arXiv:2112.01455*, 2021.

[20] Danilo Jimenez Rezende, SM Eslami, Shakir Mohamed, Peter Battaglia, Max Jaderberg, and Nicolas Heess. Unsupervised learning of 3d structure from images. *Advances in neural information processing systems*, 29, 2016.

[21] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4401–4410, 2019.

[22] Nikita Kitaev and Dan Klein. Constituency parsing with a self-attentive encoder. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2676–2686, Melbourne, Australia, July 2018. Association for Computational Linguistics.

[23] Bowen Li, Xiaojuan Qi, Thomas Lukasiewicz, and Philip H. S. Torr. Controllable text-to-image generation. *arXiv preprint arXiv:1909.07083*, 2019.

[24] Chun-Liang Li, Manzil Zaheer, Yang Zhang, Barnabas Poczos, and Ruslan Salakhutdinov. Point cloud gan. *arXiv preprint arXiv:1810.05795*, 2018.

[25] Fayao Liu, Chunhua Shen, and Guosheng Lin. Deep convolutional neural fields for depth estimation from a single image. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5162–5170, 2015.

[26] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[27] Zhengzhe Liu, Yi Wang, Xiaojuan Qi, and Chi-Wing Fu. Towards implicit text-guided 3d shape generation. *arXiv preprint arXiv:2203.14622*, 2022.

[28] Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[29] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *European conference on computer vision*, pages 405–421. Springer, 2020.

[30] Paritosh Mittal, Yen-Chi Cheng, Maneesh Singh, and Shubham Tulsiani. Autosdf: Shape priors for 3d completion, reconstruction and generation. *arXiv preprint arXiv:2203.09516*, 2022.

[31] Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[32] Songyou Peng, Michael Niemeyer, Lars Mescheder, Marc Pollefeys, and Andreas Geiger. Convolutional occupancy networks. In *European Conference on Computer Vision*, pages 523–540. Springer, 2020.

[33] Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 652–660, 2017.

[34] Charles Ruizhongtai Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017.

[35] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

[36] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

[37] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pages 8821–8831. PMLR, 2021.

[38] Aditya Sanghi, Hang Chu, Joseph G Lambourne, Ye Wang, Chin-Yi Cheng, and Marco Fumero. Clip-forge: Towards zero-shot text-to-shape generation. *arXiv preprint arXiv:2110.02624*, 2021.

[39] Matan Shoef, Sharon Fogel, and Daniel Cohen-Or. Pointwise: An unsupervised point-wise feature learning network. *arXiv preprint arXiv:1901.04544*, 2019.

[40] Vincent Sitzmann, Michael Zollhöfer, and Gordon Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. *Advances in Neural Information Processing Systems*, 32, 2019.

[41] Towaki Takikawa, Joey Litalien, Kangxue Yin, Karsten Kreis, Charles Loop, Derek Nowrouzezahrai, Alec Jacobson, Morgan McGuire, and Sanja Fidler. Neural geometric level of detail: Real-time rendering with implicit 3d shapes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11358–11367, 2021.

[42] Ming Tao, Hao Tang, Songsong Wu, Nicu Sebe, Xiao-Yuan Jing, Fei Wu, and Bingkun Bao. Df-gan: Deep fusion generative adversarial networks for text-to-image synthesis. *arXiv preprint arXiv:2008.05865*, 2020.

[43] Shubham Tulsiani and Abhinav Gupta. Pixeltransformer: Sample conditioned signal generation. *arXiv preprint arXiv:2103.15813*, 2021.

[44] Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

[45] Aaron van den Oord, Oriol Vinyals, and koray kavukcuoglu. Neural discrete representation learning. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[46] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[47] Can Wang, Menglei Chai, Mingming He, Dongdong Chen, and Jing Liao. Clip-nerf: Text-and-image driven manipulation of neural radiance fields. *arXiv preprint arXiv:2112.05139*, 2021.

[48] Nanyang Wang, Yinda Zhang, Zhuwen Li, Yanwei Fu, Wei Liu, and Yu-Gang Jiang. Pixel2mesh: Generating 3d mesh models from single rgb images. In *Proceedings of the European conference on computer vision (ECCV)*, pages 52–67, 2018.

[49] Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *Acm Transactions On Graphics (tog)*, 38(5):1–12, 2019.

[50] Udaranga Wickramasinghe, Edoardo Remelli, Graham Knott, and Pascal Fua. Voxel2mesh: 3d mesh model generation from volumetric data. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 299–308. Springer, 2020.

[51] Ruben Wiersma, Elmar Eisemann, and Klaus Hildebrandt. Cnns on surfaces using rotation-equivariant features. *ACM Transactions on Graphics (TOG)*, 39(4):92–1, 2020.

[52] Tao Xu, Pengchuan Zhang, Qiuyuan Huang, Han Zhang, Zhe Gan, Xiaolei Huang, and Xiaodong He. Attngan: Fine-grained text to image generation with attentional generative adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1316–1324, 2018.

[53] Xingguang Yan, Liqiang Lin, Niloy J Mitra, Dani Lischinski, Danny Cohen-Or, and Hui Huang. Shapeformer: Transformer-based shape completion via sparse representation. *arXiv preprint arXiv:2201.10326*, 2022.

[54] Hui Ye, Xiulong Yang, Martin Takac, Rajshekhar Sunderraman, and Shihao Ji. Improving text-to-image synthesis using contrastive learning. *arXiv preprint arXiv:2107.02423*, 2021.

[55] Han Zhang, Jing Yu Koh, Jason Baldridge, Honglak Lee, and Yinfei Yang. Cross-modal contrastive learning for text-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 833–842, 2021.

[56] Minfeng Zhu, Pingbo Pan, Wei Chen, and Yi Yang. Dm-gan: Dynamic memory generative adversarial networks for text-to-image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5802–5810, 2019.