Computing Circuits Optimization via Model-Based Circuit Genetic Evolution

Zhihai Wang[1][*], **Jie Wang**[1][†], **Xilin Xia**[1], **Dongsheng Zuo**[3], **Lei Chen**[2], **Yuzhe Ma**[3], **JianYe Hao**[2,4], **Mingxuan Yuan**[2], **Feng Wu**[1]

[1]MoE Key Laboratory of Brain-inspired Intelligent Perception and Cognition,
University of Science and Technology of China
[2] Noah's Ark Lab, Huawei Technologies
[3] Microelectronics Thrust, Hong Kong University of Science and Technology (Guangzhou)
[4] College of Intelligence and Computing, Tianjin University

Abstract

Optimizing computing circuits such as multipliers and adders is a fundamental challenge in modern integrated circuit design. Recent efforts propose formulating this optimization problem as a reinforcement learning (RL) proxy task, offering a promising approach to search high-speed and area-efficient circuit design solutions. However, we show that the RL-based formulation (proxy task) converges to a *local optimal* design solution (original task) due to the deceptive reward signals and incrementally localized actions in the RL-based formulation. To address this challenge, we propose a novel **m**odel-based circ**u**it gene**t**ic **e**volution (MUTE) framework, which reformulates the problem as a genetic evolution process by proposing a grid-based genetic representation of design solutions. This novel formulation avoids misleading rewards by evaluating and improving generated solutions using the true objective value rather than proxy rewards. To promote globally diverse exploration, MUTE proposes a *multi-granularity* genetic crossover operator that recombines design substructures at varying column ranges between two grid-based genetic solutions. To the best of our knowledge, MUTE is *the first* to reformulate the problem as a circuit genetic evolution process, which enables effectively searching for global optimal design solutions. We evaluate MUTE on several fundamental computing circuits, including multipliers, adders, and multiply-accumulate circuits. Experiments on these circuits demonstrate that MUTE significantly Pareto-dominates state-of-the-art approaches in terms of both area and delay. Moreover, experiments demonstrate that circuits designed by MUTE well generalize to large-scale computation-intensive circuits as well.

1 Introduction

Computing circuits such as multipliers and adders serve as the fundamental building blocks in numerous real-world circuits, particularly in central processing units, graphics processing units, and artificial intelligence (AI) chips (Holdsworth, 1987; Das et al., 2019; Sze et al., 2020). The multiplication and addition operations stand out as the most fundamental and frequently utilized arithmetic operations across various computation-intensive applications, including deep neural networks (DNNs), digital signal processors, and microprocessors (Hashemian, 2002; Elguibaly, 2000; Zuo et al., 2023). Notably, in many popular DNN architectures such as ResNet (He et al., 2016), ViT (Dosovitskiy et al., 2021), Transformer (Vaswani et al., 2017), and BERT (Devlin et al., 2019), the multiplication and addition operations constitute over 99% of all operations. Therefore, the design of high-speed and area-efficient computing circuits plays a pivotal role in enhancing the performance of computation-intensive applications, especially in AI chips.

However, computing circuit optimization is a challenging combinatorial optimization problem due to its $\mathcal{NP}$-hard nature (Hillar & Lim, 2013; Song et al., 2022). On one hand, the combinatorial

---

[*]This work was done when Zhihai Wang was an intern at Huawei Noah's Ark Lab.
[†]Corresponding author. Email: jiewangx@ustc.edu.cn.

design space grows exponentially with the input bit widths of the computing circuits (Roy et al., 2021). On the other hand, evaluating the post-synthesis performance of a circuit design (i.e., design performance) with circuit synthesis tools is highly time-consuming, leading to high sampling costs. Therefore, searching high-speed and area-efficient circuits in the vast design space using limited samples emerges as a significant challenge.

To search high-speed and area-efficient circuits, recent efforts (Roy et al., 2021; Zuo et al., 2023; Song et al., 2022) propose formulating the computing circuits optimization problem as a reinforcement learning (RL) proxy task, offering a promising avenue for optimizing circuit designs using limited samples. Specifically, they start from an initial design solution, learn policies to incrementally modify the local design structure, and utilize design performance gains between two consecutive designs as reward signals. Intuitively, the manually designed rewards can guide RL agents to explore directions that progressively improve design performance at each step.

However, we show that the RL-based formulation (proxy task) converges to a *local optimal* design solution (original task) due to the deceptive reward signals and incrementally localized actions. First, the reward signals based on performance gains between two consecutive designs are deceptive, as maximizing the cumulative discounted rewards misaligns with the true objective. More specifically, the proxy RL formulation indeed optimizes the cumulative discounted performance of all encountered design solutions across a trajectory, while the true objective is to find the single best-performing designs. Second, the actions based on the incrementally local modifications of design structure suffer from poor exploration capability, and thus struggle to escape local optima.

To address these challenges, we propose a novel **m**odel-based circ**u**it gene**t**ic **e**volution (MUTE) framework, which proposes a grid-based genetic representation of solutions and reformulates the problem as a circuit genetic evolution process. The evolution formulation is an iterative process between circuit genetic variation and model-based selection, where each iteration evaluates and improves solutions using the true objective value, thus gradually converging toward the best-performing solution (i.e., the original task). To promote globally diverse exploration for escaping local optima, MUTE proposes a multi-granularity crossover operator that recombines design substructures at varying column ranges between two grid-based genetic solutions. Moreover, to tackle the problem of high sampling costs, MUTE introduces a model-based selection method, which learns a model for rapid evaluation of a large number of solutions.

We evaluate MUTE on several fundamental computing circuits, including multipliers, adders, and multiply-accumulate circuits. Experiments on these circuits, spanning a wide range of input widths, demonstrate that MUTE discovers state-of-the-art designs that significantly Pareto-dominate those produced by manual design, mathematical optimization, and learning-based approaches, improving the hypervolume by up to 38%. Moreover, we deploy circuits optimized by MUTE and the baselines into large-scale computation-intensive circuits, and experiments show that MUTE significantly outperforms the baselines in terms of both area and delay. Our results highlight the superior ability of MUTE to discover high-speed and area-efficient circuits for real-world important computing applications, especially for high-performance AI chips.

We summarize our major contributions as follows. (1) We show that the RL-based formulation for computing circuits optimization converges to a local optimal design solution, indicating a significant objective gap between the RL-based formulation and the true objective. (2) To the best of our knowledge, our MUTE is *the first* to reformulate the optimization problem as a novel circuit genetic evolution process, which enables effectively searching for the global optimal circuit design solutions. (3) MUTE proposes a multi-granularity genetic crossover operator to promote globally diverse exploration of the design space. (4) Experiments show that MUTE significantly outperforms state-of-the-art approaches in terms of both area and delay.

2 Background

2.1 Computing Circuits Architecture

Most computing circuits such as prefix adders, vector adders, subtracters, multipliers, and multiply-accumulate circuits rely on two fundamental circuit structures, i.e., the Compressor Tree and Prefix Tree (Weste & Harris, 2015; Roy et al., 2021; Zuo et al., 2023; Wang et al., 2024g). Note that the Compressor Tree and Prefix Tree both share similar tree structures that can both be represented by grid-based design solutions. We take a multiplier circuit with four input bits as an example to in-

Figure 1: An illustration of the multiplication process and multiplier architecture.

troduce the Compressor Tree structure as shown in Figure 1. In binary multiplication, two unsigned binary numbers—the multiplicand and the multiplier—are combined to yield their product. Contemporary multiplier designs typically comprise three primary components: a partial product generator (PPG), a Compressor Tree, and a carry propagation adder (CPA). **Initially**, the PPG generates a bit matrix based on the multiplicand and multiplier, with each element representing a partial product. **Subsequently**, the Compressor Tree compresses each column of the bit matrix to one or two bits by concurrently summing up the partial products within each column. **Finally**, the CPA aggregates the resultant bit matrix from the Compressor Tree to derive the final product.

In constructing a Compressor Tree, **a large number of full and half adders are typically employed to execute the summation of generated partial products concurrently**. A full adder, i.e., a 3:2 compressor, accepts three inputs—two single-bit values and a carry-in bit—and produces two outputs: a sum bit and a carry-out bit. A half adder, i.e., a 2:2 compressor, takes two single-bit values as inputs and yields two outputs: a sum bit and a carry-out bit. Notably, when a 3:2 (2:2) compressor is applied to the i-th column, it reduces two (one) bits in column i while increasing one bit in column $(i + 1)$. Thus, a Compressor Tree employs numerous compressors (i.e., full and half adders) across multiple stages to compress the partial products matrix into only two rows in parallel, significantly dominating the final performance of a multiplier circuit. Moreover, modifying the arrangement of 3:2 and 2:2 compressors within a Compressor Tree can result in significantly different tree structure designs, leading to variable design performance.

2.2 RL for Computing Circuits Optimization

As the Compressor Tree and/or Prefix Tree usually dominates the final performance of a computing circuit (Zuo et al., 2023; Xiao et al., 2021), recent efforts have focused on optimizing the tree structure by formulating the optimization problem as a reinforcement learning (RL) proxy task (Zuo et al., 2023; Roy et al., 2021). We take the existing RL-based Compressor Tree optimization method as an example. RL-MUL starts from an initial Compressor Tree design solution, learns policies to sequentially modify the design structure locally, and utilizes design performance gains as reward signals. We specify the state space, action space, and reward function as follows. **(1) State Space** $\mathcal{S}$. RL-MUL formulates each legal design solution as a state, where each state is represented by a grid-based image. **(2) Action Space** $\mathcal{A}$. RL-MUL designs four types of local modifications to a Compressor Tree solution at a certain column. These local modifications include adding a 2:2 compressor, removing a 2:2 compressor, replacing a 3:2 compressor with a 2:2 compressor, and replacing a 2:2 compressor with a 3:2 compressor. The action space is a discrete set composed of $4 \times N_C$ discrete actions, where N_C denotes the number of columns. Each action $i \in [0, 1, \ldots, (4 \times N_C - 1)]$ is represented by executing the j-th modification type at the k-th column, where $j = i \pmod 4$ and $k = \lfloor \frac{i}{4} \rfloor$. **(3) Reward Function** r. RL-MUL uses a circuit synthesis tool to obtain the performance of the designed solution at each step. The reward r_t is defined as the difference between the area (delay) of the design at step $t - 1$ and that at step t. That is, $r(s_t, a_t, s_{t+1}) = f(s_t) - f(s_{t+1})$, where f denotes the design evaluation function. Finally, RL-MUL leverages the deep Q-network algorithm (Mnih et al., 2015) to train Q-networks. We defer details to Appendix D.

3 Limitations of Existing RL Formulation

3.1 Deceptive Reward Signals

Existing methods formulate the optimization problem as an infinite-horizon Markov decision process (MDP) denoted by a tuple $(\mathcal{S}, \mathcal{A}, r, T, \gamma, \mu_0)$, where $\mathcal{S}$ denotes the state space, $\mathcal{A}$ denotes the

action space, $r : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ denotes the reward function, T denotes the deterministic transition function, γ denotes the discount factor, and μ_0 denotes the given initial design solution. Based on the MDP, the return of a deterministic policy π is defined as $R^\pi = \sum_{t=0}^{\infty} \gamma^t r(s_t, a_t, s_{t+1})$, where $s_0 = \mu_0, a_t = \pi(s_t)$, and $s_{t+1} = T(s_t, a_t)$. Note that the reward is defined by the performance gain between the states s_t and s_{t+1}, i.e.,

$$r(s_t, a_t, s_{t+1}) = f(s_t) - f(s_{t+1}). \tag{1}$$

Here $f : \mathcal{S} \to \mathbb{R}$ denotes the underlying evaluation function of design solutions given by circuit synthesis tools. Note that multiple evaluation functions are employed, such as area and delay evaluation functions. For ease of analysis and consistent with previous work (Roy et al., 2021; Zuo et al., 2023), we assume that the evaluation function f is a linear weighted average of these evaluation functions. Intuitively, the manually designed proxy rewards based on performance gains are able to guide RL agents toward directions that progressively improve design performance, as the RL agent receives positive rewards for improving design performance. Thus, a desired question is: *Does the optimal policy in the RL formulation converge to the global optimal design solution?*

To investigate this question, we first theoretically show *the RL-based optimal policy converges to a local optimal design solution*. Then we empirically show that the underlying evaluation function f is highly oscillatory, resulting in the local optimal design solutions found by the optimal policy diverging significantly from the global optimal solution.

Theoretical Analysis We assume that the state space $\mathcal{S}$ is finite. For simplicity, we assume a terminal action for each state that can terminate the episode at this state. We define a state $s \in \mathcal{S}$ as a local optimum of the function f if for all action $a \in \mathcal{A}$ we have $f(T(s, a)) \geq f(s)$.

Theorem 3.1. *The optimal RL policy $\pi^* := \arg\max_\pi R^\pi$ terminates at a state, and the state is a local optimal design solution of the evaluation function f.*

This theorem demonstrates the superior capability of RL methods in achieving local optimal solutions. However, this raises a further question: *Is the converged local optimal point also the global optimum?* Given the lack of detailed information about the optimization objective function f, a rigorous analysis of this problem is currently infeasible. Therefore, we present an intuitive and empirical analysis to demonstrate that *the converged local optimal solution can significantly diverge from the global optimal solution* as follows.

Illustrative Example We revisit the optimization objective in the RL formulation, i.e.,

$$R^\pi = \sum_{t=0}^{\infty} \gamma^t (f(s_t) - f(s_{t+1})) = f(s_0) - \sum_{t=0}^{\infty} \gamma^t (1 - \gamma) f(s_{t+1}). \tag{2}$$

This implies that standard RL methods in the existing formulation aim to minimize the *cumulative discounted performance* of all visited solutions across a trajectory, except the initial state, when the discount factor $\gamma < 1$. This is a practical discount factor setting in standard RL and previous methods (Roy et al., 2021; Zuo et al., 2023). In contrast, the circuit optimization task is a best-case-seeking task, i.e., the final performance is measured by the *single or few best-performing* design solutions found during training. Consequently, the RL-based optimization objective is inconsistent with the original optimization objective, possibly leading to a significant optimization objective gap.

To illustrate the optimization objective gap problem, we provide a motivating example as shown in Figure 2 (Left). Specifically, we illustrate two distinct trajectories in the circuit optimization environment from a given starting solution following two deterministic policies π_1 and π_2. We denote the two trajectories by $(s_0^{\pi_1}, a_0^{\pi_1}, s_1^{\pi_1}, a_1^{\pi_1}, \ldots, s_T^{\pi_1})$ and $(s_0^{\pi_2}, a_0^{\pi_2}, s_1^{\pi_2}, a_1^{\pi_2}, \ldots, s_T^{\pi_2})$, respectively. Each point in Figure 2 (Left) corresponds to the performance of a state across the trajectory. As shown in Figure 2 (Left), the return of the policy π_2 is larger than that of the policy π_1, while the best solution found by π_1

Figure 2: **(Left)** A motivating example of two distinct trajectories with conflicting returns and found best solutions. **(Right)** A practical training curve of the EA method.

Figure 3: An illustration of the MUTE framework with a) Genetic Formulation, b) Population Initialization, c) Circuit Genetic Variation Operators, and d) Model-Based Cascade Ranking.

is better than that found by π_2. This illustrates a significant optimization objective gap between the RL-based formulation and the original true objective.

3.2 Incrementally Localized Actions

Non-smooth Objective Functions We further empirically investigate the properties of the objective function f. As the domain of f is the high-dimensional space $\mathcal{S}$, directly visualizing the landscape of the objective function is challenging. Instead, we sample a large number of diverse state points from the state space to approximate the function's behavior. Specifically, we visualize the training curve produced by a simple evolutionary algorithm (EA) that uses random actions from the RL action space $a \in \mathcal{A}$ to repeatedly perturb the current best solution locally (see Appendix E for details.) As shown in Figure 2 (Right), the sampled function values exhibit significant oscillations, indicating that the underlying objective function is highly oscillatory as well. The major reason for the oscillations of the evaluation function stems from the complex optimization mechanisms employed by circuit synthesis tools. Even minor modifications to the circuit structure can result in substantial performance variations when evaluated by these tools. Consequently, the oscillatory nature of the optimization objective results in numerous local optimal solutions.

Limited Exploration Ability of Localized Actions The oscillatory nature of the objective functions results in numerous local optimal solutions, thus requiring globally diverse exploration of the design space to escape local optima. However, the actions in the existing RL formulation are limited to local modifications of design structure at a certain column, severely constraining the agent's ability to explore diverse or distant regions of the search space. As a result, the search process may become confined to suboptimal regions, limiting the chances of discovering global optima.

4 A Model-Based Circuit Genetic Evolution Framework

We start with an overview of our proposed MUTE in Section 4.1. Next, we outline the formal procedure at the core of MUTE, specifying the circuit genetic evolution formulation and population initialization in Section 4.2, our proposed efficient and effective circuit genetic variation operators in Section 4.3, and model-based cascade ranking for selection in Section 4.4.

4.1 Overview of Our Framework

We provide an illustration of our MUTE in Figure 3. To bridge the gap between the RL-based formulation and the original task, we design a grid-based genetic representation of solutions, and reformulate the computing circuits optimization problem as a circuit genetic evolution process. The evolution formulation is an iterative process between circuit genetic variation and model-based selection, where each iteration evaluates and improves solutions using the true objective value, thus bridging the objective gap. First, we propose a learning-based population initialization method to accelerate the evolution process by leveraging the existing RL methods to generate a population of high-performing design solutions. Then, we propose efficient and effective genetic variation operators to avoid redundant exploration and promote globally diverse exploration. Finally, to further improve sample efficiency, we propose a model-based cascade ranking method for efficient selection from a large number of generated offspring design solutions.

4.2 Genetic Evolution Formulation and Population Initialization

Circuit Genetic Evolution Formulation For computing circuits such as adders and multipliers, we can represent each circuit design solution by a grid of numbers. We take a compressor tree design solution as an example. As the total number of different full and/or half adders at each column implicitly encodes the structure of a compressor tree, it significantly impacts the post-synthesis performance of multipliers (Xiao et al., 2021; Zuo et al., 2023). Specifically, we employ a $2 \times N_C$ grid to represent the compressor tree design solution, where two rows denote the total number of full and half adders across N_C columns, respectively.

To enable circuit genetic evolution, we propose to formulate each element in the grid-based design solution representation as a circuit gene, and thus the grid as a genetic individual. Note that the existing RL-based method can formulate the grid-based design solution as the state representation as well. Thus, the grid-based genetic formulation allows us to seamlessly incorporate learning into our genetic evolution framework, which can significantly improve sample efficiency.

To directly optimize the original circuit design performance, we formulate the fitness function as the underlying design evaluation function f given by circuit synthesis tools. Thus, the optimization objective of our circuit genetic formulation takes the form of $\arg\min_{s \in \mathcal{S}} f(s)$, where $\mathcal{S}$ denotes the set of all possible legal design solutions.

Learning-Based Population Initialization Although the performance of existing RL methods is limited by deceptive reward signals, they can efficiently converge to a local optimal design solution. Thus, to speed up the evolution process, we incorporate the learning method into our population initialization to generate a set of high-performing circuit design solutions. During the learning process, we maintain an *elite pool* of N best-performing design solutions, and progressively update the pool at each training episode. Finally, we use the elite pool as an initial population.

Following previous work (Song et al., 2022; Zuo et al., 2023; Wang et al., 2024g), we use a scalarized version of the Deep Q-network (DQN) algorithm (Mnih et al., 2015) to learn solution modification policies. We maintain a progressively updated elite pool, and each episode starts the environment with a design solution s_0 sampled from the elite pool. Every action a_t from the Q-network Q_θ modifies the design solution s_t to another design solution s_{t+1}, and returns a weighted reward r_t that indicates the decrease in the normalized circuit area and delay. That is,

$$r_t = w_a(\text{area}(s_t) - \text{area}(s_{t+1})) + w_d(\text{delay}(s_t) - \text{delay}(s_{t+1})). \tag{3}$$

After each episode, we insert each design solution at this episode into the elite pool when its design performance is better than the worst solution in the current elite pool.

4.3 Efficient and Effective Genetic Variation Operators

Designing efficient and effective genetic variation operators is important for the success of genetic algorithms (Zhu et al., 2023a; Bai et al., 2023b; Li et al., 2024a). Thus, we propose a sequential mutation operator for efficient long-term exploration via sequential modifications of design solutions based on the Q-network learned during initialization. We propose a multi-granularity crossover operator for globally diverse exploration by recombining two genetic solutions across diverse granularities. By using these genetic variation operators, we can generate a large set of offspring solutions from a population of design solutions at each iteration. We present details as follows.

A Sequential Mutation Operator for Efficient Exploration To explore the design solution space, a common idea is to perform random local modifications on design solutions. However, the random modification strategy can lead to redundant and myopic exploration, thus resulting in low sample efficiency and sub-optimal solutions. To promote efficient long-term exploration, we propose a sequential mutation operator to perform sequential local modifications on a given solution based on the learned Q-network. Specifically, for a design solution s_0 sampled from the current generation of populations, we leverage the learned Q-network Q_θ to guide episodic modifications on the design solution by sampling T local modification actions for generating mutated solutions. Thus, we generate T mutated offspring solutions by sampling a sequence of modification actions from the Q-network, i.e., $a_t = \arg\max_a Q_\theta(s_t, a), t = 0, \ldots, T$. To prevent premature convergence, we follow the ϵ-greedy strategy (Sutton & Barto, 1998) to sample actions.

This sequential mutation operator offers two key advantages. (1) Guided by the learned Q-function, we can prioritize modifications that enhance design performance, rather than relying on random

modifications. (2) By leveraging the long-term predictive capabilities of the learned Q-function, we can identify strong combinations of local modifications, leading to more effective design solutions.

A Multi-Granularity Crossover Operator for Diverse Exploration As shown in Figure 2, the objective function f is highly oscillatory, resulting in many local optimal design solutions. However, relying solely on existing local modifications severely restricts the exploration capability, as it only incrementally adjusts the number of full or half adders at a single column within a specific design solution. To enable global exploration for escaping local optima, it is crucial to develop design variation operators capable of making globally diverse exploration of the design space.

To this end, we propose a multi-granularity genetic crossover operator that recombines design substructures at varying column ranges between two grid-based genetic solutions. The key advantage of this approach is its ability to expand design variation from the single-gene level to the cross-column level. This allows for transitions from small changes involving a single column to more significant modifications that span multiple columns. This significantly enhances our global exploration capability, improving the ability to escape local optima.

Single Gene/Column Crossover Given two high-performing design solutions s^0 and s^1, we view the solutions as a sequence of genes, i.e., $s^0 = \left\{ (g_{3:2}^0(0), g_{2:2}^0(0)), \cdots, (g_{3:2}^0(N), g_{2:2}^0(N)) \right\}$ and $s^1 = \left\{ (g_{3:2}^1(0), g_{2:2}^1(0)), \cdots, (g_{3:2}^1(N), g_{2:2}^1(N)) \right\}$.

To recombine the two high-performing solutions to obtain diverse offspring solutions, the single column crossover randomly selects a column and recombines the genes at that column. Specifically, the column granularity crossover operator generates two children in the following form:

$$s_c^0 = \left\{ \cdots, (\mathbf{g_{3:2}^1(i)}, \mathbf{g_{2:2}^1(i)}), \cdots \right\} \text{ and } s_c^1 = \left\{ \cdots, (\mathbf{g_{3:2}^0(i)}, \mathbf{g_{2:2}^0(i)}), \cdots \right\}, \tag{4}$$

where i is the selected column. Meanwhile, the single gene crossover only recombines the genes representing a certain adder type at the selected column.

Cross Columns Crossover Given two high-performing design solutions s^0 and s^1, the cross columns crossover randomly selects two columns and recombines the two grid-based genetic solutions within the selected two columns. Specifically, the cross columns crossover generates two offspring solutions in the following form:

$$s_c^0 = \left\{ \cdots, (\mathbf{g_{3:2}^1(i)}, \mathbf{g_{2:2}^1(i)}), \cdots, (\mathbf{g_{3:2}^1(j)}, \mathbf{g_{2:2}^1(j)}), \cdots \right\} \text{ and }$$
$$s_c^1 = \left\{ \cdots, (\mathbf{g_{3:2}^0(i)}, \mathbf{g_{2:2}^0(i)}), \cdots, (\mathbf{g_{3:2}^0(j)}, \mathbf{g_{2:2}^0(j)}), \cdots \right\}, \tag{5}$$

where i and j are the selected two columns. Depending on the values of i and j, this crossover can recombine substructures across any different columns, thereby promoting global diverse exploration.

Note that the crossover operator could lead to illegal solutions. Thus, we design simple legalization rules following previous work (Zuo et al., 2023) to ensure that these generated children are legal design solutions. Please refer to Appendix F.5 for details.

4.4 MODEL-BASED CASCADE RANKING FOR EFFICIENT SELECTION

The success of genetic algorithms often relies on sampling a large number of solutions (Zhu et al., 2023a; Bai et al., 2023b; Li et al., 2024a). However, in circuit optimization tasks, evaluating each design solution using circuit synthesis tools is highly time-consuming, which significantly limits the number of samples for searching. To significantly improve sample efficiency, we propose learning a design evaluation model $\hat{f}_\Theta$ using the collected populations during evolution.

Model Training Inspired by standard model-based RL (Janner et al., 2019; Wang et al., 2023c), we first train a prediction model using the collected replay buffer during the population initialization process, and then adaptively update the model using a few populations with true evaluations during the evolution process. In terms of the model architecture, we employ the ResNet-18 as the state encoder and a multi-head decoder to predict the area and delay of the input state. The multi-head decoder comprises two multi-layer perceptrons (MLPs), each with two hidden layers with 256 units and ReLU activations. In terms of the training details, we use the mean squared error loss to update the model parameters. We use the Adam optimizer with a learning rate of 1e-3.

Model Usage Previous model-based RL methods (Janner et al., 2019; Wang et al., 2023c) have shown that directly using the learned model to replace the real environment suffers from model exploitation, i.e., overfitting to model errors. To address this challenge, we propose a model-based

Figure 4: The results demonstrate that the multipliers optimized by MUTE consistently and significantly Pareto-dominate the designs optimized by all five baselines across eight multiplier design problems, improving the hypervolume by up to 38%.

cascade ranking method to efficiently and accurately select high-performing solutions from a large set of generated solutions. The key idea is to progressively select solutions through two-stage ranking models, where the first stage model is our learned model and the second stage model is the real circuit synthesis environment. Specifically, we primarily use the model to rapidly evaluate the children solutions generated by the designed genetic variation operators. We generate at least 100 children solutions at each iteration, and use the model to pre-rank these solutions. The top-5 solutions are then selected for evaluation in the true environment. This approach allows us to generate a substantial number of children solutions, promoting diverse global exploration.

5 EXPERIMENTS

We first introduce the experimental setup, baselines, and evaluation metrics in Section 5.1. Then, our experiments are designed with four primary objectives. 1) We evaluate the performance of MUTE in optimizing computing circuits, including multipliers, adders, and MACs, across a broad range of input widths in Section 5.2. 2) We investigate the generalization performance of multipliers optimized by MUTE to large-scale macros widely-used in real-world AI chips in Section 5.3. 3) We perform carefully designed ablation studies to demonstrate the importance of our genetic evolution formulation and provide insights into each component in MUTE in Section 5.4. 4) We conduct a thorough trade-off evaluation of the runtime and performance gains of MUTE in Section 5.5.

5.1 EXPERIMENTAL SETTINGS

Experimental Setup Throughout our experiments, we utilize the OpenROAD flow (Ajayi & Blaauw, 2019) alongside the NanGate 45nm open-cell library (Nangate Inc., 2008) for circuit synthesis, coupled with OpenSTA (Parallax Software Inc.) for timing analysis. The setting follows previous work (Zuo et al., 2023). These tools represent the state-of-the-art open-source EDA tools, and are widely used in research of EDA (Kahng, 2021; Tan et al., 2021; Pilipović et al., 2021). Our training procedure employs the Adam optimizer (Ruder, 2016) within the PyTorch framework (Paszke et al., 2019). For fair comparison, we controlled the training time of our method to be comparable with the baseline methods (see Appendix H.2). We apply our method to eight distinct multiplier design tasks, encompassing 8-bit, 16-bit, 32-bit, and 64-bit multipliers based on both AND gate-based and Booth encoding-based PPG techniques. Moreover, we apply our method to six distinct adder and MAC design tasks as well. We defer more results to Appendix H.

Baselines Our baselines encompass five competitive approaches, ranging from traditional human-designed heuristics to state-of-the-art (SOTA) learning-based methods. **1) Wallace Tree** (Wallace, 1964) represents a classical human-designed compression algorithm. **2) GOMIL** (Xiao et al., 2021) is an expert-designed algorithmic method based on integer programming. **3) RL-MUL** (Zuo et al., 2023), **4) AdaReset** (Song et al., 2022), and **5) HAVE** (Wang et al., 2024g) are three recent SOTA RL-based multiplier and adder optimization methods.

Evaluation Metrics The computing circuits optimization problem is an optimization task with multiple conflicting objectives, such as area and delay. Thus, we employ two widely-used multi-objective optimization evaluation metrics (Basaklar et al., 2022; Hung et al., 2023) to compare the

Table 1: The results demonstrate that MUTE significantly outperforms previous SOTA approaches in terms of the hypervolume on both adder and MAC design tasks.

Adder	16-bit		32-bit		64-bit	
Methods	HyperVolume ↑	Improvement(%)↑	HyperVolume ↑	Improvement(%) ↑	HyperVolume ↑	Improvement(%) ↑
RL-MUL	88.03	NA	211.76	NA	503.45	NA
AdaReset	92.66	5.26	213.71	0.92	513.07	1.91
HAVE	113.92	29.41	254.09	19.99	566.26	12.48
MUTE (Ours)	**116.94**	**32.84**	**281.66**	**33.01**	**582.73**	**15.75**
MAC	**16-bit**		**32-bit**		**64-bit**	
Methods	HyperVolume ↑	Improvement(%)↑	HyperVolume ↑	Improvement(%) ↑	HyperVolume ↑	Improvement(%) ↑
RL-MUL	371.10	NA	4114.00	NA	6184.50	NA
AdaReset	369.60	-0.40	5123.00	24.53	10212.62	65.13
HAVE	401.80	8.27	5221.24	26.91	10604.57	71.47
MUTE (Ours)	**414.80**	**11.78**	**5843.00**	**42.03**	**11487.37**	**85.74**

Figure 5: The results illustrate that PE arrays designed by MUTE consistently and significantly outperform the designs discovered by all five baselines in terms of Pareto-dominance across four multiplier design problems, i.e., 16-bit (And), 32-bit (And), 16-bit (Booth), 32-bit (Booth).

performance of our method with the baselines. First, we visualize the found Pareto points in terms of the area and delay for circuits designed by both our method and the baselines. Second, we utilize the hypervolume (HV) of the found Pareto points, which is defined by the volume of the region between a reference point and these found Pareto points. We defer more details to Appendix F.7.

5.2 MAIN EVALUATION OF OPTIMIZING COMPUTING CIRCUITS

Multiplier Design We highlight the superiority of MUTE through a comparative analysis with five competitive baselines on eight multiplier design problems across a wide range of input sizes. The results in Figure 4 demonstrate that multipliers optimized by MUTE consistently and significantly outperform designs produced by all baselines across all eight multiplier design tasks. Moreover, we present the hypervolume of the Pareto points discovered by MUTE in Tables 6 and 7 in Appendix H.1. The results demonstrate that MUTE achieves a substantial improvement over the previous SOTA, improving the hypervolume by up to 38%. Overall, these results demonstrate the strong ability of MUTE to optimize multipliers, leading to significant reductions in both area and delay.

Broad Applicability to Adders and MACs To demonstrate that our approach is able to optimize a broad class of computing circuits, we apply our MUTE to optimizing two more fundamental computing circuits, i.e., adders and MACs. Specifically, we compare our MUTE with the three SOTA RL-based computing circuits optimization methods, i.e., RL-MUL (Zuo et al., 2023), AdaReset (Song et al., 2022), and HAVE (Wang et al., 2024g), on adders and MACs. As shown in Table 1, the results demonstrate that MUTE significantly outperforms previous SOTA approaches, improving the hypervolume by up to 42% compared to RL-MUL. The results not only highlight the superiority of our MUTE over previous SOTA approaches on optimizing computing circuits, but also demonstrate the broad applicability of our MUTE to a wide range of fundamental computing circuits.

5.3 GENERALIZATION TO LARGE-SCALE CIRCUITS

To evaluate the generalization ability of our designed computing units to large-scale real-world computing circuits with numerous circuit units, we integrate these units optimized by MUTE and baselines into Processing Element (PE) arrays (Park & Chung, 2020; Son et al., 2023), which follows previous work (Zuo et al., 2023; Wang et al., 2024g). PE arrays are widely used in parallel computing tasks and large-scale data processing like Deep Neural Network (DNN) accelerators.

The results in Figure 5 show that PE arrays incorporating multipliers optimized by MUTE consistently and significantly Pareto-dominate those utilizing multipliers obtained from baselines. Furthermore, we present the hypervolume of the Pareto frontiers discovered by MUTE in Table 11 in Appendix H.4. The results demonstrate a significant improvement in hypervolume achieved by MUTE, outperforming previous SOTA by up to 48.18%. We provide detailed results in Appendix

Table 3: Analysis on the trade-off between performance gains and runtime of each module in MUTE.

	16-bit And			32-bit And		
Methods	HyperVolume	Improvement(%)	RunTime (h)	HyperVolume	Improvement(%)	RunTime (h)
Wallace	332.91	-25.96	-	1685.61	-70.09	-
HAVE	505.83	12.50	20.33	5822.03	3.29	37.27
SA	449.63	NA	9.33	5636.51	NA	17.40
CGE	594.15	32.14	10.96	6285.00	11.51	18.35
CGE+Learning	608.25	35.28	15.17	6336.50	12.42	26.25
CGE+Learning+Model (MUTE)	**622.55**	**38.46**	**17.33**	**6461.65**	**14.64**	**37.11**

H.4. Overall, the results highlight the strong capability of MUTE to well generalize to large-scale computation-intensive circuits, thereby substantially improving real-world AI chips.

5.4 ABLATION STUDY

We present carefully designed ablation studies on multiplier design tasks as follows.

Contribution of Each Component To demonstrate the effectiveness of each component within MUTE, we conduct a thorough ablation study on multiplier design tasks.

In terms of the efficient and effective genetic variation module, we have designed two methods, called MUTE without Crossover (**w/o Crossover**) and MUTE without Mutation (**w/o Mutation**). MUTE without Crossover and MUTE without Mutation removes the designed

Table 2: The results demonstrate that each component within MUTE is significant.

	16-bit And		32-bit And	
Methods	HyperVolume ↑	Improvement(%) ↑	HyperVolume ↑	Improvement(%) ↑
Wallace	332.91	NA	1685.61	NA
MUTE (Ours)	**622.55**	**87.00**	**6461.65**	**283.34**
	Genetic Variation Module			
w/o Crossover	585.30	75.81	5996.00	255.72
w/o Mutation	600.10	80.26	6385.00	278.79
	Model-Based Module			
w/o Model	605.20	81.79	6278.00	272.45
	Learning Module			
w/o Learning	578.10	73.65	5766.00	242.07

genetic crossover and mutation operators, respectively. The results in Table 2 show that our designed genetic mutation and crossover operators are both critical for optimizing computing circuits, demonstrating the strong ability of the designed operators for promoting efficient and diverse exploration.

In terms of the model module, we have designed MUTE without Model (**w/o Model**) by removing the model-based module. The results in Table 2 show that learning a model can further improve the found designs in terms of the hypervolume. In terms of the learning module, we have designed MUTE without Learning (**w/o Learning**) by removing the learning module. The results demonstrate the significance of introducing learning into our genetic evolution for improving sampling efficiency.

5.5 PERFORMANCE GAIN AND RUNTIME TRADE-OFF EVALUATION

To further investigate the cost-effectiveness of each module of MUTE, we conducted an ablation study evaluating the trade-off between runtime and performance gains. MUTE consists of three modules: (1) the Circuit Genetic Evolution (CGE) module, (2) the Learning module, and (3) the Model-based module. The CGE module reformulates the multiplier design as a genetic evolution problem, using grid-based genetic representation and a random mutation policy. The Learning module introduces policy-guided population initialization and mutation. The Model-based module incorporates a learned model and a cascade ranking selection procedure.

Experimental results, summarized in Table 3, show that the CGE module significantly improves performance, achieving up to 32.14% gain with minimal runtime increase. The Learning module, while increasing runtime due to its computational overhead, enhances exploration efficiency and improves hypervolume. The Model-based module further improves hypervolume by 3.18%, though it increases runtime due to model training and additional sample collection. Despite these increases, the total runtime of MUTE remains comparable to the recent state-of-the-art approach, HAVE, highlighting the balance between performance gains and computational costs.

6 CONCLUSION

In this paper, we theoretically and empirically show a significant objective gap between the existing RL-based formulation and the original task due to the deceptive reward signals and incrementally localized actions in the RL-based formulation. To address this challenge, we propose a novel **m**odel-based circ**u**it gene**t**ic **e**volution (MUTE) framework, which reformulates the problem as a genetic evolution process by proposing a grid-based genetic representation of design solutions. Experiments on these circuits demonstrate that MUTE significantly Pareto-dominates state-of-the-art approaches in terms of both area and delay, improving the hypervolume by up to 38%.

7 ACKNOWLEDGEMENTS

The authors would like to thank all the anonymous reviewers for their insightful comments and valuable suggestions. This work was supported by the National Key R&D Program of China under contract 2022ZD0119801 and the National Nature Science Foundations of China grants U23A20388, 62021001 and 624B1011.

REPRODUCIBILITY STATEMENT

In this study, to ensure the reproducibility of our approach, we provide key information from the main text and Appendix as follows.

1. **Algorithm.** We provide the architecture and illustration of our MUTE in Figure 3 and Section 4. We also provide the detailed implementation of MUTE in Appendix F. See Appendix F.6 for the hyperparameters of MUTE.
2. **Source Code.** To facilitate the evaluation process and support a thorough review, we have released our source code at the following link: https://anonymous.4open.science/r/AI4MUL-4199.
3. **Experimental Details.** We provide detailed experiment settings in Section 5.1.
4. **Theoretical Proofs.** We provide all proofs in Appendix A.

REFERENCES

Hervé Abdi and Lynne J Williams. Principal component analysis. *Wiley interdisciplinary reviews: computational statistics*, 2(4):433–459, 2010.

Tutu Ajayi and David Blaauw. Openroad: Toward a self-driving, open-source digital layout implementation tool chain. In *Proceedings of Government Microcircuit Applications and Critical Technology Conference*, 2019.

Bushra Alhijawi and Arafat Awajan. Genetic algorithms: Theory, genetic operators, solutions, and applications. *Evolutionary Intelligence*, 17(3):1245–1256, 2024.

Nina Amenta, Marshall Bern, and Manolis Kamvysselis. A new voronoi-based surface reconstruction algorithm. In *Proceedings of the 25th annual conference on Computer graphics and interactive techniques*, pp. 415–421, 1998.

Nina Amenta, Sunghee Choi, Tamal K Dey, and Naveen Leekha. A simple algorithm for homeomorphic surface reconstruction. In *Proceedings of the sixteenth annual symposium on Computational geometry*, pp. 213–222, 2000.

Chen Bai, Qi Sun, Jianwang Zhai, Yuzhe Ma, Bei Yu, and Martin D.F. Wong. Boom-explorer: Riscv boom microarchitecture design space exploration framework. In *2021 IEEE/ACM International Conference On Computer Aided Design (ICCAD)*, pp. 1–9, 2021. doi: 10.1109/ICCAD51958.2021.9643455.

Chen Bai, Jiayi Huang, Xuechao Wei, Yuzhe Ma, Sicheng Li, Hongzhong Zheng, Bei Yu, and Yuan Xie. Archexplorer: Microarchitecture exploration via bottleneck analysis. In *2023 56th IEEE/ACM International Symposium on Microarchitecture (MICRO)*, pp. 268–282, 2023a.

Hui Bai, Ran Cheng, and Yaochu Jin. Evolutionary reinforcement learning: A survey. *Intelligent Computing*, 2:0025, 2023b.

Yinqi Bai, Jie Wang, Lei Chen, Zhihai Wang, Yufei Kuang, Mingxuan Yuan, Jianye Hao, and Feng Wu. A graph enhanced symbolic discovery framework for efficient circuit synthesis. In *The Thirteenth International Conference on Learning Representations*, 2025.

Toygun Basaklar, Suat Gumussoy, and Umit Y Ogras. Pd-morl: Preference-driven multi-objective reinforcement learning algorithm. *arXiv preprint arXiv:2208.07914*, 2022.

Andrew Beaumont-Smith and C-C Lim. Parallel prefix adder design. In *Proceedings 15th IEEE Symposium on Computer Arithmetic. ARITH-15 2001*, pp. 218–225. IEEE, 2001.

Yoshua Bengio, Andrea Lodi, and Antoine Prouvost. Machine learning for combinatorial optimization: a methodological tour d'horizon. *European Journal of Operational Research*, 290(2): 405–421, 2021.

Brent and Kung. A regular layout for parallel adders. *IEEE transactions on Computers*, 100(3): 260–264, 1982.

Frédéric Cazals and Joachim Giesen. Delaunay triangulation based surface reconstruction. In *Effective computational geometry for curves and surfaces*, pp. 231–276. Springer, 2006.

Lei Chen, Xing Li, Tsaras Dimitrios, Zhihai Wang, Yinqi Bai, and Mingxuan Yuan. A general framework for efficient logic synthesis. In *2024 2nd International Symposium of Electronics Design Automation (ISEDA)*, pp. 361–362. IEEE, 2024a.

Ruifeng Chen, Xu-Hui Liu, Tian-Shuo Liu, Shengyi Jiang, Feng Xu, and Yang Yu. Foresight distribution adjustment for off-policy reinforcement learning. In *Proceedings of the 23rd International Conference on Autonomous Agents and Multiagent Systems*, pp. 317–325, 2024b.

Shixin Chen, Shanyi Li, Zhen Zhuang, Su Zheng, Zheng Liang, Tsung-Yi Ho, Bei Yu, and Alberto L Sangiovanni-Vincentelli. Floorplet: Performance-aware floorplan framework for chiplet integration. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, 2023.

Shixin Chen, Su Zheng, Chen Bai, Wenqian Zhao, Shuo Yin, Yang Bai, and Bei Yu. Soc-tuner: An importance-guided exploration framework for dnn-targeting soc design. In *2024 29th Asia and South Pacific Design Automation Conference (ASP-DAC)*, pp. 207–212. IEEE, 2024c.

Luigi Dadda. Some schemes for fast serial input multipliers. In *1983 IEEE 6th Symposium on Computer Arithmetic (ARITH)*, pp. 52–59. IEEE, 1983.

Biplab Das, Avijit Kumar Paul, and Debashis De. An unconventional arithmetic logic unit design and computing in actin quantum cellular automata. *Microsystem Technologies*, pp. 1–14, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 4171–4186. Association for Computational Linguistics, 2019. doi: 10.18653/V1/N19-1423. URL https://doi.org/10.18653/v1/n19-1423.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Yan Duan, Xi Chen, Rein Houthooft, John Schulman, and Pieter Abbeel. Benchmarking deep reinforcement learning for continuous control. In *International conference on machine learning*, pp. 1329–1338. PMLR, 2016.

Fayez Elguibaly. A fast parallel multiplier-accumulator using the modified booth algorithm. *IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing*, 47(9):902–908, 2000.

Gautam Garai. Application of genetic algorithm in numerous scientific fields. In *Genetic algorithms*. IntechOpen, 2022.

Roman Garnett. *Bayesian optimization*. Cambridge University Press, 2023.

Maxime Gasse, Didier Chetelat, Nicola Ferroni, Laurent Charlin, and Andrea Lodi. Exact combinatorial optimization with graph convolutional neural networks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Zijie Geng, Xijun Li, Jie Wang, Xiao Li, Yongdong Zhang, and Feng Wu. A deep instance generative framework for milp solvers under limited data availability. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 26025–26047. Curran Associates, Inc., 2023.

Zijie Geng, Jie Wang, Ziyan Liu, Siyuan Xu, Zhentao Tang, Mingxuan Yuan, Jianye Hao, Yongdong Zhang, and Feng Wu. Reinforcement learning within tree search for fast macro placement. In *International Conference on Machine Learning*. PMLR, 2024.

Zijie Geng, Jie Wang, Xijun Li, Fangzhou Zhu, Jianye HAO, Bin Li, and Feng Wu. Differentiable integer linear programming. In *The Thirteenth International Conference on Learning Representations*, 2025a. URL `https://openreview.net/forum?id=FPfCUJTsCn`.

Zijie Geng, Jie Wang, Ziyan Liu, Siyuan Xu, Zhentao Tang, Shixiong Kai, Mingxuan Yuan, Jianye HAO, and Feng Wu. LaMPlace: Learning to optimize cross-stage metrics in macro placement. In *The Thirteenth International Conference on Learning Representations*, 2025b. URL `https://openreview.net/forum?id=YLIsIzC74j`.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. PMLR, 2018.

Reza Hashemian. A new multiplier using wallace structure and carry select adder with pipelining. In *ISCAS '02 Conference Proceedings*, 2002.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Christopher J Hillar and Lek-Heng Lim. Most tensor problems are np-hard. *Journal of the ACM (JACM)*, 60(6):1–39, 2013.

B. Holdsworth. *Digital logic design, 2nd ed.* 1987. ISBN 0408015667.

Yi-Qi Hu, Xu-Hui Liu, Shu-Qiao Li, and Yang Yu. Cascaded algorithm selection with extreme-region ucb bandit. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(10): 6782–6794, 2021.

Guyue Huang, Jingbo Hu, Yifan He, Jialong Liu, Mingyuan Ma, Zhaoyang Shen, Juejian Wu, Yuanfan Xu, Hengrui Zhang, Kai Zhong, et al. Machine learning for electronic design automation: A survey. *ACM Transactions on Design Automation of Electronic Systems (TODAES)*, 26(5):1–46, 2021.

Wei Hung, Bo Kai Huang, Ping-Chun Hsieh, and Xi Liu. Q-pensieve: Boosting sample efficiency of multi-objective RL through memory sharing of q-snapshots. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=AwWaBXLIJE`.

Niichi Itoh, Yasumasa Tsukamoto, Takeshi Shibagaki, Koji Nii, Hidehiro Takata, and Hiroshi Makino. A 32/spl times/24-bit multiplier-accumulator with advanced rectangular styled wallace-tree structure. In *2005 IEEE International Symposium on Circuits and Systems (ISCAS)*, pp. 73–76. IEEE, 2005.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. *Advances in neural information processing systems*, 32, 2019.

Chengxing Jia, Fuxiang Zhang, Yi-Chen Li, Chen-Xiao Gao, Xu-Hui Liu, Lei Yuan, Zongzhang Zhang, and Yang Yu. Disentangling policy from offline task representation learning via adversarial data augmentation. *arXiv preprint arXiv:2403.07261*, 2024.

Andrew B Kahng. Advancing placement. In *Proceedings of the 2021 International Symposium on Physical Design*, pp. 15–22, 2021.

Łukasz Kaiser, Mohammad Babaeizadeh, Piotr Miłos, Błażej Osiński, Roy H Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, et al. Model based reinforcement learning for atari. In *International Conference on Learning Representations*, 2020.

Yao Lai, Yao Mu, and Ping Luo. Maskplace: Fast chip placement via reinforced visual representation learning. *Advances in Neural Information Processing Systems*, 35:24019–24030, 2022.

Yao Lai, Jinxin Liu, Zhentao Tang, Bin Wang, Jianye Hao, and Ping Luo. Chipformer: Transferable chip placement via offline decision transformer. In *International Conference on Machine Learning*, pp. 18346–18364. PMLR, 2023.

Yao Lai, Jinxin Liu, David Z. Pan, and Ping Luo. Scalable and effective arithmetic tree generation for adder and multiplier designs. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=5pnhGedG98.

Pengyi Li, Jianye Hao, Hongyao Tang, Xian Fu, Yan Zhen, and Ke Tang. Bridging evolutionary algorithms and reinforcement learning: A comprehensive survey on hybrid algorithms. *IEEE Transactions on Evolutionary Computation*, 2024a.

Pengyi Li, HAO Jianye, Hongyao Tang, Yan Zheng, and Fazl Barez. Value-evolutionary-based reinforcement learning. In *Forty-first International Conference on Machine Learning*, 2024b.

Xihan Li, Xing Li, Lei Chen, Xing Zhang, Mingxuan Yuan, and Jun Wang. Circuit transformer: End-to-end circuit design by predicting the next gate, 2024c.

Xijun Li, Fangzhou Zhu, Hui-Ling Zhen, Weilin Luo, Meng Lu, Yimin Huang, Zhenan Fan, Zirui Zhou, Yufei Kuang, Zhihai Wang, Zijie Geng, Yang Li, Haoyang Liu, Zhiwu An, Muming Yang, Jianshu Li, Jie Wang, Junchi Yan, Defeng Sun, Tao Zhong, Yong Zhang, Jia Zeng, Mingxuan Yuan, Jianye Hao, Jun Yao, and Kun Mao. Machine learning insides optverse ai solver: Design principles and applications, 2024d.

Xing Li, Lei Chen, Jiantang Zhang, Shuang Wen, Weihua Sheng, Yu Huang, and Mingxuan Yuan. Effisyn: Efficient logic synthesis with dynamic scoring and pruning. In *2023 IEEE/ACM International Conference on Computer Aided Design (ICCAD)*, pp. 1–9, 2023. doi: 10.1109/ICCAD57390.2023.10323902.

Yixuan Li, Can Chen, Jiajun Li, Jiahui Duan, Xiongwei Han, Tao Zhong, Vincent Chau, Weiwei Wu, and Wanyuan Wang. Fast and interpretable mixed-integer linear program solving by learning model reduction. *arXiv preprint arXiv:2501.00307*, 2024e.

Yixuan Li, Wanyuan Wang, Weiyi Xu, Yanchen Deng, and Weiwei Wu. Factor graph neural network meets max-sum: A real-time route planning algorithm for massive-scale trips. In *Proceedings of the 23rd International Conference on Autonomous Agents and Multiagent Systems*, pp. 1165–1173, 2024f.

Haotian Ling, Zhihai Wang, and Jie Wang. Learning to stop cut generation for efficient mixed-integer linear programming. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38 (18):20759–20767, Mar. 2024. doi: 10.1609/aaai.v38i18.30064. URL https://ojs.aaai.org/index.php/AAAI/article/view/30064.

Haoyang Liu, Yufei Kuang, Jie Wang, Xijun Li, Yongdong Zhang, and Feng Wu. Promoting generalization for exact solvers via adversarial instance augmentation, 2023a. URL https://arxiv.org/abs/2310.14161.

Haoyang Liu, Jie Wang, Wanbo Zhang, Zijie Geng, Yufei Kuang, Xijun Li, Bin Li, Yongdong Zhang, and Feng Wu. MILP-studio: MILP instance generation via block structure decomposition. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024a. URL https://openreview.net/forum?id=W433RI0VU4.

Haoyang Liu, Jie Wang, Zijie Geng, Xijun Li, Yuxuan Zong, Fangzhou Zhu, Jianye HAO, and Feng Wu. Apollo-MILP: An alternating prediction-correction neural solving framework for mixed-integer linear programming. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=mFY0tPDWK8.

Jianhua Liu, Shuo Zhou, Haikun Zhu, and Chung-Kuan Cheng. An algorithmic approach for generic parallel adders. In *ICCAD-2003. International Conference on Computer Aided Design (IEEE Cat. No. 03CH37486)*, pp. 734–740. IEEE, 2003.

Jiantao Liu, Carmine Rizzi, and Lana Josipović. Load-store queue sizing for efficient dataflow circuits. In *2022 International Conference on Field-Programmable Technology (ICFPT)*, pp. 1–9, 2022. doi: 10.1109/ICFPT56656.2022.9974425.

Junfeng Liu, Liwei Ni, Xingquan Li, Min Zhou, Lei Chen, Xing Li, Qinghua Zhao, and Shuai Ma. Aimap: Learning to improve technology mapping for asics via delay prediction. In *2023 IEEE 41st International Conference on Computer Design (ICCD)*, pp. 344–347. IEEE, 2023b.

Junfeng Liu, Min Zhou, Shuai Ma, and Lujia Pan. Mata*: Combining learnable node matching with a* algorithm for approximate graph edit distance computation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pp. 1503–1512, 2023c.

Junfeng Liu, Liwei Ni, Lei Chen, Xing Li, Qinghua Zhao, Xingquan Li, and Shuai Ma. A delay-driven iterative technology mapping framework. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, pp. 1–1, 2024b. doi: 10.1109/TCAD.2024.3524463.

Qiyuan Liu, Qi Zhou, Rui Yang, and Jie Wang. Robust representation learning by clustering with bisimulation metrics for visual reinforcement learning with distractions. In *Thirty-Seventh AAAI Conference on Artificial Intelligence*, pp. 8843–8851. AAAI Press, 2023d.

Xu-Hui Liu, Zhenghai Xue, Jingcheng Pang, Shengyi Jiang, Feng Xu, and Yang Yu. Regret minimization experience replay in off-policy reinforcement learning. *Advances in Neural Information Processing Systems*, 34:17604–17615, 2021.

Xuhui Liu, Feng Xu, Xinyu Zhang, Tianyuan Liu, Shengyi Jiang, Ruifeng Chen, Zongzhang Zhang, and Yang Yu. How to guide your learner: Imitation learning with active adaptive expert involvement. In *Proceedings of the 2023 International Conference on Autonomous Agents and Multiagent Systems*, pp. 1276–1284, London, UK, 2023e.

Zhihan Liu, Miao Lu, Shenao Zhang, Boyi Liu, Hongyi Guo, Yingxiang Yang, Jose Blanchet, and Zhaoran Wang. Provably mitigating overoptimization in rlhf: Your sft loss is implicitly an adversarial regularizer. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Zhihan Liu, Hao Hu, Shenao Zhang, Hongyi Guo, Shuqi Ke, Boyi Liu, and Zhaoran Wang. Reason for future, act for now: A principled framework for autonomous llm agents with provable sample efficiency. *arXiv preprint arXiv:2309.17382*, 2023f.

Zhihan Liu, Miao Lu, Wei Xiong, Han Zhong, Hao Hu, Shenao Zhang, Sirui Zheng, Zhuoran Yang, and Zhaoran Wang. Maximize to explore: One objective function fusing estimation, planning, and exploration. *Advances in Neural Information Processing Systems*, 36, 2024c.

Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Wenjie Jiang, Ebrahim Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Azade Nazi, et al. A graph placement methodology for fast chip design. *Nature*, 594(7862):207–212, 2021.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, February 2015. ISSN 00280836. URL http://dx.doi.org/10.1038/nature14236.

Nangate Inc. "Open Cell Library v2008 10 SP1". http://www.nangate.com/openlibrary/, 2008.

Walter Lau Neto, Matheus Trevisan Moreira, Luca Amaru, Cunxi Yu, and Pierre-Emmanuel Gaillardon. Read your circuit: leveraging word embedding to guide logic optimization. In *Proceedings of the 26th Asia and South Pacific Design Automation Conference*, pp. 530–535, 2021.

Vojin G. Oklobdzija, David Villeger, and Simon S. Liu. A method for speed optimized partial product reduction and generation of fast parallel multipliers using an algorithmic approach. *IEEE Transactions on computers*, 45(3):294–306, 1996.

Parallax Software Inc. OpenSTA. https://github.com/The-OpenROAD-Project/OpenSTA.

Sang-Soo Park and Ki-Seok Chung. Cenna: cost-effective neural network accelerator. *Electronics*, 9(1):134, 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/bdbca288fee7f92f2bfa9f7012727740-Paper.pdf.

Ratko Pilipović, Patricio Bulić, and Uroš Lotrič. A two-stage operand trimming approximate logarithmic multiplier. *IEEE Transactions on Circuits and Systems I: Regular Papers*, 68(6):2535–2545, 2021.

Haoxing Ren and Jiang Hu. *Machine Learning Applications in Electronic Design Automation*. Springer Nature, 2023.

Rajarshi Roy, Jonathan Raiman, Neel Kant, Ilyas Elkin, Robert Kirby, Michael Siu, Stuart Oberman, Saad Godil, and Bryan Catanzaro. Prefixrl: Optimization of parallel prefix circuits using deep reinforcement learning. In *2021 58th ACM/IEEE Design Automation Conference (DAC)*, pp. 853–858. IEEE, 2021.

Subhendu Roy, Mihir Choudhury, Ruchir Puri, and David Z Pan. Towards optimal performance-area trade-off in adders by synthesis of parallel prefix structures. In *Proceedings of the 50th Annual Design Automation Conference*, pp. 1–8, 2013.

Sebastian Ruder. An overview of gradient descent optimization algorithms. *arXiv preprint arXiv:1609.04747*, 2016.

Daniela Sánchez, Lorenzo Servadei, Gamze Naz Kiprit, Robert Wille, and Wolfgang Ecker. A comprehensive survey on electronic design automation and graph neural networks: Theory and applications. *ACM Trans. Des. Autom. Electron. Syst.*, 28(2), feb 2023. ISSN 1084-4309. doi: 10.1145/3543853. URL https://doi.org/10.1145/3543853.

Yunqi Shi, Ke Xue, Lei Song, and Chao Qian. Macro placement by wire-mask-guided black-box optimization. In *Advances in Neural Information Processing Systems*, volume 36, pp. 6825–6843, New Orleans, LA, 2023.

Yunqi Shi, Siyuan Xu, Shixiong Kai, Xi Lin, Ke Xue, Mingxuan Yuan, and Chao Qian. Timing-driven global placement by efficient critical path extraction. In *Proceedings of Design Automation Test in Europe Conference Exhibition (DATE)*, 2025.

Jack Sklansky. Conditional-sum addition logic. *IRE Transactions on Electronic computers*, (2):226–231, 1960.

Adam Slowik and Halina Kwasnicka. Evolutionary algorithms and their applications to engineering problems. *Neural Computing and Applications*, 32:12363–12379, 2020.

Hyun-Wook Son, Ali A Al-Hamid, Yong-Seok Na, Dong-Yeong Lee, and Hyung-Won Kim. Cnn accelerator using proposed diagonal cyclic array for minimizing memory accesses. *Computers, Materials & Continua*, 76(2), 2023.

Jialin Song, Rajarshi Roy, Jonathan Raiman, Robert Kirby, Neel Kant, Saad Godil, and Bryan Catanzaro. Multi-objective reinforcement learning with adaptive pareto reset for prefix adder design. In *Workshop on ML for Systems at NeurIPS*, 2022.

R.S. Sutton and A.G. Barto. Reinforcement learning: An introduction. *IEEE Transactions on Neural Networks*, 9(5):1054–1054, 1998. doi: 10.1109/TNN.1998.712192.

Vivienne Sze, Yu-Hsin Chen, Tien-Ju Yang, and Joel S Emer. *Efficient processing of deep neural networks*. Springer, 2020.

Cheng Tan, Chenhao Xie, Ang Li, Kevin J Barker, and Antonino Tumeo. Aurora: Automated refinement of coarse-grained reconfigurable accelerators. In *2021 Design, Automation & Test in Europe Conference & Exhibition (DATE)*, pp. 1388–1393. IEEE, 2021.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ international conference on intelligent robots and systems*, pp. 5026–5033. IEEE, 2012.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf`.

Christopher S Wallace. A suggestion for a fast multiplier. *IEEE Transactions on electronic Computers*, (1):14–17, 1964.

Chenguang Wang and Tianshu Yu. Efficient training of multi-task neural solver with multi-armed bandits. *arXiv preprint arXiv:2305.06361*, 2023.

Chenguang Wang, Yaodong Yang, Congying Han, Tiande Guo, Haifeng Zhang, and Jun Wang. A game-theoretic approach for improving generalization ability of tsp solvers. 2021.

Chenguang Wang, Congying Han, Tiande Guo, and Man Ding. Solving uncapacitated p-median problem with reinforcement learning assisted by graph attention networks. *Applied Intelligence*, 53(2):2010–2025, 2023a.

Chenguang Wang, Zhouliang Yu, Stephen McAleer, Tianshu Yu, and Yaodong Yang. Asp: Learn a universal neural solver! *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024a.

Jie Wang, Rui Yang, Zijie Geng, Zhihao Shi, Mingxuan Ye, Qi Zhou, Shuiwang Ji, Bin Li, Yongdong Zhang, and Feng Wu. Generalization in visual reinforcement learning with the reward sequence distribution. *arXiv preprint arXiv:2302.09601*, 2023b.

Jie Wang, Zhihai Wang, Xijun Li, Yufei Kuang, Zhihao Shi, Fangzhou Zhu, Mingxuan Yuan, Jia Zeng, Yongdong Zhang, and Feng Wu. Learning to cut via hierarchical sequence/set model for efficient mixed-integer programming, 2024b.

Jie Wang, Zhihai Wang, Xijun Li, Yufei Kuang, Zhihao Shi, Fangzhou Zhu, Mingxuan Yuan, Jia Zeng, Yongdong Zhang, and Feng Wu. Learning to cut via hierarchical sequence/set model for efficient mixed-integer programming. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, pp. 1–17, 2024c. doi: 10.1109/TPAMI.2024.3432716.

Xiyao Wang, Ruijie Zheng, Yanchao Sun, Ruonan Jia, Wichayaporn Wongkamjan, Huazhe Xu, and Furong Huang. Coplanner: Plan to roll out conservatively but to explore optimistically for model-based rl. In *The Twelfth International Conference on Learning Representations*, 2023c.

Zhihai Wang, Jie Wang, Qi Zhou, Bin Li, and Houqiang Li. Sample-efficient reinforcement learning via conservative model-based actor-critic. *Proceedings of the AAAI Conference on Artificial Intelligence*, 36(8):8612–8620, Jun. 2022. doi: 10.1609/aaai.v36i8.20839. URL `https://ojs.aaai.org/index.php/AAAI/article/view/20839`.

Zhihai Wang, Xijun Li, Jie Wang, Yufei Kuang, Mingxuan Yuan, Jia Zeng, Yongdong Zhang, and Feng Wu. Learning cut selection for mixed-integer linear programming via hierarchical sequence model. In *The Eleventh International Conference on Learning Representations*, 2023d. URL `https://openreview.net/forum?id=Zob4P9bRNcK`.

Zhihai Wang, Taoxing Pan, Qi Zhou, and Jie Wang. Efficient exploration in resource-restricted reinforcement learning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 37(8): 10279–10287, Jun. 2023e. doi: 10.1609/aaai.v37i8.26224. URL `https://ojs.aaai.org/index.php/AAAI/article/view/26224`.

Zhihai Wang, Lei Chen, Jie Wang, Yinqi Bai, Xing Li, Xijun Li, Mingxuan Yuan, Jianye Hao, Yongdong Zhang, and Feng Wu. A circuit domain generalization framework for efficient logic synthesis in chip design. In *Forty-first International Conference on Machine Learning*. PMLR, 2024d.

Zhihai Wang, Zijie Geng, Zhaojie Tu, Jie Wang, Yuxi Qian, Zhexuan Xu, Ziyan Liu, Siyuan Xu, Zhentao Tang, Shixiong Kai, et al. Benchmarking end-to-end performance of ai-based chip placement algorithms. *arXiv preprint arXiv:2407.15026*, 2024e.

Zhihai Wang, Jie Wang, Qingyue Yang, Yinqi Bai, Xing Li, Lei Chen, Jianye HAO, Mingxuan Yuan, Bin Li, Yongdong Zhang, and Feng Wu. Towards next-generation logic synthesis: A scalable neural circuit generation framework. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024f. URL `https://openreview.net/forum?id=ZYNYhh3ocW`.

Zhihai Wang, Jie Wang, Dongsheng Zuo, Ji Yunjie, Xilin Xia, Yuzhe Ma, Jianye HAO, Mingxuan Yuan, Yongdong Zhang, and Feng Wu. A hierarchical adaptive multi-task reinforcement learning framework for multiplier circuit design. In *Forty-first International Conference on Machine Learning*, 2024g. URL `https://openreview.net/forum?id=LGz7GaUSEB`.

Neil HE Weste and David Harris. *CMOS VLSI design: a circuits and systems perspective*. Pearson Education India, 2015.

Weihua Xiao, Weikang Qian, and Weiqiang Liu. Gomil: Global optimization of multiplier by integer linear programming. In *2021 Design, Automation & Test in Europe Conference & Exhibition (DATE)*, pp. 374–379. IEEE, 2021.

Rui Yang, Jie Wang, Zijie Geng, Mingxuan Ye, Shuiwang Ji, Bin Li, and Feng Wu. Learning task-relevant representations for generalization via characteristic functions of reward sequence distributions. In *The 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 2242–2252. ACM, 2022a.

Rui Yang, Jie Wang, Zijie Geng, Mingxuan Ye, Shuiwang Ji, Bin Li, and Feng Wu. Learning task-relevant representations for generalization via characteristic functions of reward sequence distributions. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 2242–2252, 2022b.

Rui Yang, Jie Wang, Guoping Wu, and Bin Li. Uncertainty-based offline variational bayesian reinforcement learning for robustness under diverse data corruptions. In *Advances in Neural Information Processing Systems 38*, 2024.

Xufeng Yao, Haoyang Li, Tsz Ho Chan, Wenyi Xiao, Mingxuan Yuan, Yu Huang, Lei Chen, and Bei Yu. Hdldebugger: Streamlining hdl debugging with large language models. *arXiv preprint arXiv:2403.11671*, 2024a.

Xufeng Yao, Yiwen Wang, Xing Li, Yingzhao Lian, Ran Chen, Lei Chen, Mingxuan Yuan, Hong Xu, and Bei Yu. Rtlrewriter: Methodologies for large models aided rtl code optimization. *arXiv preprint arXiv:2409.11414*, 2024b.

Jiaxi Zhang, Qiuyang Gao, Yijiang Guo, Bizhao Shi, and Guojie Luo. Easymac: design exploration-enabled multiplier-accumulator generator using a canonical architectural representation. In *2022 27th Asia and South Pacific Design Automation Conference (ASP-DAC)*, pp. 647–653. IEEE, 2022.

Shenao Zhang, Donghan Yu, Hiteshi Sharma, Han Zhong, Zhihan Liu, Ziyi Yang, Shuohang Wang, Hany Hassan, and Zhaoran Wang. Self-exploring language models: Active preference elicitation for online alignment. *arXiv preprint arXiv:2405.19332*, 2024.

Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E Gonzalez, and Yuandong Tian. Noveld: A simple yet effective exploration criterion. *Advances in Neural Information Processing Systems*, 34:25217–25230, 2021.

Qingling Zhu, Xiaoqiang Wu, Qiuzhen Lin, Lijia Ma, Jianqiang Li, Zhong Ming, and Jianyong Chen. A survey on evolutionary reinforcement learning algorithms. *Neurocomputing*, 556: 126628, 2023a.

Xuliang Zhu, Ruofei Tang, Lei Chen, Xing Li, Xin Huang, Mingxuan Yuan, Weihua Sheng, and Jianliang Xu. A database dependent framework for k-input maximum fanout-free window rewriting. In *2023 60th ACM/IEEE Design Automation Conference (DAC)*, pp. 1–6, 2023b. doi: 10.1109/DAC56929.2023.10247727.

Dongsheng Zuo, Yikang Ouyang, and Yuzhe Ma. Rl-mul: Multiplier design optimization with deep reinforcement learning. In *2023 60th ACM/IEEE Design Automation Conference (DAC)*, pp. 1–6, 2023. doi: 10.1109/DAC56929.2023.10247941.

Dongsheng Zuo, Jiadong Zhu, Chenglin Li, and Yuzhe Ma. Ufo-mac: A unified framework for optimization of high-performance multipliers and multiply-accumulators. *arXiv preprint arXiv:2408.06935*, 2024a.

Dongsheng Zuo, Jiadong Zhu, Yikang Ouyang, and Yuzhe Ma. Rl-mul 2.0: Multiplier design optimization with parallel deep reinforcement learning and space reduction. *ACM Transactions on Design Automation of Electronic Systems*, 2024b.

A   THEORETICAL ANALYSIS

This section presents a theoretical analysis of the significant misalignment between the result of the optimal policy obtained through RL and the original optimal circuit design. First, the proof of Theorem 3.1 is provided in subsection A.1. Second, subsection A.2 offers further theoretical insights into the deceptive nature of the existing reward formulation.

Throughout the following theoretical analysis, we assume that the state space $\mathcal{S}$ is finite, and there is a terminal action for each state that can terminate the episode at this state. The assumptions usually hold in practical multiplier optimization problems. We focus on deterministic policies.

A.1   PROOF OF THEOREM 3.1

Lemma A.1. *For any policy π in the MDP, there exists a policy π' that terminates at a certain state such that $R^{\pi'} \geq R^{\pi}$.*

Proof. Since state space $\mathcal{S}$ is finite, the states in trajectory generated by policy π are finite as well. Therefore, there exists a state $s_T = \arg\min_{s \in \tau_{\pi}} f(s)$, where τ_{π} is the set of states in the trajectory of π and T is a finite number. We denote the trajectory τ_{π} by $\{s_0, s_1, \ldots, s_T, \ldots\}$.

Then we construct a new policy π' that generates a trajectory $\tau_{\pi'} = \{s'_0, \ldots, s'_T\}$, where $s'_t = s_t, \forall t \leq T$. Note that the trajectory $\tau_{\pi'}$ terminates at the state s_T. Then we have

$$R^{\pi'} = \sum_{t=0}^{T-1} \gamma^t (f(s_t) - f(s_{t+1})) \tag{6}$$

$$= \sum_{t=0}^{T-1} \gamma^t f(s_t) - \sum_{t=0}^{T-1} \gamma^t f(s_{t+1}) \tag{7}$$

$$= f(s_0) - \sum_{t=0}^{T-2} (\gamma^t - \gamma^{t+1}) f(s_{t+1}) - \gamma^{T-1} f(s_T) \tag{8}$$

$$= f(s_0) - (1-\gamma) \sum_{t=0}^{T-2} \gamma^t f(s_{t+1}) - (1-\gamma) \sum_{t=T-1}^{\infty} \gamma^t f(s_T) \tag{9}$$

$$\geq f(s_0) - (1-\gamma) \sum_{t=0}^{T-2} \gamma^t f(s_{t+1}) - (1-\gamma) \sum_{t=T-1}^{\infty} \gamma^t f(s_{t+1}) \tag{10}$$

$$= R^{\pi} \tag{11}$$

$\square$

Then we prove Theorem 3.1 as follows.

Proof. Recall that Theorem 3.1 states that "The optimal RL policy $\pi^* := \arg\max_{\pi} R^{\pi}$ terminates at a state, and the state is a local optimal state of the evaluation function f." We prove this Theorem in the following two steps.

(1) π^* **has a terminal state** If the optimal policy π^* doesn't terminate, then according to Lemma A.1 there exists a distinct policy with a higher return, which contradicts with the definition of the optimal policy π^*. Thus, π^* terminates at a certain state.

(2) **Local Minimality** Denote the terminate state of π^* as s_T. By contradiction, suppose $\exists a_0 \in \mathcal{A}, a_0 \neq$ terminate such that $f(T(s_T, a_0)) < f(s_T)$. Then consider a new policy π' whose trajectory is identical to π before the T-th step but execute action a_0 rather than terminating at T-th step, and

Figure 6: Sampled points from the training curve illustrating the oscillatory properties of the evaluation function.

execute terminate at step $T + 1$. Then the return of policy π' is

$$R^{\pi'} = \sum_{t=0}^{T} \gamma^t (f(s_t) - f(s_{t+1})) \tag{12}$$

$$= R^{\pi^*} + \gamma^T (f(s_T) - f(T(s_T, a_0))) \tag{13}$$

$$> R^{\pi^*} \tag{14}$$

which contradicts the definition of the optimal π^*. □

A.2 MULTIPLE HIGH HILLS CONDITION FOR GAP EXISTENCE

Theorem 3.1 indicates that the existing reward formulation guides the RL agent to evolve the circuit from an initial design to a locally optimal solution. However, the conditions under which this local optimum is the same as the global optimum remain unclear. In this subsection, we provide heuristic conclusions based on the oscillatory behavior of the objective function.

First, we sample a trajectory from the sigh-dimensional solution space using a basic EA algorithm for the purpose of visualization and simplified analysis, denoted as τ_{Sim}, as shown in Figure 2. Our analysis focuses on the impact of the proxy reward function on the optimization objective along the sampled one-dimensional function curve, avoiding the complexities of the high-dimensional state space. Using the sampled trajectory τ_{Sim}, we define a simplified MDP (Sim-MDP) with the tuple $(\mathcal{S}_{Sim}, \mathcal{A}_{Sim}, T_{Sim}, r, \gamma, \mu_0)$. Here, $\mathcal{S}_{Sim} = \tau_{Sim}$. The action space is simplified into $\mathcal{A}_{Sim} = \{Go, Terminate\}$. The transition function is defined as $T_{Sim}(s_t, Go) = s_{t+1}$, and the episode terminates upon executing the terminate action. The reward function, discount factor, and initial state are consistent with the original MDP. Any policy in this Sim-MDP corresponds to a trajectory terminating at a certain state. The Sim-MDP simplifies state and action spaces while keeping the reward function unchanged, facilitating the analysis of the optimization objective gap.

Based on the Sim-MDP, we calculate the cumulative discounted rewards of policies starting from the initial state and terminating at various points along the curve. We then compare the returns of these policies with the return of the policy π_{s^*} that converges to the global minimum point s^* in the Sim-MDP. For discount factors of 0.8, 0.9, and 0.99, the proportions of policies with returns higher than π_{s^*} accounts for approximately 54.14%, 54.07%, and 45.71%, respectively. Moreover, for discount factors of 0.8, 0.9, and 0.99, the relative objective gap between the optimal RL policy and the global optimal point are roughly 35.52%, 34.75%, and 26.19%, respectively. This demonstrates a significant gap between the RL proxy optimization objective and the original optimization objective, attributed to the highly oscillatory nature of the optimization objective function.

Second, to further understand the reasons for this gap, we theoretically show conditions for the existence of optimization objective gap in the Sim-MDP, based on the observation that the evaluation function is highly oscillatory, leading to many peak and trough points. We first rigorously formulate the evaluation function f across the sampled trajectory τ_{Sim} by using many repeated hills, which is inspired by the properties of oscillatory functions. A state $s_t \in \mathcal{S}_{Sim}$ is a **Peak Point** if $f(s_t) >$

$f(s_{t-1})$ and $f(s_t) > f(s_{t+1})$. In contrast, a state $s_t \in \mathcal{S}_{\text{Sim}}$ is a **Trough Point** if $f(s_t) < f(s_{t-1})$ and $f(s_t) < f(s_{t+1})$. Without loss of generality, we assume the initial state of Sim-MDP is a through point. We denote p_i as the step index of the i-th peak point, and t_i as the step index of the i-th through point. The i-th **Hill** is defined by a set of states between the i-th trough point and the $(i+1)$-th trough point, i.e., $P_i := \{s_t | t_i \le t \le t_{i+1}\}$. We denote the number of ascending steps $p_i - t_i$ by m_i, and the number of descending steps $t_{i+1} - p_i$ by n_i. Inspired by the fact that the action will always affine the structure of the multiplier which changes the evaluation function, for the i-th Hill we denote the lower bound of the variation of f as $\delta_i := \min_{j \in [t_i, p_i)} \{|f(s_{j+1}) - f(s_j)|\}$; on the other hand the evaluation function f is bounded, thus we denote the upper bound of the variation of as $\epsilon_i := \max_{j \in [p_i, t_{i+1})} \{|f(s_j) - f(s_{j+1})|\}$. The formulation is illustrated in Figure 6. With the multiple hills formulation, we provide a Multiple High Hills Condition for the existence of optimization objective gap.

Theorem A.2 (Multiple High Hills Condition). *Denote the number of hills in the Sim-MDP before s^* as N, where $s^* := \arg\min_{s \in \mathcal{S}_{sim}} f(s)$ is the global optimal state in Sim-MDP. If there exists the i-th trough point s_{t_i} such that*

$$\sum_{j=i}^{N} \gamma^{t_j - t_i} \left[\frac{\gamma^{m_j}(1 - \gamma^{n_j})}{1 - \gamma} \epsilon_j - \frac{1 - \gamma^{m_j}}{1 - \gamma} \delta_j \right] < 0, \tag{15}$$

then the optimization objective gap exists, i.e., the optimal policy in Sim-MDP π^*_{Sim} converges to a sub-optimal solution rather than the global optimal state s^*.

Proof. Suppose s^* is achieved at step T, and denote the policy that terminates at s^* as π_0. For any through point s_{t_i}, consider a new policy π' that terminates at s_{t_i} and its return is

$$R^{\pi'} = \sum_{t=0}^{t_i - 1} \gamma^t (f(s_t) - f(s_{t+1})) \tag{16}$$

Then we have

$$R^{\pi_0} - R^{\pi'} = \sum_{t=t_i}^{T-1} \gamma^t (f(s_t) - f(s_{t+1})) \tag{17}$$

$$= \sum_{j=i}^{N} \sum_{t=t_j}^{t_{j+1}-1} \gamma^t (f(s_t) - f(s_{t+1})) \tag{18}$$

$$= \sum_{j=i}^{N} \left\{ \sum_{t=t_j}^{t_j+m_j-1} \gamma^t (f(s_t) - f(s_{t+1})) + \sum_{t=t_j+m_j}^{t_j+m_j+n_j-1} \gamma^t (f(s_t) - f(s_{t+1})) \right\} \tag{19}$$

$$= \sum_{j=i}^{N} \left\{ \gamma^{t_j} \sum_{t=0}^{m_j-1} \gamma^t (f(s_t) - f(s_{t+1})) + \gamma^{t_j+m_j} \sum_{t=0}^{n_j-1} \gamma^t (f(s_t) - f(s_{t+1})) \right\} \tag{20}$$

$$\le \sum_{j=i}^{N} \left\{ \gamma^{t_j} \sum_{t=0}^{m_j-1} \gamma^t (-\delta_i) + \gamma^{t_j+m_j} \sum_{t=0}^{n_j-1} \gamma^t \epsilon_i \right\} \tag{21}$$

$$= \sum_{j=i}^{N} \gamma^{t_j} \left\{ \frac{1 - \gamma^{m_j}}{1 - \gamma} (-\delta_i) + \gamma^{m_j} \frac{1 - \gamma^{n_j}}{1 - \gamma} \epsilon_i \right\} \tag{22}$$

$$\tag{23}$$

Then $\sum_{j=i}^{N} \gamma^{t_j} \left\{ \frac{1-\gamma^{m_j}}{1-\gamma}(-\delta_i) + \gamma^{m_j} \frac{1-\gamma^{n_j}}{1-\gamma} \epsilon_i \right\} < 0 \Rightarrow R^{\pi_0} < R^{\pi'}$, i.e. π' has higher return, and further the optimal policy in Sim-MDP π^*_{Sim} converges to a sub-optimal solution rather than the global optimal state s^*. □

This Theorem implies that if there are multiple high hills, i.e., unexpected high peak points (large δ_j), on the trajectory between a trough point (i.e., a local optimum) and the global optimum, then

Figure 7: Optimization objective landscape of 16-bit and gate-based multiplier. The global minimum is marked as the red point. The grey lines mark RL-MUL and HAVE trajectories, with points indicating the optimal solutions found every five episodes. The optimum found by RL-MUL and HAVE is marked as the yellow point, with the objective value annotated nearby.

the RL optimization objective converges to the local optimum rather than the global optimum, due to the noisy information in the cumulative discounted performance objective from those unexpected high peak points.

B   VISUALIZATION OF OPTIMIZATION OBJECTIVE LANDSCAPE

In this section, we visualize the optimization objective landscape using the 16-bit AND gate-based multiplier optimization task.

Visualizing optimization objective landscape

(1) **Data Collection** To ensure comprehensive sampling and maximize coverage of the solution space, we first employ the RL-MUL (Zuo et al., 2023) and HAVE (Wang et al., 2024g) algorithms to generate initial populations, each comprising 2,500 solutions. Building on this initial population, we extensively apply our genetic variation operators, ultimately producing a total of 50,000 solutions.

(2) **Data Visualization** To visualize the high-dimensional solution space, we use Principal Component Analysis (PCA) (Abdi & Williams, 2010) to reduce its dimensionality to two dimensions. This enables the creation of a 3D surface plot depicting the relationship between solutions and their fitness values, i.e., our optimization objective landscape. We reconstruct the objective function surface from the data points using Delaunay triangulation, which is widely used in surface reconstruction from a set of points (Amenta et al., 1998; 2000; Cazals & Giesen, 2006).

(3) **Results** As shown in Figure 7, the results reveal that the optimization surface is highly oscillatory and characterized by numerous local optima. Using the visualization method described above, we transformed the points collected during the training processes of RL-MUL and HAVE into curves. The results reveal that both RL-MUL and HAVE converged to specific local optima.

The convergence into local optima of RL-MUL and HAVE

Using the visualization method described above, we transformed the points collected during the training processes of RL-MUL and HAVE into curves. The results reveal that both RL-MUL and HAVE converged to specific local optima.

C   RELATED WORK

C.1   COMPUTING CIRCUITS OPTIMIZATION

Computing circuits like adders and multipliers are widely employed in practical applications, leveraging Compressor Tree and Prefix Tree for efficient parallel operations. Generally, optimization methods for these circuits can be categorized into three main approaches. (1) **Manual designs** involve leveraging human expertise to craft architectures derived from regular designs, which require

substantial engineering effort. Various compressor Trees have been devised to reduce partial products, as shown in (Wallace, 1964; Dadda, 1983; Itoh et al., 2005; Oklobdzija et al., 1996), while Prefix Trees are optimized for more efficient parallel addition, as demonstrated in (Beaumont-Smith & Lim, 2001; Sklansky, 1960; Brent & Kung, 1982). (2) **Conventional algorithmic** methods (Xiao et al., 2021; Zuo et al., 2024a; Liu et al., 2003; Roy et al., 2013) generate circuit architectures using specific strategies such as mathematical programming and heuristic search. However, they often optimize circuits using proxy metrics such as size and depth, which may result in a significant discrepancy from actual performance in the real design flow. (3) Recent methods (Zuo et al., 2023; 2024b; Roy et al., 2021; Song et al., 2022; Wang et al., 2024g; Lai et al., 2024) propose using **reinforcement learning** to optimize circuits based on the post-synthesis metrics, incorporating synthesis into the optimization loop, This offers promising approaches to bridge the gap between proxy metrics and actual performance. In this paper, we focus on optimizing computing circuits using post-synthesis metrics as well.

C.2 Reinforcement Learning

Reinforcement Learning (RL) has achieved great success in sequential decision-making problems, encompassing applications from video game playing to robotic control(Mnih et al., 2015; Kaiser et al., 2020; Duan et al., 2016; Zhang et al., 2024; Liu et al.). RL approaches can be generally divided into model-free Haarnoja et al. (2018); Wang et al. (2023e); Yang et al. (2022b); Liu et al. (2024c); Wang et al. (2023b); Liu et al. (2021); Yang et al. (2022a); Liu et al. (2023d), model-based Janner et al. (2019); Liu et al. (2023f); Wang et al. (2022), and offline RL Hu et al. (2021); Chen et al. (2024b); Jia et al. (2024); Liu et al. (2023e); Yang et al. (2024) approaches. In this paper, our MUTE falls into the model-based category.

C.3 Genetic Evolution Algorithms

Genetic evolutionary algorithms (GA) are one of the most established and famous optimization methods, encompassing a diverse range of variants that find extensive applications across various fields (Garai, 2022; Alhijawi & Awajan, 2024). Inspired by Darwinian theories of species evolution in nature, genetic algorithms utilize selection, crossover, and mutation operators to evolve solutions, ultimately achieving global optimization (Slowik & Kwasnicka, 2020). Recently, Evolutionary Reinforcement Learning algorithms (ERLs) have emerged as a promising solution, effectively integrating the strengths of both reinforcement learning and evolutionary algorithms (Zhu et al., 2023a; Bai et al., 2023b; Li et al., 2024a). In this paper, we propose a learning-based population initialization, a sequential mutation operator, a multi-granularity crossover operator, and a model-based cascade ranking within a genetic algorithm framework for optimizing computing circuits.

C.4 Machine Learning for Chip Design

With the exponential growth in chip complexity driven by advances in semiconductor technology, the application of machine learning (ML) to assist in the automated chip design workflow has garnered significant attention in recent years (Mirhoseini et al., 2021; Huang et al., 2021; Sánchez et al., 2023; Neto et al., 2021; Lai et al., 2022; 2023). The chip design process encompasses several stages (Huang et al., 2021; Ren & Hu, 2023), including high-level synthesis (Yao et al., 2024a; Liu et al., 2022; Yao et al., 2024b), logic synthesis (Li et al., 2023; Zhu et al., 2023b; Li et al., 2024c; Liu et al., 2023b;c; 2024b; Bai et al., 2025; Wang et al., 2024f;d; Chen et al., 2024a), placement (Lai et al., 2022; 2023; Geng et al., 2024; Chen et al., 2023; Shi et al., 2023; 2025; Wang et al., 2024e; Geng et al., 2025b), and design space exploration (Chen et al., 2024c; Bai et al., 2023a; 2021), among others.

C.5 Machine Learning for Combinatorial Optimization

Optimizing multiplier circuit designs is also essentially a combinatorial optimization problem. The use of machine learning to tackle combinatorial optimization problems has been an active topic of significant interest in recent years (Bengio et al., 2021; Gasse et al., 2019; Geng et al., 2023; Wang et al., 2023d; 2024b; Ling et al., 2024; Li et al., 2024d; Wang et al., 2021; 2024a; 2023a; Wang & Yu, 2023; Wang et al., 2024c; Geng et al., 2025a; Liu et al., 2023a; 2025; 2024a; Li et al., 2024f;e).

Figure 8: State representation in RL-MUL.

D   IMPLEMENTATION DETAILS OF RL-MUL

State Representation We use the total number of 3:2 and 2:2 compressors in each column to present the multiplier structure. As illustrated in Figure 8, 4-bit multiplier structure and its matrix representation M are shown. Given a matrix $M \in \mathbf{R}^{K \times (N_b + M_b)}$, where m_{ij} indicates the quantity of the i-th compressor used in column j. RL-MUL follows a fixed scheme to extend the matrix M to a tensor to obtain a unique representation for the assignment of compressors in multiplier stages. As shown in Figure 8, RL-MUL utilizes $\mathcal{T} \in \mathbf{R}^{K \times (M_b + N_b) \times ST}$ to represent a multi-stage state, where K is the total types of compressors, ST is the number of compression stages, and N_b and M_b is the input width. For any element t_{ij}^k within $\mathcal{T}$, it signifies the utilization of the i-th type of compressor at column j and stage i. The assignment method is to assign the compressors from the least significant bit (LSB) columns to the most significant bit (MSB) columns and assign the 3:2 compressors first as many as possible. After assigning the 3:2 compressors, if at column j there are still more than two PPs, it assigns the 2:2 compressors. Repeat this progress until all compressors are assigned. For example at column 4 in Figure 8, we first assign a 3:2 compressor in the first stage, then assign a 2:2 compressor in the second stage.

Legalization Rules When selecting actions, RL-MUL exclusively considers whether the action reduces the final production products to either 1 or 2. RL-MUL has four actions, including adding a 3:2 compressor, removing a 2:2 compressor, replacing a 3:2 compressor, and replacing a 2:2 compressor. Furthermore, an action performed at column j will have an impact on column j+1 and cause column j+1 illegal due to the propagation of the carry bit. RL-MUL employs a legalization strategy that refines the state from column j+1 to the most significant bit, ensuring that the PPs in every line are reduced to 1 or 2 following the actions. The strategy adds a 3:2 or replaces a 2:2 compressor if there is an over of PPs, and deletes a compressor if there is a lack of PPs.

E   IMPLEMENTATION DETAILS OF THE BASELINES

GOMIL (Xiao et al., 2021) is a global optimization method that simultaneously considers the CT and CPA. The author provides the open-source C++ code. We can extract the required structure from its solution files.

E.1   RL-BASED BASELINES

RL-MUL (Zuo et al., 2023) encodes the state into a tensor $\mathcal{T}$ described in Appendix D, using ResNet-18 as the network backbone and training based on the DQN algorithm. Different from the Random method, RL-MUL only chooses the action randomly in warm-up steps. In future steps, it chooses the action that can maximize the masked Q-value of the network.

MBPO Janner et al. (2019) is a state-of-the-art model-based RL method, which can significantly improve sample efficiency by learning an environment model. We implement the algorithm in our multiplier optimization environment by setting the Update-To-Data ratio as five.

E.2 Evolutionary Algorithms

MFEA Slowik & Kwasnicka (2020) is a population-based global optimization method inspired by biological evolution. We maintain a population of candidate solutions, iteratively evolving them through random mutations, crossovers, and selections. The population is then updated based on the fitness values of the individuals.

MBBO Garnett (2023) is a global optimization method. We model the solution space as a high-dimensional vector space. We first sample a trajectory using a random walk. Then during each iteration, we fit an RBF kernel Gaussian Process model and use UCB (Upper Confidence Bound) as the acquisition function to determine the next sampling point.

F Implementation Details of Our MUTE

F.1 Hardware Specification

Our experiments were executed on a Linux-based system equipped with a 3.60 GHz Intel Xeon Gold 6246R CPU and NVIDIA RTX 3090 GPU.

F.2 Synthesis Tool Setup

Nangate45 is a widely used standard cell library in the semiconductor industry. It is open source and free, and we can obtain it at `https://silvaco.com/services/library-design/`. Readers can refer to `https://github.com/The-OpenROAD-Project/OpenROAD-flow-scripts`, seeking the artifact of OpenROAD flow matched with the distribution.

In terms of the verilog generation, previous work uses EasyMAC Zhang et al. (2022) to implement it. We encode our CT following EasyMAC Zhang et al. (2022) rules which use a sequence $s_{ct} = p_0 p_1 \cdots p_r$ to represent a CT. Each $p_i = (index_i, type_i)$ signifies the index and type of a compressor. Considering that generating Verilog HDL codes by EasyMAC and running the logical synthesis are still time-consuming, we directly generate multiplier Verilog codes using our designed template. Compared to EasyMAC, our method can generate verilog code faster. To ensure fairness in comparison, we have employed a uniform default adder to implement CPA for all methods.

F.3 Details on the Learning-Based Population Initialization

F.3.1 Best-Case Learning

In terms of population Initialization, we propose a best-case learning module, which maintains an elite pool with 20 currently found best design solutions for enhanced diversity. We restart the initial state by sampling a state from the elite pool at the beginning of each episode. In terms of the RL algorithms, we follow previous work (Zuo et al., 2023; Wang et al., 2024g) to use a DQN agent to learn Q-functions for selecting modification actions. In terms of the Q-network architecture, we use the ResNet-18 as the tensor state encoder, and use a multi-layer perceptron (MLP) to predict Q-values for each candidate action. The MLP contains two hidden layers with 256 units and the ReLU activation function. To train the Q-network, we use an Adam optimizer, and set the learning rate as 1e-4. For a fair comparison, we set hyperparameters to align with previous work (Zuo et al., 2023; Wang et al., 2024g).

F.3.2 Evaluation Model Learning and Conservative Model Usage

In terms of the model architecture, we employ the ResNet-18 as the tensor state encoder and a multi-head decoder to predict the area and delay of the input state. The multi-head decoder comprises two multi-layer perceptrons (MLPs), each with two hidden layers with 256 units and ReLU activation.

In terms of the training details, we use the mean squared error loss to update the model parameters. We use the Adam optimizer with a learning rate of 1e-3.

In terms of model usage, we primarily use the model to fast evaluate the children solutions generated by the designed genetic variation operators. Specifically, we generate at least 100 children solutions at each iteration, and use the model to pre-rank these solutions. The top-5 solutions are then selected for evaluation in the true environment. This approach allows us to generate a substantial number of children solutions, promoting extensive globally diverse exploration. Note that we do not use the model in the RL learning, as it will suffer from the **cumulative multi-step model errors** due to the sequential characteristics of RL methods. In contrast, using the model in our evolution process only suffers from **single-step model errors**.

RunTime of Design Evaluation As demonstrated in Table 4, our learned model can significantly reduce the design evaluation time compared to calling synthesis tools. RL-MUL (Zuo et al., 2023) employs EasyMAC and OpenRoad, while Vgen refers to a Verilog generation method we implemented, detailed in Appendix F.2. Al-

Table 4: Runtime comparison

Method/Circuit	RunTime (s, every 100 samples)	
	32-bit And	64-bit And
EasyMAC+OpenRoad	2930	10930
Vgen+OpenRoad	303	973
Model (Ours)	**1.4**	**1.44**

though Vgen considerably accelerates evaluation compared to EasyMAC, it remains inefficient when evaluating large volumes of design solutions.

F.4 DETAILS ON THE RL-GUIDED MUTATION OPERATOR

The action space The actions consist of four types of local modifications to a Compressor Tree solution at a specific column. These modifications include adding a 2:2 compressor, removing a 2:2 compressor, replacing a 3:2 compressor with a 2:2 compressor, and replacing a 2:2 compressor with a 3:2 compressor.

Q-network model Our Q-network comprises a ResNet-18 (He et al., 2016) as an encoder to represent the input state, and a multi-layer perceptron as a decoder to predict Q-values. The input state is a grid-based genetic representation of the design solution. The output comprises the state-action values for each action.

The learning process We employ the Deep Q-network (DQN) algorithm (Mnih et al., 2015) to train the Q-network. During the population initialization phase, we train the Q-network using collected interactions with the circuit synthesis environment. We then periodically update the Q-network by sampling some interactions with the circuit synthesis environment throughout the evolution process.

Managing invalid designs We indeed apply a legalization rule to transforming any invalid design solution into a valid solution, which is designed by RL-MUL (Zuo et al., 2023). Specifically, a valid design requires each column to have exactly one or two remaining partial products after compression. Invalid designs—resulting from actions that impact subsequent columns—occur when a column has either zero or three remaining partial products. To resolve this, we implement a legalization process that starts from the affected column and progresses toward the most significant column. For columns with three remaining partial products, a 2:2 compressor is either replaced with or augmented by a 3:2 compressor. For columns with zero remaining partial products, a 2:2 or 3:2 compressor is removed, as appropriate. This process ensures that all columns maintain a valid number of remaining partial products (either one or two).

F.5 DETAILS ON THE MULTI-GRANULARITY CROSSOVER OPERATOR

Legalization Mechanism Note that the crossover operators may lead to illegal solutions. Thus, we need to design a reasonable and simple legalization mechanism. Fortunately, we can follow the legalization rule proposed in RL-MUL (Zuo et al., 2023) to legalize these illegal solutions. Specifically, given a state that is modified from column i to any column, we can refine the state from column i to the most significant bit, ensuring that the final partial products (PPs) in every line are reduced to 1 or 2 following the actions. The legalization rule adds a 3:2 or replaces a 2:2 compressor if there is an over of PPs, and deletes a compressor if there is a lack of PPs.

F.6 ADDITIONAL COMMON HYPERPARAMETERS

In the above sections, we have provided implementation details and hyperparameters. Here, we list the common parameters used in the comparative evaluation and ablation study in Table 5. Note that

(a) Pareto Points   (b) Hypervolume

Figure 9: **(a)** An example for a Pareto optimal set with 2 objectives and 5 Pareto optimal solutions (Pareto points). **(b)** An example for hypervolume with a selected reference point r_0. Integrated area $H(P, r_0)$ is the union of the rectangular areas where the reference point r_0 and the Pareto point $P(i)$ are diagonally opposite corners.

we use the same hyperparameter as that of previous work (Zuo et al., 2023; Wang et al., 2024g) if possible for fair comparison.

Table 5: Common parameters used in the comparative evaluation and ablation study.

Parameter	Value
Learning-Based Population Initialization Module	
environment steps per learning episode	25
policy updates per environment step	1
optimizer	Adam
discount (γ)	0.8
total learning episodes for initialization	40
Genetic Variation Module	
samples generated by sequential mutation operator at each iteration	100
samples generated by genetic crossover operator at each iteration	200
total iterations for evolution	400
Model-Based Module	
samples for circuit synthesis evaluation at each iteration	5

F.7 EVALUATION METRICS

Indeed, the multiplier optimization problem is a multi-objective optimization task with multiple conflicting objectives, such as area and delay. Thus, we use two evaluation metrics to compare our method with baselines. First, we visualize the approximated Pareto front in terms of the area and delay for multipliers designed by our method and baselines. Second, we use the hypervolume of the approximated Pareto front. We present details on the two metrics as follows.

Multi-Objective Optimization Metrics

Without loss of generality, considering a maximization optimization problem in n objectives, we aim to find the set of optimal solutions known as the Pareto optimal set. For an n-objective optimization problem, a solution x Pareto dominates another solution y if x is not worse than y in all objectives and has at least one strictly better value, i.e., $\forall i \in [1, n], f_i(x) \geq f_i(y) \land \exists i \in [1, n], f_i(x) > f_i(y)$.

A Pareto optimal solution is not dominated by any solution, and the set composed of all Pareto optimal solutions is referred to as the Pareto optimal solution set. One metric to evaluate the quality of a Pareto optimal solution set is hypervolume, which is illustrated in Figure 9. The hypervolume of a set is the volume of the space that is dominated by the solution in the set. When calculating the hypervolume of a set, we need to choose a reference point. When reference points are fixed, a Pareto solution set with a larger hypervolume is considered superior.

Definition F.1 (Hypervolume metric)**.** Let P be a Pareto front approximation in an n-dimensional objective space and contain N solutions. Let $r_0 \in R^m$ be the reference point. Then, the hypervolume metric is defined as:

$$\mathcal{H}(P, r_0) = \int_{R^n} \mathbb{1}_{H(P, r_0)(z)dz}$$

, where $H(P, r_0) = \{z \in Z | \exists 1 \leq i \leq |P| : r_0 \leq z \leq P(i)\}$. $P(i)$ is the i-th solution in P, $\leq$ is the relation operator of objective dominance, and $\mathbb{1}_{H(P, r_0)}$ is a Dirac delta function that equals 1 if $z \in H(P, r_0)$ and 0 otherwise.

F.8 CONTRIBUTION OF OUR WORK TO AI COMMUNITY

Advancing AI Chips Our work directly contributes to the advancement of AI chips, such as NVIDIA's GPUs and Google's TPUs, by introducing an innovative optimization framework for the design of high-speed, area-efficient, and energy-efficient computing circuits. Note that NVIDIA's AI researchers have integrated AI-designed adders into their H100 chip [5], demonstrating the potential of our AI-based approach for advancing AI chips. The ability to optimize AI chips is crucial for addressing the ever-growing computational demands of modern AI systems, ensuring their scalability, efficiency, and sustainability.

A Novel and Broadly Applicable Genetic Evolution Algorithm Our work introduces a sequential mutation operator and a multi-granularity crossover operator that leverages a grid-based genetic solution representation to facilitate efficient and diverse exploration of large search spaces. This approach presents a broadly applicable framework suitable for addressing a wide range of search problems. Moreover, we propose a model-based cascade ranking approach, which efficiently and accurately selects high-performing solutions from a large pool of generated candidates. These contributions offer a versatile and robust methodology for tackling complex optimization problems.

Identifying the Limitations of a Commonly-Used RL Formulation for Combinatorial Optimization The existing RL formulation for computing circuit optimization adheres to a widely adopted paradigm in neural combinatorial optimization [6, 7, 8], commonly referred to as the "learn-to-improve" framework. In this paradigm, the state is defined as a candidate solution, the action represents a local modification to the solution, and the reward is based on the performance improvement achieved. This paper theoretically and empirically demonstrates that the RL-based formulation tends to converge to local optima, primarily due to deceptive reward signals and incrementally localized actions. These findings provide valuable insights for developing more robust and effective methods applicable to a broad class of neural combinatorial optimization problems.

G LICENSES

We credit the following open-source code and data used in this paper. We will also open-source our code once the paper is accepted.

Environment

1. OpenRoadFlowScripts BSD 3-Clause License
2. OpenRoad BSD 3-Clause License
3. Yosys ISC License
4. EasyMAC No License

Algorithms

1. GOMIL No License

2. MBPO MIT License

3. NovelD Creative Commons Public Licenses

H   MORE RESULTS

H.1   MORE RESULTS OF MAIN EVALUATION

The details about the hypervolume of MUTE and other baselines can be found at Table 6 and Table 7. Table 6 records the hypervolumes of the method on four multipliers with different bit-widths based on the And-Gate, showing that our method has the greatest improvement. Table 7 shows our improvements on the multipliers based on Booth-encode.

Table 6: We record the hypervolume of multipliers based on And-Gate.The results demonstrate that MUTE has the maximum hypervolume on each circuit design task.

	8-bit And		16-bit And		32-bit And		64-bit And	
Methods	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)
Wallace	149.94	NA	332.91	NA	1685.61	NA	13870.80	NA
GOMIL	153.02	2.05%	394.25	18.43%	3304.67	96.05%	16628.51	19.88%
RL-MUL	160.84	7.27%	470.78	41.41%	5329.71	216.19%	25311.45	82.48%
AdaReset	168.34	12.27%	473.20	42.14%	5768.29	242.21%	32827.17	136.66%
HAVE	179.49	19.71%	504.94	51.67%	5822.03	245.40%	33030.52	138.13%
MUTE (Ours)	**189.68**	**26.50%**	**622.55**	**87.00%**	**6461.65**	**283.34%**	**36419.85**	**162.56%**

Table 7: We record the hypervolume of multipliers based on Booth-encode. The results demonstrate that MUTE has the maximum hypervolume on each circuit design task.

	8-bit Booth		16-bit Booth		32-bit Booth		64-bit Booth	
Methods	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)
Wallace	304.86	NA	625.70	NA	4045.40	NA	13184.57	NA
GOMIL	314.22	3.07%	773.43	23.61%	3686.76	-8.87%	11456.09	-13.11%
RL-MUL	339.72	11.43%	897.02	43.36%	6090.67	50.56%	19341.59	46.70%
AdaReset	339.72	11.43%	910.00	45.44%	6970.98	72.32%	23946.19	81.62%
HAVE	339.72	11.43%	975.94	55.98%	7452.70	84.23%	25910.38	96.52%
MUTE (Ours)	**366.63**	**20.26%**	**1060.86**	**69.55%**	**8057.07**	**99.17%**	**29441.15**	**123.30%**

Table 8: The runtime of MUTE is comparable to or shorter than that of the recent state-of-the-art HAVE, while MUTE significantly improves hypervolume.

	16-bit And			32-bit And		
RL/ERL Method	RunTime (hours)	HV ↑	Iterations	RunTime (hours)	HV ↑	Iterations
MUTE (Ours)	17.33	622.55	400	37.11	6461.65	400
RL-MUL	14.75	470.78	400	31.17	5329.71	400
ParetoReset	15.37	473.2	400	31.37	5606	400
HAVE	20.33	505.83	400	37.27	5822.03	400
VEB-RL	33.17	485	400	64.97	5402	400
MBPO	28.4	491.53	400	51.73	4978.11	400
EA Method						
MFEA	10.7	473.39	400	19.7	5478.03	400
MBBO	12.7	473.36	400	35.1	5445.18	400

H.2   RUNTIME COMPARISON OF MUTE WITH BASELINES

The results in Table 8 indicate that the runtime of our method is comparable to or shorter than that of the recent state-of-the-art HAVE (Wang et al., 2024g), while our method significantly improves the hypervolume of found Pareto points.

H.3   MORE RESULTS OF COMPARISON WITH RL METHODS

Figure 10 illustrates the Pareto frontier of our MUTE and all RL-based methods. Moreover, we provide the results of hypervolume on 16-bit Booth and 32-bit Booth in Table 9. Through the table and figure, we can observe that MUTE outperforms other RL methods comprehensively, achieving the smallest area and delay.

H.4   MORE RESULTS OF GENERALIZATION

Table 11 shows the hypervolume of PE arrays designed by MUTE and other baselines. MUTE achieves the highest hypervolume across all circuit designs.

Table 9: Results of comparison with RL methods on 16-bit Booth and 32-bit Booth.

	16-bit Booth		32-bit Booth	
Methods	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)
Wallace	625.70	NA	4045.40	NA
RL-MUL	897.02	43.36	6090.67	50.56
NoveID	873.31	39.57	6436.80	59.11
PD-MORL	871.02	39.21	6639.44	64.12
DDQN	894.74	43.00	6504.40	60.79
MBPO	942.20	50.58	6056.30	49.71
RL-EA	910.00	45.44	6970.98	72.32
MBPO-EA	932.86	49.09	6772.67	67.42
MUTE (Ours)	**1060.86**	**69.55**	**8057.07**	**99.17**

Figure 10: The results demonstrate that multipliers optimized by MUTE consistently and significantly outperform designs produced by all RL-based methods in terms of Pareto-dominance across four multiplier design problems.

H.5 MORE ABLATION STUDY

The Importance of Our Genetic Evolution Formulation Although we have compared our MUTE with three specifically designed RL methods for computing circuits optimization, i.e., RL-MUL, AdaReset, and HAVE, the three methods are all based on the deep Q-network (DQN) algorithm (Mnih et al., 2015), which is a classical RL method. To further demonstrate the superiority of our formulation over the existing RL formulation, we further apply five advanced RL methods to multiplier design tasks. Specifically, we compare MUTE with four advanced RL methods, including NovelD (Zhang et al., 2021), PD-MORL (Basaklar et al., 2022), DDQN (Van Hasselt et al., 2016), and MBPO

Table 10: MUTE significantly outperforms advanced (evolutionary) RL methods.

	16-bit And		32-bit And	
Methods	HyperVolume ↑	Improvement(%) ↑	HyperVolume ↑	Improvement(%) ↑
Wallace	332.91	NA	1685.61	NA
Specifically Designed RL Methods				
RL-MUL	470.78	41.41	5329.71	216.19
AdaReset	473.20	42.14	5768.29	242.21
HAVE	504.94	51.67	5822.03	245.40
Advanced Standard RL Methods				
NoveID	473.20	42.14	4953.97	193.90
PD-MORL	485.03	45.69	4665.43	176.78
DDQN	473.20	42.14	4773.51	183.19
MBPO	491.53	47.65	4978.11	195.33
SOTA Evolutionary RL Method				
VEB-RL	485.00	45.69	5402.00	220.48
Our Genetic Evolution Formulation				
MUTE (Ours)	**622.55**	**87.00**	**6461.65**	**283.34**

(Janner et al., 2019), and an evolutionary RL method, i.e., VEB-RL (Li et al., 2024b).

The results in Table 10 suggest the following key conclusions. (1) MUTE significantly outperforms these advanced (evolutionary) RL methods, demonstrating the superiority of our proposed circuit genetic evolution formulation. (2) Advanced RL methods do not consistently and significantly outperform DQN-based circuit optimization methods, i.e., RL-MUL, AdaReset, and HAVE. This implies that the multiplier optimization task diverges significantly from standard RL benchmarks, such as Mujoco control (Todorov et al., 2012), due to its unique challenges.

Table 11: We record the hypervolume of PE arrays across four PE array design problems. The results demonstrate that MUTE has the maximum hypervolume on each circuit design task.

	16-bit And		32-bit And		16-bit Booth		32-bit Booth	
Methods	HyperVolume	Improvement (%)	HyperVolume	Improvement (%)	HyperVolume	Improvement(%)	HyperVolume	Improvement(%)
Wallace	73073.23	NA	329263.00	NA	156874.00	NA	692705.30	NA
GOMIL	84820.07	16.08%	627041.10	90.44%	174168.70	11.02%	628020.70	-9.34%
RL-MUL	103507.80	41.65%	944998.90	187.00%	219779.80	40.10%	1049519.00	51.51%
AdaReset	104073.20	42.42%	1009747.00	206.67%	230816.90	47.14%	1237265.00	78.61%
HAVE	108277.90	48.18%	1019332.00	209.58%	247851.40	57.99%	1306568.00	88.62%
MUTE (Ours)	**143485.40**	**96.36%**	**1165307.00**	**253.91%**	**258221.60**	**64.60%**	**1388204.00**	**100.40%**