Learning Generalizable Risk-Sensitive Policies to Coordinate in Decentralized Multi-Agent General-Sum Games

Abstract

While various multi-agent reinforcement learning methods have been proposed in cooperative settings, few works investigate how self-interested learning agents achieve mutual coordination in decentralized general-sum games and generalize pre-trained policies to non-cooperative opponents during execution. In this paper, we present a generalizable and sample efficient algorithm for multi-agent coordination in decentralized general-sum games without any access to other agents' rewards or observations. Specifically, we first learn the distributions over the return of individuals and estimate a dynamic risk-seeking bonus to encourage agents to discover risky coordination strategies. Furthermore, to avoid overfitting opponents' coordination strategies during training, we propose an auxiliary opponent modeling task so that agents can infer their opponents' type and dynamically alter corresponding strategies during execution. Empirically, we show that agents trained via our method can achieve mutual coordination during training and avoid being exploited by non-cooperative opponents during execution, which outperforms other baseline methods and reaches the state-of-the-art.

1 Introduction

Inspired by advances in deep reinforcement learning (DRL)[1–3], many researchers recently focus on utilizing DRL methods to tackle multi-agent problems[4–6]. However, most of these works either consider the fully cooperative multi-agent reinforcement learning (MARL) settings [7–11] or general-sum games but make restrictive assumptions about opponents[12–14], e.g., either stationary[13] or altruistic [15, 16]. Considering future applications of MARL, such as self-driving cars[17] and human-robot interactions [18], multiple learning agents optimize their own rewards independently in general-sum games where win-win outcomes are only achieved through coordination which often coupled with risk[19, 12, 20] ("Risk" refers to the uncertainty of future outcomes[21]), and their pre-trained policies should generalize to non-cooperative opponents during execution.

To achieve coordination alongside other learning agents and generalize learned policies to non-cooperative opponents, the agent must be willing to undertake a certain amount of risk and identify the opponents' type efficiently. One set of approaches use explicit reward shaping to force agents to coordinate[22, 16, 15], which can be viewed as an approach to shape the risk degree of coordination strategies. To learn generalizable policies, [15, 20] propose to train an adaptive agent with population-based training methods. However, training a population of policy profiles is computationally intractable in real-world complex multi-agent scenarios, and cannot leverage features about

opponent's type emergent in multi-agent exploration procedure. Other works either treat the other agents as stationary[13, 23, 24, 20], or directly access to opponent's policy parameters[12].

By contrast, we are interested in a less restrictive setting where we do not assume access to opponents' rewards, observations, or policy parameters, instead, each agent can infer other agents' current strategies from the past behaviors of other agents. Considering in self-driving scenarios, the ego car has no knowledge about what the front cars observed or their true payoffs, but it can see the actions made by the front cars, e.g., risky merging and lane changing, and thus adjust its own strategies.

In this paper, one key insight is that learning from opponent's past behaviors allows the agent to infer the opponent's type and dynamically alter his strategy between different modes, e.g., either cooperate or compete, during execution. Moreover, given that the other learning agents are non-stationary, decision-making over the agent's return distributions enables the agent to tackle uncertainties resulting from other agents' behaviors and alter his risk preference, i.e., from risk-neutral to risk-seeking, to discover coordination strategies. Motivated by the analysis above, we propose GRSP, a Generalizable Risk-Sensitive MARL algorithm and our contributions are summarized as follows:

Leading to mutual coordination in decentralized general-sum games. We estimate a dynamic risk-seeking bonus using a complete distortion risk measure Wang's Transform (WT)[25] to encourage agents to discover risky cooperative strategies. The risk-seeking bonus only affects the action selection procedure instead of shaping environment rewards and decreases throughout training, leading to an unbiased policy.

Generalizing pre-trained policies to non-cooperative opponents during execution. Policies learned independently can overfit to the other agents' policies during training, failing to sufficiently generalize during execution[26]. We further propose to train each learning agent with two objectives: a standard Quantile Regression objective[27, 28] and a supervised agent modeling objective, which models the behaviors of opponent, applied on intermediate representation of the value network. The auxiliary supervised task allows the shallow part of the value network, which is designed as a feature extractor, to be influenced by opponent's past behaviors. During execution, the agent can update parameters of the feature extractor using his local observations and observed opponent's actions, forcing the intermediate representation to adapt to the new opponent.

Evaluating in multi-agent settings. We evaluate GRSP in four different Markov games: Monster-Hunt[15, 29], Escalation[15, 16], Iterated Prisoners' Dilemma (IPD)[12, 20] and Iterated Stag Hunt (ISH)[19, 15]. Compared with several baseline methods, including Multi-Agent Deep Deterministic Policy Gradient (MADDPG)[30], Multi-Agent PPO (MAPPO)[31], Local Information Agent Modelling (LIAM)[13] and Indenpendent Actor Critic (IAC)[32], GRSP learns substantially faster, achieves mutual coordination during training and can generalize to the non-cooperative opponent during execution, which outperforms other baseline methods and reaches the state-of-the-art.

2 Related Work

Risk-sensitive RL. Risk-sensitive policies, which depend upon more than mean of the outcomes, enable agents to handle the intrinsic uncertainty arising from the stochasticity of the environment. In MARL, the intrinsic uncertainties are amplified due to the non-stationarity and partial observability created by other agents that change their policies during the learning procedure[33–35]. Distributional RL[36, 28] provides a new perspective for optimizing policy under different risk preferences within a unified framework[21, 37]. With distributions of return, it is able to approximate value function under different risk measures, such as variance-related measure[38–40], Conditional Value at Risk (CVaR)[41, 42] and WT[25], and thus produce risk-averse or risk-seeking policies. Qiu et al.[11] propose a cooperative MARL method called RMIX with the CVaR measure over the learned distributions of individuals' Q values as risk-averse policies. However, RMIX focuses on the fully cooperative setting and learns a centralized but factored value function to guide optimization of the decentralized policies, which cannot be applied beyond cooperative games. Lyu et al.[43] propose a decentralized risk-sensitive policy LH-IQN for all agents to seek higher team rewards. In contrast

with these works, we are interested in decentralized general-sum games where agents use risk-seeking policies to explore coordination strategies and can generalize them to non-cooperative opponents.

Generalization across different opponents. Many real world scenarios require agents to adapt to different opponents during execution. However, most of existing works focus on learning a fixed and team-dependent policy in fully cooperative setting[44, 8, 9, 11, 10] which can not generalize to slightly altered environments or new opponents. Other works either use a population-based training method to train an adaptive agent[15], or adapt to different opponents under the Tit-for-Tat principle[20, 45]. Our work is closely related to test-time training methods[46, 47]. However, they focus on image recognition or single agent policy adaption. We consider generalization across different opponents in MARL and use opponents' past behaviors as supervised information. Ad hoc teamwork[48, 49] also requires agents to generalize to new teams, but they focus on cooperative games and has different concerns with us.

Opponent modeling. Our approach to learning generalizable policies can be viewed as a kind of opponent modeling method[50]. These approaches either model intention[51, 52], assume an assignment of roles[53] or exploit opponent learning dynamics[12, 54]. Our approach is similar to policy reconstruction methods[52] which make explicit predictions about opponent's actions. However, instead of predicting the opponent's future actions, we learn from opponent's past behaviors to update the belief, i.e., parameters of value network, of the opponent's type.

3 Preliminaries

Stochastic games. In this work, we consider multiple self-interested learning agents interact with each other. We model the problem as a Partially-Observable Stochastic Game (POSG)[55, 56], which consists of N agents, a state space $\mathcal{S}$ describing the possible configurations of all agents, a set of actions $\mathcal{A}^1, \ldots, \mathcal{A}^N$ and a set of observations $\mathcal{O}^1, \ldots, \mathcal{O}^N$ for each agent. At each time step, each agent i receives his own observation $o^i \in \mathcal{O}^i$, and selects an action $a^i \in \mathcal{A}^i$ based on a stochastic policy $\pi^i : \mathcal{O}^i \times \mathcal{A}^i \mapsto [0, 1]$, which results in a joint action vector $\boldsymbol{a}$. The environment then transitions to a new state s' based on the transition function $P(s'|s, \boldsymbol{a})$. Each agent i obtains rewards as a function of the state and his action $R^i : \mathcal{S} \times \mathcal{A}^i \mapsto \mathbb{R}$. The initial states are determined by a distribution $\rho : \mathcal{S} \mapsto [0, 1]$. We treat the reward "function" R^i of each agent as a random variable to emphasize its stochasticity, and use $Z^{\pi^i}(s, a^i) = \sum_{t=0}^{T} \gamma^t R^i(s_t, a_t^i)$ to denote the random variable of the cumulative discounted rewards where $S_0 = s$, $A_0^i = a^i$, γ is a discount factor and T is the time horizon.

Distributional reinforcement learning with quantile regression. Instead of learning the expected return Q, distributional RL focuses on learning the full distribution of the random variable Z directly[36, 28, 21]. As with the scalar setting, a distributional Bellman optimality operator can be defined by

$$\mathcal{T}Z(s, a) := R(s, a) + \gamma Z \left(s', \arg\max_{a' \in \mathcal{A}} \mathbb{E}Z(s', a') \right), \tag{1}$$

with s' distributed according to $P(s'|s, a)$.

Bellmare et al.[36] show that the distributional Bellman operator is a contraction in a maximal form of the Wasserstein metric between probability distributions, but the proposed algorithm C51 dose not itself minimize the Wasserstein metric. This theory-practice gap is closed by Dabney et al.[28] as they propose to use Quantile Regression for distributional RL. In this paper, we focus on the quantile representation used in QR-DQN[28], where the distribution of Z is represented by a uniform mix of M supporting quantiles $Z_\theta(s, a) \doteq \frac{1}{M} \sum_{i=1}^{M} \delta_{\theta_i(s,a)}$, where δ_x denotes a Dirac at $x \in \mathbb{R}$, and each θ_i is an estimation of the quantile corresponding to the quantile fractions $\hat{\tau}_i \doteq \frac{\tau_{i-1} + \tau_i}{2}$ with $\tau_i \doteq \frac{i}{M}$ for $0 \leq i \leq M$. The state-action value $Q(s, a)$ can then be approximated by $\frac{1}{M} \sum_{i=1}^{M} \theta_i(s, a)$.

These quantile estimates are trained using the Huber[57] quantile regression loss. The loss of the quantile value network is then given by

$$\mathcal{J}\left(s_t, a_t, r_t, s_{t+1}\right) = \frac{1}{M} \sum_{i=0}^{M-1} \sum_{j=0}^{M-1} \rho_{\hat{\tau}_i}^\kappa \left(\delta_{ij}^t\right) \tag{2}$$

where $\delta_{ij}^t \doteq r_t + \gamma \theta_j\left(s_{t+1}, \pi\left(s_{t+1}\right)\right) - \theta_i(s_t, a_t)$, and $\rho_{\hat{\tau}_i}^\kappa(x) \doteq |\hat{\tau}_i - \mathbb{I}\left\{\delta_{ij} < 0\right\}| \frac{\mathcal{L}_\kappa(\delta_{ij})}{\kappa}$ where $\mathbb{I}$ is the indicator function and $\mathcal{L}_\kappa(x)$ is the Huber loss:

$$\mathcal{L}_\kappa(x) \doteq \begin{cases} \frac{1}{2}x^2 & \text{if } x \leq \kappa \\ \kappa\left(|x| - \frac{1}{2}\kappa\right) & \text{otherwise} \end{cases} \tag{3}$$

Distorted expectation. Distorted expectation is a risk weighted expectation of value distribution under a specific distortion function[58]. A function $g : [0,1] \mapsto [0,1]$ is a distortion function if it is non-decreasing and satisfies $g(0) = 0$ and $g(1) = 1$[59]. The distorted expectation of Z under g is defined as $\Psi(Z) = \int_0^1 F_Z^{-1}(\tau)dg(\tau) = \int_0^1 g'(\tau)F_Z^{-1}(\tau)d\tau$, where F_Z^{-1} is the quantile function at $\tau \in [0,1]$ for the random variable Z. We introduce two common distortion functions as follow:

- **CVaR** is the expectation of the lower or upper tail of the value distribution, corresponding to risk-averse or risk-seeking policy respectively. Its distortion function is $g(\tau) = \min(\tau/\alpha, 1)$ (risk-averse) or $\max\left(0, 1 - (1-\tau)/\alpha\right)$ (risk-seeking), $\alpha \in (0,1)$ denotes confidence level.

- **WT** is proposed by Wang[25]: $g_\lambda(\tau) = \Phi\left(\Phi^{-1}(\tau) + \lambda\right)$, where Φ is the distribution of a standard normal. The parameter λ is called the market price of risk and reflects systematic risk. $\lambda > 0$ for risk-averse and $\lambda < 0$ for risk-seeking.

CVaR_α assigns a 0-value to all percentiles below the α or above $1 - \alpha$ significance level which leads to erroneous decisions in some cases[59]. Instead, WT is a complete distortion risk measure and ensures using all the information in the original loss distribution which makes training much more stable, and we will empirically demonstrate it in Sec. 5.

4   Methods

In this section, we describe our proposed GRSP method. We first introduce the risk-seeking bonus used to encourage agents to discover coordination strategies in Sec. 4.1 and then propose the auxiliary opponent modeling task to learn generalizable policies in Sec. 4.2. Finally, we provide the details of test-time policy adaptation under different opponents in Sec. 4.3.

4.1   Risk-Seeking Bonus

In this section, we first provide an illustrative example for the insight behind risk-seeking bonus and then describe its details. Consider a two-player 10 steps Sequential matrix game Stag Hunt, where each player should decide whether to hunt stag (S) or hunt hare (H) in each round. If both agents choose S they will receive the highest payoff 2. However, if one agent defects, he will receive a descent reward 1 for eating the hare alone while the other agent with an S action will suffer from a big loss -10. If both agents choose H they will receive payoff 1.

Figure 1: Quantile value distribution of cooperation and defection in Sequential Stag Hunt weighted by WT compared with risk-neutral policy.

Even state of the art RL algorithms fail to discover the "risky" cooperation strategies[15, 16, 19]. One important reason is that the expected, i.e., risk-neutral, Q value ignores the complete distribution information, especially the upper and lower tail information when the learned distribution is asymmetric. Another reason is that when the risk is high, i.e., a high loss for

being betrayed, the probability of finding the S-S (Cooperation) strategy via policy gradient is very low[15].

Therefore, we adopt the distributional RL method to model the whole distribution of Q value. Fig.1 left part shows the quantile distribution of cooperation and defection of risk-neutral policy learned by QR-DQN. The mean value of defection is higher than that of cooperation, but the quantile value distribution of cooperation has a longer upper tail which means that it has a higher potential payoff.

We propose to use WT distortion function to reweight the expectation of quantile distribution. Specifically, the risk-seeking bonus for agent i is

$$\Psi(Z^{\pi^i}) = \int_0^1 g'_\lambda(\tau) F_{Z^{\pi^i}}^{-1}(\tau) d\tau \approx \frac{1}{M} \sum_{j=1}^M g'_\lambda(\hat{\tau}_j) \theta_j^i, \tag{4}$$

where $g'_\lambda(\tau)$ is the derivatives of WT distortion function at $\tau \in [0, 1]$, and λ controls the risk-seeking level. Fig.1 right part shows the WT weighted quantile distribution in which the upper quantile values are multiplied by bigger weights and lower quantile values are multiplied by smaller weights to encourage agents to adopt risky coordination strategies.

Instead of using ϵ-greedy method for exploration, we adopt the left truncated variance of quantile distribution to further leverage the intrinsic uncertainty for efficient exploration. The left truncated variance is defined as

$$\sigma_+^2 = \frac{1}{2M} \sum_{j=\frac{M}{2}}^M \left(\theta_{\frac{M}{2}} - \theta_j \right)^2, \tag{5}$$

and analysed in [60]. We anneal the two exploration bonuses dynamically so that in the end we produce unbiased policies. The anneal coefficients are defined as $c_{tj} = c_j \sqrt{\frac{\log t}{t}}, j = 1, 2$ which is the parametric uncertainty decay rate[61], and c_j is a constant factor. This approach leads to choosing the action such that

$$a^{i*} = \arg \max_{a^i \in \mathcal{A}^i} \left(Q^{\pi^i}(o^i, a^i) + c_{t1} \Psi(Z^{\pi^i}(o^i, a^i)) + c_{t2} \sqrt{\sigma_+^2(o^i, a^i)} \right) \tag{6}$$

4.2 Auxiliary Opponent Modeling Task

In order to alter the agent's strategies under different opponents, we split the Q value network into two parts: feature extractor $\mathcal{E}_\phi$ and decision maker $\mathcal{D}_{\psi_a}$. Specifically, the parameters of the Q value network Q_{θ^i} for agent i are divided into ϕ^i and ψ_a^i, i.e., $\theta^i = (\phi^i, \psi_a^i)$. The auxiliary opponent modeling task shares a common feature extractor $\mathcal{E}_{\phi^i}$ with the value network. We can update the parameters of $\mathcal{E}_{\phi^i}$ during execution using gradients from the auxiliary opponent modeling task, such that π_{θ^i} can generalize to different opponents. The supervised prediction head and its specific parameters are $\mathcal{D}_{\psi_s^i}$ with ψ_s^i. The details of our network architecture are provided in appendix B.

During training, the agent i can collect a set of transitions $\{(o_t^i, o_{t+1}^i, \mathbf{a}_t^{-i})\}_{t=0}^T$ where $\mathbf{a}_t^{-i}$ indicates the joint actions of other agents except i at time step t. We use the embeddings of agent i's observations o_t^i and o_{t+1}^i to predict the joint actions $\mathbf{a}_t^{-i}$, i.e., the $\mathcal{D}_{\psi_s^i}$ is a multi-head neural network whose outputs are multiple soft-max distributions over the action space of each other agent, and the objective function of the auxiliary opponent modeling task can be formulated as

$$\mathcal{L}\left(o_t^i, o_{t+1}^i, \mathbf{a}_t^{-i}; \phi^i, \psi_s^i\right) = \frac{1}{N-1} \sum_{j=1, j \neq i}^N \ell \left(a_t^j, \mathcal{D}_{\psi_s^i} \left(\mathcal{D}_{\psi_a^i} \left(o_t^i \right), \mathcal{D}_{\psi_a^i} \left(o_{t+1}^i \right) \right)^j \right), \tag{7}$$

where $\ell(\cdot)$ is the cross-entropy loss function. The strategies of opponents will change constantly during the procedure of multi-agent exploration and thus various strategies will emerge. The agent can leverage them to gain some experience about how to make the best response by jointly optimizing the auxiliary opponent modeling task and quantile value distribution. The joint training problem is therefore

$$\min_{\phi^i, \psi_s^i, \psi_a^i} \mathcal{J}\left(o_t^i, a_t^i, r_t^i, o_{t+1}^i; \phi^i, \psi_a^i\right) + \mathcal{L}\left(o_t^i, o_{t+1}^i, \mathbf{a}_t^{-i}; \phi^i, \psi_s^i\right) \tag{8}$$

4.3 Test-Time Policy Adaptation under Different Opponents

We assume the agent can observe actions made by his opponents during execution, so we can continue optimizing $\mathcal{J}$ to update the parameters of value network's feature extractor $\mathcal{E}_\phi$. Learning from opponents' past behaviors at test time makes the agent generalize his policy to different opponents efficiently. The can be formulated as

$$\min_{\phi^i, \psi_s^i} \mathcal{L}\left(o_t^i, o_{t+1}^i, \mathbf{a}_t^{-i}; \phi^i, \psi_s^i\right) \tag{9}$$

5 Experiments

In this section, we empirically evaluate our method on four multi-agent environments. In sec. 5.1 and 5.2 we introduce the four environments we use for experiments and describe the baseline methods. In sec. 5.3 we compare the performance of GRSP with other baselines. In sec. 5.4 we evaluate the generalization ability of GRSP under different opponents during execution. The ablations are studied in sec. 5.5. More details can be found in Appendix C.

5.1 Environment Setup

Repeated games. We consider two kinds of repeated matrix games: Iterated Stag Hunt (ISH) and Iterated Prisoners' Dilemma (IPD). Both of them consist two agents and a constant episode length of 10 time steps[12, 15, 19]. At each time step, the agents can choose either cooperation or defection. If both agents choose to cooperate simultaneously, they both get a bonus of 2. However, if a single agent choose to cooperate, he gets a penalty of -10 in ISH and -1 in IPD, and the other agent get a bonus of 1 and 3, respectively. If both agents choose to defection, they get a bonus of 1 in ISH and 0 in IPD. The optimal strategy in ISH and IPD is to cooperate at each time step, and the highest global payoffs of two agents are 40, i.e., 20 for each of them.

Monster-Hunt. The environment is a 5×5 grid-world, consisting of two agents, two apples and one monster. The apples are static while the monster keeps moving towards its closest agent. When a single agent meets the monster, he gets a penalty of -10. If two agents catch the monster together, they both get a bonus of 5. If a single agent meets an apple, he get a bonus of 2. Whenever an apple is eaten or the monster meets an agent, the entity will respawn randomly. The optimal strategy, i.e., both agents move towards and catch the monster, is a risky coordination strategy since an agent will receive a penalty if the other agent deceives.

Figure 2: Monster-Hunt.

Escalation. Escalation is a 5×5 grid-world with sparse rewards, consisting of two agents and a static light. If both agents step on the light simultaneously, they receive a bonus of 1, and then the light moves to a random adjacent grid. If only one agent steps on the light, he gets a penalty of $1.5L$, where L denotes the latest consecutive cooperation steps, and the light will respawn randomly. To maximize their individual payoffs and global rewards, agents must coordinate to stay together and step on the light grid. For each integer L, there is a corresponding coordination strategy where each agent follows the light for L steps then simultaneously stop coordination.

Figure 3: Escalation.

5.2 Baselines and Training

In this subsection, we introduce the baseline methods. We do not share parameters between agents, and more implementation details can be found in Appendix B.

Independent actor-critic (IAC). IAC is a decentralized multi-agent policy gradient method in which each agent learns policy and value networks based on his local observations and treat other agents as part of the environment.

Centralized training and decentralized execution (CTDE) methods. MADDPG[30] and MAPPO[31] are two kinds of multi-agent policy gradient methods which improve upon decentralized RL by adopting an actor-critic structure and learning a centralized critic. We implement the two algorithms based on their open-sourced codes and perform a limited grid-search over certain hyper-parameters, including learning rate, entropy bonus coefficient and buffer size (MADDPG).

Local information agent modelling (LIAM). LIAM[13] learns latent representations of the modeled agents from the local information of the controlled agent using encoder-decoder architecture. The modeled agent's observations and actions are utilized as reconstruction targets for the decoder, and the learned latent representation conditions the policy of the controlled agent in addition to its local observation. The policy and model are optimized based on A2C algorithm.

Training. We carry out our experiments on one NVIDIA RTX 3080 Ti and Intel i9-11900K.

Figure 4: Mean evaluation returns for GRSP, MADDPG, MAPPO, IAC and LIAM on two repeated matrix games. The average global rewards equal to 40 means that all agents have learned coordination strategy, i.e., cooperating at each time step.

5.3 Evaluation of Returns

In this subsection, we evaluate all methods on four multi-agent environments and use 5 different random seeds to train each method. We pause training every 50 episodes and run 30 independent episodes with each agent performing greedy action selection to evaluate the average performance of each method.

5.3.1 Iterated Games

Fig. 4 shows the average global rewards, i.e., the summation of all agents' average returns, of all methods evaluated during training in ISH and IPD environments. The shadowed part represents a 95% confidence interval. The average global rewards equal to 40 means that all agents have learned coordination strategy, i.e., cooperating at each time step. We can find that agents trained with our method can achieve mutual coordination in a sample efficient way in two repeated matrix games with high risk while other methods only converge to safe non-cooperative strategies though some of them have much more restrictive assumptions.

5.3.2 Grid-Worlds

We further show the effectiveness of GRSP in two grid-world games, Monster-Hunt and Escalation[15], both of which have high payoff but risky cooperation strategies for agents to converge to. Fig. 5. shows that, compared with other baseline methods, GRSP constantly and significantly outperform baselines with higher sample efficiency over the whole training process both in global rewards and agent's individual rewards. Specifically, in Monster-Hunt, GRSP agents efficiently find one of the risky cooperation strategies where two agents stay together and wait for the monster.

Furthermore, the policies learned by each agent are very stable and neither would like to deviate from the cooperative strategy. However, other baseline methods only converge to safe non-cooperative strategies and get low payoff due to their poor exploration. In Escalation, GRSP outperforms other baselines significantly and both agents have achieved coordination in a decentralized paradigm.

Figure 5: Mean evaluation returns for GRSP, MADDPG, MAPPO, IAC and LIAM on Monster-Hunt and Escalation. Global rewards are summation of both agents rewards.

5.4 Generalization Study

Table 1: Mean evaluation return of GRSP with and without auxiliary opponent modeling task on four multi-agent encironments.

Oppo: Coop(Defect)	ISH	IPD	M-H	Escalation
GRSP-No-Aom	$20(-100)$	$20(-5)$	$20.62(-15.03)$	$9.45(-0.545)$
GRSP-Aom	$\mathbf{20(0.65)}$	$\mathbf{20(-1.08)}$	$\mathbf{21.36(-12.07)}$	$\mathbf{11.3(0.175)}$

This subsection investigates how well the pre-trained GRSP agent can generalize to different opponents, i.e., cooperation or defection, during execution. The cooperative opponents are trained by GRSP method while the non-cooperative opponents are trained by MADDPG. During evaluation, random seeds of four environments are different from that during training, and hyperparameters of the GRSP are same and fixed between different opponent types. Furthermore, the pre-trained coordinated agents can not access to the rewards to update their policies anymore and they must utilize the auxiliary opponent modeling task to force them to adapt to different opponents. The network details and hyperparameters can be found in Appendix B.

Table 1 shows the mean evaluation return of GRSP agent with and without the auxiliary opponent modeling task on four multi-agent environments when interacting with different opponents. All returns are averaged on 100 episodes. The performance of the GRSP-Aom agent that utilizes the auxiliary opponent modeling task to adapt to different opponents outperforms that of the GRSP-No-Aom agent significantly, especially when interacting with non-cooperative opponents. Specifically, the GRSP-Aom agent using history behaviors of its opponents to update its policy can learn to alter its strategy from coordination to not when encountering a non-cooperative opponent. The empirical results further demonstrate that policies learned independently can overfit to the other agents' policies during training, and our auxiliary opponent modeling task provides a method to tackle this problem.

Figure 6: Mean evaluation return of GRSP compared with other ablation methods in two grid-world multi-agent environments.

5.5 Ablations

In this subsection, we perform an ablation study to examine the components of GRSP to better understand our method. GRSP is based on QR-DQN and has three components: the risk-seeking exploration bonus, the left truncated variance (Tv) and the auxiliary opponent modeling task (Aom). We design and evaluate six different ablations of GRSP in two grid-world environments, as show in Fig. 6. The performance of GRSP-No-Aom which we ablate the Aom module and retain all other features of our method is a little lower than that of GRSP but has a much higher variance, indicating that learning from opponent's behaviors can stable training and improve performance. Moreover, the GRSP-No-Aom is a completely decentralized method whose training without any opponent information, and the ablation results of GRSP-No-Aom show that our risk-seeking bonus is essential for agents to achieve mutual coordination in general-sum games. We observe that ablating the left truncated variance module leads to a significantly lower return than the GRSP in the Escalation but no difference in the Monster-Hunt. Furthermore, ablating the risk-seeking bonus increases the training variance, leads to slower convergence and perform worse than the GRSP. It is noteworthy that the Escalation is a sparse reward and hard-exploration multi-agent environment since our two decentralized agents can get a reward only if they navigate to and step on the light simultaneously and constantly. These two ablations indicate that the exploration ability of left truncated variance is important to our method and the risk-seeking bonus can encourage agents to coordinate with each other stably and converge to high-risky cooperation strategies efficiently. We also implement our risk-seeking bonus by CVaR instead of WT, and the results are shown as GRSP-CVaR. The GRSP-CVaR performs worse than our method and has a higher training variance. Finally, we ablate all components of the GRSP and use ϵ-greedy policy for exploration which leads to the IQR-DQN algorithm. As shown in Fig. 6, IQR-DQN can not learn effective policies in the Monster-Hunt and perform badly in the Escalation.

6 Discussion

Conclusion. While various MARL methods have been proposed in cooperative settings, few works investigate how self-interested learning agents can achieve mutual coordination which is coupled with risk in decentralized general-sum games and generalize learned policies to non-cooperative opponents during execution. In this paper, we present GRSP, a novel decentralized MARL algorithm with estimated risk-seeking bonus and auxiliary opponent modeling task. Empirically, we show that agents trained via GRSP can not only achieve mutual coordination during training with high sample efficiency but generalize learned policies to non-cooperative opponents during execution, while other baseline methods can not.

Limitations and future work. The risk-seeking bonus in GRSP is estimated using WT distorted expectation and its risk-sensitive level is a hyperparameter that can not dynamically change throughout training. Developing a method that can adjust agents' risk-sensitive levels dynamically by utilizing their observation, rewards, or opponents' information is the direction of our future work.

References

[1] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[2] Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

[3] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

[4] Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

[5] Arambam James Singh, Akshat Kumar, and Hoong Chuin Lau. Hierarchical multiagent reinforcement learning for maritime traffic management. 2020.

[6] Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

[7] Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[8] Tabish Rashid, Mikayel Samvelyan, Christian Schroeder, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 4295–4304. PMLR, 2018.

[9] Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Earl Hostallero, and Yung Yi. Qtran: Learning to factorize with transformation for cooperative multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 5887–5896. PMLR, 2019.

[10] Jianhao Wang, Zhizhou Ren, Terry Liu, Yang Yu, and Chongjie Zhang. Qplex: Duplex dueling multi-agent q-learning. *arXiv preprint arXiv:2008.01062*, 2020.

[11] Wei Qiu, Xinrun Wang, Runsheng Yu, Rundong Wang, Xu He, Bo An, Svetlana Obraztsova, and Zinovi Rabinovich. Rmix: Learning risk-sensitive policies forcooperative reinforcement learning agents. *Advances in Neural Information Processing Systems*, 34, 2021.

[12] Jakob N Foerster, Richard Y Chen, Maruan Al-Shedivat, Shimon Whiteson, Pieter Abbeel, and Igor Mordatch. Learning with opponent-learning awareness. *arXiv preprint arXiv:1709.04326*, 2017.

[13] Georgios Papoudakis, Filippos Christianos, and Stefano Albrecht. Agent modelling under partial observability for deep reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[14] Richard Mealing and Jonathan L Shapiro. Opponent modeling by expectation–maximization and sequence prediction in simplified poker. *IEEE Transactions on Computational Intelligence and AI in Games*, 9(1):11–24, 2015.

[15] Zhenggang Tang, Chao Yu, Boyuan Chen, Huazhe Xu, Xiaolong Wang, Fei Fang, Simon Du, Yu Wang, and Yi Wu. Discovering diverse multi-agent strategic behavior via reward randomization. *arXiv preprint arXiv:2103.04564*, 2021.

[16] Alexander Peysakhovich and Adam Lerer. Prosocial learning agents solve generalized stag hunts better than selfish ones. *arXiv preprint arXiv:1709.02865*, 2017.

[17] Behrad Toghi, Rodolfo Valiente, Dorsa Sadigh, Ramtin Pedarsani, and Yaser P Fallah. Social coordination and altruism in autonomous driving. *arXiv preprint arXiv:2107.00200*, 2021.

[18] Hirokazu Shirado and Nicholas A Christakis. Locally noisy autonomous agents improve global human coordination in network experiments. *Nature*, 545(7654):370–374, 2017.

[19] Woodrow Z Wang, Mark Beliaev, Erdem Bıyık, Daniel A Lazar, Ramtin Pedarsani, and Dorsa Sadigh. Emergent prosociality in multi-agent games through gifting. *arXiv preprint arXiv:2105.06593*, 2021.

[20] Weixun Wang, Jianye Hao, Yixi Wang, and Matthew Taylor. Towards cooperation in sequential prisoner's dilemmas: a deep multiagent reinforcement learning approach. *arXiv preprint arXiv:1803.00162*, 2018.

[21] Will Dabney, Georg Ostrovski, David Silver, and Rémi Munos. Implicit quantile networks for distributional reinforcement learning. In *International conference on machine learning*, pages 1096–1105. PMLR, 2018.

[22] Ardi Tampuu, Tambet Matiisen, Dorian Kodelja, Ilya Kuzovkin, Kristjan Korjus, Juhan Aru, Jaan Aru, and Raul Vicente. Multiagent cooperation and competition with deep reinforcement learning. *PloS one*, 12(4):e0172395, 2017.

[23] Aditya Grover, Maruan Al-Shedivat, Jayesh Gupta, Yuri Burda, and Harrison Edwards. Learning policy representations in multiagent systems. In *International conference on machine learning*, pages 1802–1811. PMLR, 2018.

[24] Georgios Papoudakis and Stefano V Albrecht. Variational autoencoders for opponent modeling in multi-agent systems. *arXiv preprint arXiv:2001.10829*, 2020.

[25] Shaun S Wang. A class of distortion operators for pricing financial and insurance risks. *Journal of risk and insurance*, pages 15–36, 2000.

[26] Marc Lanctot, Vinicius Zambaldi, Audrunas Gruslys, Angeliki Lazaridou, Karl Tuyls, Julien Pérolat, David Silver, and Thore Graepel. A unified game-theoretic approach to multiagent reinforcement learning. *Advances in neural information processing systems*, 30, 2017.

[27] Roger Koenker and Gilbert Bassett Jr. Regression quantiles. *Econometrica: journal of the Econometric Society*, pages 33–50, 1978.

[28] Will Dabney, Mark Rowland, Marc Bellemare, and Rémi Munos. Distributional reinforcement learning with quantile regression. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

[29] Zihan Zhou, Wei Fu, Bingliang Zhang, and Yi Wu. Continuously discovering novel strategies via reward-switching policy optimization. In *Deep RL Workshop NeurIPS 2021*, 2021.

[30] Ryan Lowe, Yi I Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *Advances in neural information processing systems*, 30, 2017.

[31] Chao Yu, Akash Velu, Eugene Vinitsky, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of ppo in cooperative, multi-agent games. *arXiv preprint arXiv:2103.01955*, 2021.

[32] Filippos Christianos, Lukas Schäfer, and Stefano Albrecht. Shared experience actor-critic for multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 33: 10707–10717, 2020.

[33] Woodrow Zhouyuan Wang, Andy Shih, Annie Xie, and Dorsa Sadigh. Influencing towards stable multi-agent interactions. In *Conference on Robot Learning*, pages 1132–1143. PMLR, 2022.

[34] Georgios Papoudakis, Filippos Christianos, Arrasy Rahman, and Stefano V Albrecht. Dealing with non-stationarity in multi-agent deep reinforcement learning. *arXiv preprint arXiv:1906.04737*, 2019.

[35] Pablo Hernandez-Leal, Michael Kaisers, Tim Baarslag, and Enrique Munoz de Cote. A survey of learning in multiagent environments: Dealing with non-stationarity. *arXiv preprint arXiv:1707.09183*, 2017.

[36] Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, pages 449–458. PMLR, 2017.

[37] Jared Markowitz, Ryan Gardner, Ashley Llorens, Raman Arora, and I-Jeng Wang. A risk-sensitive policy gradient method. 2021.

[38] Dotan Di Castro, Aviv Tamar, and Shie Mannor. Policy gradients with variance related risk criteria. *arXiv preprint arXiv:1206.6404*, 2012.

[39] Xiaoteng Ma, Li Xia, Zhengyuan Zhou, Jun Yang, and Qianchuan Zhao. Dsac: Distributional soft actor critic for risk-sensitive reinforcement learning. *arXiv preprint arXiv:2004.14547*, 2020.

[40] LA Prashanth and Mohammad Ghavamzadeh. Variance-constrained actor-critic algorithms for discounted and average reward mdps. *Machine Learning*, 105(3):367–417, 2016.

[41] R Tyrrell Rockafellar and Stanislav Uryasev. Conditional value-at-risk for general loss distributions. *Journal of banking & finance*, 26(7):1443–1471, 2002.

[42] Yinlam Chow, Aviv Tamar, Shie Mannor, and Marco Pavone. Risk-sensitive and robust decision-making: a cvar optimization approach. *Advances in neural information processing systems*, 28, 2015.

[43] Xueguang Lyu and Christopher Amato. Likelihood quantile networks for coordinating multi-agent reinforcement learning. *arXiv preprint arXiv:1812.06319*, 2018.

[44] Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning. *arXiv preprint arXiv:1706.05296*, 2017.

[45] Alexander Peysakhovich and Adam Lerer. Consequentialist conditional cooperation in social dilemmas with imperfect information. *arXiv preprint arXiv:1710.06975*, 2017.

[46] Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts. In *International Conference on Machine Learning*, pages 9229–9248. PMLR, 2020.

[47] Nicklas Hansen, Rishabh Jangir, Yu Sun, Guillem Alenyà, Pieter Abbeel, Alexei A Efros, Lerrel Pinto, and Xiaolong Wang. Self-supervised policy adaptation during deployment. *arXiv preprint arXiv:2007.04309*, 2020.

[48] Peter Stone, Gal A Kaminka, Sarit Kraus, and Jeffrey S Rosenschein. Ad hoc autonomous agent teams: Collaboration without pre-coordination. In *Twenty-Fourth AAAI Conference on Artificial Intelligence*, 2010.

[49] Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E Gonzalez, and Yuandong Tian. Multi-agent collaboration via reward attribution decomposition. *arXiv preprint arXiv:2010.08531*, 2020.

[50] Stefano V Albrecht and Peter Stone. Autonomous agents modelling other agents: A comprehensive survey and open problems. *Artificial Intelligence*, 258:66–95, 2018.

[51] Zhikun Wang, Katharina Mülling, Marc Peter Deisenroth, Heni Ben Amor, David Vogt, Bernhard Schölkopf, and Jan Peters. Probabilistic movement modeling for intention inference in human–robot interaction. *The International Journal of Robotics Research*, 32(7):841–858, 2013.

[52] Roberta Raileanu, Emily Denton, Arthur Szlam, and Rob Fergus. Modeling others using oneself in multi-agent reinforcement learning. In *International conference on machine learning*, pages 4257–4266. PMLR, 2018.

[53] Dylan P Losey, Mengxi Li, Jeannette Bohg, and Dorsa Sadigh. Learning from my partner's actions: Roles in decentralized robot teams. In *Conference on robot learning*, pages 752–765. PMLR, 2020.

[54] Chongjie Zhang and Victor Lesser. Multi-agent learning with policy prediction. In *Twenty-fourth AAAI conference on artificial intelligence*, 2010.

[55] Lloyd S Shapley. Stochastic games. *Proceedings of the national academy of sciences*, 39(10): 1095–1100, 1953.

[56] Eric A Hansen, Daniel S Bernstein, and Shlomo Zilberstein. Dynamic programming for partially observable stochastic games. In *AAAI*, volume 4, pages 709–715, 2004.

[57] Peter J Huber. Robust estimation of a location parameter. In *Breakthroughs in statistics*, pages 492–518. Springer, 1992.

[58] Julia L Wirch and Mary R Hardy. Distortion risk measures: Coherence and stochastic dominance. In *International congress on insurance: Mathematics and economics*, pages 15–17, 2001.

[59] Alejandro Balbás, José Garrido, and Silvia Mayoral. Properties of distortion risk measures. *Methodology and Computing in Applied Probability*, 11(3):385–399, 2009.

[60] Borislav Mavrin, Hengshuai Yao, Linglong Kong, Kaiwen Wu, and Yaoliang Yu. Distributional reinforcement learning for efficient exploration. In *International conference on machine learning*, pages 4424–4434. PMLR, 2019.

[61] Roger Koenker and Kevin F Hallock. Quantile regression. *Journal of economic perspectives*, 15(4):143–156, 2001.