Topological Continual Learning
with Wasserstein Distance and Barycenter

Abstract

Continual learning in neural networks suffers from a phenomenon called catastrophic forgetting, in which a network quickly forgets what was learned in a previous task. The human brain, however, is able to continually learn new tasks and accumulate knowledge throughout life. Neuroscience findings suggest that continual learning success in the human brain is potentially associated with its modular structure and memory consolidation mechanisms. In this paper we propose a novel topological regularization that penalizes cycle structure in a neural network during training using principled theory from persistent homology and optimal transport. The penalty encourages the network to learn modular structure during training. The penalization is based on the closed-form expressions of the Wasserstein distance and barycenter for the topological features of a 1-skeleton representation for the network. Our topological continual learning method combines the proposed regularization with a tiny episodic memory to mitigate forgetting. We demonstrate that our method is effective in both shallow and deep network architectures for multiple image classification datasets.

1 Introduction

Persistent homology (Edelsbrunner et al., 2000) has emerged as a tool for understanding, characterizing and quantifying the topology of brain networks by interpreting brain networks as 1-skeletons of a simplicial complex (Songdechakraiwut et al., 2021, 2022). The topology of a 1-skeleton is *completely* characterized by connected components and cycles. In this paper we show that persistent homology can be used to improve performance of neural networks in continual learning tasks. In particular, we interpret a network as a 1-skeleton and propose a novel *topological regularization* of the 1-skeleton's cycle structure to avoid catastrophic forgetting of previously learned tasks. Regularizing the cycle structure allows the network to explicitly learn its complement, i.e., the modular structure, through gradient optimization. Our approach is made computationally efficient by use of the closed form expressions for the Wasserstein barycenter and the gradient of Wasserstein distance between network cycle structures. We evaluate our approach using image classification across multiple data sets and show that it generally improves classification performance compared to competing approaches in the challenging case of both shallow and deep networks of limited width.

2 Efficient Computation of Topology for Network Graphs

Graph Filtration Represent a neural network as an undirected weighted graph $G = (V, \mathbb{W})$ with a set of nodes V, and a set of edge weights $\mathbb{W} = \{w_{i,j}\}$. The number of nodes and weights are denoted

Submitted to the 6th Workshop on Meta-Learning at NeurIPS 2022, New Orleans. Do not distribute.

Figure 1: Illustration of graph filtration. A toy neural network G showing its maximum spanning tree (MST) as edges denoted by dark lines and a subnetwork with non-MST edges shown as dashed lines. As the filtration value increases, the number of connected components β_0 monotonically increases while the number of cycles β_1 monotonically decreases. Connected components are born at the MST edge weights e_2, e_4, e_5, e_6 while cycles die at the non-MST edge weights e_1, e_3.

by $|V|$ and $|\mathbb{W}|$, respectively. Create a binary graph G_ϵ with the identical node set V by thresholding the edge weights so that an edge between nodes i and j exists if $w_{i,j} > \epsilon$. The binary graph is a simplicial complex consisting of only nodes and edges known as a *1-skeleton* (Munkres, 1996). As ϵ increases, more and more edges are removed from the network G, resulting in a nested sequence of 1-skeletons: $G_{\epsilon_0} \supseteq G_{\epsilon_1} \supseteq \cdots \supseteq G_{\epsilon_k}$, where $\epsilon_0 \leq \epsilon_1 \leq \cdots \leq \epsilon_k$ are called filtration values. This sequence of 1-skeletons is called a *graph filtration* (Lee et al., 2012).

Birth and Death Decomposition The only non-trivial topological features in a 1-skeleton are *connected components* and *cycles*. Persistent homology keeps track of the birth and death of topological features over filtration values ϵ. If a topological feature is born at a filtration value b_l and persists up to a filtration value d_l, then this feature is represented as a two-dimensional *persistence point* (b_l, d_l) in a plane. The set of all points $\{(b_l, d_l)\}_l$ is called *persistence barcode* (Ghrist, 2008). The use of the 1-skeleton simplifies the persistence barcodes to one-dimensional descriptors (Songdechakraiwut et al., 2021). Specifically, the representation of the connected components can be simplified to a collection of *birth values* $\mathbb{B}(G) = \{b_l\}$ and that of cycles to a collection of *death values* $\mathbb{D}(G) = \{d_l\}$. In addition, neural networks of the same architecture have a birth set $\mathbb{B}$ and a death set $\mathbb{D}$ of the *same* cardinality as $|V| - 1$ and $|\mathbb{W}| - (|V| - 1)$, respectively. This result completely resolves the problem of point mismatch in persistence barcodes for same-architecture neural networks. The example network of Fig. 1 has $\mathbb{W} = \{e_i\}_{i=1}^6$, $\mathbb{B}(G) = \{e_2, e_4, e_5, e_6\}$ and $\mathbb{D}(G) = \{e_1, e_3\}$. Supplementary description of the decomposition is provided in Appendix A.

Closed Form Wasserstein Distance and Gradient The Wasserstein distance between 1-skeleton network representations has a closed-form expression. Here we only consider the Wasserstein distance for cycle structure, which depends solely on the death sets. Let G, H be two given networks based on the same architecture. Their (squared) *2-Wasserstein distance for cycles* is defined as the optimal matching cost between $\mathbb{D}(G)$ and $\mathbb{D}(H)$. That is, $W_{cycle}^2(G, H) = \min_\phi \sum_{d_l \in \mathbb{D}(G)} \left[d_l - \phi(d_l) \right]^2$, where ϕ is a bijection from $\mathbb{D}(G)$ to $\mathbb{D}(H)$. This Wasserstein distance form has a closed-form expression that allows for very efficient computation (Rabin et al., 2011) as

$$W_{cycle}^2(G, H) = \sum_{d_l \in \mathbb{D}(G)} \left[d_l - \phi^*(d_l) \right]^2,$$

where ϕ^* maps the l-th smallest death value in $\mathbb{D}(G)$ to the l-th smallest death value in $\mathbb{D}(H)$ for all l. In addition, the gradient of the Wasserstein distance for cycles $\nabla_G W_{cycle}^2(G, H)$ also has a closed-form expression as (Songdechakraiwut et al., 2022) $\partial W_{cycle}^2(G, H)/\partial d_l = 2\left[d_l - \phi^*(d_l) \right]$. Supplementary description of the closed form expressions is provided in Appendix A.

Closed Form Wasserstein Barycenter The Wasserstein barycenter is the mean of a collection of networks under the Wasserstein distance and represents the topological centroid. Consider same-architecture networks $G^{(1)}, ..., G^{(N)}$. Let $\mathbb{D}(G^{(i)}) : d_1^{(i)} \leq \cdots \leq d_{|\mathbb{D}|}^{(i)}$ be the death set of network $G^{(i)}$. The *Wasserstein barycenter for cycles* $\mathcal{G}_{cycle}$ has a closed form expression as

67    $\mathcal{G}_{cycle} : \overline{d}_1 \leq \cdots \leq \overline{d}_{|\mathbb{D}|}$, where $\overline{d}_l = \sum_{i=1}^N \nu_i d_l^{(i)} \big/ \sum_{i=1}^N \nu_i$. The complete proof is given in
68   Appendix D.

3   Topology Based Continual Learning

70 Consider a *continual learning* scenario in which T supervised learning tasks are learned sequen-
71 tially. Each task has a task descriptor $\tau \in \mathbb{T} = \{1, 2, ..., T\}$ with a corresponding dataset
72 $\mathbb{P}_\tau = \{(\boldsymbol{x}_{i,\tau}, \boldsymbol{y}_{i,\tau})_{i=1}^{N_\tau}\}$ containing N_τ labeled training examples consisting of a feature vector
73 $\boldsymbol{x}_{i,\tau} \in \mathcal{X}$ and a target vector $\boldsymbol{y}_{i,\tau} \in \mathcal{Y}$. We further consider the continuum of training examples that
74 are experienced *only once*, and assume that the continuum is *locally independent and identically*
75 *distributed* (iid), i.e., $(\boldsymbol{x}_{i,\tau}, \boldsymbol{y}_{i,\tau}) \overset{iid}{\sim} P_\tau$ following the prior work of Lopez-Paz & Ranzato (2017).
76 The goal is to train a model $f : \mathcal{X} \times \mathbb{T} \to \mathcal{Y}$ that predicts a target vector $\boldsymbol{y}$ corresponding to a test
77 pair $(\boldsymbol{x}, \tau)$, where $(\boldsymbol{x}, \boldsymbol{y}) \sim P_\tau$.

78 Our approach to addressing this problem is to topologically penalize training with future tasks based
79 on the underlying 1-skeleton of the neural network. Define a neural network $G^{(\tau)}$ for learning task τ
80 with nodes given by neurons, and edge weights defined by the weight/parameter set $\mathbb{W}$. All past-task
81 networks $G^{(j)}$, for $j = 1, ..., \tau - 1$, have the identical node sets with the trained weight set $\mathbb{W}_j^*$
82 denoting the weights after training through the entire sequence up to task j. Since these graphs
83 have the same architecture, their death sets have the same cardinality denoted by $|\mathbb{D}|$. Then the
84 birth-death decomposition of the weight set $\mathbb{W}_j^*$ results in the death set $\mathbb{D}(G^{(j)}) : d_1^{(j)} \leq \cdots \leq d_{|\mathbb{D}|}^{(j)}$.
85 The Wasserstein barycenter for cycles of the first $\tau - 1$ training tasks associated with networks
86 $G^{(1)}, ..., G^{(\tau-1)}$ is

$$\mathcal{G}_{cycle}^{(\tau-1)} : \overline{d}_1^{(\tau-1)} \leq \cdots \leq \overline{d}_{|\mathbb{D}|}^{(\tau-1)},$$

87 where $\overline{d}_l^{(\tau-1)} = \sum_{j=1}^{\tau-1} \nu_j d_l^{(j)} \big/ \sum_{j=1}^{\tau-1} \nu_j$. Our approach to learning task τ minimizes the empirical
88 risk minimization loss (ERM) with the Wasserstein distance and barycenter penalty

$$\mathcal{L}_\tau(\mathbb{W}) = \mathcal{L}_{ERM,\tau}(\mathbb{W}) + \frac{\lambda}{2} W_{cycle}^2(G^{(\tau)}, \mathcal{G}_{cycle}^{(\tau-1)}) \quad \text{for all task } \tau > 1,$$

89 where λ controls relative importance between past- and current-task cycle structure. Intuitively, we
90 penalize changes of cycle structure in a neural network while allowing the network to explicitly learn
91 the modular structure represented by births of connected components. Complete description of the
92 topology based continual learning is provided in Appendix B.

4   Image Classification Experiments

94 **Datasets**   We perform continual learning experiments on four datasets: (1) *Permuted MNIST* (P-
95 MNIST) (Kirkpatrick et al., 2017), (2) *Rotated MNIST* (R-MNIST) (Lopez-Paz & Ranzato, 2017),
96 (3) *Split CIFAR* (Krizhevsky, 2009) and (4) *split miniImageNet* (Russakovsky et al., 2015; Vinyals
97 et al., 2016). Complete description of each dataset is provided in Appendix C.

98 **Network architecture**   The P-MNIST and R-MNIST datasets use a fully-connected neural network
99 with two hidden layers each with 128 neurons. The split CIFAR and split miniImageNet datasets use
100 a downsized version of ResNet18 (He et al., 2016) with eight times fewer feature maps across all
101 layers, similar to (Lopez-Paz & Ranzato, 2017).

102 **Method comparison**   We evaluate our method performance in relative to eight baseline approaches
103 that learn a sequence of tasks in a fixed-size network architecture: (1) *finetune*, i.e., a model trained
104 sequentially without any regularization and past-task episodic memory, (2) *elastic weight consolida-*
105 *tion* (EWC) (Kirkpatrick et al., 2017), (3) *recursive gradient optimization* (RGO) (Liu & Liu, 2022),
106 (4) *averaged gradient episodic memory* (A-GEM) (Chaudhry et al., 2019a), (5) ORTHOG-SUB
107 (Chaudhry et al., 2020), (6) *experience replay* (Chaudhry et al., 2019b) with *reservoir sampling*
108 (Vitter, 1985) (ER-Res), (7) ER with *ring buffer* (ER-Ring) (Lopez-Paz & Ranzato, 2017) and (8)
109 *multitask* method that jointly learns the entire dataset in one training round and thus is not a continual

Table 1: ACC and BWT performance for P-MNIST, R-MNIST, split CIFAR and split miniImageNet datasets. The mean and standard deviation over five different task sequences are shown.

		P-MNIST		R-MNIST	
Methods	Memory	ACC (%)	BWT (%)	ACC (%)	BWT (%)
Finetune	N	34.44 ± 2.07	-58.89 ± 2.23	41.43 ± 2.09	-55.42 ± 2.09
EWC	N	48.05 ± 1.27	-44.55 ± 1.46	39.80 ± 2.01	-55.26 ± 2.03
RGO	N	73.18 ± 0.57	-19.86 ± 0.61	63.34 ± 0.96	-29.30 ± 0.95
A-GEM	Y	59.50 ± 1.20	-33.63 ± 1.24	53.38 ± 0.90	-43.35 ± 0.93
ORTHOG-SUB	Y	42.83 ± 1.22	-9.94 ± 1.05	23.85 ± 0.84	-3.45 ± 1.08
ER-Res	Y	66.38 ± 1.29	-25.02 ± 1.51	72.54 ± 0.36	-23.48 ± 0.39
ER-Ring	Y	70.10 ± 0.89	-23.19 ± 1.01	70.52 ± 0.51	-25.72 ± 0.51
TOP-Res	Y	68.13 ± 0.66	-24.50 ± 0.66	74.33 ± 0.66	-20.80 ± 0.63
TOP-Ring	Y	71.05 ± 0.80	-22.18 ± 0.86	72.12 ± 0.81	-23.85 ± 0.84
Multitask	–	90.31	–	93.43	–
		Split CIFAR		Split miniImageNet	
Methods	Memory	ACC (%)	BWT (%)	ACC (%)	BWT (%)
Finetune	N	40.62 ± 5.09	-23.80 ± 5.31	33.13 ± 2.72	-24.95 ± 2.30
EWC	N	38.26 ± 3.71	-25.30 ± 4.57	33.48 ± 1.79	-19.56 ± 2.24
RGO	N	38.93 ± 1.03	-18.98 ± 0.89	42.03 ± 1.22	-14.19 ± 1.56
A-GEM	Y	43.54 ± 6.23	-23.25 ± 5.65	39.52 ± 4.10	-18.48 ± 4.39
ORTHOG-SUB	Y	37.93 ± 1.59	-5.44 ± 1.37	32.36 ± 1.44	-5.52 ± 1.07
ER-Res	Y	43.28 ± 1.26	-23.08 ± 1.51	38.51 ± 2.40	-13.58 ± 3.49
ER-Ring	Y	52.75 ± 1.18	-14.51 ± 1.79	44.67 ± 1.81	-12.23 ± 1.79
TOP-Res	Y	45.92 ± 1.50	-20.10 ± 1.00	39.95 ± 1.91	-14.34 ± 2.06
TOP-Ring	Y	54.27 ± 1.54	-11.70 ± 1.27	49.08 ± 1.71	-8.42 ± 1.48
Multitask	–	61.08	–	57.99	–

learning strategy but served as an upper bound reference for other methods. We employ our proposed topological regularization with reservoir sampling and ring buffer strategies, termed TOP-Res and TOP-Ring.

Continual learning evaluation We evaluate the algorithms based on two performance measures: average accuracy (ACC) and backward transfer (BWT) as proposed by Lopez-Paz & Ranzato (2017). Formally, ACC and BWT are defined as $\text{ACC} = \frac{1}{T} \sum_{j=1}^{T} R_{T,j}$, $\text{BWT} = \frac{1}{T-1} \sum_{j=1}^{T-1} R_{T,j} - R_{j,j}$, where T is the total number of sequential tasks, and $R_{i,j}$ is the accuracy of the model on the j^{th} task after learning the i^{th} task in sequence. We report ACC and BWT averaged over five different task sequences for each dataset. We follow the training protocol of Chaudhry et al. (2020). Complete description of the protocol is provided in Appendix C.4.

Experimental results Table 1 shows method performance on all four datasets (see Appendix C for complete experimental results). *Finetune* without any continual learning strategy produces lowest ACC and BWT performance, while the oracle *multitask* is trained across all tasks and sets the upper bound ACC performance for all datasets. Gradient-based RGO and ORTHOG-SUB rely on over-parameterization in a neural network to reduce interference between tasks. Given the long sequence of tasks and small network architecture in our experiments, it is likely that over-parameterization is insufficient for strong performance. Although ORTHOG-SUB achieves highest BWT, it also has the lowest ACC scores, in some cases worse than *Finetune*. ER-Res and ER-Ring achieve high ACC and BWT scores relative to the other baseline methods across all experiments. Our TOP-Res and TOP-Ring methods in turn demonstrate clear performance improvement over ER-Res and ER-Ring based on both ACC and BWT, suggesting that our topological continual learning strategy facilitates the consolidation of past-task knowledge beyond that provided by memory replay alone.

References

Serguei Barannikov. The framed Morse complex and its invariants. *Advances in Soviet Mathematics, American Mathematical Society*, 1994.

Danielle S Bassett, Nicholas F Wymbs, Mason A Porter, Peter J Mucha, Jean M Carlson, and Scott T Grafton. Dynamic reconfiguration of human brain networks during learning. *Proceedings of the National Academy of Sciences*, 108(18):7641–7646, 2011. doi: 10.1073/pnas.1018985108.

Ed Bullmore and Olaf Sporns. Complex brain networks: Graph theoretical analysis of structural and functional systems. *Nature Reviews Neuroscience*, 10(3):186–198, 2009.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with A-GEM. In *International Conference on Learning Representations*, 2019a.

Arslan Chaudhry, Marcus Rohrbach, Mohamed Elhoseiny, Thalaiyasingam Ajanthan, Puneet K Dokania, Philip HS Torr, and Marc'Aurelio Ranzato. On tiny episodic memories in continual learning. *arXiv preprint arXiv:1902.10486*, 2019b.

Arslan Chaudhry, Naeemullah Khan, Puneet Dokania, and Philip Torr. Continual learning in low-rank orthogonal subspaces. In *Advances in Neural Information Processing Systems*, volume 33, pp. 9900–9911. Curran Associates, Inc., 2020.

Herbert Edelsbrunner and John Harer. Persistent homology–a survey. *Contemporary Mathematics*, 453:257–282, 2008.

Herbert Edelsbrunner, David Letscher, and Afra Zomorodian. Topological persistence and simplification. In *Proceedings 41st Annual Symposium on Foundations of Computer Science*, pp. 454–463. IEEE, 2000.

Karolina Finc, Kamil Bonna, Xiaosong He, David M Lydon-Staley, Simone Kühn, Włodzisław Duch, and Danielle S Bassett. Dynamic reconfiguration of functional brain networks during working memory training. *Nature Communications*, 11(1):1–15, 2020.

Robert Ghrist. Barcodes: The persistent topology of data. *Bulletin of the American Mathematical Society*, 45(1):61–75, 2008.

Corey B Hart and Simon F Giszter. A neural basis for motor primitives in the spinal cord. *Journal of Neuroscience*, 30(4):1322–1336, 2010. doi: 10.1523/JNEUROSCI.5894-08.2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Christopher J Honey, Rolf Kötter, Michael Breakspear, and Olaf Sporns. Network structure of cerebral cortex shapes functional connectivity on multiple time scales. *Proceedings of the National Academy of Sciences*, 104(24):10240–10245, 2007.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017. doi: 10.1073/pnas.1611835114.

Jens G Klinzing, Niels Niethard, and Jan Born. Mechanisms of systems memory consolidation during sleep. *Nature Neuroscience*, 22(10):1598–1610, 2019.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Joseph B Kruskal. On the shortest spanning subtree of a graph and the traveling salesman problem. *Proceedings of the American Mathematical society*, 7(1):48–50, 1956.

Yung-Keun Kwon and Kwang-Hyun Cho. Analysis of feedback loops and robustness in network evolution based on boolean models. *BMC Bioinformatics*, 8(1):1–9, 2007.

Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998. doi: 10.1109/5.726791.

Hyekyoung Lee, Hyejin Kang, Moo K. Chung, Bung-Nyun Kim, and Dong Soo Lee. Persistent brain network homology from the perspective of dendrogram. *IEEE Transactions on Medical Imaging*, 31(12):2267–2277, 2012. doi: 10.1109/TMI.2012.2219590.

Xilai Li, Yingbo Zhou, Tianfu Wu, Richard Socher, and Caiming Xiong. Learn to grow: A continual structure learning framework for overcoming catastrophic forgetting. In *International Conference on Machine Learning*, pp. 3925–3934. PMLR, 2019.

Hao Liu and Huaping Liu. Continual learning with recursive gradient optimization. In *International Conference on Learning Representations*, 2022.

David Lopez-Paz and Marc' Aurelio Ranzato. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. volume 24 of *Psychology of Learning and Motivation*, pp. 109–165. Academic Press, 1989. doi: 10.1016/S0079-7421(08)60536-8.

James L McGaugh. Memory–a century of consolidation. *Science*, 287(5451):248–251, 2000.

James R Munkres. *Elements Of Algebraic Topology*. Avalon Publishing, 1996. ISBN 9780201627282.

Nina Otter, Mason A Porter, Ulrike Tillmann, Peter Grindrod, and Heather A Harrington. A roadmap for the computation of persistent homology. *EPJ Data Science*, 6, 2017. doi: 10.1140/epjds/s13688-017-0109-5.

Ertugrul M Ozbudak, Attila Becskei, and Alexander Van Oudenaarden. A system of counteracting feedback loops regulates Cdc42p activity during spontaneous cell polarization. *Developmental Cell*, 9(4):565–571, 2005.

Robert Clay Prim. Shortest connection networks and some generalizations. *The Bell System Technical Journal*, 36(6):1389–1401, 1957.

Julien Rabin, Gabriel Peyré, Julie Delon, and Marc Bernot. Wasserstein barycenter and its application to texture mixing. In *Scale Space and Variational Methods in Computer Vision*, pp. 435–446. Springer, 2011.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. iCaRL: Incremental classifier and representation learning. In *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, pp. 2001–2010, 2017.

Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, , and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference. In *International Conference on Learning Representations*, 2019.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C Berg, and Li Fei-Fei. ImageNet large scale visual recognition challenge. *International Journal of Computer Vision*, 115(3):211–252, 2015.

Joan Serra, Didac Suris, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *International Conference on Machine Learning*, pp. 4548–4557. PMLR, 2018.

Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Herbert A Simon. The architecture of complexity. *Proceedings of the American Philosophical Society*, 106, 1962.

Tananun Songdechakraiwut, Li Shen, and Moo Chung. Topological learning and its application to multimodal brain network integration. In *Medical Image Computing and Computer Assisted Intervention – MICCAI 2021*, pp. 166–176, Cham, 2021. Springer International Publishing. ISBN 978-3-030-87196-3.

Tananun Songdechakraiwut, Bryan M Krause, Matthew I Banks, Kirill V Nourski, and Barry D Van Veen. Fast topological clustering with Wasserstein distance. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=0kPL3xO4R5`.

Vladimir Vapnik. Principles of risk minimization for learning theory. In *Advances in Neural Information Processing Systems*, volume 4. Morgan-Kaufmann, 1991.

KV Venkatesh, Sharad Bhartiya, and Anurag Ruhela. Multiple feedback loops are key to a robust dynamic performance of tryptophan regulation in Escherichia coli. *FEBS Letters*, 563(1-3): 234–240, 2004.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, koray kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

Jeffrey S Vitter. Random sampling with a reservoir. *ACM Trans. Math. Softw.*, 11(1):37–57, 1985. doi: 10.1145/3147.3165.

Larry Wasserman. Topological data analysis. *Annual Review of Statistics and Its Application*, 5: 501–532, 2018.

Orion D Weiner, Paul O Neilsen, Glenn D Prestwich, Marc W Kirschner, Lewis C Cantley, and Henry R Bourne. A PtdInsP 3-and Rho GTPase-mediated positive feedback loop regulates neutrophil polarity. *Nature Cell Biology*, 4(7):509–513, 2002.

Ju Xu and Zhanxing Zhu. Reinforced continual learning. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

Jaehong Yoon, Eunho Yang, Jeongtae Lee, and Sung Ju Hwang. Lifelong learning with dynamically expandable networks. In *International Conference on Learning Representations*, 2018.

Jaehong Yoon, Saehoon Kim, Eunho Yang, and Sung Ju Hwang. Scalable and order-robust continual learning with additive parameter decomposition. In *International Conference on Learning Representations*, 2020.

Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *International Conference on Machine Learning*, pp. 3987–3995. PMLR, 2017.

Afra Zomorodian. Fast construction of the Vietoris-Rips complex. *Computers & Graphics*, 34(3): 263–271, 2010.

A

A.1 Motivation

Neural networks can be trained to achieve impressive performance on a variety of learning tasks. However, when an already trained network is further trained on a new task, a phenomenon called *catastrophic forgetting* (McCloskey & Cohen, 1989) occurs, in which previously learned tasks are

Figure 2: Schematic illustrating our topological continual learning approach. A tiny episodic memory replays past examples from previously learned tasks. The cycle topology of a subset of layers (shaded) is regularized based on the Wasserstein distance between the network and barycenter of previously learned networks to improve the generalization of the learning and memory consolidation processes.

quickly forgotten with additional training. The human brain, however, is able to continually learn new tasks and accumulate knowledge throughout life without significant loss of previously learned skills. The biological mechanisms behind this trait are not yet fully understood. Neuroscience findings suggest that the principle of modularity (Hart & Giszter, 2010) may play an important role. Modular structures (Simon, 1962) are aggregates of modules (components) that perform specific functions without perturbing one another. Human brains have been characterized by modular structures during learning (Finc et al., 2020). Such structures are hypothesized to reduce the interdependence of components, enhance robustness, and facilitate learning (Bassett et al., 2011). Another important learning mechanism is the hippocampal and neocortical interaction responsible for memory consolidation (McGaugh, 2000). In particular, the hippocampal system encodes recent experiences that later are replayed multiple times before consolidation as episodic memory in the neocortex (Klinzing et al., 2019). The interplay between the modularity principle and memory consolidation, among other mechanisms, is potentially associated with continual learning success.

Persistent homology (Barannikov, 1994; Edelsbrunner et al., 2000; Wasserman, 2018) has emerged as a tool for understanding, characterizing and quantifying the topology of brain networks. For example, it has been used to evaluate biomarkers of the neural basis of consciousness (Songdechakraiwut et al., 2022) and the impact of twin genetics (Songdechakraiwut et al., 2021) by interpreting brain networks as 1-skeletons (Munkres, 1996) of a simplicial complex. The topology of a 1-skeleton is *completely* characterized by connected components and cycles (Songdechakraiwut et al., 2022). Brain networks naturally organize into modules or connected components (Bullmore & Sporns, 2009; Honey et al., 2007), while cycle structure is ubiquitous and is often interpreted in terms of information propagation, redundancy and feedback loops (Kwon & Cho, 2007; Ozbudak et al., 2005; Venkatesh et al., 2004; Weiner et al., 2002).

In this paper we show that persistent homology can be used to improve performance of neural networks in continual learning tasks. In particular, we interpret a network as a 1-skeleton and propose a novel *topological regularization* of the 1-skeleton's cycle structure to avoid catastrophic forgetting of previously learned tasks. Regularizing the cycle structure allows the network to explicitly learn its complement, i.e., the modular structure, through gradient optimization. Figure 2 illustrates that our proposed approach employs topological regularization with a tiny episodic memory to mitigate forgetting and facilitate learning.

A.2 Birth and Death Decomposition

The only non-trivial topological features in a 1-skeleton are *connected components* (0-dimensional topological features) and *cycles* (1-dimensional topological features). There are no higher-dimensional topological features in the 1-skeleton, in contrast to clique complexes (Otter et al., 2017) and Rips complexes (Ghrist, 2008; Zomorodian, 2010). Persistent homology keeps track of the birth and death of topological features over filtration values ϵ. If a topological feature is born at a filtration value b_l and persists up to a filtration value d_l, then this feature is represented as a two-dimensional *persistence* point (b_l, d_l) in a plane. The set of all points $\{(b_l, d_l)\}_l$ is called *persistence diagram*

(Edelsbrunner & Harer, 2008) or, equivalently, *persistence barcode* (Ghrist, 2008). The use of the 1-skeleton simplifies the persistence barcodes to one-dimensional descriptors as follows.

The graph filtration begins with a graph with all parametrizing edge weights $G_{-\infty}$, sequentially removes edges at higher filtration values ϵ, and arrives at an edgeless graph $G_{+\infty}$. As ϵ increases, the number of connected components $\beta_0(G_\epsilon)$ and cycles $\beta_1(G_\epsilon)$ are monotonically increasing and decreasing, respectively (Songdechakraiwut et al., 2021). Specifically, $\beta_0(G_\epsilon)$ increases from $G_{-\infty}$ consisting of a single connected component $\beta_0(G_{-\infty}) = 1$ to the node set $\beta_0(G_\infty) = |V|$. There are $\beta_0(G_\infty) - \beta_0(G_{-\infty}) = |V| - 1$ connected components that are born over the filtration. Once connected components are born, they will remain for all larger filtration values, so their death values are all at $+\infty$. Thus, the representation of the connected components can be simplified to a collection of sorted *birth values* $\mathbb{B}(G) = \{b_l\}_{l=1}^{|V|-1}$.

On the other hand, cycles are born with $G_{-\infty}$ and thus have birth values at $-\infty$. Again we can simplify the representation of the cycles as a collection of sorted *death values* $\mathbb{D}(G) = \{d_l\}$. The removal of an edge must result in either the birth of a connected component or the death of a cycle (Songdechakraiwut et al., 2021). Thus every edge weight must also be in either $\mathbb{B}(G)$ or $\mathbb{D}(G)$, resulting in the decomposition of the edge weight set $\mathbb{W}$ into $\mathbb{B}(G)$ and $\mathbb{D}(G)$. As a result, the number of death values for cycles is equal to $|\mathbb{D}(G)| = |\mathbb{W}| - (|V| - 1)$. Thus, neural networks of the same architecture have a birth set $\mathbb{B}$ and a death set $\mathbb{D}$ of the *same* cardinality as $|V| - 1$ and $|\mathbb{W}| - (|V| - 1)$, respectively. This result completely resolves the problem of point mismatch in persistence barcodes for same-architecture neural networks. The example network of Fig. 1 has $\mathbb{W} = \{e_i\}_{i=1}^6$, $\mathbb{B}(G) = \{e_2, e_4, e_5, e_6\}$ and $\mathbb{D}(G) = \{e_1, e_3\}$.

$\mathbb{B}(G)$ comprises edge weights in the *maximum spanning tree* (MST) of G (Lee et al., 2012), and can be computed using standard methods such as Kruskal's (Kruskal, 1956) and Prim's algorithms (Prim, 1957). Once $\mathbb{B}(G)$ is identified, $\mathbb{D}(G)$ is given as the remaining edge weights that are not in the MST. Thus $\mathbb{B}(G)$ and $\mathbb{D}(G)$ are computed very efficiently in $O(n \log n)$ operations, where n is the number of edges in networks.

A.3   Closed Form Wasserstein Distance and Gradient

The birth set of connected components and the death set of cycles are theoretically shown to completely characterize the topology of a 1-skeleton network representation as described in Appendix A.2. The Wasserstein distance between 1-skeleton network representations has a closed-form expression (Songdechakraiwut et al., 2022). Here we only consider the Wasserstein distance for cycle structure, which depends solely on the death sets. Let G, H be two given networks based on the same architecture. Their (squared) *2-Wasserstein distance for cycles* is defined as the optimal matching cost between $\mathbb{D}(G)$ and $\mathbb{D}(H)$:

$$W_{cycle}^2(G, H) = \min_\phi \sum_{d_l \in \mathbb{D}(G)} \big[d_l - \phi(d_l)\big]^2, \tag{1}$$

where ϕ is a bijection from $\mathbb{D}(G)$ to $\mathbb{D}(H)$. The Wasserstein distance form given in (1) has a closed-form expression that allows for very efficient computation as follows (Songdechakraiwut et al., 2022)

$$W_{cycle}^2(G, H) = \sum_{d_l \in \mathbb{D}(G)} \big[d_l - \phi^*(d_l)\big]^2, \tag{2}$$

where ϕ^* maps the l-th smallest death value in $\mathbb{D}(G)$ to the l-th smallest death value in $\mathbb{D}(H)$ for all l.

In addition, the gradient of the Wasserstein distance for cycles $\nabla_G W_{cycle}^2(G, H)$ with respect to edge weights $w_{i,j} \in \mathbb{W}$ is given as a gradient matrix whose i, j-th entry is (Songdechakraiwut et al., 2022)

$$\frac{\partial W_{cycle}^2(G, H)}{\partial w_{i,j}} = \begin{cases} 0 & \text{if } w_{i,j} \in \mathbb{B}(G); \\ 2\big[w_{i,j} - \phi^*(w_{i,j})\big] & \text{if } w_{i,j} \in \mathbb{D}(G). \end{cases} \tag{3}$$

This follows because the edge weight set decomposes into the collection of births and the collection of deaths as described in Appendix A.2. Intuitively, by slightly adjusting the edge weight $w_{i,j}$ corresponding to a death value in $\mathbb{D}(G)$, we in turn alter the cycle structure of the network G. The gradient form given in (3) can be equivalently expressed as

$$\frac{\partial W_{cycle}^2(G, H)}{\partial d_l} = 2\big[d_l - \phi^*(d_l)\big], \tag{4}$$

where $d_l \in \mathbb{D}(G)$ and ϕ^* is the optimal matching from $\mathbb{D}(G)$ to $\mathbb{D}(H)$. The gradient computation requires sorting to find the optimal matching ϕ^*, which requires $O(n \log n)$ operations, where n is the number of edges in networks.

A.4 Closed Form Wasserstein Barycenter

The Wasserstein barycenter is the mean of a collection of networks under the Wasserstein distance and represents the topological centroid. Consider same-architecture networks $G^{(1)}, ..., G^{(N)}$. Their death sets have identical cardinality, i.e., $|\mathbb{D}| = |\mathbb{D}(G^{(1)})| = |\mathbb{D}(G^{(2)})| = \cdots = |\mathbb{D}(G^{(N)})|$ because the cardinality depends only on the number of nodes and edge weights. The *Wasserstein barycenter for cycles* $\mathcal{G}_{cycle}$ is defined as the death set that minimizes the *weighted* sum of the Wasserstein distances for cycles:

$$\mathcal{G}_{cycle} = \arg\min_{\mathcal{G}} \sum_{i=1}^{N} \nu_i W_{cycle}^2(\mathcal{G}, G^{(i)}), \tag{5}$$

where ν_i is a non-negative weight corresponding to network $G^{(i)}$ that is used to emphasize the contribution of some networks to the final barycenter more than others. The closed-form Wasserstein distance given in (2) results in a closed form expression for the Wasserstein barycenter as follows.

Let $\mathbb{D}(G^{(i)}) : d_1^{(i)} \leq \cdots \leq d_{|\mathbb{D}|}^{(i)}$ be the death set of network $G^{(i)}$. It follows that the l-th smallest death value of the barycenter $\mathcal{G}_{cycle}$ of the N networks is given by the weighted mean of all the l-th smallest death values of such networks, i.e., $\mathcal{G}_{cycle} : \overline{d}_1 \leq \cdots \leq \overline{d}_{|\mathbb{D}|}$, where

$$\overline{d}_l = \sum_{i=1}^{N} \nu_i d_l^{(i)} \Big/ \sum_{i=1}^{N} \nu_i. \tag{6}$$

Equation (6) is derived by setting the derivative of quadratic function in Eq. 5 equal to zero. The complete proof is given in Appendix D.

B Topology Based Continual Learning

Consider a *continual learning* scenario in which T supervised learning tasks are learned sequentially. Each task has a task descriptor $\tau \in \mathbb{T} = \{1, 2, ..., T\}$ with a corresponding dataset $\mathbb{P}_\tau = \{(\boldsymbol{x}_{i,\tau}, \boldsymbol{y}_{i,\tau})_{i=1}^{N_\tau}\}$ containing N_τ labeled training examples consisting of a feature vector $\boldsymbol{x}_{i,\tau} \in \mathcal{X}$ and a target vector $\boldsymbol{y}_{i,\tau} \in \mathcal{Y}$. We further consider the continuum of training examples that are experienced *only once*, and assume that the continuum is *locally independent and identically distributed* (iid), i.e., $(\boldsymbol{x}_{i,\tau}, \boldsymbol{y}_{i,\tau}) \overset{iid}{\sim} P_\tau$ following the prior work of Lopez-Paz & Ranzato (2017). The goal is to train a model $f : \mathcal{X} \times \mathbb{T} \rightarrow \mathcal{Y}$ that predicts a target vector $\boldsymbol{y}$ corresponding to a test pair $(\boldsymbol{x}, \tau)$, where $(\boldsymbol{x}, \boldsymbol{y}) \sim P_\tau$.

Consider a neural network predictor f parameterized by a weight set $\mathbb{W}$. For the first task $\tau = 1$, we find optimal weight set $\mathbb{W}^*$ by minimizing the expectation of a loss function as:

$$\mathbb{W}^* = \arg\min_{\mathbb{W}} \mathbb{E}_{(\boldsymbol{x}, \boldsymbol{y}) \sim P_1} L\big(f(\mathbb{W}; \boldsymbol{x}, \tau = 1), \boldsymbol{y}\big), \tag{7}$$

which is typically accomplished by employing the empirical risk minimization (ERM) principle (Vapnik, 1991). That is, the minimization problem given in (7) is approximated by minimizing the empirical loss function

$$\mathcal{L}_{ERM}(\mathbb{W}) = \frac{1}{N_1} \sum_{i=1}^{N_1} L\big(f(\mathbb{W}; \boldsymbol{x}_{i,1}, \tau = 1), \boldsymbol{y}_{i,1}\big). \tag{8}$$

This minimization can be effectively solved by gradient descent. However, extending this approach to more tasks causes catastrophic forgetting (McCloskey & Cohen, 1989) of previously learned tasks. That is, the model forgets how to predict past tasks after it is exposed to future tasks. Our approach to addressing this problem is to topologically penalize training with future tasks based on the underlying 1-skeleton of the neural network.

Define a neural network $G^{(\tau)}$ for learning task τ with nodes given by neurons, and edge weights defined by the weight/parameter set $\mathbb{W}$. All past-task networks $G^{(j)}$, for $j = 1, ..., \tau - 1$, have the identical node sets with the trained weight set $\mathbb{W}_j^*$ denoting the weights after training through the entire sequence up to task j. Since these graphs have the same architecture, their death sets have the same cardinality denoted by $|\mathbb{D}|$. Then the birth-death decomposition of the weight set $\mathbb{W}_j^*$ results in the death set $\mathbb{D}(G^{(j)}) : d_1^{(j)} \leq \cdots \leq d_{|\mathbb{D}|}^{(j)}$. The Wasserstein barycenter for cycles of the first $\tau - 1$ training tasks associated with networks $G^{(1)}, ..., G^{(\tau-1)}$ is

$$\mathcal{G}_{cycle}^{(\tau-1)} : \overline{d}_1^{(\tau-1)} \leq \cdots \leq \overline{d}_{|\mathbb{D}|}^{(\tau-1)}, \tag{9}$$

where $\overline{d}_l^{(\tau-1)} = \sum_{j=1}^{\tau-1} \nu_j d_l^{(j)} \big/ \sum_{j=1}^{\tau-1} \nu_j$. Our approach to learning task τ minimizes the ERM loss with the Wasserstein distance and barycenter penalty

$$\mathcal{L}_\tau(\mathbb{W}) = \mathcal{L}_{ERM,\tau}(\mathbb{W}) + \frac{\lambda}{2} W_{cycle}^2(G^{(\tau)}, \mathcal{G}_{cycle}^{(\tau-1)}) \quad \text{for all task } \tau > 1, \tag{10}$$

where λ controls relative importance between past- and current-task cycle structure. Intuitively, we penalize changes of cycle structure in a neural network while allow the network to explicitly learn the modular structure.

Minimization of Eq. (10) is accomplished via gradient descent over all training samples in learning task τ. Direct application of the gradient form given in (4) results in

$$\frac{\partial W_{cycle}^2(G^{(\tau)}, \mathcal{G}_{cycle}^{(\tau-1)})}{\partial d_l^{(\tau)}} = 2\big[d_l^{(\tau)} - \phi^*(d_l^{(\tau)})\big], \tag{11}$$

where $d_l^{(\tau)} \in \mathbb{D}(G^{(\tau)})$ and ϕ^* is the optimal matching from $\mathbb{D}(G^{(\tau)})$ to $\mathcal{G}_{cycle}^{(\tau-1)}$. In other words, the gradient computation is achieved in two steps: 1) compute birth-death decomposition of $\mathbb{W}$ to find $\mathbb{D}(G^{(\tau)})$; 2) sort $\mathbb{D}(G^{(\tau)})$ to find the optimal matching ϕ^* between $\mathbb{D}(G^{(\tau)})$ and $\mathcal{G}_{cycle}^{(\tau-1)}$. Furthermore, we execute the first step every m iterations. When $m = 1$, we compute birth-death decomposition every iteration to determine which edge belongs to $\mathbb{D}(G^{(\tau)})$ before sorting, while $m > 1$ allows to utilize multiple gradient descent updates to consolidate changes to previously determined edges in $\mathbb{D}(G^{(\tau)})$ by directly sorting updated weights in $\mathbb{D}(G^{(\tau)})$ from previous iterations. This approach may mimic human learning and memory consolidation over multiple temporal scales from days to decades (Bassett et al., 2011). Thus, the computational complexity for gradient computation is $n \log n$ operations, where n is the number of weights/parameters in the neural network graph.

At any time, we only need to store *one* Wasserstein barycenter from the previous task $\mathcal{G}_{cycle}^{(\tau-1)} = \{\overline{d}_l^{(\tau-1)}\}_l$. The barycenter for the current task $\mathcal{G}_{cycle}^{(\tau)} = \{\overline{d}_l^{(\tau)}\}_l$ can be computed as:

$$\overline{d}_l^{(\tau)} = \frac{p\overline{d}_l^{(\tau-1)} + qd_l^{(\tau)}}{p + q}, \tag{12}$$

where $d_l^{(\tau)} \in \mathbb{D}(G^{(\tau)}(\mathbb{W}_\tau^*))$ and $p, q > 0$ used to emphasize the contribution of $\mathcal{G}_{cycle}^{(\tau-1)}$ and $\mathbb{D}(G^{(\tau)})$ to $\mathcal{G}_{cycle}^{(\tau)}$. This online update satisfies the closed-form Wasserstein barycenter given in (6). A proof by induction is provided in Appendix D.

We summarize our topological continual learning steps in Algorithm 1.

Subgraph regularization We note that it is straightforward and may be advantageous to limit the topological regularization to specific layers and depths in the neural network. For example,

Algorithm 1 Topological continual learning algorithm

1: **procedure** TOP($\mathbb{P}, \mathbb{W} = \{w\}, \lambda, p, q, \gamma$)
2:    $\mathbb{M} \leftarrow \{\}$ $\triangleright$ Allocate a tiny memory buffer
3:    **for** $B_\mathbb{P} \sim \mathbb{P}_1$ **do** $\triangleright$ Sample without replacement a mini-batch from 1^{st} dataset
4:       $g_{sgd} \leftarrow \nabla_w \mathcal{L}_{ERM}(B_\mathbb{P})$ $\triangleright$ Compute gradient using the mini-batch
5:       $w \leftarrow w - \gamma \cdot g_{sgd}$
6:       $\mathbb{M} \leftarrow$ mem_update($\mathbb{M}, B_\mathbb{P}$) $\triangleright$ Update memory; see Appendix C
7:    **end for**
8:    $\mathcal{G}^{(1)} \leftarrow \mathbb{D}(\mathbb{W})$ $\triangleright$ Initial barycenter described in Equation (9)
9:    **for** $\tau \in \{2, .., T\}$ **do**
10:       $iter \leftarrow 0$
11:       **for** $B_\mathbb{P} \sim \mathbb{P}_\tau$ **do** $\triangleright$ Sample without replacement a mini-batch from τ^{th} dataset
12:          $B_\mathbb{M} \sim \mathbb{M}$ $\triangleright$ Sample a mini-batch from the buffer
13:          **if** $iter$ mod $m == 0$ **then** $\triangleright$ Every m iterations
14:             $\mathbb{D} \leftarrow$ bd_decomposition($\mathbb{W}$) $\triangleright$ Compute death set from current weight set
15:          **end if**
16:          $g_{sgd} \leftarrow \nabla_w \mathcal{L}_{ERM}(B_\mathbb{P} \cup B_\mathbb{M})$ $\triangleright$ Compute gradient using aggregated mini-batch
17:          **if** $w \in \mathbb{D}$ **then**
18:             $g_{top} \leftarrow w - \phi^*(w)$ $\triangleright$ Compute closed form gradient in Equation (11)
19:             $w \leftarrow w - \gamma \cdot (g_{sgd} + \lambda \cdot g_{top})$
20:          **else**
21:             $w \leftarrow w - \gamma \cdot g_{sgd}$
22:          **end if**
23:          $iter \leftarrow iter + 1$
24:          $\mathbb{M} \leftarrow$ mem_update($\mathbb{M}, B_\mathbb{P}$)
25:       **end for**
26:       $\mathcal{G}^{(\tau)} \leftarrow \mathcal{G}^{(\tau-1)}(p, q)$ $\triangleright$ Update barycenter using Equation (12)
27:    **end for**
28:    **return** $\mathbb{W}$ $\triangleright$ Return optimal weight set
29: **end procedure**

---

a convolutional neural network is typically constructed as a series of convolutional (conv) layers followed by a fully-connected (fc) layer. The conv layers extract high-level features from data for the fc layer, which in turn uses those features for classification. We can define subgraphs based on groupings of a conv layer with the following fc layer and restrict the topological regularizer to a subset of layers, typically layers towards the output side of the neural network. Formally, if we have K subnetwork graphs $G^{(\tau,1)}, ..., G^{(\tau,K)}$ and their barycenters $\mathcal{G}_{cycle}^{(\tau-1,1)}, ..., \mathcal{G}_{cycle}^{(\tau-1,K)}$, then our topological penalty is expressed as the sum of Wasserstein distances for each separate graph, i.e.,

$$\mathcal{L}_\tau(\mathbb{W}) = \mathcal{L}_{ERM,\tau}(\mathbb{W}) + \frac{\lambda}{2}\sum_{k=1}^{K} W_{cycle}^2(G^{(\tau,k)}, \mathcal{G}_{cycle}^{(\tau-1,k)}) \quad \text{for all task } \tau > 1. \tag{13}$$

C   Image Classification Experiments

C.1   Datasets

We perform continual learning experiments on four datasets. (1) *Permuted MNIST* (P-MNIST) (Kirkpatrick et al., 2017) is a variant of the MNIST dataset of handwriten digits (Lecun et al., 1998) where each task is constructed by a fixed random permutation of image pixels in each original MNIST example. (2) *Rotated MNIST* (R-MNIST) (Lopez-Paz & Ranzato, 2017) is another variant of the MNIST dataset where each task contains digits rotated by a fixed angle between 0 and 180 degrees. Both P-MNIST and R-MNIST contain 30 sequential tasks, each has 10,000 training examples and 10 classes. Each task in P-MNIST and R-MNIST is constructed with different permutations and rotations, respectively, resulting in different distributions among tasks. The other two datasets, (3) *Split CIFAR* and (4) *split miniImageNet*, are constructed by randomly splitting 100 classes in the original CIFAR-100 dataset (Krizhevsky, 2009) and ImageNet dataset (Russakovsky et al., 2015; Vinyals et al., 2016) into 20 learning tasks each with 5 classes.

C.2 Network architecture

The P-MNIST and R-MNIST datasets use a fully-connected neural network with two hidden layers each with 128 neurons. The split CIFAR and split miniImageNet datasets use a downsized version of ResNet18 (He et al., 2016) with eight times fewer feature maps across all layers, similar to (Lopez-Paz & Ranzato, 2017). For P-MNIST and R-MNIST, we evaluate classification performance in a *single-head* setting where all tasks share the final classifier layer in the fully-connected network, and thus the inference is performed without task identifiers. For the split CIFAR and split miniImageNet datasets, the classification performance is evaluated in a *multi-head* setting where each task has a separate classifier in the reduced ResNet18.

C.3 Method comparison

We evaluate our method performance in relative to eight baseline approaches that learn a sequence of tasks in a fixed-size network architecture. (1) *Finetune* is a model trained sequentially without any regularization and past-task episodic memory. (2) *Elastic weight consolidation* (EWC) (Kirkpatrick et al., 2017) is a regularization-based method that penalizes changes in parameters that were important for the previous tasks using the Fisher information. (3) *Recursive gradient optimization* (RGO) (Liu & Liu, 2022) combines use of gradient direction modification and task-specific random rearrangement to network layers to mitigate forgetting between tasks. (4) *Averaged gradient episodic memory* (A-GEM) (Chaudhry et al., 2019a) and (5) ORTHOG-SUB (Chaudhry et al., 2020) methods store past-task examples in an episodic memory buffer used to project gradient updates to avoid interference with previous tasks. (6) *Experience replay* with *reservoir sampling* (ER-Res) and (7) ER with *ring buffer* (ER-Ring) mitigate forgetting by directly computing gradient based on aggregated examples from new tasks and a memory buffer (Chaudhry et al., 2019b). The ring buffer (Lopez-Paz & Ranzato, 2017) allocates equally sized memory for each class using FIFO scheduling, while reservoir sampling (Vitter, 1985) maintains a memory buffer by randomly drawing out already stored samples when the buffer is full. (8) *Multitask* jointly learns the entire dataset in one training round, and thus is not a continual learning strategy but served as an upper bound reference for other methods.

In our topology-based method we regularize different aspects of the two types of neural networks employed. In the fully-connected network applied to P-MNIST and R-MNIST we apply subgraph regularization based on two separate bipartite graphs: one consisting of neurons and weights from the two hidden layers, the other consisting of neurons and weights from the last hidden layer and the output layer. For ResNet18, we use one bipartite graph comprising neurons and weights from the pooling layer and the fully-connected output layer. Bias neurons are not included in our regularization. We employ topological regularization with reservoir sampling and ring buffer strategies, termed TOP-Res and TOP-Ring. Universally, m is set to 5, p to 9, and q to 1 in our experiment.

C.4 Training protocol

We follow the training protocol of Chaudhry et al. (2020) as follows. The training is done universally through plain stochastic gradient descent with batch size of 10. All training examples in the datasets are observed only once, except for past-task examples stored in an episodic memory buffer, which can be replayed multiple times. We consider a tiny episodic memory with the size of one *example per class* for all memory-based methods. For example, there are 100 classes in split CIFAR, and thus the memory buffer stores up to 100 past-task examples. The size of past-task batch sampled from the episodic memory is also universally set to 10, the gradient descent batch size. Hyper-parameter tuning is performed on the first three tasks in each dataset. A separate test set not used in the training tasks is used for performance evaluation.

C.5 Performance measures

We evaluate the algorithms based on two performance measures: average accuracy (ACC) and backward transfer (BWT) as proposed by Lopez-Paz & Ranzato (2017). ACC is the average test

classification accuracy for all tasks, while BWT indicates the influence of new learning on the past knowledge, i.e., negative BWT indicates the degree of forgetting. Formally, ACC and BWT are defined as

$$\text{ACC} = \frac{1}{T} \sum_{j=1}^{T} R_{T,j}, \quad \text{BWT} = \frac{1}{T-1} \sum_{j=1}^{T-1} R_{T,j} - R_{j,j}, \quad (14)$$

where T is the total number of sequantial tasks, and $R_{i,j}$ is the accuracy of the model on the j^{th} task after learning the i^{th} task in sequence. Higher ACC and BWT indicate better continual learning performance. We report ACC and BWT averaged over five different task sequences for each dataset.

C.6 Experimental results

Table 1 shows method performance on all four datasets. *Finetune* without any continual learning strategy produces lowest ACC and BWT performance, while the oracle *multitask* is trained across all tasks and sets the upper bound ACC performance for all datasets. Gradient-based RGO and ORTHOG-SUB rely on over-parameterization in a neural network to reduce interference between tasks. Given the long sequence of tasks and small network architecture in our experiments, it is likely that over-parameterization is insufficient for strong performance. Although ORTHOG-SUB achieves highest BWT, it also has the lowest ACC scores, in some cases worse than *Finetune*. ER-Res and ER-Ring achieve high ACC and BWT scores relative to the other baseline methods across all experiments. Our TOP-Res and TOP-Ring methods in turn demonstrate clear performance improvement over ER-Res and ER-Ring based on both ACC and BWT, suggesting that our topological continual learning strategy facilitates the consolidation of past-task knowledge beyond that provided by memory replay alone.

Figure 3 illustrates the impact of parameters λ and m of the proposed method on the ACC and BWT measures for the P-MNIST dataset. The two leftmost column plots depict the increase in ACC and BWT scores provided by TOP-Ring and TOP-Res relative to ER-Ring and ER-Res baselines for all λ, the topological regularizer weight. In addition, we demonstrate classification performance of TOP, our method without any episodic memory buffer. The results show that TOP outperforms *finetune* baseline and demonstrates clear past-task knowledge retention. TOP without any memory buffer performs better than the regularization-based EWC and gradient-based ORTHOG-SUB with memory buffers, as displayed in Table 1. The third column plot displays ACC scores as a function of m, the number of iterations between birth-death decomposition updates. We observe stable upward trend as m increases for TOP-Ring and TOP-Res. Less frequent birth-death decomposition update ($m = 10, 20$) improves performance and reduces run time. The last column displays ACC scores as a function of memories per class of 1, 2, 3 and 5. We observe that ACC scores increases as more past-task examples are stored in a tiny memory buffer. TOP-Ring and TOP-Res improves the performance over ER-Ring and ER-Res for all memory sizes. Finally, we explored ACC as a function of p/q of $9/1, 7/3, 5/5, 3/7$ and $1/9$, and found that the performance of both TOP-Ring and TOP-Res are not dependent on p/q.

C.7 Related Work

Approaches to continual learning in neural networks can broadly be categorized into three classes. 1) Regularization-based methods estimate importance of neural network parameters from previously learned tasks, and penalize changes to those important parameters during current tasks to mitigate forgetting (Kirkpatrick et al., 2017; Serra et al., 2018; Zenke et al., 2017). Our topological regularization based method does not estimate importance for each individual parameter, but rather focuses on global network attributes. Thus, our method does not penalize individual parameters in the network, but rather penalizes cycle structure. 2) Memory-based methods attempt to overcome catastrophic forgetting by either storing examples from past tasks in a memory buffer for rehearsal (Chaudhry et al., 2020; Lopez-Paz & Ranzato, 2017; Rebuffi et al., 2017; Riemer et al., 2019), or synthesizing past-task data from generative models for pseudo-rehearsal (Shin et al., 2017). 3) Expansion-based methods allocate a different set of parameters within a neural network for each task (Li et al., 2019;

Figure 3: ACC and BWT scores as a function of the hyper-parameters of TOP-Ring, TOP-Res and TOP for P-MNIST dataset. $\lambda = 0$ for TOP-Ring, TOP-Res and TOP describe ER-Ring, ER-Res and *finetune*, respectively. TOP is our method without any memory buffer and uses a neural network graph constructed with the whole neural network. λ: weight for the topological regularization, m: frequency of optimal matching update.

Xu & Zhu, 2018; Yoon et al., 2018, 2020). These methods may expand network size in an attempt to eliminate forgetting by design. In contrast, our method does not require network growth, but continually learns within a fixed network architecture.

Gradient-based methods, such as ORTHOG-SUB and RGO, can offer strong performance using over-parameterized neural networks (Chaudhry et al., 2020; Liu & Liu, 2022). However, their performance degrades substantially in a more challenging scenario of limited network width and a long sequence of learning tasks, as in our experiments. Such scenarios are especially important when computational power is limited. Large neural networks not only demand more computation to optimize, but also demand a large memory footprint to store their parameter set. Our topology-based method does not require over-parameterized neural networks to be effective and thus has limited computational burden. In particular, subgraph regularization penalizes a subset of layers towards the output side of the network and further reduces computation. Subgraph regularization gradient computation requires $n \log n$ operations and its space complexity is n where $n \ll |\mathbb{W}|$. Our topology-regularized continual learning framework demonstrates the best performance in a computation constrained setting, and furthermore may provide additional insight into effective mechanisms for continual learning.

D   Proofs

D.1   Closed Form Wasserstein Barycenter

Let $\mathbb{D}(G^{(i)}) : d_1^{(i)} \leq \cdots \leq d_{|\mathbb{D}|}^{(i)}$ be the death set of network $G^{(i)}$. It follows that the l-th smallest death value of the barycenter $\mathcal{G}_{cycle}$ of the N networks is given by the weighted mean of all the l-th smallest death values of such networks, i.e., $\mathcal{G}_{cycle} : \overline{d}_1 \leq \cdots \leq \overline{d}_{|\mathbb{D}|}$, where

$$\overline{d}_l = \sum_{i=1}^{N} \nu_i d_l^{(i)} \bigg/ \sum_{i=1}^{N} \nu_i.$$

547 Recall that the *Wasserstein barycenter for cycles* $\mathcal{G}_{cycle}$ is defined as the death set that minimizes the
548 *weighted* sum of the Wasserstein distances for cycles, i.e.,

$$\mathcal{G}_{cycle} = \arg\min_{\mathcal{G}} \sum_{i=1}^{N} \nu_i W_{cycle}^2(\mathcal{G}, G^{(i)})$$

$$= \arg\min_{\mathcal{G}} \sum_{i=1}^{N} \nu_i \sum_{\overline{d}_l \in \mathcal{G}} \left[\overline{d}_l - \phi_i^*(\overline{d}_l)\right]^2,$$

where ν_i is a non-negative weight, and ϕ_i^* maps the l-th smallest death value in $\mathcal{G}$ to the l-th smallest
death value in $\mathbb{D}(G^{(i)})$ for all l. The sum can be expanded as

$$\sum_{i=1}^{N} \nu_i \sum_{\overline{d}_l \in \mathcal{G}} \left[\overline{d}_l - \phi_i^*(\overline{d}_l)\right]^2 = \sum_{i=1}^{N} \nu_i \left([\overline{d}_1 - d_1^{(i)}]^2 + \cdots + [\overline{d}_{|\mathbb{D}|} - d_{|\mathbb{D}|}^{(i)}]^2\right),$$

549 which is quadratic. By setting its derivative equal to zero, we find the minimum at $\overline{d}_l = $
550 $\sum_{i=1}^{N} \nu_i d_l^{(i)} / \sum_{i=1}^{N} \nu_i$.

D.2 Online Computation for Closed Form Wasserstein Barycenter

552 Given the Wasserstein barycenter from the previous task $\mathcal{G}_{cycle}^{(\tau-1)} = \{\overline{d}_l^{(\tau-1)}\}_l$. The barycenter for the
553 current task $\mathcal{G}_{cycle}^{(\tau)} = \{\overline{d}_l^{(\tau)}\}_l$ can be computed as:

$$\overline{d}_l^{(\tau)} = \frac{p\overline{d}_l^{(\tau-1)} + qd_l^{(\tau)}}{p+q},$$

554 where $d_l^{(\tau)} \in \mathbb{D}(G^{(\tau)})$ and $p, q > 0$.

555 Let $\rho = q/(p+q)$. Then $1 - \rho = p/(p+q)$. Recall $\mathbb{D}(G^{(j)}) = \{d_l^{(j)}\}_l$ be the death set of weights
556 after training through the entire sequence up to task j.

557 When $\tau = 2$, we have the barycenter after training through the entire sequence up to the second task
558 $\mathcal{G}_{cycle}^{(2)} = \{\overline{d}_l^{(2)}\}_l$, where $\overline{d}_l^{(2)} = (1-\rho)d_l^{(1)} + \rho d_l^{(2)}$. That is, $\mathcal{G}_{cycle}^{(2)}$ is the barycenter of $G^{(1)}$ and
559 $G^{(2)}$ with weights associated with $G^{(1)}$ and $G^{(2)}$ as $(1-\rho)$ and ρ, respectively.

560 For $\tau > 2$, suppose $\mathcal{G}_{cycle}^{(\tau-1)} = \{\overline{d}_l^{(\tau-1)}\}_l$ is the barycenter after training through the sequence up to
561 task $\tau - 1$. Then the online computation for barycenter for the next task results in $\{\overline{d}_l^{(\tau)}\}_l$, where

$$\overline{d}_l^{(\tau)} = (1-\rho)\overline{d}_l^{(\tau-1)} + \rho d_l^{(\tau)}$$

$$= (1-\rho)\sum_{i=1}^{\tau-1} \nu_i d_l^{(i)} \Big/ \sum_{i=1}^{\tau-1} \nu_i + \rho d_l^{(\tau)} \quad \nu_i > 0, \forall i.$$

562 It follows that the sum of weights associated with $G^{(1)}, ..., G^{(\tau)}$

$$(1-\rho)\sum_{i=1}^{\tau-1} \nu_i \Big/ \sum_{i=1}^{\tau-1} \nu_i + \rho = (1-\rho) \cdot 1 + \rho$$

$$= 1,$$

563 indicating that the l^{th} smallest death value $\overline{d}_l^{(\tau)}$ is given by the weighted mean of all the l^{th} smallest
564 death values of networks $G^{(1)}, ..., G^{(\tau)}$. Thus, $\mathcal{G}_{cycle}^{(\tau)} = \{\overline{d}_l^{(\tau)}\}_l$ is the barycenter after additional
565 training of the τ^{th} task.

E Experimental Details

E.1 Implementation of Candidate Methods

For baseline methods, we used existing implementation codes from authors' publications and publicly available repository websites. Codes for EWC (Kirkpatrick et al., 2017), A-GEM (Chaudhry et al., 2019a), ORTHOG-SUB (Chaudhry et al., 2020), and ER-Res/ER-Ring (Chaudhry et al., 2019b) are available at `https://github.com/arslan-chaudhry/orthog_subspace` under the MIT License. Code for RGO (Liu & Liu, 2022) is available at `https://openreview.net/forum?id=7YDLgf9_zgm`.

E.2 Hyperparameters Tuning

Grid search across different hypeparameter values is used to choose a set of optimal hyperparameters for all candidate methods. We consider gradient descent learning rates in $\{0.003, 0.01, 0.03, 0.1, 0.3, 1.0\}$ following Chaudhry et al. (2020); Liu & Liu (2022). Other additional hyperparameters of EWC, A-GEM, ORTHOG-SUB, and ER-Res/ER-Ring follow Chaudhry et al. (2020), while those of RGO follow the authors' official implementation (Liu & Liu, 2022). Specifically, below we report grids for the candidate methods with the optimal hyperparameter settings for different benchmarks given in parenthesis.

1. Finetune
   - Learning rate: 0.003, 0.01, **0.03 (miniImageNet)**, **0.1 (P-MNIST, R-MNIST)**, **0.3 (CIFAR)**, 1
2. EWC
   - Learning rate: 0.003, 0.01, **0.03 (CIFAR, miniImageNet)**, **0.1 (P-MNIST, R-MNIST)**, 0.3, 1
   - Regularization: 0.01, 0.1, 1, **10 (P-MNIST, R-MNIST, CIFAR, miniImageNet)**, 100, 1000
3. RGO
   - Learning rate: 0.003, 0.01, **0.03 (CIFAR, miniImageNet)**, **0.1 (P-MNIST, R-MNIST)**, 0.3, 1
4. A-GEM
   - Learning rate: 0.003, 0.01, **0.03 (miniImageNet)**, **0.1 (P-MNIST, R-MNIST, CIFAR)**, 0.3, 1
5. ORTHOG-SUB
   - Learning rate: 0.003, 0.01, **0.03 (R-MNIST)**, **0.1 (P-MNIST, CIFAR, miniImageNet)**, 0.3, 1
6. ER-Res
   - Learning rate: 0.003, 0.01, **0.03 (miniImageNet)**, **0.1 (R-MNIST, CIFAR)**, **0.3 (P-MNIST)**, 1
7. ER-Ring
   - Learning rate: 0.003, 0.01, **0.03 (miniImageNet)**, **0.1 (P-MNIST, R-MNIST, CIFAR)**, 0.3, 1
8. Multitask
   - Learning rate: 0.003, 0.01, **0.03 (CIFAR, miniImageNet)**, **0.1 (P-MNIST, R-MNIST)**, 0.3, 1
9. TOP-Res
   - Learning rate: 0.003, 0.01, 0.03, **0.1 (CIFAR, miniImageNet)**, **0.3 (P-MNIST, R-MNIST)**, 1
   - Regularization: **0.01 (CIFAR, miniImageNet)**, 0.1, **1 (P-MNIST, R-MNIST)**, 10
10. TOP-Ring
    - Learning rate: 0.003, 0.01, 0.03, **0.1 (P-MNIST, R-MNIST, CIFAR, miniImageNet)**, 0.3, 1
    - Regularization: **0.01 (R-MNIST, miniImageNet)**, 0.1, **1 (P-MNIST, CIFAR)**, 10

E.3 Computational Resources

$1\times$ NVIDIA GeForce GTX 1080