CALIBRATING THE RIGGED LOTTERY: MAKING ALL TICKETS RELIABLE

ABSTRACT

Although sparse training has been successfully used in various deep learning tasks to save memory and reduce inference time, the reliability of the produced sparse models remains unexplored. Previous research has shown that deep neural networks tend to be over-confident, and we find that sparse training exacerbates this problem. Therefore, calibrating the sparse models is crucial for reliable prediction and decision making. In this paper, we propose a new sparse training method to produce sparse models with improved confidence calibration. In contrast to previous research that uses only one mask to control the sparse topology, our method utilizes two masks, including a deterministic mask and a random mask. The former efficiently searches and activates important weights by exploiting the magnitude of weights and gradients. While the latter brings better exploration and finds more appropriate weight values by random updates. Theoretically, we prove our method can be viewed as a hierarchical variational approximation of a probabilistic deep Gaussian process. Extensive experiments on multiple datasets, model architectures, and sparsities show that our method can reduce ECE values by up to 47.8% and simultaneously maintain or even improve accuracy with only a slight increase in computational and storage burden.

1   INTRODUCTION

Sparse training is gaining increasing attention and has been used in various deep neural network (DNN) learning tasks (Evci et al., 2020; Dietrich et al., 2021; Sokar et al., 2021; Bibikar et al., 2022). In sparse training, a fraction of weights are set to zero to save memory and reduce inference time, enabling DNNs for resource-constrained situations. The sparse topology is usually controlled by a mask, and various sparse training methods have been proposed to find a suitable mask to achieve comparable or even higher accuracy compared to dense training (Evci et al., 2020; Jayakumar et al., 2020; Liu et al., 2021; Özdenizci & Legenstein, 2021; Schwarz et al., 2021). However, in order to deploy the sparse models in real-world applications, a key question remains to be answered: how reliable are these models?

There has been a line of work on studying the reliability of dense DNNs (Guo et al., 2017; Nixon et al., 2019; Zhang et al., 2020; Wang et al., 2021b), which means that DNNs should know what it does not know (Wang et al., 2021a). In other words, a model's confidence (the probability associated with the predicted class label) should reflect its ground truth correctness likelihood. However, previous research has shown that DNNs tend to be over-confident (Guo et al., 2017; Rahaman et al., 2021; Patel et al., 2022), suggesting that the model may be too confident to notice incorrect decisions, leading to safety issues in real-world applications such as automated healthcare and self-driving cars (Jiang et al., 2012; Bojarski et al., 2016).

In this work, we provide the *first* comprehensive study on the reliability of sparse training. We start with the question of how reliable the current sparse training is. We find that the over-confidence problem becomes even more pronounced when sparse training is applied . Figures 1 (a)-(b) show that the gap (blue area) between confidence and accuracy of the sparse model (95% sparsity) is larger than that of the dense model (0% sparsity), implying the sparse model is more over-confident than the dense model. Figure 1 (c) shows the test accuracy (pink curve) and ECE value (blue curve, a measure of reliability) (Guo et al., 2017) at different sparsities. When the accuracy is comparable to dense training (0%-95%), we observe that the ECE values increase with sparsity, implying that

(a) Reliability Diag. (0%)   (b) Reliability Diag. (95%)   (c) Test Accuracy and ECE Value

Figure 1: Reliability diagrams for (a) the dense model and (b) the sparse model. The sparse model is more over-confident than the dense model. (c) the scatter plot of test accuracy (%) and ECE value at different sparsities. From the high sparse model to the dense model, the ECE value first decreases, then increases, and then decreases again, showing a double descent pattern.

the problem of over-confidence becomes more severe at higher sparsity. And when the accuracy decreases sharply (>95%), the ECE value first decreases and then increases again. This leads to a *double descent* phenomenon (Nakkiran et al., 2021) when we view the ECE value curve from left to right (99.9%-0%) (see Section 6 for more discussion).

To improve the reliability, we propose a new sparse training method to produce well-calibrated predictions while maintaining a high accuracy performance. We call our method "The Calibrated Rigged Lottery" or CigL. Unlike previous sparse training methods with only one mask, our method employs two masks, including a deterministic mask and a random mask, to better explore the sparse topology and weight space. The deterministic one efficiently searches and activates important weights by exploiting the magnitude of weights/gradients. And the random one adds more exploration and leads to better convergence. When approaching the end of training, we collect weights and masks at each epoch, and use the designed weight & mask averaging procedure to combine the collected samples into one sparse model. From theoretical analysis, we show our method can be viewed as a hierarchical variational approximation (Ranganath et al., 2016) to a probabilistic deep Gaussian process (Gal & Ghahramani, 2016), which leads to a large family of variational distributions and better Bayesian posterior approximations . Our contributions are summarized as follows:

- We conduct the first comprehensive study on the reliability of sparse training and find that sparse training exacerbates the over-confidence problem of DNNs.

- We then propose CigL, a new sparse training method that improves confidence calibration with comparable and even higher accuracy.

- We prove that CigL can be viewed as a hierarchical variational approximation to a probabilistic deep Gaussian process which improves the calibration by better characterizing the posterior.

- We perform extensive experiments on multiple benchmark datasets, model architectures, and sparsities. CigL reduces ECE values by up to **47.8%** and simultaneously maintain or even improve accuracy with only a slight increase in computational and storage burden.

2 RELATED WORK

2.1 SPARSE TRAINING

As the scale of models continues to grow, there is an increasing attention to the sparse training which maintains sparse weights throughout the training process. Different sparse training methods have been investigated, and various pruning and growth criteria, such as weight/gradient magnitude, random selection, weight sign, and random selection, are designed (Mocanu et al., 2018; Bellec et al., 2018; Frankle & Carbin, 2019; Mostafa & Wang, 2019; Dettmers & Zettlemoyer, 2019; Evci et al., 2020; Jayakumar et al., 2020; Liu et al., 2021; Özdenizci & Legenstein, 2021; Zhou et al., 2021; Schwarz et al., 2021). However, sparse training is more challenging in fully exploring the

weight space because a large portion of the weights are fixed to zero, cutting off the update route and producing spurious local minima (Evci et al., 2019; Sun & Li, 2021; He et al., 2022). Existing sparse training methods use only one mask to determine the sparse topology, which is not sufficient to explore the space well enough to find a reliable model.

2.2 CONFIDENCE CALIBRATION IN DNNS

Many studies have been devoted to investigate whether the confidences of DNNs are well-calibrated (Guo et al., 2017; Nixon et al., 2019; Zhang et al., 2020), and existing research has found DNNs tend to be over-confident (Guo et al., 2017; Rahaman et al., 2021; Patel et al., 2022), which may mislead our choices and cause unreliable decisions in real-world applications. A number of methods have been developed to improve confidence calibration. A widely-used method is temperature scaling (Guo et al., 2017), which adds a scaling parameter to the softmax formulation and adjusts it on a validation set. Some other works incorporate regularization in the training, such as Mixup (Zhang et al., 2017) and label smoothing (Szegedy et al., 2016). In addition, Bayesian methods have also shown the ability to improve calibration, such as Monte Carlo Dropout (Gal & Ghahramani, 2016) and Bayesian deep ensembles (Ashukha et al., 2020). However, current confidence calibration methods have mainly focused on dense training, and how to obtain a well-calibrated DNN in sparse training is more challenging and remains unexplored.

3 METHOD

We propose a new sparse training method, CigL, to improve the confidence calibration of the produced sparse models, which simultaneously maintains comparable or even higher accuracy. Specifically, CigL starts with a random sparse network and uses two masks to control the sparse topology and explore the weight space, including a deterministic mask and a random mask. The former is updated periodically to determine the non-zero weights, while the latter is sampled randomly in each iteration to bring better exploration in the model update. Then, with the designed weight & mask averaging, we combine information about different aspects of the weight space to obtain a single output sparse model. Our CigL method is outlined in Algorithm 1.

3.1 DETERMINISTIC MASK & RANDOM MASK

In our CigL, we propose to utilize two masks, a deterministic mask M and a random mask Z, to search for a sparse model with improved confidence calibration and SOTA accuracy. We will first describe the two masks in detail and discuss how to set their sparsity.

The deterministic mask controls the entire sparse topology with the aim of finding a well-performing sparse model. That is, the mask determines which weights should be activated and which should not. Inspired by the widely-used sparse training method RigL (Evci et al., 2020), we believe a larger weight/gradient magnitude implies that the weight is more helpful for loss reduction and needs to be activated. Thus, CigL removes a portion of the weights with small magnitudes, and activates new weights with large gradient magnitudes at fixed time intervals ΔT.

The random mask allows the model to better explore the weight space under sparsity constraints. In each iteration prior to backpropagation, the mask is randomly drawn from Bernoulli distribution. In this way, the mask randomly selects a portion of the non-zero weights to be temporarily deactivated and forces the model to explore more in other directions of the weight space, which adds more randomness in the weight update step and leads to a better exploration of the weight space. As a result, the model is more likely to jump out of spurious local minima while avoiding deviations from the sparse topology found by the deterministic mask.

The sparsity setting of the two masks is illustrated as below. On the one hand, the deterministic mask is responsible for the overall sparsity of the output sparse model. Suppose we want to train a network with 95% sparsity, the deterministic mask will also have the same sparsity, with only 5% of the elements being 1. On the other hand, the random mask deactivates some non-zero weights during the training process, producing some temporary models with increasing sparsity. Since highly sparse models (like 95% sparsity) are sensitive to further increases in sparsity, we set a low sparsity, such

as 10%, for the random mask so that no significant increases in sparsity and no dramatic degradation in performance occurs in these temporary models.

3.2 Weight & Mask Averaging

With the two masks designed above, we propose a weight & mask averaging procedure to obtain one single sparse model with improved confidence calibration and comparable or even higher accuracy. We formalize this procedure as follows. We first iteratively update the two masks and model weights. Consistent with widely used sparse training methods (Evci et al., 2020; Liu et al., 2021), the deterministic mask stops updating near the end of the training process. While we still continuously draw different random masks from the Bernoulli distribution and collect a pair of sparse weights and random masks $\{Z^{(t)}, W^{(t)}\}$ at each epoch after the preset T^*. Then, with these samples, we can produce multiple temporary sparse models $Z^{(t)} \odot W^{(t)}$ with different weight values and different sparse topologies, which contain more knowledge about the weight space than the single-mask training methods. Finally, inspired by a popular way of combining models (Izmailov et al., 2018; Wortsman et al., 2022), we obtain the single output sparse model by averaging the weights of these temporary sparse models, which can be viewed as a mask-based weighted averaging.

Algorithm 1 CigL

Input: initialize $W^{(0)}$, M, and W_{CigL} = None, set epoch length m, update interval ΔT, number of iterations T, start iteration for weight & mask averaging T^*, random mask rate p, and learning rate α_t
for $t = 1$ **to** T **do**
    Sample a mini-batch data B_t with size n
    if $t \mod \Delta T = 0$ **then**
        Update mask M using weights and gradients
        Prune and regrow weights $W^{(t)}$ based on M
    end if
    Sample mask $Z^{(t)}$ and $Z_{ij}^{(t)} = \text{Bernoulli}(p)$
    Update sparse weights: $W^{(t)} = W^{(t-1)} - \alpha_t Z^{(t)} \odot \nabla L(Z^{(t)} \odot W^{(t-1)}; B_t)$
    if $t \mod m = 0$ and $t > T^*$ **then**
        if $W_{\text{CigL}} = $ None **then**
            $W_{\text{CigL}} = W^{(t)} \odot Z^{(t)}$
            $n_{\text{models}} = 1$
        else
            $W_{\text{CigL}} = \frac{W_{\text{CigL}} \cdot n_{\text{models}} + W^{(t)} \odot Z^{(t)}}{n_{\text{models}} + 1}$
            $n_{\text{models}} = n_{\text{models}} + 1$
        end if
    end if
end for
Output: Sparse Weights W_{CigL}

---

4 Making All Tickets Reliable

4.1 CigL as a Hierarchical Bayesian Approximation

We prove that training sparse neural networks with our CigL are mathematically equivalent to approximating the probabilistic deep GP (Damianou & Lawrence, 2013; Gal & Ghahramani, 2016) with hierarchical variational inference. To demonstrate the equivalence, we show that the objective of CigL is actually to minimize the Kullback–Leibler (KL) divergence between a hierarchical variational distribution and the posterior of a deep GP. During our study, we do not restrict the type of network architecture so that the results are applicable to a wide range of applications. Due to space constraints, the detailed derivation is shown in Appendix B.

We first present the minimisation objective function of CigL for a sparse neural network (NN) model with L layers and loss function E. The sparse weights and bias of the l-th layer are denoted by $W_l \in \mathbb{R}^{K_i \times K_{i-1}}$ and $b_l \in \mathbb{R}^{K_i}$ ($l = 1, \cdots, L$), and the output prediction is denoted by $\widehat{y}_i$. Given data $\{x_i, y_i\}$, we train the NN model by iteratively update the deterministic mask and the sparse weights. Since the random mask is drawn from a Bernoulli distribution, it has no parameters that need to be updated. For deterministic mask updates, we set the portion with the larger weight magnitude to 1 and the rest to 0. For the weight update, we minimise Eq. (1) which is composed of the difference between $\widehat{y}_i$ and the true label y_i and a widely-used L_2 regularisation.

$$\mathcal{L}_{\text{CigL}} := \frac{1}{N} \sum_{i=1}^{N} E(y_i, \widehat{y}_i) + \lambda \sum_{l=1}^{L} (||W_l||_2^2 + ||b_l||_2^2), \tag{1}$$

where the sparse topology of $\{W_l, l = 1, \cdots, L\}$ is controlled by $\{M_l, l = 1, \cdots, L\}$.

Then, we derive the minimization objective function of Deep GP which is a flexible probabilistic NN model that can model the distribution of functions (Gal & Ghahramani, 2016). We assume that

$\boldsymbol{W}_l$ is a random matrix and $\boldsymbol{w} = \{\boldsymbol{W}_l\}_{l=1}^L$, and denote the prior by $p(\boldsymbol{w})$. Then, the predictive distribution of the deep GP can be expressed as Eq. (2) given a precision $\tau > 0$

$$p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{X}, \boldsymbol{Y}) = \int p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{w})p(\boldsymbol{w}|\boldsymbol{X}, \boldsymbol{Y})d\boldsymbol{w}, \tag{2}$$

$$p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{w}) = \mathcal{N}(\boldsymbol{y}; \widehat{\boldsymbol{y}}, \tau^{-1}\boldsymbol{I}), \quad \widehat{\boldsymbol{y}} = \sqrt{\frac{1}{K_L}}\boldsymbol{W}_L\sigma\left(\cdots\sqrt{\frac{1}{K_1}}\boldsymbol{W}_2\sigma\left(\boldsymbol{W}_1\boldsymbol{x} + \boldsymbol{u}_1\right)\right).$$

The posterior distribution $p(\boldsymbol{w}|\boldsymbol{X}, \boldsymbol{Y})$ is intractable, and one way of training the deep GP is variational inference where a family of tractable distributions $q(\boldsymbol{w})$ is chosen to approximate the posterior. Specifically, we define the hierarchy of $q(\boldsymbol{w})$ as Eq. (3)

$$q(\boldsymbol{W}_{lij}|\boldsymbol{Z}_{lij}, \boldsymbol{U}_{lij}, \boldsymbol{M}_l) \sim \boldsymbol{Z}_{lij} \cdot \mathcal{N}(\boldsymbol{M}_{lij}\boldsymbol{U}_{lij}, \sigma^2) + (1 - \boldsymbol{Z}_{lij}) \cdot \mathcal{N}(0, \sigma^2),$$

$$q(\boldsymbol{M}_l|\boldsymbol{U}_l) \propto \exp(\boldsymbol{M}_l \odot |\boldsymbol{U}_l|), \quad \boldsymbol{U}_{lij} \sim \mathcal{N}(\boldsymbol{V}_{lij}, \sigma^2), \quad \boldsymbol{Z}_{lij} \sim \text{Bernoulli}(p_l), \tag{3}$$

where $l = 1, \cdots, L$, i and j denote the row and column index, $\boldsymbol{M}_l$ is a matrix that takes the value 0 or 1, and the number of 1 is restricted, $\boldsymbol{W}_l$ is the sparse weights, $\boldsymbol{U}_l$ is the variational parameters, and $\boldsymbol{V}_l$ is the variational hyper parameters.

We iteratively update $\boldsymbol{M}_l$ and $\boldsymbol{W}_l$ to approximate the posterior. For the update of $\boldsymbol{M}_l$, we obtain a point estimate by maximising $q(\boldsymbol{M}_l|\boldsymbol{U}_l)$ under the sparsity constraint, which is equivalent to setting the part with larger weight magnitude to 1 and the rest to 0. For the update of $\boldsymbol{W}_l$, we minimise the KL divergence between $q(\boldsymbol{w})$ and the posterior of deep GP as shown in Eq. (4)

$$-\int q(\boldsymbol{w}) \log p(\boldsymbol{Y}|\boldsymbol{X}, \boldsymbol{w})d\boldsymbol{w} + D_{\text{KL}}(q(\boldsymbol{w})\|p(\boldsymbol{w})). \tag{4}$$

For the first term in Eq. (4), we can first rewrite it as $-\sum_{n=1}^N \int q(\boldsymbol{w}) \log p(y_n|\boldsymbol{x}_n, \boldsymbol{w})$. Then, we can approximate each integration in the sum with a single estimate $\widehat{\boldsymbol{w}}$. For the second term in Eq. (4), we can approximate it as $\sum_{l=1}^L (\frac{p_l}{2}\|\boldsymbol{U}_l\|_2^2 + \frac{1}{2}\|\boldsymbol{u}_l\|_2^2)$. As a result, we can derive the objective as

$$\mathcal{L}_{\text{GP}} := \frac{1}{N}\sum_{i=1}^N \frac{-\log p(\boldsymbol{y}_n|\boldsymbol{x}_n, \widehat{\boldsymbol{w}})}{\tau} + \sum_{l=1}^L (\frac{p_l}{2}\|\boldsymbol{U}_l\|_2^2 + \frac{1}{2}\|\boldsymbol{u}_l\|_2^2), \tag{5}$$

which is shown to have the same form as the objective function in Eq. (1) with appropriate hyperparameters for the deep GP. This suggests that our CigL can be viewed as an approximation to the deep GP using hierarchical variational inference.

4.2 CigL with Better Confidence Calibration

Obtaining reliable DNNs is more challenging in sparse training, and we will show why our CigL provides a solution to this problem. Bayesian methods have shown the ability to improve confidence calibration (Gal & Ghahramani, 2016; Ashukha et al., 2020), but they become more difficult to fit the posterior well under sparse constraints, limiting their ability to solve unreliable problems. CigL can be viewed as a Bayesian method that can improve confidence calibration by performing better posterior approximations in two ways discussed below.

On the one hand, the model is more challenging to fully explore the weight space due to sparsity constraint, while inappropriate weight values can also negatively affect the mask search. A large percentage of weights are fixed to zero, which cuts off the update routes and thus narrows the family of Bayesian proposal distributions. This makes both optimization and sampling more difficult. Since our CigL adds a hierarchical structure to the variational distributions, we have a larger family of distributions, which makes it possible to capture more complex marginal distributions and reduces the difficulty of fitting the posterior.

On the other hand, the posterior landscape changes when sparsity constraints are added, such as an increased correlation between hidden variables. In CigL, there is a stronger correlation between $\boldsymbol{Z}$ and $\boldsymbol{W}$ (shown in the Appendix C). When in a dense model, the accuracy does not change much if we randomly draw $\boldsymbol{Z}$ and use $\boldsymbol{Z} \odot \boldsymbol{W}$ instead of $\boldsymbol{W}$. However, at high sparsity like 95%, we see a significant decrease in accuracy when $\boldsymbol{Z} \odot \boldsymbol{W}$ is used instead of $\boldsymbol{W}$. Thus, in CigL, the pairings of $\boldsymbol{Z}$ and $\boldsymbol{W}$ are collected to to capture the correlation, leading to a better posterior approximation.

4.3 Connection to Dropout

Our CigL can be seen as a new version of Dropout, and our random mask Z is related to the Dropout mask. Dropout is a widely used method to overcome the overfitting problem (Hinton et al., 2012; Wan et al., 2013; Srivastava et al., 2014). Two widely used types are unit dropout and weight dropout, which randomly discard units (neurons) and individual weights at each training step, respectively. Both methods use dropouts only in the training phase and remove them in the testing phase, which is equivalent to discarding Z and only using W for prediction. However, simply dropping Z can be detrimental to the fit of the posterior. Thus, MC dropout collects multiple models by randomly selecting multiple dropout masks, which is equivalent to extracting multiple Z and using one W for prediction. However, only using one W neither fully expresses the posterior landscape nor captures the correlation between Z and W. In contrast, our CigL uses multiple pairings of Z and W, which can better approximate the posterior under sparsity constraints.

4.4 Connection to Weight Averaging

Our weight & mask averaging can be seen as an extension of weight averaging (WA), which averages the weights of multiple model samples to produce a single output model (Izmailov et al., 2018; Wortsman et al., 2022). Compared to deep ensembles (Ashukha et al., 2020), WA outputs only one model, which reduces the forward FLOPs and speeds up prediction. When these model samples are located in one low error basin, it usually leads to wider optima and better generalization. However, although WA can produce better generalization, it does not improve the confidence calibration (Wortsman et al., 2022). In contrast to WA, our weight & mask averaging uses masks for weighted averaging and improves the confidence calibration with similar FLOPs in the prediction.

5 Experiments

We perform a comprehensive empirical evaluation of CigL, comparing it with the popular baseline method RigL (Evci et al., 2020). RigL is a popular sparse training method that uses weights magnitudes to prune and gradient magnitudes to grow connections.

Datasets & Model Architectures: We follow the settings in Evci et al. (2020) for a comprehensive comparison. Our experiments are based on three benchmark datasets: CIFAR-10 and CIFAR-100 (Krizhevsky et al., 2009) and ImageNet-2012 (Russakovsky et al., 2015). For model architectures, we used ResNet-50 (He et al., 2016) and Wide-ResNet-22-2 (Zagoruyko & Komodakis, 2016). We repeat all experiments 3 times and report the mean and standard deviation.

Sparse Training Settings: For sparse training, we check multiple sparsities, including 80%, 90%, 95%, and 99%, which can sufficiently reduce the memory requirement and is of more interest.

Implementations: We follow the settings in (Evci et al., 2020; Sundar & Dwaraknath, 2021). The parameters are optimized by SGD with momentum. For the learning rate, we use piecewise constant decay scheduler. For CIFAR-10 and CIFAR-100, we train all the models for 250 epochs with a batch size of 128. For ImageNet, we train all the models for 100 epochs with a batch size of 64.

5.1 Comparison between Popular Sparse Training Method

Results on CIFAR-10 and CIFAR-100. We first compare our CigL and RigL by the expected calibration error (ECE) (Guo et al., 2017), a popular measure of the discrepancy between a model's confidence and true accuracy, with a lower ECE indicating better confidence calibration and higher reliability. In Figure 2, the pink and blue curves represent CigL and RigL, respectively, where the colored ares represent the 95% confidence intervals. We can see that the pink curves are usually lower than the blue curves for different sparsities (80%, 90%, 95%, 99%), which implies that our CigL can reduce the ECE and improve the confidence calibration of the produced sparse models.

Apart from ECE value, we also compare our CigL and RigL by the testing accuracy for multiple sparsities (80%, 90%, 95%, 99%). We summarize the results for sparse ResNet-50 in Table 1. It is observed that CigL tends to bring comparable or higher accuracy, which demonstrates that CigL can simultaneously maintain or improve the accuracy.

(a) CIFAR-10, ResNet-50 (b) CIFAR-10, Wide-ResNet-22-2 (c) CIFAR-100, ResNet-50

Figure 2: ECE value comparison between CigL and RigL at different sparsities (80%, 90%, 95%, 99%). Compared to RigL, CigL produces sparse models with smaller ECE values.

Table 1: Testing accuracy (%) comparison between CigL and RigL at different sparsities (80%, 90%, 95%, 99%). Compared to RigL, CigL maintains comparable or higher test accuracy.

	CIFAR-10		CIFAR-100	
	RIGL	RIGL+ADOPT	RIGL	RIGL+ADOPT
80% SPARSITY	94.02 (0.115)	**94.75** (0.107)	72.08 (0.109)	**76.84** (0.089)
90% SPARSITY	93.84 (0.184)	**94.56** (0.189)	71.90 (0.172)	**76.24** (0.181)
95% SPARSITY	93.19 (0.198)	**94.20** (0.202)	70.90 (0.210)	**74.71** (0.197)
99% SPARSITY	91.31 (0.205)	**92.42** (0.196)	65.57 (0.208)	**66.42** (0.206)

Results on ImageNet-2012. We also compare the ECE values and test accuracy of our CigL and RigL on a larger dataset, ImageNet-2012, where the sparsity of ResNet-50 is 80% and 90%. As shown in Figure 3, the pink and blue bars represent our CigL and RigL, respectively. For the comparison of ECE values in (a), the pink bars are shorter than the blue bars, indicating an improved reliability of the sparse model produced by CigL. For the test accuracy comparison in (b), the pink and blue bars are very similar in height, implying that the accuracy of CigL is comparable to that of RigL.

(a) ECE value (RM) (b) Test accuracy (RM)

Figure 3: ECE value and test accuracy(%) of CigL and RigL at 80% & 90% sparsities on ImageNet-2012. Compared with RigL, CigL has smaller ECE values and comparable test accuracies.

5.2 COMPARISON BETWEEN DIFFERENT DROPOUT METHODS

In this section, since our CigL is related to dropout methods, we compare our CigL with RigL using existing popular dropout methods, namely weight dropout (W-DP) and MC dropout (MC-DP). **The comparison of test accuracy** is shown in Table 2. Our CigL usually provides a comparable or higher accuracy compared to RigL. However, using weight dropout and MC dropout in RigL usually result in a decrease in accuracy. We also summarize **the comparison of the ECE value** between CigL and different dropout methods in Table 3. For each sparsity and architecture, we have marked in bold those cases where the ECE value is significantly reduced ($\geq$ 15% reduction compared to RigL). Our CigL are always bolded, indicating its ability to reduce ECE value and increase reliability in sparse training. But RigL + weight dropout does not significantly reduce ECE values in almost all cases and RigL + MC dropout also does not improve the calibration in highly sparse cases (99% sparsity).

5.3 COMPARISON BETWEEN OTHER CALIBRATION METHODS

In this section, we compare our CigL with existing popular calibration methods, including mixup (Zhang et al., 2017), temperature scaling (TS) (Guo et al., 2017), and label smoothing (LS) (Szegedy et al., 2016). **The testing ECE** are depicted in Figure 4, where the pink and blue polygons represent CigL and other calibration methods, respectively. We can see that CigL usually gives smaller polygons, indicating a better confidence calibration.

Table 2: Testing accuracy (%) comparison between CigL, RigL + weight dropout (W-DP), and RigL + MC dropout (MC-DP) at different sparsities (80%, 90%, 95%, 99%). Compared to RigL, RigL + W-DP, and RigL + MC-DP, CigL maintains comparable or higher test accuracy.

		80% Sparsity	90% Sparsity	95% Sparsity	99% Sparsity
ResNet-50	RigL	94.02 (0.115)	93.84 (0.184)	93.19 (0.198)	91.31 (0.205)
	RigL + W-DP	93.26 (0.114)	93.47 (0.186)	92.71 (0.193)	89.99 (0.210)
	RigL + MC-DP	93.39 (0.105)	93.71 (0.181)	92.87 (0.205)	89.84 (0.212)
	CigL	**94.75** (0.107)	**94.56** (0.189)	**94.20** (0.202)	**92.42** (0.196)
WRN-22-2	RigL	93.12 (0.188)	92.26 (0.187)	91.02 (0.179)	83.82 (0.224)
	RigL + W-DP	91.77 (0.182)	91.44 (0.191)	89.66 (0.183)	80.42 (0.215)
	RigL + MC-DP	91.75 (0.149)	91.49 (0.187)	89.39 (0.177)	77.48 (0.198)
	CigL	**93.95** (0.088)	**93.05** (0.219)	**91.34** (0.171)	**83.96** (0.189)

Table 3: Testing ECE comparison between CigL, RigL + weight dropout (W-DP), and RigL + MC dropout (MC-DP) at different sparsities (80%, 90%, 95%, 99%). Compared to RigL + W-DP and RigL + MC-DP, CigL more consistently achieves a significant reduction in the ECE value of RigL.

		80% Sparsity	90% Sparsity	95% Sparsity	99% Sparsity
ResNet-50	RigL	0.0423 (0.001)	0.0441 (0.001)	0.0504 (0.001)	0.0571 (0.001)
	RigL + W-DP	0.0504 (0.002)	0.0438 (0.001)	0.0462 (0.002)	**0.0315** (0.002)
	RigL + MC-DP	**0.0322** (0.001)	**0.0200** (0.001)	**0.0121** (0.001)	0.0528 (0.002)
	CigL	**0.0356** (0.001)	**0.0361** (0.001)	**0.0385** (0.001)	**0.0298** (0.001)
WRN-22-2	RigLt	0.0319 (0.003)	0.0272 (0.001)	0.0235 (0.001)	0.0150 (0.002)
	RigL + W-DP	0.0433 (0.003)	0.0348 (0.002)	0.0256 (0.002)	0.0174 (0.003)
	RigL + MC-DP	**0.0159** (0.001)	**0.0077** (0.002)	0.0384 (0.001)	0.1502 (0.002)
	CigL	**0.0178** (0.001)	**0.0159** (0.001)	**0.0131** (0.001)	**0.0101** (0.002)

(a) ADOPT vs. Mixup   (b) ADOPT vs. Temper. Scaling   (c) ADOPT vs. Label Smoothing

Figure 4: ECE value comparison between CigL and RigL + other calibration methods at different sparsities (80%, 90%, 95%, 99%). The pink polygons (CigL) are smaller than the blue polygons (other calibration methods), indicating a better confidence calibration using CigL compared to (a) Mixup, (b) Temperature scaling, and (c) Label smoothing.

5.4 Ablation Studies

We do ablation studies to demonstrate the importance of each component in our CigL, where we train sparse networks using our CigL without random masks (CigL w/o RM) and CigL without weight & mask averaging (CigL w/o WMA), respectively. In CigL w/o RM, we search for sparse topologies using only the deterministic mask. In CigL w/o WMA, we collect multiple model samples and use prediction averaging during testing. Figures 5(a)-(b) show **the effect of random masks** on the test accuracy and ECE values, where the blue, green, and pink bars represent RigL, CigL w/o

(a) Test accuracy (RM)   (b) ECE value (RM)   (c) Test accuracy (WMA)   (d) ECE value (WMA)

Figure 5: Ablation studies: test accuracy(%) and ECE value comparison between CigL, CigL without random mask (CigL w/o RM), and CigL without weight & mask averaging (CigL w/o WMA) at different sparsities (80%, 90%, 95%, 99%). Compared to (a)-(b) CigL w/o RM and (c)-(d) CigL w/o WMA, CigL more consistently produces sparse models with low ECE values and high accuracy.

RM, and CigL, respectively. We can see that if we remove the random mask, we can still obtain an improvement in accuracy compared to RigL. However, the ECE values do not decrease as much as CigL, indicating that the CigL w/o RM is not as effective as CigL in improving the confidence calibration. Figures 5(c)-(d) further show **the effect of weight & mask averaging**. We can see that without using weight & mask averaging, the accuracy decreases and the ECE value increases in high sparsity such as 95% and 99%, which demonstrates the importance of weight & mask averaging in sparsity training.

6   DISCUSSION & CONCLUSION

We provide the first comprehensive study on the reliability of sparse training and find that sparse training exacerbates the over-confidence problem of DNNs. We then develop a new sparse training method, CigL, to produce more reliable sparse models, which can simultaneously maintain or even improve accuracy with only a slight increase in computational and storage burden. Our CigL utilizes two masks, including a deterministic mask and a random mask, which allows the sparse model to better explore the weight space. Then, we design weight & mask averaging method to combine multiple sparse weights and random masks into a single model with improved reliability. We prove that CigL can be viewed as a hierarchical variational approximation to the probabilistic deep Gaussian process. Experiments results on multiple benchmark datasets, model architectures, and sparsities show that our CigL reduces ECE values by up to **47.8%** with comparable or higher accuracy.

One phenomenon we find worth discussing is the *double descent* in reliability of sparse training. Nakkiran et al. (2021) first observed this double descent phenomenon in DNNs, where as the model size, data size, or training time increases, the performance of the model first improves, then gets worse, and then improves again. Consistent with the previous definition, we consider sparsity and reliability as the measures of model size and performance, respectively. Then, as shown in the Figure 1 (c), as the sparsity decreases (model size increases), the reliability (model performance) gets better, then gets worse, and then gets better again. To explain this phenomenon, we divide sparsity into four phases from left (99.9%) to right (0%). **(a) The sparse model starts as a poor model**, which is too sparse to learn the data well (low reliability & accuracy). **(b) It gradually becomes equivalent to a shallow model** that can learn some patterns but is not flexible enough to learn all the data well (high reliability & moderate level of accuracy). **(c) Then, it moves to a sparse deep model** that can accommodate complex patterns but suffers from poor exploration (low reliability & high accuracy). **(d) Finally, it reaches a dense deep model** with over-confidence issues (moderate level of reliability & high accuracy). It is observed that at around 95% sparsity, the sparse model can achieve comparable accuracy and high sparsity at the same time, which makes it important in practical applications. However, the ECE value is at the peak of the double-descent curve at this point, which implies that the reliability of the sparse model is at a low level. Thus, our CigL smooths the double descent curve and produce reliable models on those important high sparsity levels.

REFERENCES

Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. *arXiv preprint arXiv:2002.06470*, 2020.

Guillaume Bellec, David Kappel, Wolfgang Maass, and Robert Legenstein. Deep rewiring: Training very sparse deep networks. *International Conference on Learning Representations (ICLR)*, 2018.

Sameer Bibikar, Haris Vikalo, Zhangyang Wang, and Xiaohan Chen. Federated dynamic sparse training: Computing less, communicating less, yet learning better. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 6080–6088, 2022.

Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*, volume 4. Springer, 2006.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, et al. End to end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016.

Andreas Damianou and Neil D Lawrence. Deep gaussian processes. In *Artificial intelligence and statistics*, pp. 207–215. PMLR, 2013.

Tim Dettmers and Luke Zettlemoyer. Sparse networks from scratch: Faster training without losing performance. *arXiv preprint arXiv:1907.04840*, 2019.

Anastasia Dietrich, Frithjof Gressmann, Douglas Orr, Ivan Chelombiev, Daniel Justus, and Carlo Luschi. Towards structured dynamic sparse pre-training of bert. *arXiv preprint arXiv:2108.06277*, 2021.

Utku Evci, Fabian Pedregosa, Aidan Gomez, and Erich Elsen. The difficulty of training sparse neural networks. *arXiv preprint arXiv:1906.10732*, 2019.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In *International Conference on Machine Learning*, pp. 2943–2952. PMLR, 2020.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *International Conference on Learning Representations (ICLR)*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International conference on machine learning*, pp. 1321–1330. PMLR, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Zheng He, Zeke Xie, Quanzhi Zhu, and Zengchang Qin. Sparse double descent: Where network pruning aggravates overfitting. In *International Conference on Machine Learning*, pp. 8635–8659. PMLR, 2022.

Geoffrey E Hinton, Nitish Srivastava, Alex Krizhevsky, Ilya Sutskever, and Ruslan R Salakhutdinov. Improving neural networks by preventing co-adaptation of feature detectors. *arXiv preprint arXiv:1207.0580*, 2012.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Siddhant Jayakumar, Razvan Pascanu, Jack Rae, Simon Osindero, and Erich Elsen. Top-kast: Top-k always sparse training. *Advances in Neural Information Processing Systems*, 33:20744–20754, 2020.

Xiaoqian Jiang, Melanie Osl, Jihoon Kim, and Lucila Ohno-Machado. Calibrating predictive model estimates to support personalized medicine. *Journal of the American Medical Informatics Association*, 19(2):263–274, 2012.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. *Technical report, University of Toronto*, 2009.

Shiwei Liu, Lu Yin, Decebal Constantin Mocanu, and Mykola Pechenizkiy. Do we actually need dense over-parameterization? in-time over-parameterization in sparse training. In *International Conference on Machine Learning*, pp. 6989–7000. PMLR, 2021.

Decebal Constantin Mocanu, Elena Mocanu, Peter Stone, Phuong H Nguyen, Madeleine Gibescu, and Antonio Liotta. Scalable training of artificial neural networks with adaptive sparse connectivity inspired by network science. *Nature communications*, 9(1):1–12, 2018.

Hesham Mostafa and Xin Wang. Parameter efficient training of deep convolutional neural networks by dynamic sparse reparameterization. In *International Conference on Machine Learning*, pp. 4646–4655. PMLR, 2019.

Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep double descent: Where bigger models and more data hurt. *Journal of Statistical Mechanics: Theory and Experiment*, 2021(12):124003, 2021.

Jeremy Nixon, Michael W Dusenberry, Linchuan Zhang, Ghassen Jerfel, and Dustin Tran. Measuring calibration in deep learning. In *CVPR Workshops*, volume 2, 2019.

Ozan Özdenizci and Robert Legenstein. Training adversarially robust sparse networks via bayesian connectivity sampling. In *International Conference on Machine Learning*, pp. 8314–8324. PMLR, 2021.

Kanil Patel, William Beluch, Kilian Rambach, Michael Pfeiffer, and Bin Yang. Improving uncertainty of deep learning-based object classification on radar spectra using label smoothing. In *2022 IEEE Radar Conference (RadarConf22)*, pp. 1–6. IEEE, 2022.

Rahul Rahaman et al. Uncertainty quantification and deep ensembles. *Advances in Neural Information Processing Systems*, 34:20063–20075, 2021.

Rajesh Ranganath, Dustin Tran, and David Blei. Hierarchical variational models. In *International conference on machine learning*, pp. 324–333. PMLR, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Jonathan Schwarz, Siddhant Jayakumar, Razvan Pascanu, Peter E Latham, and Yee Teh. Power-propagation: A sparsity inducing weight reparameterisation. *Advances in Neural Information Processing Systems*, 34:28889–28903, 2021.

Ghada Sokar, Elena Mocanu, Decebal Constantin Mocanu, Mykola Pechenizkiy, and Peter Stone. Dynamic sparse training for deep reinforcement learning. *arXiv preprint arXiv:2106.04217*, 2021.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Yiyou Sun and Yixuan Li. On the effectiveness of sparsification for detecting the deep unknowns. *arXiv preprint arXiv:2111.09805*, 2021.

Varun Sundar and Rajat Vadiraj Dwaraknath. [reproducibility report] rigging the lottery: Making all tickets winners. *arXiv preprint arXiv:2103.15767*, 2021.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2818–2826, 2016.

Li Wan, Matthew Zeiler, Sixin Zhang, Yann Le Cun, and Rob Fergus. Regularization of neural networks using dropconnect. In *International conference on machine learning*, pp. 1058–1066. PMLR, 2013.

Xiao Wang, Hongrui Liu, Chuan Shi, and Cheng Yang. Be confident! towards trustworthy graph neural networks via confidence calibration. *Advances in Neural Information Processing Systems*, 34:23768–23779, 2021a.

Yezhen Wang, Bo Li, Tong Che, Kaiyang Zhou, Ziwei Liu, and Dongsheng Li. Energy-based open-world uncertainty modeling for confidence calibration. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9302–9311, 2021b.

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International Conference on Machine Learning*, pp. 23965–23998. PMLR, 2022.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *British Machine Vision Conference*, 2016.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

Jize Zhang, Bhavya Kailkhura, and T Yong-Jin Han. Mix-n-match: Ensemble and compositional methods for uncertainty calibration in deep learning. In *International conference on machine learning*, pp. 11117–11128. PMLR, 2020.

Xiao Zhou, Weizhong Zhang, Hang Xu, and Tong Zhang. Effective sparsification of neural networks with global sparsity constraint. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3599–3608, 2021.

A APPENDIX: BACKGROUND

In this section, we briefly summarize CigL, Gaussian processes, and hierarchical variational inference, which will be used to support the main theoretical analysis of this work.

A.1 SPARSE TRAINING: CIGL

We first review our CigL method for the case of a single hidden layer neural network (NN). This is done for ease of notation, and it is straightforward to generalise to multiple layers (Gal & Ghahramani, 2016). Denote by $\boldsymbol{W}_1$, $\boldsymbol{W}_2$ the sparse weight matrices connecting the first layer to the hidden layer and connecting the hidden layer to the output layer respectively. For the sparse mask controlling the sparse topology, we use $\boldsymbol{M}_1$, $\boldsymbol{M}_2$ to denote the corresponding deterministic masks for $\boldsymbol{W}_1$ and $\boldsymbol{W}_2$, respectively. And we use $\boldsymbol{Z}_1$, $\boldsymbol{Z}_2$ to denote the corresponding random masks for $\boldsymbol{W}_1$ and $\boldsymbol{W}_2$, respectively. These linearly transform the layers' inputs before applying some element-wise non-linearity $\sigma()$. Denote by $\boldsymbol{b}$ the biases by which we shift the input of the non-linearity. We assume the model to output D dimensional vectors while its input is Q dimensional vectors, with K hidden units. Thus $\boldsymbol{W}_1$, $\boldsymbol{M}_1$, and $\boldsymbol{Z}_1$ are $Q \times K$ matrices, $\boldsymbol{W}_2$, $\boldsymbol{M}_1$, and $\boldsymbol{Z}_1$ are $K \times D$ matrices, and $\boldsymbol{b}$ is a K dimensional vector. A sparse NN model with the two masks would output $\widehat{y} = \sigma(\boldsymbol{x}\boldsymbol{Z}_1 \odot \boldsymbol{W}_1 + \boldsymbol{b})\boldsymbol{Z}_2 \odot \boldsymbol{W}_2$ given some input $\boldsymbol{x}$.

For the update of masks, the deterministic masks is updated by exploiting the magnitude of weights and gradients. The random mask is randomly sampled. For the update of weights, we use E to denote the loss function, which is the euclidean loss for regression problem

$$E = \frac{1}{2N} \sum_{n=1} N||y_n - \widehat{y}_n||_2^2,$$

(6)

where y_n is the observed response, $\widehat{y}_n$ is the prediction based on input $\boldsymbol{x}_n$ for $n = 1, \cdots, N$.

For classification task with D classes, we use softmax function to map the output $\widehat{y}_n$ to the probability score for each class $\widehat{p}_{nd} = \exp(\widehat{y}_{nd})/(\sum_k \exp(\widehat{y}_{nk}))$, and the loss function will be

$$E = -\frac{1}{N} \sum_{n=1} N \log(\widehat{p}_{n,c_n}),$$

(7)

where $c_n \in [1, 2, \cdots, D]$ is the true class label for $\boldsymbol{x}_n$.

During NN optimization process, apart from the loss function mentioned above, l_2 regularisation is often used to improve the performance, leading to a minimisation objective:

$$\mathcal{L}_{\text{CigL}} := \frac{1}{N} \sum_{i=1}^{N} E(y_i, \widehat{y}_i) + \lambda_1 ||\boldsymbol{W}_1||_2^2 + \lambda_2 ||\boldsymbol{W}_2||_2^2 + \lambda_3 ||\boldsymbol{b}||_2^2.$$

(8)

Therefore, duing the training process of CigL, we iteratively update the sparse weights $\boldsymbol{W}$ by minimising Eq. (8) and update deterministic mask based on the magnitude of weights and gradients.

A.2 GAUSSIAN PROCESS

The Gaussian process (GP) is a popular non-parametric Bayesian methodto model distributions over functions, which can be applied to bothe regression and classification tasks. It has good performance in various fields, but it will bring huge computation burden when faced with a large number of data. The use of variational inference for GP can make it scalable to large data.

Given a data $\{\boldsymbol{x}_n, \boldsymbol{y}_n\}, n = 1, \cdots, N$, the task is to estimate an unknown function $\boldsymbol{y} = f(\boldsymbol{x})$, where $\boldsymbol{X} \in \mathbb{R}^{N \times Q}$ and $\boldsymbol{Y} \in \mathbb{R}^{N \times D}$. GP usually put a prior over the function space and we want to fit the posterior distribution over the function space:

$$p(\boldsymbol{f}|\boldsymbol{X}, \boldsymbol{Y}) \propto p(\boldsymbol{Y}|\boldsymbol{X}, \boldsymbol{f})p(\boldsymbol{f}).$$

Within Gaussian process, we usually place a Gaussian prior over the function space, and it equivalent to placing a joint Gaussian distribution over all function values

$$\boldsymbol{F}|\boldsymbol{X} \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{K}(\boldsymbol{X}, \boldsymbol{X}))$$

(9)

$$\boldsymbol{Y}|\boldsymbol{F} \sim \mathcal{N}(\boldsymbol{F}, \tau^{-1})$$

where τ is a precision parameter and $\boldsymbol{I}_N$ is the identity matrix with dimensions $N \times N$.

For classification tasks, we can formulate the model as

$$\boldsymbol{F}|\boldsymbol{X} \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{K}(\boldsymbol{X}, \boldsymbol{X})) \tag{10}$$

$$\boldsymbol{Y}|\boldsymbol{F} \sim \mathcal{N}(\boldsymbol{F}, \tau^{-1}),$$

$$c_n|\boldsymbol{Y} \sim \text{Categorical}\left(\exp(\widehat{y}_{nd})/(\sum_k \exp(\widehat{y}_{nk})) \right) \tag{11}$$

An important aspect of Gaussian process is the choice of the covariance function, which reflects how we believe the similarity between each pair of inputs $\boldsymbol{x}_i$ and $\boldsymbol{x}_j$. One widely-used covariance function is stationary squared exponential covariance function. In addition, some non-stationary covariance function are proposed, such as dot-product kernels and more flexible deep network kernels.

A.3 HIERARCHICAL VARIATIONAL INFERENCE

Variational inference (VI) is a broadly-used technique to approximate intractable integrals in Bayesian modeling, which sets up a parameterized family of tractable distributions over the latent variables and then optimizes the parameters to be close to the posterior. More specifically, suppose $\boldsymbol{w}$ is the set of random variables defining our model. Then, the predictive distribution will be formulated as

$$p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{X}, \boldsymbol{Y}) = \int p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{w})p(\boldsymbol{w}|\boldsymbol{X}, \boldsymbol{Y})d\boldsymbol{w},$$

where the posterior $p(\boldsymbol{w}|\boldsymbol{X}, \boldsymbol{Y})$ is usually intractable. Thus, we define a family of tractable approximating variational distributions $q(\boldsymbol{w})$ to approach the posterior.

To find the closest approximating distribution among the family of $q(\boldsymbol{w})$, we minimise the Kullback–Leibler (KL) divergence between $q(\boldsymbol{w})$ and posterior $p(\boldsymbol{w}|\boldsymbol{X}, \boldsymbol{Y})$, which is equivalent to maximising the log evidence lower bound (ELBO) with respect to $q(\boldsymbol{w})$:

$$\mathcal{L}_{\text{VI}} := \int q(\boldsymbol{w}) \log p(\boldsymbol{Y}|\boldsymbol{X}, \boldsymbol{w})d\boldsymbol{w} - D_{\text{KL}}(q(\boldsymbol{w})\|p(\boldsymbol{w})).$$

After obtaining an good approximation $q(\boldsymbol{w})$, we can update the predictive distribution to

$$p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{X}, \boldsymbol{Y}) = \int p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{w})q(\boldsymbol{w})d\boldsymbol{w}.$$

However, when faced with posterior difficult to fit, $q(\boldsymbol{w})$ can be limited and not flexible enough to approach the posterior. In this case, VI cannot capture the posterior dependencies between latent variables that both improve the fidelity of the approximation and are sometimes intrinsically meaningful. To solve this limitation of VI, hierarchical variational inference (HVI) is proposed, which can capture both posterior dependencies between the latent variables and more complex marginal distributions (Ranganath et al., 2016). More specifically about HVI, we extend the limited family of VI distribution hierarchically, i.e., by placing a prior on the parameters of the likelihood. Suppose VI uses $q(\boldsymbol{w}; \lambda)$ to approximate the posterior where λ is the variational parameters to optimise. HVI will add prior on λ and uses $q(\boldsymbol{w}|\lambda)q(\lambda; \theta)$. The ELBO equivalently will be as:

$$\mathcal{L}_{\text{HVI}} := \mathbb{E}_{q_{\text{HVI}}(\boldsymbol{w};\lambda)}[\log p(\boldsymbol{x}, \boldsymbol{w}) - \log q_{\text{HVI}}(\boldsymbol{w}; \theta)]$$
$$\leq \mathbb{E}_{q_{\text{HVI}}(\boldsymbol{w};\lambda)}[\log p(\boldsymbol{x}, \boldsymbol{w})] - \mathbb{E}_{q(\boldsymbol{w},\lambda)}[\log q(\lambda) + \log q(\boldsymbol{w}|\lambda) - \log r(\lambda|\boldsymbol{w}; \theta)].$$

where $r(\lambda|\boldsymbol{w}; \theta)$ is introduced to apply the variational principle.

B APPENDIX: CigL AS A HIERARCHICAL BAYESIAN APPROXIMATION

We show that sparse deep NNs trained with CigL are mathematically equivalent to approximate hierarchical variational inference in the deep Gaussian process (marginalised over its covariance

function parameters). For this we build on previous work (Gal & Ghahramani, 2016) that proved unit dropout applied before every weight layer are mathematically equivalent to approximate variational inference in the deep Gaussian process. Starting with the full Gaussian process we will develop an approximation that will be shown to be equivalent to the sparse NN optimisation objective with CigL (eq. (8)) with either the Euclidean loss in the case of regression or softmax loss in the case of classification. This view of CigL will allow us to derive new probabilistic results in sparse training.

B.1 A Gaussian Process Approximation

In this section, we will re-parameterise the deep GP model and marginalise over the additional auxiliary random variables, which is built on Gal & Ghahramani (2016). To define our covariance function, let $\sigma(.)$ be some non-linear activation function and $\boldsymbol{K}(\boldsymbol{x}, \boldsymbol{y})$ can be formulated as:

$$\boldsymbol{K}(\boldsymbol{x}, \boldsymbol{y}) = \int p(\mathrm{w}) p(\mathrm{b}) \sigma(\mathrm{w}^\top \boldsymbol{x} + \boldsymbol{b}) \sigma(\mathrm{w}^\top \boldsymbol{y} + \boldsymbol{b}) d\boldsymbol{w} d\boldsymbol{b},$$

where $p(\mathrm{w})$ is a standard multivariate normal distribution in dimension Q.

We use Monte Carlo integration with K samples to approximate the integral above and get the finite rank covarinace function

$$\widehat{\boldsymbol{K}}(\boldsymbol{x}, \boldsymbol{y}) = \frac{1}{K} \sum_{k=1}^{K} \sigma(\mathrm{w}_k^\top \boldsymbol{x} + \boldsymbol{b}_k) \sigma(\mathrm{w}_k^\top \boldsymbol{y} + \boldsymbol{b}_k),$$

where $\mathrm{w}_k \sim p(\mathrm{w})$ and $\boldsymbol{b}_k \sim p(\mathrm{b})$. K is the number of hidden units in our single hidden layer sparse NN approximation. The generative model will be as follow when we use $\widehat{\boldsymbol{K}}$ instead of $\boldsymbol{K}$:

$$\boldsymbol{w} \sim p(\boldsymbol{w}), \quad \mathrm{b}_k \sim p(\mathrm{b}),$$

$$\boldsymbol{W}_1 = [\boldsymbol{w}_{qk}]_{q=1}^{Q}{}_{k=1}^{K}, \quad \boldsymbol{b} = [b_k]_{k=1}^{K},$$

$$\widehat{\boldsymbol{K}}(\boldsymbol{x}, \boldsymbol{y}) = \frac{1}{K} \sum_{k=1}^{K} \sigma(\mathrm{w}_k^\top \boldsymbol{x} + \boldsymbol{b}_k) \sigma(\mathrm{w}_k^\top \boldsymbol{y} + \boldsymbol{b}_k),$$

$$\boldsymbol{F} | \boldsymbol{X}, \boldsymbol{W}_1, \boldsymbol{b} \sim \mathcal{N}(0, \widehat{\boldsymbol{K}}(\boldsymbol{x}, \boldsymbol{y})),$$

$$\boldsymbol{Y} | \boldsymbol{F} \sim \mathcal{N}(\boldsymbol{F}, \tau^{-1} \boldsymbol{I}_n),$$

where $\boldsymbol{W}_1 \in \mathbb{R}^{Q \times K}$ which parameterise the covariance function.

We can get the predictive distribution by integrating over the $\boldsymbol{F}$, $\boldsymbol{W}_1$, and $\boldsymbol{b}$

$$p(\boldsymbol{Y} | \boldsymbol{X}) = \int p(\boldsymbol{Y} | \boldsymbol{F}) p(\boldsymbol{F} | \boldsymbol{W}_1, \boldsymbol{b}, \boldsymbol{X}) p(\boldsymbol{W}_1) p(\boldsymbol{b}) d\boldsymbol{W}_1 d\boldsymbol{b}.$$

Denoting a $1 \times K$ row vector

$$\phi(\boldsymbol{x}, \boldsymbol{W}_1, \boldsymbol{b}) = \sqrt{\frac{1}{K}} \sigma(\boldsymbol{W}_1^\top \boldsymbol{x} + \boldsymbol{b})$$

and a $N \times K$ feature matrix $\Phi = [\phi(\boldsymbol{x}_n, \boldsymbol{W}_1, \boldsymbol{b})]_{n=1}^{N}$. Then, we can get $\widehat{\boldsymbol{K}}(\boldsymbol{X}, \boldsymbol{X}) = \Phi \Phi^\top$ and the predictive distribution can be rewritten as

$$p(\boldsymbol{Y} | \boldsymbol{X}) = \int \mathcal{N}(\boldsymbol{Y}; 0, \Phi \Phi^\top + \tau^{-1} \boldsymbol{I}_N) p(\boldsymbol{W}_1) p(\boldsymbol{b}) d\boldsymbol{W}_1 d\boldsymbol{b}$$

The normal distribution of $\boldsymbol{Y}$ inside the integral above can be written as a joint normal distribution over $\boldsymbol{y}_d$ which denoting the d'th columns of the $N \times D$ matrix $\boldsymbol{Y}$ $(d = 1, \cdots, D)$. For each term in the joint distribution, following Bishop & Nasrabadi (2006), we introduce a $K \times 1$ auxiliary random variable $\boldsymbol{w}_d \sim \mathcal{N}(0, \boldsymbol{I}_K)$,

$$\mathcal{N}(\boldsymbol{y}_d; 0, \Phi \Phi^\top + \tau^{-1} \boldsymbol{I}_N) = \int \mathcal{N}(\boldsymbol{y}_d; \Phi \boldsymbol{w}_d, \tau^{-1} \boldsymbol{I}_N) \mathcal{N}(\boldsymbol{w}_d; 0, \boldsymbol{I}_K) d\boldsymbol{w}_d.$$

We use $\boldsymbol{W}_2 = [\boldsymbol{w}_d]_{d=1}^{D} \in \mathbb{R}^{K \times D}$ and we get the predictive distribution as

$$p(\boldsymbol{Y} | \boldsymbol{X}) = \int p(\boldsymbol{Y} | \boldsymbol{X}, \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) p(\boldsymbol{W}_1) p(\boldsymbol{W}_2) p(\boldsymbol{b}) d\boldsymbol{W}_1 d\boldsymbol{W}_2 d\boldsymbol{b}.$$

B.2 Hierarchical Variational Inference in the Approximate Model

We next approximate the posterior over these variables with appropriate hierarchical approximating variational distributions. We define a hierarchical variational distribution as:

$$q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \coloneqq q(\boldsymbol{W}_1)q(\boldsymbol{W}_2)q(\boldsymbol{b}) = \int q(\boldsymbol{W}_1|\boldsymbol{U}_1)q(\boldsymbol{W}_2|\boldsymbol{U}_2)q(\boldsymbol{U}_1)q(\boldsymbol{U}_2)q(\boldsymbol{b})d\boldsymbol{U}_1 d\boldsymbol{U}_2,$$

where we define $q(\boldsymbol{W}_1)$ to be a Gaussian mixture distribution with two components, which is factorised over Q and K:

$$q(\boldsymbol{W}_1|\boldsymbol{U}_1) = \prod_{q=1}^{Q}\prod_{k=1}^{K} q(\boldsymbol{w}_{qk}|\boldsymbol{u}_{qk}),$$

$$q(\boldsymbol{w}_{qk}|\boldsymbol{u}_{qk}) = p_1 \mathcal{N}(\boldsymbol{u}_{qk}, \sigma^2) + (1 - p_1)\mathcal{N}(0, \sigma^2),$$

$$q(\boldsymbol{u}_{qk}) = \mathcal{N}(\boldsymbol{v}_{qk}, \sigma^2)$$

where $p_1 \in [0, 1]$, and $\sigma > 0$. Similarly, we can define a hierarchical variational distribution over $\boldsymbol{W}_2$

$$q(\boldsymbol{W}_2|\boldsymbol{U}_2) = \prod_{k=1}^{K}\prod_{d=1}^{D} q(\boldsymbol{w}_{kd}|\boldsymbol{u}_{kd}),$$

$$q(\boldsymbol{w}_{kd}|\boldsymbol{u}_{kd}) = p_2 \mathcal{N}(\boldsymbol{u}_{kd}, \sigma^2) + (1 - p_2)\mathcal{N}(0, \sigma^2),$$

$$q(\boldsymbol{u}_{kd}) = \mathcal{N}(\boldsymbol{v}_{kd}, \sigma^2)$$

For $\boldsymbol{b}$, we use a simple Gaussian distribution

$$q(\boldsymbol{b}) = \mathcal{N}(\boldsymbol{u}, \sigma^2 \boldsymbol{I}_K).$$

B.3 Evaluating the Log Evidence Lower Bound for Regression

Next we evaluate the log evidence lower bound for the task of regression. The log evidence lower bound is as below

$$\mathcal{L}_{\text{GP-VI}} \coloneqq \int q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \log p(\boldsymbol{Y}|\boldsymbol{X}, \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) - D_{\text{KL}}(q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b})\|p(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b})).$$

where the integration is with respect to $\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}$.

During regression, we can rewrite the integrand as a sum:

$$\log p(\boldsymbol{Y}|\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) = \sum_{d=1}^{D} \log \mathcal{N}(\boldsymbol{y}_d; \Phi\boldsymbol{w}_d, \tau^{-1}\boldsymbol{I}_N),$$

$$= -\frac{ND}{2}\log(2\pi) + \frac{ND}{2}\log(\tau) - \sum_{d=1}^{D} \frac{\tau}{2}\|\boldsymbol{y}_d - \Phi\boldsymbol{w}_d\|_2^2.$$

as the output dimensions of a multi-output Gaussian process are assumed to be independent. Denote $\widehat{\boldsymbol{Y}} = \Phi\boldsymbol{W}_2$. We can then sum over the rows instead of the columns of $\widehat{\boldsymbol{Y}}$ and write

$$\sum_{d=1}^{D} \frac{\tau}{2}\|\boldsymbol{y}_d - \widehat{\boldsymbol{y}}_d\|_2^2 = \sum_{n=1}^{N} \frac{\tau}{2}\|\boldsymbol{y}_n - \widehat{\boldsymbol{y}}_n\|_2^2.$$

Here we have $\widehat{\boldsymbol{y}}_n = \phi(\boldsymbol{x}, \boldsymbol{W}_1, \boldsymbol{b})\boldsymbol{W}_2 = \sqrt{\frac{1}{K}}\sigma(\boldsymbol{x}_n\boldsymbol{W}_1 + \boldsymbol{b})\boldsymbol{W}_2$, leading to

$$\log p(\boldsymbol{Y}|\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) = \sum_{n=1}^{N} \log \mathcal{N}(\boldsymbol{y}_n; \phi(\boldsymbol{x}_n, \boldsymbol{W}_1, \boldsymbol{b})\boldsymbol{W}_2, \tau^{-1}\boldsymbol{I}_D).$$

Therefore, we can update the log evidence lower bound as

$$\sum_{n=1}^{N} \int q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \log p(\boldsymbol{Y}|\boldsymbol{x}_n, \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) - D_{\text{KL}}(q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \| p(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b})).$$

We re-parametrise the integrands in the sum to not depend on $\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}$ directly, but instead on the standard normal distribution and the Bernoulli distribution. Let $q(\epsilon_1) = \mathcal{N}(0, \boldsymbol{I}_{Q \times K})$, $q(\mathbf{z}_{1,q,k}) = \text{Bernoulli}(p_1)$, $q(\epsilon_2) = \mathcal{N}(0, \boldsymbol{I}_{K \times D})$, $q(\mathbf{z}_{2,k,d}) = \text{Bernoulli}(p_2)$, $q(\epsilon) = \mathcal{N}(0, \boldsymbol{I}_K)$, $q(\epsilon_3) = \mathcal{N}(0, \boldsymbol{I}_{Q \times K})$, and $q(\epsilon_4) = \mathcal{N}(0, \boldsymbol{I}_{K \times D})$. Then, we can have

$$\boldsymbol{W}_1 = \boldsymbol{Z}_1 \odot (\boldsymbol{U}_1 + \sigma\epsilon_1) + (1 - \boldsymbol{Z}_1) \odot \sigma\epsilon_1,$$
$$\boldsymbol{W}_2 = \boldsymbol{Z}_2 \odot (\boldsymbol{U}_2 + \sigma\epsilon_2) + (1 - \boldsymbol{Z}_2) \odot \sigma\epsilon_2,$$
$$\boldsymbol{b} = \boldsymbol{u} + \sigma\epsilon, \ \boldsymbol{U}_1 = \sigma\epsilon_3, \ \boldsymbol{U}_2 = \sigma\epsilon_4$$

where $\odot$ means element-wise multiplication. Thus, we can update the above the sum over the integrals

$$\sum_{n=1}^{N} \int q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \log p(\boldsymbol{y}_d|\boldsymbol{x}_n, \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}),$$

$$= \sum_{n=1}^{N} \int q(\boldsymbol{Z}_1, \epsilon_1, \boldsymbol{Z}_2, \epsilon_2, \epsilon, \epsilon_3, \epsilon_4) \log p(\boldsymbol{y}_d|\boldsymbol{x}_n, \boldsymbol{W}_1(\boldsymbol{Z}_1, \epsilon_1, \epsilon_3), \boldsymbol{W}_2(\boldsymbol{Z}_2, \epsilon_2, \epsilon_4), \boldsymbol{b}(\epsilon)).$$

For the first term in $\mathcal{L}_{\text{GP-MC}}$, we can estimate the integrals using Monte Carlo integration with a distinct single sample to obtain

$$\mathcal{L}_{\text{GP-MC}} := \sum_{n=1}^{N} \int \log p(\boldsymbol{y}_d|\boldsymbol{x}_n, \widehat{\boldsymbol{W}}_1^n, \widehat{\boldsymbol{W}}_2^n, \widehat{\boldsymbol{b}}^n) - D_{\text{KL}}(q(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b}) \| p(\boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{b})).$$

Following Gal & Ghahramani (2016), by optimising the stochastic objective $\mathcal{L}_{\text{GP-MC}}$, we can converge to the same limit as $\mathcal{L}_{\text{GP-VI}}$, which justifies this stochastic approximation.

Moving to the second term in $\mathcal{L}_{\text{GP-MC}}$, we use w and u to denote certain component in the weights ($\boldsymbol{W}_1$) and variational parameters ($\boldsymbol{U}_1$), respectively. Then, we can have

$$-D_{\text{KL}}\left(q(\mathbf{w})\|p(\mathbf{w})\right) = -\int q(\mathbf{w}) \log \frac{q(\mathbf{w})}{p(\mathbf{w})} d\mathbf{w}$$

$$= \int \int q(\mathbf{w}, \mathbf{u}) d\boldsymbol{u} \log \frac{p(\mathbf{w})}{\int q(\mathbf{w}, \mathbf{u}) d\mathbf{u}} d\mathbf{w}$$

$$= \int q(\mathbf{u}) \{ \int q(\mathbf{w}|\mathbf{u}) \log \frac{p(\mathbf{w})}{\int q(\mathbf{w}, \mathbf{u}) d\mathbf{u}} d\mathbf{w} \} d\mathbf{u}$$

$$= \int q(\mathbf{u})[\int q(\mathbf{w}|\mathbf{u}) \log p(\mathbf{w}) d\mathbf{w}] d\mathbf{u} - \int q(\mathbf{u}) \{ \int q(\mathbf{w}|\mathbf{u}) \log[\int q(\mathbf{w}, \mathbf{u}) d\mathbf{u}] d\mathbf{w} \} d\mathbf{u}$$

$$= \int q(\mathbf{u})[\int q(\mathbf{w}|\mathbf{u}) \log p(\mathbf{w}) d\mathbf{w}] d\mathbf{u} - \int [\int q(\mathbf{w}, \mathbf{u}) d\mathbf{u}] \log[\int q(\mathbf{w}, \mathbf{u}) d\mathbf{u}] d\mathbf{w} \quad (12)$$

For the first term in Eq. (12), we can first follow the Proposition 1 in (Gal & Ghahramani, 2016) to approximate $\int q(\mathbf{w}|\mathbf{u}) \log p(\mathbf{w}) d\mathbf{w}$ as below:

$$\int q(\mathbf{w}|\mathbf{u}) \log p(\mathbf{w}) d\mathbf{w} \approx -\frac{1}{2}(p \cdot \mathbf{u}^2 + \sigma^2)$$

Then, we can approximate the first term in Eq. (12) as

$$\int q(\mathbf{u})[\int q(\mathbf{w}|\mathbf{u}) \log p(\mathbf{w}) d\mathbf{w}] d\mathbf{u} \approx \int q(\mathbf{u})[-\frac{1}{2}(p \cdot \mathbf{u}^2 + \sigma^2)] d\mathbf{u}$$

$$= -\frac{1}{2}\sigma^2 - \frac{p}{2} \int q(\mathbf{u})\mathbf{u}^2 d\mathbf{u} = -\frac{p+1}{2}\sigma^2 - \frac{p}{2}\mathbf{v}^2$$

For the second term in Eq. (12), we can estimate the integral $\int q(\mathrm{w}, \mathrm{u})d\mathrm{u}$ using Monte Carlo integration with a distinct single sample to obtain

$$\int [\int q(\mathrm{w}, \mathrm{u})d\mathrm{u}] \log[\int q(\mathrm{w}, \mathrm{u})d\mathrm{u}]d\mathrm{w} \approx \int q(\mathrm{w}|\widehat{\mathrm{u}}) \log[q(\mathrm{w}|\widehat{\mathrm{u}})]d\mathrm{w}$$

Then we can follow the Proposition 1 in (Gal & Ghahramani, 2016) to approximate it as

$$\int q(\mathrm{w}|\widehat{\mathrm{u}}) \log[q(\mathrm{w}|\widehat{\mathrm{u}})]d\mathrm{w} \approx \frac{1}{2}(\log \sigma^2 + 1 + 2\log \pi) + C$$

Therefore, we can get the approximation for Eq. (12) as Eq. (13):

$$-D_{\mathrm{KL}}\Big(q(\mathrm{w})\|p(\mathrm{w})\Big) = -\frac{p+1}{2}\sigma^2 - \frac{p}{2}\mathrm{v}^2 + \frac{1}{2}(\log \sigma^2 + K(1 + 2\log \pi)) + C \qquad (13)$$

Then, we can have the following equation based on Eq. (13):

$$D_{\mathrm{KL}}(q(\boldsymbol{W}_1)\|p(\boldsymbol{W}_1)) \approx \frac{QK(p+1)}{2}\sigma^2 - \frac{QK}{2}(\log(\sigma^2) + 1) + \frac{p_1}{2}\sum_{q=1}^{Q}\sum_{k=1}^{K}\mathrm{v}_{qk}^2 + C,$$

where C is a constant and $D_{\mathrm{KL}}(q(\boldsymbol{W}_2)\|p(\boldsymbol{W}_2))$ can be approximated in a similar way. For $D_{\mathrm{KL}}(q(\boldsymbol{b})\|p(\boldsymbol{b}))$, it can be written as

$$D_{\mathrm{KL}}(q(\boldsymbol{b})\|p(\boldsymbol{b})) = \frac{1}{2}(\boldsymbol{u}^\top \boldsymbol{u} + K(\sigma^2 - \log(\sigma^2) - 1)) + C.$$

B.4 LOG EVIDENCE LOWER BOUND OPTIMISATION FOR CIGL

Next we explain the relation between the above equations with equations for CigL. Ignoring the constant terms τ, σ we obtain the maximisation objective

$$\mathcal{L}_{\text{GP-MC}} \propto -\frac{\tau}{2}\sum_{n=1}^{N}||\boldsymbol{y}_n - \widehat{\boldsymbol{y}}_n||_2^2 - \frac{p_1}{2}||\boldsymbol{V}_1||_2^2 - \frac{p_2}{2}||\boldsymbol{V}_2||_2^2 - \frac{1}{2}||\boldsymbol{u}||_2^2. \qquad (14)$$

We will show the equivalence between the iterative update of $\boldsymbol{M}_1$, $\boldsymbol{Z}_1$ and $\boldsymbol{U}_1$ in CigL and the hierarchical variational inference for deep GP. The update for $\boldsymbol{M}_2$, $\boldsymbol{Z}_2$ and $\boldsymbol{U}_2$ will be similar. In the hierarchical variational distribution, the distribution of sparse weights $\boldsymbol{W}_1$ depends on three random variables $\boldsymbol{M}_1$, $\boldsymbol{Z}_1$, and $\boldsymbol{U}_1$. Given $\boldsymbol{Z}_1$ and $\boldsymbol{U}_1$, we can know the variational distribution for $\boldsymbol{M}_1$ as:

$$q(\boldsymbol{M}_1|\boldsymbol{U}_1) \propto \exp(\boldsymbol{M}_1 \odot |\boldsymbol{U}_1|) \qquad (15)$$

where $\boldsymbol{M}_1$ is under certain sparsity constraint. Thus, we can update $\boldsymbol{M}_1$ by choosing $\widehat{\boldsymbol{M}}_1$ that maximising Eq. (15), which is aligned with the $\boldsymbol{M}_1$ update procedure in CigL.

Given $\boldsymbol{M}_1$, we can use $\widehat{\boldsymbol{V}}_1$ to approximate $\widehat{\boldsymbol{U}}_1$. Then, we can let σ tend to zero (Gal & Ghahramani, 2016), and the random variable realisations $\widehat{\boldsymbol{W}}_1^n, \widehat{\boldsymbol{W}}_2^n, \widehat{\boldsymbol{b}}^n$ can be

$$\widehat{\boldsymbol{W}}_1^n \approx \widehat{\boldsymbol{Z}}_1 \odot \widehat{\boldsymbol{U}}_1, \quad \widehat{\boldsymbol{W}}_2^n \approx \widehat{\boldsymbol{Z}}_2 \odot \widehat{\boldsymbol{U}}_2, \quad \widehat{\boldsymbol{b}}^n \approx \widehat{\boldsymbol{u}}$$

Then, we can get

$$\widehat{\boldsymbol{y}}_n \approx \sqrt{\frac{1}{K}}\sigma(\boldsymbol{x}_n(\widehat{\boldsymbol{Z}}_1 \odot \widehat{\boldsymbol{U}}_1) + \widehat{\boldsymbol{u}})(\widehat{\boldsymbol{Z}}_2 \odot \widehat{\boldsymbol{U}}_2).$$

We scale the optimisation objective by a positive constant $\frac{1}{\tau N}$ and get the objective:

$$\mathcal{L}_{\text{GP-MC}} \propto -\frac{1}{2N}\sum_{n=1}^{N}||\boldsymbol{y}_n - \widehat{\boldsymbol{y}}_n||_2^2 - \frac{p_1}{2\tau N}||\boldsymbol{U}_1||_2^2 - \frac{p_2}{2\tau N}||\boldsymbol{U}_2||_2^2 - \frac{1}{2\tau N}||\boldsymbol{u}||_2^2.$$

So, we recover equation for CigL. With correct stochastic optimisation scheduling, both will converge to the same limit.

For prediction, we can collect samples of $\{\widehat{\boldsymbol{Z}}_1, \widehat{\boldsymbol{U}}_1\}$ during the optimization process, where we use $\widehat{\boldsymbol{V}}_1$ at different epochs to approximate $\widehat{\boldsymbol{U}}_1$. By using weight & mask averaging and letting σ tend to zero (Gal & Ghahramani, 2016), the random variable $\widehat{\boldsymbol{W}}_1, \widehat{\boldsymbol{W}}_2, \widehat{\boldsymbol{b}}$ can be approximated as

$$\widehat{\boldsymbol{W}}_1 \approx \frac{1}{S}\sum_{s=1}^{S}\widehat{\boldsymbol{Z}}_1^{(s)} \odot \widehat{\boldsymbol{U}}_1^{(s)}, \quad \widehat{\boldsymbol{W}}_2 \approx \frac{1}{S}\sum_{s=1}^{S}\widehat{\boldsymbol{Z}}_2^{(s)} \odot \widehat{\boldsymbol{U}}_2^{(s)}, \quad \widehat{\boldsymbol{b}} \approx \frac{1}{S}\sum_{s=1}^{S}\widehat{\boldsymbol{u}}^{(s)}.$$

C   Appendix: Additional Experimental Results

Empirically, we find that a stronger correlation between $\boldsymbol{Z}$ and $\boldsymbol{W}$ in sparse training. We use CigL to train sparse Wide-ResNet-22-2 on CIFAR-10 at multiple sparsities (0%, 50%, 80%, 90%). Then, we randomly draw five random masks $\boldsymbol{Z}_i, i \in 1, \cdots, 5$ from Bernoulli distribution. Using the final sparse weights $\boldsymbol{W}$, we obtain several new sparse models $\boldsymbol{Z}_i \odot \boldsymbol{W}, i \in 1, \cdots, 5$, and record their test accuracies. We compare the test accuracy of $\boldsymbol{W}$ with the average accuracy of $\boldsymbol{Z}_i \odot \boldsymbol{W}, i \in 1, \cdots, 5$ to see the correlation. The larger decrease in test accuracy after multiplying by $\boldsymbol{Z}_i$ implies a stronger correlation between $\boldsymbol{Z}$ and $\boldsymbol{W}$.

As shown in Figure 6 (a), both the accuracy of $\boldsymbol{W}$ (red curve) and the average accuracy of $\boldsymbol{Z}_i \odot \boldsymbol{W}, i \in 1, \cdots, 5$ (blue curve) are decrease with increasing sparsity, and we see a more pronounced decrease in the blue curve. Figure 6 (b) further shows the decrease in test accuracy at each sparsity. We observe that the decrease is very small in the dense or sparse model at low sparsity. However, when it shifts to high sparsity such as 90%, we observe a larger decrease, which indicates a stronger correlation between $\boldsymbol{Z}$ and $\boldsymbol{W}$ in sparse training.

(a) Test accuracy of $\boldsymbol{W}$ and $\boldsymbol{Z}_i \odot \boldsymbol{W}$ (b) Test accuracy decrease from $\boldsymbol{W}$ to $\boldsymbol{Z}_i \odot \boldsymbol{W}$

Figure 6: (a) Test accuracy of sparse model $\boldsymbol{W}$ and the newly produced sparse model $\boldsymbol{Z}_i \odot \boldsymbol{W}$. (b) decrease in test accuracy from sparse model $\boldsymbol{W}$ to newly produced sparse model $\boldsymbol{Z}_i \odot \boldsymbol{W}$. At low sparsity, the decrease of the dense or sparse models is small. At high sparsity, the decrease is larger.