CANIFE: CRAFTING CANARIES FOR EMPIRICAL PRIVACY MEASUREMENT IN FEDERATED LEARNING

ABSTRACT

Federated Learning (FL) is a setting for training machine learning models in distributed environments where the clients do not share their raw data but instead send model updates to a server. However, model updates can be subject to attacks and leak private information. Differential Privacy (DP) is a leading mitigation strategy which involves adding noise to clipped model updates, trading off performance for strong theoretical privacy guarantees. Previous work has shown that the threat model of DP is conservative and that the obtained guarantees may be vacuous or may not directly translate to information leakage in practice. In this paper, we aim to achieve a tighter measurement of the model exposure by considering a realistic threat model. We propose a novel method, CANIFE, that uses *canaries*—carefully crafted samples by a strong adversary to evaluate the empirical privacy of a training round. We apply this attack to vision models trained on CIFAR-10 and CelebA and to language models trained on Sent140 and Shakespeare. In particular, in realistic FL scenarios, we demonstrate that the empirical epsilon obtained with CANIFE is 2–7× lower than the theoretical bound.

1 INTRODUCTION

Federated Learning (FL) has recently become a popular paradigm for training machine learning models across a large number of clients, each holding local data samples (McMahan et al., 2017a). The primary driver of FL's adoption by the industry is its compatibility with the "privacy by design" principle, since the clients' raw data are not communicated to other parties during the training procedure (Kairouz et al., 2019; Huba et al., 2022; Xu et al., 2022). Instead, clients train the global model locally before sending back updates, which are aggregated by a central server. However, model updates, in their individual or aggregate form, leak information about the client local samples (Geiping et al., 2020; Gupta et al., 2022).

Differential Privacy (DP) (Dwork et al., 2006; Abadi et al., 2016) is a standard mitigation to such privacy leakage. Its adaptation to the FL setting, DP-FEDAVG (McMahan et al., 2017b), provides user-level guarantees by adding Gaussian noise to the aggregated clipped model updates received by the server. In practice, training with strong privacy guarantees comes at the expense of model utility (Bassily et al., 2014; Kairouz et al., 2019), notwithstanding efforts to close this gap, either with public pre-training and partial model updates (Xu et al., 2022), accountants with better compositionality properties (Mironov, 2017) or DP variants such as DP-FTRL (Kairouz et al., 2021).

Hence, it is common in practical deployments of DP-FL to train with a high privacy budget ε resulting in loose privacy guarantees (Ramaswamy et al., 2020). Such large privacy budgets often provide vacuous guarantees on the information leakage, for instance, against membership inference attacks (Mahloujifar et al., 2022). Encouragingly, recent work has shown that the information recovered in practice using state-of-the-art attacks is less than what theoretical bounds may allow (Nasr et al., 2021). This suggests that DP is conservative and that a tighter measurement of the model exposure may be achieved by considering more realistic threat models.

In this paper, we propose to complement DP-FL training with a novel attack method, CANaries In Federated Environments (CANIFE), to measure empirical privacy under a realistic threat model. We view privacy measurement as a membership inference game depicted in Figure 2, where a rogue client is allowed to craft a training sample, the *canary*, which will result in an outlier model update. The training round proceeds normally, after which the rogue client performs a statistical test to detect

Figure 1: Empirical privacy measurements over the course of FL training for popular LEAF benchmarks Sent140, CelebA and Shakespeare with $\varepsilon \in \{10, 30, 50\}$. We observe a notable gap between the theoretical ε obtained with DP-FEDAVG and the empirical $\hat{\varepsilon}$ obtained with CANIFE.

the canary in the global noisy model update provided to the server by any secure aggregation protocol. Finally, we translate the attack results into a per round measure of empirical privacy (Jagielski et al., 2020; Nasr et al., 2021) and propose a method using amplification by subsampling to compute the empirical privacy incurred during training as depicted in Figure 1 for standard FL benchmarks.

Critically, our privacy attack is designed to approximate the worst-case *data sample*, not the worst-case *update vector*. The rogue client seeks to undermine the privacy guarantee by manipulating its input, which is consistent with FL environments using secure sandboxing to protect the integrity of the training process (Frey, 2021). We additionally model the server as the honest party, not allowing it to poison the global model in order to reconstruct training samples, in contrast with a recent line of work (Fowl et al., 2021; Boenisch et al., 2021; Wen et al., 2022; Fowl et al., 2022).

In summary, our contributions are as follows:

- We propose CANIFE (Section 3), a novel and practical privacy attack on FL that injects crafted *canary* samples. It augments the standard DP-FL training with a tight measure of the model's privacy exposure given a realistic yet conservative threat model.

- CANIFE is compatible with natural language and image modalities, lightweight and requires little representative data and computation to be effective. As a sanity check, we demonstrate that CANIFE tightly matches DP guarantees in a toy setup (Section 4.1) before exploring how it behaves in the federated setting (Section 4.2).

- Our work highlights the gap between the practical privacy leakage and the DP guarantees in various scenarios. For instance, on the CelebA benchmark, we obtain an empirical measure $\hat{\varepsilon} \approx 7$ for a model trained with a theoretical privacy budget of $\varepsilon = 50$.

2 BACKGROUND

2.1 DIFFERENTIAL PRIVACY

Differential Privacy Dwork et al. (2006); Dwork & Roth (2014) defines a standard notion of privacy that guarantees the output of an algorithm does not depend significantly on a single sample or user.

Definition 1 (Differential Privacy). *A randomised algorithm $\mathcal{M} \colon \mathcal{D} \to \mathcal{R}$ satisfies (ε, δ)-differential privacy if for any two adjacent datasets $D, D' \in \mathcal{D}$ and any subset of outputs $S \subseteq \mathcal{R}$,*

$$\mathbb{P}(\mathcal{M}(D) \in S) \le e^{\varepsilon}\mathbb{P}(\mathcal{M}(D') \in S) + \delta.$$

The privacy parameter ε is called the *privacy budget* and it determines an upper bound on the information an adversary can obtain from the output of an (ε, δ)-DP algorithm. The parameter δ defines the probability of failing to guarantee the differential privacy bound for any two adjacent datasets. In this work, we are interested in *user-level* differential privacy which takes D and D' to be *adjacent* if D' can be formed by adding or removing all samples associated with a single user from D.

Standard DP results state that the privacy budget (ε, δ) accumulates (roughly) in proportion to the square root of the number of iterations. Advanced privacy accountants leverage the uncertainty due

to random sampling (Mironov, 2017; Wang et al., 2019b; Gopi et al., 2021). We use the Rényi Differential Privacy (RDP) accounting implemented in the Opacus library (Yousefpour et al., 2021).

2.2 PRIVATE FEDERATED LEARNING

A standard FL protocol, such as FEDAVG (McMahan et al., 2017a) computes a weighted average of the model updates from clients before performing a gradient descent step on the global model. Other variants exist to deal with common optimization problems in the federated setting such as convergence speed (Wang et al., 2019a), heterogeneity (Karimireddy et al., 2020a;b), reducing communication bandwidth (Alistarh et al., 2017) and adding momentum (Reddi et al., 2020). In this work, we focus on DP-FEDSGD, a private extension of FEDAVG (McMahan et al., 2017b). At each round, the selected clients compute their clipped model update u_i and transmit it to the server, which aggregates the model updates and adds Gaussian noise. If we omit the scalar weighting terms for clarity, the aggregated noisy model update becomes

$$\tilde{u} = \sum_i u_i + \mathcal{N}(0, \sigma^2 I_d).$$

In practice, federated algorithms rely on Secure Aggregation (SegAgg) protocols to aggregate each client update without revealing any individual u_i to the server or to other participants (Bonawitz et al., 2017; Bell et al., 2020). In a TEE-based SecAgg (Huba et al., 2022), a trusted execution environment (TEE) aggregates the individual model updates and calibrated DP noise before handing over the noisy model update $\tilde{u}$ to the server. These specific models are orthogonal to our work and we assume from now on that the server and clients participate in a TEE-based SecAgg protocol. We discuss our threat model with regards to our attack in Section 3.1.

2.3 ATTACKS & EMPIRICAL PRIVACY

Centralized and FL Attacks. There is a vast body of literature on attacking models trained in the centralised setting. For example, membership inference attacks (MIA) attempt to distinguish whether a sample was present in the training set given only the trained model (Shokri et al., 2017; Sablayrolles et al., 2019). Others attacks consider the more difficult problem of reconstructing entire training samples from a trained model, often using (batch) gradient information (Yin et al., 2021; Jeon et al., 2021; Balle et al., 2022). Since model updates u_i are essentially just aggregated gradients, it is natural that FL updates may leak private information as well. Nasr et al. (2019) show that it is possible to perform both passive and active membership-inference attacks in the federated setting. Other works such as that of Fowl et al. (2021) and Wen et al. (2022) have designed attacks on model updates which allow for the reconstruction of training samples used in federated training. However, they assume that the server can poison the global model, whereas we assume an honest server.

Canaries. The notion of canary samples usually refers to natural data samples used to measure memorization in large language models (Carlini et al., 2019; 2021; Thakkar et al., 2020; Shi et al., 2022). For instance, Parikh et al. (2022) propose to reconstruct canaries inserted in training data and Stock et al. (2022) insert canaries to track and quantify the information leakage when training a causal language model. In all prior work, the canary is either a sample from the training set or a handcrafted instance such as "My SSN is 123-45-6789". In contrast, CANIFE provides an explicit method for crafting canary samples that are as adversarial as possible within the given threat model (see Appendix E for canary samples) to obtain tight measurement of the model's exposure. Moreover, the proposed method applies to any training modality allowing to backpropagate in the sample space (in particular, pixels for images and tokens for natural language).

Empirical Privacy. The proposed approach departs from existing attacks in the FL setup. For instance, Jayaraman & Evans (2019) and Jagielski et al. (2020) have derived empirical measures of privacy through attacks and often shown gaps between the empirically measured and theoretical privacy. More recently, Nasr et al. (2021) study a range of membership-inference attacks on varying adversary's powers. We argue that the threat model of many of these attacks is often too permissive relative to what a realistic adversary can achieve in the federated setting. For example, those in Nasr et al. (2021) assume knowledge of the other samples in the dataset.

Figure 2: Illustration of the proposed CANIFE method for one training round. The adversary is a rogue client that crafts a training sample resulting in an extremely out-of-distribution model update u_c and performs a membership inference attack on the (public) aggregated noisy model update $\tilde{u}$ provided to the server by SecAgg. Attack results are converted to empirical privacy guarantees $\hat{\varepsilon}$ for this round. We then compound these guarantees over the course over the training as in Section 3.4.

3 METHODOLOGY

We would like to design a canary sample z to measure the empirical privacy of a given FL training round under a realistic threat model defined in Section 3.1. We view this problem as a membership inference game where a rogue client crafts a canary z specific to the global model at round r (Section 3.3) and uses this canary to produce an extremely out-of-distribution model update. After this, the server proceeds as usual, aggregating model updates via any secure aggregation primitive and adding noise. At the end of the round, the adversary attempts to detect the presence of the canary in the aggregated noisy model update $\tilde{u}$ (Section 3.2) and computes a per-round empirical privacy measure. These per-round empirical privacy guarantees are compounded over the whole course of the training to give a final global empirical privacy guarantee as explained in Section 3.4.

3.1 THREAT MODEL

We assume an *honest-but-curious* threat model where the clients and the server do not deviate from the training protocol (Bonawitz et al., 2017; Kairouz et al., 2019; Huba et al., 2022). In particular, the clients cannot directly manipulate gradients nor the final model updates from the local training and the server cannot modify the model maliciously to eavesdrop on the clients.

To craft the canary for a given training round, we assume that the adversary — a rogue client — has access to (1) the current server-side public model and to (2) emulated *mock clients*. Mock clients are crafted using a public set of samples called the *design pool* along with assumptions about the true data distribution of the clients. We show in Section 4 that the adversary is able to design a strong and robust canary sample with a small amount of public data under mild assumptions about the true data distribution. We also demonstrate that the computational resources required to design the canary are small, which means that even adversaries under resource constraints are able to launch such attacks.

We argue such a threat model is realistic and discuss practical limitations that influence the adversary's success in Section 3.4: our goal is to design an attack that is as adversarial as possible (in order to derive a worst-case measure of empirical privacy) under a set of reasonable assumptions.

3.2 CANARY DETECTION

The adversary's objective is to craft a canary z such that the resulting model update is extremely out-of-distribution. More precisely, we require that the canary gradient $\nabla_\theta \ell(z)$ is orthogonal to all individual clipped model updates u_i in the current round: $\langle u_i, \nabla_\theta \ell(z) \rangle = 0$. We demonstrate that this allows the adversary to detect the presence of the canary by separating two Gaussian distributions.

The server trains a model parameterized by $\theta \in \mathbb{R}^d$ with a certain level of DP noise σ across a population of clients each holding a local dataset D_i. Since the rogue client holds a dataset that

only contains the canary $D_c = \{z\}$, its clipped model update will be proportional[1] to the canary gradient: $u_c \propto \nabla_\theta \ell(z)$. Recall that the aggregated private model update $\tilde{u}$ is formed by the noisy sum of individual clipped model updates: $\tilde{u} = \sum_i u_i + \mathcal{N}(0, \sigma^2 I_d)$. Then, as a counter-factual, if the rogue client does not participate in the training round:

$$\langle \tilde{u}, u_c \rangle \propto \sum_i \underbrace{\langle u_i, \nabla_\theta \ell(z) \rangle}_{=0 \text{ by design}} + \langle \mathcal{N}(0, \sigma^2 I_d), \nabla_\theta \ell(z) \rangle = \mathcal{N}(0, \sigma^2).$$

Hence, $\langle \tilde{u}, u_c \rangle$ is drawn from a one-dimensional zero-mean Gaussian with variance σ_c^2, where σ_c accounts for the proportionality factor. Similarly, if the rogue client participates in the training round, $\langle \tilde{u}, u_c \rangle$ is drawn from a one-dimensional Gaussian with variance σ_c^2 centered at $\|u_c\|^2$. Thus, the membership inference game is reduced to separating two Gaussians distributions centered respectively at 0 and 1. Note that the result is unchanged up to a fixed scaling factor if the client updates u_i are weighted by their local dataset size as in (McMahan et al., 2017b). The testing approach is described in full in Algorithm 1 and involves computing the attack score $s_r := \langle \tilde{u}, u_c \rangle$. We derive a connection with the likelihood ratio test in Appendix A.

3.3 CANARY DESIGN

At given round r, the rogue client is given the current server-side model parameterized by θ. Given a set of heldout clipped model updates $\{u_i\}$, it crafts the canary by minimizing:

$$\mathcal{L}(z) = \sum_i \langle u_i, \nabla_\theta \ell(z) \rangle^2 + \max(C - \|\nabla_\theta \ell(z)\|, 0)^2. \tag{1}$$

Recall that $\nabla_\theta \ell(z)$ denotes the gradient of the network's parameters with respect to its training loss ℓ when forwarding the canary z through the network. The first loss term is designed so that the canary gradient $\nabla_\theta \ell(z)$ is orthogonal to the set of heldout model updates while the second term enforces that the canary has sufficiently high norm to prevent optimization collapse. It is natural to choose the constant in the second term to be the clipping constant C as it is the maximum norm the canary update can achieve. In Appendix D, we provide experiments that show that choosing the gradient norm constant too large has a detrimental effect on optimization.

Using an automatic differentiation framework such as PyTorch (Paszke et al., 2019), we compute $\nabla_z \mathcal{L}(z)$ and perform stochastic gradient descent directly in the sample space as described in Algorithm 1. (Recall that the model parameters θ are fixed during the optimization procedure.) Computing $\nabla_z \mathcal{L}(z)$ is straightforward for continuous data, such as images, as we can simply back-propagate in the pixel space. For language models, the problem is more complex as the input is a sequence of discrete tokens. Hence, we leverage the work of Guo et al. (2021), who derive a method for designing adversarial language examples by utilising the Gumbel-Softmax distribution (Jang et al., 2016). This allows them to use gradient-based methods by optimising a probability distribution over each token in a sequence.

We investigate various methods to initialize the canary, including starting from a random training sample or random pixels or tokens. Depending on the task at hand, we might need to fix a target for the canary. For instance, for image classification, we need to assign the canary to a class in order to be able to compute $\nabla_\theta \ell(z)$. We investigate various canary initialization and target choice strategies experimentally in Section 4. We also investigate other optimization considerations for designing the canary such as slightly modifying the loss in Appendix D.

Adversarial Examples. We can view the canary z as "adversarial" in the sense that it should be extremely out-of-distribution to get a worst-case measure of privacy. This is different from the unrelated notion of *adversarial examples* which typically constrain the changes of a sample to be imperceptible to humans (Biggio et al., 2013). In our setup, we do not impose this constraint as we wish to encompass the realistic worst-case of an extreme out-of-distribution sample.

3.4 MEASURING EMPIRICAL PRIVACY

The CANIFE attack is carried out over a certain number (n) of fake rounds where the server does not update its global model but where the pool of selected (regular) clients differs every time. Hence,

---

[1]We assume that the client's local optimizer is SGD with no momentum (McMahan et al., 2017b).

Algorithm 1 CANIFE attack by a rogue client

Input: Design pool D_{pool}, Design iterations T, Canary learning rate β, Global model θ
 1: Form mock clients from the design pool D_{pool}
 2: For each mock client i, compute the clipped model update u_i
 3: Initialise the canary z_0 ▷ See Section 3.3
 4: **for** $t = 1, \dots, T$ **do**
 5:     $\mathcal{L}(z_t) \leftarrow \sum_i \langle u_i, C \cdot \nabla_\theta \ell(z_t) \rangle^2 + \max(C - ||\nabla_\theta \ell(z_t)||, 0)^2$ ▷ Canary optimization loss
 6:     Compute $\nabla_{z_t} \mathcal{L}(z_t)$ ▷ Gradient of the canary loss w.r.t z_t
 7:     $z_{t+1} \leftarrow z_t - \beta \cdot \nabla_{z_t} \mathcal{L}(z_t)$ ▷ For NLP, see Section 3.3
 8: **end for**
 9: Compute u_c ▷ Model update with $D_c = \{(z_T, y_c)\}$
10: **return** $s_r \leftarrow \langle \tilde{u}, u_c \rangle$ ▷ $\tilde{u}$ is deemed public after the round has finished

---

CANIFE has no influence on the model's final accuracy. The adversary crafts a single canary and inserts it into every fake round with probability $1/2$. Once the n attack scores are computed, the adversary deduces the performance of the attack at a calibrated threshold γ. Building on previous work (Jagielski et al., 2020; Nasr et al., 2021), we compute the empirical privacy guarantee $\hat{\varepsilon}$ based on the False Positive Rate (FPR) and False Negative Rate (FNR) of the attack at the threshold γ as

$$\hat{\varepsilon} = \max \left(\log \frac{1 - \delta - \text{FPR}}{\text{FNR}}, \log \frac{1 - \delta - \text{FNR}}{\text{FPR}} \right).$$

We also deduce confidence intervals for $\hat{\varepsilon}$. Our measure differs from that of (Nasr et al., 2021) as our attack measures privacy at a single round of training. Thus, $\hat{\varepsilon}$ is a *per-round* privacy measure which we denote as $\hat{\varepsilon}_r$ and we can compare this to a per-round theoretical ε_r. In order to deduce a global empirical epsilon $\hat{\varepsilon}$ we convert the per-round $\hat{\varepsilon}_r$ into a noise estimate $\hat{\sigma}_r$ under amplification by subsampling. We then compose for s steps with an RDP accountant, until we perform the next attack and update our $\hat{\sigma}_r$, as detailed in Appendix C.

Relationship to DP. Our threat model and canary design procedure have been chosen to ensure that the adversary is as strong as possible but still constrained by realistic assumptions. At least three factors of the design process restrict the adversary in practice:

1. The adversary only has partial knowledge of the model updates in the form of an aggregated noisy sum $\tilde{u}$. Furthermore, when designing a canary, the adversary uses a design pool to mock clients. In our design, we have been conservative by assuming the adversary has access to heldout data that matches the federated distribution.

2. The optimization process induces two possible sources of error: the convergence itself and the generalization ability of the canaries to unseen model updates.

3. We calculate the maximum accuracy that can be derived from the attack. This is conservative, as in practice an adversary would not be able to perform n fake rounds with the same canary and would have to calibrate an accuracy threshold on a public heldout dataset.

If these practical constraints were not imposed on an adversary, then the privacy measure we derive from our attack would essentially be tight with the DP upper bound. For example, if we could always design a perfect canary z that has gradient orthogonal to all possible model updates u_i then the DP noise σ completely determines whether we can distinguish if z is present in $\tilde{u}$ or not. However, in practice, the assumptions listed above make the attack more difficult as we will see in Section 4.1.

4 EXPERIMENTS

In this section, we begin by highlighting the power of our attack on the simplest federated setting where participants only have a single sample (Section 4.1). We then show how our attack allows us to monitor privacy empirically over a federated training run (Section 4.2) before concluding with an ablation study that shows our canary is robust to various design choices (Section 4.3).

(a) $\sigma = 0$ (b) $\sigma = 0.423$ (c)

Figure 3: Experiments on CIFAR-10 on a toy setup where each client holds a single data sample. (a) Attack histograms without DP noise, showing that our attack completely succeeds. (b) Attack histograms with DP noise: as the DP noise σ increases, it becomes harder to separate both histograms. (c) Varying the design pool size and the number of participating clients. The y-axis shows the mean standard deviation of the histograms formed from the attack.

Setup. We evaluate our attack on both image and language models. We utilise LEAF (Caldas et al., 2018) which provides benchmark federated datasets for simulating clients with non-IID data and a varying number of local samples. We study image classification on CIFAR10 (IID) (Krizhevsky et al., 2009) and CelebA (non-IID) (Liu et al., 2015). We train a simple Convolutional Neural Network (CNN) and a ResNet18 model. For our language tasks, we train an LSTM model on non-IID splits of Sent140 (Go et al., 2009) and Shakespeare (McMahan et al., 2017a). For more information on datasets, model architectures and training hyperparameters, see Appendix B. We train, design, and evaluate our attacks using the FLSim framework [2] with the Opacus library for privacy accounting (Yousefpour et al., 2021). All experiments were run on a single A100 40GB GPU with model training taking at most a few hours. We discuss CPU benchmarks for the canary design in Section 4.3. For canary design, we use the Adam optimizer (Kingma & Ba, 2014) with a learning rate of $\beta = 1$ and fix $C = 1$. We form the CANIFE design pool from the LEAF test split, resulting in canaries designed on non-IID data which approximates data held by training clients.

4.1 EXAMPLE ATTACK: CIFAR10

We first investigate the attack in the simplest federated setting where each client holds a single sample. It follows that the clipped model update u_i is simply a scaled gradient of the client's single data sample. This setting corresponds to the central setting where the number of clients participating per round is equivalent to a (central) batch size. In Figure 3, we train a ResNet18 model on CIFAR10 to 60% test accuracy and perform our CANIFE attack. We design a canary on the checkpointed model, having the server perform 100 mock rounds where the model is frozen, with half the rounds having the canary client inserted and half without. We compute attack scores from these 100 trials and repeat this process 5 times, designing a new canary each time and averaging the attack results.

In Figure 3a, we present one histogram of the attack scores on a model that has 64 clients participating per round with no DP ($\varepsilon = \infty$). We use a design pool of $m = 512$ to design the canary. We observe that our attack is quite tight in this non-private setting. Since $\sigma = 0$, we hope that if the canary was designed well, the standard deviation of the histograms would also be close to 0. It turns out that the average standard deviation of the histograms is 0.006. Recall in Section 3.4, we discussed there is inherent error from both the optimization procedure and the fact the server designs the canary on heldout data but in this case the error is small. In Figure 3b, we display another example attack, this time for a model trained under privacy with a final $\varepsilon = 25$ corresponding to $\sigma = 0.423$ with 64 clients per round. We observe the attack is still fairly tight as the standard deviation of the histograms (average 0.478) is close to that of the privacy noise σ.

We conclude by exploring how both the design pool size and the number of clients affects the standard deviation of the histograms (Figure 3c). We vary both the number of clients and the design pool size. We train a model without privacy for each combination of parameters until it reaches 60%

---

[2]https://github.com/facebookresearch/FLSim

(a) Sent140 (2-layer LSTM) (b) CelebA (ResNet18) (c) CANIFE empirical epsilon $\hat{\varepsilon}$

Figure 4: (a) and (b) Monitoring per-round empirical privacy on LEAF benchmarks. Models are trained to $\varepsilon = 50$ with 100 clients per round. CIs for $\hat{\varepsilon}_r$ are compared with the theoretical per-round epsilon ε_r, rounds with an upper CI of ∞ do not have CIs displayed. (c) CANIFE empirical privacy incurred during the whole training, averaged over 5 independent runs (see Figure 1 for details).

train accuracy and then attack the model, plotting the average standard deviation of the histograms. We conclude with two observations. First, the attack is much tighter when there is a smaller number of clients participating per round. Second, the size of the design pool has a diminishing effect on reducing the standard deviation. We further explore these in Section 4.3.

4.2 Monitoring Empirical Privacy

One main goal of our attack is to provide a lightweight method for monitoring empirical privacy during federated training. We explore this in Figure 4, training ResNet18 on CelebA and a 2-layer LSTM model on Sent140 and Shakespeare. We train to a final $\varepsilon = 50$ and achieve 63.9% test accuracy on Sent140, 89.9% on CelebA and 44.8% on Shakespeare. We carry out the CANIFE attack at a regular interval, freezing the model, designing a single canary, and performing 100 attack trials with the designed canary before continuing training. This generates 100 scores which are used to compute an empirical per-round privacy measure $\hat{\varepsilon}_r$ as outlined in Section 3.4. See Appendix C.2 for further details. The canary sample z is initialised randomly and we explore how this affects optimization in Section 4.3. We note in practice that participants (and the server) would not want to waste rounds with a frozen model. CANIFE can alternatively collect attack scores over rounds where the model is unfrozen or have the server design multiple canaries in a round to generate scores.

We monitor the optimization of the canary loss by computing the *canary health* which measures the percentage improvement of the final canary loss compared to the initial loss. A perfect health of 1 means the canary achieved minimal design loss. As an example, for Sent140, we find that the average canary health across 5 separate training runs is 0.970 ± 0.098. Excluding the first 1000 rounds from each run, the average canary health becomes 0.990 ± 0.01. Thus, after two model epochs, optimization stabilises and the initial canary loss is reduced by 99%.

In Figure 4a, we display per-round privacy estimates $\hat{\varepsilon}_r$ and their 95% confidence intervals (CIs) for Sent140 trained with $\varepsilon = 50$ and compare to the (constant) theoretical per-round privacy ε_r. We observe $\hat{\varepsilon}_r$ is initially small and grows to an almost constant level within a single epoch and stays there during training. We note a significant ($\approx 7\times$) gap between the theoretical per-round epsilon ε_r and the one measured by our attack. We obtain similar results for CelebA (ResNet18) in Figure 4b and Shakespeare in Appendix C.3. We compound these per-round estimates $\hat{\varepsilon}_r$ to provide a cumulative overall measure of the model's privacy $\hat{\varepsilon}$ and display this in Figure 1 for models trained with $\varepsilon \in \{10, 30, 50\}$. We again note a significant gap between the final theoretical privacy and the measure derived under CANIFE. The final empirical privacy $\hat{\varepsilon}$ averaged over 5 separate training runs is shown in Figure 4c. We observe that CANIFE estimates are stable across runs with a relatively small standard deviation (SD), for example, on CelebA the SD is at most 0.4.

4.3 Ablation Study

There are various design decisions that affect the quality of the crafted canary and the overall power of the attack. In Figure 5, we study some of these settings and how they affect CANIFE. We present

(a) Canary Initialisation   (b) Design Iterations: Varying T (c) Model test vs attack accuracy

Figure 5: Ablations studies for CANIFE **without addition of DP noise**. (a) Canary initialization when varying the design pool size (CelebA, 4-layer CNN). (b) Number of design iterations required to produce robust and well-designed canaries (CelebA, 4-layer CNN). (c) Attack accuracy generally increases as model test accuracy increases (Sent140, 2-layer LSTM).

results on CelebA trained with a simple CNN model and Sent140, both with $\sigma = 0$. In Appendix D, we present further ablations.

Canary Initialisation.   In Figure 5a, we explore how initialising the canary affects the optimization. We consider two initialisation strategies: initialising the canary randomly or initialising the canary as a sample from the design pool (which is then excluded from the design). We observe no significant difference on the average standard deviation of the attack histograms.

Design Pool Size.   In Figure 5a, we vary the design pool size. We observe there is no significant effect on the average standard deviation of the attack histograms. This confirms what we observed in Figure 3c: the design pool size has diminishing impact on reducing the standard deviation.

Design Iterations.   In Figure 5b, we explore how the number of design iterations impacts the quality of the canary measured through the calibrated attack accuracy. We observe that just $t = 1000$ iterations are needed to obtain 95% accuracy and that with $t = 3000$ the attack improves to almost 100% accuracy, staying close to constant as t increases further. We additionally benchmarked the average CPU time on an M1 MacBook Air (2020) for a single design iteration. For Sent140, it takes an average of 0.06 seconds per iteration and 0.23 seconds for CelebA (ResNet18). For $t = 2500$, the design procedure took on average 165 and 591 seconds respectively. Hence, the canary design process takes at most 10 minutes on a CPU and only a few minutes with a GPU. Thus our attack is lightweight, requiring only a few thousand design iterations to achieve near-optimal canaries.

Model Accuracy.   We conclude by noting that the accuracy of the model and that of our attack are often highly correlated. In Figure 5c, we plot both the model test accuracy and the calibrated attack accuracy across five Sent140 runs trained without DP. We observe that early on in training, when the model accuracy is low, then the attack accuracy is similarly low. Once the model converges to a sufficiently high test accuracy the attack accuracy is close to 100%. To provide a fair comparison in experiments that require a comparison across different models (such as Figure 3c) we checkpoint them to a fixed test accuracy to avoid this confounding effect.

5   CONCLUSION

Motivated by the fact that DP is conservative, we consider a more realistic threat model to extract private information about client data when training a model with FL. We introduce CANIFE, a novel method to measure empirical privacy where a rogue client crafts a canary sample that results in an outlier model update. We argue that the difficulty of tracing this malicious model update in the aggregated noisy model update provides a tighter measurement of the model's privacy exposure. We hope this work can benefit practical deployments of DP-FL pipelines such as DP-FedAvg (McMahan et al., 2017b) or DP-FTRL (Kairouz et al., 2021) by complementing the theoretical bound with an arguably more realistic measure of the privacy leakage.

REFERENCES

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pp. 308–318, 2016.

Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. QSGD: Communication-efficient SGD via gradient quantization and encoding. *Advances in neural information processing systems*, 30, 2017.

Borja Balle, Giovanni Cherubin, and Jamie Hayes. Reconstructing training data with informed adversaries. *arXiv preprint arXiv:2201.04845*, 2022.

Raef Bassily, Adam Smith, and Abhradeep Thakurta. Differentially private empirical risk minimization: Efficient algorithms and tight error bounds, 2014.

James Henry Bell, Kallista A Bonawitz, Adrià Gascón, Tancrède Lepoint, and Mariana Raykova. Secure single-server aggregation with (poly) logarithmic overhead. In *Proceedings of the 2020 ACM SIGSAC Conference on Computer and Communications Security*, pp. 1253–1269, 2020.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*, pp. 387–402. Springer, 2013.

Franziska Boenisch, Adam Dziedzic, Roei Schuster, Ali Shahin Shamsabadi, Ilia Shumailov, and Nicolas Papernot. When the curious abandon honesty: Federated learning is not private. *arXiv preprint arXiv:2112.02918*, 2021.

Keith Bonawitz, Vladimir Ivanov, Ben Kreuter, Antonio Marcedone, H Brendan McMahan, Sarvar Patel, Daniel Ramage, Aaron Segal, and Karn Seth. Practical secure aggregation for privacy-preserving machine learning. In *proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, pp. 1175–1191, 2017.

Sebastian Caldas, Sai Meher Karthik Duddu, Peter Wu, Tian Li, Jakub Konečný, H Brendan McMahan, Virginia Smith, and Ameet Talwalkar. LEAF: A benchmark for federated settings. *arXiv preprint arXiv:1812.01097*, 2018.

Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. The secret sharer: Evaluating and testing unintended memorization in neural networks. In *28th USENIX Security Symposium (USENIX Security 19)*, pp. 267–284, 2019.

Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pp. 2633–2650, 2021.

Cynthia Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Foundations and Trends in Theoretical Computer Science*, 2014.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pp. 265–284. Springer, 2006.

Liam Fowl, Jonas Geiping, Wojtek Czaja, Micah Goldblum, and Tom Goldstein. Robbing the fed: Directly obtaining private data in federated learning with modified models. *arXiv preprint arXiv:2110.13057*, 2021.

Liam Fowl, Jonas Geiping, Steven Reich, Yuxin Wen, Wojtek Czaja, Micah Goldblum, and Tom Goldstein. Decepticons: Corrupted transformers breach privacy in federated learning for language models. *arXiv preprint arXiv:2201.12675*, 2022.

Suzanne Frey. Introducing Android's private compute services. 2021. URL https://security.googleblog.com/2021/09/.

Jonas Geiping, Hartmut Bauermeister, Hannah Dröge, and Michael Moeller. Inverting gradients—how easy is it to break privacy in federated learning? *Advances in Neural Information Processing Systems*, 33:16937–16947, 2020.

Alec Go, Richa Bhayani, and Lei Huang. Twitter sentiment classification using distant supervision. *CS224N project report, Stanford*, 1(12):2009, 2009.

Sivakanth Gopi, Yin Tat Lee, and Lukas Wutschitz. Numerical composition of differential privacy. *Advances in Neural Information Processing Systems*, 34:11631–11642, 2021.

Chuan Guo, Alexandre Sablayrolles, Hervé Jégou, and Douwe Kiela. Gradient-based adversarial attacks against text transformers. *arXiv preprint arXiv:2104.13733*, 2021.

Samyak Gupta, Yangsibo Huang, Zexuan Zhong, Tianyu Gao, Kai Li, and Danqi Chen. Recovering private text in federated learning of language models, 2022.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dzmitry Huba, John Nguyen, Kshitiz Malik, Ruiyu Zhu, Mike Rabbat, Ashkan Yousefpour, Carole-Jean Wu, Hongyuan Zhan, Pavel Ustinov, Harish Srinivas, et al. Papaya: Practical, private, and scalable federated learning. *Proceedings of Machine Learning and Systems*, 4:814–832, 2022.

Matthew Jagielski, Jonathan Ullman, and Alina Oprea. Auditing differentially private machine learning: How private is private SGD? *Advances in Neural Information Processing Systems*, 33: 22205–22216, 2020.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with Gumbel-Softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Bargav Jayaraman and David Evans. Evaluating differentially private machine learning in practice. In *28th USENIX Security Symposium (USENIX Security 19)*, pp. 1895–1912, 2019.

Jinwoo Jeon, Kangwook Lee, Sewoong Oh, Jungseul Ok, et al. Gradient inversion with generative image prior. *Advances in Neural Information Processing Systems*, 34:29898–29908, 2021.

Peter Kairouz, H. Brendan McMahan, Brendan Avent, Aurélien Bellet, Mehdi Bennis, Arjun Nitin Bhagoji, Kallista Bonawitz, Zachary Charles, Graham Cormode, Rachel Cummings, Rafael G. L. D'Oliveira, Hubert Eichner, Salim El Rouayheb, David Evans, Josh Gardner, Zachary Garrett, Adrià Gascón, Badih Ghazi, Phillip B. Gibbons, Marco Gruteser, Zaid Harchaoui, Chaoyang He, Lie He, Zhouyuan Huo, Ben Hutchinson, Justin Hsu, Martin Jaggi, Tara Javidi, Gauri Joshi, Mikhail Khodak, Jakub Konečný, Aleksandra Korolova, Farinaz Koushanfar, Sanmi Koyejo, Tancrède Lepoint, Yang Liu, Prateek Mittal, Mehryar Mohri, Richard Nock, Ayfer Özgür, Rasmus Pagh, Mariana Raykova, Hang Qi, Daniel Ramage, Ramesh Raskar, Dawn Song, Weikang Song, Sebastian U. Stich, Ziteng Sun, Ananda Theertha Suresh, Florian Tramèr, Praneeth Vepakomma, Jianyu Wang, Li Xiong, Zheng Xu, Qiang Yang, Felix X. Yu, Han Yu, and Sen Zhao. Advances and open problems in federated learning, 2019.

Peter Kairouz, Brendan McMahan, Shuang Song, Om Thakkar, Abhradeep Thakurta, and Zheng Xu. Practical and private (deep) learning without sampling or shuffling. In *International Conference on Machine Learning*, pp. 5213–5225. PMLR, 2021.

Sai Praneeth Karimireddy, Martin Jaggi, Satyen Kale, Mehryar Mohri, Sashank J Reddi, Sebastian U Stich, and Ananda Theertha Suresh. Mime: Mimicking centralized stochastic algorithms in federated learning. *arXiv preprint arXiv:2008.03606*, 2020a.

Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank Reddi, Sebastian Stich, and Ananda Theertha Suresh. Scaffold: Stochastic controlled averaging for federated learning. In *International Conference on Machine Learning*, pp. 5132–5143. PMLR, 2020b.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Saeed Mahloujifar, Alexandre Sablayrolles, Graham Cormode, and Somesh Jha. Optimal membership inference bounds for adaptive composition of sampled gaussian mechanisms, 2022.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017a.

H Brendan McMahan, Daniel Ramage, Kunal Talwar, and Li Zhang. Learning differentially private recurrent language models. *arXiv preprint arXiv:1710.06963*, 2017b.

Ilya Mironov. Rényi differential privacy. In *2017 IEEE 30th computer security foundations symposium (CSF)*, pp. 263–275. IEEE, 2017.

Milad Nasr, Reza Shokri, and Amir Houmansadr. Comprehensive privacy analysis of deep learning: Passive and active white-box inference attacks against centralized and federated learning. In *2019 IEEE symposium on security and privacy (SP)*, pp. 739–753. IEEE, 2019.

Milad Nasr, Shuang Songi, Abhradeep Thakurta, Nicolas Papemoti, and Nicholas Carlin. Adversary instantiation: Lower bounds for differentially private machine learning. In *2021 IEEE Symposium on Security and Privacy (SP)*, pp. 866–882. IEEE, 2021.

Rahil Parikh, Christophe Dupuy, and Rahul Gupta. Canary extraction in natural language understanding models. *arXiv preprint arXiv:2203.13920*, 2022.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*. 2019.

Swaroop Ramaswamy, Om Thakkar, Rajiv Mathews, Galen Andrew, H Brendan McMahan, and Françoise Beaufays. Training production language models without memorizing user data. *arXiv preprint arXiv:2009.10031*, 2020.

Sashank Reddi, Zachary Charles, Manzil Zaheer, Zachary Garrett, Keith Rush, Jakub Konečnỳ, Sanjiv Kumar, and H Brendan McMahan. Adaptive federated optimization. *arXiv preprint arXiv:2003.00295*, 2020.

Alexandre Sablayrolles, Matthijs Douze, Cordelia Schmid, Yann Ollivier, and Hervé Jégou. White-box vs black-box: Bayes optimal strategies for membership inference. In *International Conference on Machine Learning*, pp. 5558–5567. PMLR, 2019.

Weiyan Shi, Si Chen, Chiyuan Zhang, Ruoxi Jia, and Zhou Yu. Just fine-tune twice: Selective differential privacy for large language models. *arXiv preprint arXiv:2204.07667*, 2022.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE symposium on security and privacy (SP)*, pp. 3–18. IEEE, 2017.

Pierre Stock, Igor Shilov, Ilya Mironov, and Alexandre Sablayrolles. Defending against reconstruction attacks with Rényi differential privacy. *arXiv preprint arXiv:2202.07623*, 2022.

Om Thakkar, Swaroop Ramaswamy, Rajiv Mathews, and Françoise Beaufays. Understanding unintended memorization in federated learning. *arXiv preprint arXiv:2006.07490*, 2020.

Jianyu Wang, Anit Kumar Sahu, Zhouyi Yang, Gauri Joshi, and Soummya Kar. Matcha: Speeding up decentralized SGD via matching decomposition sampling. In *2019 Sixth Indian Control Conference (ICC)*, pp. 299–300. IEEE, 2019a.

Yu-Xiang Wang, Borja Balle, and Shiva Prasad Kasiviswanathan. Subsampled Rényi differential privacy and analytical moments accountant. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1226–1235. PMLR, 2019b.

Yuxin Wen, Jonas Geiping, Liam Fowl, Micah Goldblum, and Tom Goldstein. Fishing for user data in large-batch federated learning via gradient magnification. *arXiv preprint arXiv:2202.00580*, 2022.

Mingbin Xu, Congzheng Song, Ye Tian, Neha Agrawal, Filip Granqvist, Rogier van Dalen, Xiao Zhang, Arturo Argueta, Shiyi Han, Yaqiao Deng, et al. Training large-vocabulary neural language models by private federated learning for resource-constrained devices. *arXiv preprint arXiv:2207.08988*, 2022.

Hongxu Yin, Arun Mallya, Arash Vahdat, Jose M Alvarez, Jan Kautz, and Pavlo Molchanov. See through gradients: Image batch recovery via gradinversion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16337–16346, 2021.

Ashkan Yousefpour, Igor Shilov, Alexandre Sablayrolles, Davide Testuggine, Karthik Prasad, Mani Malek, John Nguyen, Sayan Ghosh, Akash Bharadwaj, Jessica Zhao, et al. Opacus: User-friendly differential privacy library in PyTorch. *arXiv preprint arXiv:2109.12298*, 2021.

A   CONNECTIONS TO LIKELIHOOD RATIO TEST

Let us assume that each model update follows a Gaussian distribution $\mathcal{N}(\mu, \Sigma)$. The sum of k model updates then either follows $\mathcal{N}(k\mu, k\Sigma)$ (without the canary) or $\mathcal{N}(k\mu + \nabla\ell(z), k\Sigma)$ (with the canary), recalling that $u_c \propto \nabla\ell(z)$. Then we have

$$p_0(u) = \frac{1}{\sqrt{\det(2\pi k\Sigma)}} \exp\left(-(u - k\mu)^T (k\Sigma)^{-1}(u - k\mu)/2\right)$$

$$p_1(u) = \frac{1}{\sqrt{\det(2\pi k\Sigma)}} \exp\left(-(u - (k\mu + \nabla\ell(z)))^T (k\Sigma)^{-1}(u - (k\mu + \nabla\ell(z)))/2\right)$$

$$= \frac{1}{\sqrt{\det(2\pi k\Sigma)}} \exp\left(-((u - k\mu) - \nabla\ell(z)))^T (k\Sigma)^{-1}((u - k\mu) - \nabla\ell(z))/2\right).$$

We can write the (log) likelihood ratio as

$$\log\frac{p_1(u)}{p_0(u)} = \frac{1}{2}\left((u - k\mu)^T (k\Sigma)^{-1}(u - k\mu) - ((u - k\mu) - \nabla\ell(z)))^T (k\Sigma)^{-1}((u - k\mu) - \nabla\ell(z)))\right)$$

$$= \frac{1}{2}\left((u - k\mu)^T (k\Sigma)^{-1}(u - k\mu) - ((u - k\mu) - \nabla\ell(z)))^T (k\Sigma)^{-1}((u - k\mu) - \nabla\ell(z)))\right)$$

$$= \nabla\ell(z)^T (k\Sigma)^{-1}(u - k\mu) - \frac{1}{2}\nabla\ell(z)^T (k\Sigma)^{-1}\nabla\ell(z).$$

In particular for the centers of the Gaussian with and without the canary, $u \in \{k\mu, k\mu + \nabla\ell(z)\}$,

$$\log\left(\frac{p_1(u)}{p_0(u)}\right) = \pm\frac{1}{2}\nabla\ell(z)^T (k\Sigma)^{-1}\nabla\ell(z).$$

Maximizing this term will thus help separate the two Gaussians. However, doing this directly is infeasible as it requires to form and invert the full covariance matrix Σ in very high dimensions. Instead, we propose to *minimize* $z \mapsto (\nabla\ell(z)^T)\Sigma(\nabla\ell(z))$ as it is tractable and can be done with SGD. Note that for sample model updates $\{u_i\}$ we can estimate the (uncentered) covariance matrix as $\frac{1}{n}\sum_i u_i u_i^T$ and thus

$$(\nabla\ell(z)^T)\Sigma(\nabla\ell(z)) \approx \frac{1}{n}\sum_i \nabla\ell(z)^T (u_i u_i^T)\nabla\ell(z) = \frac{1}{n}\sum_i \langle u_i, \nabla\ell(z)\rangle^2.$$

Which, ignoring constants, is the first term of $\mathcal{L}(z)$ defined in Equation 1. One could alternatively minimise $\langle\nabla\ell(z), \hat{\mu}\rangle^2$ with $\hat{\mu} = \frac{1}{n}\sum_i u_i$. We explore the empirical differences in Appendix D.

B   DATASETS & MODEL ARCHITECTURES

Here we detail the training setup and model architectures for our experiments. In all experiments we train with DP-FEDSGD and without momentum. We use both client (η_C) and server (η_S) learning rates. We train without dropout in all model architectures. In more detail:

- **CIFAR10** is an image classification tasks with 10 classes (Krizhevsky et al., 2009). We train a ResNet18 model (He et al., 2016) on CIFAR10. We form an IID split of $50,000$ train users and $10,000$ test users where each user holds a single sample and thus has a local batch size of 1. We use a client learning rate of $\eta_C = 0.01$ and server learning rate $\eta_S = 1$.

- **CelebA** is a binary image classification task (Liu et al., 2015). We train a ResNet18 model with $11,177,538$ parameters and a simple Convolutional Neural Network (CNN) with four convolutional layers following that used by Caldas et al. (2018) with $29,282$ parameters. We use the standard non-IID LEAF split resulting in 8408 train users and 935 test users and a local batch size of 32. We train with a client learning rate of $\eta_C = 0.899$ and a server learning rate of $\eta_S = 0.0797$.

Algorithm 2 Measuring $\hat{\varepsilon}$

Input: Privacy parameter δ, Sampling rate q, Number of attack scores n, Attack frequency s
1: **for** $r = 1, \ldots, R$ **do**
2:     **if** $r \mod s = 0$ **then**
3:         Freeze the model θ_r and use Algorithm 1 to compute n attack scores $\{s_r\}$
4:         Calculate the FPR and FNR from $\{s_r\}$
5:         Compute $\hat{\varepsilon}_r \leftarrow \max\left(\log \frac{1-\delta-\text{FPR}}{\text{FNR}}, \log \frac{1-\delta-\text{FNR}}{\text{FPR}}\right)$
6:         Compute $\hat{\sigma}_r \leftarrow \text{GetNoise}(\hat{\varepsilon}_r, \delta, q)$ ▷ Amplification by subsampling with RDP
7:         Compose $\hat{\sigma}_r$ with the accountant over the next s rounds
8:     **end if**
9: **end for**
10: **return** $\hat{\varepsilon} \leftarrow \text{GetPrivacy}(\{\hat{\sigma}_r\}; \delta, q)$ ▷ Convert sequence of noise estimates into $\hat{\varepsilon}$ under RDP

(a) Shakespeare per-round privacy ($\varepsilon = 50$)   (b) Shakespeare per-round privacy ($\varepsilon = \infty$)

Figure 6: Measuring privacy during Shakespeare training

- **Sent140** is a sentiment analysis (binary classification) task (Go et al., 2009). We train a 2-layer LSTM with $272,102$ parameters on Sent140 following the architecture of Caldas et al. (2018). We use standard non-IID LEAF splits resulting in $59,214$ train users and $39,477$ test users and a local batch size of 32. We train for 15 epochs, and for $\varepsilon = 0$ achieve an average test accuracy of 64.8%. We train with a client learning rate of $\eta_C = 5.75$ and a server learning rate of $\eta_S = 0.244$.

- **Shakespeare** is a next character prediction task with 47 classes (McMahan et al., 2017a). We train a similar LSTM model to Sent140, based on the architecture used by Caldas et al. (2018) with $819,920$ parameters. We use standard non-IID LEAF splits with 1016 train users and 113 test users and a local batch size of 128. We train our models for 15 epochs resulting in an average final test accuracy of 44.4% for $\varepsilon = 0$. We use a client learning rate of $\eta_C = 3$ and a server learning rate of $\eta_S = 0.524$.

C   MEASURING EMPIRICAL PRIVACY

C.1   ALGORITHM

In Section 3.4 we explained how we obtain a per-round privacy measurement $\hat{\varepsilon}_r$ from CANIFE and compound this to form a global privacy estimate $\hat{\varepsilon}$ over a training run. We detail this method in Algorithm 2. In order to compound our per-round estimates $\hat{\varepsilon}_r$ from CANIFE, since we only attack the model every s rounds we assume that the noise estimate $\hat{\sigma}_r$ remains constant between rounds r and $r + s$ before we attack the model again and re-estimate the noise $\hat{\sigma}_r$.

(a) Loss modifications

(b) Varying number of clients per round: Attack accuracy

(c) Varying number of clients per round: Empirical $\hat{\varepsilon}$

Figure 7: Further Ablations on CelebA; (a) CNN (b), (c); ResNet18

(a) Attack accuracy

(b) Canary health

Figure 8: Varying the canary gradient norm constant on CelebA (CNN)

C.2 DETAILS FOR MONITORING PRIVACY

In Section 4.2, we present experiments using CANIFE to measure empirical privacy during the training run of federated models. We ran each training run five times and examples of these runs are displayed in Figure 4. Here we provide extra details of the training setup:

- **CelebA.** We train a ResNet18 model for 30 epochs and have 100 clients participate per training round. This results in 85 rounds per epoch. We freeze and attack the model every $s = 40$ rounds resulting in 64 empirical privacy estimates ($\hat{\varepsilon}_r$) across training.

- **Sent140.** We train for 15 epochs and have 100 clients participate per training round. This results in 593 rounds per epoch and 8895 rounds in total. We freeze and attack the model every $s = 100$ resulting in 90 empirical privacy measurements across training.

- **Shakespeare.** We train for 30 epochs and have 60 clients participate per training round. This results in 17 rounds per epoch and 510 training rounds in total. We freeze and attack the model every $s = 8$ rounds resulting in 64 empirical privacy estimates across training.

C.3 FURTHER EXPERIMENTS: SHAKESPEARE

In Figure 4, we displayed example per-round estimates $\hat{\varepsilon}_r$ across training runs for CelebA and Sent140. In Figure 6a we display a similar plot but for an example training run on Shakespeare. We also note that one can use CANIFE to measure $\hat{\varepsilon}_r$ for models that are trained without privacy. In Figure 6b, we show an example training run on Shakespeare without DP ($\varepsilon = \infty$). We observe that initially in the early stages of training, the empirical privacy measure is stable, but eventually reaches frequent periods where the empirical estimate $\hat{\varepsilon}_r = \infty$ as the model begins to learn and the attack reaches 100% accuracy.

Canary Sample after optimization
mRnt,,,,,,,,,,,,'d,,,,,,R,,,,,A,,,,,,,,,,,,,,A,,,,,,,,,,,,,,,,,,AA,,,,V2,E >H &3 4i
Yet I confess that often ere thisMday,x?h\nnPImh!v7DhNAd}I!H';kXXI'PmP1Iert 6Fa
th, nothing bu; aZ empty box, sir, wQich in my lord's beealf I cote to e? rtat 3

Table 1: Canary Samples on Shakespeare.

D   FURTHER ABLATION STUDIES

Loss modification.   As discussed in Appendix A, we can minimise the dot-product of the canary with the average model update ("Loss 1") or the covariance loss ("Loss 2") which we choose to use in all experiments. In Figure 7a, we vary the design sample size and carry out 5 attacks with a checkpointed CNN model on CelebA while varying these losses. We observe that there is a clear difference in accuracy between the two losses, with Loss 2 having consistently high attack accuracy which is almost constant as we increase the sample size. We note that Loss 1 seems more sensitive to the total number of design samples, with increasing attack accuracy as the design sample size increases.

Number of clients per round.   In Figure 7b, we vary the number of clients per round and plot the average attack accuracy over 5 training runs. We note that the attack accuracy decreases slowly as the number of clients increases which is consistent with the observations made in Figure 3c. In Figure 7c, we plot the empirical estimate $\hat{\varepsilon}$ during training. We find that although the average accuracy decreases, that this doesn't have a significant affect on the final estimate $\hat{\varepsilon}$ which are fairly consistent across the different number of clients.

Canary gradient norm.   To conclude, we investigate the effect of the canary gradient norm constant in the second term of the loss $\mathcal{L}(z)$. We fix the privacy clipping constant to be $C = 1$ and vary the gradient norm constant on CelebA. We use a checkpointed CNN model trained without DP to 70% test accuracy. We attack the model 10 times and average the results. In Figure 8a, we display the average accuracy of the attack and in Figure 8b the average canary health as we vary the gradient norm constant. We observe that choosing the constant too large can significantly decrease the efficacy of the attack and that choosing the constant around C is enough to guarantee high accuracy and well-behaved optimization. We note that the canary health does not significantly decrease until the norm constant is chosen to be very large (> 600), yet the attack suffers a large drop in accuracy for constants > 50. This implies that as you increase the constant, it is first possible to design a canary that has large gradient norm but at the expense of orthogonality to the other model updates, and as the constant gets very large, it becomes too difficult to optimise either term of $\mathcal{L}(z)$.

E   CANARY SAMPLES

We display in Table 1 some examples of designed canaries with CANIFE when initializing the crafting procedure with training sentences on Shakespeare.