Analytical Study of Momentum-Based Acceleration Methods in Paradigmatic High-Dimensional Non-Convex Problems

Abstract

The optimization step in many machine learning problems rarely relies on vanilla gradient descent but it is common practice to use momentum-based accelerated methods. Despite these algorithms are widely applied to arbitrary loss functions, their behaviour in generically non-convex, high dimensional landscapes is poorly understood. In this work we use dynamical mean field theory techniques to describe analytically the average dynamics of these methods in a prototypical non-convex model: the (spiked) matrix-tensor model. We derive a closed set of equations that describe the behaviour of heavy-ball momentum and Nesterov acceleration. Using these equations we show that these methods speed-up the dynamics but they do not improve the algorithmic threshold with respect to gradient descent in the spiked model.

1 Introduction

In many computer science applications one of the critical steps is the minimization of a cost function. Apart from very few exceptions, the simplest way to approach the problem is by running local algorithms that move down in the cost landscape and hopefully approach a minimum at a small cost. The simplest algorithm of this kind is gradient descent, that has been used since the XIX century to address optimization problems [1]. Later on, faster and more stable algorithms have been developed: second order methods [2, 3, 4, 5, 6, 7] where information from the Hessian is used to adapt the descent to the local geometry of the cost landscape, and first order methods based on momentum [8, 9, 10, 11, 12] that introduce inertia in the algorithm and provably speed-up convergence in a variety of convex problems. In the era of deep-learning and large datasets, the research has pushed towards memory efficient algorithms, in particular stochastic gradient descent that trades off computational and statistical efficiency [13, 14], and momentum-based methods are very used in practice [15]. Which algorithm is the best in practice seems not to have a simple answer and there are instances where a class of algorithms outperforms the other and vice-versa [16]. Most of the theoretical literature on momentum-based methods concerns convex problems [17, 18, 19, 20, 21] and, despite these methods have been successfully applied to a variety of problems, only recently high dimensional non-convex settings have been considered [22, 23, 24]. Furthermore, with few exceptions [25], the majority of these studies focus on *worst-case* analysis while empirically one could also be interested in the behaviour of such algorithms on typical instances of the optimization problem, formulated in terms of a generative model extracted from a probability distribution.

The main contribution of this paper is the analytical description of the average evolution of momentum-based methods in two simple non-convex, high-dimensional, optimization problems. First we consider the mixed p-spin model [26, 27], a paradigmatic random high-dimensional optimization problem. Furthermore we consider its spiked version, the spiked matrix-tensor [28, 29] which is a prototype

high-dimensional non-convex inference problem in which one wants to recover a signal hidden in the landscape. The second main result of the paper is the characterization of the algorithmic threshold for accelerated-methods and the surprising finding that this coincides with the threshold for gradient descent.

The definition of the model and the algorithms used are reported in section 2. In section 3 and 4 we use dynamical mean field theory [30, 31, 32] to derive a set of equations that describes the average behaviour of these algorithms starting from random initialization in the high dimensional limit. To the best of our knowledge this is the first time that an analytic expression for the state evolution of accelerated gradient methods is derived in a high dimensional fully non-convex setting.

We apply our equations to the spiked matrix-tensor model, which displays a similar phenomenology as the one described in [24, 33] for the phase retrieval problem: all algorithms have two dynamical regimes. First, they navigate in the non-convex landscape and, second, if the signal to noise ratio is strong enough, the dynamics eventually enters in the basin of attraction of the signal and rapidly reaches the bottom of the cost function. We use the derived state evolution of the algorithms to determine their algorithmic threshold for signal recovery.

Finally we show that in the analysed models, momentum-based methods only have an advantage in terms of speed but they do not outperform vanilla gradient descent in terms of algorithmic threshold. Indeed in section 5 we show that all the analysed methods share the same threshold.

2 Model definition

We consider two prototypical non-convex models: the mixed p-spin model [32, 34], and the spiked matrix-tensor model [28, 29]. Given a tensor $\boldsymbol{T} \in (\mathbb{R}^N)^{\otimes p}$ and a matrix $\boldsymbol{Y} \in \mathbb{R}^{N \times N}$, the goal is to find a common low-rank representation $\boldsymbol{x}$ that minimizes the loss

$$\mathcal{L} = -\frac{1}{\Delta_p} \sqrt{\frac{(p-1)!}{N^{p-1}}} \sum_{i_1,\ldots,i_p=1}^{N} T_{i_1,\ldots,i_p} x_{i_1} \ldots x_{i_p} - \frac{1}{\Delta_2} \frac{1}{\sqrt{N}} \sum_{i,j=1}^{N} Y_{ij} x_i x_j, \tag{1}$$

with $\boldsymbol{x}$ in the N-dimensional sphere of radius $\sqrt{N}$. The two problems differ by the definition of the variables $\boldsymbol{T}$ and $\boldsymbol{Y}$. Call $\boldsymbol{\xi}^{(p)}$ and $\boldsymbol{\xi}^{(2)}$ order p tensor and a matrix having i.i.d. Gaussian elements, with zero mean and variances Δ_p and Δ_2 respectively. In the mixed p-spin model, tensor and matrix are completely random $\boldsymbol{T} = \boldsymbol{\xi}^{(p)}$ and $\boldsymbol{Y} = \boldsymbol{\xi}^{(2)}$. While in the spiked matrix-tensor model there is a low-rank representation given by $\boldsymbol{x}^* \in \mathcal{S}^{N-1}(\sqrt{N})$ embedded in the problem as follows:

$$T_{i_1\ldots i_p} = \sqrt{\frac{(p-1)!}{N^{p-1}}} x_{i_1}^* \ldots x_{i_p}^* + \xi_{i_1\ldots i_p}^{(p)}, \qquad Y_{ij} = \frac{x_i^* x_j^*}{\sqrt{N}} + \xi_{ij}^{(2)}. \tag{2}$$

These problems have been studied both in physics, and computer science. In the physics literature, research has focused on the relationship of gradient descent and Langevin dynamics and the corresponding topology of the complex landscape [32, 35, 34, 36, 27, 37]. The state evolution of the gradient descent dynamics for the mixed spiked matrix-tensor model has been studied only more recently [38]. All these works considered simple gradient descent dynamics and its noisy (Langevin) dressing.

In this work we focus on accelerated methods and provide an analytical characterization of the average performance of these algorithms for the models introduced above. In order to simplify the analysis we relax the hard constraint on the norm of the vector $\boldsymbol{x}$ and consider $\boldsymbol{x} \in \mathbb{R}^N$ while adding a penalty term to $\mathcal{L}$ to enforce a soft constraint $\frac{\mu}{4N}\left(\sum_i x_i^2 - N\right)^2$, so that the total cost function is $\mathcal{H} = \mathcal{L} + \frac{\mu}{4N}\left(\sum_i x_i^2 - N\right)^2$. Using the techniques described in detail in the next section we write the state evolution for the following algorithms:

- **Nesterov acceleration** [9] starting from $\boldsymbol{y}[0] = \boldsymbol{x}[0] \in \mathbb{S}^{N-1}\left(\sqrt{N}\right)$

$$\boldsymbol{x}[t+1] = \boldsymbol{y}[t] - \alpha\nabla\mathcal{H}(\boldsymbol{y}[t]), \tag{3}$$

$$\boldsymbol{y}[t+1] = \boldsymbol{x}[t+1] + \frac{t}{t+3}\left(\boldsymbol{x}[t+1] - \boldsymbol{x}[t]\right). \tag{4}$$

given α the learning rate of the algorithm.

- **Polyak's or heavy ball momentum** (HB) [8] starting from $\boldsymbol{y}[0] = \boldsymbol{0}$ and $\boldsymbol{x}[0] \in \mathbb{S}^{N-1}\left(\sqrt{N}\right)$, given the parameters α, β

$$\boldsymbol{y}[t+1] = \beta\boldsymbol{y}[t] + \nabla\mathcal{H}(\boldsymbol{x}[t]), \tag{5}$$
$$\boldsymbol{x}[t+1] = \boldsymbol{x}[t] - \alpha\boldsymbol{y}[t+1]; \tag{6}$$

- **gradient descent** (GD) starting from $\boldsymbol{x}[0] \in \mathbb{S}^{N-1}\left(\sqrt{N}\right)$

$$\boldsymbol{x}[t+1] = \boldsymbol{x}[t] - \alpha\nabla\mathcal{H}(\boldsymbol{x}[t]). \tag{7}$$

This case has been considered in [27, 38] with the constraint $\sum_i x_i^2 = N$. The generalization to the present case in which constraint is soft is a straightforward small extension of these previous works.

We will not compare the performance of these accelerated gradient methods to algorithms of different nature (such as for example message passing ones) in the same settings. Our goal will be the derivation of a set of dynamical equations describing the average evolution of such algorithms in the high dimensional limit $N \to \infty$.

3   Dynamical mean field theory

Figure 1: **Simulation and DMFT comparison in mixed p-spin model.** The simulations in the figures have parameters $p = 3$, $\Delta_3 = 2/p$, $\Delta_2 = 1$, ridge parameter $\mu = 10$ and input dimension $N = 1024$. In all our simulations we use the dilution technique [39, 40] to reduce the computational cost. We consider: Nesterov acceleration in pink; heavy ball momentum in blue with $\alpha = 0.01$ and $\beta = 0.9$; and gradient descent in grey. We run 100 simulations (in transparency) and draw the average. The parameters for heavy ball are the best parameters found in our simulations, see also Fig. 2 for a comparison. The results from the DMFT equations are drawn with dotted lines.

We use dynamical mean field theory (DMFT) techniques to derive sets of equation describing the evolution of the algorithms. The method has its origin in statistical physics and can be applied to the study of Langevin dynamics of disordered systems [30, 31, 41]. More recently it was proved to be rigorous in the case of the mixed p-spin model [42, 43]. The application to the inference version of the optimization problem is in [29, 38]. The same techniques have also been applied to study the stochastic gradient descent dynamics in single layer networks [44] and in the analysis of recurrent neural networks [45, 46, 47]. The idea behind DMFT is that, if the input dimension N is sufficiently large, one can obtain a description of the dynamics in terms of the typical evolution of a representative entry of the vector $\boldsymbol{x}$ (and vector $\boldsymbol{y}$ when it applies). The representative element evolves according to a non-Markovian stochastic process whose memory term and noise source encode, in a self-consistent way, the interaction with all the other components of vector $\boldsymbol{x}$ (and $\boldsymbol{y}$). The memory terms as well as the statistical properties of the noise are described by dynamical order parameters which, in the present model, are given by the dynamical two-time correlation and response functions.

In this first step of the analysis we obtain an effective dynamics for a representative entry x_i (and y_i). The next step consists in using such equations to compute self-consistently the properties of the

corresponding stochastic processes, namely the memory kernel and the statistical correlation of the noise. In Fig. 1 we anticipate the results by comparing numerical simulations with the integration of the DMFT equations for the different algorithms: on the left we observe the evolution of the loss, on the right we observe the evolution of the radius of the vector $\boldsymbol{x}$, defined as the L_2 norm of the vector $||\boldsymbol{x}||_2$. We find a good agreement between the DMFT state evolution and the numerical simulations.

We compare Nesterov acceleration with the heavy ball momentum in the mixed p-spin model Fig. 1, and in the spiked model Fig. 3. Nesterov acceleration allows for a fast convergence to the asymptotic energy without need of parameter tuning. In Fig. 2 we compare the numerical simulations for the HB algorithm and the DMFT description of the corresponding massive momentum version for several control parameters.

DMFT equations

In the following we describe the resulting DMFT equations for the correlation and response functions. The details of their derivation for the case of the Nesterov acceleration are provided in the following section, while we leave the other cases to the supplementary material (SM). The dynamical order parameters appearing in the DMFT equations are one-time or two-time correlations, e.g. $C_{xy}[t, t'] = \sum_i x_i[t] y_i[t]/N$, and response to instantaneous perturbation of the dynamics, e.g. $R_x[t, t'] = \left(\sum_i \delta x_i[t]/\delta H_i[t'] \right)/N$ by a local field $\boldsymbol{H}$. In this section we show only the equations for the mixed p-spin model and we discuss the difference and the derivation of the equations for the spiked tensor in the SM.

From the order parameters we can evaluate useful quantities that describe the evolution of the algorithms. In particular in Figs. 1,2,3 we show the loss, the radius, and the overlap with the solution in the spiked case (Fig. 3):

- Average loss

$$\mathcal{L}[t] = -\frac{\alpha}{\Delta_p C_x[t,t]^{\frac{p}{2}}} \sum_{t''=0}^{t} R_x[t,t'] C_x[t,t']^{p-1} - \frac{\alpha}{\Delta_2 C_x[t,t]} \sum_{t''=0}^{t} R_x[t,t'] C_x[t,t']; \quad (8)$$

- Radius $\sqrt{C_x[t,t]}$;

- Define $m_x[t] = \frac{1}{N} \sum_i x_i[t] x_i^*$ an additional order parameter for the spiked matrix-tensor model (more details are given in the SM), the overlap with ground truth is

$$\frac{\boldsymbol{x}[t] \cdot \boldsymbol{x}^*}{||\boldsymbol{x}||} = \frac{m_x[t]}{\sqrt{C_x[t,t]}}$$

Nesterov acceleration. It has been shown that this algorithm has a quadratic convergence rate to the minimum in convex optimization problems, thus it outperforms standard gradient descent whose convergence is linear in the number of iterations [9]. The analysis of the algorithm is described by the flow of the following dynamical correlation functions

$$C_x[t, t'] = \frac{1}{N} \sum_i x_i[t] x_i[t'], \quad (9)$$

$$C_y[t, t'] = \frac{1}{N} \sum_i y_i[t] y_i[t'], \quad (10)$$

$$C_{xy}[t, t'] = \frac{1}{N} \sum_i x_i[t] y_i[t], \quad (11)$$

$$R_x[t, t'] = \frac{1}{N} \sum_i \frac{\delta x_i[t]}{\delta H_i[t']}, \quad (12)$$

$$R_y[t, t'] = \frac{1}{N} \sum_i \frac{\delta y_i[t]}{\delta H_i[t']}. \quad (13)$$

The dynamical equations are obtained following the procedure detailed in section 4. Call $Q(x) = x^2/(2\Delta_2) + x^p/(p\Delta_p)$,

$$C_x[t+1,t'] = C_{xy}[t,t'] - \alpha\mu\left(C_y[t,t]-1\right)C_y[t,t'] + \alpha^2\sum_{t''=0}^{t'}R_x[t',t'']Q'\left(C_y[t,t'']\right)+$$
$$+ \alpha^2\sum_{t''=0}^{t}R_y[t,t'']Q''\left(C_y[t,t'']\right)C_{xy}[t',t'']; \tag{14}$$

$$C_{xy}[t+1,t'] = C_y[t,t'] - \alpha\mu\left(C_y[t,t]-1\right)C_{xy}[t,t'] + \alpha^2\sum_{t''=0}^{t'}R_y[t',t'']Q'\left(C_y[t,t'']\right)+$$
$$+ \alpha^2\sum_{t''=0}^{t}R_y[t,t'']Q''\left(C_y[t,t'']\right)C_y[t',t'']; \tag{15}$$

$$C_{xy}[t',t+1] = \frac{2t+3}{t+3}C_x[t+1,t'] - \frac{t}{t+3}C_x[t,t']; \tag{16}$$

$$C_y[t',t+1] = \frac{2t+3}{t+3}C_{xy}[t+1,t'] - \frac{t}{t+3}C_{xy}[t,t']; \tag{17}$$

$$R_x[t+1,t'] = R_y[t,t'] + \delta_{t,t'} - \alpha\mu\left(C_y[t,t]-1\right)R_y[t,t']$$
$$+ \alpha^2\sum_{t''=t'}^{t}R_y[t,t'']R_y[t'',t']Q''\left(C_y[t,t'']\right); \tag{18}$$

$$R_y[t',t+1] = \frac{2t+3}{t+3}R_x[t+1,t'] - \frac{t}{t+3}R_x[t,t']. \tag{19}$$

The initial conditions are: $C_x[0,0] = 1$, $C_y[0,0] = 1$, $C_{xy}[0,0] = 1$, $R_x[t+1,t] = 1$, $R_y[t+1,t] = \frac{2t+3}{t+3}$.

The equations show a discretized version of the typical structure of DMFT equations. We can observe: terms immediately ascribable to the dynamical equations (3,4) and summations whose interpretation is less trivial without looking into the derivation. They represent memory kernels that take into account linear response theory for small perturbations to the dynamics (e.g. the last term of Eq. (14)) and a noise whose statistical properties encode the effect of all the degrees of freedom on a representative one (e.g. the second last term of Eq. (14)).

Figure 2: **DMFT for HB.** Simulations of HB momentum in the mixed p-spin model with $p = 3$, $\Delta_3 = 2/p$, $\Delta_2 = 1$, ridge parameter $\mu = 10$ and input dimension $N = 1024$. The parameters are $\alpha = 0.01$ for all the simulations and $\beta \in \{0.5, 0.7, 0.9\}$. We use solid lines to represent the result from the simulation, the dotted lines for the DMFT of HB.

142 **Heavy ball momentum.** The DMFT equations are obtained analogously to previous ones,

$$C_y[t+1,t'] = \beta C_y[t,t'] + \mu \left(C_x[t,t]-1\right) C_{xy}[t,t'] + \alpha \sum_{t''=0}^{t'} R_y[t',t'']Q'\left(C_x[t,t'']\right) \tag{20}$$

$$+ \alpha \sum_{t''=0}^{t} R_x[t,t'']Q''\left(C_x[t,t'']\right) C_{xy}[t'',t'];$$

$$C_{xy}[t',t+1] = \beta C_{xy}[t',t] + \mu \left(C_x[t,t]-1\right) C_x[t,t'] + \alpha \sum_{t''=0}^{t'} R_x[t',t'']Q'\left(C_x[t,t'']\right) \tag{21}$$

$$+ \alpha \sum_{t''=0}^{t} R_x[t,t'']Q''\left(C_x[t,t'']\right) C_x[t',t''];$$

$$C_{xy}[t+1,t'] = C_{xy}[t,t'] - \alpha C_y[t+1,t']; \tag{22}$$

$$C_x[t+1,t'] = C_x[t,t'] - \alpha C_{xy}[t',t+1]; \tag{23}$$

$$R_y[t+1,t'] = \beta R_y[t,t'] + \frac{1}{\alpha}\delta_{t,t'} + \mu \left(C_x[t,t]-1\right) R_x[t,t']$$

$$+ \alpha \sum_{t''=0}^{t} R_x[t,t'']R_x[t'',t']Q''\left(C_x[t,t'']\right); \tag{24}$$

$$R_x[t+1,t'] = R_x[t,t'] - \alpha R_y[t+1,t']. \tag{25}$$

143 with initial conditions: $C_x[0,0] = 1$, $C_y[0,0] = 0$, $C_{xy}[0,0] = 0$, $R_y[t+1,t] = 1/\alpha$, $R_x[t+1,t] =$
144 -1. Fig. 2 shows the consistency of theory and simulations.

145 Some authors proposed mappings between discrete update equation and continuous flow for both
146 heavy ball momentum and Nesterov acceleration. In the SM we considered the work [48] that maps
147 HB to second order ODEs in some regimes of α and β. This mapping establishes the equivalence of
148 the algorithm to the physics problem of a massive particle moving under the action of a potential.
149 This problem has been studied in [49] but the result is limited to the under-damped regime where the
150 first order derivative becomes vanishingly small. In the SM we use a different approach from [49]
151 obtaining the dynamical equations for arbitrary damping regimes, and we recover the equivalence
152 established in [48] comparing the results from the two DMFTs formulations.

153 **Gradient descent.** A simple way to obtain the gradient descent DMFT is by taking the limit $m \to 0$
154 in the DMFT of the massive momentum description of HB. We get

$$C_x[t+1,t'] = C_x[t,t'] - \alpha\mu \left(C_x[t,t]-1\right) C_x[t,t'] + \alpha^2 \sum_{t''=0}^{t'} R_x[t',t'']Q'\left(C_x[t,t'']\right) \tag{26}$$

$$+ \alpha^2 \sum_{t''=0}^{t} R_x[t,t'']Q''\left(C_x[t,t'']\right) C_x[t',t''];$$

$$R_x[t+1,t'] = R_x[t,t'] + \delta_{t,t'} + \alpha^2 \sum_{t''=0}^{t} R_x[t,t'']R_x[t'',t']Q''\left(C_x[t,t'']\right) \tag{27}$$

$$- \alpha\mu \left(C_x[t,t]-1\right) R_x[t,t'].$$

155 with initial conditions: $C_x[0,0] = 1$, and $R_x[t+1,t] = 1$. Apart from the μ-dependent term, these
156 equations are a particular case of the ones that appear in [34, 50] and we point to these previous
157 references for details.

4 Derivation of DMFT for Nesterov acceleration

159 The approach for the DMFT proposed in this section is based on the dynamical cavity method [41].
160 Consider the problem having dimension $N + 1$ and denote the additional entry of the vectors $\boldsymbol{x}$ and
161 $\boldsymbol{y}$ with the subscript 0, x_0 and y_0. The idea behind cavity method is to evaluate how this additional

Figure 3: **DMFT in the spiked matrix-tensor model.** Performance of heavy ball and Nesterov in the spiked matrix-tensor model with $p = 3$, $1/\Delta_2 = 2.7$, $\Delta_3 = 1.0$, and $\mu = 10$. The parameters in the simulations are: $\alpha = 0.01$ and $\beta = 0.9$ for HB. The different solid lines correspond to simulations with input dimension $N = 8192$, while the dotted lines are obtained from the DMFT that, by definition, is in the infinite dimension limit. In the spiked version of the model the finite size effects are stronger and larger simulation sizes are needed.

dimension changes the dynamics of all degrees of freedom. If the dimension is sufficiently large the dynamics is only slightly modified by the additional dimension, and the effect of the additional degree of freedom can be tracked in perturbation theory.

Consider the Nesterov update algorithm and isolate the effect of the additional degree of freedom

$$x_i[t+1] = y_i[t] + \alpha \sum_{j\neq 0} J_{ij} y_j[t] + \alpha \sum_{(i,i_2,\dots,i_p)} J_{i,i_2,\dots,i_p} y_{i_2}[t]\dots y_{i_p}[t] - \alpha\mu \left(\sum_{j\neq 0} \frac{y_j^2[t]}{N} - 1 \right) y_i[t] \tag{28}$$

$$+ \alpha \sum_{(i,0,i_3,\dots,i_p)} J_{i,0,i_3,\dots,i_p} y_0[t] y_{i_3}[t]\dots y_{i_p}[t] + \alpha J_{i0} y_0[t] + \frac{\mu}{N} y_0^2[t] y_i[t], \tag{29}$$

$$y_i[t+1] = x_i[t+1] + \frac{t}{t+3}\left(x_i[t+1] - x_i[t]\right). \tag{30}$$

Identify Eq. (29) with the perturbation acting on the dynamics $H_i[t]$. In the linear response regime, the perturbed entries are given by:

$$x_i[t] \approx x_i^0 + \alpha \sum_{t''=0}^{t} \frac{\delta x_i[t]}{\delta H_i[t'']} H_i[t''], \qquad y_i[t] \approx y_i^0 + \alpha \sum_{t''=0}^{t} \frac{\delta y_i[t]}{\delta H_i[t'']} H_i[t'']. \tag{31}$$

The dynamics of the 0th position to the leading order in the perturbation is

$$x_0[t+1] = y_0[t] - \alpha\mu\left(\frac{1}{N}\sum_j y_j^2[t] - 1\right) y_0[t] + \Xi[t] + \alpha^2 \sum_j J_{0j} \sum_{t''=0}^{t} \frac{\delta y_j[t]}{\delta H_j[t'']} H_j[t''] \tag{32}$$

$$+ \alpha^2 \sum_{(0,i_2,\dots,i_p)} J_{0,i_2,\dots,i_p} \left(\sum_{t''=0}^{t} \frac{\delta y_{i_2}[t]}{\delta H_{i_2}[t'']} H_{i_2}[t''] y_{i_3}[t]\dots y_{i_p}[t] + \text{perm.} \right) + \mathcal{O}\left(\frac{1}{N}\right), \tag{33}$$

$$y_i[t+1] = x_i[t+1] + \frac{t}{t+3}\left(x_i[t+1] - x_i[t]\right), \tag{34}$$

with $\Xi = \alpha \sum_j J_{0j} y_j[t] + \alpha \sum_{(0,i_2,\dots,i_p)} J_{0,i_2,\dots,i_p} y_{i_2}[t]\dots y_{i_p}[t]$ a Gaussian stochastic process with moments:

$$\mathbb{E}[\Xi[t]] = 0,$$

$$\mathbb{E}[\Xi[t]\Xi[t']] = \frac{1}{\Delta_2} C_y[t,t'] + \frac{1}{\Delta_p} C_y^{p-1}[t,t'] = Q'\left(C_y[t,t']\right) \doteq \mathbb{K}[t,t'].$$

The terms in Eqs. (32,33) can be simplified. Consider the last term in Eq. (32):

$$\alpha^2 \sum_j J_{0j} \sum_{t''=0}^{t} \frac{\delta y_j[t]}{\delta H_j[t'']} J_{0j} y_0[t''] \approx \frac{\alpha^2}{\Delta_2 N} \sum_{t''=0}^{t} \frac{\delta y_j[t]}{\delta H_j[t'']} y_0[t''] = \frac{\alpha^2}{\Delta_2} \sum_{t''=0}^{t} R_y[t,t''] y_0[t'']. \tag{35}$$

Where the last equality follows from the definition of response function in y.

Same simplification applies to Eq. (33) taking carefully into account the permutations

$$\frac{\alpha^2(p-1)}{\Delta_p} \sum_{t''=0}^{t} R_y[t,t''] \left(C_y[t,t'']\right)^{p-2} y_0[t''].$$ (36)

Finally the effective dynamics of the additional dimension

$$x_0[t+1] = y_0[t] + \alpha\Xi[t] - \alpha\mu\left(C_y[t,t]-1\right)y_0[t] + \alpha^2\sum_{t''=0}^{t} R_y[t,t'']Q''\left(C_y[t,t'']\right)y_0[t''];$$ (37)

$$y_0[t+1] = x_0[t+1] + \frac{t}{t+3}\left(x_0[t+1]-x_0[t]\right).$$ (38)

In order to derive the updates of the order parameters, we need the expected values of $\langle\Xi[t]x_0[t']\rangle$ and $\langle\Xi[t]y_0[t']\rangle$ with respect to the stochastic process. These are obtained using Girsanov theorem

$$\langle\Xi[t]x_0[t']\rangle = \alpha\sum_{t''} R_x[t',t'']Q'\left(C_y[t,t'']\right), \qquad \langle\Xi[t]y_0[t']\rangle = \alpha\sum_{t''} R_y[t',t'']Q'\left(C_y[t,t'']\right).$$

Final step consists in substituting the Eqs. (37,38) into the equations of the order parameters Eqs. (14-19). Then we identify the order parameters in the equations and use the results of Girsanov theorem to obtain the dynamical equations reported in section 3.

5   Algorithmic threshold

Figure 4: **Phase diagram of the spiked matrix-tensor model.** The horizontal and vertical axis represent the parameters of the model Δ_p and $1/\Delta_2$. We identify two regions in the diagram: where Nesterov, heavy ball and gradient descent algorithms lead to the hidden solution (upper region), and where they fail (lower region). The grey square connected by a solid line represents the threshold of gradient descent estimated numerically as detailed in the text. We use points to indicate the threshold extrapolated from the DMFT: pink circles for Nesterov acceleration and blue diamonds for heavy ball momentum with $\beta = 0.9$ and $\alpha = 0.01$.

Finally we investigate the performance of accelerated methods in recovering a signal in a complex non-convex landscape. The dynamics of the gradient descent has been studied in the spiked matrix-tensor model in [38]. Using DMFT it was possible to compute the phase diagram for signal recovery in terms of the noise levels Δ_2 and Δ_p. This phase diagram was later confirmed theoretically [51].

Given the DMFT equations derived in the previous sections we can apply the analysis proposed in [38] to accelerated gradient methods. Given order of the tensor p and Δ_p, increasing Δ_2 the problem becomes harder and moves from the easy phase - where the signal can be partially recovered - to an algorithmically impossible phase - where the algorithm remains stuck at vanishingly small overlap.

The goal of the analysis is to characterize the algorithmic threshold that separates the two phases. Using the DMFT we estimate the *relaxation time* – the time the accelerated methods need to find the signal. Since this time diverges approaching the algorithmic threshold, the fit of the divergence point gives an estimation of the threshold.

More precisely, for each value of Δ_p as the noise to signal ratio (Δ_2) increases the simulation time required to arrive close to the signal[1] increases like a power law $\sim a \, |\Delta_2 - \Delta_2^{al \cdot}(\Delta_p)|^{-\theta}$. The algorithmic threshold $\Delta_2^{al \cdot}(\Delta_p)$ is obtained by fitting the parameters of the power law $(a, \theta, \Delta_2^{al \cdot})$. In the SM we show an example of the extrapolation of a single point where many initial conditions $m_x(0)$ are considered in order to correctly characterize the limits $N \to \infty$ and $m_x(0) \to 0^+$. Finally the fits obtained for the three algorithms and for several Δ_p are shown in the phase diagram of Fig. 4 for $p = 3$. We observe that all the algorithms give very close thresholds. DMFT allows to obtain a good estimation of the threshold, free from finite size effects and stochastic fluctuations that are present in the direct estimation from the simulations.

Conclusions and broader impact

In this work we analysed momentum-accelerated methods in two paradigmatic high-dimensional non-convex problems: the mixed p-spin model and the spiked matrix-tensor model. Our analysis is based on dynamical mean field theory and provides a set of equations that correctly characterizes the average evolution of the dynamics. We have focused on Polyak's heavy ball and Nesterov acceleration, but the same techniques apply to more recent methods such as quasi-hyperbolic momentum [12] and proportional integral-derivative control algorithm [11]. In the future we plan to extend this work to more complex models such as 1-layer feedforward networks [44], and recurrent networks [46, 47] where DMFT has already been used for gradient-based methods. Our study is theoretical in nature and we do not foresee any harmful societal impact.

References

[1] Augustin Cauchy. Méthode générale pour la résolution des systemes d'équations simultanées. *Comp. Rend. Sci. Paris*, 25(1847):536–538, 1847.

[2] Kenneth Levenberg. A method for the solution of certain non-linear problems in least squares. *Quarterly of applied mathematics*, 2(2):164–168, 1944.

[3] Donald W Marquardt. An algorithm for least-squares estimation of nonlinear parameters. *Journal of the society for Industrial and Applied Mathematics*, 11(2):431–441, 1963.

[4] Charles G Broyden. The convergence of a class of double-rank minimization algorithms: 2. the new algorithm. *IMA journal of applied mathematics*, 6(3):222–231, 1970.

[5] Roger Fletcher. A new approach to variable metric algorithms. *The computer journal*, 13(3):317–322, 1970.

[6] Donald Goldfarb. A family of variable-metric methods derived by variational means. *Mathematics of computation*, 24(109):23–26, 1970.

[7] David F Shanno. Conditioning of quasi-newton methods for function minimization. *Mathematics of computation*, 24(111):647–656, 1970.

[8] Boris T Polyak. Some methods of speeding up the convergence of iteration methods. *USSR Computational Mathematics and Mathematical Physics*, 4(5):1–17, 1964.

[9] Yurii E Nesterov. A method for solving the convex programming problem with convergence rate o (1/kˆ 2). In *Dokl. akad. nauk Sssr*, volume 269, pages 543–547, 1983.

[10] Saman Cyrus, Bin Hu, Bryan Van Scoy, and Laurent Lessard. A robust accelerated optimization algorithm for strongly convex functions. In *2018 Annual American Control Conference (ACC)*, pages 1376–1381. IEEE, 2018.

---

[1] Since the best possible overlap for maximum a posteriori estimator m^{MAP} can be computed explicitly, "close" means the time that the algorithms takes to arrive at $0.9 m^{\text{MAP}}$

[11] Wangpeng An, Haoqian Wang, Qingyun Sun, Jun Xu, Qionghai Dai, and Lei Zhang. A pid controller approach for stochastic optimization of deep networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 8522–8531, 2018.

[12] Jerry Ma and Denis Yarats. Quasi-hyperbolic momentum and adam for deep learning. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

[13] Herbert Robbins and Sutton Monro. A stochastic approximation method. *The annals of mathematical statistics*, pages 400–407, 1951.

[14] Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In *International conference on machine learning*, pages 1139–1147. PMLR, 2013.

[15] Laurent Lessard, Benjamin Recht, and Andrew Packard. Analysis and design of optimization algorithms via integral quadratic constraints. *SIAM Journal on Optimization*, 26(1):57–95, 2016.

[16] Rahul Kidambi, Praneeth Netrapalli, Prateek Jain, and Sham Kakade. On the insufficiency of existing momentum schemes for stochastic optimization. In *2018 Information Theory and Applications Workshop (ITA)*, pages 1–9. IEEE, 2018.

[17] Euhanna Ghadimi, Hamid Reza Feyzmahdavian, and Mikael Johansson. Global convergence of the heavy-ball method for convex optimization. In *2015 European control conference (ECC)*, pages 310–315. IEEE, 2015.

[18] Nicolas Flammarion and Francis Bach. From averaging to acceleration, there is only a step-size. In *Conference on Learning Theory*, pages 658–695. PMLR, 2015.

[19] Igor Gitman, Hunter Lang, Pengchuan Zhang, and Lin Xiao. Understanding the role of momentum in stochastic gradient methods. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32, pages 9633–9643. Curran Associates, Inc., 2019.

[20] Tao Sun, Penghang Yin, Dongsheng Li, Chun Huang, Lei Guan, and Hao Jiang. Non-ergodic convergence analysis of heavy-ball algorithms. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 5033–5040, 2019.

[21] Nicolas Loizou and Peter Richtárik. Momentum and stochastic momentum for stochastic gradient, newton, proximal point and subspace descent methods. *Computational Optimization and Applications*, 77(3):653–710, 2020.

[22] Tianbao Yang, Qihang Lin, and Zhe Li. Unified convergence analysis of stochastic momentum methods for convex and non-convex optimization. *arXiv preprint arXiv:1604.03257*, 2016.

[23] Sébastien Gadat, Fabien Panloup, Sofiane Saadane, et al. Stochastic heavy ball. *Electronic Journal of Statistics*, 12(1):461–529, 2018.

[24] Jun-Kun Wang and Jacob Abernethy. Quickly finding a benign region via heavy ball momentum in non-convex optimization. *arXiv preprint arXiv:2010.01449*, 2020.

[25] Damien Scieur and Fabian Pedregosa. Universal average-case optimality of polyak momentum. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 8565–8572. PMLR, 13–18 Jul 2020.

[26] Alain Barrat, Silvio Franz, and Giorgio Parisi. Temperature evolution and bifurcations of metastable states in mean-field spin glasses, with connections with structural glasses. *Journal of Physics A: Mathematical and General*, 30(16):5593–5612, aug 1997.

[27] Giampaolo Folena, Silvio Franz, and Federico Ricci-Tersenghi. Rethinking mean-field glassy dynamics and its relation with the energy landscape: The surprising case of the spherical mixed p-spin model. *Physical Review X*, 10(3):031045, 2020.

[28] Emile Richard and Andrea Montanari. A statistical model for tensor pca. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27, pages 2897–2905. Curran Associates, Inc., 2014.

[29] Stefano Sarao Mannelli, Giulio Biroli, Chiara Cammarota, Florent Krzakala, Pierfrancesco Urbani, and Lenka Zdeborová. Marvels and pitfalls of the langevin algorithm in noisy high-dimensional inference. *Physical Review X*, 10(1):011057, 2020.

[30] Paul Cecil Martin, ED Siggia, and HA Rose. Statistical dynamics of classical systems. *Physical Review A*, 8(1):423, 1973.

[31] C De Dominicis. Dynamics as a substitute for replicas in systems with quenched random impurities. *Physical Review B*, 18(9):4913, 1978.

[32] Andrea Crisanti and H-J Sommers. The sphericalp-spin interaction spin glass model: the statics. *Zeitschrift für Physik B Condensed Matter*, 87(3):341–354, 1992.

[33] Stefano Sarao Mannelli, Giulio Biroli, Chiara Cammarota, Florent Krzakala, Pierfrancesco Urbani, and Lenka Zdeborová. Complex dynamics in simple neural networks: Understanding gradient flow in phase retrieval. In *2020 Conference on Neural Information Processing Systems-NeurIPS 2020*, 2020.

[34] Leticia F Cugliandolo and Jorge Kurchan. Analytical solution of the off-equilibrium dynamics of a long-range spin-glass model. *Physical Review Letters*, 71(1):173, 1993.

[35] Andrea Crisanti and Luca Leuzzi. Spherical 2+ p spin-glass model: An analytically solvable model with a glass-to-glass transition. *Physical Review B*, 73(1):014412, 2006.

[36] Antonio Auffinger, Gérard Ben Arous, and Jiří Černỳ. Random matrices and complexity of spin glasses. *Communications on Pure and Applied Mathematics*, 66(2):165–201, 2013.

[37] Giampaolo Folena, Silvio Franz, and Federico Ricci-Tersenghi. Gradient descent dynamics in the mixed p-spin spherical model: finite size simulation and comparison with mean-field integration. *arXiv preprint arXiv:2007.07776*, 2020.

[38] Stefano Sarao Mannelli, Florent Krzakala, Pierfrancesco Urbani, and Lenka Zdeborová. Passed & spurious: Descent algorithms and local minima in spiked matrix-tensor models. In *International Conference on Machine Learning*, pages 4333–4342, 2019.

[39] Guilhem Semerjian, Leticia F Cugliandolo, and Andrea Montanari. On the stochastic dynamics of disordered spin models. *Journal of statistical physics*, 115(1):493–530, 2004.

[40] Florent Krzakala and Lenka Zdeborová. Performance of simulated annealing in p-spin glasses. In *Journal of Physics: Conference Series*, volume 473, page 012022. IOP Publishing, 2013.

[41] Marc Mézard, Giorgio Parisi, and Miguel Angel Virasoro. *Spin glass theory and beyond: An Introduction to the Replica Method and Its Applications*, volume 9. World Scientific Publishing Company, 1987.

[42] Gérard Ben Arous, Amir Dembo, and Alice Guionnet. Cugliandolo-Kurchan equations for dynamics of spin-glasses. *Probability theory and related fields*, 136(4):619–660, 2006.

[43] Amir Dembo and Eliran Subag. Dynamics for spherical spin glasses: disorder dependent initial conditions. *Journal of Statistical Physics*, pages 1–50, 2020.

[44] Francesca Mignacco, Florent Krzakala, Pierfrancesco Urbani, and Lenka Zdeborová. Dynamical mean-field theory for stochastic gradient descent in gaussian mixture classification. In *2020 Conference on Neural Information Processing Systems-NeurIPS 2020*, 2020.

[45] Haim Sompolinsky, Andrea Crisanti, and Hans-Jurgen Sommers. Chaos in random neural networks. *Physical review letters*, 61(3):259, 1988.

[46] Francesca Mastrogiuseppe and Srdjan Ostojic. Intrinsically-generated fluctuating activity in excitatory-inhibitory networks. *PLoS computational biology*, 13(4):e1005498, 2017.

[47] Tankut Can, Kamesh Krishnamurthy, and David J Schwab. Gating creates slow modes and controls phase-space complexity in grus and lstms. In *Mathematical and Scientific Machine Learning*, pages 476–511. PMLR, 2020.

[48] Ning Qian. On the momentum term in gradient descent learning algorithms. *Neural networks*, 12(1):145–151, 1999.

[49] Leticia F Cugliandolo, Gustavo S Lozano, and Emilio N Nessi. Non equilibrium dynamics of isolated disordered systems: the classical hamiltonian p-spin model. *Journal of Statistical Mechanics: Theory and Experiment*, 2017(8):083301, 2017.

[50] Andrea Crisanti, Heinz Horner, and H-J Sommers. The sphericalp-spin interaction spin-glass model. *Zeitschrift für Physik B Condensed Matter*, 92(2):257–271, 1993.

[51] Stefano Sarao Mannelli, Giulio Biroli, Chiara Cammarota, Florent Krzakala, and Lenka Zde-borová. Who is afraid of big bad minima? analysis of gradient-flow in spiked matrix-tensor models. In *Advances in Neural Information Processing Systems*, pages 8679–8689, 2019.