ADVERSARIAL ROBUSTNESS AGAINST MULTIPLE l_p-THREAT MODELS AT THE PRICE OF ONE AND HOW TO QUICKLY FINE-TUNE ROBUST MODELS TO ANOTHER THREAT MODEL

ABSTRACT

Adversarial training (AT) in order to achieve adversarial robustness wrt single l_p-threat models has been discussed extensively. However, for safety-critical systems adversarial robustness should be achieved wrt all l_p-threat models simultaneously. In this paper we develop a simple and efficient training scheme to achieve adversarial robustness against the union of l_p-threat models. Our novel E-AT scheme is based on geometric considerations of the different l_p-balls and costs as much as normal adversarial training against a single l_p-threat model. Moreover, we show that using our E-AT scheme one can fine-tune with just 3 epochs *any* l_p-robust model (for $p \in \{1, 2, \infty\}$) and achieve multiple norm adversarial robustness. In this way we boost the state-of-the-art for multiple-norm robustness to more than 51% on CIFAR-10 and report up to our knowledge the first ImageNet models with multiple norm robustness. Moreover, we study the general transfer of adversarial robustness between different threat models and in this way boost the previous SOTA l_1-robustness on CIFAR-10 by almost 10%.

1 INTRODUCTION

The problem of adversarial examples, that is small adversarial perturbations of the input (Szegedy et al., 2014; Kurakin et al., 2017) changing the decision of a classifier, is a serious obstacle for the use of machine learning in safety-critical systems. Many adversarial defenses have been proposed but most of them could be broken either by stronger attacks with a higher computational budget (Carlini & Wagner, 2017; Athalye et al., 2018; Mosbach et al., 2018) or using adaptive attacks (Tramèr et al., 2020). Apart from provable adversarial defenses which are however still restricted to rather simple CNNs (Wong et al., 2018; Gowal et al., 2018), the only successful technique so far remains adversarial training (Madry et al., 2018) and its improvements (Zhang et al., 2019; Carmon et al., 2019; Wu et al., 2020; 2021). We refer to Gowal et al. (2020) for a recent overview of "tricks of the trade" for improving adversarial training yielding the currently most robust models for l_2 and l_∞ on CIFAR-10. While the community initially focused on adversarial examples for l_∞-perturbations, there has been recently more interest in other l_p-attacks, such as l_1 and l_2, or perceptual threat models (Stutz et al., 2019; Wong & Kolter, 2021; Laidlaw et al., 2021). It is well known that robustness in one l_p-ball does not necessarily generalize to some other l_q-ball for $p \neq q$ (Kang et al., 2019; Tramèr & Boneh, 2019). However, in safety-critical systems we need robustness against all l_p-norms simultaneously which has triggered recent extensions of adversarial training for multiple l_p-norms (Tramèr & Boneh, 2019; Maini et al., 2020) and provable defenses for all l_p with $p \geq 1$ (Croce & Hein, 2020b).

In this paper we show that, using the geometry of the l_p-balls, the computationally expensive multiple norm training procedures of Tramèr & Boneh (2019); Maini et al. (2020), which cost up to three times as much as normal adversarial training, can be replaced by a very effective and simple form of adaptively alternating between the two extreme norms, namely l_1 and l_∞. This simple scheme achieves similar robustness for the union of the threat models as more costly previous approaches. Moreover, we show that already 3 epochs of fine-tuning with our extreme norms adversarial training (E-AT) are enough to turn any l_p-robust model for $p \in \{1, 2, \infty\}$ into a model which is robust

Figure 1: We fine-tune for 3 epochs the WideResNet-70-16 on CIFAR-10 from Gowal et al. (2020) with highest l_∞-robustness to be either robust wrt l_1 (left) or with our E-AT to be robust wrt to the union of the l_∞-, l_2-, and l_1-threat models (right). We achieve state-of-the-art results in both threat models. The plots show the robust accuracy in the individual threat models and in their union for the initial l_∞-robust classifier (middle) and the fine-tuned ones, with the target threat model highlighted.

against all l_p-threat models for $p \in \{1, 2, \infty\}$, even if the original classifier was completely non-robust against one of the threat models. We apply the proposed method to many existing models originally trained to be robust in a single norm: fine-tuning the currently most robust network in the l_∞-threat model from Gowal et al. (2020) for CIFAR-10 we improve the current state-of-the-art performance for multiple norm robustness by more than 6% (robustness over the union of l_1, l_2 and l_∞-balls). Moreover, we employ our E-AT fine-tuning scheme with just a single epoch to yield the first ImageNet model which is robust against multiple attacks at the same time. Finally, we show that fine-tuning with just *3 epochs* for CIFAR-10 and *one epoch* for ImageNet is sufficient to transfer robustness from one threat model to another one which very quickly yields baselines for all threat models. In this way we achieve SOTA l_1-robustness on CIFAR-10 by fine-tuning the most robust l_∞-model from Gowal et al. (2020) to become l_1-robust, and get an ImageNet model robust wrt l_1. These results are quite striking as the original classifiers show no or only very little l_1-robustness. Fig. 1 summarizes the results of robust fine-tuning on CIFAR-10 (see Table 2 and 4 for details).

2 RELATED WORK

Adversarial training: In image classification adversarial examples were first described by Szegedy et al. (2014) even though earlier discussion of adversarial examples in email spam classification can be found in Dalvi et al. (2004); Lowd & Meek (2005). An early approach of adversarial training was the Fast Gradient Sign Method (FGSM) (Goodfellow et al., 2015), which then was extended to a multi-step attack in Kurakin et al. (2017). Nowadays, adversarial training as formulated in Madry et al. (2018) as a min-max optimization problem has been one of the few adversarial defenses which could not be broken by stronger attacks (Athalye et al., 2018). Other types of defenses use more sophisticated techniques, typically preventing the direct optimization of the attack. However, adaptive attacks specifically designed for these defenses have often shown that these alternative techniques are non-robust or much less robust than claimed (Tramèr et al., 2020). Thus adversarial training remains the only general method ensuring adversarial robustness across architectures and datasets. Recent improvements have been achieved by using different objectives (Zhang et al., 2019), unlabeled data (Carmon et al., 2019), adversarial weights perturbations (Wu et al., 2020) and wider networks Wu et al. (2021). In Gowal et al. (2020) several recent variants were systematically explored and for a very large architecture, a WideResNet-70-16, they obtain the most robust models for l_∞ (radius $\frac{8}{255}$) and l_2 (radius 0.5) for CIFAR-10, which we use for our fine-tuning experiments.

Multiple norm robustness: It was early on discovered that adversarial robustness against a specific l_p threat model does typically not transfer to l_q threat models for $p \neq q$ (see Kang et al. (2019); Tramèr & Boneh (2019) for extensive studies). On the other hand to achieve really reliable machine learning models l_p-robustness wrt all p is necessary. The first approach to such a generally robust model was done in Schott et al. (2019) which uses multiple variational auto-encoders for an analysis by synthesis (ABS) architecture. While this model is restricted to MNIST, it is robust against l_0, l_2 and l_∞-attacks. However, it has been recently shown that with a stronger black-box attack (Croce et al., 2020b) the l_0-robustness is significantly lower than originally claimed. Tramèr & Boneh (2019); Maini et al. (2020); Madaan et al. (2021) use variants of adversarial training to

achieve robustness in multiple norms. Since these are the most similar methods to ours, we present them in detail below. Madaan et al. (2021) additionally proposes a meta-learning approach where one learns optimal noise to augment the samples and uses consistency regularization to enforce similar predictions on clean, augmented and adversarial samples. Finally, Stutz et al. (2020) combine adversarial training with a reject option for the classifier by down-weighting the confidence of adversarial samples. Their models generalize to other threat models but the comparison to normal adversarially trained models is difficult as their model is non-robust without the reject option.

Provable robustness: In the area of provably robust defenses, Croce & Hein (2020b) motivated a regularization approach based on the geometry of the l_p-balls which enforces multiple-norm robustness during training which allows then to derive provable guarantees for multiple-norm robustness in contrast to the empirical evaluation of adversarial training. However, their approach works only for small network architectures and relatively small radii of the l_p-balls.

Fine-tuning of robust models: Fine-tuning of an existing neural network is a commonly used technique in deep learning (Goodfellow et al., 2016) to quickly adapt an existing model to a different objective e.g. for language models (Howard & Ruder, 2018). More recently, it has been shown in the area of adversarial robustness that fine-tuning of pre-trained models, possibly using self-supervision, yields better adversarial robustness (Hendrycks et al., 2019; Chen et al., 2020; Xu & Yang, 2020). In Jeddi et al. (2020) it is shown that fine-tuning of non-robust models with 10 epochs can yield robust models with the caveat that their robustness evaluation is done using only a single run of PGD with 20 steps. We are not aware of any prior work discussing fine-tuning to transform an existing robust model wrt a single l_p into a robust model wrt multiple threat models or wrt another l_q-threat model. In particular, we show that one can fine-tune an l_∞-robust model so that it becomes l_1-robust even though the original model has not been l_1-robust at all.

Evaluation of adversarial robustness: Many white-box attacks for l_∞ (Madry et al., 2018; Gowal et al., 2019), l_2 (Madry et al., 2018; Carlini & Wagner, 2017) and l_1 (Chen et al., 2018; Modas et al., 2019; Rony et al., 2021) have been proposed as well as several black box attacks (Brendel et al., 2018; Liu et al., 2019; Cheng et al., 2019; Al-Dujaili & O'Reilly, 2020; Meunier et al., 2019; Zhao et al., 2019; Andriushchenko et al., 2020) for different threat models. It has recently been shown that AutoAttack (Croce & Hein, 2020c), a parameter-free ensemble of the white-box attacks APGD for the cross-entropy and DLR-loss, FAB-attack (Croce & Hein, 2020a) and the black-box Square-attack (Andriushchenko et al., 2020) is reliably evaluating adversarial robustness for l_2 and l_∞. AutoAttack has recently been extended to l_1 (Croce & Hein, 2021) outperforming all existing state-of-the art attacks for l_1. Croce & Hein (2020c; 2021) showed that on models defended with adversarial training the two versions of APGD (with budget as in AutoAttack) already give an accurate robustness evaluation. As we have to evaluate very large models always for three threat models, we use those as a strong standard attack in our experiments.

2.1 ADVERSARIAL TRAINING FOR THE UNION OF l_1-, l_2- AND l_∞-BALLS

Let us denote by $f_\theta : \mathbb{R}^d \to \mathbb{R}^K$ the classifier parameterized by $\theta \in \mathbb{R}^n$, with input $x \in \mathbb{R}^d$ and $f_\theta(x) \in \mathbb{R}^K$ where K is the number of classes of the task. Let further $\mathcal{D} = \{(x_i, y_i)\}_i$ be the training set, with y_i the correct label of x_i, and $\mathcal{L} : \mathbb{R}^K \times \mathbb{R}^K \to \mathbb{R}$ a given loss function. The aim is to enforce adversarial robustness in all multiple l_p-balls simultaneously, i.e., defining $B_p(\epsilon_p) = \{x \in \mathbb{R}^d : \|x\|_p \le \epsilon_p\}$, the threat model is the union of the individual l_p-balls

$$\Delta = B_1(\epsilon_1) \cup B_2(\epsilon) \cup B_\infty(\epsilon_\infty),$$

which is a non convex set, since in practice the ϵ_p are chosen such that no l_p-ball contains any of the others. In adversarial training the worst case loss for input perturbation in the threat model, $\max_{\delta \in \Delta} \mathcal{L}(f_\theta(x_i + \delta), y_i)$, is minimized. Efficiently maximizing the loss $\mathcal{L}$ in the union of threat models is non-trivial and different approaches to extend adversarial training to this setting have been proposed. They basically differ in the way how the inner maximization problem is tackled.

MAX: Tramèr & Boneh (2019) suggest to run the three attacks for each $B_p(\epsilon_p)$ for $p \in \{1, 2, \infty\}$ independently and then use the one which realizes the highest loss, that is

$$\max_{\delta \in \Delta} \mathcal{L}(f_\theta(x_i + \delta), y_i) = \max_{p \in \{1,2,\infty\}} \max_{\delta \in B_p(\epsilon_p)} \mathcal{L}(f_\theta(x_i + \delta), y_i).$$

This training optimizes directly the worst case in the union but comes at the price of being nearly three times as expensive as normal adversarial training wrt a single l_p-ball.

AVG: In their AVG alternative Tramèr & Boneh (2019) suggest to run the three attacks for each $B_p(\epsilon_p)$ for $p \in \{1, 2, \infty\}$ independently but replace the inner maximization problem with

$$\sum_{p \in \{1,2,\infty\}} \max_{\delta \in B_p(\epsilon_p)} \mathcal{L}(f_\theta(x_i + \delta), y_i),$$

and thus one basically averages the updates of all l_p-balls with the motivation of not "wasting" the computed attacks, in particular when the attained loss values are rather similar and thus the max is ambiguous. Again this costs three times as much as normal adversarial training.

MSD: Maini et al. (2020) argue that the correct way to maximize the loss in the union is to test during the PGD attacks all the three steepest ascent updates corresponding to the three norms (sign of the gradient for l_∞, normalized gradient for l_2 and a smoothed l_1-step by using the top-k components in magnitude of the gradient) and then take the step which yields the highest loss. Maini et al. (2020) report that MSD outperforms both AVG and MAX, also in terms of a more stable training. As all three updates (forward passes) are tested but only one backward pass is needed (gradient is the same) this costs roughly two times as much as normal adversarial training.

SAT: Madaan et al. (2021) introduce Stochastic Adversarial Training (SAT) which randomly samples $p \in \{1, 2, \infty\}$ for each batch and performs PGD only for the corresponding l_p-norm. While SAT has the same cost as standard adversarial training, Madaan et al. (2021) report that it does not perform very well.

3 Fast multiple-norm robustness via extreme norms adversarial training and fine-tuning

All previous methods assume that for achieving robustness to multiple norms each of the threat models has to be used at training time. In the following we first present an argument, using recent results from Croce & Hein (2020b), showing that this is not the case. Based on this analysis we introduce our extreme norms adversarial training (E-AT) which achieves multiple norm robustness at the same price as training for a single norm threat model. Finally, we show that only a few epochs of fine-tuning with E-AT turns a model robust wrt a single norm into one which has competitive robustness wrt multiple norms.

3.1 Geometry of the union of l_p-balls and their convex hull

The main insight we use for E-AT is that a linear classifier which is robust in both an l_1- and an l_∞-ball is also robust wrt the largest l_p-ball for $1 \leq p \leq \infty$ which fits into the convex hull of the union of the l_1- and l_∞-ball. This ball is significantly larger than the largest l_p-ball contained into the union of the l_1- and l_∞-ball (see Fig. 2). Thus it is sufficient to be robust wrt the two "extreme" norms l_1 and l_∞ to ensure robustness. While this is exact for affine classifiers, we conjecture that for neural networks this will at least hold approximately true (note that typical ReLU-networks yield piecewise affine classifiers (Arora et al., 2018)) and for the model it is the most efficient way in terms of capacity to be l_1- and l_∞-robust.

We now state the main results from Croce & Hein (2020b) which are the basis for our E-AT. We work in the non-trivial setting, where the balls are not included in each other, that is $B_1(\epsilon_1) \not\subseteq B_\infty(\epsilon_\infty)$ and $B_\infty(\epsilon_\infty) \not\subseteq B_1(\epsilon_1)$ as otherwise the problem of enforcing multiple norms (including l_1 or l_∞) robustness boils down again to single norm robustness. In order to be in this non-trivial setting it has to hold $\epsilon_1 \in (\epsilon_\infty, d\epsilon_\infty)$. For $\epsilon_\infty = \frac{8}{255}$ and dimension $d = 3072$ as in CIFAR-10 this yields an upper bound $\epsilon_1 \leq 96.38$ which is far higher than what has been used for l_1-threat models (we use $\epsilon_1 = 12$ for CIFAR-10). We denote by $U_{1,\infty}(\epsilon_1, \epsilon_\infty) = B_1(\epsilon_1) \cup B_\infty(\epsilon_\infty)$ the union of the l_1- and l_∞-balls. One can then ask the obvious question: how much l_p-robustness do I get for $1 < p < \infty$ from a classifier robust in $U_{1,\infty}(\epsilon_1, \epsilon_\infty)$? This question is answered in the following result:

Proposition 3.1 (Croce & Hein (2020b)) *If $d \geq 2$ and $\epsilon_1 \in (\epsilon_\infty, d\epsilon_\infty)$, then*

$$\min_{x \in \mathbb{R}^d \setminus U_{1,\infty}(\epsilon_1, \epsilon_\infty)} \|x\|_p = \left(\epsilon_\infty^p + \frac{(\epsilon_1 - \epsilon_\infty)^p}{(d-1)^{p-1}} \right)^{\frac{1}{p}}. \tag{1}$$

Figure 2: Visualization of the l_2-ball contained in the union resp. the convex hull of the union of l_1- and l_∞-balls in $\mathbb{R}^2$. **First:** co-centric l_1-ball (blue) and l_∞-ball (black). **Second:** in red the largest l_2-ball contained in the union of l_1- and l_∞-ball. **Third:** in green the convex hull of the union of the l_1- and l_∞-ball. **Fourth:** the largest l_2-ball (red) contained in the convex hull. The l_2-ball contained in the convex hull is significantly larger than that in the union of l_1- and l_∞-ball.

Thus a classifier which is robust for the union $U_{1,\infty}(\epsilon_1, \epsilon_\infty)$ has automatically a non-trivial robustness for all intermediate l_p-norms. For us the case $p = 2$ is most interesting which given that $\epsilon_1 \gg \epsilon_\infty$ can be tightly upper bounded as

$$\epsilon_2 := \min_{x \in \mathbb{R}^d \setminus U_{1,\infty}(\epsilon_1, \epsilon_\infty)} \|x\|_2 \leq \sqrt{\epsilon_\infty^2 + \frac{\epsilon_1^2}{d-1}}. \tag{2}$$

For the case of CIFAR-10 where $d = 3072$ and $\epsilon_1 = 12$ and $\epsilon_\infty = \frac{8}{255}$ as chosen in Maini et al. (2020) one gets $\epsilon_2 \leq 0.2188$. As the radius of the l_2-threat model in Maini et al. (2020) is chosen as $\epsilon_2 = 0.5$, robustness in the union alone would not be sufficient to achieve the desired robustness wrt l_p for $p \in \{1, 2, \infty\}$. But the above point of view is the worst case. In the following we see that if we consider affine classifiers then a guarantee for $B_1(\epsilon_1)$ *and* $B_\infty(\epsilon_\infty)$ implies a guarantee with respect to the convex hull C of their union $B_1(\epsilon_1) \cup B_\infty(\epsilon_\infty)$ as an affine classifier generates a half-space and thus only the extreme points of $B_1(\epsilon_1)$ resp. $B_\infty(\epsilon_\infty)$ matter (see Figure 2 for illustrations of B_1, B_∞, their union and their convex hull).

Theorem 3.1 (Croce & Hein (2020b)) *Let C be the convex hull of $B_1(\epsilon_1) \cup B_\infty(\epsilon_\infty)$. If $d \geq 2$ and $\epsilon_1 \in (\epsilon_\infty, d\epsilon_\infty)$, then*

$$\min_{x \in \mathbb{R}^d \setminus C} \|x\|_p = \frac{\epsilon_1}{\left(\epsilon_1/\epsilon_\infty - \alpha + \alpha^q\right)^{1/q}}, \tag{3}$$

where $\alpha = \frac{\epsilon_1}{\epsilon_\infty} - \lfloor \frac{\epsilon_1}{\epsilon_\infty} \rfloor$ and $\frac{1}{p} + \frac{1}{q} = 1$.

As standard architectures using ReLU activation function yield a piecewise affine classifier one can anticipate that this result gives at least a rule of thumb on the expected l_p-robustness when one is l_1- and l_∞-robust. Again with the choice of $\epsilon_1, \epsilon_\infty$ from above one gets for the radius of the l_2-ball that fits into the convex hull C of the union of $B_1(\epsilon_1)$ and $B_\infty(\epsilon_\infty)$:

$$\epsilon_2 := \min_{x \in \mathbb{R}^d \setminus C} \|x\|_2 = \frac{\epsilon_1}{\sqrt{\epsilon_1/\epsilon_\infty - \alpha + \alpha^2}} \approx 0.6178. \tag{4}$$

Thus for a desired l_2-robustness with radius less than 0.6178 it is sufficient for an affine classifier, and at least plausible for a ReLU network, to enforce l_1-robustness with $\epsilon_1 = 12$ and l_∞-robustness with $\epsilon_\infty = \frac{8}{255}$. This motivates our extreme norms adversarial training (E-AT) and fine-tuning.

3.2 Extreme norms adversarial training (E-AT)

In light of the geometrical argument presented in the previous section, we propose to train only on adversarial perturbations for the l_∞- and l_1-threat models if the l_2-radius obtained from Theorem 3.1 is larger than the radius ϵ_2 of the l_2-threat model. In this case it is sufficient to just train for the extremes l_1 and l_∞ in order to achieve robustness also to the intermediate l_p-attacks with $p \in (1, \infty)$. Since we seek a method as expensive as standard adversarial training, for each batch we do either the l_1- or the l_∞-attack. For full training from a random initialization simply alternating or sampling

Table 1: **CIFAR-10 - Comparison of different full training schemes:** We train WideResNet-28-10 with TRADES-XENT loss (except for MNG-AC which we use as originally proposed) for each scheme (repeated for 3 seeds), and report the robust accuracy wrt l_∞, l_2, l_1 and the union of the threat models. Moreover, we show the clean accuracy and the time per epoch of training.

method	clean	l_∞ ($\epsilon_\infty = \frac{8}{255}$)	l_2 ($\epsilon_2 = 0.5$)	l_1 ($\epsilon_1 = 12$)	union	time/epoch
l_∞-AT	82.6 ± 0.52	52.0 ± 0.70	59.7 ± 0.22	9.1 ± 0.22	9.1 ± 0.22	922 s
l_2-AT	88.2 ± 0.37	35.9 ± 0.17	70.9 ± 0.39	36.1 ± 0.25	31.3 ± 0.17	928 s
l_1-AT	83.7 ± 0.16	30.7 ± 0.74	65.1 ± 0.50	61.6 ± 0.34	30.7 ± 0.74	949 s
SAT	80.5 ± 0.57	45.9 ± 0.46	66.7 ± 0.29	55.9 ± 0.49	45.7 ± 0.62	925 s
MNG-AC	81.3 ± 0.33	43.5 ± 0.66	66.9 ± 0.22	57.6 ± 0.84	43.3 ± 0.70	1500 s
AVG	82.5 ± 0.41	45.4 ± 1.11	68.0 ± 0.87	55.0 ± 0.25	45.1 ± 1.06	2771 s
MAX	79.9 ± 0.14	48.4 ± 0.74	65.3 ± 0.29	50.2 ± 0.59	47.4 ± 0.77	2479 s
MSD	80.6 ± 0.33	48.0 ± 0.19	65.6 ± 0.33	51.7 ± 0.39	46.9 ± 0.09	1554 s
E-AT unif.	79.7 ± 0.17	45.4 ± 0.50	66.0 ± 0.46	55.6 ± 0.54	45.1 ± 0.65	939 s
E-AT	79.9 ± 0.69	46.6 ± 0.24	66.2 ± 0.61	56.0 ± 0.37	46.4 ± 0.28	921 s

uniformly at random from the l_1- and l_∞-attack, works already well. However, for very quick fine-tuning, e.g. just one epoch in the case of ImageNet, for multiple norm robustness from an existing classifier robust wrt a single threat model, one has to take into account the existing robustness of the model. Thus we use an adaptive sampling strategy based on the running averages, reset at every epoch, of the robust training errors rerr$_1$ and rerr$_\infty$ (note that these running averages are computed just from averaging the robust error on the batches where the respective attack has been performed, thus no extra attacks are necessary), such that the probability for sampling the l_p-threat model is

$$\frac{\text{rerr}_p}{\text{rerr}_1 + \text{rerr}_\infty}, \quad \text{for } p \in \{1, \infty\}. \tag{5}$$

The motivation for this sampling scheme is that the robust error in the union Δ is mainly influenced by the worst threat model. We show the effect of the biased sampling in E-AT fine-tuning in Sec. C.3. The next section shows that E-AT is a very competitive baseline compared to the significantly more involved and up to three times more expensive training schemes discussed in Sec. 2.1.

3.3 MULTIPLE NORM ROBUSTNESS FROM RANDOM INITIALIZATION

In this experiment on CIFAR-10 we evaluate the performance of the different adversarial training variants to achieve adversarial robustness wrt the union of the l_∞, l_2 and l_1-threat models where we use the standard radii $\epsilon_1 = 12$, $\epsilon_2 = 0.5$ and $\epsilon_\infty = \frac{8}{255}$. As baselines we report the l_p-robustness of models specifically trained for only a single norm: l_1-AT, l_2-AT and l_∞-AT. We train WideResNet-28-10 (Zagoruyko & Komodakis, 2016) with the TRADES-XENT loss since Gowal et al. (2020) show that this yields slightly higher robustness than standard TRADES (Zhang et al., 2019) without additional data (see Sec. A for more details). For l_p-AT, SAT and E-AT we use APGD (Croce & Hein, 2020c) for training, while for AVG, MAX and MSD we use standard PGD for l_2, l_∞ and SLIDE (Tramèr & Boneh, 2019) for l_1-PGD, even though we have observed no strong difference for multiple norms training compared to APGD. However, note that for MSD we do not use the l_1-PGD variant suggested by Maini et al. (2020) as this resulted in significantly worse performance (worse than all other methods). For MNG-AC (Madaan et al., 2021) we use the original code (with the ϵ_1 we consider here and rescaled step size). Finally, we show also the performance of E-AT using a uniformly random sampling scheme (named E-AT unif.) for selecting the l_p-attack to use for each batch rather than the biased one presented in Eq. (5).

In the results in Table 1 we can see that the models we retrained using MSD and MAX perform best with 46.9% and 47.4% adversarial robustness in the union, but our E-AT attains very close results with 46.4% (within the range of standard deviation) with $1.7\times$ and $2.7\times$ faster runtime per epoch. Given that a pure l_∞-training yields 52.0% l_∞-robustness which turns out to be the most difficult norm, it is quite remarkable that multiple-norm robustness can be achieved with a relatively minor loss. The other variants SAT, MNG-AT, AVG and E-AT unif. perform worse with higher or similar computational cost to E-AT. Note that E-AT unif. performs similarly to SAT (which also samples uniformly the l_p-attack for each batch) in every threat model without seeing l_2-attacks at training

Table 2: **CIFAR-10 - 3 epochs of E-AT fine-tuning on l_p-robust models:** We use E-AT to fine-tune models robust wrt a single l_p-norm for multiple-norm robustness, and report the robust accuracy on 1000 test points for all threat models, and the difference compared to the initial classifier. (*) indicates that additional data is used.

model		clean		l_∞ ($\epsilon_\infty = \frac{8}{255}$)		l_2 ($\epsilon_2 = 0.5$)		l_1 ($\epsilon_1 = 12$)		union	
Fine-tuning l_∞-robust models											
RN-50 - l_∞		88.7		50.9		59.4		5.0		5.0	
(Engstrom et al., 2019) + FT		86.2	-2.5	46.0	-4.9	70.1	10.7	49.2	44.2	43.4	38.4
WRN-34-20 - l_∞		87.2		56.6		63.7		8.5		8.5	
(Gowal et al., 2020) + FT		88.3	1.1	49.3	-7.3	71.8	8.1	51.2	42.7	46.2	37.7
WRN-28-10 - l_∞ (*)		90.3		59.1		65.7		8.0		8.0	
(Carmon et al., 2019) + FT		90.3	0.0	52.6	-6.5	74.7	9.0	54.0	46.0	48.7	40.7
WRN-28-10 - l_∞ (*)		89.9		62.9		67.2		10.8		10.8	
(Gowal et al., 2020) + FT		91.2	1.3	53.9	-9.0	76.0	8.8	56.9	46.1	50.1	39.3
WRN-70-16 - l_∞ (*)		90.7		65.6		66.9		8.1		8.1	
(Gowal et al., 2020) + FT		91.6	0.9	54.3	-11.3	78.2	11.3	58.3	50.2	51.2	43.1
Fine-tuning l_2-robust models											
RN-50 - l_2		91.5		29.7		70.3		27.0		23.0	
(Engstrom et al., 2019) + FT		87.8	-3.7	43.1	13.4	70.8	0.5	50.2	23.2	41.7	18.7
RN-50 - l_2 (*)		91.1		37.7		73.4		31.2		28.8	
(Augustin et al., 2020) + FT		87.0	-4.1	47.2	9.5	70.4	-3.0	54.1	22.9	46.0	17.2
WRN-70-16 - l_2 (*)		94.1		43.1		81.7		34.6		32.4	
(Gowal et al., 2020) + FT		91.2	-2.9	51.9	8.8	79.2	-2.5	58.8	24.2	49.7	17.3
Fine-tuning l_1-robust models											
RN-18 - l_1		87.1		22.0		64.8		60.3		22.0	
(Croce & Hein, 2021) + FT		83.5	-3.6	40.3	18.3	68.1	3.3	55.7	-4.6	40.1	18.1

time. Thus E-AT provides a very efficient and effective alternative to MSD and MAX which allows to scale adversarial training for multiple norms to larger problems such as ImageNet. We repeat the comparison with the same setup but on the smaller PreAct ResNet-18 (He et al., 2016) in Sec. B.3 with standard adversarial training on the cross-entropy loss and obtain similar results. Thus, E-AT generalizes across architectures and training schemes. Finally, we observe how almost all methods for multiple norms lead to a drop of clean accuracy compared to the single norm l_p-AT, showing that the threat model of the union is significantly more challenging.

3.4 MULTIPLE-NORM ROBUSTNESS VIA FAST FINE-TUNING OF EXISTING ROBUST MODELS

In the previous section, we have shown that training for only the two extreme threat models is sufficient to achieve robustness wrt all three norms. Prior works (Tramèr & Boneh, 2019; Kang et al., 2019) observed that models adversarially trained wrt l_∞ give non trivial robustness to l_2-attacks, although lower than what one gets directly training against such attacks, and vice versa. This is confirmed by our evaluation of the models in Table 1 (top part), where we also notice that l_1-AT provides good robust accuracy in l_2. On the other hand, training for l_∞ resp. l_1 does not yield particular robustness to the dual norm, which is reasonable since the perturbations generated in the two threat models are very different, while l_2 can be seen as an intermediate case which can defend at least partially against l_∞- and l_1-attacks. Therefore, we propose to use models trained for robustness wrt a single norm as good initializations to achieve, within a small computational budget, multiple norms robustness. This is done by fine-tuning pretrained models with our E-AT for 3 epochs when using CIFAR-10 and 1 epoch with ImageNet-1k, starting with learning rate 0.05 or 0.01, depending on the model, and decreasing by a factor of 10 at each epoch. We do 10 steps of APGD in adversarial training for CIFAR-10, while 5 and 15 with l_∞ and l_1 respectively on ImageNet since optimizing in

Table 3: **ImageNet - Results of one epoch of E-AT fine-tuning of existing robust models:** We use existing models trained to be robust wrt a single l_p-ball (either l_∞ or l_2) from Engstrom et al. (2019) and fine-tune them for a single epoch with our E-AT scheme.

model	clean		l_∞ ($\epsilon_\infty = \frac{4}{255}$)		l_2 ($\epsilon_2 = 2$)		l_1 ($\epsilon_1 = 255$)		union	
RN-50 - l_∞	62.9		29.8		17.7		0.0		0.0	
(Engstrom et al., 2019) + FT	58.0	-4.9	27.3	-2.5	41.1	23.4	24.0	24.0	21.7	21.7
RN-50 - l_2	58.7		25.0		40.5		14.0		13.5	
(Engstrom et al., 2019) + FT	56.7	-2.0	26.7	1.7	41.0	0.5	25.4	11.4	23.1	9.6

the l_1-ball requires more iterations in that case. When the model was originally trained with extra data beyond the training set on CIFAR-10, we use the 500k images introduced by Carmon et al. (2019) as additional data for fine-tuning (see also Sec. A).

CIFAR-10: RobustBench (Croce et al., 2020a) provides a collection of the currently most robust classifiers. We took the most robust models, among those which do not use synthetic data, for l_2- and l_∞-norm and the l_1-robust one from Croce & Hein (2021) (all are trained with the same radii ϵ_p as in our experiment). Each of them is fine-tuned for 3 epochs with E-AT where ($*$) denotes models trained using extra data, which also means that we used the extra data from Carmon et al. (2019) for fine-tuning (Gowal et al. (2020) have created their own extra data but which is not available). We present in Table 2 the results. First of all the fine-tuning works for all tested architectures and results in many cases in stronger robustness in the union than for the specifically trained WideResNet-28-10 models. In particular, the most robust l_∞-model from Gowal et al. (2020) with 65.6% l_∞-robustness and only 8.1% l_1-robustness can be fine-tuned to a multiple-norm robust model with 51.2% robustness which is up to our knowledge the best reported multiple-norm robustness. Very interesting is that the l_2-robustness of 78.2% is quite close to the 81.7% l_2-robustness of the specifically l_2-trained model from Gowal et al. (2020). Moreover, the l_1-robustness of 58.3% is close to the best reported one of 60.3% from Croce & Hein (2021) (however we improve this a lot in the next section) and the model has even higher clean accuracy. Clearly, this comes at the price of a significant loss in l_∞ but this is to be expected. Striking is that fine-tuning the l_2-robust model from Gowal et al. (2020) results in a very similar result. In a nutshell, E-AT fine-tuning of existing l_p-robust models yields very efficient and competitive baselines for future research in this area.

ImageNet: Similarly to CIFAR-10 we start with the specific l_2-resp. l_∞-robust models from Engstrom et al. (2019) which have been trained with $\epsilon_2 = 3$ and $\epsilon_\infty = \frac{4}{255}$. We use $\epsilon = 2$ for the experiments as the robust accuracy is still in a reasonable range of 40% and together with our choice of $\epsilon_1 = 255$ and $\epsilon_\infty = \frac{4}{255}$ the l_2-radius from Theorem 3.1 is almost exactly 2. We fine-tune the two models only for a single epoch and report the results in Table 3. Again, we note that our evaluation is stronger than the original one (although this is on a different number of data points) which effects in particular the l_∞-robustness. Note that the initial l_∞-model is completely non-robust for l_1 but achieves 24.0% l_1-robust accuracy and also the l_2-robust accuracy improves from 17.1% to 41.1% and this at the price of a relatively small loss in l_∞-robust and clean accuracy. For the l_2-robust model all robust accuracies improve as the original model was trained for $\epsilon = 3$. It yields the best multiple-norm robust accuracy of 23.1%. Up to our knowledge no multiple-norm robustness has been reported before for ImageNet and thus these results are an important baseline.

Additional experiments: Sec. C in the appendix contains further studies about E-AT fine-tuning: we show that fine-tuning a naturally trained model does not provide competitive robustness and leads to low clean accuracy. Moreover, we show the stability of the scheme over random seeds, and that increasing the number of epochs progressively improves the robustness in the union.

4 FINE-TUNING l_p-ROBUST MODELS TO BECOME l_q-ROBUST FOR $p \neq q$

Motivated by our results for the multiple-norm threat model we study to which extent we can fine-tune an l_p-robust model to a l_q-robust model with $p \neq q$. Again the emphasis is on an extremely short fine-tuning time so that this is much faster than full adversarial training.

Table 4: **Fine-tuning l_p-robust models to another threat model:** For each norm we fine-tune the most robust models wrt the other ones for 3 epochs for CIFAR-10 and 1 epoch for ImageNet and report clean and robust accuracy for all threat models. Even for the threat models where the robustness of the original model is low, the fine-tuning is sufficient to yield robustness almost at the same level of the specialized models with same architecture. For each threat model (column) we highlight in blue the model trained for the specific norm, in orange those only fine-tuned in the target norm. The values of the thresholds ϵ are the same used the multiple norms experiments.

CIFAR-10					**ImageNet**				
	clean	l_∞	l_2	l_1		clean	l_∞	l_2	l_1
WRN-70-16 (Gowal et al., 2020) - l_∞ (*)					RN-50 (Engstrom et al., 2019) - l_∞				
original	90.7	65.6	66.9	8.1	original	62.9	29.8	17.7	0.0
+ FT wrt l_2	92.8	47.4	80.0	34.0	+ FT wrt l_2	62.9	25.5	41.5	8.4
+ FT wrt l_1	92.4	33.9	74.7	**70.2**	+ FT wrt l_1	57.7	18.0	37.6	27.4
WRN-70-16 (Gowal et al., 2020) - l_2 (*)					RN-50 (Engstrom et al., 2019) - l_2				
original	94.1	43.1	81.7	34.6	original	58.7	25.0	40.5	14.0
+ FT wrt l_∞	92.3	58.5	73.5	11.4	+ FT wrt l_∞	59.1	31.5	40.1	7.5
+ FT wrt l_1	92.8	29.2	75.7	68.9	+ FT wrt l_1	56.8	18.0	37.1	**28.7**
RN-18 (Croce & Hein, 2021) - l_1									
original	87.1	22.0	64.8	60.3					
+ FT wrt l_∞	82.7	44.2	66.6	25.4					
+ FT wrt l_2	88.0	31.0	69.8	39.7					

CIFAR-10: We fine-tune for 3 epochs the most l_∞-robust model at $\epsilon_\infty = \frac{8}{255}$ of Gowal et al. (2020) with adversarial training wrt l_2 and l_1 with $\epsilon_2 = 0.5$ and $\epsilon_1 = 12$. Table 4 shows that fine-tuning for l_1-robustness yields 70.2% l_1-robust accuracy which is 9.9% more than the previously most robust model. Also we get a strikingly high l_2-robust accuracy for the l_2-fine-tuned model of 80.0% not far away from the 81.7% which ones gets by training for l_2 from scratch. Surprisingly, fine-tuning the l_2-robust model of Gowal et al. (2020) wrt l_1 does not outperform the l_1-robustness achieved by fine-tuning their l_∞-robust model. Interestingly, fine-tuning the l_1-robust PreAct ResNet-18 for l_2 yields a better l_2-robustness than l_2-training from scratch, see Table 5. Again this shows that fine-tuning of existing models is minimal effort and already provides strong baselines for adversarial robustness obtained by adversarial training from scratch and in some cases even outperforms them.

ImageNet: We fine-tune the l_2- and l_∞-robust models from Engstrom et al. (2019) to the other threat model respectively and wrt l_1. The results are in Table 4. The resulting classifiers are both more robust than the originally trained models from Engstrom et al. (2019): we get a l_2-robust accuracy of 41.5% which is 0.6% higher than the l_2-model and a l_∞-robust accuracy of 31.5% which is 1.7% better than the original l_∞-model. For both models it is possible to achieve within one epoch of fine-tuning a non-trivial robustness in l_1. In particular, notice that the model for l_∞ initially has 0.0% robustness wrt l_1, while after fine-tuning it achieves 27.4% robust accuracy which is similar to what obtained by fine-tuning the l_2-robust model for l_1 which yields 28.7%. Note that when we fine-tuned for multiple-norm robustness we got a l_1-robust accuracy of 21.7% resp. 23.1% (Table 3). Thus by fine-tuning specifically for l_1-robustness one gains 5.7% resp. 5.6% l_1-robust accuracy. Up to our knowledge our ImageNet models are the first ones for which l_1-robustness is reported.

5 CONCLUSION

Based on the geometry of the l_p-balls we have introduced E-AT, a novel training scheme for multiple norm robustness which achieves comparable adversarial robustness in the union while being significantly faster. We also show for the first time that fine-tuning can be used to transfer adversarial robustness from a single l_p-threat model to the multiple norms one, and that one can even obtain an l_q-robust classifier with a quick fine-tuning of an l_p-robust one with $p \neq q$. This yields strong baselines for future research. We have in this way generated models with SOTA performance for multiple-norm and l_1-robustness on CIFAR-10 and the first models on ImageNet which show significant multiple-norm as well as l_1-robustness.

ETHICS STATEMENT

There are no conflicts of interest in this work. As we consider the efficient training and fine-tuning of adversarially robust models, we think that this work contributes to more trustworthy AI systems and thus has rather positive implications.

REPRODUCIBILITY STATEMENT

We provide information about training in Sec. 2.1 and Sec. 4 of the main part, and add further details in Sec. A of the appendix. We provide in the supplementary material an implementation of our method in PyTorch. Note that most of the models used for fine-tuning are available in RobustBench, and the evaluation code is part of AutoAttack. We report for most of the experiments the mean and standard deviations over different random seeds, as well as the runtime and infrastructure used.

REFERENCES

Abdullah Al-Dujaili and Una-May O'Reilly. There are no bit parts for sign bits in black-box attacks. In *ICLR*, 2020.

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search. In *ECCV*, 2020.

Raman Arora, Amitabh Basu, Poorya Mianjy, and Anirbit Mukherjee. Understanding deep neural networks with rectified linear unit. In *ICLR*, 2018.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *ICML*, 2018.

Maximilian Augustin, Alexander Meinke, and Matthias Hein. Adversarial robustness on in- and out-distribution improves explainability. In *ECCV*, 2020.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. In *ICLR*, 2018.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, 2017.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. In *NeurIPS*, pp. 11190–11201. 2019.

Pin-Yu Chen, Yash Sharma, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. Ead: Elastic-net attacks to deep neural networks via adversarial examples. In *AAAI*, 2018.

Tianlong Chen, Sijia Liu, Shiyu Chang, Yu Cheng, Lisa Amini, and Zhangyang Wang. Adversarial robustness: From self-supervised pre-training to fine-tuning. In *CVPR*, 2020.

Minhao Cheng, Thong Le, Pin-Yu Chen, Jinfeng Yi, Huan Zhang, and Cho-Jui Hsieh. Query-efficient hard-label black-box attack: An optimization-based approach. In *ICLR*, 2019.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack. In *ICML*, 2020a.

Francesco Croce and Matthias Hein. Provable robustness against all adversarial l_p-perturbations for $p \geq 1$. In *ICLR*, 2020b.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *ICML*, 2020c.

Francesco Croce and Matthias Hein. Mind the box: l_1-apgd for sparse adversarial attacks on image classifiers. In *ICML*, 2021.

Francesco Croce, Maksym Andriushchenko, Vikash Sehwag, Nicolas Flammarion, Mung Chiang, Prateek Mittal, and Matthias Hein. Robustbench: a standardized adversarial robustness benchmark. *arXiv preprint arXiv:2010.09670*, 2020a.

Francesco Croce, Maksym Andriushchenko, Naman D. Singh, Nicolas Flammarion, and Matthias Hein. Sparse-rs: a versatile framework for query-efficient sparse black-box adversarial attacks. *arXiv preprint, arXiv:2006.12834*, 2020b.

Nilesh Dalvi, Pedro Domingos, Mausam, Sumit Sanghai, and Deepak Verma. Adversarial classification. In *KDD*, 2004.

Logan Engstrom, Andrew Ilyas, Hadi Salman, Shibani Santurkar, and Dimitris Tsipras. Robustness (python library), 2019. URL https://github.com/MadryLab/robustness.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. preprint, arXiv:1810.12715v3, 2018.

Sven Gowal, Jonathan Uesato, Chongli Qin, Po-Sen Huang, Timothy Mann, and Pushmeet Kohli. An alternative surrogate loss for pgd-based adversarial testing. 2019.

Sven Gowal, Chongli Qin, Jonathan Uesato, Timothy Mann, and Pushmeet Kohli. Uncovering the limits of adversarial training against norm-bounded adversarial examples. *arXiv preprint arXiv:2010.03593v2*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *ECCV*, 2016.

Dan Hendrycks, Kimin Lee, and Mantas Mazeika. Using pre-training can improve model robustness and uncertainty. In *ICML*, 2019.

Jeremy Howard and Sebastian Ruder. Universal language model fine-tuning for text classification. In *ACL*, 2018.

Ahmadreza Jeddi, Mohammad Javad Shafiee, and Alexander Wong. A simple fine-tuning is all you need: Towards robust deep learning via adversarial fine-tuning. *arXiv preprint, arXiv:2012.13628*, 2020.

Daniel Kang, Yi Sun, Tom Brown, Dan Hendrycks, and Jacob Steinhardt. Transfer of adversarial robustness between perturbation types. *arXiv preprint, arXiv:1905.01034*, 2019.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. In *ICLR Workshop*, 2017.

Cassidy Laidlaw, Sahil Singla, and Soheil Feizi. Perceptual adversarial robustness: Defense against unseen threat models. In *ICLR*, 2021.

Sijia Liu, Pin-Yu Chen, Xiangyi Chen, and Mingyi Hong. signSGD via zeroth-order oracle. In *ICLR*, 2019.

Daniel Lowd and Christopher Meek. Adversarial learning. In *KDD*, 2005.

Divyam Madaan, Jinwoo Shin, and Sung Ju Hwang. Learning to generate noise for multi-attack robustness. In *ICML*, 2021.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

Pratyush Maini, Eric Wong, and Zico Kolter. Adversarial robustness against the union of multiple perturbation models. In *ICML*, 2020.

Laurent Meunier, Jamal Atif, and Olivier Teytaud. Yet another but more efficient black-box adversarial attack: tiling and evolution strategies. *arXiv preprint, arXiv:1910.02244*, 2019.

Apostolos Modas, Seyed-Mohsen Moosavi-Dezfooli, and Pascal Frossard. Sparsefool: a few pixels make a big difference. In *CVPR*, 2019.

Marius Mosbach, Maksym Andriushchenko, Thomas Trost, Matthias Hein, and Dietrich Klakow. Logit pairing methods can fool gradient-based attacks. In *NeurIPS 2018 Workshop on Security in Machine Learning*, 2018.

Jérôme Rony, Eric Granger, Marco Pedersoli, and Ismail Ben Ayed. Augmented Lagrangian adversarial attacks. In *ICCV*, 2021.

Lukas Schott, Jonas Rauber, Matthias Bethge, and Wieland Brendel. Towards the first adversarially robust neural network model on mnist. In *ICLR*, 2019.

David Stutz, Matthias Hein, and Bernt Schiele. Disentangling adversarial robustness and generalization. *CVPR*, 2019.

David Stutz, Matthias Hein, and Bernt Schiele. Confidence-calibrated adversarial training: Generalizing to unseen attacks. In *ICML*, 2020.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, pp. 2503–2511, 2014.

Florian Tramèr and Dan Boneh. Adversarial training and robustness for multiple perturbations. In *NeurIPS*, 2019.

Florian Tramèr, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. In *NeurIPS*, 2020.

Eric Wong and J. Zico Kolter. Learning perturbation sets for robust machine learning. In *ICLR*, 2021.

Eric Wong, Frank R Schmidt, Jan Hendrik Metzen, and J Zico Kolter. Scaling provable adversarial defenses. In *NeurIPS*, 2018.

Boxi Wu, Jinghui Chen, Deng Cai, Xiaofei He, and Quanquan Gu. Do wider neural networks really help adversarial robustness? *arXiv preprint arXiv:2010.01279v2*, 2021.

Dongxian Wu, Shu tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization. In *NeurIPS*, 2020.

Cong Xu and Min Yang. Adversarial momentum-contrastive pre-training. *arXiv preprint, arXiv:2012.13154v2*, 2020.

S. Zagoruyko and N. Komodakis. Wide residual networks. In *BMVC*, pp. 87.1–87.12, 2016.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *ICML*, 2019.

Pu Zhao, Sijia Liu, Pin-Yu Chen, Nghia Hoang, Kaidi Xu, Bhavya Kailkhura, and Xue Lin. On the design of black-box adversarial examples by leveraging gradient-free optimization and operator splitting method. In *ICCV*, pp. 121–130, 2019.

A   EXPERIMENTAL DETAILS

For the comparison of training schemes we use for multiple-norm robustness we train PreAct ResNet-18 (He et al., 2016) with softplus activation function for 80 epochs with initial learning rate of 0.05 reduced by a factor of 10 after 70 epochs. When training WideResNet-28-10 (Zagoruyko & Komodakis, 2016) we use a cyclic schedule for the learning rate with maximum value 0.1 for 30 epochs. We use SGD optimizer with momentum of 0.9 and weight decay of $5 \cdot 10^{-4}$, batch size of 128. We use random cropping and horizontal flipping as augmentation techniques. For adversarial training of models robust wrt a single norm and with SAT and our novel scheme E-AT we use APGD with default parameters, while for the retrained AVG, MAX, and MSD we use PGD for l_∞ (step size $\epsilon_\infty/4$) and l_2 (step size $\epsilon/3$), SLIDE (Tramèr & Boneh, 2019) for l_1 (standard parameters). For all methods we use 10 steps for the inner maximization problem in adversarial training (note that AVG and MAX repeat the attack for all threat models, and MSD tests multiple steps, thus they are more expensive). For all schemes we select the best performing checkpoint for the comparison when using the piecewise schedule, the final checkpoint with the cyclic schedule. Moreover, we use the TRADES-XENT loss (TRADES loss (Zhang et al., 2019) with adversarial points maximizing the cross-entropy loss) since Gowal et al. (2020) show that this gives slightly better robustness on CIFAR-10 without additional data, while we use standard adversarial training (Madry et al., 2018) for PreAct ResNet-18. We train the classifiers of MNG-AC (Madaan et al., 2021) with the original code, where we set $\epsilon_1 = 12$ and rescale the step size linearly. Finally, for the runtime comparison we run each method on a single Tesla V100 GPU.

For fine-tuning on CIFAR-10 we use 3 epochs and the same setup as for full training except for the learning rate schedule, since in this case we use as initial value the best performing one in $\{0.01, 0.05\}$ (the larger value works best for the smaller networks) and reduce it by a factor of 10 at the beginning of each epoch. When the model was originally trained with extra data beyond the training set on CIFAR-10, we use the 500k images introduced by Carmon et al. (2019) as additional data for fine-tuning, and each batch is splitted equally between standard and extra images, and we count 1 epoch when the whole standard training set has been used: note that in this way, using only 3 epochs not the whole pseudo-labelled dataset is exploited.

For fine-tuning on ImageNet we use 1 epoch, initial learning rate of 0.01, reduced by a factor of 10 every 1/3 of training steps. We follow the setup of Engstrom et al. (2019) for data augmentation and setting batch size to 256 and weight decay to 10^{-4}. For adversarial training we use APGD with 5 steps for l_∞ and l_2, 15 steps for l_1 since optimizing in the l_1-ball intersected with the box constraints is more challenging, see Croce & Hein (2021).

B   ADDITIONAL ANALYSIS, EVALUATION AND EXPERIMENTS FOR E-AT

We here analyze in more details our E-AT scheme and expand the comparison to existing methods presented above.

B.1   ROBUSTNESS WRT l_2 OF E-AT

To show the effect of E-AT on l_2-robustness we plot in Fig. 3 the robust accuracy wrt l_2 computed with FAB (Croce & Hein, 2020a), which minimizes the size of the perturbations, as a function of the threshold ϵ_2 for a PreAct ResNet-18 trained with l_2-AT at $\epsilon_2 = 0.5$ and one using E-AT (see complete results for such models in Sec. B.3). Theorem 3.1 suggests that the extreme norms training provides robustness at $\epsilon_2 \approx 0.62$, which is confirmed by the plots. Although no l_2-attack has been used during training by the E-AT model, it has robustness wrt l_2 similar to that of the classifier specifically trained for such threat model.

B.2   CONFIRMATION THAT ADVERSARIAL TRAINING WITH THE EXTREME NORMS IS SUFFICIENT: ANALYSIS OF MAX AND MSD TRAINING

Both MAX and MSD schemes perform adversarial training considering all the threat models simultaneously, and we analyze here their training procedure in more detail. Fig. 4 shows for the MAX strategy how many times, in percentage, for each epoch the points computed for each threat model realize the maximal loss over the three attacks (l_1, l_2, l_∞), and then are subsequently used for the

Figure 3: l_2-robustness curve of a model trained with l_2-adversarial training (AT) for $\epsilon_2 = 0.5$ (orange) versus our E-AT (blue), which is expected to yield robustness at $\epsilon_2 = 0.62$. **Although l_2-attacks are not used for training, our extreme-adv. training scheme E-AT yields l_2-robustness similar to the one obtained with specific l_2-adversarial training.**

Figure 4: **CIFAR-10, ResNet18. Left:** For MAX-training we show for each epoch during training the percentage of points attaining for the indicated l_p-threat model ($p \in \{1, 2, \infty\}$) the highest loss over the the three threat models. **Right:** For MSD-training we show the percentage of steps taken wrt each threat model over epochs (note that MSD does the steepest descent step for each l_p-threat model and then realizes the one yielding maximal loss).

update of the model. Similarly, for MSD, we show the frequency with which a step wrt each l_p-norm is taken when computing the adversarial points (average over all iterations and training points). In both cases the l_∞-threat model is the most used one with the l_1-threat model being used $3 - 4$ times less often. However, the l_2-threat model is almost never chosen. This empirically confirms the analysis from Theorem 3.1 which shows that training only wrt l_∞ and l_1 is (at least for a linear classifier) sufficient to achieve l_2-robustness for the chosen ϵ_2 and thus during training no extra updates wrt the l_2-threat model are necessary. This is in line with the results reported in Fig. 3 which show that for different thresholds the l_2-robustness achieved by E-AT-training is similar to that of standard l_2-training (for generating Fig. 3 we use FAB attack (Croce & Hein, 2020a) to compute robust accuracy at varying ϵ_2).

B.3 E-AT FROM RANDOM INITIALIZATION WITH DIFFERENT ARCHITECTURE

We repeat the experiment from the main part about training for multiple norms robustness from random initialization with a smaller architecture like PreAct ResNet-18 (He et al., 2016). MAX-training yields the most robust model but E-AT is only 1.6% worse outperforming SAT and AVG but note that the standard deviation is rather high. Since it has the same architecture we additionally include the original MSD model of Maini et al. (2020), marked with (*), which obtains 41.4% robustness in the union, whereas with our reimplementation we get 43.9%, improving their results significantly. Note that they reported in their paper 47.0% robustness in the union, while our APGD-

Table 5: **CIFAR-10 - Comparison of different full training schemes for multiple-norm robustness on PreAct ResNet-18:** For each scheme we report the robust accuracy wrt l_∞, l_2, l_1 and the worst case over the union of the threat models. Moreover, we show the clean accuracy and the time per epoch of training. MSD and MAX perform best in the union, but our E-AT achieves almost the same robustness in the union but is better in l_1- and l_2-robustness and requires only about about a third or half of the training time. (*) indicates the original MSD model from Maini et al. (2020).

method	clean	l_∞ ($\epsilon_\infty = \frac{8}{255}$)	l_2 ($\epsilon_2 = 0.5$)	l_1 ($\epsilon_1 = 12$)	union	time/epoch
l_∞-AT	84.0 ± 0.31	48.1 ± 0.21	59.7 ± 0.41	6.3 ± 0.97	6.3 ± 0.97	151 s
l_2-AT	88.9 ± 0.57	27.3 ± 1.79	68.7 ± 0.09	25.3 ± 1.60	20.9 ± 1.80	153 s
l_1-AT	85.9 ± 1.07	22.1 ± 0.14	64.9 ± 0.49	59.5 ± 0.85	22.1 ± 0.09	195 s
SAT	83.9 ± 0.82	40.7 ± 0.71	68.0 ± 0.39	54.0 ± 1.20	40.4 ± 0.66	161 s
AVG	84.6 ± 0.31	40.8 ± 0.66	68.4 ± 0.71	52.1 ± 0.37	40.1 ± 0.78	479 s
MAX	80.4 ± 0.54	45.7 ± 0.90	66.0 ± 0.41	48.6 ± 0.82	44.0 ± 0.71	466 s
MSD (*)	82.1	43.1	64.5	46.5	41.4	-
MSD	81.1 ± 1.14	44.9 ± 0.63	65.9 ± 0.64	49.5 ± 1.18	43.9 ± 0.76	306 s
E-AT unif.	82.2 ± 1.84	42.7 ± 0.74	67.5 ± 0.46	53.6 ± 0.12	42.4 ± 0.60	163 s
E-AT	81.9 ± 1.44	43.0 ± 0.87	66.4 ± 0.58	53.0 ± 0.29	42.4 ± 0.73	160 s

based evaluation reduces this to 41.4% which shows that our robustness evaluation is significantly stronger.

C FINE-TUNING WITH E-AT FOR MULTIPLE NORMS ROBUSTNESS

C.1 FINE-TUNING ROBUST AND NATURAL MODELS

Table 6: **CIFAR-10 - 3 epochs of fine-tuning with E-AT:** We report the results of fine-tuning PreAct ResNet-18 models to become robust wrt the union of the threat models. Fine-tuning any l_p-robust model leads to competitive clean and robust accuracy to full training, differently from using a naturally trained model.

model		clean		l_∞ ($\epsilon_\infty = \frac{8}{255}$)		l_2 ($\epsilon_2 = 0.5$)		l_1 ($\epsilon_1 = 12$)		union	
RN-18 - standard		94.4		0.0		0.0		0.0		0.0	
	+ FT	66.6	-27.8	29.9	29.9	50.1	50.1	38.5	38.5	29.8	29.8
RN-18 - l_∞		83.7		48.1		59.8		7.7		7.7	
	+ FT	82.3	-1.4	43.4	-4.7	68.0	8.2	48.0	40.3	41.2	33.5
RN-18 - l_2		88.2		29.8		68.6		27.5		23.1	
	+ FT	85.4	-2.8	40.6	10.8	69.8	1.2	48.7	21.2	39.1	16.0
RN-18 - l_1		87.1		22.0		64.8		60.3		22.0	
	+ FT	83.5	-3.6	40.3	18.3	68.1	3.3	55.7	-4.6	40.1	18.1

We fine-tune for 3 epochs PreAct ResNet-18 either naturally trained or robust wrt a single l_p-norm. Table 6 shows clean and robust accuracy for each threat model for the initial classifier and after E-AT fine-tuning: while for all robust models the fine-tuning yields values competitive with the full training for multiple norms (see Table 5), starting from a standard model leads to significantly lower both clean performance and robustness in the union of the three l_p-balls.

C.2 RUNTIME WITH LARGE MODELS

We reported in Table 1 and Table 5 the runtime per epoch of E-AT. For larger architectures the computational cost increases significantly, and adversarial training with the WideResNet-70-16, the largest one we consider, on CIFAR-10 takes, in our experiments, around 6100 s per epoch when using only the training set and over 10000 s if the unlabelled data is used (since twice more training steps are effectively used). This shows how transfering robustness with fine-tuning might allow to obtain classifiers robust wrt different threat models fast and at much lower computational cost.

C.3 RESULTS OVER RANDOM SEEDS AND EFFECT OF BIASED SAMPLING SCHEME

Table 7: **CIFAR-10 - Uniform vs biased sampling in E-AT for fine-tuning:** We fine-tune with E-AT for 3 epochs the RN-18 robust wrt individual norms with either uniform (E-AT unif.) or biased (E-AT) sampling scheme (mean and standard deviation of the clean and robust accuracy over 5 seeds is reported). The biased sampling scheme is helpful when fine-tuning the l_2 and l_1 models which are not robust in the most challenging threat model, i.e. l_∞.

model	clean	l_∞ ($\epsilon_\infty = \frac{8}{255}$)	l_2 ($\epsilon_2 = 0.5$)	l_1 ($\epsilon_1 = 12$)	union
RN-18 - l_∞ - uniform	82.6 ± 0.62	44.4 ± 0.37	68.0 ± 0.26	48.5 ± 0.96	42.2 ± 0.34
RN-18 - l_∞ - biased	82.7 ± 0.41	44.3 ± 0.63	68.1 ± 0.48	48.7 ± 0.46	42.2 ± 0.78
RN-18 - l_2 - uniform	85.9 ± 0.51	40.0 ± 0.65	69.4 ± 0.68	50.3 ± 0.44	38.9 ± 0.79
RN-18 - l_2 - biased	85.8 ± 0.68	40.7 ± 0.90	69.5 ± 0.50	49.5 ± 0.54	39.4 ± 0.72
RN-18 - l_1 - uniform	83.5 ± 0.68	39.8 ± 0.51	68.0 ± 0.19	55.8 ± 0.55	39.6 ± 0.47
RN-18 - l_1 - biased	83.6 ± 0.56	40.5 ± 0.38	68.1 ± 0.13	55.3 ± 0.38	40.3 ± 0.33

We study the effect of randomness in the training process when fine-tuning for robustness wrt multiple norms using E-AT. Moreover, we compare the biased sampling scheme introduced in Eq. (5) to a uniform one when to choose which l_p, with $p \in \{1, \infty\}$, attack to use for adversarial training for each batch. In Table 6 we report the average results and corresponding standard deviation over 5 runs with different seeds on CIFAR-10 models originally robust wrt a single norm. For all metrics and starting models different runs show similar performance (the largest standard deviation is 0.96%) showing the stability of the scheme. Note that in the previous experiments we used the same seed for all runs and methods, without selecting the best one in a pool. Moreover, the biased sampling schemes yields slightly better results when fine-tuning the l_2- and in particular the l_1-robust model: we hypothesize that, since l_∞ is the most challenging threat model, it is important to use it more often at training time when the initial model is non robust wrt l_∞.

C.4 RESULTS USING MORE EPOCHS

Table 8: **CIFAR-10 - Fine-tuning for more epochs:** We show the effect of fine-tuning for different number of epochs (3 is the standard we use) the PreAct ResNet-18 (standard or robust wrt l_∞).

model	clean		l_∞ ($\epsilon_\infty = \frac{8}{255}$)		l_2 ($\epsilon_2 = 0.5$)		l_1 ($\epsilon_1 = 12$)		union	
RN-18 - l_∞	83.7		48.1		59.8		7.7		7.7	
+ 3 epochs FT	82.3	-1.4	43.4	-4.7	68.0	8.2	48.0	40.3	41.2	33.5
+ 5 epochs FT	83.0	-0.7	45.2	-2.9	68.8	9.0	50.1	42.4	43.1	35.4
+ 7 epochs FT	83.1	-0.6	44.6	-3.5	68.7	8.9	50.4	42.7	42.6	34.9
+ 10 epochs FT	84.0	0.3	44.9	-3.2	69.2	9.4	51.0	43.3	42.8	35.1
+ 15 epochs FT	84.6	0.9	44.9	-3.2	69.5	9.7	52.1	44.4	43.2	35.5
RN-18 - standard	94.4		0.0		0.0		0.0		0.0	
+ 3 epochs FT	66.6	-27.8	29.9	29.9	50.1	50.1	38.5	38.5	29.8	29.8
+ 5 epochs FT	70.6	-23.8	33.8	33.8	55.2	55.2	44.4	44.4	33.4	33.4
+ 7 epochs FT	72.1	-22.3	36.1	36.1	58.9	58.9	45.9	45.9	35.6	35.6
+ 10 epochs FT	75.4	-19.0	37.1	37.1	61.0	61.0	47.9	47.9	36.9	36.9
+ 15 epochs FT	76.0	-18.4	40.2	40.2	61.6	61.6	49.2	49.2	40.0	40.0

Table 8 shows the effect of our E-AT-fine-tuning for different numbers of epochs on either a RN-18 robust wrt l_∞ or naturally trained. For the robust model, with longer training the clean accuracy progressively improves, as well as the robustness in the union of the threat models. In particular, the models fine-tuned for 15 epochs has robust accuracy similar to that achieved by the MAX-training (43.2% compared to 43.3%, see Table 5), while still being significantly faster even considering the training time of the initial model. When starting from a standard model, E-AT fine-tuning leads to a large drop in clean accuracy while the robustness in the union remains lower than what can be achieved with robust models, even when using 15 epochs.