Design of Experiments
for Stochastic Contextual Linear Bandits

Abstract

In the stochastic linear contextual bandit setting there exist several minimax procedures for exploration with policies that are *reactive* to the data being acquired. In practice, there can be a significant engineering overhead to deploy these algorithms, especially when the dataset is collected in a distributed fashion or when a human in the loop is needed to implement a different policy. Exploring with a single non-reactive policy is beneficial in such cases. Assuming some batch contexts are available, we design a single stochastic policy to collect a good dataset from which a near-optimal policy can be extracted. We present a theoretical analysis as well as numerical experiments on both synthetic and real-world datasets.

1 Introduction

Designers in many application areas can now deploy personalized decision policies. For example, recent work used manual classification of students to deploy semi-personalized literacy tips text messages which can be done easily by leveraging popular text messaging platforms. This work found significant improvements in young children's literacy scores (Doss et al. (2019)), but also noted the substantial variation in when and what type of text messages were most effective for different families (Cortes et al. (2019); Doss et al. (2019)).

This setting and many others might substantially benefit from data-driven contextualized decision policies that optimize the desired expected outcome (such as literacy). Online machine learning methods like multi-armed bandits and reinforcement learning, that adaptively change interventions in response to outcomes in a closed loop process (see Figure 1a), may not yet be practical for such settings due to the expertise and infrastructure needed. However running an experiment with a fixed decision policy is likely to be both simple logistically (since such organizations already often design such decision policies by hand) and palatable, since many areas (education, healthcare, social sciences) commonly deploy experiments across a few conditions to find the best approach. For these reasons, a key opportunity is to design *static* or *non-reactive* policies that can be used to gather data to identify optimal contextualized decision policies.

More generally, a fixed data collection strategy is practically desirable (1) whenever multiple agents collect data asynchronously and communication to update their policy is difficult or impossible, and (2) whenever changing the policy requires a significant overhead either in the engineering infrastructure or in the training of human personnel. Indeed several works limit the number of policy switches with minimal sample complexity impact (Han et al., 2020; Ruan et al., 2020; Ren et al., 2020; Bai et al., 2019; Wang et al., 2021). In this work, motivated by the above settings, we go further and look for a *single*, *non-reactive* policy for data collection.

Setting and goal We consider the linear stochastic contextual bandit setting where each context $s \in \mathcal{S}$ is sampled from a distribution μ and a context-dependent action set $a \in \mathcal{A}_s$ is made available to the learner. The bandit instance is defined by a feature extractor $\phi(s, a)$ and some unknown

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

(a) Traditional online RL framework

(b) Design of experiment with an online and offline component

Figure 1: Comparison between the traditional RL setting and design of experiments

parameter $\theta^\star$. Upon choosing an action $a \in \mathcal{A}_s$, the linear reward function $r(s, a) = \phi(s, a)^\top \theta^\star + \eta$ is revealed to the learner corrupted by mean zero 1-subGaussian noise η. Our goal is to construct an exploration policy π_e to gather a dataset, such that after that dataset is gathered, we can extract a near optimal policy $\widehat{\pi}$ from it.

Perhaps surprisingly, there has been relatively little work on this setting. Prior work on exploration to quickly identify a near-optimal policy focuses on best-arm identification using adaptive policies that react to the observed rewards (Soare et al., 2014; Tao et al., 2018; Jedra and Proutiere, 2020) or design of experiments that produces a non-reactive policy for data collection (Kiefer and Wolfowitz, 1960; Esfandiari et al., 2019; Lattimore and Szepesvari, 2020); both lines of work assume that a *single*, repeated context with unchanging action set is presented to the learner. In contrast we are interested in identifying near-optimal context-specific decision policies. The closest related work (Ruan et al., 2020) investigates our task as a subtask for online regret learning, but requires an amount of data that scales as $\Omega(d^{16})$, which is impractical in applications with even moderate d.

Without any apriori information about the problem, no algorithm can do much better than deploying a random policy, which can require an amount of data that scales exponentially in d, see appendix F.1. However, in many common applications, *prior data about the context distribution $\mu(s)$* and the state–action feature representation ϕ is available. For example, an organization will often know information about its customers and specify the feature representation used for state–action spaces in advance of trying out such actions.[1] The available contexts are referred to as *offline* contexts data.

Our algorithm leverages historical context data to enable data efficient design of experiments for stochastic linear contextual bandits. It uses offline context data $\mathcal{C}$ to design a non-reactive policy π_e to collect new, *online* data where reward feedback is observed (see Figure 1b), and uses the resulting dataset $\mathcal{D}'$ to learn a near-optimal on average decision policy $\widehat{\pi}$ for future use. We highlight that the algorithm does not get to adjust the exploratory policy π_e while the online data is being collected.

Contribution We make the following contributions.

- Using past contexts only, we design a single, non-reactive policy to acquire online data that can be used to compute a context-dependent decision policy that is near-optimal in expectation across the contexts with high probability, for future use.
- Our algorithm achieves the minimax lower bound $\Omega(\min\{d \log(|\mathcal{S} \times \mathcal{A}|, d^2)\}/\epsilon^2)$ on the number of online samples (ignoring log and constants), while keeping the number of offline contexts polynomially small ($O(d^2/\epsilon^2)$ or $O(d^3/\epsilon^2)$).
- Our experiments on a simulation and on a learning to rank Yahoo dataset show our strategic design of experiments approach can learn better decision policies with less exploration data compared to standard exploration strategies that fail to exploit structure encoded in the historical contexts.

2 Related Work

There is an extensive line of literature on linear bandits, with most papers focusing on online regret. Research on sample complexity results has focused primarily on adaptive algorithms for non-contextual bandits with a simple or vectored action space (Soare et al., 2014; Tao et al., 2018; Xu et al., 2018; Fiez et al., 2019; Jedra and Proutiere, 2020; Degenne et al., 2020). Their sample complexity bounds depend on the suboptimality gap of the action set, and are therefore, instance-

---

[1]In other words, given a set of previously observed states $s_1, \ldots, s_M$, and a known state–action representation ϕ, for any potential action a, we can compute the resulting representation $\phi(s, a)$.

dependent. The design of experiments literature (Kiefer and Wolfowitz, 1960; Esfandiari et al., 2019; Lattimore and Szepesvari, 2020; Ruan et al., 2020) has also focused on non-contextual bandits, but in designing a non-adaptive policy such that the resulting dataset can be used to identify an optimal arm with high probability.

Few recent papers consider learning the optimal policy for a contextual bandit setting in the pure exploration setting (Deshmukh et al., 2018; Ruan et al., 2020). They propose an algorithm that yields an online reactive policy for when the reward is generated by a RKHS function on the input space: in contrast we focus on non-adaptive policies for stochastic linear contextual bandits.

The most related paper to this work is Ruan et al. (2020). The main focus of Ruan et al. (2020) is to minimize the number of policy switches in the online phase while keeping the expected regret optimal. Directly applying Theorem 6 of Ruan et al. (2020) yields a $\widetilde{O}(d^2/\epsilon^2)$ online sample complexity and $\widetilde{O}(d^{16})$ offline sample complexity. Note that the offline sample complexity is independent of ϵ. As a trade-off, Ruan et al. (2020) have a highly suboptimal dependence on d, which leads to burn-in phase too large to be practically useful; their algorithm also suffers from a high computational complexity. However, note their work is focused on a different objective than what we have here.

3 Setup

We consider the stochastic linear contextual bandit model with stochastic contexts. A bandit instance is characterized by a tuple $\langle \mathcal{S}, \mathcal{A}, \mu, r \rangle$ where $\mathcal{S}$ is the context space and μ is the context distribution. For a context $s \in \mathcal{S}$, the action space is denoted by $\mathcal{A}_s$. The feature map $\phi : (s, a) \mapsto \phi(s, a) \in \mathbb{R}^d$ is assumed to be known and defines the linear reward model $r(s, a) = \phi(s, a)^\top \theta^\star + \eta$ for some $\theta^\star \in \mathbb{R}^d$ parameter and some mean-zero 1-subgaussian random variable η.

We occasionally use the $\widetilde{O}$ notation to suppress $\mathrm{polylog}$ factors of the input parameters $d, \lambda, \frac{1}{\delta}$. We write $f \lesssim g$ if $f = O(g)$, and $f \lesssim g$ if $f = \widetilde{O}(g)$. For a positive semi-definite matrix $\Sigma \in \mathbb{R}^{d \times d}$ and a vector $x \in \mathbb{R}^d$, let $\|x\|_\Sigma = \sqrt{x^\top \Sigma x}$. For two symmetric matrices A, B, we say $A \preccurlyeq B$ if $B - A$ is positive semi-definite.

Our analysis consists of an offline and online component. We often add $'$ to indicate the online quantities, e.g., we denote with $s_1, s_2, \ldots$ the offline contexts and with $s'_1, s'_2, \ldots$ the online contexts.

3.1 Objective and Error Decomposition

Our objective is to use offline contexts $\mathcal{C} = \{s_1, \ldots, s_M\}$ where $s_m \sim \mu$ to design a single stochastic policy π_e to acquire data from an online data stream $\mathcal{C}' = \{s'_1, \ldots, s'_N\}$. This generates a dataset $\mathcal{D}' = \{(s'_n, a'_n, r'_n)\}_{n=1,\ldots,N}$ where $s'_n \sim \mu, a'_n \sim \pi_e(s'_n)$ and $r'_n = r(s'_n, a'_n)$. Using $\mathcal{D}'$, the least-square predictor $\widehat{\theta}$ and the corresponding greedy policy $\widehat{\pi}$ can be extracted

$$\widehat{\theta} = \left(\Sigma'_N\right)^{-1} \sum_{i=1}^N \phi(s'_n, a'_n) r'_n, \qquad \widehat{\pi}(s) = \arg\max_{a \in \mathcal{A}_s} \phi(s, a)^\top \widehat{\theta} \qquad (1)$$

where $\Sigma'_N = \left(\sum_{n=1}^N \phi(s'_n, a'_n)\phi(s'_n, a'_n)^\top + \lambda_{reg} I\right)$ is the empirical cumulative covariance matrix with regularization level λ_{reg}. The quality of the dataset $\mathcal{D}'$ (and of the whole two-step procedure) is measured by the suboptimality of the extracted policy $\widehat{\pi}$ obtained after data collection:

$$\mathbb{E}_{s \sim \mu}[\max_a \phi(s, a)^\top \theta^\star - \phi(s, \widehat{\pi}(s))^\top \theta^\star]. \qquad (2)$$

Note that Eq. (2) measures the expectation over the contexts of the suboptimality between the resulting decision policy $\widehat{\pi}$ and the optimal policy. This is a looser criteria than a maximum norm bound which evaluates the error over any possible context s: in general this latter error may not be easily reduced if certain directions in feature space are rarely available.

A related objective is to minimize the maximum prediction error on the linear bandit instance

$$\mathbb{E}_{s \sim \mu} \max_a |\phi(s, a)^\top (\theta^\star - \widehat{\theta})| \leq \mathbb{E}_{s \sim \mu} \max_a \|\phi(s, a)\|_{(\Sigma'_N)^{-1}} \|\theta^\star - \widehat{\theta}\|_{\Sigma'_N} \qquad (3)$$

$$\leq \sqrt{\beta}\, \mathbb{E}_{s \sim \mu} \max_a \|\phi(s, a)\|_{(\Sigma'_N)^{-1}}. \qquad (4)$$

In Eq. (4), the least square error $\|\theta^\star - \widehat{\theta}\|_{\Sigma'_N} \leq \sqrt{\beta}$ comes from least square regression analyses (Lattimore and Szepesvári, 2020): with probability at least $1 - \delta$ we have

$$\|\widehat{\theta} - \theta^\star\|_{\Sigma'_N} \leq \sqrt{\beta} = \min\left\{ \underbrace{\sqrt{2\ln 2|\mathcal{S} \times \mathcal{A}| + \ln\frac{1}{\delta}}}_{\text{Small } \mathcal{S} \times \mathcal{A}}, \underbrace{2\sqrt{2d\ln 6 + \ln\frac{1}{\delta}}}_{\text{Large } \mathcal{S} \times \mathcal{A}} \right\} + \underbrace{\sqrt{\lambda_{reg}}\|\theta^\star\|_2}_{\text{Regularization Effect}} . \quad (5)$$

The above expression assumes that the state-action-rewards (s'_n, a'_n, r'_n) are drawn i.i.d. from a fixed distribution. This is satisfied in our setting as the data-collection policy π_e is non-reactive to the online data. The parameter β governs the sample complexity as a function of the size of the state-action space and also highlights the impact of the regularization bias.

Small predictive error (Eq. (4)) can be used to bound the suboptimal gap of the greedy policy (Eq. (2)). Therefore to obtain good performance, it is sufficient to bound $\mathbb{E}_{s\sim\mu} \max_a \|\phi(s,a)\|_{(\Sigma'_N)^{-1}}$. This can be achieved by designing an appropriate sampling policy π_e to yield a set of (s'_n, a'_n, r'_n) tuples whose empirical cumulative covariance matrix Σ'_N is as 'large' as possible.

4 Algorithms

Reward-free LINUCB First, assume it is acceptable to have an algorithm that updates its policy reactively. In order to reduce $\mathbb{E}_{s\sim\mu} \max_a \|\phi(s,a)\|_{(\Sigma'_n)^{-1}}$ we could use an algorithm that, every time a context $s \sim \mu$ is observed, chooses the action $\arg\max_{a\in\mathcal{A}_s} \|\phi(s,a)\|_{(\Sigma'_n)^{-1}}$ where the norm $\|\phi(s,a)\|_{(\Sigma'_n)^{-1}}$ that represents the uncertainty is highest (cf. section 3.1). This corresponds to running the LINUCB algorithm (Abbasi-Yadkori et al., 2011a) with the empirical reward function set to zero. One can show that after $\approx d^2/\epsilon^2$ iterations the uncertainty $\sqrt{\beta}\,\mathbb{E}_{s\sim\mu} \max_a \|\phi(s,a)\|_{(\Sigma'_n)^{-1}} \leq \epsilon$; if the algorithm stores the observed reward $r(s,a)$ in every visited context s and chosen action a, the greedy policy that can be extracted from this dataset (of size $\approx d^2/\epsilon^2$) is ϵ-optimal (cf. Eqs. (2),(4)), as desired.

Unfortunately we cannot run this reward-free algorithm online, as its policy is *reactive* to the online stream of observed online contexts s and selected actions a, while we want a non-reactive policy.

Algorithm 1 PLANNER (Reward-free LINUCB)

1: **Input**: Contexts $\mathcal{C} = \{s_1, \ldots, s_M\}$, reg. λ_{reg}
2: $\Sigma_1 = \lambda_{reg} I$
3: $m = 1$
4: **for** $m = 1, 2, \ldots M$ **do**
5:    **if** $\det(\Sigma_m) > 2\det(\Sigma_{\underline{m}})$ or $m = 1$ **then**
6:       $\underline{m} \leftarrow m$
7:       $\Sigma_{\underline{m}} \leftarrow \Sigma_m$
8:    **end if**
9:    Define $\pi_m : s \mapsto \arg\max_{a\in\mathcal{A}_s} \|\phi(s,a)\|_{\Sigma_{\underline{m}}^{-1}}$
10:   $\Sigma_{m+1} = \Sigma_m + \alpha\phi_m\phi_m^\top; \; \phi_m = \phi(s_m, \pi_m(s_m))$
11: **end for**
12: **return** policy mixture π_{mix} of $\{\pi_1, \ldots, \pi_M\}$

Algorithm 2 SAMPLER

1: **Input**: $\pi_{mix} = \{\pi_1, \ldots, \pi_M\}$, reg. λ_{reg}
2: Set $\mathcal{D}' = \emptyset$
3: **for** $n = 1, 2, \ldots N$ **do**
4:    Receive context $s'_n \sim \mu$
5:    Sample $m \in [M]$ uniformly at random
6:    Select action $a'_n = \pi_m(s'_n)$
7:    Receive feedback reward r'_n
8:    Store feedback $\mathcal{D}' = \mathcal{D}' \cup \{s'_n, a'_n, r'_n\}$
9: **end for**
10: **return** dataset $\mathcal{D}'$

Our algorithm leverages this idea and consists of two subroutines: 1) the *planner* (Alg. 1) which operates on offline contexts and identifies a mixture policy π_{mix} (this is the exploratory policy π_e mentioned in the introduction) 2) the *sampler* (Alg. 2) which runs π_{mix} online to finally gather the dataset. This way, π_{mix} is non-reactive to the online dataset.

Planner The purpose of the planner is to use past contexts to compute the exploratory policy. The planner runs the reward-free version of LINUCB on the offline context dataset $\mathcal{C}$ as described earlier in this section. This way, the planner selects the action a in the current offline context s_m that maximizes the uncertainty encoded in $\|\phi(s_m, a)\|_{\Sigma_{\underline{m}}^{-1}}$ where $\Sigma_{\underline{m}}$ is a scaled, regularized, cumulative covariance over the contexts parsed so far and the actions selected. Note this procedure is possible since the state–action function $\phi(s_m, a)$ is assumed to be known for any input (s_m, a) pair, and

Sample Complexity Bounds				
		Small $\mathcal{S} \times \mathcal{A}$	Large $\mathcal{S} \times \mathcal{A}$	Large $\mathcal{S} \times \mathcal{A}$
Offline Data	M	d^3/ϵ^2	d^3/ϵ^2	d^2/ϵ^2
Online Data	N	$(d \ln |\mathcal{S} \times \mathcal{A}|)/\epsilon^2$	d^2/ϵ^2	d^2/ϵ^2
Regularization	λ_{reg}	1	1	d

Table 1: Sample complexity bounds (ignoring constants and log terms) to obtain an ϵ-optimal optimal policy

no actual rewards are observed. The doubling schedule yields a short descriptor for the planner's policies $\{\pi_1, \ldots, \pi_M\}$. The variable $\underline{m}$ indicates the last doubling update before iteration m.

A key choice is the parameter $\alpha \in (0, 1]$ in the cumulative covariance matrix update. The rationale is that when $\alpha < 1$ each rank-one update $\phi_m \phi_m^\top$ to the cumulative covariance gets *discounted*. The smaller α is, the more offline samples the planner needs to get to a sufficiently positive definite covariance matrix Σ_M. This choice effectively averages the updates and increases the estimation accuracy of the planner's covariance with respect to its conditional expectation.

Sampler Upon termination, the planner identifies a sequence of policies $\pi_1, \ldots, \pi_M$. Now consider the average policy π_{mix}: every time an action is needed, π_{mix} samples one index $m \in [M]$ uniformly at random and plays π_m. This is the policy that the sampler (Alg. 2) implements for $N = \alpha M \leq M$ fresh online contexts.

Upon playing π_m in state s'_n, the corresponding reward is observed and the tuple $(\{s'_n, a'_n, r'_n\})$ is stored. Since π_{mix} is the average policy played by the planner, we expect that running π_{mix} on the online dataset produces a covariance matrix Σ'_N similar to the planner's Σ_M. This means the sampler acquires the same information that the planner would have acquired in presence of reward signal. Since the planner is the reward-free LINUCB algorithm, we expect its policy to efficiently reduce our uncertainty over the reward parameters and learn a near optimal policy; our analysis will make this intuition precise. Note the sampler's policy is non-reactive to the online stream of data.

5 Main Result

Theorem 1. *Consider running Alg. 1 for $M = \widetilde{\Omega}\left(\frac{d^2 \beta}{\lambda_{reg} \epsilon^2}\right)$ iterations and Alg. 2 for $N = \widetilde{\Omega}\left(\frac{d\beta}{\epsilon^2}\right)$ iterations with regularization $\lambda_{reg} = \Omega(\ln(d/\delta))$. Let $\widehat{\theta}, \widehat{\pi}$ be as in Eq. (1). For any $\epsilon \leq 1$, with probability at least $1 - \delta$ the expected maximum uncertainty*

$$\mathbb{E}_{s \sim \mu} \max_{a \in \mathcal{A}_s} |\phi(s, a)^\top (\theta^\star - \widehat{\theta})| \leq \epsilon \tag{6}$$

and the suboptimality of the greedy policy $\widehat{\pi}$ satisfies

$$\mathbb{E}_{s \sim \mu} \max_{a \in \mathcal{A}_s} (\phi(s, a) - \phi(s, \widehat{\pi}(s)))^\top \theta^\star \leq 2\epsilon. \tag{7}$$

In Table 1 we instantiate the bounds from Theorem 1 in different settings, ignoring constants and log terms. This highlights different tradeoffs between the regularization λ_{reg} and the number of offline contexts ($M = N/\alpha$) needed to achieve the online minimax sample complexity lower bound $\approx \min\{d, \ln |\mathcal{S} \times \mathcal{A}|\} \times d/\epsilon^2$ (Chu et al., 2011; Abbasi-Yadkori et al., 2011b).

In the large action regime $\ln |\mathcal{S} \times \mathcal{A}| \gtrapprox d$, a regularization level $\lambda_{reg} \approx d$ gives the optimal online sample complexity $N \approx d^2/\epsilon^2$ while requiring a context dataset of the same size ($M \approx d^2/\epsilon^2$, by choosing $\alpha = 1$).

More often, a lower level of regularization can be preferable to introduce less bias. For example $\lambda_{reg} = 1$ is a common choice in linear bandits (Abbasi-Yadkori et al., 2011b; Chu et al., 2011). When the cumulative covariance matrix is less regularized, we may need to compensate with additional offline data to ensure the covariance matrices are accurately estimated, which is achieved by setting $M = N/\alpha \approx dN$ (i.e., $\alpha \approx 1/d$). In this way, additional samples are collected by the planner to maintain its covariance estimation accuracy (and hence its planning accuracy) despite the lower regularization. However, here we mention that the algorithm seems to perform well numerically even when $\lambda_{reg} < 1$ and $\alpha = 1$.

More generally, the amount of regularization should be set following the classical bias-variance tradeoff; its choice is mostly a statistical learning question, and its optimal value is normally problem dependent. As a result, the problem dependent tradeoff between different values of λ_{reg} is not reflected in our minimax analyses but can be appreciated in our numerical experiments on the real world dataset.

6 Proof Sketch

We give a brief proof sketch where we ignore constants and log factors; the full analysis can be found in appendix. First we introduce some notation. We define the scaled cumulative covariance Σ_M at step m for the planner and the cumulative covariance Σ'_n for the sampler at step n:

$$\Sigma_m = \alpha \sum_{j=1}^{m-1} \phi(s_j, a_j)\phi(s_j, a_j)^\top + \lambda_{reg}I, \qquad \Sigma'_n = \sum_{j=1}^{n-1} \phi(s'_j, a'_j)\phi(s'_j, a'_j)^\top + \lambda_{reg}I \qquad (8)$$

where the planner's j actions is $a_j = \pi_j(s_j)$ and likewise the sampler's j actions is $a'_j \sim \pi_{mix}(s'_j)$.

Uncertainty Stochastic Process We represent the value of the uncertainty though a stochastic process. Let us define the filtration for the planner $\mathcal{F}_m = \sigma(s_1, \ldots, s_{m-1})$ at stage m and for the sampler $\mathcal{F}'_n = \sigma(s_1, \ldots, s_M, s'_1, \ldots, s'_{n-1})$ at stage n to represent the amount of information available. Let us also define the observed uncertainty U_m for the planner and likewise U'_n for the sampler:

$$U'_m \overset{def}{=} \max_{a \in \mathcal{A}_{s_m}} \|\phi(s_m, a)\|_{(\Sigma_m)^{-1}}, \qquad U'_n \overset{def}{=} \max_{a \in \mathcal{A}_{s_n}} \|\phi(s_n, a)\|_{(\Sigma'_n)^{-1}}. \qquad (9)$$

We ultimately want to bound $\mathbb{E}'_n U'_n = \mathbb{E}[U'_n \mid \mathcal{F}_n] = \mathbb{E}_{s \sim \mu} \max_a \|\phi(s, a)\|_{(\Sigma'_n)^{-1}}$ when $n = N$, i.e., the average uncertainty at the end, see Section 4. Likewise, let us define $\mathbb{E}_m U_m = \mathbb{E}[U_m \mid \mathcal{F}_m] = \mathbb{E}_{s \sim \mu} \max_a \|\phi(s, a)\|_{(\Sigma_m)^{-1}}$.

We show that $\mathbb{E}'_N U'_N$ is minimized in two steps: 1) we show that the planner's uncertainty $\mathbb{E}_M U_M$ can be bounded 2) since the sampler implements the planner's average policy, $\mathbb{E}'_N U'_N$ cannot be too far from $\mathbb{E}_M U_M$.

We highlight that $M \geq N$ in general, i.e., the stochastic processes proceed a different speed. In fact, the planner needs more data than the sampler ($M \geq N$) as the planner's policy is reactive to the offline contexts; this forces us to use more data-hungry concentration inequalities for the planner.

6.1 Offline Uncertainty

The next lemma is formally reported in Lemma 4 in appendix and examines the reduction in the planner's expected uncertainty $\mathbb{E}_M U_M$.

Lemma 1 (Offline Expected Uncertainty). *With high probability we have*

$$\mathbb{E}_M U_M \leq \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_m U_m \lessapprox \frac{1}{M} \sum_{m=1}^{M} U_m \lessapprox \sqrt{\frac{d}{\alpha M}}.$$

Proof sketch. We start by modifing a result from the classical bandit literature (e.g., Abbasi-Yadkori et al. (2011a)) to bound the average realized uncertainty U_m while accounting for the extra α scaling factor contained in the covariance matrix Σ_M:

$$\frac{1}{M} \sum_{m=1}^{M} U_m = \frac{1}{M} \sum_{m=1}^{M} \|\phi(s_m, a_m)\|_{\Sigma_m^{-1}} \lessapprox \sqrt{\frac{d}{\alpha M}}.$$

The parameter α on the right hand side above arises from its inclusion in the definition of cumulative covariance Eq. 8. This justifies the last inequality in the lemma's statement.

While we bounded $\frac{1}{M} \sum_{m=1}^{M} U_m$, we need to bound the average conditional expectations $\frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_m U_m$. Bernstein's inequality would bound the actual deviation $\sum_{m=1}^{M} U_m$ by the conditional variances (or expectations $\sum_{m=1}^{M} \mathbb{E}_m U_m$ given our boundness assumptions); here we need the opposite, and so we 'reverse' the inequality in Theorem 3 *(Reverse Bernstein for Martingales)* to claim $\sum_{m=1}^{M} \mathbb{E}_m U_m \lessapprox \sum_{m=1}^{M} U_m$ with high probability to conclude. $\qquad \square$

6.2 Online Uncertainty

In the prior section we showed that the planner would be successful in reducing its final uncertainty $\mathbb{E}_M U_M$ if it was collecting reward information; moreover, its sequence of policies $\pi_1, \ldots, \pi_M$ only depends on the observed contexts. Because of this, if the sampler runs the planner's average policy π_{mix}, we would expect a similar reduction in the uncertainty $\mathbb{E}'_N U'_N$ after $N = \alpha M$ iterations (the α factor simply arises because the planner's information are discounted by α). The argument is formalized in Lemma 3 *(Relations between Offline and Online Uncertainty)* in appendix, which we preview here. We let K be the number of policy switches by the sampler which is bounded by $K \lesssim d$ in Lemma 13 *(Number of Switches)* in appendix.

Lemma 2 (Relations between Offline and Online Uncertainty). *If $\lambda_{reg} = \Omega(\ln \frac{d}{\delta})$ and $M = \Omega\left(\frac{KN}{\lambda_{reg}} \ln \frac{dNK}{\lambda_{reg}\delta}\right)$, upon termination of Alg. 1 and 2 it holds with high probability that*

$$\mathbb{E}'_N U'_N \lesssim \mathbb{E}_M U_M.$$

Proof. Let $d_1, \ldots, d_M$ be the conditional distributions of the feature vectors sampled at timesteps $1, \ldots, M$ in Alg. 1 after the algorithm has terminated. Conditioned on $\mathcal{F}_M$, the d_i's are non-random. Then the conditional expected covariance matrix given $\mathcal{F}_M$ can be defined as

$$\overline{\Sigma} = \alpha \sum_{i=1}^{M} \mathbb{E}_{\phi \sim d_i} \phi\phi^\top + \lambda_{reg} I \tag{10}$$

Now, our argument relies on some matrix concentration inequalities which hold if

$$\lambda_{reg} = \Omega(\ln \frac{d}{\delta}), \qquad \frac{1}{\alpha} = \Omega\left(\frac{K}{\lambda_{reg}} \ln \frac{dNK}{\lambda_{reg}\delta}\right). \tag{11}$$

Precisely, from Lemma 11 *(Matrix Upper Bound Offline Phase)* and Lemma 12 *(Matrix Upper Bound Online Phase)* with high probability we have that

$$\forall x, \|x\|_2 \leq 1 : \qquad \|x\|_{(\Sigma'_N)^{-1}} \lesssim \|x\|_{\overline{\Sigma}^{-1}} \qquad \text{and} \qquad \|x\|_{\overline{\Sigma}^{-1}} \lesssim \|x\|_{\Sigma_M^{-1}}. \tag{12}$$

In words, we can confuse the planner's (random) scaled covariance Σ_M with its conditional expectation $\overline{\Sigma}$ with the guarantee that it won't be very different from the sampler's covariance Σ'_N (which implements the planner's policy). These concentration inequalities are key to proceed and are investigated in the appendix.

Define the policy maximizing the online uncertainty $\pi'_n(s) = \arg\max_{a \in \mathcal{A}_s} \|\phi(s,a)\|_{(\Sigma'_n)^{-1}}$. Under the event in Eq. (12) we can write

$$\mathbb{E}'_N U'_N \stackrel{def}{=} \mathbb{E}_{s \sim \mu} \max_{a \in \mathcal{A}_s} \|\phi(s,a)\|_{(\Sigma'_N)^{-1}} = \mathbb{E}_{s \sim \mu} \|\phi(s, \pi'_N(s))\|_{(\Sigma'_N)^{-1}} \lesssim \mathbb{E}_{s \sim \mu} \|\phi(s, \pi'_N(s))\|_{\overline{\Sigma}^{-1}}$$

$$\lesssim \mathbb{E}_{s \sim \mu} \|\phi(s, \pi'_N(s))\|_{\Sigma_M^{-1}} \leq \mathbb{E}_{s \sim \mu} \max_a \|\phi(s,a)\|_{\Sigma_M^{-1}} = \mathbb{E}_M U_M.$$

$\square$

6.3 Conclusion and Tradeoffs

We can now tune the parameters α, λ_{reg}. Starting from Eq. (4), we can write

$$\mathbb{E}_{s \sim \mu} \max_a \phi(s,a)^\top (\theta^\star - \widehat{\theta}) \leq \sqrt{\beta}\, \mathbb{E}'_N U'_N \lesssim \sqrt{\beta}\, \mathbb{E}_M U_M \lesssim \sqrt{\frac{\beta d}{\alpha M}} = \sqrt{\frac{\beta d}{N}}. \tag{13}$$

Thus, the rate-optimal online sample complexity $N \approx \frac{\beta d}{\epsilon^2}$ always suffices. However, we need a different number of offline contexts depending on the regularization that we want to adopt. Since $K \lesssim d$, the reader can verify that if $\lambda_{reg} \approx d$ then the preconditions in Eq. (11) are verified with $M \approx N$, so $\alpha \approx 1$. If a lower value for the regularization $\lambda \approx 1$ is desired, $M \approx dN$ would be required (thus $\alpha \approx \frac{1}{d}$).

The reason why we might need $M \geq N$ (i.e., $\alpha \leq 1$) is that the planner's policy is adaptive to the observed offline contexts. This means that the planner's cumulative covariance Σ_M is not a sum of i.i.d. rank-one random matrices; in this case, we need either a more data-hungry concentration inequality or heavier regularization, leading to the the precondtion on α in Eq. (11).

7 Experiments

In this section, we study the empirical properties of the planner and sampler in both a synthetic dataset and a real-world dataset from the Yahoo! Learning to Rank challenge (Chapelle and Chang, 2011). The objective of these experiments is to compare the performance of the planner-sampler pair with alternatives and analyze its sensitivity to regularization.

7.1 Synthetic dataset

(a) (b)

Figure 2: Synthetic Setting. In the left figure, the policy value performance of the sampler-planner (S-P) is compared with a random algorithm (Random), a largest norm algorithm (Norm), and an algorithm that always chooses the same single action (Single). Supervised learning (SL) represents an approximate upper bound; however, we don't expect the algorithms to be able to reach the SL performance as they all receive bandit feedback compared to the full feedback available to SL (10,000 samples). In the right figure, the empirical distributions over the actions chosen by the algorithms are compared, with the exception of Single, which always chooses action 1.

We first conduct a synthetic validation experiment in order to verify that the algorithms behave consistently with the intuition and theory developed in the previous sections. Towards this end, we constructed a simple linear contextual bandit problem with $d = 20$ and $\mathcal{A} = \{1, \ldots, 10\}$. Each context $s \in \mathcal{S}$ is associated with features vectors $\{\phi(x, a)\}_{a \in \mathcal{A}}$. Each context belongs to one of three discrete categories with equal probability. In category i, the action $a = i$ has features distributed as $\phi(X, a) \sim \mathcal{N}(0, \Sigma_1)$ where $\Sigma_1 = \mathrm{diag}(1, 10^{-9}, \ldots, 10^{-9})$. There are also two other actions with variance 1 at unique coordinates on the diagonal for each context. All contexts also share two actions $a = 5, 6$ such that $\phi(X, 5), \phi(X, 6) \sim \mathcal{N}(0, \mathrm{diag}(10^{-9}, \ldots, 10^{-9}, 5))$ independently. All remaining actions lead to identically zero features. The first $d - 1$ coordinates of θ were chosen randomly from $\{-1, 1\}^{d-1}$. The last coordinate is always zero.

We considered four algorithms: (1) a random algorithm that always chooses actions uniformly from $\mathcal{A}$, (2) a largest norm algorithm that always chooses the feature with the largest norm, (3) an algorithm that always chooses action 1 and (4) the sampler-planner algorithms proposed in this work. The planner is first run on an independent dataset of the same size as the one to be used for training in order to experience contexts from the same distribution that generates the online contexts. All algorithms are then run in the online phase with reward feedback. The algorithms are then evaluated based on their resulting policy values during the online phase on held-out test set. All algorithms used $\lambda = 1$ and the planner used $\alpha = 1$ as these worked well empirically.

The synthetic dataset is designed in such a way that most actions are uninformative and that it is often most prudent to get information about the first and last coordinates since there is the most variance in those directions. Thus a random algorithm should perform poorly, spending time on irrelevant actions. The largest norm algorithm also fails: while much is learned about the last coordinate of θ, little is learned about the others which are necessary for making good decisions. Finally, the single action algorithm fails to account for the switching modes of the contexts. Figure 2 shows the policy values plotted over the number of samples taken and also the action distributions of the algorithms. Each line represents the mean of 20 trials and the error bars represent the standard error.

7.2 Learning to rank dataset

We evaluate the planner-sampler performance on real-world data from the Yahoo! Learning to Rank challenge (Chapelle and Chang, 2011), which has been used previously (Foster et al., 2018).

The ranking dataset is structured as follows. Each datapoint (row) is a 700-dimensional feature vector associated with a ranking relevance score between taking on values in $\{0, 1, 2, 3, 4\}$. Each datapoint is also associated with a single context, termed a query. Multiple datapoints matched with the same query correspond to actions (documents) that the learner can choose when presented with that query. The dataset is already divided into training, validation, and testing data.

The objective is to choose actions, among those presented for a given query, that maximize the relevance scores. Unlike the previous synthetic dataset, the reward function here is misspecified, i.e., it does not exactly follow a linear model. To reduce the computational burden, we randomly subsampled coordinates of the original 700-dimensional features down to 300-dimensional features. We then normalized them to ensure the norms are at most 1. Similar to prior work, we also limit the number actions (documents) available at any given context to $K = 20$.

As before, we compare the planner-sampler pair to a random algorithm and a supervised learning oracle that observes all the context-action features and relevance scores, which is 200,000 training samples in total. To simulate streaming the data online to the algorithms, we sequentially iterate through the contexts and present the associated features to the learner as actions. During the offline phase, we run the planner on the validation set where none of the relevance scores are observed in order to generate the sampling policies. During the online phase, we run both the sampler and the random algorithm on the training data such that they observe the same contexts but may take different actions. The maximum number of distinct context we can iterate over is about $3'000$. The resulting policies are evaluated on the full test set after every 20 training observations. This ex-

Figure 3: The sampler-planner (S-P) pair is compared with a random sampler (Rand) with varying levels of regularization λ. The supervised learning oracle (SL), which observes state-action pairs in the training set, is shown as baseline.

periment was repeated with varying values of the regularization parameter $\lambda \in \{0.1, 1, 10\}$. The planner uses $\alpha = 1$; we did not find significant improvements with $\alpha < 1$. Additional values for λ are reported in the supplementary material.

Figure 3 depicts the results. Each point on the graph represents the mean of 10 independent trials and the error bands represent the standard deviation. The randomness is due only to internal randomness in the algorithms and the randomized order in which the contexts are revealed. The sampler-planner consistently outperforms the random algorithm in most regimes, including $\lambda = 1$ where the pinnacle performance of both algorithms is achieved. The gap between the algorithms is widened for larger choices of λ. We notice that for $\lambda = 0.1$ the curves appear to catch up as more data is gathered; it is possible that they would outperform larger value of regularization if more samples were available. The optimal choice for λ depends on the bias-variance tradeoff for such problem.

8 Conclusion

Assuming access to a set of offline contexts, this work proposes an algorithm to find a single stochastic policy to acquire data strategically. The procedure is sound as validated by a theoretical analysis and by experiments even when the reward model is not linear.

Our work opens several interesting directions: (1) can we devise a procedure that works across all values of regularization without severely impacting the amount of offline data we need? (2) how does the performance of the algorithm degrade if the online context distribution differs from the offline one? (3) can we incorporate prior reward data to reduce the sample complexity, and how is the benefit of such data impacted by the size of the state-action space, and the decision policy used to gather the prior reward data, which might be an adversarial procedure?

Our work presents little direct negative potential societal impacts though whether contextualized decision policies are beneficial or harmful depends on the setting and the optimization (reward function) chosen by a system designer.

References

Abbasi-Yadkori, Y., Pal, D., and Szepesvari, C. (2011a). Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems (NIPS)*.

Abbasi-Yadkori, Y., Pál, D., and Szepesvári, C. (2011b). Improved algorithms for linear stochastic bandits. In *NIPS*, volume 11, pages 2312–2320.

Bai, Y., Xie, T., Jiang, N., and Wang, Y. X. (2019). Provably efficient q-learning with low switching cost. *Advances in Neural Information Processing Systems*, 32.

Beygelzimer, A., Langford, J., Li, L., Reyzin, L., and Schapire, R. (2011). Contextual bandit algorithms with supervised learning guarantees. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 19–26. JMLR Workshop and Conference Proceedings.

Chapelle, O. and Chang, Y. (2011). Yahoo! learning to rank challenge overview. In *Proceedings of the learning to rank challenge*, pages 1–24. PMLR.

Chu, W., Li, L., Reyzin, L., and Schapire, R. (2011). Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214. JMLR Workshop and Conference Proceedings.

Cortes, K. E., Fricke, H. D., Loeb, S., Song, D. S., and York, B. N. (2019). When behavioral barriers are too high or low–how timing matters for parenting interventions. Technical report, National Bureau of Economic Research.

Degenne, R., Ménard, P., Shang, X., and Valko, M. (2020). Gamification of pure exploration for linear bandits. In *International Conference on Machine Learning*, pages 2432–2442. PMLR.

Deshmukh, A. A., Sharma, S., Cutler, J. W., Moldwin, M., and Scott, C. (2018). Simple regret minimization for contextual bandits. *arXiv preprint arXiv:1810.07371*.

Doss, C., Fahle, E. M., Loeb, S., and York, B. N. (2019). More than just a nudge supporting kindergarten parents with differentiated and personalized text messages. *Journal of Human Resources*, 54(3):567–603.

Esfandiari, H., Karbasi, A., Mehrabian, A., and Mirrokni, V. (2019). Regret bounds for batched bandits. *arXiv preprint arXiv:1910.04959*.

Fiez, T., Jain, L., Jamieson, K., and Ratliff, L. (2019). Sequential experimental design for transductive linear bandits. *arXiv preprint arXiv:1906.08399*.

Foster, D., Agarwal, A., Dudik, M., Luo, H., and Schapire, R. (2018). Practical contextual bandits with regression oracles. In *International Conference on Machine Learning*, pages 1539–1548. PMLR.

Han, Y., Zhou, Z., Zhou, Z., Blanchet, J., Glynn, P. W., and Ye, Y. (2020). Sequential batch learning in finite-action linear contextual bandits. *arXiv preprint arXiv:2004.06321*.

Jedra, Y. and Proutiere, A. (2020). Optimal best-arm identification in linear bandits. *Advances in Neural Information Processing Systems*, 33.

Kiefer, J. and Wolfowitz, J. (1960). The equivalence of two extremum problems. *Canadian Journal of Mathematics*, 12:363–366.

Lattimore, T. and Szepesvári, C. (2020). *Bandit Algorithms*. Cambridge University Press.

Lattimore, T. and Szepesvari, C. (2020). Learning with good feature representations in bandits and in rl with a generative model. In *International Conference on Machine Learning (ICML)*.

Ren, Z., Zhou, Z., and Kalagnanam, J. R. (2020). Batched learning in generalized linear contextual bandits with general decision sets. *IEEE Control Systems Letters*.

Ruan, Y., Yang, J., and Zhou, Y. (2020). Linear bandits with limited adaptivity and learning distributional optimal design. *arXiv preprint arXiv:2007.01980*.

Soare, M., Lazaric, A., and Munos, R. (2014). Best-arm identification in linear bandits. In *Advances in Neural Information Processing Systems (NIPS)*, pages 828–836.

Tao, C., Blanco, S., and Zhou, Y. (2018). Best arm identification in linear bandits with linear dimension dependency. In *International Conference on Machine Learning*, pages 4877–4886. PMLR.

Tropp, J. A. (2012). User-friendly tail bounds for sums of random matrices. *Foundations of computational mathematics*, 12(4):389–434.

Wang, T., Zhou, D., and Gu, Q. (2021). Provably efficient reinforcement learning with linear function approximation under adaptivity constraints. *arXiv preprint arXiv:2101.02195*.

Xu, L., Honda, J., and Sugiyama, M. (2018). A fully adaptive algorithm for pure exploration in linear bandits. In *International Conference on Artificial Intelligence and Statistics*, pages 843–851. PMLR.

Zanette, A., Cheng, C.-A., and Agarwal, A. (2021). Cautiously optimistic policy optimization and exploration with linear function approximation. *arXiv preprint arXiv:2103.12923*.