Capturing Graphs with Hypo-Elliptic Diffusions

Abstract

Convolutional layers within graph neural networks operate by aggregating information about local neighbourhood structures; one common way to encode such substructures is through random walks. The distribution of these random walks evolves according to a diffusion equation defined using the graph Laplacian. We extend this approach by leveraging classic mathematical results about hypo-elliptic diffusions. This results in a novel tensor-valued graph operator, which we call the hypo-elliptic graph Laplacian. We provide theoretical guarantees and efficient low-rank approximation algorithms. In particular, this gives a structured approach to capture long-range dependencies on graphs that is robust to pooling. Besides the attractive theoretical properties, our experiments show that this method competes with graph transformers on datasets requiring long-range reasoning but scales only linearly in the number of edges as opposed to quadratically in nodes.

1 Introduction

Obtaining a latent description of the non-Euclidean structure of a graph is central to many applications. One common approach is to construct a set of features for each node that represents the local neighborhood of this node; pooling these node features then provides a latent description of the whole graph. A classic way to arrive at such node features is by random walks: at the given node one starts a random walk, and extracts a summary of the local neighbourhood from its sample trajectories. We revisit this random walk construction and are inspired by two classical mathematical results:

Hypo-elliptic Laplacian. In the Euclidean case of Brownian motion $B = (B_t)_{t \geq 0}$ evolving in $\mathbb{R}^n$, the quantity $u(t, x) = \mathbb{E}[f(B_t)|B_0 = x]$ solves the heat equation $\partial_t u = \Delta u$ on $[0, \infty) \times \mathbb{R}^n$, $u(0, x) = f(x)$. Seminal work of Gaveau [22] in the 1970s shows that if one replaces $f(B_t)$ in the expectation by a functional of the whole trajectory, $F(B_s : s \in [0, t])$, then a path-dependent heat equation can be derived where the classical Laplacian Δ is replaced by the so-called hypo-elliptic Laplacian.

Free Algebras. A simple way to capture a sequence – for us, a sequence of nodes visited by a random walk on a graph – is to associate with each sequence element an element in an algebra[1] and multiply these algebra elements together. If the algebra multiplication is commutative, the sequential structure is lost but if it is non-commutative, this captures the order in the sequence. In fact, by using the free associative algebra, this can be done faithfully and linear functionals of this algebra correspond to functionals on the space of sequences.

We leverage these ideas from the Euclidean case of $\mathbb{R}^d$ to the non-Euclidean case of graphs. In particular, we construct features for a given node by sampling from a random walk started at this node, but instead of averaging over the end points, we average over path-dependent functions. Put

---

[1]An algebra is a vector space where one can multiply elements; e.g. the set of $n \times n$ matrices with matrix multiplication. This multiplication can be non-commutative; e.g. $A \cdot B \neq B \cdot A$ for general matrices A, B.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

informally, instead of asking a random walker that started at a node, *"What do you see now?"* after k steps, we ask *"What have you seen along your way?"*. The above notions from mathematics about the hypo-elliptic Laplacian and the free algebra allow us to formalize this in the form of a generalized graph diffusion equation and we develop algorithms that make this a scalable method.

Related Work. From the ML literature, [46, 25] popularized the combination of deep learning architectures to capture random walk histories. Such ideas have been incorporated, sometimes implicitly, into graph neural networks (GNN) [49, 9, 50, 17, 27, 5, 31] that in turn build on convolutional approaches [35, 36, 25], as well as their combination with attention or message passing [43, 59, 23], and more recent improvements [66, 44, 41, 14] that provide and improve on theoretical guarantees. Another classic approach are graph kernels, see [7] for a recent survey; in particular, the seminal paper [34] explored the connection between diffusion equations and random walkers in a kernel learning context. More recently, [13] proposed sequence kernels to capture the random walk history. Furthermore, [16] uses the signature kernel maximum mean discrepancy (MMD) [15] as a metric for trees which implicitly relies on the algebra of tensors that we use, and [45] aggregates random walk histories to derive a kernel for graphs. Moreover, the concept of network motifs [42, 51] relates to similar ideas that describe a graph by node sequences. Directly related to our approach is the topic of learning diffusion models [33, 12, 54, 19, 10] on graphs. While similar ideas on random walks and diffusion for graph learning have been developed by different communities, our proposed method leverages these perspectives by capturing random walk histories through a novel diffusion operation.

Our main mathematical influence is the seminal work of Gaveau [22] from the 1970s that shows how Brownian motion can be lifted into a Markov process evolving in a free algebra to capture path-dependence. This leads to a heat equation governed by the hypo-elliptic Laplacian. These insights had a large influence in PDE theory, see [48, 29], but it seems that their discrete counterpart on graphs has received no attention despite the well-developed literature on random walks on graphs and general non-Euclidean objects, [62, 18, 24, 57]. A key challenge to go from theory to application is to handle the computational complexity. To do so, we build on ideas from [56] to design effective algorithms for the hypo-elliptic graph diffusion.

Contribution and Outline. We introduce the hypo-elliptic graph Laplacian which allows to effectively capture random walk histories through a generalized diffusion model.

- In Section 3, we introduce the hypo-elliptic variants of standard graph matrices such as the adjacency matrix and (normalized) graph Laplacians. These hypo-elliptic variants are formulated in terms of tensor-valued matrices rather than scalar-valued matrices, and can be manipulated using linear algebra in the same manner as the classical setting.

- The hypo-elliptic Laplacian leads to a corresponding diffusion model, and in Theorem 1, we show that the solution to this generalized diffusion equation summarizes the microscopic picture of *the entire history of random walks* and not just their location after k steps.

- This solution provides a rich description of the local neighbourhood about a node, which can either be used directly as node features or be pooled over the graph to obtain a latent description of the graph. Theorem 2 shows that these node features characterize random walks on the graph, and we provide an analogous statement for graph features in Appendix E.

- In principle, one can solve the hypo-elliptic graph diffusion equation directly with linear algebra, but this is computationally prohibitive and Theorem 3 provides an efficient low-rank approximation.

- Finally, Section 5 provides experiments and benchmarks. A particular focus is to test the ability of our model to capture long-range interactions between nodes and the robustness of pooling operations which makes it less susceptible to the "over-squashing" phenomenon [2].

2   Sequence Features by Non-Commutative Multiplication.

We define the *space of sequences in* $\mathbb{R}^d$ by

$$\mathsf{Seq}(\mathbb{R}^d) := \bigcup_{k=0}^{\infty} (\mathbb{R}^d)^{k+1},$$

where elements are sequences denoted by $\mathbf{x} = (x_0, x_1, \ldots, x_k) \in (\mathbb{R}^d)^{k+1}$. Assume we are given an injective map, which we call the *algebra lifting*,

$$\varphi : \mathbb{R}^d \to H.$$

from $\mathbb{R}^d$ into an algebra H. We can use this to define a *sequence feature map*[2]

$$\widetilde{\varphi} : \mathsf{Seq}(\mathbb{R}^d) \to H, \quad \widetilde{\varphi}(\mathbf{x}) = \varphi(\delta_1 \mathbf{x}) \cdots \varphi(\delta_k \mathbf{x}), \tag{1}$$

where $\delta_0 \mathbf{x} = x_0$ and $\delta_i \mathbf{x} := x_i - x_{i-1}$ for $i \geq 1$ are used to denote the *increments* of a sequence $\mathbf{x} = (x_0, \ldots, x_k)$. This map associates to any sequence $\mathbf{x} \in \mathsf{Seq}(\mathbb{R}^d)$ an element of the algebra H. If the multiplication in H is commutative, then the map $\widetilde{\varphi}$ would have no information about the order of increments, i.e. $\varphi(\delta_0 \mathbf{x}) \cdots \varphi(\delta_k \mathbf{x}) = \varphi(\delta_{\pi(0)} \mathbf{x}) \cdots \varphi(\delta_{\pi(k)} \mathbf{x})$ for any permutation π of $\{0, \ldots, k\}$. However, if the multiplication in H is "non-commutative enough" we expect $\widetilde{\varphi}$ to be injective.

A Free Construction. Many choices for H are possible, but intuitively it makes sense to use the "most general object" for H. The mathematically rigorous approach is to use the *free algebra over* $\mathbb{R}^d$ and we give a summary in Appendix B. Despite this abstract motivation, the algebra H has a concrete form: it is realized as a sequence of tensors in $\mathbb{R}^d$ of increasing degree, and is defined by

$$H := \{\mathbf{v} = (\mathbf{v}_0, \mathbf{v}_1, \mathbf{v}_2, \ldots) : \mathbf{v}_m \in (\mathbb{R}^d)^{\otimes m}, \, m \in \mathbb{N}, \, \|\mathbf{v}\| < \infty\},$$

where by convention $(\mathbb{R}^d)^{\otimes 0} = \mathbb{R}$, and we describe the norm $\|\mathbf{v}\|$ in the paragraph below. For example, if $\mathbf{v} = (\mathbf{v}_m)_{m \geq 0} \in H$, then $\mathbf{v}_0$ is a scalar, $\mathbf{v}_1$ is a vector, $\mathbf{v}_2 \in (\mathbb{R}^d)^{\otimes 2}$ is a $d \times d$ matrix, and so on. The vector space structure of H is given by addition and scalar multiplication according to

$$\mathbf{v} + \mathbf{w} := (\mathbf{v}_m + \mathbf{w}_m)_{m \geq 0} \in H \quad \text{and} \quad \lambda \mathbf{v} := (\lambda \mathbf{v}_m)_{m \geq 0} \in H$$

for $\lambda \in \mathbb{R}$, and the algebra structure is given by

$$\mathbf{v} \cdot \mathbf{w} := \left(\sum_{i=0}^{m} \mathbf{v}_i \otimes \mathbf{w}_{m-i} \right)_{m \geq 0} \in H. \tag{2}$$

An Inner Product. If $e^1, \ldots, e^d$ is a basis of $\mathbb{R}^d$, then every tensor $\mathbf{v}_m \in (\mathbb{R}^d)^{\otimes m}$ can be written as

$$\mathbf{v}_m = \sum_{1 \leq i_1, \ldots, i_m \leq d} c_{i_1, \ldots, i_m} e^{i_1} \otimes \cdots \otimes e^{i_m}.$$

This allows us to define an inner product $\langle \cdot, \cdot \rangle_m$ on $(\mathbb{R}^d)^{\otimes m}$ by extending

$$\langle e^{i_1} \otimes \cdots \otimes e^{i_m}, e^{j_1} \otimes \cdots \otimes e^{j_m} \rangle_m = \left\{ \begin{array}{ll} 1 & : i_1 = j_1, \ldots, i_m = j_m, \\ 0 & : \text{otherwise.} \end{array} \right. \tag{3}$$

to $(\mathbb{R}^d)^{\otimes m}$ by linearity. This gives us an inner product on H,

$$\langle \mathbf{v}, \mathbf{w} \rangle := \sum_{m \geq 0} \langle \mathbf{v}_m, \mathbf{w}_m \rangle_m$$

such that H is a Hilbert space; in particular we get a norm $\|\mathbf{v}\| := \sqrt{\langle \mathbf{v}, \mathbf{v} \rangle}$. To sum up, the space H has a rich structure: it has a vector space structure, it has an algebra structure (a noncommutative product), and it is a Hilbert space (an inner product between elements of H gives a scalar).

Characterizing Random Walks. We have constructed a map $\widetilde{\varphi}$ that maps a sequence $\mathbf{x} \in \mathsf{Seq}(\mathbb{R}^d)$ of arbitrary length into the space H. Our aim is to apply this to the sequence of node attributes corresponding to random walks on a graph. Therefore, the expectation of $\widetilde{\varphi}$ should be able to characterize the distribution of the random walk. Formally the map $\widetilde{\varphi}$ is *characteristic* if the map $\mu \mapsto \mathbb{E}_{\mathbf{x} \sim \mu}[\widetilde{\varphi}(\mathbf{x})]$ from the space of probability measures on $\mathsf{Seq}(\mathbb{R}^d)$ into H is injective. Indeed, if the chosen lifting φ satisfies some mild conditions this holds for $\widetilde{\varphi}$; see Appendix C and [15, 56].

---

[2]There are variants of this sequence feature map, which are discussed in Appendix G.

Linear Functionals. The quantity $\mathbb{E}_{\mathbf{x}\sim\mu}[\widetilde{\varphi}(\mathbf{x})]$ characterizes the probability measure μ but is valued in the infinite-dimensional Hilbert space H. Using the inner product, we can instead consider

$$\langle \boldsymbol{\ell}, \mathbb{E}_{\mathbf{x}\sim\mu}[\widetilde{\varphi}(\mathbf{x})]\rangle \text{ for } \boldsymbol{\ell} = (\boldsymbol{\ell}_0, \boldsymbol{\ell}_1, \boldsymbol{\ell}_2, \ldots, \boldsymbol{\ell}_M, 0, \ldots) \in H \text{ and } M \geq 1 \qquad (4)$$

which is equivalent to knowing $\mathbb{E}_{\mathbf{x}\sim\mu}[\widetilde{\varphi}(\mathbf{x})]$; i.e. the set (4) characterizes μ. This is analogous to how one can use either the moment generating function of a real-valued random variable or its sequence of moments to characterize its distribution; the former is one infinite-dimensional object (a function), the latter is a infinite sequence of scalars. We extend a key insight from [56] in Section 4: a linear functional $\langle \boldsymbol{\ell}, \mathbb{E}_{\mathbf{x}\sim\mu}[\widetilde{\varphi}(\mathbf{x})]\rangle$ can be efficiently approximated without directly computing $\mathbb{E}_{\mathbf{x}\sim\mu}[\widetilde{\varphi}(\mathbf{x})]$ or storing large tensors.

The Tensor Exponential. While we will continue to keep φ arbitrary for our main results (see [56] and Appendix G for other choices), we will use the *tensor exponential* $\exp_\otimes : \mathbb{R}^d \to H$, defined by

$$\exp_\otimes(x) = \left(\frac{x^{\otimes m}}{m!}\right)_{m \geq 0},$$

as the primary example throughout this paper and in the experiments in Section 5. With this choice, the induced sequence feature map is the discretized version of a classical object in analysis, called the path signature, see Appendix C.

3 Hypo-Elliptic Diffusions

Throughout this section, we fix a labelled graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, f)$, that is $\mathcal{V}$ is a set of n nodes $\mathcal{V} = \{1, \ldots, n\}$, $\mathcal{E}$ denotes edges and $f : \mathcal{V} \to \mathbb{R}^d$ is the set of continuous node attributes[3] which map each node to an element in the vector space $\mathbb{R}^d$. Two nodes $i, j \in \mathcal{V}$ are *adjacent* if $(i, j) \in \mathcal{E}$ is an edge, and we denote this by $i \sim j$. The *adjacency matrix* A of a graph is defined by

$$A_{i,j} = \begin{cases} 1 & : i \sim j \\ 0 & : \text{otherwise.} \end{cases}$$

We use $\deg(i)$ to denote the number nodes that are adjacent to node i.

Random Walks on Graphs. Let $(B_k)_{k\geq0}$ be the simple random walk on the nodes $\mathcal{V}$ of $\mathcal{G}$, where the initial node is chosen uniformly at random. The *transition matrix* of this time-homogeneous Markov chain is

$$P_{i,j} \coloneqq \mathbb{P}(B_k = j | B_{k-1} = i) = \begin{cases} \frac{1}{\deg(i)} & : i \sim j \\ 0 & : \text{otherwise.} \end{cases}$$

Denote by $(L_k)_{k\geq0}$ the random walk lifted to the node attributes in $\mathbb{R}^d$, that is

$$L_k \coloneqq f(B_k). \qquad (5)$$

Recall that the *normalized graph Laplacian* for random walks is defined as $\mathcal{L} = I - D^{-1}A$, where D is diagonal degree matrix; in particular, the entry-wise definition is

$$\mathcal{L}_{i,j} \coloneqq \begin{cases} -\frac{1}{\deg(i)} & : i \sim j \\ 1 & : i = j \\ 0 & : \text{otherwise.} \end{cases}$$

The discrete graph diffusion equation for $U_k \in \mathbb{R}^{n\times d}$ is given by

$$U_k - U_{k-1} = -\mathcal{L}U_{k-1}, \quad U_0^{(i)} = f(i) \qquad (6)$$

where the initial condition $U_0 \in \mathbb{R}^{n\times d}$ is specified by the node attributes.[4] The probabilistic interpretation of the solution to this diffusion equation is classical and given as

$$U_k = (\mathbb{E}[L_k \mid B_0 = i])_{i=1}^n = P^k U_0. \qquad (7)$$

This allows us to compute the solution u_k using the transition matrix $P = I - \mathcal{L}$.

---

[3]The labels given by the labelled graph are called *attributes*, while the computed updates are called *features*.

[4]The attributes over all nodes are given by an $n \times d$ matrix; in particular $U_k^{(i)}$ is the i^{th} row of the matrix.

Random Walks on Algebras. We now incorporate the history of a random walker by considering the quantity

$$\mathbb{E}[\widetilde{\varphi}(\mathbf{L}_k) \,|\, B_0 = i] = \mathbb{E}[\varphi(\delta_0 \mathbf{L}) \cdots \varphi(\delta_k \mathbf{L}) \,|\, B_0 = i] \tag{8}$$

where $\mathbf{L}_k = (L_0, \dots, L_k)$. Since $\widetilde{\varphi}$ captures the whole history of the random walk $\mathbf{L}_k$ over node attributes, we expect this expectation to provide a much richer summary of the neighborhood of node i than $\mathbb{E}[L_k | B_0 = i]$. The price is however, the computational complexity, since (8) is H-valued. We first show, that analogous to (6), the quantity (8) satisfies a diffusion equation that can be computed with linear algebra. To do so, we develop a graph analogue of the hypo-elliptic Laplacian and replace the scalar entries of the matrices with entries from the algebra H.

Matrix Rings over Algebras. We first revisit the adjacency matrix $A \in \mathbb{R}^{n \times n}$ and replace it by the *tensor adjacency matrix* $\widetilde{A} = (\widetilde{A})_{i,j} \in H^{n \times n}$, that is $\widetilde{A}$ is a matrix but instead of scalar entries its entries are elements in the algebra H. The matrix A has an entry at i, j if nodes i and j are connected; $\widetilde{A}$ replaces the i, j entry with an element of H that tells us how the node attributes of i and j differ,

$$\widetilde{A}_{i,j} := \begin{cases} \varphi(f(j) - f(i)) & : i \sim j \\ 0 & : \text{otherwise.} \end{cases}$$

Matrix multiplication works for elements of $H^{n \times n}$ by replacing scalar multiplication by multiplication in H, that is $(\widetilde{B} \cdot \widetilde{C})_{i,j} = \sum_{k=1}^{n} \widetilde{B}_{i,k} \cdot \widetilde{C}_{k,j}$ for $\widetilde{B}, \widetilde{C} \in H^{n \times n}$ and $\widetilde{B}_{i,k} \cdot \widetilde{C}_{k,j}$ denotes multiplication in H as in Equation (2). For the classical adjacency matrix A, the k-th power counts the number of length k walks in the graph, so that $(A^k)_{i,j}$ is the number of walks of length k from node i to node j. We can take powers of $\widetilde{A}$ in the same way as in the classical case, where

$$(\widetilde{A}^k)_{i,j} = \sum_{\mathbf{x}} \widetilde{\varphi}(\mathbf{x}), \tag{9}$$

where the sum is taken over all length k walks $\mathbf{x} = (f(i), \dots f(j))$ from node i to node j (full details are provided in Appendix D). Since $\widetilde{\varphi}(\mathbf{x})$ characterizes each walk $\mathbf{x}$, the entry $\widetilde{A}_{i,j}^k$ can be interpreted as a summary of all walks which connect nodes i and j.

Hypo-elliptic Graph Diffusion. Similar to the tensor adjacency matrix, we define the *hypo-elliptic graph Laplacian* as the $n \times n$ matrix

$$\widetilde{\mathcal{L}} = I - D^{-1}\widetilde{A} \in H^{n \times n},$$

where D is the degree matrix embedded into $H^{n \times n}$ at tensor degree 0. The entry-wise definition is

$$\widetilde{\mathcal{L}}_{i,j} := \begin{cases} \frac{-\varphi(f(j) - f(i))}{\deg(i)} & : i \sim j \\ 1 & : i = j \\ 0 & : \text{otherwise.} \end{cases} \tag{10}$$

We can now formulate the *hypo-elliptic graph diffusion equation* for $\mathbf{v}_k \in H^n$ as

$$\mathbf{v}_k - \mathbf{v}_{k-1} = -\widetilde{\mathcal{L}}\mathbf{v}_{k-1}, \quad \mathbf{v}_0^{(i)} = \varphi(f(i)). \tag{11}$$

Analogous to the classic graph diffusion (7), the hypo-elliptic graph diffusion (11) has a probabilistic interpretation in terms of $\mathbf{L}$ as shown in Theorem 1 (the proof is given in Appendix D).

Theorem 1. *Let $k \in \mathbb{N}$, $\mathbf{L}_k = (L_0, \dots, L_k)$ be the lifted random walk from (5), and $\widetilde{P} = I - \widetilde{\mathcal{L}}$ be the tensor transition matrix. The solution to the hypo-elliptic graph diffusion equation (11) is*

$$\mathbf{v}_k = (\mathbb{E}[\widetilde{\varphi}(\mathbf{L}_k) \,|\, B_0 = i])_{i=1}^n = \widetilde{P}^k \mathbf{v}_0.$$

In the classical diffusion equation, U_k captures the concentration of the random walkers after k time steps over the nodes. In the hypo-elliptic diffusion equation, $\mathbf{v}_k$ captures summaries of random walk histories after k time steps over the nodes since $\widetilde{\varphi}(\mathbf{L}_k)$ summarizes the whole trajectory $\mathbf{L}_k = (L_0, \dots, L_k)$ and not only the endpoint L_k.

Node Features and Graph Features. Theorem 1 can then be used to compute features $\Phi(i) \in H$ for individual nodes as well as a feature $\Psi(\mathcal{G})$ for the entire graph. The former is given by i-th component $\mathbf{v}_k^{(i)}$ of the solution $\mathbf{v}_k = (\mathbf{v}_k^{(i)})_{i=1,\dots,n} \in H^n$ of Equation (11),

$$\Phi(i) := \mathbf{v}_k^{(i)} = \mathbb{E}[\widetilde{\varphi}(\mathbf{L}_k) \,|\, B_0 = i] = (\widetilde{P}^k \mathbf{v}_0)^{(i)} \in H,$$

since the random walk B chooses the starting node $B_0 = i$ uniformly at random. The latter can be computed by mean pooling the node features, which also has a probabilistic interpretation as

$$\Psi(\mathcal{G}) := \frac{1}{n} \sum_{i=1}^n \mathbf{v}_k^{(i)} = \mathbb{E}[\widetilde{\varphi}(\mathbf{L}_k)] = n^{-1}(\mathbb{1}_H^T \widetilde{P}^k \mathbf{v}_0) \in H, \tag{12}$$

where $\mathbb{1}_H^T := (1_H, \dots, 1_H) \in H^n$ is the all-ones vector in H and 1_H denotes the unit in H.

Characterizing Graphs with Random Walks. The graph and node features obtained through the hypo-elliptic diffusion equation are highly descriptive: they characterize the entire history of the random walk process if one also includes the time parametrization, as described in Appendix C.

Theorem 2. *Suppose Ψ is the graph feature map from Equation (12) induced by the tensor exponential algebra lifting including time parametrization. Let $\mathcal{G}$ and $\mathcal{G}'$ be two labelled graphs, and $\mathbf{L}_k = (L_0, \dots, L_k)$ and $\mathbf{L}_k' = (L_0', \dots, L_k')$ be the k-step lifted random walk as defined in Equation (5). Then, $\Psi(\mathcal{G}) = \Psi(\mathcal{G}')$ if and only if the distributions of $\mathbf{L}_k$ and $\mathbf{L}_k'$ are equal.*

An analogous result holds for the node features, and we prove both results in Appendix E. While we use the tensor exponential in this article, many other choices of $\widetilde{\varphi}$ are possible and result in graph and node features with such properties: under mild conditions, if the algebra lifting $\varphi : \mathbb{R}^d \to H$ characterizes measures on $\mathbb{R}^d$, the resulting node feature map Φ characterizes the random walk, see [56], which in turn implies the above results. Possible variations are discussed in Appendix G.

General (Hypo-elliptic) Diffusions and Attention. One can consider more general diffusion operators, such as the normalized Laplacian $\mathcal{K}$ of a weighted graph. We define its lifted operator $\widetilde{\mathcal{K}} \in H^{n \times n}$ analogous to Equation (10), resulting in a generalization of Theorem 1 with $\widetilde{\mathcal{K}}$ replacing $\widetilde{\mathcal{L}}$. In the flavour of convolutional GNNs [8], we consider a weighted adjacency matrix $A \in \mathbb{R}^{n \times n}$

$$A_{i,j} = \begin{cases} c_{i,j} & : i \sim j \\ 0 & : \text{otherwise}, \end{cases}$$

for $c_{i,j} > 0$. The corresponding normalized Laplacian $\mathcal{K}$ is given by $\mathcal{K} = I - D^{-1}A$, where D is a diagonal matrix with $D_{i,i} = \sum_{j \in \mathcal{N}(i)} c_{i,j}$. A common way to learn the coefficients is by introducing parameter sharing across graphs by modelling them as $c_{i,j} = \exp(a(f(i), f(j)))$ using a local attention mechanism, $a : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}$ [59]. In our implementation, we use additive attention [4] given by $a(f(i), f(j)) = \text{LeakyRelu}_{0.2}(W_s f(i) + W_t f(j))$, where $W_s, W_t \in \mathbb{R}^{1 \times d}$ are linear transformations for the source and target nodes, but different attention mechanisms can also be used; e.g. scaled dot-product attention [58]. Then, the corresponding transition matrix $P = D^{-1}A$ is defined as $P_{ij} = \text{softmax}_{k \in \mathcal{N}(i)}(a(f(i), f(k)))_j$. The lifted transition matrix is defined as

$$\widetilde{P} = \begin{cases} P_{i,j} \varphi(f(j) - f(i)) & : i \sim j \\ 0 & : \text{otherwise}. \end{cases}$$

The statements of Theorem 1 immediately generalize to this variation by replacing the expectation with respect to a non-uniform random walk. Hence, in this case the use of attention can be interpreted as learning the transition probabilities of a random walk on the graph.

4 Efficient Algorithms for Deep Learning

We now focus on the computation of linear maps of $\Phi(i)$ defined as $Q : H \to \mathbb{R}^{d'}$, $\Phi(i) \mapsto (\langle \boldsymbol{\ell}^j, \Phi(i) \rangle)_{j=1,\dots,d'}$ for $\boldsymbol{\ell}^j = (\ell_0^j, \ell_1^j, \dots, \ell_M^j, 0, 0, \dots) \in H$. These maps capture the distribution of the random walk $\mathbf{L}_k$ conditioned to start at node i and pooling them captures the graph as seen by the random walk, see Section 3. These linear maps are parametrized by $\boldsymbol{\ell}^j$ which we view as

learnable parameters of our model and hence, requires efficient computation. For any ℓ, we could compute $\langle \ell, \Phi(i) \rangle$ by first evaluating $\Phi(i)$ using linear algebra by Theorem 1 and subsequently taking their inner product with ℓ. However, this involves computations with high-degree tensors, which makes this approach not scalable. In this section, we leverage ideas about tensor decompositions to design algorithms to compute $\langle \ell, \Phi(i) \rangle$ efficiently [56]; in particular, we do not need to compute $\Phi(i) \in H$ directly or store large tensors.

Computing a Rank-1 Functional. First, we focus on a *rank*-1 linear functional $\ell \in H$ given as

$$\ell = (\ell_m)_{m \geq 0} \text{ with } \ell_m = u_{M-m+1} \otimes \cdots \otimes u_M \text{ and } \ell_m = 0 \text{ for } m > M, \tag{13}$$

where $u_m \in \mathbb{R}^d$ for $m = 1, \ldots, M$ for a fixed $M \geq 1$. Theorem 3 shows that for such ℓ, the computation of $\langle \ell, \Phi(i) \rangle$ can be done (a) efficiently by factoring this low-rank structure into the recursive computation, and (b) simultaneously for all nodes $i \in \mathcal{V}$ in parallel. This can then be used to compute rank-R functionals for $R > 1$, see Appendix F.

Theorem 3. *Let ℓ be as in* (13) *and define $f_{k,m} \in \mathbb{R}^n$ for $m = 1, \ldots, M$ as*

$$f_{1,m} := \frac{1}{m!} \left(P \odot C^{u_{M-m+1}} \odot \cdots \odot C^{u_M} \right) \cdot \mathbb{1},$$

where $\mathbb{1}^T := (1, \ldots, 1) \in \mathbb{R}^n$ is the all-ones vector; and for $2 \leq k$ and $1 \leq m \leq M$ recursively as

$$f_{k,m} := P \cdot f_{k-1,m} + \sum_{r=1}^{m} \frac{1}{r!} \left(P \odot C^{u_{M-m+1}} \odot \cdots \odot C^{u_{M-m+r}} \right) \cdot f_{k-1,m-r}, \tag{14}$$

where the matrix $C^u = (C^u_{i,j}) \in \mathbb{R}^{n \times n}$ is defined as

$$C^u_{i,j} := \begin{cases} \langle u, f(j) - f(i) \rangle & : i \sim j, \\ 0 & : otherwise. \end{cases}$$

and $\odot$ denotes element-wise[5] multiplication, while $\cdot$ denotes matrix multiplication. Then, it holds for $i \in \mathcal{V}$, random walk length $k \in \mathbb{Z}_+$, and tensor degree $m = 1, \ldots, M$, that

$$f_{k,m}(i) = \langle \ell_m, \Phi_k(i) \rangle.$$

Remark 1. Overall, Eq. (14) computes $f_{k,m}(i)$ for all $i \in \mathcal{V}$, $k = 1, \ldots, K$, $m = 1, \ldots, M$ in $O(K \cdot M^2 \cdot N_E + M \cdot N_E \cdot d)$ operations, where $N_E \in \mathbb{N}$ denotes the number of edges; see App. F.

Building Neural Networks. Given an algorithm to compute rank-1 functionals of $\Phi(i)$, we proceed in the following steps to build neural network models: (1) given a random walk length $k \in \mathbb{N}$, max tensor degree $M \in \mathbb{N}$ and max tensor rank $R \in \mathbb{N}$, we introduce R rank-1 degree-M functionals $\tilde{\ell}_M^j$, and compute $f_{k,m}^j(i)$ for all $j = 1, \ldots, R$ and $m = 1, \ldots, M$ using Theorem 3 that gives a linear mapping between $H \to \mathbb{R}^{RM}$. (2) Apply a linear mixing layer $\mathbb{R}^{RM} \to \mathbb{R}^R$ to the rank-1 functionals to recover at most rank-R functionals. Update the node labels, which now incorporate neighbourhood information up to hop-k. (3) Iterate this construction by repeating steps (1) and (2).

The drawback of using at most rank-R functionals is a loss of expressiveness: not all linear functionals of tensors can be represented as rank-R functionals if R is not large enough. However, we hypothesize that iterations of low-rank functionals allows to approximate any general linear functional as in [56]. Further, this has a probabilistic interpretation, where instead of considering one long random walk we use a random walk over random walks, increasing the effective random walk length additively.

5 Experiments

We implemented the above approach and call the resulting model **Graph2Tens Networks** since it represents the neighbourhood of a node as a sequence of tensors, which is further pushed through a low-tensor-rank constrained linear mapping, similarly to how neural networks linearly transform their inputs pre-activation. A conceptual difference is that in our case the non-linearity is applied first and the projection secondly, albeit the computation is coupled between these steps.

---

[5]For example $\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \odot \begin{bmatrix} 5 & 6 \\ 7 & 8 \end{bmatrix} = \begin{bmatrix} 5 & 12 \\ 21 & 32 \end{bmatrix}$.

Experimental Setup. The aim of our main experiment is to test the following key properties of our model: (1) ability to capture long-range interactions between nodes in a graph, (2) robustness to pooling operations, hence making it less susceptible to the "over-squashing" phenomenon [2]. We do this by following the experiments in [64]. In particular, we show that our model is competitive with previous approaches for retaining long-range context in graph-level learning tasks but without computing all pairwise interactions between nodes, thus keeping the influence distribution localized [67]. We further give a detailed ablation study to show the robustness of our model to various architectural choices, and compare different variations on the algorithm from App. G. As a second experiment, we follow the previous applications of diffusion approaches to graphs that have mostly considered inductive learning tasks, e.g. on the citation datasets [12, 54, 10]. Our experimentation on these datasets are available in Appendix H.3, where the model performs on par with short-range GNN models, but does not seem to benefit from added long-range information.

Datasets. We use two biological graph classification datasets (NCI1 and NCI109), that contain around ~4000 biochemical compounds represented as graphs with ~30 nodes on average [61, 1]. The task is to predict whether a compound contains anti-lung-cancer activity. The dataset is split in a ratio of $80\% - 10\% - 10\%$ for training, validation and testing. Previous work [2] has found that GNNs that only summarize local structural information can be greatly outperformed by models that are able to account for global contextual relationships through the use of *fully-adjacent* layers. This was further improved on by [64], where a local neighbourhood encoder consisting of a GNN stack was upgraded with a Transformer submodule [58] for learning global interactions.

Model Details. We build a GNN architecture primarily motivated by the GraphTrans (small) model from [64], and only fine-tune the pre- and postprocessing layers(s), random walk length, functional degree and optimization settings. In detail, a preprocessing MLP layer with 128 hidden units is followed by a stack of 4 `G2TN` layers each with RW length-5, max rank-128, max tensor degree-2, all equipped with JK-connections [67] and a max aggregator. Afterwards, the node features are combined into a graph-level representation using gated attention pooling [39]. The pooled features are transformed using a final MLP layer with 256 hidden units, and then fed into a softmax classification layer. The pre- and postprocessing MLP layers employ skip-connections [28]. Both MLP and `G2TN` layers are followed by layer normalization [3], where GTN layers normalize their rank-1 functionals independently across different tensor degrees, which corresponds to a particular realization of group normalization [63]. We randomly drop 10% of the features for all hidden layers during training [52]. The attentional variant, `G2T(A)N` also randomly drops 10% of its edges and uses 8 attention heads [59]. Training is performed by minimizing the categorical cross-entropy loss with an ℓ_2 regularization penalty of 10^{-4}. For optimization, Adam [30] is used with a batch size of 128 and an inital learning rate of 10^{-3} that is decayed via a cosine annealing schedule [40] over 200 epochs. Further intuition about the model and architectural choices are available in Appendix H.1.

Baselines. We compare against (1) the baseline models reported in [64], (2) variations of Graph-Trans, (3) other recently proposed hierarchical approaches for long-range graph tasks [47]. Groups of models in Table 1 are separated by dashed lines if they were reported in separate papers, and the first citation after the name is where the result first appeared. The number of GNN layers in HGNet are not discussed by [47], and we report it as implied by their code. We organize the models into three groups divided by solid lines: (a) baselines that only apply neighbourhood aggregations, and hierarchical or global pooling schemes, (b) baselines that first employ a local neighbourhood encoder, and afterwards fully densify the graph in one way or another so that all nodes interact with each other *directly*, (c) our models that we emphasize thematically belong to (a).

Results. In Table 1, we report the mean and standard deviation of classification accuracy computed over 10 different seeds. Overall, both our models improve over all baselines in group (a) on both datasets, maximally by 1.9% on NCI1 and by 4.8% on NCI109. In group (b), `G2T(A)N` is solely outperformed by GraphTrans (large) on NCI1 by only 0.7%. Interestingly, the attention-free variation, `G2TN` , performs better on NCI109, where it performs very slightly worse than GraphTrans (small).

Ablation Study. Further to using attention, we give a list of ideas for variations on our models in Appendix G, which can be summarized briefly as: (i) using increments of node attributes (`Diff`), (ii) preprending a zero point to sequences (`ZeroStart`), (iii) optimizing over the algebra embedding (`AlgOpt`), all of which are built into our main models. Further, the previous architectural choices

Table 1: Comparison of classification accuracies on NCI biological datasets, where we report mean and standard deviation over 10 random seeds for our models.

Model	GNN Type	GNN Count	NCI1 (%)	NCI109 (%)
Set2Set [38, 60]	GCN	3	68.6 ± 1.9	69.8 ± 1.2
SortPool [38, 69]	GCN	3	73.8 ± 1.0	74.0 ± 1.2
SAGPool$_h$ [38]	GCN	3	67.5 ± 1.1	67.9 ± 1.4
SAGPool$_g$ [38]	GCN	3	74.2 ± 1.2	74.1 ± 0.8
GIN [20, 66]	GIN	8	80.0 ± 1.4	-
GCN + VN [68, 23]	GCN	2	71.5	-
HGNet-EdgePool [68, 50]	GCN+RGCN	$3 + 2$	77.1	-
HGNet-Louvain [68, 50]	GCN+RGCN	$3 + 2$	75.1	-
GIN + FA [2, 66]	GIN	8	81.5 ± 1.2	-
GraphTrans (small) [64, 58]	GCN	3	81.3 ± 1.9	79.2 ± 2.2
GraphTrans (large) [64, 58]	GCN	4	82.6 ± 1.2	82.3 ± 2.6
G2T(A)N (ours)	G2T(A)N	4	$\mathbf{81.9 \pm 1.2}$	78.0 ± 2.3
G2TN (ours)	G2TN	4	80.7 ± 2.5	$\mathbf{78.9 \pm 2.5}$

Table 2: Accuracies computed over 5 seeds of G2T(A)N ablated by changing a single option.

Dataset	NoDiff	NoZeroStart	NoAlgOpt	NoJK	NoSkip	NoNorm	AvgPool
NCI1	80.1 ± 0.7	79.5 ± 1.8	81.6 ± 1.6	82.1 ± 1.8	81.8 ± 0.9	81.6 ± 1.5	82.4 ± 0.9
NCI109	78.2 ± 1.2	77.7 ± 1.8	77.5 ± 1.3	77.6 ± 1.2	78.3 ± 1.3	79.8 ± 1.4	77.6 ± 1.3

aimed at incorporating several commonly used tricks for training GNNs. We investigate the effect of the previous variations and ablate the architectural "tricks" by measuring the performance change resulting from ceteris paribus removing it. Table 2 shows the result for G2T(A)N . To summarize the main observations, the model is robust to all the architectural changes, removing the layer norm even improves on NCI109. Importantly, replacing the attention pooling with mean pooling does not significantly affect the performance, but actually slightly improves on NCI1. Regarding variations, AlgOpt slightly improves on both datasets, while removing Diff and ZeroStart significantly degrades the accuracy on NCI1. The latter means that translations of node attributes are important, not just their distances. We give further discussions and ablations in Appendix H.2 including G2TN .

Discussion. The previous experiments demonstrate that our approach performs very favourably on long-range reasoning tasks compared to GNN-based alternatives without global pairwise node interactions. Several of the works we compare against have focused on extending GNNs to larger neighbourhoods by specifically designed graph coarsening and pooling operations, and we emphasize two important points: (1) our approach can efficiently capture large neighbourhoods without any need for coarsening, (2) it already performs well with simple mean-pooling as justified by Theorem 2 and experimentally supported by the ablations. Although the Transformer-based GraphTrans slightly outperforms our model potentially due to its ability to learn global interactions, it is not entirely clear how much of the global graph structure it is able to infer from interactions of short-range neighbourhood summaries. Intuitively, better and larger summaries should also help the Transformer submodule to make inference about questions regarding the global structure. Finally, Transformer models can be bottlenecked by their quadratic complexity in nodes, while our approach only scales with edges, and hence, it can be more favourable for large sparse graphs in terms of computations.

6 Conclusion

Inspired by classical results from analysis [22], we introduce the hypo-elliptic graph Laplacian. This yields a diffusion equation and also generalizes its classical probabilistic interpretation via random walks but now takes their history into account. In addition to several attractive theoretical guarantees, we provide scalable algorithms. Our experiments show that this can lead to largely improved baselines for long-range reasoning tasks. A promising future research theme is to develop improvements for the classical Laplacian in this hypo-elliptic context; this includes lazy random walks [65]; nonlinear diffusions [11]; and source/sink terms [54]. Another theme could be to extend the geometric study [55] of over-squashing to this hypo-elliptic point of view which is naturally tied to sub-Riemannian geometry [53].

References

[1] Pubchem. `https://pubchem.ncbi.nlm.nih.gov/`.

[2] Uri Alon and Eran Yahav. On the bottleneck of graph neural networks and its practical implications. In *International Conference on Learning Representations*, 2021.

[3] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[4] Dzmitry Bahdanau, Kyung Hyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *3rd International Conference on Learning Representations, ICLR 2015*, 2015.

[5] Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, et al. Interaction networks for learning about objects, relations and physics. *Advances in neural information processing systems*, 29, 2016.

[6] Patric Bonnier, Chong Liu, and Harald Oberhauser. Adapted topologies and higher rank signatures. *arXiv preprint arXiv:2005.08897*, 2020.

[7] Karsten Borgwardt, Elisabetta Ghisu, Felipe Llinares-López, Leslie O'Bray, and Bastian Rieck. Graph kernels: State-of-the-art and future challenges. *arXiv preprint arXiv:2011.03854*, 2020.

[8] Michael M. Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric Deep Learning: Grids, Groups, Graphs, Geodesics, and Gauges. *arXiv:2104.13478 [cs, stat]*, May 2021.

[9] Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral networks and locally connected networks on graphs. *arXiv preprint arXiv:1312.6203*, 2013.

[10] Benjamin Paul Chamberlain, James Rowbottom, Davide Eynard, Francesco Di Giovanni, Xiaowen Dong, and Michael M. Bronstein. Beltrami flow and neural diffusion on graphs. *CoRR*, abs/2110.09443, 2021.

[11] Benjamin Paul Chamberlain, James Rowbottom, Maria I. Gorinova, Stefan D. Webb, Emanuele Rossi, and Michael M. Bronstein. GRAND: Graph Neural Diffusion. In *The Symbiosis of Deep Learning and Differential Equations*, September 2021.

[12] Benjamin Paul Chamberlain, James R. Rowbottom, Maria I. Gorinova, Stefan Webb, Emanuele Rossi, and Michael M. Bronstein. Grand: Graph neural diffusion. In *ICML*, 2021.

[13] Dexiong Chen, Laurent Jacob, and Julien Mairal. Convolutional kernel networks for graph-structured data. In *International Conference on Machine Learning*, pages 1576–1586. PMLR, 2020.

[14] Zhengdao Chen, Soledad Villar, Lei Chen, and Joan Bruna. On the equivalence between graph isomorphism testing and function approximation with gnns. *Advances in neural information processing systems*, 32, 2019.

[15] Ilya Chevyrev and Harald Oberhauser. Signature moments to characterize laws of stochastic processes. *arXiv:1810.10971 [math, stat]*, 2018.

[16] Thomas Cochrane, Peter Foster, Varun Chhabra, Maud Lemercier, Terry Lyons, and Cristopher Salvi. Sk-tree: a systematic malware detection algorithm on streaming trees via the signature kernel. In *2021 IEEE International Conference on Cyber Security and Resilience (CSR)*, pages 35–40. IEEE, 2021.

[17] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. *Advances in neural information processing systems*, 29, 2016.

[18] Persi Diaconis. Group representations in probability and statistics. *Lecture notes-monograph series*, 11:i–192, 1988.

[19] Ahmed A. A. Elhag, Gabriele Corso, Hannes Stärk, and Michael M. Bronstein. Graph anisotropic diffusion, 2022.

[20] Federico Errica, Marco Podda, Davide Bacciu, and Alessio Micheli. A fair comparison of graph neural networks for graph classification. In *International Conference on Learning Representations*, 2019.

[21] Michel Fliess. Fonctionnelles causales non linéaires et indéterminées non commutatives. *Bulletin de la société mathématique de France*, 109:3–40, 1981.

[22] Bernard Gaveau. Principe de moindre action, propagation de la chaleur et estimees sous elliptiques sur certains groupes nilpotents. *Acta Mathematica*, 139(none):95–153, January 1977.

[23] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pages 1263–1272. PMLR, 2017.

[24] Alexander Grigoryan. *Heat kernel and analysis on manifolds*, volume 47. American Mathematical Soc., 2009.

[25] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 855–864, 2016.

[26] Ben Hambly and Terry Lyons. Uniqueness for the signature of a path of bounded variation and the reduced path group. *Ann. of Math.*, 171(1):109–167, 2010.

[27] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017.

[28] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[29] Lars Hörmander. Hypoelliptic second order differential equations. *Acta Mathematica*, 119:147–171, 1967.

[30] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

[31] Thomas Kipf and Max Welling. Semi-Supervised Classification with Graph Convolutional Networks. In *International Conference on Learning Representations*, 2017.

[32] Franz J. Kiraly and Harald Oberhauser. Kernels for sequentially ordered data. *J. Mach. Learn. Res.*, 20(31):1–45, 2019.

[33] Johannes Klicpera, Stefan Weissenberger, and Stephan Günnemann. Diffusion improves graph learning. *ArXiv*, abs/1911.05485, 2019.

[34] Risi Kondor. Diffusion kernels on graphs and other discrete structures. In *ICML 2002*, 2002.

[35] Yann LeCun, Yoshua Bengio, et al. Convolutional networks for images, speech, and time series. *The handbook of brain theory and neural networks*, 3361(10):1995, 1995.

[36] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[37] Darrick Lee and Robert Ghrist. Path Signatures on Lie Groups. *arXiv:2007.06633 [cs, math, stat]*, 2020.

[38] Junhyun Lee, Inyeop Lee, and Jaewoo Kang. Self-attention graph pooling. In *International conference on machine learning*, pages 3734–3743. PMLR, 2019.

[39] Yujia Li, Richard Zemel, Marc Brockschmidt, and Daniel Tarlow. Gated graph sequence neural networks. In *Proceedings of ICLR'16*, 2016.

[40] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *ICLR*, 2017.

[41] Haggai Maron, Heli Ben-Hamu, Hadar Serviansky, and Yaron Lipman. Provably powerful graph networks. *Advances in neural information processing systems*, 32, 2019.

[42] Ron Milo, Shai S. Shen-Orr, Shalev Itzkovitz, Nadav Kashtan, Dmitri B. Chklovskii, and Uri Alon. Network motifs: simple building blocks of complex networks. *Science*, 298 5594:824–7, 2002.

[43] Federico Monti, Davide Boscaini, Jonathan Masci, Emanuele Rodola, Jan Svoboda, and Michael M Bronstein. Geometric deep learning on graphs and manifolds using mixture model cnns. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5115–5124, 2017.

[44] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and Leman Go Neural: Higher-Order Graph Neural Networks. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):4602–4609, July 2019.

[45] Giannis Nikolentzos and Michalis Vazirgiannis. Random walk graph neural networks. *Advances in Neural Information Processing Systems*, 33:16211–16222, 2020.

[46] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 701–710, 2014.

[47] Ladislav Rampášek and Guy Wolf. Hierarchical graph neural nets can capture long-range interactions. In *2021 IEEE 31st International Workshop on Machine Learning for Signal Processing (MLSP)*, pages 1–6. IEEE, 2021.

[48] Linda Preiss Rothschild and Elias M. Stein. Hypoelliptic differential operators and nilpotent groups. *Acta Mathematica*, 137:247–320, 1976.

[49] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

[50] Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *European semantic web conference*, pages 593–607. Springer, 2018.

[51] Alice C Schwarze and Mason A Porter. Motifs for processes on networks. *SIAM Journal on Applied Dynamical Systems*, 20(4):2516–2557, 2021.

[52] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

[53] Robert S Strichartz. Sub-riemannian geometry. *Journal of Differential Geometry*, 24(2):221–263, 1986.

[54] Matthew Thorpe, Tan Minh Nguyen, Hedi Xia, Thomas Strohmer, Andrea Bertozzi, Stanley Osher, and Bao Wang. GRAND++: Graph neural diffusion with a source term. In *International Conference on Learning Representations*, 2022.

[55] Jake Topping, Francesco Di Giovanni, Benjamin Paul Chamberlain, Xiaowen Dong, and Michael M. Bronstein. Understanding over-squashing and bottlenecks on graphs via curvature, 2021.

[56] Csaba Toth, Patric Bonnier, and Harald Oberhauser. Seq2Tens: An Efficient Representation of Sequences by Low-Rank Tensor Projections. In *International Conference on Learning Representations*, 2021.

[57] N Th Varopoulos. Analysis and geometry on groups. *Cambridge Tracts in Math.*, 100, 1992.

[58] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[59] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018.

[60] Oriol Vinyals, Samy Bengio, and Manjunath Kudlur. Order matters: Sequence to sequence for sets. In *ICLR*, 2016.

[61] Nikil Wale, Ian A. Watson, and George Karypis. Comparison of descriptor spaces for chemical compound retrieval and classification. *Knowledge and Information Systems*, 14(3):347–375, March 2008.

[62] Wolfgang Woess. *Random Walks on Infinite Graphs and Groups*. Cambridge Tracts in Mathematics. Cambridge University Press, Cambridge, 2000.

[63] Yuxin Wu and Kaiming He. Group normalization. In *Proceedings of the European conference on computer vision (ECCV)*, pages 3–19, 2018.

[64] Zhanghao Wu, Paras Jain, Matthew Wright, Azalia Mirhoseini, Joseph E Gonzalez, and Ion Stoica. Representing long-range context for graph neural networks with global attention. *Advances in Neural Information Processing Systems*, 34:13266–13279, 2021.

[65] Louis-Pascal A. C. Xhonneux, Meng Qu, and Jian Tang. Continuous graph neural networks. In *Proceedings of the 37th International Conference on Machine Learning*, ICML'20, pages 10432–10441. JMLR.org, July 2020.

[66] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *International Conference on Learning Representations*, 2019.

[67] Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken-ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In *International Conference on Machine Learning*, pages 5453–5462. PMLR, 2018.

[68] Rex Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L. Hamilton, and Jure Leskovec. Hierarchical graph representation learning with differentiable pooling. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pages 4805–4815, Red Hook, NY, USA, December 2018. Curran Associates Inc.

[69] Muhan Zhang, Zhicheng Cui, Marion Neumann, and Yixin Chen. An end-to-end deep learning architecture for graph classification. In *Thirty-second AAAI conference on artificial intelligence*, 2018.