EYELIGNR: Aligning Gaze and Text via Contrastive Learning for Improved Reading Scanpath Prediction

Abstract

One of the main challenges for scanpath prediction is the joint modeling of gaze and language. Existing scanpath predictors either leverage language in ways that fail to respect the temporal progression of reading or ignore linguistic structure altogether, and their effectiveness is further constrained by the scarcity and heterogeneity of available eye-tracking data. To remedy these issues, we introduce EYELIGNR, a framework that integrates language into spatiotemporal scanpath prediction at the representation level. EYELIGNR adapts language representations to fixation order and aligns gaze and text in a shared embedding space through contrastive learning. Experiments on five reading corpora, including educational datasets, show that EYELIGNR consistently outperforms the prior state of the art and generalizes well across reading conditions, with improvements on multiple scanpath metrics (e.g., up to NLD ∼57%, NLL ∼27%, and FLA ∼59%).

1 Introduction

Scanpaths are sequences of eye movements over visual stimuli, and when recorded on text, they provide evidence of reading behavior. These data capture three aspects that come together in human text processing (Kintsch, 1992, 1994): the linguistic features of the text (e.g., lexical and semantic properties), the spatial trajectories of the eyes (e.g., forward and backward movements), and the temporal unfolding of those movements (e.g., order and duration of word fixations). Accordingly, the task of *scanpath prediction* aims to estimate the sequence of word fixations during reading, and it has become an important testbed for research in several areas of natural language processing (NLP), including entity recognition (Hollenstein and Zhang, 2019), text summarization (Wu et al., 2021), and paraphrase detection (Khurana et al., 2023). To date, however, jointly modeling the linguistic, spatial, and temporal aspects of reading remains difficult.

Figure 1: Modeling the linguistic, spatial, and temporal dimensions of reading under data scarcity. Fixation-ordered language and gaze embeddings, including fixation duration, are obtained via masked language modeling and aligned contrastively for scanpath prediction.

Researchers have explored several methods to equip scanpath models with linguistic information (Deng et al., 2024; Bolliger et al., 2025). These methods typically align gaze encodings with pretrained language representations by mapping the sequence of fixations (e.g., "Sally to the store went") onto a canonical left-to-right textual order ("Sally went to the store"). In doing so, they fail to capture the actual progression of reading, including nonlinear phenomena like word skipping or backtracking. The temporal dynamics of eye movements have not been fully exploited either: most studies consider only word fixation order while overlooking duration (Deng et al., 2023; Bolliger et al., 2023), which is a key signal of human attentional allocation and language understanding. Lastly, data scarcity poses additional challenges (Stebakov and Pershin, 2025). Training robust predictors requires large eye-tracking data, but such data are collected under varying experimental protocols, making standardization difficult and limiting the models' generalization abilities.

Recent work has begun to address (part of) these problems with ScanEZ, an architecture that explicitly includes fixation duration into gaze representations, and that mitigates data scarcity through self-supervised modeling (Sood et al., 2025). Notably,

ScanEZ achieves state-of-the-art results on scan-path prediction without using any linguistic input, raising the question of whether language information can further improve downstream performance. We address this question here by expanding on the modeling approach of ScanEZ with a principled integration of gaze and text.

This paper presents EYELIGNR, a contrastive gaze–text alignment framework for spatiotemporal scanpath prediction. EYELIGNR constructs textual representations that preserve the temporal sequence of reading by adapting a pretrained language encoder with masked language modeling (MLM) on fixation-ordered token sequences. The architecture combines this adapted language encoder with a Transformer-based encoder for eye movements, learning a shared multimodal embedding space through contrastive training. This design models spatial trajectories, temporal dynamics (including fixation duration) and linguistic context within a unified framework (cf. Figure 1). The self-supervised pretraining and contrastive multimodal alignment further enable EYELIGNR to effectively learn dataset-agnostic gaze–text representations and remain robust to limited and heterogeneous eye-tracking data.

In sum, we advance scanpath prediction with:

(1) a language representation strategy based on MLM that fine-tunes a pretrained encoder on fixation-ordered token sequences;

(2) a contrastive gaze–text alignment approach that injects linguistic information into spatiotemporal scanpath representations.

Based on these contributions, we test the hypothesis that gaze-informed text embeddings improve downstream performance. We show that this is indeed the case: our approach surpasses models that use no language representations (scanpath metrics increase by as much as 58%) or assume a canonical left-to-right textual order (82%). The gains hold consistently on five datasets spanning laboratory and educational reading settings, proving that EYELIGNR generalizes across reading conditions.

2 Related Work

A growing body of research in NLP uses eye movements during reading, either as prediction targets (Li and Rudzicz, 2021; Srivastava, 2022) or auxiliary supervisory signals for downstream tasks (Bondar et al., 2025; Barrett and Hollenstein, 2020). Still, leveraging gaze representations poses two related challenges.

First, Data Scarcity. Limited eye-tracking data constrain the scalability of scanpath models, especially in the absence of standardized evaluation protocols. Shubi et al. (2025) address this gap by introducing EyeBench, a benchmark for predictive modeling from gaze which harmonizes datasets and task generalization regimes; Stebakov and Pershin (2025) tackle a complementary problem with a unified evaluation framework that benchmarks existing models across datasets, reading conditions, and psycholinguistic phenomena. Beyond evaluation-focused efforts, the use of synthetic scanpaths has emerged as a promising response to the data scarcity bottleneck. In particular, ScanEZ (Sood et al., 2025) proposes pretraining on scanpaths generated from the cognitively grounded reading model E-Z Reader (Reichle et al., 2003), before fine-tuning on smaller human eye-tracking data. By framing scanpath prediction as a self-supervised sequence modeling problem, ScanEZ learns continuous spatiotemporal fixation trajectories via a masked reconstruction objective, without reliance on large labeled datasets.

Second, Language-Gaze Alignment. Researchers typically address the mismatch between sentence order and the order of reading fixations at the architectural level. For instance, Eyettention encodes the stimulus text in the left-to-right sentence order and the scanpath following the reading order, aligning the two streams via local cross-attention to predict the next fixation (Deng et al., 2023). ScanDL and ScanDL 2.0 (Bolliger et al., 2023, 2025) formulate scanpath generation as a diffusion process conditioned on the stimulus sentence, using frozen pretrained BERT embeddings as textual conditioning while learning gaze dynamics in a joint embedding space. In these models, language representations remain fixed and are aligned to gaze through attention mechanisms or embedding reindexing, limiting their ability to model reading-order-specific language-gaze interactions.

In this work, we retain ScanEZ's Transformer-based encoder for spatiotemporal gaze modeling and its masked fixation reconstruction objective for self-supervised learning. We augment ScanEZ with language through contrastive learning, as a data-efficient alternative to sequence-level supervision, proven effective for constructing multimodal gaze

representations (Jindal and Manduchi, 2023; Zhao et al., 2024). Crucially, we shift the focus from the architectural level to the representation level. Rather than aligning frozen textual embeddings through attention mechanisms or token reindexing, we directly obtain a reading-aware text embedding space by fine-tuning the language encoder parameters on fixation-ordered token sequences.

3 Task Definition and the EYELIGNR Architecture

A scanpath consists of a sequence of fixations over a text, such as a page or stimuli at other textual levels, depending on the dataset (Deng et al., 2023). Each fixation is represented by a triplet (x, y, t), where x and y denote the continuous spatial coordinates of the fixation location and t denotes the fixation duration (the temporal order of reading is given, implicitly, by the order of fixations in the sequence). We formulate scanpath prediction as a masked sequence modeling task: given a partially masked scanpath, the model predicts the (x, y, t) values of the masked fixations.

To conduct this task, we build EYELIGNR around three main components: an encoder to process eye-movement sequences, an encoder to process text, and a component for contrastive learning.

Eye-Movement Encoder. We represent gaze sequences using the Transformer-based encoder of ScanEZ. This encoder processes input sequences of shape (B, T, D), where B is the batch size, T is the sequence length (up to 200 fixations), and D is the feature dimensionality (i.e., 3 dimensions corresponding to the spatiotemporal coordinates x, y, t). To handle variable-length sequences, we use attention masking that prevents the model from attending to padded positions.

Language Encoder. For text encoding, we use a pretrained RoBERTa-base model (Liu et al., 2019). The model outputs contextualized representations for each token in an input sequence of shape (B, S, H), where S is the sequence length (up to 512 tokens) and H is the hidden dimension (768).

Contrastive Component (Sequence Pooling and Projection Heads). Similar to Radford et al. (2021), we aggregate variable-length sequences into fixed-size representations using masked mean pooling. For the ScanEZ encoder output:

$$\mathbf{z}_{\text{limu}} = \frac{\sum_{t=1}^{T} m_t \mathbf{h}_t}{\sum_{t=1}^{T} m_t} \tag{1}$$

where $\mathbf{h}_t$ is the hidden state at time step t and $m_t \in \{0, 1\}$ is the corresponding mask value. Similarly, for the language encoder:

$$\mathbf{z}_{\text{text}} = \frac{\sum_{s=1}^{S} a_s \mathbf{h}_s}{\sum_{s=1}^{S} a_s} \tag{2}$$

where $a_s \in \{0, 1\}$ indicates whether token s is part of the actual text (not padding). Further, we use linear layers that map pooled representations into a shared 512-dimensional embedding space:

$$\mathbf{e}_{\text{limu}} = \text{normalize}(W_{\text{limu}} \mathbf{z}_{\text{limu}}) \tag{3}$$
$$\mathbf{e}_{\text{text}} = \text{normalize}(W_{\text{text}} \mathbf{z}_{\text{text}}) \tag{4}$$

where "normalize" is L2-normalization to the unit hypersphere. The projection heads are discarded after contrastive training.

4 Training Pipeline

We now detail the construction of fixation-ordered text representations that preserve the temporal order in which words are read, and the use of these representations within our training framework (additional details are in Appendix A.1).

4.1 Fixation-Order Encoding

For each eye movement sequence, we construct a fixation-ordered text representation by reordering the tokens according to the temporal sequence of fixations in the scanpath. Given a text with tokens $w_1, w_2, \ldots, w_n$ in left-to-right order and a scanpath with fixations at positions $p_1, p_2, \ldots, p_m$, we create the fixation-ordered sequence: $T_{\text{fixation}} = [w_{p_1}, w_{p_2}, \ldots, w_{p_m}]$, where each w_{p_i} is the token fixated at time step i. This representation captures reading phenomena such as refixation (tokens may appear at multiple time steps) and skipping (tokens may not appear at all in the gaze sequence).

4.2 Training Procedure

Our training pipeline includes three stages illustrated in Figure 2: (A) modality-specific pretraining, (B) contrastive multimodal alignment, and (C) scanpath prediction fine-tuning.

4.2.1 Stage A: Modality-Specific Pretraining

We start by pretraining the eye-movement encoder and the language encoder to learn modality-specific representations of reading behavior.

For the eye movement prediction task, we initialize the ScanEZ encoder from the checkpoints in Sood et al. (2025) and continue training it using a

Figure 2: Training pipeline of EYELIGNR. Eye-movement and language encoders are separately pretrained with self-supervised objectives (Stage A). Their pooled representations are then aligned via contrastive learning in a shared embedding space, using a pairwise similarity matrix computed between pooled gaze and text embeddings (Stage B). Lastly, the gaze encoder (without contrastive projection heads) is fine-tuned for scanpath prediction.

masked modeling approach adapted for sequential eye movement data. Following BERT's masking strategy (Devlin et al., 2019), we randomly mask a subset of the input fixation triplets and train the model to reconstruct them: for each sequence, we randomly select a subset $\mathcal{M}$ of fixation positions and mask their (x, y, t) values. The ScanEZ encoder processes the partially masked sequence, and the regression head predicts the masked triplets. The training objective is:

$$\mathcal{L}_{\text{pretrain}} = \frac{1}{|\mathcal{M}|} \sum_{i \in \mathcal{M}} (X_i - \hat{X}_i)^2 \quad (5)$$

where X_i are the true fixation coordinates and duration at position i, and $\hat{X}_i$ are the model's predictions. With pretraining, the encoder is encouraged to learn bidirectional contextual representations of reading behavior, as it must use surrounding fixations to infer masked positions.

Regarding the language model, we fine-tune RoBERTa on *fixation-ordered* sequences with a masked language modeling objective. Fine-tuning encourages the model to familiarize with the statistical patterns of fixation-ordered text and learn representations that are robust to token reordering. We initialize the model from the pretrained RoBERTa-base checkpoint and train using RoBERTa's standard objective (Liu et al., 2019): we randomly mask tokens in the fixation-ordered sequence and learn to predict the masked tokens based on their fixation-order context.

The pretrained weights serve as initialization for the subsequent stages.

4.2.2 Stage B: Joint Contrastive Pretraining

In the second stage, we jointly optimize the pretrained ScanEZ and RoBERTa encoders to align eye movement representations with their corresponding textual contexts. The goal is to promote alignment at the representation level, without enforcing explicit token-to-fixation correspondences or architectural coupling.

The training uses a symmetric contrastive loss based on the InfoNCE objective (Oord et al., 2018). For a batch of N paired eye movement-text examples, we first obtain pooled representations and project them into the shared embedding space. We then compute the cosine similarity matrix:

$$S_{ij} = \frac{\mathbf{e}_{\text{gaze}}^{(i)} \cdot \mathbf{e}_{\text{text}}^{(j)}}{\tau} \quad (6)$$

where τ is a temperature parameter that controls the sharpness of the distribution. We set $\tau = 0.05$ based on preliminary experiments showing this value provides stable training and good separation between positive and negative pairs.

The contrastive loss is computed in both directions (gaze-to-text and text-to-gaze) and averaged:

$$\mathcal{L}_{\text{e2t}} = -\frac{1}{N} \sum_{i=1}^{N} \log \frac{\exp(S_{ii})}{\sum_{j=1}^{N} \exp(S_{ij})} \quad (7)$$

$$\mathcal{L}_{\text{t2e}} = -\frac{1}{N} \sum_{j=1}^{N} \log \frac{\exp(S_{jj})}{\sum_{i=1}^{N} \exp(S_{ij})} \quad (8)$$

$$\mathcal{L}_{\text{contrastive}} = \frac{\mathcal{L}_{\text{e2t}} + \mathcal{L}_{\text{t2e}}}{2} \quad (9)$$

This formulation treats each example in the batch as a positive pair with its corresponding modal-

ity representation, while all other examples in the batch serve as negative examples. With batch size N, each example effectively learns to distinguish the correct pairing from $N - 1$ negative pairs.

4.2.3 Stage C: Scanpath Fine-tuning

In the final stage, we adapt the contrastively learned representations to the downstream prediction task. After removing the contrastive projection heads, the ScanEZ encoder (with the regression head) is fine-tuned on the scanpath prediction task, using the same masked prediction objective as in equation 5. This stage allows the model to exploit the gaze–text alignment learned during contrastive training while optimizing for scanpath prediction.

5 Experimental Setup

We evaluate EYELIGNR using 5-fold cross validation. For each fold, we split the data into 80%/20% for training/testing. Following past work (e.g., Deng et al., 2023; Sood et al., 2025), we prevent data leakage by ensuring that no scanpaths recorded from the same textual stimulus–participant pair appear in both the training and test sets. This evaluation protocol is applied across multiple eye-tracking corpora using standard scanpath prediction metrics, as described below. We also experiment with other data split strategies and metrics, discussed in Appendix A.2 and A.3.

5.1 Eye-tracking Datasets

To test model robustness under data distributional shifts, we use five public corpora that vary in stimulus granularity (e.g., sentences, full articles), genre, task demands, participant populations, scanpath lengths and coordinate distributions (due to, e.g., screen geometries and data collection protocols).

CELER L1, ZuCo 1.0, and EML (henceforth CELER, ZuCo, and EML) are the benchmarks used in the evaluation of ScanEZ. CELER (Berzak et al., 2022) is a large-scale corpus suitable for fine-grained word-level fixation modeling, built on 365 participants who read English sentences from newswire and Wikipedia – like Sood et al. (2025), we focus on data from the 69 English L1 speakers. ZuCo (Hollenstein et al., 2018) contains eye-tracking recordings from 12 participants reading isolated sentences and Wikipedia-derived articles – as in Sood et al. (2025), we focus on sentences from the natural reading task. EML (Caruso et al., 2022) contains scanpaths typical of real-world learning, obtained from 147 fluent English

readers engaged with long-form educational texts (five ~1,000-word passages across multiple pages).

SB-SAT (Ahn et al., 2020) includes long-text scanpaths, obtained from 95 undergraduates in a standardized multi-page reading comprehension test (SAT practice contexts and questions).

ROAMM (Sun et al., 2025) is a multimodal (eye-tracking and EEG) corpus of naturalistic reading and attention lapses. Obtained from 44 participants reading five full-length Wikipedia articles, this corpus provides beyond-sentence data, with realistic variation in topic and reader engagement.

Summary statistics of the data extracted from the corpora are reported in Table 1. Raw scanpaths are derived as timestamped fixation sequences, with the (x, y, t) coordinates aligned with the corresponding text tokens. Next, we harmonize scanpaths across participants and hardware configurations by normalizing fixation duration (dividing t by the maximum duration within each scanpath) and spatial coordinates (dividing x and y by the screen resolution used during recording).[1]

5.2 Evaluation Metrics

We consider five traditional scanpath metrics that capture separate prediction dimensions:

- NLL_x, NLD_x, NLL_t, i.e., the likelihood of predicted horizontal fixation coordinates, Normalized Levenshtein Distance of predicted horizontal fixation coordinates, and the likelihood of predicted fixation durations.

- *Fixation Duration Accuracy (FDA)* measures the model's accuracy in predicting how long readers fixate each word, calculated as:

$$d = |\hat{T} - T| \qquad (10)$$

$$FDA = 1 - \frac{d}{max(d)} \qquad (11)$$

where $\hat{T}$ and T are the predicted and ground truth fixation durations, respectively.

- *Fixation Location Accuracy (FLA)* evaluates spatial prediction accuracy, i.e., whether the

---

[1]Normalization leaves some degree of cross-dataset heterogeneity due to differences in screen layout (e.g., y varies across corpora depending on line breaks and paging).

Dataset	Part.	Sent.	Text Source	# Scan.	X (px)	Y (px)
CELER	69	156	News / Wikipedia	8514	666.84 ± 446.64	539.06 ± 167.50
ZuCo	12	700	Wikipedia / Sentiment	2887	329.34 ± 145.22	139.32 ± 66.11
EML	147	239	Educational texts	5808	901.25 ± 276.26	394.43 ± 192.41
SB-SAT	95	118	Standardized test (SAT)	240	477.80 ± 257.93	329.06 ± 175.20
ROAMM	44	514	Wikipedia	1720	921.75 ± 400.58	459.52 ± 307.05

Table 1: Statistics of the eye-tracking data used in our experiments. Part./Sent.: participants/sentences (for ROAMM and SB-SAT, we identify sentence-final punctuation in tokenized texts). # Scan: total number of scanpaths. X/Y: scanpath coordinates in screen-centered pixel space (mean $\pm$ standard deviation); negative values are due to dataset-specific coordinate conventions.

model correctly predicts which words are fixated, calculated as:

$$d = (\hat{X} - X)^2 + (\hat{Y} - Y)^2 \qquad (12)$$

$$FLA = 1 - \frac{\sqrt{d}}{max(\sqrt{d})} \qquad (13)$$

where $\hat{X}$ and $\hat{Y}$ are the predicted (x, y)-coordinates and X and Y the ground truth.

Better performance corresponds to lower values of NLL_x, NLD_x, and NLL_t, and higher values of FDA and FLA.

We further use Root Mean Squared Error (RMSE) to compare performance between models on the x, y and t dimensions. Paired significance tests are performed on per-scanpath differences, using Bonferroni-adjusted p-values to account for multiple comparisons, and effect sizes are reported using Cohen's d for paired samples ($|d| < 0.2$: negligible magnitude, $0.2 \leq |d| < 0.5$: small, $0.5 \leq |d| < 0.8$: moderate, $|d| \geq 0.8$: large).

Lastly, we investigate the quality of predictions using MultiMatch (Dewhurst et al., 2012), which measures similarity between predicted and ground-truth scanpaths along five sequence-level dimensions: shape, direction, length, position, and duration. Higher MultiMatch scores along these dimensions indicate higher similarity between predictions and groundtruth.

6 Results

To test the hypothesis that gaze-informed text representations improve scanpath prediction, we separately assess EYELIGNR against ScanEZ (Section 6.1) and a "Token-Ordered" baseline (Section 6.2). ScanEZ provides a language-ablated version of EYELIGNR; comparisons with this model

therefore isolate the contribution of linguistic information over purely spatiotemporal modeling. Comparing to Token-Ordered additionally tests the effect of adapting language to the unfolding of gaze, as this model is trained on the same architecture and data as EYELIGNR, but without adjusting the pretrained language embeddings to reading order.

6.1 Language Improves Scanpath Prediction

Results (Table 2) demonstrate that EYELIGNR surpasses ScanEZ on the spatial metrics NLL_x, NLD_x, and fixation-location accuracy. Gains are visible across datasets, particularly on CELER and EML: on CELER, NLL_x is reduced by 26.6% (1.524→1.118), NLD_x by 56.8% (.421→.182), and FLA increases by 58.6% (.413→.655); on EML, NLL_x drops by 25% (.996→.747) and NLD_x by 46.4% (.616→.330), with FLA raising by .193 points (.534→.727).

EYELIGNR generally outperforms ScanEZ on fixation-duration metrics as well. The only exception is CELER, where ScanEZ attains better likelihood calibration (NLL_t = 1.240) despite having lower FDA (0.650) than EYELIGNR. This outcome indicates that ScanEZ achieves better distributional fit on CELER, but EYELIGNR produces more accurate pointwise predictions. This behavior is especially plausible given CELER's constrained temporal structure (i.e., single-line reading and low variance in fixation durations), which favors models with well-calibrated uncertainty over sharper point estimates.

EYELIGNR therefore yields superior spatial trajectory modeling and, in most cases, improved temporal modeling relative to ScanEZ. The exception found on CELER is unsurprising, because contrastive language–gaze alignment was not designed to optimize fixation-duration prediction. Nonetheless, the improvements on all other datasets indi-

Data	Model	NLL$_x$↓	NLD$_x$↓	NLL$_t$↓	FDA↑	FLA↑
CELER	ScanEZ	1.524 ± 0.04	0.421 ± 0.02	**1.240 ± 0.02**	0.650 ± 0.00	0.413 ± 0.01
	Token-Ordered	2.503 ± 0.28	0.446 ± 0.01	2.028 ± 0.02	0.613 ± 0.01	0.391 ± 0.03
	EYELIGNR	**1.118 ± 0.09**	**0.182 ± 0.01**	1.599 ± 0.01	**0.693 ± 0.00**	**0.655 ± 0.01**
ZuCo	ScanEZ	1.140 ± 0.07	0.365 ± 0.00	1.334 ± 0.12	0.718 ± 0.03	0.623 ± 0.02
	Token-Ordered	1.573 ± 0.07	0.420 ± 0.01	1.803 ± 0.09	0.643 ± 0.02	0.292 ± 0.03
	EYELIGNR	**1.053 ± 0.09**	**0.335 ± 0.01**	**1.218 ± 0.10**	**0.756 ± 0.03**	**0.662 ± 0.04**
EML	ScanEZ	0.996 ± 0.02	0.616 ± 0.01	1.083 ± 0.03	0.804 ± 0.01	0.534 ± 0.01
	Token-Ordered	1.253 ± 0.02	0.416 ± 0.00	1.686 ± 0.03	0.650 ± 0.01	0.530 ± 0.00
	EYELIGNR	**0.747 ± 0.09**	**0.330 ± 0.00**	**1.039 ± 0.02**	**0.818 ± 0.00**	**0.727 ± 0.00**
SB-SAT	ScanEZ	2.904 ± 0.176	0.406 ± 0.00	2.342 ± 0.11	0.820 ± 0.01	0.738 ± 0.01
	Token-Ordered	3.434 ± 0.16	0.461 ± 0.00	3.375 ± 0.049	0.493 ± 0.01	0.460 ± 0.01
	EYELIGNR	**2.704 ± 0.15**	**0.346 ± 0.01**	**2.288 ± 0.12**	**0.825 ± 0.00**	**0.805 ± 0.02**
ROAMM	ScanEZ	2.713 ± 0.11	0.392 ± 0.01	1.394 ± 0.07	0.839 ± 0.01	0.736 ± 0.01
	Token-Ordered	3.324 ± 0.12	0.462 ± 0.00	2.368 ± 0.10	0.554 ± 0.01	0.443 ± 0.00
	EYELIGNR	**2.524 ± 0.161**	**0.341 ± 0.01**	**1.321 ± 0.06**	**0.847 ± 0.01**	**0.809 ± 0.01**

Table 2: Scanpath prediction results (mean ± standard deviation). CELER, ZuCo and EML correspond to the datasets used for the ScanEZ evaluation, as reported in Sood et al. (2025).

cate that linguistic grounding can provide a beneficial inductive bias for temporal modeling under naturalistic reading conditions. Taken together, these results establish EYELIGNR as a new state-of-the-art approach for scanpath prediction.

Sources of Spatial Performance Gains. As a diagnostic analysis, we investigate the contribution of horizontal (x) and vertical (y) predictions to the gains in spatial accuracy. To this end, we examine whether EYELIGNR has an advantage over ScanEZ in terms of RMSE.[2]

An asymmetry emerges between the x and y dimensions, suggesting that FLA reflects accurate horizontal predictions more than vertical ones. On x, EYELIGNR performs significantly better than ScanEZ across all datasets (e.g., $p < .001$, d=-2.917 on SB-SAT). Vice versa, when considering y, better performance is generally exhibited by ScanEZ (e.g., on ZuCo, d(RMSE)=1.021). We take this finding as evidence that our training procedure successfully pushed EYELIGNR to focus on language-related phenomena: EYELIGNR captures within-line reading dynamics, which are linked to linguistic processing, better than vertical across-line transitions, which are mainly determined by text layout (like screen constraints) rather than text content.

6.2 Accounting for Reading Order Matters

EYELIGNR outperforms the Token-Ordered baseline (Table 2). Improvements are observed across all datasets and metrics. For instance, spatial per-

[2]Full dataset-by-dimension RMSEs are in Appendix A.3.

formance is boosted by 82.6% on ROAMM (FLA: 0.443→0.809); on SB-SAT, the temporal evaluation shows a 32.2% reduction in NLL$_t$ and a 67.3% increase in fixation-duration accuracy. Interestingly, Token-Ordered underperforms both EYELIGNR and ScanEZ. This suggests that the use of *sentence-ordered* language embeddings can be detrimental not only relative to models based on *fixation-ordered* embeddings, but even compared to models that do not incorporate linguistic representations at all.

Emergent Temporal Gains from Fixation-Order Alignment. Comparisons based on RMSE corroborate the advantage of EYELIGNR over the Token-Ordered model. Along the x dimension, advantages are more pronounced than those observed earlier relative to ScanEZ (e.g., on SB-SAT: d=-6.378). More importantly, EYELIGNR achieves significantly lower RMSE than Token-Ordered on the duration dimension t with consistently large effects (e.g., SB-SAT: d=-2.761). In other words, by learning to predict better trajectories, EYELIGNR also approximates more realistic temporal patterns. This finding is consistent with established literature, which posits that fixation duration co-varies with spatial reading dynamics such as regressions and word skipping (Pollatsek et al., 2008).

Sequence-Level Evaluation of Fixation-Order Alignment. The likelihood-based and RMSE metrics considered so far point to the benefits of our fixation-ordered language embedding fine-tuning

Data	Model	Shape	Dir	Len	Pos	Dur
CELER	Token-Ordered	0.986 ± 0.02	0.652 ± 0.01	0.984 ± 0.01	0.827 ± 0.03	0.579 ± 0.01
	EYELIGNR	**0.993 ± 0.00**	**0.977 ± 0.00**	**0.988 ± 0.00**	**0.971 ± 0.00**	**0.787 ± 0.01**
ZuCo	Token-Ordered	0.976 ± 0.00	0.778 ± 0.01	0.971 ± 0.00	0.665 ± 0.01	0.645 ± 0.01
	EYELIGNR	**0.980 ± 0.00**	**0.917 ± 0.00**	**0.972 ± 0.00**	**0.929 ± 0.00**	**0.783 ± 0.01**
EML	Token-Ordered	0.973 ± 0.00	0.704 ± 0.00	0.973 ± 0.00	0.818 ± 0.03	0.642 ± 0.01
	EYELIGNR	**0.983 ± 0.00**	**0.908 ± 0.02**	**0.977 ± 0.00**	**0.938 ± 0.01**	**0.789 ± 0.04**
SB-SAT	Token-Ordered	0.971 ± 0.00	0.740 ± 0.01	0.969 ± 0.00	0.742 ± 0.01	0.380 ± 0.02
	EYELIGNR	**0.979 ± 0.00**	**0.915 ± 0.00**	**0.971 ± 0.00**	**0.922 ± 0.00**	**0.741 ± 0.01**
ROAMM	Token-Ordered	0.972 ± 0.00	0.740 ± 0.00	0.969 ± 0.00	0.734 ± 0.02	0.499 ± 0.02
	EYELIGNR	**0.979 ± 0.00**	**0.912 ± 0.00**	**0.972 ± 0.00**	**0.925 ± 0.00**	**0.779 ± 0.00**

Table 3: MultiMatch similarity results (mean and standard deviation). For all metrics, the higher the better. Dir: direction. Len: length. Pos: position. Dur: Duration.

and contrastive alignment. However, they evaluate accuracy locally, at the level of individual fixation coordinates or durations, without assessing the global quality of predictions. Therefore, we use MultiMatch to assess entire scanpaths across several dimensions of sequence similarity.

EYELIGNR outperforms the Token-Ordered baseline across the five dimensions of shape, direction, length, position, and duration (Table 3). Particularly large gains are observed in directional similarity. For example, on CELER, scores increase from 0.652 with Token-Ordered to 0.977 with EYELIGNR, and on SB-SAT from 0.740 to 0.915. Similarly, for positional similarity, on CELER scores rise from 0.827 to 0.971, and on SB-SAT from 0.742 to 0.922.

Since directional similarity reflects the ordering of saccades and regressions, the large gains of EYELIGNR support our hypothesis: aligning language representations with fixation order enables us to better model eye movements through text. In contrast, language embeddings derived from the canonical sentence order (as in Token-Ordered) introduce a mismatch between textual and gaze representations that disrupts the coherence of (predicted) scanpath sequences. Improvements in positional similarity further indicate that predicted fixations land closer to the locations observed in human scanpaths, suggesting that EYELIGNR more accurately captures which words are fixated, skipped, or revisited. This finding corroborates that EYELIGNR improves horizontal trajectory modeling, which largely reflects within-line reading dynamics.

Finally, gains in duration similarity (e.g., $\Delta(\text{Dur})=0.361$ on SB-SAT) suggest that fixation-order alignment produces more realistic temporal

patterns, consistent with psycholinguistic evidence showing that fixation duration co-varies with spatial reading behavior, including regressions and re-fixations triggered by processing difficulty (Pollatsek et al., 2008).

7 Conclusion

We introduce EYELIGNR, a framework that injects language information into a spatiotemporal scanpath model through contrastive gaze-text alignment. Building on masked fixation modeling, we align scanpath representations with embeddings of the corresponding text, and further refine alignment by adapting the language encoder on fixation-ordered token sequences that better match the non-monotonic order of natural reading. In doing so, we address a methodological question left open by prior work, that is, how to leverage linguistic information for scanpath prediction in a way that complements strong eye movement representations learned from gaze data, while accounting for the spatial and temporal aspects of reading.

Compared to both language-agnostic and sentence-ordered baselines, our approach achieves substantial improvements on core scanpath metrics (e.g., NLD, NLL, and FLA; CELER: ∼57%, ∼27%, ∼59%; EML: ∼46%, ∼25%, ∼36%), outperforming prior state of the art and establishing a strong baseline across diverse reading corpora, including long-form educational and learning settings. Experimental results highlighted an asymmetry between horizontal and vertical predictions, likely due to cross-corpus variation in page layout. In the future, we will therefore extend the current approach to better model vertical scanpath patterns.

8 Limitations

We evaluate EYELIGNR on multiple English reading corpora, but not across languages, scripts, or interfaces (e.g., mobile, VR), where fixation behavior and layout statistics may differ substantially. Moreover, our approach assumes access to reliable token-to-fixation alignment and consistent pre-processing across corpora; in practice, alignment quality varies with (eye-tracking) experimental protocols and annotation pipelines, and residual alignment noise can affect both fixation-order language adaptation and contrastive alignment.

Regarding our experimental results, we point out that while EYELIGNR improves core scanpath metrics, gains are not uniform across all objectives. We saw a trade-off on fixation-duration likelihood in one experimental setting (i.e., NLL_t on CELER), indicating that better spatial and sequence-level alignment does not automatically translate into better calibrated duration likelihoods. The improvements are also not evenly distributed across scanpath dimensions: y is comparatively harder to model under distributional shift, as it exhibits large variance across corpora (e.g., single-line sentences versus multi-page passages), statistics of vertical eye transitions are less consistent across datasets.

Finally, EYELIGNR builds on pretrained components (a language encoder and a spatiotemporal gaze encoder). Performance and compute cost thus depend on these choices; exploring lighter-weight alternatives, more efficient alignment objectives, and stronger modeling of vertical transitions are important directions for future work.

9 Ethical Considerations

This work did not go through an ethical committee. However, we ensured compliance with ethical principles in data usage and methodology. For the pretraining of the gaze embedding, we used synthetic eye trajectories – no real individuals can be reconstructed from them. For the scanpath prediction task, we relied on publicly available datasets and EML (all already peer-reviewed) where individuals are thoroughly anonymized.

References

Seoyoung Ahn, Conor Kelton, Aruna Balasubramanian, and Greg Zelinsky. 2020. Towards Predicting Reading Comprehension From Gaze Behavior. In *ACM Symposium on Eye Tracking Research and Applications*, ETRA '20 Short Papers, pages 1–5, New York, NY, USA. Association for Computing Machinery.

Maria Barrett and Nora Hollenstein. 2020. Sequence labelling and sequence classification with gaze: Novel uses of eye-tracking data for Natural Language Processing. *Language and Linguistics Compass*, 14(11):1–16.

Yevgeni Berzak, Chie Nakamura, Amelia Smith, Emily Weng, Boris Katz, Suzanne Flynn, and Roger Levy. 2022. CELER: A 365-Participant Corpus of Eye Movements in L1 and L2 English Reading. *Open Mind*, 6:41–50.

Lena Bolliger, David Reich, Patrick Haller, Deborah Jakobi, Paul Prasse, and Lena Jäger. 2023. ScanDL: A diffusion model for generating synthetic scanpaths on texts. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15513–15538, Singapore. Association for Computational Linguistics.

Lena Bolliger, David Reich, and Lena Ann Jäger. 2025. Scandl 2.0: A generative model of eye movements in reading synthesizing scanpaths and fixation durations. *Proceedings of the ACM on Human-Computer Interaction*, 9(3):1–29.

Anna Bondar, David Robert Reich, and Lena Ann Jäger. 2025. AlEYEgnment: Leveraging Eye-Tracking-While-Reading to align language models with human preferences. In *Proceedings of the First International Workshop on Gaze Data and Natural Language Processing*, pages 58–70, Varna, Bulgaria. INCOMA Ltd., Shoumen, BULGARIA.

Megan Caruso, Candace E. Peacock, Rosy Southwell, Guojing Zhou, and Sidney K. D'Mello. 2022. Going deep and far: Gaze-based models predict multiple depths of comprehension during and one week following reading. *International Educational Data Mining Society*.

Shuwen Deng, Paul Prasse, David Reich, Tobias Scheffer, and Lena Jäger. 2024. Fine-tuning pre-trained language models with gaze supervision. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 217–224, Bangkok, Thailand. Association for Computational Linguistics.

Shuwen Deng, David Reich, Paul Prasse, Patrick Haller, Tobias Scheffer, and Lena Ann Jäger. 2023. Eyettention: An attention-based dual-sequence model for predicting human scanpaths during reading. *Proceedings of the ACM on Human-Computer Interaction*, 7(ETRA):1–24.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages

4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Richard Dewhurst, Marcus Nyström, Halszka Jarodzka, Tom Foulsham, Roger Johansson, and Kenneth Holmqvist. 2012. It depends on how you look at it: Scanpath comparison in multiple dimensions with multimatch, a vector-based approach. *Behavior Research Methods*, 44(4):1079–1100.

Nora Hollenstein, Jonathan Rotsztejn, Marius Troendle, Andreas Pedroni, Ce Zhang, and Nicolas Langer. 2018. Zuco, a simultaneous eeg and eye-tracking resource for natural sentence reading. *Scientific data*, 5(1):1–13.

Nora Hollenstein and Ce Zhang. 2019. Entity recognition at first sight: Improving NER with eye movement information. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 1–10, Minneapolis, Minnesota. Association for Computational Linguistics.

Swati Jindal and Roberto Manduchi. 2023. Contrastive representation learning for gaze estimation. In *Gaze Meets Machine Learning Workshop*, pages 37–49. PMLR.

Varun Khurana, Yaman Kumar, Nora Hollenstein, Rajesh Kumar, and Balaji Krishnamurthy. 2023. Synthesizing human gaze feedback for improved NLP performance. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 1895–1908, Dubrovnik, Croatia. Association for Computational Linguistics.

Walter Kintsch. 1992. A cognitive architecture for comprehension. In *Cognition: Conceptual and methodological issues*, pages 143–163. American Psychological Association, Washington, DC, US.

Walter Kintsch. 1994. Text comprehension, memory, and learning. *American Psychologist*, 49(4):294–303. Num Pages: 294-303 Place: Washington, US Publisher: American Psychological Association (US).

Bai Li and Frank Rudzicz. 2021. TorontoCL at CMCL 2021 shared task: RoBERTa with multi-stage fine-tuning for eye-tracking prediction. In *Proceedings of the Workshop on Cognitive Modeling and Computational Linguistics*, pages 85–89, Online. Association for Computational Linguistics.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. 2018. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*.

Alexander Pollatsek, Barbara J Juhasz, Erik D Reichle, Debra Machacek, and Keith Rayner. 2008. Immediate and delayed effects of word frequency and word length on eye movements in reading: a reversed delayed effect of word length. *Journal of experimental psychology: human perception and performance*, 34(3):726.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR.

Erik D. Reichle, Keith Rayner, and Alexander Pollatsek. 2003. The E-Z reader model of eye-movement control in reading: Comparisons to other models. *The Behavioral and Brain Sciences*, 26(4):445–476; discussion 477–526.

Omer Shubi, David Robert Reich, Keren Gruteke Klein, Yuval Angel, Paul Prasse, Lena Ann Jäger, and Yevgeni Berzak. 2025. EyeBench: Predictive modeling from eye movements in reading. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Ekta Sood, Prajit Dhar, Enrica Troiano, Rosy Southwell, and Sidney K. D'Mello. 2025. ScanEZ: Integrating cognitive models with self-supervised learning for spatiotemporal scanpath prediction. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1132–1142, Vienna, Austria. Association for Computational Linguistics.

Harshvardhan Srivastava. 2022. Poirot at CMCL 2022 shared task: Zero shot crosslingual eye-tracking data prediction using multilingual transformer models. In *Proceedings of the Workshop on Cognitive Modeling and Computational Linguistics*, pages 102–107, Dublin, Ireland. Association for Computational Linguistics.

Ivan Stebakov and Ilya Pershin. 2025. How well can AI models generate human eye movements during reading? In *Proceedings of the Fourth Workshop on Bridging Human-Computer Interaction and Natural Language Processing (HCI+NLP)*, pages 148–162, Suzhou, China. Association for Computational Linguistics.

Haorui Sun, Ardyn Vivienne Olszko, Yida Chen, Hazen Kellner, Niharika Singh, Lincoln Lewisequerre, and David C. Jangraw. 2025. Reading observed at mindless moments (roamm): A simultaneous eeg and eye-tracking dataset of natural reading with attention annotations. In *NeurIPS 2025 Workshop on "Data on the Brain & Mind" Tutorials Track*.

Jeff Wu, Long Ouyang, Daniel M. Ziegler, Nisan Stiennon, Ryan Lowe, Jan Leike, and Paul Christiano. 2021. Recursively summarizing books with human feedback. *arXiv preprint arXiv:2109.10862*.

Zihao Zhao, Sheng Wang, Qian Wang, and Dinggang Shen. 2024. Mining gaze for contrastive learning toward computer-assisted diagnosis. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(7):7543–7551.

A Appendix

A.1 Model Training

Below are additional details on the training pipeline of EYELIGNR.

Optimization. We train the model using the AdamW optimizer with a learning rate of 5×10^{-4}. We found that higher learning rates (e.g., 1×10^{-3}) led to gradient collapse and representation degeneration, where all embeddings converged to similar values. This learning rate is used consistently across all three training stages.

Batch Size. We use a batch size of 32 during contrastive training, providing 31 negative examples per positive pair. While larger batch sizes could provide more negative examples and potentially improve performance, we were constrained by GPU memory limitations. The effective number of comparisons per batch is $N^2 = 1024$.

Data Preprocessing. Eye movement sequences are padded to the average length of time steps across datasets, with shorter sequences zero-padded and masked during attention. Text sequences are tokenized with the RoBERTa tokenizer, truncating longer texts and padding shorter ones.

Model Initialization. The language encoder is initialized from pre-trained RoBERTa-base weights, while the ScanEZ encoder is initialized from the Stage 1 pretrained checkpoint. In Stage 3, we discard the projection heads and fine-tune only the ScanEZ encoder and regression head.

Training Duration. Pretraining (Stage A) runs for 25 epochs, contrastive fine-tuning (Stage B) for 50 epochs, and scanpath prediction fine-tuning (Stage C) for 25 epochs. We monitor validation performance at each stage and save the best-performing checkpoint.

Training Datasets. We first finetune RoBERTa on the texts used for the generation of synthetic data through the E-Z Reader model (Reichle et al., 2003), following the pretraining procedure of ScanEZ (Sood et al., 2025). Training is then continued on the respective ground truth eye tracking dataset of paired eye movement-text examples, using 80%/20% training/test data splits for 5-fold cross validation.

A.2 Evaluating Scanpath Prediction under Different Data Splits Conditions

The results in Section 6 are based on data splits that prevent any participant-stimulus combination from appearing both in the training and the test sets, such that models are kept from exploiting document- or participant-specific regularities.

We here experiment with two (more lenient) types of data splits to enable a full comparison with the evaluation protocol of Sood et al. (2025). These split strategies enforce non-overlap between training and test sets with respect to either participants or textual stimuli, respectively.

The comparison between EYELIGNR and ScanEZ (Tables 4 and 5) align with our earlier findings: with the exception of NLL$_t$ on CELER, all numbers consistently indicate that EYELIGNR outperforms ScanEZ.

A.3 Pointwise and Sequence-level Metrics

Table 6 reports the full statistical comparisons of EYELIGNR with ScanEZ and Token-Ordered, including paired significance tests and effect sizes. These comparisons are based on model performance measured using Root Mean Squared Error (RMSE) to quantify how closely the predicted trajectories match the ground truth. We also report Explained Variance (EV) – for CELER, where vertical scanpaths are single-line, EV in y is calculated using a fallback formulation with prediction variance in the denominator when $\text{Var}(y) = 0$, to avoid undefined values. Tests are conducted separately for the all coordinates. Except for the vertical dimension (y), we observe that EYELIGNR exhibits significantly lower RMSE and higher EV than the baseline models.

The RMSE and EV evaluation metrics focus on *local, pointwise* errors. To complement them with a more holistic sequence-level perspective, we investigate the quality of predictions using Multi-Match (Dewhurst et al., 2012). Results (Table 7) corroborate and refine our earlier insights. We see that both EYELIGNR and ScanEZ achieve high similarity in coarse spatial structure (shape and length). However, EYELIGNR yields substantially higher directional similarity across datasets, indicating more human-like ordering of saccades and regressions. This improvement in directionality is consistent with EYELIGNR's stronger modeling of within-line reading dynamics, which are closely tied to linguistic processing, and reflects

Data	Model	NLL$_x\downarrow$	NLD$_x\downarrow$	NLL$_t\downarrow$	FDA$\uparrow$	FLA$\uparrow$
CELER	ScanEZ	1.555 ±0.013	0.424 ±0.025	**1.235 ±0.072**	0.651 ±0.012	0.412 ± 0.007
	EYELIGNR	**1.227 ± 0.010**	**0.166 ± 0.000**	1.464 ± 0.050	**0.688 ± 0.020**	**0.660 ± 0.000**
ZuCo	ScanEZ	1.204 ± 0.021	0.336 ± 0.002	1.353 ± 0.033	0.714 ± 0.005	0.670 ± 0.006
	EYELIGNR	**1.063 ± 0.014**	**0.328 ± 0.002**	**1.356 ± 0.034**	**0.724 ± 0.004**	**0.682 ± 0.007**
EML	ScanEZ	0.928 ± 0.037	0.585 ± 0.014	1.098 ± 0.026	0.803 ± 0.006	0.556 ± 0.013
	EYELIGNR	**0.835 ± 0.109**	**0.341 ± 0.002**	**1.018 ± 0.017**	**0.806 ± 0.006**	**0.735 ± 0.007**
SB-SAT	ScanEZ	2.894 ± 0.176	0.343 ± 0.004	2.274 ± 0.096	0.825 ± 0.001	0.833 ± 0.007
	EYELIGNR	**2.807 ± 0.190**	**0.335 ± 0.000**	**2.260 ± 0.090**	**0.829 ± 0.000**	**0.861 ± 0.010**
ROAMM	ScanEZ	2.857 ± 0.125	0.344 ± 0.004	1.359 ± 0.094	0.841 ± 0.011	0.804 ± 0.004
	EYELIGNR	**2.602 ± 0.118**	**0.303 ± 0.004**	**1.323 ± 0.095**	**0.848 ± 0.009**	**0.817 ± 0.004**

Table 4: Scanpath prediction results on the participant split strategy.

Data	Model	NLL$_x\downarrow$	NLD$_x\downarrow$	NLL$_t\downarrow$	FDA$\uparrow$	FLA$\uparrow$
CELER	ScanEZ	1.603 ± 0.017	0.430 ± 0.047	**1.269 ± 0.068**	0.653 ± 0.011	0.408 ± 0.008
	EYELIGNR	**1.418 ± 0.044**	**0.276 ± 0.001**	1.609 ± 0.032	**0.678 ± 0.004**	**0.518 ± 0.006**
ZuCo	ScanEZ	1.045 ± 0.031	0.329 ± 0.003	1.479 ± 0.036	0.698 ± 0.004	0.665 ± 0.001
	EYELIGNR	**1.060 ± 0.014**	**0.319 ± 0.004**	**1.296 ± 0.035**	**0.739 ± 0.004**	**0.690 ± 0.006**
EML	ScanEZ	1.000 ± 0.012	0.589 ± 0.012	1.106 ± 0.022	0.803 ± 0.004	0.553 ± 0.020
	EYELIGNR	**0.791 ± 0.039**	**0.335 ± 0.001**	**1.084 ± 0.005**	**0.813 ± 0.003**	**0.733 ± 0.003**
SB-SAT	ScanEZ	3.052 ± 0.198	0.353 ± 0.004	2.394 ± 0.058	0.819 ± 0.009	0.807 ± 0.005
	EYELIGNR	**2.908 ± 0.018**	**0.345 ± 0.003**	**2.299 ± 0.073**	**0.828 ± 0.008**	**0.818 ± 0.004**
ROAMM	ScanEZ	2.717 ± 0.047	0.357 ± 0.002	**1.336 ± 0.019**	0.836 ± 0.002	0.801 ± 0.002
	EYELIGNR	**2.555 ± 0.045**	**0.349 ± 0.001**	1.371 ± 0.021	**0.842 ± 0.002**	**0.810 ± 0.001**

Table 5: Scanpath prediction results on the textual stimulus-based split strategy, where a textual stimulus can be a single sentence or longer texts, depending on the dataset.

sequence-level gains that are not captured by point-wise error metrics alone. The comparison between EYELIGNR and the Token-Ordered baseline is discussed in the body of the paper.

Dataset	Dim.	Model	RMSE				EV			
			p_{adj}	d	Magn.	Better	p_{adj}	d	Magn.	Better
CELER	x	ScanEZ	< .001	-0.196	negl.	EYELIGNR	< .001	0.693	med.	EYELIGNR
		Token-Ordered	< .001	-2.310	large	EYELIGNR	< .001	0.749	med.	EYELIGNR
	y	ScanEZ	0.126	0.091	negl.	ScanEZ	1.000	-0.042	negl.	ScanEZ
		Token-Ordered	< .001	-1.628	large	EYELIGNR	1.000	-0.043	negl.	Token-Ordered
	t	ScanEZ	< .001	0.246	small	ScanEZ	< .001	-0.345	small	ScanEZ
		Token-Ordered	< .001	-1.453	large	EYELIGNR	< .001	0.378	small	EYELIGNR
ZuCo	x	ScanEZ	< .001	-0.837	large	EYELIGNR	< .001	1.351	large	EYELIGNR
		Token-Ordered	< .001	-3.701	large	EYELIGNR	< .001	3.132	large	EYELIGNR
	y	ScanEZ	< .001	1.021	large	ScanEZ	< .001	-0.536	med.	ScanEZ
		Token-Ordered	< .001	-5.160	large	EYELIGNR	< .001	1.580	large	EYELIGNR
	t	ScanEZ	< .001	0.558	med.	ScanEZ	1.000	0.111	negl.	EYELIGNR
		Token-Ordered	< .001	-1.938	large	EYELIGNR	< .001	2.030	large	EYELIGNR
EML	x	ScanEZ	< .001	-1.484	large	EYELIGNR	< .001	1.357	large	EYELIGNR
		Token-Ordered	< .001	-1.868	large	EYELIGNR	< .001	2.982	large	EYELIGNR
	y	ScanEZ	< .001	0.547	med.	ScanEZ	0.006	-0.143	negl.	ScanEZ
		Token-Ordered	< .001	-3.339	large	EYELIGNR	< .001	2.509	large	EYELIGNR
	t	ScanEZ	1.000	-0.057	negl.	EYELIGNR	0.085	0.116	negl.	EYELIGNR
		Token-Ordered	< .001	-1.336	large	EYELIGNR	< .001	2.119	large	EYELIGNR
ROAMM	x	ScanEZ	< .001	-1.545	large	EYELIGNR	< .001	1.354	large	EYELIGNR
		Token-Ordered	< .001	-4.964	large	EYELIGNR	< .001	5.397	large	EYELIGNR
	y	ScanEZ	0.166	0.196	negl.	ScanEZ	0.034	-0.228	small	ScanEZ
		Token-Ordered	< .001	-5.477	large	EYELIGNR	< .001	1.570	large	EYELIGNR
	t	ScanEZ	0.015	-0.243	small	EYELIGNR	0.213	0.190	negl.	EYELIGNR
		Token-Ordered	< .001	-1.980	large	EYELIGNR	< .001	1.499	large	EYELIGNR
SB-SAT	x	ScanEZ	< .001	-2.917	large	EYELIGNR	< .001	2.530	large	EYELIGNR
		Token-Ordered	< .001	-6.378	large	EYELIGNR	< .001	7.048	large	EYELIGNR
	y	ScanEZ	< .001	-0.814	large	EYELIGNR	< .001	0.897	large	EYELIGNR
		Token-Ordered	< .001	-5.781	large	EYELIGNR	< .001	7.902	large	EYELIGNR
	t	ScanEZ	1.000	-0.076	negl.	EYELIGNR	1.000	0.079	negl.	EYELIGNR
		Token-Ordered	< .001	-2.761	large	EYELIGNR	< .001	2.783	large	EYELIGNR

Table 6: Paired comparisons of the baseline models with EYELIGNR with respect to RMSE and EV across the normalized dimensions (Dim.) x, y, and t. Bonferroni-corrected p-values and paired-sample Cohen's d are rounded to three decimals. Better: the model which predicts most similar to the ground truth. Mag.: magnitude of the effect size. Med. and negl.: medium and negligible effect sizes, respectively.

Data	Model	Shape	Dir	Len	Pos	Dur
CELER	ScanEZ	0.986 ± 0.00	0.717 ± 0.01	0.985 ± 0.01	0.928 ± 0.00	0.772 ± 0.01
	Token-Ordered	0.986 ± 0.02	0.652 ± 0.01	0.984 ± 0.01	0.827 ± 0.03	0.579 ± 0.01
	EYELIGNR	**0.993 ± 0.00**	**0.977 ± 0.00**	**0.988 ± 0.00**	**0.971 ± 0.00**	**0.787 ± 0.01**
ZuCo	ScanEZ	0.979 ± 0.00	0.877 ± 0.01	0.969 ± 0.01	0.923 ± 0.00	0.769 ± 0.01
	Token-Ordered	0.976 ± 0.00	0.778 ± 0.01	0.971 ± 0.00	0.665 ± 0.01	0.645 ± 0.01
	EYELIGNR	**0.980 ± 0.00**	**0.917 ± 0.00**	**0.972 ± 0.00**	**0.929 ± 0.00**	**0.783 ± 0.01**
EML	ScanEZ	0.982 ± 0.00	0.901 ± 0.00	0.976 ± 0.00	0.935 ± 0.00	0.784 ± 0.02
	Token-Ordered	0.973 ± 0.00	0.704 ± 0.00	0.973 ± 0.00	0.818 ± 0.03	0.642 ± 0.01
	EYELIGNR	**0.983 ± 0.00**	**0.908 ± 0.02**	**0.977 ± 0.00**	**0.938 ± 0.01**	**0.789 ± 0.04**
SB-SAT	ScanEZ	0.973 ± 0.00	0.835 ± 0.01	0.967 ± 0.00	0.887 ± 0.00	0.728 ± 0.01
	Token-Ordered	0.971 ± 0.00	0.740 ± 0.01	0.969 ± 0.00	0.742 ± 0.01	0.380 ± 0.02
	EYELIGNR	**0.979 ± 0.00**	**0.915 ± 0.00**	**0.971 ± 0.00**	**0.922 ± 0.00**	**0.741 ± 0.01**
ROAMM	ScanEZ	0.976 ± 0.00	0.853 ± 0.01	0.970 ± 0.01	0.901 ± 0.03	0.765 ± 0.01
	Token-Ordered	0.972 ± 0.00	0.740 ± 0.00	0.969 ± 0.00	0.734 ± 0.02	0.499 ± 0.02
	EYELIGNR	**0.979 ± 0.00**	**0.912 ± 0.00**	**0.972 ± 0.00**	**0.925 ± 0.00**	**0.779 ± 0.00**

Table 7: MultiMatch prediction results (mean and standard deviation) for all used models. For all metrics, the higher the better.