UNLEARNING MAPPING ATTACK: EXPOSING HIDDEN VULNERABILITIES IN MACHINE UNLEARNING

ABSTRACT

As machine learning becomes increasingly data-dependent, concerns over privacy and content regulation among data owners have intensified. Machine Unlearning has emerged as a promising solution, allowing for the removal of specific data from pre-trained systems to protect user privacy and regulate information. Existing research on Machine Unlearning has shown considerable success in eliminating the influence of certain data while preserving model performance. However, the resilience of Machine Unlearning to malicious attacks has not been thoroughly examined. In this paper, we investigate the hidden vulnerabilities within current Machine Unlearning techniques. We propose a novel adversarial attack, the Unlearning Mapping Attack (UMA), capable of undermining the unlearning process without altering its procedures. Through experiments on both generative and discriminative tasks, we demonstrate the susceptibility of existing unlearning techniques to UMA. These findings highlight the need to reassess unlearning objectives across various tasks, prompting the introduction of a Robust Unlearning standard that prioritizes protection against adversarial threats. Our extensive studies show the successful adaptation of current unlearning methods to this robust framework. The Python implementation will be made publicly available upon acceptance of the paper.

1 INTRODUCTION

In recent years, the rapid growth of Machine Learning (ML) and Deep Neural Networks (DNNs) has led to significant advancements in various fields, including image classification (Krizhevsky et al., 2012; Sahoo et al., 2019), natural language processing (Xu et al., 2019; Radford et al., 2018), and autonomous driving (Litman, 2020). As DNNs become increasingly data-dependent, personal data may be involved for model training, raising critical privacy concerns. In response to privacy regulations such as the General Data Protection Regulation (GDPR) (Regulation, 2018) and the California Consumer Privacy Act (CCPA) (Pardau, 2018), the concept of Machine Unlearning (MUL) has emerged as a potential solution. MUL aims to remove specific data from trained models, allowing for the "right to be forgotten." Beyond privacy concerns, content regulation has become another key motivation for machine unlearning (Kurmanji et al., 2024; Shumailov et al., 2024). To remove impermissible knowledge such as unlicensed copyrighted material (Yao et al., 2023), malicious information (Yao et al., 2023), or harmful capabilities (Shumailov et al., 2024) from models, machine unlearning ensures that the unlearned models align with ethical and legal standards.

While existing MUL techniques have demonstrated strong performance in eliminating the influence of specific data on both privacy-sensitive and content-sensitive tasks (Warnecke et al., 2021; Li et al., 2024; Graves et al., 2021; Tarun et al., 2023; Golatkar et al., 2020; Liu et al., 2022), they often overlook a critical vulnerability: the susceptibility of unlearned models to malicious attacks. This gap raises a crucial question regarding the robustness of current MUL methods:

Are unlearned systems sufficiently resilient to withstand malicious attempts aimed at recovering or exploiting the unlearned information?

Recently, few studies attempts to answer this question specifically for large language models (LLMs) through in-contextual learning (Shumailov et al., 2024) or adversarial Suffix prompting (Yuan et al., 2024), but neither of them extends the investigation beyond LLMs. To address this critical question

in a broader context including various discriminative tasks and generative tasks in the computer vision domain, we revisit the concept of machine unlearning and investigate the hidden weaknesses of current MUL methods: successfully-unlearned knowledge can resurface through appropriate probs. To address this limitation, we introduce and formulate the concept of robust unlearning and a novel post-MUL adversarial attack, namely unlearning mapping attack (UMA), for MUL evaluation. Unlike traditional attempts altering the MUL process or tampering with the data to be unlearned, our UMA attack targets to failing unlearned models (i.e. reintroducing the unlearned knowledge) without being involved in the unlearning process. As a post-MUL attack, UMA only requires access to the model before and after the unlearning process, which practically makes the model provider or the MUL service provider an ideal candidate for carrying out such an attack. Our experiments, conducted on both discriminative and generative tasks using datasets such as CIFAR-10, CIFAR-100, Tiny-ImageNet, and ImageNet-1k, demonstrate that even when a model appears to have forgotten specific data, UMA can successfully retrieve the forgotten information, revealing a critical vulnerability in existing unlearning techniques.Furthermore, to mitigate this threat, we performed preliminary studies to incorporate the robust unleanrning concept into current unlearning methods to prevent adversaries from recovering forgotten data, ensures that unlearned models remain secure even in the face of advanced attacks like UMA.

Our contribution in this study can be summarized as follows:

- We revisit the definition of Machine Unlearning, and formulate the novel perspective: robust unleanring.
- We introduce a post-MUL malicious attack, UMA, to undermine Machine Unlearning, exposing a critical threat in existing unlearning methods. It compromises the unlearned systems without requiring any modifications to the data or the unlearning process, thus positioning it as a superior evaluation metric for machine unlearning verification.
- We conduct extensive empirical experiments to integrate this attack in the standard unlearning process, enhancing system robustness against such vulnerability.

2 RELATED WORK

Machine Unlearning. Machine unlearning (Cao & Yang, 2015) was initially introduced as a method to remove the influence of specific data points from machine learning models, driven by privacy and security concerns. The most straightforward unlearning method involves retraining the model from scratch without the undesired data. However, as models like LLMs increase in size and complexity, this retraining approach has become computationally prohibitive. To address this, researchers have developed alternative methods, including exact unlearning and approximate unlearning. Exact unlearning (Golatkar et al., 2020) aims to produce a model that behaves indistinguishably from a model trained from scratch without the forgotten data. For instance, SISA (Bourtoule et al., 2021) proposes to train separate models using multiple disjoint data shards and achieves exact learning by retraining the corresponding shard models associated with unlearning request. Considering scalability and cost-efficiency, approximate unlearning provides a more practical alternative, relaxing some constraints to improve efficiency while maintaining acceptable performance. For example, the first-order unlearning leverages the first-order Taylor series expansion of model parameters to compute gradient updates for MUL, while the second-order method incorporates the inverse Hessian matrix for more accurate parameter adjustments (Warnecke et al., 2021). To enhance stability and accuracy across different domains while maintaining computational efficiency, recently, SalUn (Fan et al., 2024) employs a weight saliency map, assigning different importance levels to model parameters, allowing them to be updated at varying rates. Despite these advancements, existing methods remain vulnerable to sophisticated attacks aimed at extracting forgotten information, leading to significant privacy and security concerns.

Attacks to MUL. The unlearning target usually deals with privacy-related or security-sensitive data, it is naturally assumed to be at risk of malicious attacks by adversaries. In fact, prior research has already explored various malicious attempts targeting MUL. For example, Qian et al. (2023) examines the possibility of injecting small, targeted noise into samples within the forget set. This manipulation leads the unlearned model to fail in classification tasks. Liu et al. (2024a) induces backdoor behavior in a model through the standard MUL process with selected data. Thudi et al. (2022); Zhang et al. (2024) examine how attackers can deceive others into believing the MUL process has

been completed when, in reality, the model has not forgotten the specified samples, or the unlearning process was never carried out. They leverage techniques from Data Ordering Attacks(Shumailov et al., 2021) to falsify Proof-of-Unlearning (PoUL), with the intent of either enhancing model performance or reducing computational costs. Different from these works either editing the unlearning data or modifying the unlearning algorithms, this study investigates post-MUL attack to exposing the hidden vulnerabilities in existing machine unlearning approaches.

Unlearning Verification. To evaluate the efficacy of an unlearning algorithm, various verification methods are proposed. *Attack-based verification* simulates a malicious attacker attempting to resurface or extract sensitive information from the unlearned model. For instance, membership inference attacks (MIA) (Shokri et al., 2017) is explored to determine whether a specific sample was part of the training data. Similarly, model inversion attacks (Fredrikson et al., 2015) tries to retrieve input samples given the model's outputs, potentially leaking class information to the attacker. Backdoor attacks, or backdoor verifications, are also widely used to assess unlearning efficacy (Sommer et al., 2020; Gao et al., 2024; Guo et al., 2024). Alternatively, following Proof of Learning (PoL) (Jia et al., 2021), *reproducing verification* (Zhang et al., 2024) works by recording logs during the unlearning operation, allowing users or third-party inspectors to reproduce the process and verify its authenticity, ensuring that the unlearning was executed as claimed. Beyond the above two categorical verification approaches, accuracy verification (Golatkar et al., 2020; Mehta et al., 2022) quantifies the unlearning performance on the retaining and forgetting data, and Relearning time verification (Tarun et al., 2023) inders the unlearning efficacy by counting the elasp time to relearning the forgotten information on the unlearned models. In this study, we introduces the UMA attack for evaluating unlearning efficacy.

3 ROBUST MACHINE UNLEARNING: PRELIMINARIES

Before introducing the concept and formulation of robust machine unlearning, let's first revisit the standard definition of machine unlearning.

3.1 VULNERABILITY IN CONVENTIONAL MACHINE UNLEARNING

Notation. Let $\mathcal{D} = \{(x_i, y_i)_{i=1}^N\}$ denote the training dataset used to train a model $f(\cdot; \theta)$, where N represents the number of training samples, each consisting of input features $x \in \mathbb{R}^d$ and target output y, and θ denotes the model's parameters. The model's training process is represented as $\mathcal{A}(f(\cdot; \theta), \mathcal{D})$, while the unlearning process is denoted by $\mathcal{U}(f(\cdot; \theta), \mathcal{D}_u)$, where $\mathcal{D}_u \subset \mathcal{D}$ is the subset of data to be unlearned. After the unlearning process, the updated model is expressed as $f_u(\cdot; \theta^u)$, i.e., $f_u(\cdot; \theta^u) = \mathcal{U}(f(\cdot; \theta), \mathcal{D}_u)$.

Definition 1 *(Machine Unlearning (Cao & Yang, 2015).) An unlearning process $\mathcal{U}(f(\cdot; \theta), \mathcal{D}_u)$ aims to find an unlearned model $f_u(\cdot; \theta^u)$ so that it closely aligns with a model trained from scratch on the retain set $\mathcal{D}_r = \mathcal{D}/\mathcal{D}_u$, i.e. $f_u(\cdot; \theta^u) = f_r(\cdot; \theta^r) = \mathcal{A}(f(\cdot; \theta), \mathcal{D}_r)$.*

Based on Definition 1, an unlearning algorithm should aligns closely with a retrained model on the retain set. However, for large-scale systems like foundation models whose retraining is computationally prohibitive or impractical for information unlearning, a commonly-used, practical strategy for effective forgetting is to diverge a unlearned model sufficiently from its prior behavior on the forget set while preserving its performance on the retain set. For instance, a generative unlearned model should be incapable of generating undesirable information in the forget set (Warnecke et al., 2021; Fan et al., 2024; Li et al., 2024). In other words, empirically, an unlearned model should decorrelate the input from the original output by a significant margin, ε_1, while maintaining close predictions for $x \in \mathcal{D}_r$. Specifically,

$$E_{x \in \mathcal{D}_u}[|f_u(x, \theta^u) - f(x, \theta)|_2] > \varepsilon_1, E_{x \in \mathcal{D}_r}[|f_u(x, \theta^u) - f(x, \theta)|_2] \le \varepsilon_2, \tag{1}$$

where E represents the statistical mean over a distribution, and ε_1 and ε_2 may vary depending on the task. However, Definition 1 and the conventional conditions formulated in (1) significant safety concerns, particularly regarding whether an unlearned model might reproduce the unlearned information when provided with any input.

Let's first consider the case of a generative model, which produces outputs based on various prompts or inputs. In the context of generative tasks, the primary objective of unlearning is to prevent the

Figure 1: An illustration of the novel malicious post-MUL attack on generative machine Unlearning: the attacker attempts to recover forgotten information from the unlearned neural network by injecting carefully-designed noise into the query input. The scenario corresponds to Proposition 2.

model from generating unlearned knowledge (Warnecke et al., 2021; Fan et al., 2024; Li et al., 2024). However, the standard definition of machine unlearning lacks constraints that guarantee the unlearned model cannot resurface the unlearned knowledge when exposed to arbitrary or carefully designed input prompts (Shumailov et al., 2024). This safety concern, formalized in Proposition 2, is critical in the context of using machine unlearning for knowledge regulation. We demonstrate this safety threat in Fig. 1.

Proposition 2 *For an unlearned generative system $f_u(\cdot, \theta^u)$ that satisfies conditions in (1), there may exist an input $\delta_x \notin \mathcal{D}_u$ s.t. $|f_u(\delta_x, \theta^u) - f(x, \theta)|_2 < \varepsilon_1, \forall x \in \mathcal{D}_u$.*

This safety risk also extends to machine unlearning in discriminative models, with slight modifications outlined in Proposition 3. Discriminative tasks, which focus on recognizing objects in a given query image, have the goal of preventing the model from identifying specific inputs post-unlearning. Naturally, this assumes that the inputs to the original model $f(\cdot, \theta)$ and the unlearned model $f_u(\cdot, \theta^u)$ share significant features. However, if slight perturbations δ_x on the data x can bypass the unlearning process, the system's security is compromised.

Proposition 3 *For an unlearned discriminative model $f_u(\cdot, \theta^u)$ that satisfies conditions in (1), there may exist a small non-zero $\delta_x \in \mathbb{R}^d$ (i.e. $||\delta_x|| < \epsilon$) s.t. $|f_u(x + \delta_x, \theta^u) - f(x, \theta)|_2 < \varepsilon_1, \forall x \in \mathcal{D}_u$.*

Note, δ_x in both Propositions are data-specific and model-specific. The extra constraint $||\delta_x|| < \epsilon$ for discriminative models ensures semantic similarity between x and $x + \delta_x$, so that the attack remains meaningful and realistic, aligning with its practical use of these models. By contrast, generative models allow for unconstrained δ_x, as the attack focuses exclusively on the outputs generated from crafted inputs, irrespective of input realism.

In sum, Propositions 2 and 3 emphasize that even if an unlearned system successfully decorrelates from the original output for a given input x, attackers could potentially craft inputs that cause the unlearned model to revert to outputs resembling those of the original model.

3.2 ROBUST UNLEARNING

The limitations and risks discussed in the previous section underscore significant safety concerns with unlearned models, particularly their vulnerability to malicious exploitation for knowledge resurface. While current methods generally satisfy the conditions in (**??**) and (1), they fail to guarantee that all traces of the unlearned data are entirely removed from the model, as emphasized in

Proposition 2 and 3. Furthermore, given that machine unlearning is inherently tied to security, it is crucial that unlearning algorithms exhibit strong resistance to adversarial attacks. In response, we propose a new definition, Robust Unlearning, that is adaptable across various machine learning contexts and resilient to malicious attacks, offering a more comprehensive and secure approach to unlearning.

Definition 4 *(Robust Unlearning). A unlearning process, $\mathcal{U}(f(\cdot;\theta),\mathcal{D}_u)$, is considered robust if $\forall x \in \mathcal{D}_u$, $\forall \delta_x \in \mathbb{R}^d$, we have conditions in (1), plus $|f_u(\delta_x, \theta^u) - f(x,\theta)|_2 > \varepsilon_1$ for generative tasks and $|f_u(x + \delta + x, \theta^u) - f(x,\theta)| > \varepsilon_1$ for discrimnative models (where $||\delta_x|| < \epsilon$).*

Intuitively, Robust Unlearning ensures that the system is incapable of producing the specified information, whether under normal conditions or in the presence of adversarial manipulation. We propose this as a comprehensive and robust standard for defining and evaluating unlearning algorithms. It is important to note, however, that the commonly used retraining method, a baseline in many existing unlearning techniques, does not inherently satisfy the criteria for Robust Unlearning. Due to the generalization capabilities of neural networks, even models trained without specific data may still generate corresponding information (Shumailov et al., 2024), thereby compromising the effectiveness of the unlearning process. To identify MUL-specific vulnerabilities, the unlearned model can be compared to a retrained model using the Robust Unlearning criteria in Definition 4. For instance, our empirical experiments on discriminative models with class-wise unlearning in table 1 show that retraining achieves strong robustness, while those evaluated unlearning algorithms are less robust to adversarial attacks, suggesting these vulnerabilities are intrinsic to the unlearning methods.

4 UNLEARNING MAPPING ATTACK

Building on this foundation of Robust Unlearning in the previous section, this section formally introduce our Unlearning Mapping Attack. It can serve two primary purposes in the context of machine learning. First, UMA generates malicious perturbations tailored to unlearned models, resurfacing forgotten knowledge for adversarial use. Second, UMA is a practical and actionable verification tool for benchmarking unlearning methods. By applying UMA to various unlearning algorithms with the same set of forget data, we can quantitatively assess their vulnerabilities against adversarial prob.

4.1 THREAT MODEL

Generally, in a machine unlearning workflow, the individuals involved can be divided into two groups: servers and participants (Liu et al., 2024b). Servers include model and service providers, who are responsible for providing the model or inference platform, while participants consist of data contributors and general users. While much of the existing research has focused on threats from participants, such as information leakage (Chourasia & Shah, 2023; Chen et al., 2021), adversarial unlearning (Liu et al., 2024a; Qian et al., 2023), and sabotage the unlearning process (Marchant et al., 2022), only a limited number of studies have examined unlearning threats from the server side(Thudi et al., 2022; Zhang et al., 2024).

In the unlearning threat we formulate in the previous section, the attacker is considered to be in the role of the service provider. We assume the attacker has full knowledge of the model *before and after* the unlearning process, as well as access to specific samples that need to be unlearned. Unlike previous studies where the service provider may attempt to fake unlearning to improve model performance or lower computational cost (Zhang et al., 2024), here, we assume the attacker's goal is to extract the forgotten information from the unlearned models. Given the increasing complexity of deep neural network architectures such as LLMs, it becomes nearly impossible to trace the exact amount of knowledge that remains within the network after unlearning, making these models highly susceptible to such attacks. Note, while the server is the most likely adversary due to its privileged access to the white-box attack setting, the threat is not strictly limited to the server. Anyone with access to the knowledge could theoretically execute UMA.

4.2 ATTACK FORMULATION

Recall that reproducing verification, such as Proof of Unlearning (PoUL), is a unique form of unlearning verification designed to ensure transparency from the model training side by requiring the

model trainer to report model parameters, data used, and the unlearning algorithm applied. While Thudi et al. (2022) points out that a forged map can be easily created to fake PoUL, the potential for malicious unlearning attempts from the server side is still limited, if not completely prevented.

Here, we propose an unlearning mapping attack, which focuses on uncovering residual information within the neural network rather than injecting new information. This attack method enables us to map the original output to a new input, allowing the unlearned neural network to still produce information that should have been removed. In this context, the UMA attack can be formulated as

$$\arg\min_{\delta_i} ||f_u(\delta_i, \theta^u) - f(x_i, \theta)||, \forall x_i \in \mathcal{D}_u. \tag{2}$$

Note that this attack method only modifies δ to achieve malicious information mapping. It does not require any change to the unlearning algorithm or the model parameters after the unlearning process. As a result, it would not be restricted by PoUL or any other existing verification method, making it difficult to detect and counter.

To achieve the attack goal outlined in (2), we introduce a gradient-based input mapping method. Drawing inspiration from the noise generation in adversarial attacks, we solve the optimization problem to minimize the difference between the unlearned model's output and the original model's output, as follows:

$$\arg\min_{\{\delta_i\}_{i=1}^N} \mathbb{E}\left[\mathcal{L}(f_u(\delta_i; \theta_u), f(x_i; \theta))\right], \tag{3}$$

where the loss function $\mathcal{L}$ can vary depending on the context, such as Mean Square Error Loss, Binary Cross-Entropy Loss, or KL Divergence Loss. To solve this optimization problem, we adopt the Projected Gradient Descent (PGD) method proposed in Madry et al. (2017) as a baseline to find the input δ. While PGD is normally used to maximize empirical loss, in this case, we aim to minimize the loss, thus taking the opposite direction of the gradient update:

$$\delta_i^{t+1} = \delta_i^t - \alpha \cdot sign[\nabla_\delta L(f_u(\delta_i^t; \theta_u), f(x_i; \theta))], \tag{4}$$

where α stands for the step size for each iteration. The pseudocode of the detailed input mapping attack process is provided in Algorithm 1. For simplicity, we only adopt the PGD-based mapping method as our baseline, though other optimization techniques can be substituted for potentially better performance.

Algorithm 1 Unlearning Mapping Attack

1: **Input:** Pre-trained model $f(\cdot; \theta)$, Unlearning algorithm $\mathcal{U}$, Unlearning dataset $\mathcal{D}_u$, Attack steps T, Attack step size η
2: **Output:** Unlearned model $f_u(\cdot; \theta^u)$, Attack dataset $\mathcal{D}_{atk}$
3: Save a copy of the model before unlearning $f_o(\cdot; \theta) \leftarrow f(\cdot; \theta)$
4: Perform the unlearning process $f_u(\cdot; \theta^u) \leftarrow \mathcal{U}(f(\cdot; \theta), \mathcal{D}_u)$
5: Random initialize attack noise $\{\delta_i\}_{i=1}^N$
6: **for** k = 0 **to** T **do**
7:     Calculate loss $\psi \leftarrow \sum_{x_i \in \mathcal{D}_u} \mathcal{L}(f_o(x_i; \theta), f_u(\delta_i^k; \theta^u)))_{i=1}^N$
8:     Update attack noise $\{\delta_i^{k+1}\}_{i=1}^N \leftarrow \{\delta_i^k\}_{i=1}^N - \eta \cdot sign(\nabla_{\{\delta_i^k\}_{i=1}^N} \psi)$
9:     $\{\delta_i^{k+1}\}_{i=1}^N \leftarrow clip(\{\delta_i^{k+1}\}_{i=1}^N, 0, 1)$
10: **end for**
11: Construct attack dataset $\mathcal{D}_{atk} \leftarrow (\delta_i^{k+1}, y_i)_{i=1}^N$

Note, while our gradient-based UMA does not guarantee exploration of all possible perturbations for robust unlearning, it provides a practical and actionable framework for identifying vulnerabilities in unlearning methods. Even in cases where UMA does not succeed, the absence of successful attacks strengthens the empirical evidence that the model may satisfy the robust unlearning criteria.

5 EXPERIMENTS

In this section, we first evaluate our attack method on existing unlearning methods for both discriminative and generative tasks. Then we conduct preliminary attempt to improve robustness of existing machine learning by integrating the robust unlearning concept into the standing MUL process.

CIFAR10	No Atk			$\epsilon = 8/255$		$\epsilon = 16/255$	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	94.13	100	0.9796	-	-	-	-
retrain	93.99	0	0	0	0.0012	0	0.0020
FT	92.21	22.20	0.0928	99.96	0.9934	100	0.9892
RL	91.70	0	0	18.62	0.0636	56.02	0.2534
IU	89.73	21.38	0.1522	99.68	0.9684	99.90	0.9780
l_1-sparse	91.53	0	0	73.00	0.3680	97.12	0.6886
SalUn	92.18	0	0.0002	6.04	0.0292	32.58	0.1986
CIFAR100	No Atk			$\epsilon = 8/255$		$\epsilon = 16/255$	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	75.25	100	0.9908	-	-	-	-
retrain	70.15	0	0	0	0	0	0
FT	71.38	57.28	0.5244	99.88	0.9960	99.96	0.9968
RL	71.65	3.04	0.1976	84.84	0.5172	97.52	0.6792
IU	70.88	79.16	0.7620	99.96	0.9852	99.92	0.9916
l_1-sparse	70.16	38.28	0.2072	99.96	0.9400	99.96	0.9452
SalUn	72.07	2.00	0.1976	88.24	0.6500	98.28	0.8104
Tiny-ImageNet	No Atk			$\epsilon = 8/255$		$\epsilon = 16/255$	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	64.17	99.96	1	-	-	-	-
retrain	59.41	0	0	0	0	0	0
FT	58.89	22.18	0.4192	99.94	0.9986	99.92	0.9984
RL	54.24	0.06	0.0096	90.32	0.4230	99.42	0.6726
IU	54.86	73.94	0.7932	99.94	0.9996	99.92	0.9998
l_1-sparse	55.76	0.46	0.0066	96.10	0.1108	99.88	0.1306
SalUn	54.68	0	0	59.86	0.2618	90.48	0.5630

Table 1: The Test Accuracy (TA), Unlearning Accuracy (UA), and MIA score of different baselines before and after Unlearning Mapping Attack for the Class Unlearning scenario. The attack is bounded with a maximum strength of 8/255 and 16/255. The original here indicates the model performance before unlearning.

5.1 EXPERIMENT SETUP

For **discriminative model unlearning**, we choose ResNet50 as our model backbone and conduct experiments on CIFAR10, CIFAR100, and Tiny-ImageNet datasets. We consider both class-wise and instance-wise unlearning in our experiments. For class-wise unlearning, following convention, we select class 0 for CIFAR10, class 5,16,25,34,78 for CIFAR100, and class 4,12,66,72,97,143,149,165,175,190 for Tiny-ImageNet as the unlearning target. For instance-wise unlearning, we randomly select 5000 samples for CIFAR10 and CIFAR100, 10000 samples for Tiny-ImageNet to evaluate efficacy of data forgetting. As mentioned earlier, the attack for discrimination tasks unlearning needs to be bounded or it would be meaningless otherwise. Therefore, we bound the perturbation to 8/255 and 16/255, which represent the maximum noise intensity while preserving major feature information. In the discrimination unlearning experiment, we adopt several existing unlearning methods as baselines, which include FT (Warnecke et al., 2021), RL (Golatkar et al., 2020), IU (Koh & Liang, 2017; Izzo et al., 2021), l1-sparse (Jia et al., 2023) and SalUn (Fan et al., 2024). We use both Unlearning Accuracy (UA) and Membership Inference Attack (MIA) as the evaluation metrics. Note that the Unlearning Accuracy is considered as the unlearning success rate in some existing works, where they consider UA the higher the better. However, the Unlearning Accuracy we used here is the model's pure accuracy on the forget dataset and should be considered the lower the better.

On the other hand, for **generative tasks**, we focus on image generation. We adopt class-wise unlearning using Masked AutoEncoder(MAE) on ImageNet1k dataset. We use I2I (Li et al., 2024)

CIFAR10	No Atk			8/255		16/255	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	94.13	100	0.9732	-	-	-	-
retrain	93.34	93.78	0.8636	99.98	0.9774	99.98	0.9728
FT	92.13	98.02	0.9124	99.98	0.9794	99.96	0.9810
RL	89.22	91.88	0.8012	99.96	0.9896	100	0.9866
IU	89.82	97.92	0.8926	99.98	0.9630	99.98	0.9628
l_1-sparse	91.32	95.76	0.8848	99.98	0.9842	100	0.9814
SalUn	90.55	93.48	0.8140	100	0.9884	99.98	0.9872

CIFAR100	No Atk			8/255		16/255	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	75.25	100	0.9924	-	-	-	-
retrain	73.92	72.72	0.7354	99.92	0.9910	100	0.9932
FT	70.90	96.44	0.9436	99.96	0.9970	100	0.9972
RL	71.05	86.04	0.7786	99.98	0.9946	100	0.9956
IU	71.89	99.20	0.9702	100	0.9894	100	0.9912
l_1-sparse	69.60	90.10	0.7404	99.98	0.9704	99.98	0.9756
SalUn	71.99	88.72	0.7936	99.94	0.9890	100	0.9914

Tiny-ImageNet	No Atk			8/255		16/255	
	TA	UA	MIA	UA	MIA	UA	MIA
Original	64.17	99.98	0.9978	-	-	-	-
retrain	61.81	60.17	0.6387	99.97	0.9735	100	0.9811
FT	55.66	85.42	0.8908	99.99	0.9969	99.97	0.9969
RL	55.36	72.88	0.8002	99.99	0.9962	99.98	0.9968
IU	56.33	94.85	0.9591	99.97	0.9967	99.98	0.9969
l_1-sparse	56.04	61.71	0.3836	99.99	0.7597	100	0.7614
SalUn	54.94	66.99	0.6237	99.99	0.9654	99.99	0.9681

Table 2: The Test Accuracy (TA), Unlearning Accuracy (UA), and MIA score of different baselines before and after Unlearning Mapping Attack for the Instance Unlearning scenario. The attack is bounded with a maximum strength of 8/255 and 16/255. The original here indicates the model performance before unlearning.

and SalUn (Fan et al., 2024) as our image generation unlearning baselines. Empirical comparisons and numerical evaluations including inception score (IS) (Salimans et al., 2016) and Fréchet inception distance (FID) (Heusel et al., 2017) metrics are used to evaluate image generation quality. For performance comparison, IIS is higher the better; while lower FID indicates good generation quality.

5.2 EXPERIMENT RESULT

As shown in Table 1, class-level unlearning for discriminative tasks generally show strong robustness against unlearning mapping attacks, especially in the case of retraining methods. This not only provides empirical evidence that a model can satisfy the robust unlearning criteria but also validates that class-wise discriminative unlearning effectively align the unlearned model with a retrained model. Note that we also include Test Accuracy(TA) in our evaluation metrics. While TA does not indicate any robustness of an unlearning method, it does reflect the strength of the unlearning. Since most unlearning methods have some hyperparameters that can adjust their strength, with stronger unlearning resulting in lower test accuracy, one can perform very strong unlearning to have good unlearning performance (low UA and MIA) and very low test accuracy which is impractical. Therefore, TA serves as a balancing metric, where lower TA can imply stronger unlearning, but the trade-off needs to be considered for robustness.

For instance-level unlearning, as shown in Table 2, all baseline methods display limited robustness against unlearning mapping attacks. While the retraining method performs the best, it still lacks

Figure 2: Unlearning Mapping Attack on image generation unlearning. I2I(Li et al., 2024) unlearning method is tested here. Reconstructed images are from ImageNet1k dataset.

Figure 3: Unlearning Mapping Attack on image generation unlearning. SalUn(Fan et al., 2024) unlearning method is tested here. Reconstructed images are from ImageNet1k dataset.

sufficient robustness, even with $\epsilon = 8/255$. This suggests that attackers can easily manipulate unlearned images, causing the model to re-recognize them, thus compromising the unlearning process.

Figure 2, 3 and Table 3 demonstrate our attack results on the image generation unlearning methods. Even when the unlearned model successfully avoids reconstructing images from the forget set, it can still generate well-restored images when fed an attacked input. Note that the attack can be unbounded for generation tasks since we only care about the model's output. However, as shown in both figures, only a small amount of noise is needed for the attack to succeed, highlighting the model's vulnerability to such attacks. Furthermore, the unlearning mapping attack does not significantly affect samples from the retain set, meaning there is no need to distinguish between the forget set and the retain set for this attack to be effective.

5.3 EMPIRICAL STUDY TOWARDS ROBUST UNLEARNING

Previous experiments reveal the possible hidden threat in current unlearning methods. In this section, we present our preliminary efforts, in terms of adversarial training and test-time sample pontification, to enhance the robustness of unlearning systems. The former targets to directly improve robustness of unlearning methods by altering the optimization trace, and the latter emphasizes to guard an vulnerable unlearned model via a denoising module.

Adversarial unlearning. Intuitively, this approach builds on adversarial training (Madry et al., 2017), optimizing the original unlearning objective and the robust unlearning term simultaneously:

$$\min_{f_u} \mathbb{E}\{L_u(f_u(x_u), y) + \max_{\delta \in \mathbb{A}(f, f_u, x)} L_u(f_u(\delta), y)\}, \tag{5}$$

where L_u is the unlearning loss term adopted from an existing unlearning method, x_u are the samples to be unlearned, and δ is the malicious attack input generated using $\mathbb{A}$, the attack algorithm described in Section 4.3. Our preliminary results, presented in Table 4, demonstrate a significant improvement

	IS						FID					
	No Atk		8/255		Unbound		No Atk		8/255		Unbound	
	R	F	R	F	R	F	R	F	R	F	R	F
Original	6.21	6.39	-	-	-	-	96.12	103.38	-	-	-	-
I2I	6.18	2.79	6.21	6.22	6.20	6.35	100.15	306.43	94.76	114.16	96.98	110.29
SalUn	6.05	2.42	6.02	6.11	6.13	6.27	130.45	330.79	102.75	133.82	94.15	108.44

Table 3: IS and FID results for Unlearning Mapping Attack on image generation unlearning. *R* and *F* stand for retain set and forget set. The attack strength is set to 0, 8/255, and unbound where the noise strength is unlimited. Note that a higher IS score indicates better image quality, while a lower FID score reflects improved image fidelity

	No Atk			8/255		16/255	
	TA	UA	MIA	UA	MIA	UA	MIA
RL-cifar10	91.53	0	0	1.44	0.0032	16.98	0.0532
RL-cifar100	71.15	0	0.0004	20.28	0.1088	27.32	0.2348

Table 4: Empirical experiment on Adversarial Unlearning implemented in (5). RL(Golatkar et al., 2020) serves as a backbone unlearning system and is tested on both CIFAR10 and CIFAR100 datasets. Compared to the results in Table 1, the robustness of the system increases substantially.

in system robustness when using robust unlearning. We use the unlearning method from Golatkar et al. (2020) as our backbone with the addition of the robust unlearning term. Compared to the original results in Table 1, the robustness of the system increases substantially under the robust unlearning framework.

Adversarial unlearning can generally be applied to most existing unlearning methods, provided that the forget set is used during the unlearning process. Therefore, methods such as retraining or fine-tuning, which do not directly use the forget set, cannot directly incorporate robust unlearning. It should be noted that the proposed adversarial unlearning incurs computational overheads due to the iterative adversarial sample generation in the unlearning process. The total overhead largely depends on the size of the forget set. For large-scale systems with extensive forget sets, the scalability of adversarial unlearning may be constrained by computational resources.

Test-time sample purification. Instead of modifying unlearning algorithms as adversarial unlearning, on-the-fly sample-based purification during inference help counter UMA without touching the unlearning process. As UMA operates by crafting adversarial noise added to query samples during inference, applying UMA-targeted purifiers to all queries before feeding them to the unlearned model might remove this adversarial noise and prevent forgotten knowledge from resurfacing. Preliminary studies and their quantitative results in the appendix A.2 show the potential of data purification to mitigate the UMA threat. Due to its computational-friendly, test-time purification is a practical alternative toward robust unlearning systems.

6 CONCLUSION

In this paper, we uncover a critical vulnerability present in most Machine Unlearning methods. We introduce the Unlearning Mapping Attack, which is designed to extract unlearned information from a system following the unlearning process. Our experiments demonstrate that the Unlearning Mapping Attack can successfully retrieve information that was supposed to be forgotten, across both generative and discriminative tasks. Additionally, we conduct a preliminary study on plug-in robust unlearning, which enhances the system's resilience to such attacks. We hope our work draws attention to the importance of robustness in Machine Unlearning and encourages the integration of robustness considerations when designing and evaluating unlearning methods.

REFERENCES

Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *2021 IEEE Symposium on Security and Privacy (SP)*, pp. 141–159. IEEE, 2021.

Yinzhi Cao and Junfeng Yang. Towards making systems forget with machine unlearning. In *2015 IEEE Symposium on Security and Privacy*, pp. 463–480, 2015. doi: 10.1109/SP.2015.35.

Min Chen, Zhikun Zhang, Tianhao Wang, Michael Backes, Mathias Humbert, and Yang Zhang. When machine unlearning jeopardizes privacy. In *Proceedings of the 2021 ACM SIGSAC conference on computer and communications security*, pp. 896–911, 2021.

Rishav Chourasia and Neil Shah. Forget unlearning: Towards true data-deletion in machine learning. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 6028–6073. PMLR, 23–29 Jul 2023.

Chongyu Fan, Jiancheng Liu, Yihua Zhang, Eric Wong, Dennis Wei, and Sijia Liu. Salun: Empowering machine unlearning via gradient-based weight saliency in both image classification and generation. In *The Twelfth International Conference on Learning Representations*, 2024.

Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. Model inversion attacks that exploit confidence information and basic countermeasures. In *Proceedings of the 22nd ACM SIGSAC conference on computer and communications security*, pp. 1322–1333, 2015.

Xiangshan Gao, Xingjun Ma, Jingyi Wang, Youcheng Sun, Bo Li, Shouling Ji, Peng Cheng, and Jiming Chen. Verifi: Towards verifiable federated unlearning. *IEEE Transactions on Dependable and Secure Computing*, 2024.

Aditya Golatkar, Alessandro Achille, and Stefano Soatto. Eternal sunshine of the spotless net: Selective forgetting in deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Laura Graves, Vineel Nagisetty, and Vijay Ganesh. Amnesiac machine learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 11516–11524, 2021.

Yu Guo, Yu Zhao, Saihui Hou, Cong Wang, and Xiaohua Jia. Verifying in the dark: Verifiable machine unlearning by using invisible backdoor triggers. *IEEE Transactions on Information Forensics and Security*, 19:708–721, 2024. doi: 10.1109/TIFS.2023.3328269.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.

Zachary Izzo, Mary Anne Smart, Kamalika Chaudhuri, and James Zou. Approximate data deletion from machine learning models. In *International Conference on Artificial Intelligence and Statistics*, pp. 2008–2016. PMLR, 2021.

Hengrui Jia, Mohammad Yaghini, Christopher A Choquette-Choo, Natalie Dullerud, Anvith Thudi, Varun Chandrasekaran, and Nicolas Papernot. Proof-of-learning: Definitions and practice. In *2021 IEEE Symposium on Security and Privacy (SP)*, pp. 1039–1056. IEEE, 2021.

Jinghan Jia, Jiancheng Liu, Parikshit Ram, Yuguang Yao, Gaowen Liu, Yang Liu, Pranay Sharma, and Sijia Liu. Model sparsity can simplify machine unlearning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=0jZH883i34.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International conference on machine learning*, pp. 1885–1894. PMLR, 2017.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. Towards unbounded machine unlearning. *Advances in neural information processing systems*, 36, 2024.

Guihong Li, Hsiang Hsu, Chun-Fu Chen, and Radu Marculescu. Machine unlearning for image-to-image generative models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=9hjVoPWPnh.

Todd Litman. Autonomous vehicle implementation predictions: Implications for transport planning. 2020.

Yi Liu, Lei Xu, Xingliang Yuan, Cong Wang, and Bo Li. The right to be forgotten in federated learning: An efficient realization with rapid retraining. In *IEEE INFOCOM 2022-IEEE Conference on Computer Communications*, pp. 1749–1758. IEEE, 2022.

Zihao Liu, Tianhao Wang, Mengdi Huai, and Chenglin Miao. Backdoor attacks via machine unlearning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 14115–14123, 2024a.

Ziyao Liu, Huanyi Ye, Chen Chen, and Kwok-Yan Lam. Threats, attacks, and defenses in machine unlearning: A survey, 2024b.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Neil G Marchant, Benjamin IP Rubinstein, and Scott Alfeld. Hard to forget: Poisoning attacks on certified machine unlearning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pp. 7691–7700, 2022.

Ronak Mehta, Sourav Pal, Vikas Singh, and Sathya N Ravi. Deep unlearning via randomized conditionally independent hessians. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10422–10431, 2022.

Stuart L. Pardau. The california consumer privacy act: Towards a european style privacy regime in the united states. 2018.

Wei Qian, Chenxu Zhao, Wei Le, Meiyi Ma, and Mengdi Huai. Towards understanding and enhancing robustness of deep learning models against malicious unlearning attacks. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 1932–1942, 2023.

Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. 2018.

General Data Protection Regulation. General data protection regulation (gdpr). *Intersoft Consulting, Accessed in October*, 24(1), 2018.

Doyen Sahoo, Wang Hao, Shu Ke, Wu Xiongwei, Hung Le, Palakorn Achananuparp, Ee-Peng Lim, and Steven CH Hoi. Foodai: Food image recognition via deep learning for smart food logging. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 2260–2268, 2019.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.

Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE symposium on security and privacy (SP)*, pp. 3–18. IEEE, 2017.

Ilia Shumailov, Zakhar Shumaylov, Dmitry Kazhdan, Yiren Zhao, Nicolas Papernot, Murat A Erdogdu, and Ross J Anderson. Manipulating sgd with data ordering attacks. *Advances in Neural Information Processing Systems*, 34:18021–18032, 2021.

Ilia Shumailov, Jamie Hayes, Eleni Triantafillou, Guillermo Ortiz-Jimenez, Nicolas Papernot, Matthew Jagielski, Itay Yona, Heidi Howard, and Eugene Bagdasaryan. Ununlearning: Unlearning is not sufficient for content regulation in advanced generative ai. *arXiv preprint arXiv:2407.00106*, 2024.

David Marco Sommer, Liwei Song, Sameer Wagh, and Prateek Mittal. Towards probabilistic verification of machine unlearning. *arXiv preprint arXiv:2003.04247*, 2020.

Ayush K Tarun, Vikram S Chundawat, Murari Mandal, and Mohan Kankanhalli. Fast yet effective machine unlearning. *IEEE Transactions on Neural Networks and Learning Systems*, 2023.

Anvith Thudi, Hengrui Jia, Ilia Shumailov, and Nicolas Papernot. On the necessity of auditable algorithmic definitions for machine unlearning. In *31st USENIX Security Symposium (USENIX Security 22)*, pp. 4007–4022, 2022.

Alexander Warnecke, Lukas Pirch, Christian Wressnegger, and Konrad Rieck. Machine unlearning of features and labels. *arXiv preprint arXiv:2108.11577*, 2021.

Hu Xu, Bing Liu, Lei Shu, and Philip S Yu. Bert post-training for review reading comprehension and aspect-based sentiment analysis. *arXiv preprint arXiv:1904.02232*, 2019.

Yuanshun Yao, Xiaojun Xu, and Yang Liu. Large language model unlearning. *arXiv preprint arXiv:2310.10683*, 2023.

Hongbang Yuan, Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. Towards robust knowledge unlearning: An adversarial framework for assessing and improving unlearning robustness in large language models. *arXiv preprint arXiv:2408.10682*, 2024.

Binchi Zhang, Zihan Chen, Cong Shen, and Jundong Li. Verification of machine unlearning is fragile. In *Forty-first International Conference on Machine Learning*, 2024.