LLM-Assisted versus Agentic Approaches to De Novo Minibinder Design for a KRAS G12D Neoantigen

Yilan Wang [1] Aaron Kollasch

Abstract

We compare three modes of large language model (LLM) integration into de novo protein minibinder design: (1) human-directed designs with LLM in the loop, where a researcher makes every scientific decision while using an LLM to accelerate code generation and analysis; (2) LLM-agent design, where the researcher specifies only the therapeutic target and the agent handles pipeline construction and in silico evaluation autonomously; and (3) LLM-agent designs with human in the loop, where the researcher specifies the therapeutic target and provides extensive scientific context and feedback during pipeline construction and in silico evaluation. We target the KRAS G12D neoantigen peptide VVGADGVGK on HLA-A*11:01. Across two rounds of design screens, the human-led campaign produced 17 high-confidence hits and the LLM-agent campaigns presented 41 and 6 top hits, respectively. Evaluated by our new multi-layered evaluation suite of structure/sequence quality, Rosetta-based energy calculations, and docking verification, we conclude that agents are useful for exploring new design ideas and running large parallel campaigns, but expert supervision remains essential for correct binding orientation, calibrated specificity thresholds, and viable candidate selection.

1. Introduction

1.1. Minibinders Present Emerging Opportunities For Therapeutics Development

De novo protein minibinders are small (< 120 residues), hyperstable proteins designed to bind a specific surface patch with nanomolar-to-picomolar affinity (Cao et al., 2022; Watson et al., 2023; Bennett et al., 2023). The field has validated binders to more than 200 protein targets, with wide applications in medicine, nanotechnology, and various industrial sectors (Yang et al., 2026; Listgarten & Jiang, 2026). De novo minibinders tend to show high selectivity against human extracellular proteins, likely because their rigid, helix-rich scaffolds limit the induced-fit promiscuity seen in binders with flexible loops. Deep learning models have enabled rapid structure-based minibinder designs for therapeutics (Glögl et al., 2024; Ragotte et al., 2025; Sappington et al., 2024), while key challenges remain, including low binding affinity, off-target toxicity, and unclear functional activity (Bennett et al., 2023; Yu et al., 2026; van den Berg et al., 2015; Zhang et al., 2025; Son et al., 2024; Kosonocky et al., 2026).

1.2. Peptide–MHC Class I Complexes Are Important But Challenging Design Targets

Major Histocompatibility Complex Class I (MHC-I) molecules present 8–11-residue peptides derived from intracellular proteins on the cell surface for immune surveillance. In cancer cells, disease-driving mutations generate neoantigens and are presented as short peptides by MHC, which can be targeted by engineered proteins for therapeutics and diagnostics. Compared with conventional protein targets, pMHC-I complexes pose acute specificity challenges: the dominant surface is MHC, conserved across all peptides in a given allele, while the peptide exposes only a narrow, partially solvent-accessible strip. A binder must make extensive peptide contacts while discriminating the target from thousands of self-peptides on the same HLA–demands that make pMHC-I one of the hardest binder design challenges. Previous efforts have shown that while it is often possible to generate binders to a given target, the specificity screen is extremely challenging, as we may not know *a priori* which off-target hits exist.

Three groups (Liu et al., 2025; Householder et al., 2025; Johansen et al., 2025; Hickok & Stromnes, 2025) published de novo pMHC-I minibinders using the same core toolkit: RFdiffusion (Watson et al., 2023) for backbone generation above the peptide-binding groove, ProteinMPNN (Dauparas et al., 2022) for sequence design, and AlphaFold2 (AF2) (Jumper

[1]Department of Systems Biology, Harvard Medical School, Boston MA, USA. Correspondence to: Yilan Wang <wangyilan0304@gmail.com>.

Accepted at the 2026 Workshop on Generative and Agentic AI for Biology (ICML 2026). Copyright 2026 by the authors.

et al., 2021; Bennett et al., 2023; Motmaen et al., 2023) for structural filtering and specificity screening. Collectively, they demonstrated that, for certain targets, it is possible to rapidly design de novo minibinders with high binding affinity, high specificity, and highly functional activity as part of re-engineered T cell receptors or T cell engagers. AlphaFold2, contact-based filtering (contact molecular score (Cao et al., 2022)), and inverse-folding models (ProteinMPNN (Dauparas et al., 2022)) led to a desirable number hits for experimental validation within 2-3 design rounds. Other approaches (Pacesa et al., 2025; Stark et al., 2025; Cho et al., 2025) operate without iterative rounds but have not been benchmarked on pMHC-I.

A persistent challenge across all de novo binder campaigns is the gap between in silico confidence metrics and experimentally measured binding affinity. Large-scale studies using quantitative affinity data, spanning tens of thousands of antibodies and minibinder interactions, have shown that AlphaFold-derived metrics such as interaction prediction score from aligned errors (ipSAE) and interface predicted template modeling (ipTM) enrich for binders but produce high false-positive rates and fail to rank affinity reliably (Bio, 2026; Overath et al., 2025; Cotet et al., 2025; mun, 2026). Performance varies markedly by target, point mutation campaigns are a particular blind spot, and providing structural templates during prediction improves but does not solve classification of binding vs non-binding (Bio, 2026; Pak et al., 2023). These findings explain why large campaigns generating thousands of computationally screened designs typically yield only a handful of experimentally validated hits, and why developability remains unsystematically addressed.

1.3. LLM Integration in Protein Design

Three modes of LLM integration can be identified along a spectrum of human control:

Human designs with LLM in the loop The researcher makes every scientific decision and uses an LLM as an interactive programming assistant that generates code, debugs scripts, and summarizes the literature. The LLM is easy to adopt because it accelerates specific tasks but does not require significant changes to the research workflow.

LLM-agent designs with human in the loop Platforms such as Latent Labs (Team et al., 2025; 2026), Boltz, and Tamarind Bio accept a target specification and broad objectives, with an agent handling literature search, pipeline assembly, backbone generation, sequence design, and in silico evaluation (Marshall, 2026). The researcher reviews candidate outputs rather than intermediate decisions. These platforms have claimed nanobody and scFv binders to challenging targets including GPCRs and KRAS (G12D). A recent hackathon showed that agents with access to existing

Figure 1. **General binder design pipeline.** For all human and agentic design campaigns, RFdiffusion was used to propose minibinder backbone structures for the specified target and hotspot, followed by ProteinMPNN to sample sequences and AlphaFold to predict complex structures. For round 2, partial diffusion on the final structures generated refined backbones for ProteinMPNN. Candidate filtering and refinement with Rosetta, ESMFold, and other metrics were performed after each step. The binders designed in all 3 pipelines were compared against one another.

protein design toolkits were able to design de novo binders to a certain target without human intervention and achieved similar binding hit rate (single-digit nanomolar binder validated in the wet lab) (mun, 2026).

No human in the loop Fully autonomous AI-driven science, where agents independently form hypotheses, execute wet-lab experiments, and iterate without human intervention, is an aspirational frontier that several companies are actively pursuing. However, no peer-reviewed papers, preprints, or experimental benchmarks have been published to support these claims. For the purposes of this paper, fully autonomous protein design without human oversight remains an unvalidated aspiration rather than a demonstrated capability, and we do not attempt to reproduce it here.

2. Problem Statement

We present an extremely difficult target for de novo minibinder design B.1 to prevent possibility of retrieving known binders from LLM training data or an online search– KRAS G12D is present in many cancers, yet current approaches have not generated any de novo binder for KRAS presented at the cell surface by MHC I with high specificity. The neoantigen peptide VVGADGVGK (HLA-A*11:01) differs from wildtype VVGAGGVGK by a single glycine-to-aspartate substitution at position 5. We use the Liu et al. (Liu et al., 2025) framework as a starting point (Figure 1) and ask: (1) how effectively can a researcher with LLM assistance produce viable candidates for this novel, challenging target? (2) what can an LLM agent contribute? and (3) where does domain expertise remain irreplaceable? We

expect resulting designs to be novel as all existing binders to KRAS G12D are either small molecules via intracellular delivery (O'Reilly et al., 2026; Park et al., 2026; Weller et al., 2025) or re-engineered T cell receptors or antibodies for a 10mer KRAS peptide with a different aspartate side chain 3D orientation (Ma et al., 2024; Leidner et al., 2022; Tran et al., 2016; Zheng et al., 2024; Sim et al., 2020; Ahn et al., 2026).

3. Successful binder designs inform new design evaluation metrics

3.1. Analysis of Published Designs

Prior to launching our campaigns, we analyzed 18 published binder sequences (Liu et al., 2025) to calibrate the relative difficulty of our target (PDB access number 9UV8). The peptide has a good total exposed peptide surface area with a highly exposed neoepitope (p5) (Supp. Figure B.1A), so it should be possible to design a tight binder. However, it is challenging to design a specific binder that avoids the wildtype KRAS G12, because there is only one residue difference. The nearby residues (p4-p7) are accessible but these small residues (especially glycine) may be too weak to form strong interactions with the binder, i.e., no large hydrophobic residues such as phenylalanine, leucine, or isoleucine as in Liu et al. designs (Supp. Figure B.1B). A successful design needs a precise positively-charged residue forming a salt bridge or hydrogen bond with the aspartate (p5).

We used the 18 published binder sequences (Liu et al., 2025) to determine the input configurations for running AlphaFold3 (Abramson et al., 2024) on the minibinder-peptide-MHC tertiary structures. When we omitted the β-2 microglobulin chain, two designs (prame-9 and sars-6) showed back-face MHC docking in blind AF3 predictions, i.e., the binder engaged the MHC α-helix groove rather than the peptide-presenting face. Running AlphaFold3 with default MSA setting (including MSAs for the designed minibinder in many cases) led to reduced contact between binder and peptide for 4 designs, as indicated by significantly decreased ipSAE value, though the change can be overlooked due to low overall binder root mean squared deviation (RMSD) (differences < 0.2). Running AlphaFold3 with no MSA for the minibinder and the MHC also led to reduced contact between binder and peptide for 5 designs, by the same ipSAE metric. Therefore, we ran AlphaFold3 with the full pMHC-binder complex and disabled MSA generation for the minibinder.

Structure and sequence analysis of the 18 designs revealed consistent features: all adopt 3–4-helix topologies arcing above the peptide groove; 17 designs contact the peptide with α helices and 1 design uses a loop as the primary peptide-contacting element. Net charge is consistently negative (-2.8 to -10.8), no cysteine, and the amino acid composition is dominated by Asp, Glu, Ala, Leu, and Arg. Hotspot Rosetta contact molecular surface (CMS) scores are high (including polar residues), mean binder predicted local distance difference test (pLDDT) > 85, and ipSAE > 0.8 across validated designs (Figure B.2,Table 1). Compared to criteria defined by BindCraft on other targets (Pacesa et al., 2025), the designs show higher average interface hydrophobicity and more unsatisfied hydrogen bonds (Figure B.3).

3.2. Customized evaluation metrics for pMHC binders

We provide the following additional evaluation metrics in addition to AlphaFold2 initial guess (iPAE, binder pLDDT and binder RMSD), and AlphaFold2 monomer pLDDT:

Improved AlphaFold2 initial-guess scoring with ip-SAE Each backbone–sequence pair is predicted using AlphaFold2-initial-guess protocol (Bennett et al., 2023). A key addition is to use **ipSAE** computed exclusively over binder–peptide residue pairs rather than standard interface predicted aligned error (iPAE), which is dominated by the much larger binder–MHC interface and is therefore a poor proxy for peptide-specific binding. Designs passing ipSAE $\geq$ 0.8 proceed. We examined iPAE and ipSAE values of the same designs, and observed that certain designs with iPAE> 10 but ipSAE< 0.8 still produced promising results upon further partial diffusion and sequence redesign.

Additional sequence quality evaluation To reduce non-specific binding, the designs are evaluated for net charge, surface hydrophobicity, and the presence of cysteine (can form disulfide bonds with unintended targets). The thresholds for net charge and surface hydrophobicity were calibrated based on authors' successful designs.

AlphaFold3-based evaluation on structural confidence and Rosetta energy calculations Template-based AlphaFold2 refolding decreases false negative rate, but introduces the issue of circular evaluation. AlphaFold2 models are also limited in cases where a de novo protein is present in the complex, meaning that no MSA can be computed effectively. Therefore, much of the downstream structure-based evaluations are based on template-free AlphaFold3 generated structures on a handful of high-confidence designs. Biophysical properties using Rosetta are commonly used in AI-based protein designs (Overath et al., 2025; Pacesa et al., 2025; Listgarten & Jiang, 2026), and were therefore incorporated into our evaluation framework.

It remains to be seen whether these additional metrics correlate with experimental outcomes.

4. Human Designs with LLM in the Loop

4.1. Overview of Pipeline and Evaluation Methods

The pipeline (Figure A.1) follows an existing pipeline (Liu et al., 2025) with room to innovate; the additions below constitute our primary methodological contribution. The authors directed all implementations and result visualizations in collaboration with the Claude Code (Sonnet 4.6 and Opus 4.8) by providing goals and feedback for each step. Each suggestion and script written by Claude were evaluated by the authors. The pipeline was executed on an academic computing cluster with CPU and GPU access.

To circumvent tedious manual inspections and wasting computing resources on poor backbones, careful research was conducted to filter backbones by geometric alignment with the peptide target and similarity with the authors' successful designs (secondary structure and radius of gyration) (More details in Appendix D). Among these, Claude suggested using the fraction of binder residues in proximity to the MHC over those in proximity to the peptide. While this makes intuitive sense, it practically removed promising backbones. Early human intervention avoided filtering out positive designs. Another important reason to add geometric filters is that RFdiffusion is known to have difficulty targeting polar residues README so we had to remove the mutant from the RFdiffusion hotspots input.

Round 1 produced only 2 designs with iPAE < 5 from 310 geometrically filtered backbones. Most designs also have poly-Alanines, indicating low confidence in the backbones. This motivated Round 2 partial diffusion (partial_t 12–25) from 25 surviving backbones with a less stringent threshold (iPAE < 10). This generated 199 designs passing all AlphaFold2 initial guess filters, of which 49 passed the primary specificity filter of Δ pAE_int_peptide < -0.5, iPAE of each design against G12D (on-target) and G12 WT (off-target) peptides; we note this threshold has not been independently calibrated for this specific peptide pair and experimental validation is required to assess its discriminative power.

4.2. Final Design Candidates

Upon evaluation with AlphaFold3-based metrics (Appendix E), 17 designs have appropriate energetics, specific polar interactions and overall high CMS score with the peptide P5 G12D, despite higher number of buried unsaturated hydrogen bonds and higher fraction of exposed hydrophobicity, as expected (Section 3.1, Figure B.2, Figure B.3).

These passing designs cluster around the binder_255 scaffold lineages, with highly promising candidates from binder_34 and binder_252, containing 91 or 95 residues, helix dominant topologies (3 helices) arcing above the peptide groove, and net charge -10–+2 (Table 1). Contact map analysis shows that they all carry 1–2 Arg or Lys making a

hydrogen bond or salt bridge to the p5 Asp of KRAS G12D, indicating good specificity for G12D over wild-type KRAS peptide (Figure 2).

FastRelax of the these designs yields dG_separated -52.9 to -67.6 REU (more negative indicates lower Rosetta interface energy), packstat 0.53–0.65 (higher indicates better interface packing quality), dSASA_int 2014–2858 Å² (higher indicates larger total buried interface area), delta_unsatHbonds 2–16 (lower indicates fewer unsatisfied buried hydrogen bonds, which is better), and CMS hotspot score 28–62 Å² (higher values indicates tighter geometric complementarity to the key specificity residue). All except for net charges and presence of 1 cysteine in some designs compare favorably with validated successful designs (Table 1, Figure B.2, Figure B.3). The issues with net charges and cysteine presence have been easily fixed with ProteinMPNN redesign while keeping the non-Cys interface residues fixed in Round 2.5.

4.3. Results

Scale of screening Across 2 rounds, 2,300 backbone trajectories and 18,459 backbone–sequence pairs were evaluated to yield 17 specific candidates–a ratio of 1,100 computational designs per passing candidate, consistent with published campaigns (Overath et al., 2025; Liu et al., 2025). Due to target-specific research and benchmarking, it took several weeks and many CPU and GPU resources to complete the designs.

LLM-assisted programming accelerates the design process but lacks scalability Environmental setup used to be a major bottleneck in pre-LLM period, given missing YAML files and differences in computing systems. With LLM assistance, human researchers can quickly gather relevant information to install new tools and patch environmental issues. Researchers' domain expertise helps spot hallucination and improper result interpretations by the LLM. However, given the large number of decisions and multiple screening rounds of many candidates, it can get overwhelming to remember why each decision is made, especially when designing binders across very different targets.

5. Agentic Design with a Simple Prompt and Minimal Human Supervision

5.1. Overview of Pipeline

5.1.1. ROUND 1

An LLM agent (Claude Sonnet 4.6, Anthropic) in the Claude Code harness (v2.1.132) was provided a detailed prompt instructing it to design a minibinder to pMHC presenting the KRAS G12D peptide (Appendix F.1). The agent was also provided a pdf of the relevant paper (Liu et al., 2025), its supplementary materials, and a relevant PDB template (Zhu

et al., 2025), and AlphaFold 3-no-MSA predicted pMHC-binder complexes for the published minibinders. Given these inputs, the agent autonomously read the paper, installed relevant tools (RFdiffusion (Watson et al., 2023), ProteinMPNN (Dauparas et al., 2022), and ColabFold (Mirdita et al., 2022)), wrote scripts to run the tools, and managed their execution (Figure A.1).

Three main tasks were performed in Round 1: First, 500 RFdiffusion backbones were sampled with peptide hotspot conditioning. Then, ProteinMPNN was used to sample sequences for each backbone. Finally, AlphaFold2 initial guess was used for structure prediction and filtering. Three manual interventions were needed in Round 1:

- A nudge to follow RFdiffusion's installation instructions from its README, as the agent was encountering errors creating an incorrect environment.

- A cleanup of hanging background shells.

- An instruction to run AF2 on the remaining RFdiffusion designs 93-500 – the agent had stopped folding designs after encountering errors. The agent chose to run AF2 only on 10 designs with highest predicted specificity for G12D, increased to 80 on further nudging.

5.1.2. ROUND 2

After Round 1 was complete, the agent was prompted to run Round 2, consisting of partial diffusion and sequence generation (Appendix F.2). The agent applied partial diffusion (partial_T=20) from four Round 1 seeds, followed by geometry filtering, ProteinMPNN redesign, and AF2 initial-guess evaluation on the top 40 designs per seed.

5.1.3. COMPUTATIONAL COST

The two agentic rounds completed in about 1.5 days, with a token cost of $85.57. Together with cost of the GPU server (a single cloud-hosted Nvidia RTX 5090), the total computational cost was roughly $100.

5.1.4. OPENAI CODEX

We also attempted the same Round 1 prompt using OpenAI's Codex agent (GPT-5.5). However, the agent stopped at requesting AF3 structures for the already-provided structures from the paper. After a nudge to continue without AF3 structures, it opted to download and run Boltz-2. However, at this point, the agent ran out of tokens. It is likely that this model is capable of running the same tools, but it would need a different prompt or harness to help minimize human intervention.

5.2. Final Design Candidates

Round 1 generated 500 backbones, of which 250 passed a P5 proximity screen (minimum $C\beta$ distance < 9.5 Å). Approximately 2,576 designed sequences were scored for binding specificity; the agent-defined "specificity score" was the change in ProteinMPNN likelihood of the binder given the variant peptide versus the wild-type peptide. Only 4 backbones (binder_7, binder_17, binder_86, binder_93) yielded AF2-predicted pMHC interfaces (pLDDT ≥ 67, pAE_interaction below the 31.5 "no contact" floor); the remaining backbones uniformly showed no interface signal despite passing geometry. From these 4 backbones the agent identified 9 experimental candidates (pLDDT 67–75, specificity score +0.037–+0.112).

Round 2 partial diffusion from the 4 seeds produced 800 backbones, 634 passing the geometry screen. Evaluating 160 designs (top 40 per seed by specificity), 41 passed combined filters (pLDDT ≥ 67, specificity ≥ 0.025). Sequences were 32–68% identical to Round 1. Round 2 improved on Round 1: best pLDDT rose from 75.0 to 77.96 (binder_22_s4, seed b7_t03_s7), best specificity from +0.112 to +0.189 (binder_160_s5, seed b7_t03_s2), and binder_68_s1 (seed b17_s1) reached RMSD = 2.0 Å to its design model. However, these features rarely co-occurred: only *1 design* passed the pLDDT ≥ 70 and RMSD ≤ 2.0 Å filters.

5.3. Results

Human review of the agent's analysis scripts, decisionmaking log, and results revealed several critical issues. A full review is in Appendix G. Overall, the agent was able to set up the tools and largely correctly use the tools. In the case where the agent mixed up the protein chain order input in partial diffusion, it was able to realize the lack of change in generated backbones and fix the problem without human intervention.

Innovative ways to screen designs before compute-heavy steps After ProteinMPNN sequence generation, instead of proceeding with the relatively long AlphaFold 2 initial guess to fold the designs, the agent used ESMFold to calculate binder pLDDT, which is fast and performs better than AlphaFold2 on α helix dominated miniproteins (Hýsková et al., 2026). To efficiently predict binders' preference for the G12D variant, the agent devised a ProteinMPNN-based "specificity score". Rather than computing the dssp, which requires protein folding, the agent used rough estimates based on amino acid (helix formers and strand formers), and computed aromatic contents (beneficial to hydrophobic packing), and alanine fractions. However, it still could not control the high alanine fractions.

Incorrect wild-type KRAS sequence The wildtype KRAS residue at codon 12 is Glycine (G), not Valine or Cysteine, which are two other common cancer-driving mutations, and the correct sequence was present in the input files, yet the agent used the wrong residue in both the iPAE off-target comparison and the ProteinMPNN log-likelihood scoring across multiple scripts. Providing the pdb structure of the wildtype KRAS pMHC (e.g., 8I5E) in the prompt may mitigate this problem.

Suboptimal hotspot residue choice The agent included C5 (Aspartic acid (D), polar) as an RFdiffusion hotspot, even though RFdiffusion's README explicitly discourages polar hotspots, and Liu et al. (2025), the paper provided to the agent, demonstrated that G12D should be targeted with hotspot residues adjacent to C5. In addition, the agent targeted both terminal anchor residues C1 and C7 as hotspots, constraining the geometric search space against the bent peptide conformation. Adding instructions to read the README page of the RFdiffusion repository may solve the first problem, while the second problem comes from lack of familiarity with pMHC structures and protein design.

Implausible sequences and structures All of the generated minibinders contained long stretches of Alanine (A). While this also occurred in the human Round 1, it was corrected in human Round 2 by partial diffusion and resampling, but the agentic Round 2 did not fix the issue. Also, only 4 of 500 Round 1 backbones folded satisfactorily under AlphaFold2, yet even with this filtering, the structure quality of the selected samples was poor (Table 1) and in some cases there was no contact between the minibinder and the peptide (Figure 2B).

6. Agentic Design with Harness Engineering and Human Supervision

6.1. Overview of Pipeline

An LLM agent (Claude Sonnet 4.6, Anthropic) in the Claude Code harness (v2.1.186) was provided a detailed `CLAUDE.md` file (Appendix F.3) instructing it to design a minibinder to pMHC presenting the KRAS G12D peptide. Drawing inspirations from the failure modes in Section 5 and relevant literature on best practices of harness engineering for long running tasks and best prompting practices (Lopopolo, 2026; Young, 2025).

Add scientific context In addition to providing the Liu et al. paper and all related output as in Section 5, we provided the agent with full scientific context of the binder design task (modified from a recent Hackathon (mun, 2026) and compiled by manually feeding relevant papers to Opus 4.8, Anthropic Claude for Mac v1.15962.0). We also pro-

Figure 2. **Predicted structures of binding complexes.** HLA-A*11:01 α1 and α2 domains in complex with KRAS G12D 9-mer peptide (VVGADGVGK) and designed minibinders from round 2. A) Human-designed minibinder, B) Agent-designed binder (minimal human supervision), and C) Agent-designed binder (continuous human supervision). Inset shows peptide and any polar contacts with the minibinder.

vided the wild-type KRAS peptide-MHCI pdb structure and structural templates specificity screen (pMHC fold).

Provide software setup To save wasted context, RFdiffusion, ProteinMPNN, Rosetta, AF2-initial guess, and relevant conda environment were first installed using separate Claude Code sessions. Then, given these inputs, the agent wrote scripts to run the tools, and managed their execution (Figure A.1).

Manage context better In Section 5, the agent did not effectively learn from the published minibinders because the information was not accessible to the agent. Therefore, we provided a table of contents of all the context in a short CLAUDE.md file (Appendix F.3) with a short description of all provided files in the relevant documentation, so the agent only loads relevant information into context when needed.

Give clearer instructions CLAUDE.md also defines project conventions with more details specified in other markdown files mapped. To provide a clear and specific guideline, we ran Opus 4.8 on the Liu et al. paper and

supplements to summarize the step-by-step binder design instructions, lessons learned from the experimentally validated designs, and guidance to calibrate the evaluation criteria with validated designs, rather than just a sentence to ask the agent to learn from the designs in the prompt. We provided examples whenever possible to guide the agent.

Human participates heavily in decision making Human user not only passively answered questions from the agent, but also examined the intermediate agent design output and provided guidance about tools to explore and analyses to focus on (Section 6.1.3, Appendix F.4). Only exploration efforts leading to successful designs are presented here. More details are presented in the design log, compiled by Claude and reviewed by the authors.

6.1.1. ROUND 1

Five main tasks were performed in Round 1: 1,300 backbone structures were sampled from RFdiffusion with peptide hotspot conditioning, and on average 6 sequences were sampled from ProteinMPNN for each backbone, with the best sequence per backbone selected using ESMFold pLDDT. AlphaFold2 initial guess was used for structure prediction and filtering, and passing designs were further characterized with AlphaFold2 monomer and ProteinMPNN specificity scan. 5 designs passed the AlphaFold2 initial guess iPAE <10 threshold.

6.1.2. ROUND 2

Seven main tasks were performed in Round 2: 200 RFdiffusion backbones were sampled per passing design from round 1 (different partial T), with peptide hotspot conditioning, and 8 sequences per backbone were sampled from ProteinMPNN, for a total of 8000 sequences. The best sequence per backbone was selected using ESMFold pLDDT. AlphaFold2 initial guess for structure prediction and filtering, with 20 sequences passing the iPAE <10 threshold. Finally, AlphaFold3 predictions of the binding complex with KRAS G12D and WT peptide bound to MHC I were used in Rosetta interface analysis and ipSAE calculation. We obtained 6 high-confidence hits. More details are in the summary report.

6.1.3. HUMAN INTERACTION

In contrast to the minimal-supervision run, the agent halted processing many times to ask follow up questions. This is likely caused by changes to the Claude Code harness.

Sixty-four manual interventions were needed, including responses to clarifying questions from the agent. Interactions fell into categories such as ensuring correct order of operations, preventing corner-cutting, and correcting hotspot selection (Appendix F.4).

Additionally, the human user prompted cross-pipeline comparisons, including the reasons why certain scores diverge from the pipeline in Section 4 (ipSAE thresholds, CMS values, pMHC pLDDT bugs) due to different underlying implementations by the agent in different pipelines. This is crucial for an apples-to-apples comparison in Section 7. At the end of the run, the agent was prompted to study the molecular mechanisms of how the minibinders form polar interactions with the peptide, which may or may not boost binding specificity.

6.1.4. COMPUTATIONAL COST

The two agentic rounds completed in about 6 days (including delays waiting for human input), with a token cost of $350.06 but only $50 of additional usage beyond the Claude Pro plan. Together with cost of the GPU server (a single cloud-hosted Nvidia RTX 5090), the total computational cost was roughly $150.

6.2. Final Design Candidates

Upon evaluation with AlphaFold3-based metrics (Appendix E), 6 of the 13 submitted designs show non-zero binder–peptide ipSAE (0.42–0.94), indicating predicted contact with the G12D peptide. Of these, designs from the r1b_870_87 sub-lineage (3 designs, ipTM 0.90–0.93, peptide-ipTM 0.72–0.77) show correct G12D/WT discrimination by both pMHC-fold and AF3 on/off-target comparison; r3_r1b_870_87_dldesign_6 uniquely satisfies all absolute confidence gates (AF3 ipTM = 0.93, binder–peptide chain-pair ipTM = 0.77) alongside positive ΔipTM (+0.02) and Δpeptide-ipTM (+0.03). By contrast, the r1b_403 lineage (2 designs) achieves higher absolute AF3 confidence (ipTM 0.95, ipSAE 0.92–0.94) but near-zero on/off-target discrimination ($|\Delta\text{ipTM}| \leq 0.003$), consistent with nonspecific engagement of the conserved MHC framework rather than p5-Asp-selective binding.

These 6 designs cluster around two Round 1 seed lineages: r1b_403 (2 designs from the same backbone family) and r1b_870 (4 designs across two sub-lineages, r1b_870_64 and r1b_870_87), with the most specific candidates from r1b_870_87 containing 93 or 94 residues, helix-dominant topologies (3 helices; helix fraction 0.88–0.93) arcing above the peptide-binding groove, and net charge −9 to −1 (Table 1). Contact map analysis of the AF3 five-model ensemble shows that r3_r1b_870_87_dldesign_6 and _dldesign_7 each carry Arg47 forming a salt bridge to the p5 Asp carboxylate (OD2 distance 2.09–2.88 Å in 4/5 models), providing a direct structural basis for G12D selectivity (Figure 2C). The remaining four designs make contact only with the invariant peptide backbone carbonyl at p5 or show no p5 Asp side-chain contact across the AF3 ensemble (Figure C.1), leaving r1b_870_87 as the best specificity-bearing scaffold.

FastRelax of the 6 nonzero-ipSAE AF3 on-target structures yields dG_separated -78.5 to -39.9 REU, shape complementarity 0.53–0.66, packstat 0.55–0.65, dSASA_int 1,930–2,747 Å^2, delta_unsatHbonds 11–16, and ContactMolecularSurface at p5 3.8–28.4 Å^2. Interface energy, shape complementarity, and packstat are within the worse end of the validated-design reference range with significant overlaps. However, buried unsatisfied hydrogen bonds are elevated relative to the validated set (0–8; mean 3.6), and two r1b_870 designs fall below the validated dSASA_int floor (2,099 Å^2). No cysteines are present in any of the 6 designs. The elevated BUNS and marginal net charge (-1) in r3_r1b_870_87_dldesign_7 can likely be addressed by ProteinMPNN redesign of surface-exposed non-interface residues while keeping the Arg47–Asp(p5) salt-bridge contact fixed.

6.3. Results

With well-organized scientific context and guidance by the human and markdown files, the agent was able to produce minibinder sequences with highly similar characteristics of human's designs.

Scale of screening   Across 2 rounds, 2,300 backbone trajectories and 15,774 backbone-sequence pairs were evaluated to yield 6 specific candidates. Only 1 design clears all the in silico filters. The starting number is comparable with the human pipeline but the in silico hit rate is much lower.

Repeated failure in implementing backbone geometric filter   The agent first applied Rosetta contact molecular surface score filtering to the backbone by mistake. It then attempted to filter backbone via C-beta distance to the p5 Asp, but ended up setting a cutoff that would filter out validated designs. Upon human intervention, rather than calibrate the cutoff, the agent dropped the geometric filter altogether.

Limitations of certain in silico metrics

- ProteinMPNN specificity score is not a valid backbone-ranking metric

- Binding is not super sensitive to the choice of partial T during RFdiffusion partial diffusion

- ESMFold pLDDT is a moderate backbone pre-filter but C-alpha RMSD is not

- AlphaFold2 initial guess and pMHC-fold are both pose-templated and cannot serve as independent specificity checks. They inflate the hotspot contact that can only be corrected by an untemplated refold, e.g., AlphaFold3. This happened in 7/13 designs in round 2.

- AlphaFold3 can be limited in predicting hotspot sidechain polar interactions. Given the flexibility of the peptide, different AlphaFold3 model seeds can disagree on where the side-chain is pointing: outward to the solvent/binder (Figure 2C) vs toward the MHC alpha helices (Supp. Figure C.1A) vs toward the MHC beta sheet (Supp. Figure C.1B). In these last two cases, polar interactions do not directly boost binding specificity. We thus need to exercise caution when assessing polar interactions by looking through all the model seeds.

7. Comparison of Final Design Candidates

We observe very different characteristics between designs by the agents (n=41 designs from n=39 backbones/n=6 designs from n=3 backbones) and by the humans (n=17 designs from n=12 backbones) and authors (n=18 designs) (Table 1). Humans', authors', and human-supervised agents' designs have high pLDDT (local structural confidence), low binder aligned RMSD (indicating high similarity to the backbones), low iPAE or high ipSAE (high interface confidence), a tight range of radius of gyration (indicating there is an ideal range of protein structural compactness), and low lateral distance between the center of mass of binder and that of the peptide. The opposite is true in all respects for the agent's designs with minimal human supervision, meaning that human's designs are more likely to bind than the agent's designs. Notably, while the human-supervised designs all have at least 3 α helices, 33/41 agents' designs have only 1 or 2 α helices, and all 3-α-helix designs have very different lengths, leading to poor packing and suboptimal contacts with the target. The vertical distance between authors' and agents' designs to target peptide are comparable, while the human's designs are vertically further from the target.

Despite the high similarity of sequence and structure characteristics of final high-confidence designs, there are still lots of differences between the humans' and human-supervised agent's approaches. The agent's designs in Round 1 have much higher quality than human's Round 1, likely due to the extremely low ProteinMPNN temperature (0.1 vs 0.000001). However, the human's Round 2 designs showed significantly more improvement in terms of the proportion of sequences with plausible binding interface (low AF2 iPAE) and have a much higher number of final designs passing all structure and sequence criteria (17 vs 2) (Appendix D, E). The human designs also suffer less from potential ineffective polar interactions with the Asp p5 on the KRAS peptide (0/17 vs 6/6). The agent then drew the wrong conclusion that direct Arg-Asp salt bridge and AlphaFold2-confirmed binding are in tension within the current backbone pool. Both observations can be attributed to lack of effective sampling of the sequence space due to extremely low ProteinMPNN tem-

Table 1. **Structural and quality metrics across three design cohorts.** *Author*: 18 published designs from Liu et al. (2025). *Human R2*: 17 designs from Round 2 of the human-led pipeline (subset with AF2 binder RMSD available). *Agent min R2*: 41 designs from the first agentic run with minimal human supervision and harness engineering. *Agent R2*: 6 designs from the second agentic run with continuous human supervision and harness engineering. Continuous metrics shown as min–max (median). n_helix_segs breakdown shows counts at 0/1/2/3/... helix segments. iPAE: AF2 initial-guess pAE_interaction. ipSAE: AF3 ipSAE binder–peptide. *AF2 monomer pLDDT. **AF2 initial-guess complex binder pLDDT. ***ESMFold binder pLDDT/RMSD §Per Liu et al. (2025); all crystal structures confirmed RMSD < 2 Å. Detailed descriptions of these metrics are in Appendices D and E.

Metric	Author (n = 18)	Human R2 (n = 17)	Agent min R2 (n = 41)	Agent R2 (n = 6)
binder_plddt ↑	86.9–97.3 (95.4) *	87.2–96.7 (95.1) *	47.9–78.0 (70.8) **	92.6–97.6 (94.0) ***
binder_rmsd (Å) ↓	< 2 §	0.4–1.1 (0.6)	3.8–60.9 (22.9) **	0.45–0.79 (0.62) ***
iPAE ↓	< 5	3.7–5.7 (4.9)	31.5–31.7 (31.6)	4.29–8.17 (6.52)
ipSAE ↑	0.86–0.97 (0.94)	0.80–0.94 (0.86)	N/A	0.42–0.94 (0.86)
rg (Å)	11.6–14.9 (14.2)	14.7–15.2 (14.9)	17.5–34.1 (18.5)	14.7–14.9 (14.9)
n_helix_segs (#designs at 1/2/... helices)	0/1/5/12	0/0/17/0	5/28/8/0	0/0/6/0
lateral_dist (Å) ↓	1.0–13.2 (4.9)	5.2–12.4 (10.8)	11.4–27.0 (21.9)	1.12–5.81 (2.83)
vertical_dist (Å) ↓	2.0–12.6 (10.6)	12.2–14.4 (13.5)	1.2–12.0 (4.7)	12.3–13.7 (13.0)

perature. The humans' designs match the validated design profile more on the most important specificity metrics (CMS p5, ipSAE, number of polar contacts). Both sets of designs show higher surface hydrophobicity than the validated designs (0.42-0.44 vs 0.29). This is likely the difference in target peptide (Appendix B.1). In future rounds, filtering for p5 polar contacts is the clearest path to making binders more similar to the validated designs.

8. Discussion

Despite growing interest in LLM agents for scientific research, few published benchmark has systematically compared agent-directed and human-directed campaigns on the generative protein binder design task (mun, 2026). Most existing evaluations fall into two categories that each capture only part of the problem. Crowdsourced human competitions (Cotet et al., 2025; Kosonocky et al., 2026), experimentally validating designs from human teams, provide ground-truth experimental benchmarks for computational methods but involve human designers throughout, not autonomous agents. Agent-focused benchmarks, conversely, have evaluated LLM agents on protein engineering prediction tasks (fitness scoring, sequence classification) rather than on end-to-end generative pipelines (Miller et al., 2025). So far, LLM agents underperformed human baselines on biomedical ML workflows, with no consistent advantage for domain-specialized over generalist agents (Miller et al., 2025; phy, 2026). The closest precedent is ProteinMCP, which demonstrated that an LLM agent can autonomously orchestrate de novo protein design but without benchmarking candidate quality or experimental hit rates against human-directed campaigns (Xu et al., 2026). The present work is limited

in its generalizability, covering only one minibinder design task. However, to our knowledge, our work is the first to hold target, evaluation criteria, and pipeline constant while varying the degree of human versus agent control, providing a direct comparison on a therapeutically relevant generative design task.

An ideal comparison of agentic and human-directed campaigns would include wet-lab validation of the resulting designs; unfortunately, we did not have the resources to validate our designs. However, we note that access to lab validation is a key challenge in the field of computational protein design. To address this challenge, we contribute a wide-ranging set of *in silico* design benchmarking criteria to optimize the binding affinity, specificity, and developability.

We show that Claude Code, a popular agentic tool in software engineering, can rapidly and cheaply conduct an *in silico* protein binder design campaign. The level of human interaction required was low, but not zero. However, the resulting sequences are of much lower quality than a comparable human-directed campaign. While Claude Code is capable of using protein design software, it lacks "biological intuition" to recognize when the outputs do not make sense. To bridge the gap, we used the same Claude model (Sonnet 4.6) to conduct a second run by providing as much scientific and execution context as possible, while paying special attention to context management. The resulting sequences are of much more similar quality than the human-directed campaign, though the latter still prevails–For this current task, the upper limit of scientific ability is still capped by human expertise. Accordingly, the number of times of human interactions are over 20-fold more and the amount of compute is several fold more. While it is possible to inject a

large amount of human domain knowledge into the agent via harness engineering, the agent can still be limited in highly specialized tasks and can go down the dark alley without human intervention. Nevertheless, human researchers can still leverage LLM agents equipped with domain knowledge to rapidly test many methodological and scientific hypotheses in parallel and accelerate scientific discovery. We expect that specific training of frontier language models on biological tasks (Claude for Life Sciences, GPT-Rosalind) will improve built-in biological intuition and therefore performance at this task.

9. Future Directions

We have several ideas to increase the success rate, scope, and autonomy of our agentic workflow:

Reducing bias towards specific methods   Our prompt was fairly specific and structured, including a highly relevant example paper with approaches to mimic. If we made the prompt more minimal whilie providing enough context and access to tools, it might allow the agent to explore novel approaches. The caveat to this freedom is that the model is likely to fall back on its preferred tools—those well-represented in its training set. To increase the diversity of approaches, explicitly asking for new ideas with a planning sub-agent may help.

Multi-agent task management   We expect harness developments such as multi-agent orchestrator-implementor-evaluator patterns to improve long-running task management https://www.anthropic.com/engineering/harness-design-long-running-apps. These can be incorporated into future prompts.

Aligning the agent with our expectations   While Claude is natively able to run tools like RFdiffusion and Protein-MPNN, skill development may help align the model's goals with our expectations. The grill-me skill and other interactive planning skills would be particularly useful in identifying knowledge gaps and assumptions between the prompter and the agent before the agentic process begins. However, to be successful, this approach still depends on the agent knowing what it does not know, which requires built-in experience and intuition using protein design tools.

Software and Data

The human design scripts are deposited online at https://https://github.com/ElainW/pmhc_binder_kras. The agentic scripts and design log are at https://github.com/aaronkollasch/agent_pmhc_kras_binder for the minimally supervised run and https://github.com/ElainW/agent_pmhc_kras_binder_2 for the human-supervised run.

Acknowledgements

We would like to thank Debora Marks lab for support of part of the compute for binder design. We would also like to thank helpful discussions with Debora Marks, Bingxu Liu, team members from AI proteins, Repertoire Immune Medicines. Last but not least, we would like to thank reviewers for their helpful feedback on the content of this manuscript.

Impact Statement

This paper presents work whose goal is to advance the fields of Machine Learning and Biology. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Are agents better than humans at protein design? — muni research, May 2026. URL https://muni.bio/research/agents-vs-humans-trem2.

Evaluating AI Agents in Biology, February 2026. URL https://phylo.bio/blog/evaluating-ai-agents-in-biology.

Abramson, J., Adler, J., Dunger, J., Evans, R., Green, T., Pritzel, A., Ronneberger, O., Willmore, L., Ballard, A. J., Bambrick, J., Bodenstein, S. W., Evans, D. A., Hung, C.-C., O'Neill, M., Reiman, D., Tunyasuvunakool, K., Wu, Z., Žemgulytė, A., Arvaniti, E., Beattie, C., Bertolli, O., Bridgland, A., Cherepanov, A., Congreve, M., Cowen-Rivers, A. I., Cowie, A., Figurnov, M., Fuchs, F. B., Gladman, H., Jain, R., Khan, Y. A., Low, C. M. R., Perlin, K., Potapenko, A., Savy, P., Singh, S., Stecula, A., Thillaisundaram, A., Tong, C., Yakneen, S., Zhong, E. D., Zielinski, M., Žídek, A., Bapst, V., Kohli, P., Jaderberg, M., Hassabis, D., and Jumper, J. M. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature*, 630(8016): 493–500, June 2024. ISSN 1476-4687. doi: 10.1038/s41586-024-07487-w. URL https://www.nature.com/articles/s41586-024-07487-w.

Ahn, S., Oh, T.-S., Suh, S., Jeon, J.-Y., Lah, S., Ryu, K., Choi, S., Kim, H., Lee, E. G., Lee, H., Lee, J., Kim, Y., Kim, S., Park, S. R., Yoo, H., Choi, S.-Y., Lee, J. E., Kim, D.-K., Ku, B. M., Jung, W., Ahn, M.-J., Jung, J. U., Kim, Y.-S., Oh, B.-H., and Jeong, B.-S. Discovery of TCR-like antibodies to the KRAS G12D neoantigen via *in silico-in vitro* workflow. *Molecular Therapy*, June 2026. ISSN 1525-0016. doi: 10.1016/j.ymthe.2026.05.032. URL https://www.sciencedirect.com/science/article/pii/S1525001626004776.

Bennett, N. R., Coventry, B., Goreshnik, I., Huang, B., Allen, A., Vafeados, D., Peng, Y. P., Dauparas, J., Baek, M., Stewart, L., DiMaio, F., De Munck, S., Savvides, S. N., and Baker, D. Improving de novo protein binder design with deep learning. *Nature Communications*, 14 (1):2625, May 2023. ISSN 2041-1723. doi: 10.1038/ s41467-023-38328-5. URL https://www.nature. com/articles/s41467-023-38328-5.

Bio, A.-A. Overconfident: What Structure Prediction Confidence Scores Tell Us About Binding, February 2026. URL https://aalphabio.substack.com/p/ overconfident-what-structure-prediction.

Cao, L., Coventry, B., Goreshnik, I., Huang, B., Sheffler, W., Park, J. S., Jude, K. M., Marković, I., Kadam, R. U., Verschueren, K. H. G., Verstraete, K., Walsh, S. T. R., Bennett, N., Phal, A., Yang, A., Kozodoy, L., DeWitt, M., Picton, L., Miller, L., Strauch, E.-M., DeBouver, N. D., Pires, A., Bera, A. K., Halabiya, S., Hammerson, B., Yang, W., Bernard, S., Stewart, L., Wilson, I. A., Ruohola-Baker, H., Schlessinger, J., Lee, S., Savvides, S. N., Garcia, K. C., and Baker, D. Design of protein-binding proteins from the target structure alone. *Nature*, 605(7910): 551–560, May 2022. ISSN 1476-4687. doi: 10.1038/ s41586-022-04654-9. URL https://www.nature. com/articles/s41586-022-04654-9.

Cho, Y., Pacesa, M., Zhang, Z., Correia, B. E., and Ovchinnikov, S. Boltzdesign1: Inverting All-Atom Structure Prediction Model for Generalized Biomolecular Binder Design, April 2025. URL https://www.biorxiv.org/content/ 10.1101/2025.04.06.647261v1. Pages: 2025.04.06.647261 Section: New Results.

Cotet, T.-S., Krawczuk, I., Stocco, F., Ferruz, N., Gitter, A., Kurumida, Y., Machado, L. d. A., Paesani, F., Calia, C. N., Challacombe, C. A., Haas, N., Qamar, A., Correia, B. E., Pacesa, M., Nickel, L., Subr, K., Castorina, L. V., Campbell, M. J., Ferragu, C., Kidger, P., Hallee, L., Wood, C. W., Stam, M. J., Kluonis, T., Ünal, S. M., Belot, E., Naka, A., and Organizers, A. C. Crowdsourced Protein Design: Lessons From the Adaptyv EGFR Binder Competition, April 2025. URL https://www.biorxiv.org/ content/10.1101/2025.04.17.648362v2. Pages: 2025.04.17.648362 Section: New Results.

Dauparas, J., Anishchenko, I., Bennett, N., Bai, H., Ragotte, R. J., Milles, L. F., Wicky, B. I. M., Courbet, A., de Haas, R. J., Bethel, N., Leung, P. J. Y., Huddy, T. F., Pellock, S., Tischer, D., Chan, F., Koepnick, B., Nguyen, H., Kang, A., Sankaran, B., Bera, A. K., King, N. P., and Baker, D. Robust deep learning–based

protein sequence design using ProteinMPNN. *Science*, 378(6615):49–56, October 2022. doi: 10.1126/ science.add2187. URL https://www.science. org/doi/10.1126/science.add2187.

Glögl, M., Krishnakumar, A., Ragotte, R. J., Goreshnik, I., Coventry, B., Bera, A. K., Kang, A., Joyce, E., Ahn, G., Huang, B., Yang, W., Chen, W., Sanchez, M. G., Koepnick, B., and Baker, D. Target-conditioned diffusion generates potent TNFR superfamily antagonists and agonists. *Science*, 386(6726):1154–1161, December 2024. ISSN 1095-9203. doi: 10.1126/science.adp1779. Place: New York, N.Y.

Hickok, G. H. and Stromnes, I. M. Beyond the native repertoire. *Science*, 389(6758):349–351, July 2025. doi: 10.1126/science.adz6423. URL https://www.science.org/doi/10.1126/ science.adz6423.

Householder, K. D., Xiang, X., Jude, K. M., Deng, A., Obenaus, M., Zhao, Y., Wilson, S. C., Chen, X., Wang, N., and Garcia, K. C. De novo design and structure of a peptide–centric TCR mimic binding module. *Science*, 389(6758):375–379, July 2025. doi: 10.1126/ science.adv3813. URL https://www.science. org/doi/10.1126/science.adv3813.

Hýsková, A., Maršálková, E., and Šimeček, P. Balancing speed and precision in protein folding: a comparison of AlphaFold2, ESMFold, and OmegaFold. *Frontiers in Genetics*, 16, January 2026. ISSN 1664-8021. doi: 10.3389/fgene.2025.1715037. URL https://www.frontiersin.org/journals/ genetics/articles/10.3389/fgene.2025. 1715037/full.

Johansen, K. H., Wolff, D. S., Scapolo, B., Fernández-Quintero, M. L., Risager Christensen, C., Loeffler, J. R., Rivera-de Torre, E., Overath, M. D., Kjærgaard Munk, K., Morell, O., Viuff, M. C., Lacunza, I., Damm Englund, A. T., Due, M., Gharpure, A., Forli, S., Rodriguez Pardo, C., Tamhane, T., Qingjie Andersen, E., Haldrup Björnsson, K., Fernandes, J. S., Voss, L. F., Thumtecho, S., Ward, A. B., Ormhøj, M., Reker Hadrup, S., and Jenkins, T. P. De novo-designed pMHC binders facilitate T cell–mediated cytotoxicity toward cancer cells. *Science*, 389(6758):380–385, July 2025. doi: 10.1126/ science.adv0422. URL https://www.science. org/doi/10.1126/science.adv0422.

Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K., Bates, R., Žídek, A., Potapenko, A., Bridgland, A., Meyer, C., Kohl, S. A. A., Ballard, A. J., Cowie, A., Romera-Paredes, B., Nikolov, S., Jain, R., Adler, J., Back, T., Petersen, S.,

Reiman, D., Clancy, E., Zielinski, M., Steinegger, M., Pacholska, M., Berghammer, T., Bodenstein, S., Silver, D., Vinyals, O., Senior, A. W., Kavukcuoglu, K., Kohli, P., and Hassabis, D. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873):583–589, August 2021. ISSN 1476-4687. doi: 10.1038/s41586-021-03819-2. URL https://www.nature.com/articles/s41586-021-03819-2.

Kosonocky, C. W., Abel, A. M., Feller, A. L., Rieffer, A. E. C., Woolley, P. R., Lála, J., Barth, D. R., Gardner, T., Competitors, B. t. B., Ekker, S. C., Ellington, A. D., Wierson, W. A., and Marcotte, E. M. Validation and analysis of 12,000 AI-driven CAR-T designs in the Bits to Binders competition, March 2026. URL https://www.biorxiv.org/content/10.64898/2026.03.03.709355v2. ISSN: 2692-8205 Pages: 2026.03.03.709355 Section: New Results.

Leidner, R., Silva, N. S., Huang, H., Sprott, D., Zheng, C., Shih, Y.-P., Leung, A., Payne, R., Sutcliffe, K., Cramer, J., Rosenberg, S. A., Fox, B. A., Urba, W. J., and Tran, E. Neoantigen T-Cell Receptor Gene Therapy in Pancreatic Cancer. *New England Journal of Medicine*, 386(22):2112–2119, June 2022. ISSN 0028-4793. doi: 10.1056/NEJMoa2119662. URL https://www.nejm.org/doi/full/10.1056/NEJMoa2119662. _eprint: https://www.nejm.org/doi/pdf/10.1056/NEJMoa2119662.

Listgarten, J. and Jiang, H. How artificial intelligence is reengineering protein engineering. *Science*, 392 (6794):159–166, April 2026. doi: 10.1126/science.aec8444. URL https://www.science.org/doi/10.1126/science.aec8444.

Liu, B., Greenwood, N. F., Bonzanini, J. E., Motmaen, A., Meyerberg, J., Dao, T., Xiang, X., Ault, R., Sharp, J., Wang, C., Visani, G. M., Vafeados, D. K., Roullier, N., Nourmohammad, A., Scheinberg, D. A., Garcia, K. C., and Baker, D. Design of high-specificity binders for peptide–MHC-I complexes. *Science*, 389(6758):386–391, July 2025. doi: 10.1126/science.adv0185. URL https://www.science.org/doi/10.1126/science.adv0185.

Lopopolo, R. Harness engineering: leveraging Codex in an agent-first world | OpenAI, 2026. URL https://openai.com/index/harness-engineering/.

Ma, J., Tubb, V., Mojadidi, M., Meade, K., Kong, X., Kroon, P., Sareen, A., Stringer, B., Krijgsman, O., Claasen, Y., Gadiot, J., Buchner, K., Eshuis, S., Schumacher, T., Linneman, C., Kuilman, T., van Heijst, J., Bendle, G., and Perez, A. Non-clinical evaluation of NT-112, an autologous T cell product engineered to express an HLA-C*08:02-restricted TCR targeting KRAS G12D and resistant to TGF-b inhibition. *Journal of Clinical Oncology*, 42(16_suppl):e14533–e14533, June 2024. ISSN 0732-183X. doi: 10.1200/JCO.2024.42.16_suppl.e14533. URL https://ascopubs.org/doi/10.1200/JCO.2024.42.16_suppl.e14533.

Marshall, A. AI turbocharges antibody hunt for binders with drug-like qualities. *Nature Biotechnology*, 44(3): 334–337, March 2026. ISSN 1546-1696. doi: 10.1038/s41587-026-03048-w.

Miller, H. E., Greenig, M., Tenmann, B., and Wang, B. BioML-bench: Evaluation of AI Agents for End-to-End Biomedical ML, September 2025. URL https://www.biorxiv.org/content/10.1101/2025.09.01.673319v3. ISSN: 2692-8205 Pages: 2025.09.01.673319 Section: New Results.

Mirdita, M., Schütze, K., Moriwaki, Y., Heo, L., Ovchinnikov, S., and Steinegger, M. ColabFold: making protein folding accessible to all. *Nature Methods*, 19(6): 679–682, June 2022. ISSN 1548-7105. doi: 10.1038/s41592-022-01488-1.

Motmaen, A., Dauparas, J., Baek, M., Abedi, M. H., Baker, D., and Bradley, P. Peptide-binding specificity prediction using fine-tuned protein structure prediction networks. *Proceedings of the National Academy of Sciences of the United States of America*, 120(9):e2216697120, February 2023. ISSN 1091-6490. doi: 10.1073/pnas.2216697120.

Overath, M. D., Rygaard, A., Jacobsen, C. P., Brasas, V., Morell, O., Sormanni, P., and Jenkins, T. P. Predicting Experimental Success in De Novo Binder Design: A Meta-Analysis of 3,766 Experimentally Characterised Binders, August 2025. URL https://www.biorxiv.org/content/10.1101/2025.08.14.670059v1. ISSN: 2692-8205 Pages: 2025.08.14.670059 Section: New Results.

O'Reilly, E. M., Wainberg, Z. A., Hendifar, A. E., Borad, M. J., Pietrantonio, F., Pant, S., Hammel, P., Cremolini, C., Manji, G. A., Oberstein, P. E., Garrido-Laguna, I., Springfeld, C., Azad, N. S., Ueno, M., Chui, S. Y., Zhang, Y., Patel, H., Lee, Y., Salman, Z., and Wolpin, B. M. Daraxonrasib or Chemotherapy in Previously Treated Metastatic Pancreatic Cancer. *New England Journal of Medicine*, 0(0), 2026. ISSN 0028-4793. doi: 10.1056/NEJMoa2605555. URL https://www.nejm.org/doi/full/10.1056/NEJMoa2605555. _eprint: https://www.nejm.org/doi/pdf/10.1056/NEJMoa2605555.

Pacesa, M., Nickel, L., Schellhaas, C., Schmidt, J., Pyatova, E., Kissling, L., Barendse, P., Choudhury, J., Kapoor, S.,

Alcaraz-Serna, A., Cho, Y., Ghamary, K. H., Vinué, L., Yachnin, B. J., Wollacott, A. M., Buckley, S., Westphal, A. H., Lindhoud, S., Georgeon, S., Goverde, C. A., Hatzopoulos, G. N., Gönczy, P., Muller, Y. D., Schwank, G., Swarts, D. C., Vecchio, A. J., Schneider, B. L., Ovchinnikov, S., and Correia, B. E. One-shot design of functional protein binders with BindCraft. *Nature*, 646(8084): 483–492, October 2025. ISSN 1476-4687. doi: 10.1038/s41586-025-09429-6. URL https://www.nature.com/articles/s41586-025-09429-6.

Pak, M. A., Markhieva, K. A., Novikova, M. S., Petrov, D. S., Vorobyev, I. S., Maksimova, E. S., Kondrashov, F. A., and Ivankov, D. N. Using AlphaFold to predict the impact of single mutations on protein stability and function. *PLOS ONE*, 18(3):e0282689, March 2023. ISSN 1932-6203. doi: 10.1371/journal.pone.0282689. URL https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0282689.

Park, W., Kasi, A., Spira, A. I., Rodríguez, L. P.-A., Herzberg, B. O., Pelster, M. S., Tolcher, A. W., Kuboki, Y., Kitano, S., Shoji, H., Wang, J. S., Berlin, J. D., Hollebecque, A., LoRusso, P., Fountzilas, C., Cassier, P. A., Nishina, T., Sakai, D., Inagaki, C., Morgensztern, D., Ueno, M., Jung, M., Kim, S.-W., Jänne, P. A., Italiano, A., You, B., Macarulla, T., Fujii, H., Shetty, A., Lu, Y., Cui, D., Kadam, S., Gill, S. C., Toyoshima, J., Saito, T., and Goldman, J. W. Setidegrasib in Advanced Non–Small-Cell Lung Cancer and Pancreatic Cancer. *New England Journal of Medicine*, 394(14):1409–1420, April 2026. ISSN 0028-4793. doi: 10.1056/NEJMoa2600752. URL https://www.nejm.org/doi/full/10.1056/NEJMoa2600752. _eprint: https://www.nejm.org/doi/pdf/10.1056/NEJMoa2600752.

Ragotte, R. J., Tortorici, M. A., Catanzaro, N. J., Addetia, A., Coventry, B., Froggatt, H. M., Lee, J., Stewart, C., Brown, J. T., Goreshnik, I., Sims, J. N., Milles, L. F., Wicky, B. I. M., Glögl, M., Gerben, S., Kang, A., Bera, A. K., Sharkey, W., Schäfer, A., Harkema, J. R., Baric, R. S., Baker, D., and Veesler, D. Designed miniproteins potently inhibit and protect against MERS-CoV. *Cell Reports*, 44(6):115760, June 2025. ISSN 2211-1247. doi: 10.1016/j.celrep.2025.115760.

Sappington, I., Toul, M., Lee, D. S., Robinson, S. A., Goreshnik, I., McCurdy, C., Chan, T. C., Buchholz, N., Huang, B., Vafeados, D., Garcia-Sanchez, M., Roullier, N., Glögl, M., Kim, C. J., Watson, J. L., Torres, S. V., Verschueren, K. H. G., Verstraete, K., Hinck, C. S., Benard-Valle, M., Coventry, B., Sims, J. N., Ahn, G., Wang, X., Hinck, A. P., Jenkins, T. P., Ruohola-Baker, H., Banik, S. M., Savvides, S. N., and Baker, D. Improved protein binder

design using beta-pairing targeted RFdiffusion, November 2024. URL https://www.biorxiv.org/content/10.1101/2024.10.11.617496v2. Pages: 2024.10.11.617496 Section: New Results.

Sim, M. J. W., Lu, J., Spencer, M., Hopkins, F., Tran, E., Rosenberg, S. A., Long, E. O., and Sun, P. D. High-affinity oligoclonal TCRs define effective adoptive T cell therapy targeting mutant KRAS-G12D. *Proceedings of the National Academy of Sciences of the United States of America*, 117(23):12826–12835, June 2020. ISSN 1091-6490. doi: 10.1073/pnas.1921964117.

Son, A., Park, J., Kim, W., Lee, W., Yoon, Y., Ji, J., and Kim, H. Integrating Computational Design and Experimental Approaches for Next-Generation Biologics. *Biomolecules*, 14(9):1073, September 2024. ISSN 2218-273X. doi: 10.3390/biom14091073. URL https://www.mdpi.com/2218-273X/14/9/1073.

Stark, H., Faltings, F., Choi, M., Xie, Y., Hur, E., O'Donnell, T., Bushuiev, A., Uçar, T., Passaro, S., Mao, W., Reveiz, M., Bushuiev, R., Pluskal, T., Sivic, J., Kreis, K., Vahdat, A., Ray, S., Goldstein, J. T., Savinov, A., Hambalek, J. A., Gupta, A., Taquiri-Diaz, D. A., Zhang, Y., Hatstat, A. K., Arada, A., Kim, N. H., Tackie-Yarboi, E., Boselli, D., Schnaider, L., Liu, C. C., Li, G.-W., Hnisz, D., Sabatini, D. M., DeGrado, W. F., Wohlwend, J., Corso, G., Barzilay, R., and Jaakkola, T. BoltzGen: Toward Universal Binder Design, November 2025. URL https://www.biorxiv.org/content/10.1101/2025.11.20.689494v1. ISSN: 2692-8205 Pages: 2025.11.20.689494 Section: New Results.

Team, L. L., Bridgland, A., Crabbé, J., Kenlay, H., Pretorius, D., Schmon, S. M., Hilmkil, A., Bartke-Croughan, R., Rombach, R., Flashman, M., Matteson, T., Mathis, S., Nelson, A. W. R., Yuan, D., Obika, A., and Kohl, S. A. A. Latent-X: An Atom-level Frontier Model for De Novo Protein Binder Design, July 2025. URL http://arxiv.org/abs/2507.19375. arXiv:2507.19375 [q-bio].

Team, L. L., Schmon, S. M., Pretorius, D., Mathis, S., Bartke-Croughan, R., Puvanendran, A., Vuckovic, J., Kenlay, H., Vlachynská, M., Bridgland, A., Grishin, I., Over, S., Li, D., Li, B., Crabbé, J., Hilmkil, A., Nelson, A. W. R., Yuan, D., Obika, A., and Kohl, S. A. A. Latent-Y: A Lab-Validated Autonomous Agent for De Novo Drug Design, April 2026. URL http://arxiv.org/abs/2603.29727. arXiv:2603.29727 [q-bio].

Tran, E., Robbins, P. F., Lu, Y.-C., Prickett, T. D., Gartner, J. J., Jia, L., Pasetto, A., Zheng, Z., Ray, S., Groh, E. M., Kriley, I. R., and Rosenberg, S. A. T-Cell Transfer Therapy Targeting Mutant KRAS in Cancer. *New England*

Journal of Medicine, 375(23):2255–2262, December 2016. ISSN 0028-4793. doi: 10.1056/NEJMoa1609279. URL https://www.nejm.org/doi/full/10.1056/NEJMoa1609279. eprint: https://www.nejm.org/doi/pdf/10.1056/NEJMoa1609279.

van den Berg, J. H., Gomez-Eerland, R., van de Wiel, B., Hulshoff, L., van den Broek, D., Bins, A., Tan, H. L., Harper, J. V., Hassan, N. J., Jakobsen, B. K., Jorritsma, A., Blank, C. U., Schumacher, T. N. M., and Haanen, J. B. A. G. Case Report of a Fatal Serious Adverse Event Upon Administration of T Cells Transduced With a MART-1-specific T-cell Receptor. *Molecular Therapy*, 23(9):1541–1550, September 2015. ISSN 1525-0016. doi: 10.1038/mt.2015.60. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC4817886/.

Watson, J. L., Juergens, D., Bennett, N. R., Trippe, B. L., Yim, J., Eisenach, H. E., Ahern, W., Borst, A. J., Ragotte, R. J., Milles, L. F., Wicky, B. I. M., Hanikel, N., Pellock, S. J., Courbet, A., Sheffler, W., Wang, J., Venkatesh, P., Sappington, I., Torres, S. V., Lauko, A., De Bortoli, V., Mathieu, E., Ovchinnikov, S., Barzilay, R., Jaakkola, T. S., DiMaio, F., Baek, M., and Baker, D. De novo design of protein structure and function with RFdiffusion. *Nature*, 620(7976):1089–1100, August 2023. ISSN 1476-4687. doi: 10.1038/s41586-023-06415-8. URL https://www.nature.com/articles/s41586-023-06415-8.

Weller, C., Burnett, G. L., Jiang, L., Chakraborty, S., Zhang, D., Vita, N. A., Dilly, J., Kim, E., Maldonato, B., Seamon, K., Eilerts, D. F., Milin, A., Marquez, A., Spradlin, J., Helland, C., Gould, A., Ziv, T. B., Dinh, P., Steele, S. L., Wang, Z., Mu, Y., Chugh, S., Feng, H., Hennessey, C., Wang, J., Roth, J., Rees, M., Ronan, M., Wolpin, B. M., Hahn, W. C., Holderfield, M., Wang, Z., Koltun, E. S., Singh, M., Gill, A. L., Smith, J. A. M., Aguirre, A. J., Jiang, J., Knox, J. E., and Wildes, D. A neomorphic protein interface catalyzes covalent inhibition of RASG12D aspartic acid in tumors. *Science*, 389(6758):eads0239, July 2025. ISSN 1095-9203. doi: 10.1126/science.ads0239.

Xu, X., Feng, C., Zha, C., He, W., He, M., Xiao, B., and Gao, X. ProteinMCP: An Agentic AI Framework for Autonomous Protein Engineering, March 2026. URL https://www.biorxiv.org/content/10.64898/2026.03.11.711149v1. ISSN: 2692-8205 Pages: 2026.03.11.711149 Section: New Results.

Yang, W., Wang, S., Lee, G. R., Zhang, J. Z., Courbet, A., Juergens, D., Wang, X., Schlichthaerle, T., Abedi, M., Ragotte, R., An, L., Kalvet, I., Pellock, S., Mihaljevic, L., Glasscock, C., Pillai, A., Broerman, A., Ennist, N., Haefner, E., McNamara-Bordewick, N.,

Haydon, I., Stewart, L., Bhardwaj, G., and Baker, D. The past, present and future of de novo protein design. *Nature*, 652:1139–1152, April 2026. ISSN 0028-0836. doi: 10.1038/s41586-026-10328-7. URL https://ui.adsabs.harvard.edu/abs/2026Natur.652.1139Y. ADS Bibcode: 2026Natur.652.1139Y.

Young, J. Effective harnesses for long-running agents, 2025. URL https://www.anthropic.com/engineering/effective-harnesses-for-long-running-agents.

Yu, Q., Guo, L., Qin, X., Huang, X., Tian, B., Wang, H., Liu, Y., Lang, Y., Wang, D., Shen, Z., Lin, J., and Chen, M. High-Affinity Protein Binder Design via Flow Matching and In Silico Maturation, January 2026. URL https://www.biorxiv.org/content/10.64898/2026.01.19.700484v2. ISSN: 2692-8205 Pages: 2026.01.19.700484 Section: New Results.

Zhang, G., Liu, C., Li, W., Lu, J., Li, A., and Zhu, L. Beyond evolution: *De novo* designed protein toolkit rewriting the rules of synthetic biology. *Biosafety and Health*, 7(5):306–311, October 2025. ISSN 2590-0536. doi: 10.1016/j.bsheal.2025.09.004. URL https://www.sciencedirect.com/science/article/pii/S2590053625001314.

Zheng, W., Jiang, D., Chen, S., Wu, M., Yan, B., Zhai, J., Shi, Y., Xie, B., Xie, X., Hu, K., and Ma, W. Exploring the therapeutic potential of precision T-Cell Receptors (TCRs) in targeting KRAS G12D cancer through in vitro development. *Oncology Research*, 32(12):1837–1850, 2024. ISSN 0965-0407. doi: 10.32604/or.2024.056565. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC11576958/.

Zhu, J., Chen, Z., Xu, X., Wang, Y., Liu, P., Wen, M., Wang, Q., He, Y., Jin, H., Xue, H., Wang, S., Xu, K., and Zhao, L. Structure guided analysis of KRAS G12 mutants in HLA-A*11:01 reveals a length encoded immunogenic advantage in G12D. *Communications Biology*, 9(1):26, December 2025. ISSN 2399-3642. doi: 10.1038/s42003-025-09285-0. URL https://www.nature.com/articles/s42003-025-09285-0.

A. Pipeline schematics

Figure A.1. **Schematics of human and agentic pipelines.** From left to right: human-directed pipeline (Section 4), minimal agent-directed pipeline (Section 5), and agent-directed pipeline with human supervision (Section 6). For the human-directed pipeline, * described in Appendix D and ** described in Appendix E.

B. Comparison of published and human-designed minibinders

Figure B.1. **Peptide target accessibility and amino acid type comparison.** Comparison of peptides in the pMHC complex between published minibinders (Liu et al., 2025) and target of this study. A) only residues 4-7 of KRAS G12D 9mer in the target structure are accessible for binding, compared to more highly accessible peptide residues in the published set. B) Published minibinders (Liu et al., 2025) were designed against peptides with hydrophobic dominant residues but the KRAS G12D 9mer in the target structure has no large hydrophobic residues.

Figure B.2. **CMS scores comparison.** Comparison of contact molecular surface (CMS) scores (Cao et al., 2022) between A) published minibinders (Liu et al., 2025) and B) human-designed minibinders, at each position in the HLA-displayed peptide (x), for each minibinder (y).

Figure B.3. **H-bonds and hydrophobicity comparison.**   Comparison of hydrogen bonding and exposed hydrophobic residues between A) published minibinders ([Liu et al., 2025](#)) and B) human-designed minibinders. ΔUnsatisfied H-bonds: difference in number of potential hydrogen bond donors or acceptor atoms without a partner between the bound complex and unbound subunits (lower is better). Buried unsatisfied H-bonds: number of H-bonding atoms buried in the core with an insufficient number of H-bonds (lower is better). Fraction exposed hydrophobic: fraction of hydrophobic residues exposed on the solvent-accessible surface (lower is better).

C. Additional minibinder complex structures

Figure C.1. **Alternative conformations of KRAS G12D 9mer in pMHC-minibinder complex.**
The side-chain of the KRAS G12D residue has varying predicted orientations across minibinder designs and predicted pMHC complexes.
A) Rosetta-relaxed AlphaFold3-predicted complex of pHMC with a minibinder from the human pipeline. Note that the G12D side-chain faces one of the MHC helices and does not make polar or H-bond contacts with the minibinder (the closest residue is an alanine).
B) AlphaFold3-predicted complex of pMHC with a minibinder from the human-supervised agentic pipeline. Here the G12D side-chain faces into the antigen-binding groove of MHC and is inaccessible to the minibinder.

D. Backbone geometry screen criteria

Residue count (60–100), helix segment count (≥ 2 by DSSP), radius of gyration within 13-23, no $C\alpha$ clashes, high peptide contacts, and SVD-based orientation aligned to the MHC-I groove.

- Secondary structure (≥ 2 alpha helices)

- Radius of gyration (13-23)

- No clashes (≥ 4.0 Å)

- Peptide contact C alpha <8.0 Å for P5 (G12D)

- backbone principle axis and peptide principle axis ≤ 35 degree

- displacement of the binder COM relative to the peptide COM (max lateral distance ≤ 15 Å)

E. AlphaFold3-based multi-metric filtering

Hard filters (any failure = 1 hard flag):

- dG_separated $<$ -50 REU

- dG_separated/dSASAx100 $>$ -2.3

- dSASA_int < 2000 Å^2

- hbonds_int / nres_int < 0.07

- delta_unsatHbonds / nres_int > 0.20 (calibrated to authors: 4/18 hit > 0.15, max author $= 0.20$ for yfv-2)

- surface_hydrophobicity > 0.60 (hard; 0.35 = BindCraft soft thresh)

- interface_n_K > 3

- ipsae_binder_peptide < 0.80

Soft flags (reported but do not count toward hard flag total):

- sc_value < 0.55

- packstat < 0.55

- buns_delta_unsat ≥ 4 (soft: 7/18 validated authors hit this)

- binder_aligned_rmsd > 1.0 (flag for structural inspection)

Specificity signal (reported separately, used for tiering):

- n_saltbridge_hotspot_p5 ≥ 1 (R/K contacting G12D neoepitope)

- cms_hotspot_p5 ≥ 25 (CMS at p5)

- n_contacts_hotspot_p5_polar ≥ 1

Tiering (after hard flags counted):

- Tier 1: 0 hard flags + salt bridge or hbond at p5

- Tier 2: 0 hard flags, no salt bridge or hbond at p5 (sorted by cms_hotspot_p5)

- Redesign candidate: 1 hard flag (hydrophobicity only) + salt bridge/hbond at p5 + CMS score ≥ 25

- Soft flag only: 1 hard flag (non-hydrophobicity), or soft flags only

- Deprioritize: 2+ hard flags

- Exclude: 4+ hard flags

Contact map analysis (addition beyond Liu et al.): We compute three contact types between binder and peptide: all-atom contacts < 4.0 Å; polar hydrogen-bond geometry (donor–acceptor < 4.0 Å, D–H···A angle $\geq 120°$, D···A < 3.5 Å); and hydrophobic contacts < 4.0 Å.

F. Agent Prompts

F.1. Prompt for minimally supervised campaign round 1

```
You are a computational protein design scientist who wants to design miniprotein binders
    to pMHC presenting the KRAS G12D peptide. All relevant info is in ./pmhc_design folder,
     including:
- PDB file of the target: pmhc_design/input/9UV8.pdb

See this paper for details on a relevant approach:
- pdf: pmhc_design/science.adv0185.pdf
- supplements: pmhc_design/science.adv0185_sm.pdf
```

```
- Additional: pmhc_design/science.adv0185.pdf
- Experimentally validated designs:
   - sequences: pmhc_design/paper_output/science.adv0185_data_s1.xlsx
   - AF3 predicted structures of the binders with the targeted peptide MHC complex (no MSA
        for the designed binders): pmhc_design/paper_output/af3_nomsa
   - Experimentally determined structures: pmhc_design/paper_output/mmdb_9O5S.pdb

Designs will be tested for these features:
- Folding confidence
- RMSD between the backbone and the actual binder from the predicted structure after
     alignment
- Net charge
- Secondary structure (percentage of residues in alpha helices, beta sheets, loops)
- CMS scores for the 5th peptide of KRAS G12D
- Number of hydrophobic and polar interactions between the binder and the peptide (
     interface)
- ipSAE between the peptide and the binder
- Energetics calculated after FastRelax
- Shape complementarity and packstat between the binder and the target
- Number of unsaturated hydrogen bonds at the interface
- Number of buried unsaturated hydrogen bonds within the complex
- Number of lysines and methionines at the binding interface
- Fraction of exposed hydrophobic residues
- Presence of poly alanines
However, you do not need to run all of these metrics.

You have access to a RTX 5090 on this system. You may install and run standard protein
    design models, such as RFdiffusion, ProteinMPNN, ESM, AlphaFold 2 monomer, AlphaFold 2
     initial guess, and generate input to run AlphaFold 3 on the web server (limited to 30
     jobs per day). A conda virtual environment is available at /venv/main, with pytorch
    cuda 13.0 installed. You may install standard python packages to that virtual
    environment as needed.

I have created an git repo at ./pmhc_design. Add any scripts, code, and analyses you need
    to run. You may commit to it as needed.
Keep a log of your design process, including any decisions made given intermediate results.
```

F.2. Prompt for minimally supervised campaign round 2

```
Perform partial diffusion (check the pmhc_design/science.adv0185_sm.pdf for details) on
    the top-ranking few designs and redo the sequence generation and downstream
    evaluations in the paper. At the end, compare generated sequences with round 1.
    Designs will be tested for these features:
- Folding confidence
- RMSD between the backbone and the actual binder from the predicted structure after
     alignment
- Net charge
- Secondary structure (percentage of residues in alpha helices, beta sheets, loops)
- CMS scores for the 5th peptide of KRAS G12D
- Number of hydrophobic and polar interactions between the binder and the peptide (
     interface)
- ipSAE between the peptide and the binder
- Energetics calculated after FastRelax
- Shape complementarity and packstat between the binder and the target
- Number of unsaturated hydrogen bonds at the interface
- Number of buried unsaturated hydrogen bonds within the complex
- Number of lysines and methionines at the binding interface
- Fraction of exposed hydrophobic residues
- Presence of poly alanines
However, you do not need to run all of these metrics.
```

F.3. CLAUDE.md for human-supervised and harness-engineered campaign

https://github.com/ElainW/agent_pmhc_kras_binder_2/blob/main/CLAUDE.md

```
# pmhc_design

You are a computational protein design scientist designing miniprotein binders to the pMHC
    presenting the KRAS G12D peptide (KRAS(G12D) 9-mer / HLA-A\*11:01, PDB 9UV8).

## Directory

```
./
|-- CLAUDE.md                  # this index
|-- docs/
|   |-- BASE.md                # Vast.ai GPU instance guide (services, ports, GPU/CUDA)
|   |-- 01_scientific_background.md
|   |-- 02_methods_and_inputs.md
|   |-- 03_design_log.md
|   \-- 04_summary_report.md
|-- envs_export/               # exported conda env *.yml (envs already installed)
|-- RFdiffusion/               # installed - backbone generation
|-- ProteinMPNN/               # installed - sequence design
|-- scripts/
|   \-- rosetta_reference_metrics.py # calibrate Rosetta cutoffs from the 19 validated
    designs
|-- input/
|   |-- 9UV8.pdb               # design target (G12D pMHC)
|   |-- 8I5E.pdb               # wild-type off-target pMHC
|   \-- pmhc_fold_scaffold/
|       |-- 6jtp_prep.pdb
|       |-- 6o4y_prep.pdb
|       |-- 8i5c_prep.pdb
|       |-- 8i5d_prep.pdb
|       \-- 8i5e_prep.pdb
|-- paper/
|   |-- pMHCI_binder_design/   # cloned Liu et al. pipeline repo (see its own README)
|   |-- science.adv0185.pdf
|   |-- science.adv0185_sm.pdf
|   \-- science.adv0185_mdar_reproducibility_checklist.pdf
\-- paper_output/
    |-- af3_nomsa/             # AF3 (no-MSA) structures of the 18 validated binders
    |-- science.adv0185_data_s1.xlsx # validated binder sequences
    |-- design_hotspots.csv   # per-target peptide hotspots
    |-- mmdb_9O5S.pdb         # experimental binder-pMHC structure
    \-- af3_nomsa/binder_pMHC_full_noMSA_MHC.json # real AF3 Server submission schema
        example (dialect "alphafoldserver" v1, "proteinChain") - keep MSA for MHC (unlike
        this example) to avoid false-negative binding
```

Documentation

Load the file you need when you need it -- do not read everything up front.

Doc	Contents	Update policy
[`docs/BASE.md`](docs/BASE.md)	Agent guide for this **Vast.ai GPU instance**:
environment/privileges, Python venvs, storage persistence, supervisor/Caddy services,
ports, GPU/CUDA, provisioning, managing the instance. Read before exposing a service,
calling an API, or installing CUDA libs.	Pre-existing; do not regenerate.
[`docs/01_scientific_background.md`](docs/01_scientific_background.md)	Target,
rationale, why prior small molecules / TCRs / antibodies struggled, the 9UV8
opportunity.	**Frozen** -- do not edit.
[`docs/02_methods_and_inputs.md`](docs/02_methods_and_inputs.md)	Inputs & sequences,
    design constraints, scoring metrics, tools, Liu et al. method + parameters,
```

```
    alternative methods (PXDesign, Mosaic), lessons from validated designs, the pipeline +
    decided scoring plan. | Update as the paper/repo are read more closely. |
| [`docs/03_design_log.md`](docs/03_design_log.md) | Per-candidate metrics table (CSV-
    backed) + round-by-round decisions. | Update as the campaign runs. |
| [`docs/04_summary_report.md`](docs/04_summary_report.md) | Draft summary report:
    objective, method, round-by-round results, full candidate stats table, sequence/
    structure comparison to validated designs, recommendation. | Draft -- update as the
    shortlist evolves. |
```

Project conventions

- **Peptide numbering:** the mutant Asp (KRAS D12) is **peptide position 5 (p5)** in the 9
    UV8 9-mer `VVGADGVGK`; it is the specificity-determining residue every design must
    contact. (Different index in other registers -- see doc 01.)
- **Running any model/filter** (RFdiffusion, ProteinMPNN, pMHC-fold, contact/spec filters,
    scaffold docking): follow `paper/pMHCI_binder_design/README.md` and the per-module
    folders -- use its commands and input conventions (renumber pMHC from residue 1;
    relabel MHC+peptide to chain B). Prefer **AF3 for folding pMHCs** (repo's 2026 update).

- **Specificity is the objective**, not raw interface score -- counter-screen G12D vs WT
    (`8I5E`); deprioritize MHC-framework-only binders. Constraint: binders **<= 120 aa**.
- **RFdiffusion hotspots must be peptide-only -- never HLA helix residues**, even though
    the binder's eventual footprint may legitimately include the flanking a1/a2 helices.
    Conditioning generation on HLA framework residues biases the dock toward the (larger,
    easier) conserved surface instead of the peptide -- the specificity failure round 1
    hit (strong AF2 binding, weak `mpnn_spec_score`; see `docs/03_design_log.md`).
- **Design log discipline:** record *every* candidate (failures included) in `designs/
    candidates.csv`; leave downstream columns blank when a design fails early.
- **Design format (from the 19 validated hits):** single-chain **a-helical miniprotein
    ˜60-100 aa**, **net-negative charge**, **no cysteines**, <=2 Met, no poly-Ala run >3.
- **Binding mode:** the binder must make a **direct contact to p5 (mutant Asp)** with a
    complementary basic/H-bond partner (Arg/Lys/His) -- validated hits use ˜7-14 interface
    residues contacting p5 + >=1 flanking position; **reject any design that does not
    contact p5.**
- **Confidence & calibration:** AF3 (no-MSA) **iptm >= 0.90** and **binder-peptide chain-
    pair iptm >= 0.77**; calibrate Rosetta cutoffs (ddG/sc/packstat/buried-unsat) from the
    validated set via `scripts/rosetta_reference_metrics.py` (PyRosetta in the **`
    dl_binder_design`** env) rather than guessing.

F.4. Classes of human interventions into human-supervised campaign

- Pipeline order of operations – Repeated corrections about running steps in the right order (e.g., specificity screen before
  Rosetta, ProteinMPNN spec scan before expensive AlphaFold2, pMHC fold placement in the funnel)

- Preventing corner-cutting – Stopping the agent from skipping steps or using shortcuts (e.g., only using top ProteinMPNN
  sequence, skipping AlphaFold2 on all sequences, relying too heavily on ProteinMPNN spec scan as a filter) which lead
  to very few successful design output

- Matching the published protocol – Frequent reminders to check Liu et al.'s supplement more carefully (backbone
  counts, sequences per backbone, specificity screen methodology)

- Calibration of filtering metrics – When exploring new filtering metrics, frequent reminders to calibrate the filter design
  using Liu et al. designs

- Hotspot selection for RFdiffusion – Corrections around which residues to use as hotspots (peptide only, no HLA
  residues, avoid polar residues, specific residue choices like B184/B186/B187)

- Documentation accuracy – Correcting misleading or incorrect interpretations in design logs and summary docs (e.g.,
  specificity-vs-binding tradeoff framing, hotspot conditioning claims)

- Compute efficiency tradeoffs – Balancing thoroughness vs. speed (ESMFold pre-filter, partial diffusion, sequences per
  backbone, when to use AF2 vs. AF3)

- Version control and reproducibility – Committing scripts to git, keeping file paths documented, maintaining CLAUDE.md

- Diagnosing failure modes – Conducting controlled analyses on e.g., how choices of partial_T affect the backbone generation quality

G. Human Review of Agent Results (minimal human supervision)

RFdiffusion   The hotspot selection is suboptimal, as RFdiffusion struggles to target polar residues effectively, yet C5 (the G12D mutation site) was included as a hotspot. Additionally, including both C1 and C7 as hotspots makes the design significantly harder to succeed, given the bent structure described in the Nature Communications paper associated with the uploaded 9UV8.pdb. The input structure was also not truncated, which unnecessarily consumes computing resources since chain B for the beta globulin is not required.

ProteinMPNN   No constraints were applied to the charges or types of residues, and there were no considerations made to preserve the interface residues. The run temperature was set to 0.1, but also 0.3, which may be too high for early design rounds.

AF2 Screening (no initial guess)   ColabFold was used for screening. Designs were screened using ESMFold pLDDT and ProteinMPNN scores, selecting the top 5. However, early rounds require a much larger number of designs, as the scores are not particularly discriminatory when all designs perform poorly in the first round. The approaches are smart but need to be applied to more designs.

AF2 Prediction (pMHC fold and initial guess)   The iPAE calculation uses the wrong wild-type amino acid: it should be G, not C. The initial guess also used a different model, alphafold2_multimer_v3, though the MSA mode is correct.

Score Specificity (first pass)   A new per-residue score based on Kyte-Doolittle hydrophobicity was introduced, which could be useful for building a loss function. Rather than instructing ProteinMPNN to omit certain amino acids as in BindCraft, it would be more useful to focus on surface hydrophobicity instead. The wild-type residue for KRAS was incorrect: it should be G, but V was used. For sequence properties, rather than computing DSSP, rough estimates based on amino acid propensities (helix formers, strand formers) should be used, along with aromatic content and alanine fractions. The ProteinMPNN log likelihood metric is, in practice, not particularly useful when we have backbones at different lengths. It is, however, very useful to rank the sequences after we narrow down to promising backbones. Contact scoring between the peptide and binder was computed based on C-alphas, which is acceptable for early rounds, but later analyses will need to account for amino acid type and contact type, distinguishing polar from hydrophobic contacts.

Score Backbones   Backbone scoring should be performed immediately after backbone generation. The number of peptide contacts based on C-beta is a good metric, as is the focus on residues C4, C5, and C7. Hotspot coverage is a reasonable approach, though the hotspot selection itself is poor. The pep_frac vs. mhc_frac metric is good, and requiring a polar residue at C5 is the correct consideration.

Score Specificity (second pass)   It is unclear how this script differs from `05_score_specificity.py`. The wrong wild-type residue for the peptide was used again.

Partial Diffusion   Following instructions from the human, the run started with 4 backbones, which should be evaluated. Hotspots were included for partial diffusion and should also be used in the human version. Diffusion was run for 20 steps, which may be too many – the output needs to be checked.

Analyze Designs   Rosetta was not accessible, which should be remedied by providing access. Lysine (K) and methionine (M) counts were calculated together rather than separately. Exposed hydrophobicity could not be calculated without Rosetta. For ipSAE, a distance cutoff should be applied. The analysis of interaction modes between the binder and the target is good. The wild-type pMHC complex PDB should have been provided from the outset.

Summary   The agents should be prompted to consult the README of the relevant repositories. The RFdiffusion README explicitly advises against using polar residues as hotspots, and this reflects a gap in practical knowledge that can nonetheless be bridged easily. Insufficient context and tools were provided: Rosetta was not accessible, the wild-type PDB was not supplied, and the agents were not instructed to use evaluation metrics such as net charge and surface hydrophobicity to iteratively improve designs. On the positive side, the overall process was very fast and cost-effective, making it well-suited for exploring a wide range of ideas, and the use of ESMFold and ColabFold was an innovative choice. A major recurring error was the use of the wrong wild-type residue for KRAS on multiple occasions, pointing to a gap in biological knowledge. Overall, this is a solid start, and with greater human input and guidance, the workflow has strong potential.