On the Sample Complexity of Privately Learning Axis-Aligned Rectangles

Abstract

We revisit the fundamental problem of learning Axis-Aligned-Rectangles over a finite grid $X^d \subseteq \mathbb{R}^d$ with differential privacy. Existing results show that the sample complexity of this problem is at most $\min\left\{ d \cdot \log |X| \,,\ d^{1.5} \cdot (\log^* |X|)^{1.5} \right\}$. That is, existing constructions either require sample complexity that grows linearly with $\log |X|$, or else it grows super linearly with the dimension d. We present a novel algorithm that reduces the sample complexity to only $\widetilde{\mathcal{O}}\left(d \cdot (\log^* |X|)^{1.5} \right)$, attaining a dimensionality optimal dependency without requiring the sample complexity to grow with $\log |X|$. The technique used in order to attain this improvement involves the deletion of "exposed" data-points on the go, in a fashion designed to avoid the cost of the adaptive composition theorems. The core of this technique may be of individual interest, introducing a new method for constructing statistically-efficient private algorithms.

1 Introduction

Differential privacy [Dwork et al., 2006] is a mathematical definition for privacy, that aims to enable statistical analyses of databases while providing strong guarantees that individual-level information does not leak. More specifically, consider a database containing data pertaining to individuals, and suppose that we have some data analysis procedure that we would like to apply to this database. We say that this procedure preserves *differential privacy* if no individual's data has a significant effect on the distribution of the outcome of the procedure. Intuitively, this guarantees that whatever is learned about an individual from the outcome of the computation could also be learned with her data arbitrarily modified (or without her data). Formally,

Definition 1.1 (Dwork et al. [2006])**.** *A randomized algorithm $\mathcal{A}$ is (ε, δ)-differentially private if for every two databases S, S' that differ on one row, and every set of outcomes F, we have* $\Pr[\mathcal{A}(S) \in F] \leq e^{\varepsilon} \cdot \Pr[\mathcal{A}(S') \in F] + \delta$. *The definition is referred to as* pure *differential privacy when $\delta = 0$, and* approximate *differential privacy when $\delta > 0$.*

Over the last decade, we have witnessed an explosion of research on differential privacy, and by now it is largely accepted as a gold-standard for privacy preserving data analysis. In particular, there has been a lot of interest in designing *private learning algorithms*, which are learning algorithms that guarantee differential privacy for their training data. Intuitively, this guarantees that the outcome of the learner (the identified hypothesis) leaks very little information on any particular point from the training set. Works in this vein include [Kasiviswanathan et al., 2011, Beimel et al., 2014, 2019b, 2016, 2020, Bun et al., 2015b, Feldman and Xiao, 2015, Bun et al., 2019, Beimel et al., 2019a, Kaplan et al., 2019b, 2020a, Alon et al., 2020, Kaplan et al., 2020b, Bun et al., 2020, Alon et al., 2019], and much more.

However, in spite of the dramatic progress made in recent years on the theory and practice of private learning, much remains unknown and answers to fundamental questions are still missing. In this work, we revisit one such fundamental open question, specifically,

Question 1.2. *What is the sample complexity of learning axis-aligned rectangles with privacy?*

Non-privately, learning axis aligned rectangles is one of the most simple and basic of learning tasks, often given as *the first* example for PAC learning in courses or teaching books. Nevertheless, somewhat surprisingly, the sample complexity of learning axis-aligned rectangles with differential privacy is not well-understood. In this work we make a significant progress in understanding this basic question.

1.1 Existing and New Results

Recall that the VC dimension of the class of all axis-aligned rectangles over $\mathbb{R}^d$ is $O(d)$, and hence a sample of size $O(d)$ suffices to learn axis-aligned rectangles non-privately (we omit throughout the introduction the dependency of the sample complexity in the accuracy, confidence, and privacy parameters). In contrast, it turns out that with differential privacy, learning axis-aligned rectangles over $\mathbb{R}^d$ is impossible, even when $d = 1$ [Feldman and Xiao, 2015, Bun et al., 2015b, Alon et al., 2019]. In more detail, let $X = \{1, 2, \ldots, |X|\}$ be a finite (one dimensional) grid, and consider the task of learning axis-aligned rectangles over the finite d-dimensional grid $X^d \subseteq \mathbb{R}^d$. In other words, consider the task of learning axis-aligned rectangles under the promise that the underlying distribution is supported on (a subset of) the finite grid X^d.

For pure-private learning, Feldman and Xiao [2015] showed a lower bound of $\Omega\left(d \cdot \log |X|\right)$ on the sample complexity of this task. This lower bound is tight, as a pure-private learner with sample complexity $\Theta\left(d \cdot \log |X|\right)$ can be obtained using the generic upper bound of Kasiviswanathan et al. [2011]. This should be contrasted with the non-private sample complexity, which is independent of $|X|$.

For approximate-private learning, Beimel et al. [2016] showed that the dependency of the sample complexity in $|X|$ can be significantly reduced. This, however, came at the cost of increasing the dependency in the dimension d. Specifically, the private learner of Beimel et al. [2016] has sample complexity $\tilde{O}\left(d^3 \cdot 8^{\log^* |X|}\right)$. We mention that a dependency on $\log^* |X|$ is known to be necessary [Bun et al., 2015b, Alon et al., 2019]. Recently, Beimel et al. [2019a] and Kaplan et al. [2020b] studied the related problem of privately learning *halfspaces* over a finite grid X^d, and presented algorithms with sample complexity $\tilde{O}\left(d^{2.5} \cdot 8^{\log^* |X|}\right)$. Their algorithms can be used to privately learn axis-aligned rectangles over X^d with sample complexity $\tilde{O}\left(d^{1.5} \cdot 8^{\log^* |X|}\right)$. This can be further improved using the recent results of Kaplan et al. [2020a], and obtain a differentially private algorithm for learning axis-aligned rectangles over X^d with sample complexity $\tilde{O}\left(d^{1.5} \cdot (\log^* |X|)^{1.5}\right)$. We consider this bound to be the baseline for our work, and we will elaborate on it later.

To summarize, our current understanding of the task of privately learning axis-aligned rectangles over X^d gives us two kinds of upper bounds on the sample complexity: Either $d \cdot \log |X|$ or $d^{1.5} \cdot (\log^* |X|)^{1.5}$. That is, current algorithms either require sample complexity that scales with $\log |X|$, or else it scales super linearly in the dimension d. This naturally leads to the following question.

Question 1.3. *Is there a differentially private algorithm for learning axis-aligned rectangles with sample complexity that scales linearly in d and asymptotically smaller than $\log |X|$?*

We answer this question in the affirmative, and present the following theorem.

Theorem 1.4 (informal)**.** *There exists a differentially private algorithm for learning axis-aligned rectangles over X^d with sample complexity $\tilde{O}\left(d \cdot (\log^* |X|)^{1.5}\right)$.*

1.2 Baseline Construction using Composition

Before we present the technical ideas behind our construction (obtaining sample complexity linear in d), we first elaborate on the algorithm obtaining sample complexity $\tilde{O}\left(d^{1.5} \cdot (\log^* |X|)^{1.5}\right)$, which

we consider to be the baseline for this work. This baseline algorithm is based on a reduction to (privately) solving the following problem, called the *interior point problem*.

Definition 1.5 (Bun et al. 2015a). *An algorithm $\mathcal{A}$ is said to solve the* Interior Point Problem *for domain X with failure probability β and sample complexity n, if for every $m \geq n$ and every database S containing m elements from X it holds that:* $\Pr[\min(S) \leq \mathcal{A}(S) \leq \max(S)] \geq 1 - \beta$.

That is, given a database S containing (unlabeled) elements from a (one dimensional) grid X, the interior point problem asks for an element of X between the smallest and largest elements in S. The baseline we consider for privately learning axis-aligned rectangles is as follows. Suppose that we have a differentially private algorithm $\mathcal{A}$ for the interior point problem over domain X with sample complexity n (let us ignore the failure probability for simplicity). We now use $\mathcal{A}$ to construct the following algorithm $\mathcal{B}$ that takes a database S containing labeled elements from X^d. For simplicity, we assume that S contains "enough" positive elements, as otherwise we could simply return the all-zero hypothesis.

1. For every axis $i \in [d]$:
    (a) Project the positive points in S onto the ith axis.
    (b) Let A_i and B_i denote the smallest n and the largest n (projected) points, without their labels.
    (c) Let $a_i \leftarrow \mathcal{A}(A_i)$ and $b_i \leftarrow \mathcal{A}(B_i)$.
2. Return the axis-aligned rectangle defined by the intervals $[a_i, b_i]$ at the different axes.

Now, recall that each application of algorithm $\mathcal{A}$ returns an *interior point* of its input points. Hence, for every axis i, it holds that the interval $[a_i, b_i]$ contains (the projection) of all but at most $2n$ of the positive examples in the ith axis. Therefore, the rectangle returned in Step 2 contains all but at most $2nd$ of the positive points (and it does not contain any of the negative points, because this rectangle is *contained* inside the target rectangle). So algorithm $\mathcal{B}$ errs on at most $2nd$ of its input points.

Assuming that $|S| \gg 2nd$, we therefore get that algorithm $\mathcal{B}$ has small empirical error. As the VC dimension of the class of axis-aligned rectangles is $O(d)$, this means that algorithm $\mathcal{B}$ is a PAC learner for this class with sample complexity $O(nd)$. The issue here is that algorithm $\mathcal{B}$ executes algorithm $\mathcal{A}$ many times (specifically, $2d$ times). Hence, in order to argue that $\mathcal{B}$ is (ε, δ)-differentially private, standard composition theorems for differential privacy require each execution of algorithm $\mathcal{A}$ to be done with a privacy parameter of $\approx \varepsilon/\sqrt{2d}$. This, in turn, would mean that n (the sample complexity of algorithm $\mathcal{A}$) needs to be at least $\sqrt{2d}$, which means that algorithm $\mathcal{B}$ errs on $2nd \approx d^{1.5}$ input points, which translates to sample complexity of $|S| \gg d^{1.5}$.

The takeaway from this baseline learner is that in order to reduce the sample complexity to be linear in d, we want to bypass the costs incurred from composition. That is, we still want to follow the same strategy (apply algorithm $\mathcal{A}$ twice on every axis), but we want to do it without appealing to composition arguments in the privacy analysis. We now briefly survey two intuitive attempts that fail to achieve this, but are useful for the presentation.

Failed Attempt #1. As before, let $\mathcal{A}$ denote an algorithm for the interior point problem over domain X with sample complexity n. Consider the following modification to algorithm $\mathcal{B}$ (marked in red). As before, algorithm $\mathcal{B}$ takes a database S containing labeled elements from X^d, where we assume for simplicity that S contains "enough" positive elements.

1. For every axis $i \in [d]$:
    (a) Project the positive points in S onto the ith axis.
    (b) Let A_i and B_i denote the smallest n and the largest n (projected) points, without their labels.
    (c) Let $a_i \leftarrow \mathcal{A}(A_i)$ and $b_i \leftarrow \mathcal{A}(B_i)$.
    (d) Delete from S all points (with their labels) that correspond to A_i and B_i.
2. Return the axis-aligned rectangle defined by the intervals $[a_i, b_i]$ at the different axes.

The (incorrect) idea here is that by adding Step 1d we make sure that each datapoint from S is "used only once", and hence we do not need to pay in composition. In other words, the hope is that if every execution of algorithm $\mathcal{A}$ is done with a privacy parameter ε, then the whole construction would satisfy differential privacy with parameter $O(\varepsilon)$.

The failure point of this idea is that by deleting *one* point from the data we can create a "domino effect" that effects (one by one) many of the sets A_i, B_i throughout the execution. Specifically, consider two neighboring datasets S and $S' = S \cup \{(x', y')\}$ for some point $x' \in X^d$ and $y' \in \{0, 1\}$. Suppose that during the execution on S' it holds that $x' \in A_1$. So the additional point x' participates "only" in the first iteration of the algorithm, and gets deleted afterwards. However, since the size of the sets A_i, B_i is fixed, during the execution on S (without the point x') it holds that *a different point* z gets included in A_1 instead of x', and this point z is then deleted from S (but it is not deleted from S' during the execution on S'). Therefore, also during the second iteration we have that S and S' are not identical (they still differ on one point) and this domino effect can continue throughout the execution. That is, a single data point can effect many of the executions of $\mathcal{A}$, and we would still need to pay in composition to argue privacy.

Failed Attempt #2. In order to overcome the previous issue, one might try the following variant of algorithm $\mathcal{B}$.

1. For every axis $i \in [d]$:

    (a) Project the positive points in S onto the ith axis.

    (b) Let $\text{size}_{A_i} = 2n + \text{Noise}$ and let $\text{size}_{B_i} = 2n + \text{Noise}$.

    (c) Let A_i and B_i denote the smallest size_{A_i} and the largest size_{B_i} (projected) points, respectively, without their labels.

    (d) Let $a_i \leftarrow \mathcal{A}(A_i)$ and $b_i \leftarrow \mathcal{A}(B_i)$.

    (e) Delete from S all points (with their labels) that correspond to A_i and B_i.

2. Return the axis-aligned rectangle defined by the intersection of the intervals $[a_i, b_i]$ at the different axes.

The idea now is that the noises we add to the sizes of the A_i's and the B_i's would "mask" the domino effect mentioned above. Specifically, the hope is as follows. Consider the execution of (the modified) algorithm $\mathcal{B}$ on S and on $S' = S \cup \{(x', y')\}$, and let i be the first axis such that $x' \in A_i \cup B_i$ during the execution on S'. Suppose w.l.o.g. that $x' \in B_i$. Now, the hope is that if during the execution on S we have that the noise size_{B_i} is smaller by 1 than its value during the execution on S', then this eliminates the domino effect we mentioned, because we would not need to add another point instead of x'. Specifically, during time i, the point x' gets deleted from S', and every other point is either deleted from both S, S' or not deleted from any of them. So after time i the two executions continue identically. Thus, the hope is that by correctly "synchronizing" the noises between the two executions (such that only the size of the "correct" set gets modified by 1) we can make sure that only one application of $\mathcal{A}$ is effected (in the last example – only the execution of $\mathcal{A}(B_i)$ is effected), and so we would not need to apply composition arguments.

Although very convincing, this idea fails. The (very subtle) issue here is that it is not clear how to synchronize the noises between the two executions. To see the problem, let us try to formalize the above argument.

Fix two neighboring databases S and $S' = S \cup \{(x', y')\}$. Let us write A_i, B_i and A_i', B_i' to denote these sets during the executions on S and on S', respectively. Aiming to synchronize the two executions, let us define a mapping $\pi : \mathbb{R}^{2d} \to \mathbb{R}^{2d}$ from noise vectors during the execution on S' to noise vectors during the execution on S (determining the values of $\text{size}_{A_1}, \text{size}_{B_1}, \ldots, \text{size}_{A_d}, \text{size}_{B_d}$), such that throughout the execution we have that $A_i = A_i'$ and $B_i = B_i'$, except for a single pair, say $B_j \neq B_j'$ of neighboring sets.

The straightforward way for defining such a mapping is as follows: Let j be the first time step in which the additional point x' gets included in a set A_j' or B_j', and say that it is included in B_j'. Then the mapping would be to reduce (by 1) the value of size_{B_j} (the noisy size of B_j during the execution on S). This would indeed make sure that, conditioned on the noise vectors v' and $v = \pi(v')$, the two executions differ only in a single application of the interior point algorithm $\mathcal{A}$, and hence the outcome distribution of these two (conditioned) executions are very similar (in the sense of differential privacy). That is, for any noise vector v and any event F,

$$\Pr[\mathcal{B}(S') \in F | v] \le e^\varepsilon \cdot \Pr[\mathcal{B}(S) \in F | \pi(v)] + \delta.$$

Furthermore, (assuming an appropriate noise distribution) we can make sure that the probability of obtaining the noise vectors v and $\pi(v)$ are similar, with densities differing by at most an e^ε factor (as

is standard in the literature of differential privacy). Therefore, *had the mapping π we defined was a bijection*, for any event F we would have that

$$\Pr[\mathcal{B}(S') \in F] = \sum_v \Pr[v] \cdot \Pr[\mathcal{B}(S') \in F|v]$$

$$\leq \sum_v e^\varepsilon \cdot \Pr[\pi(v)] \cdot (e^\varepsilon \cdot \Pr[\mathcal{B}(S) \in F|\pi(v)] + \delta)$$

$$= \sum_{\pi(v)} e^\varepsilon \cdot \Pr[\pi(v)] \cdot (e^\varepsilon \cdot \Pr[\mathcal{B}(S) \in F|\pi(v)] + \delta)$$

$$= e^{2\varepsilon} \cdot \Pr[\mathcal{B}(S) \in F] + e^\varepsilon \cdot \delta,$$

which would be great. Unfortunately, the mapping π we defined is *not* a bijection, and hence the second-to-last equality above is incorrect. To see that it is not a bijection, suppose that $d = 2$ and consider a database S containing many copies of the point $(0, 0)$, as well as 10 copies of the point $(1, 0)$ and 10 copies of the point $(0, 1)$. The neighboring database S' contains, in addition to all these points, also the point $\left(\frac{1}{2}, \frac{1}{2}\right)$. Now suppose that during the execution on S' we have that $|B'_1| = 5$ and $|B'_2| = 4$. That is, the additional point is included in B'_1. During the execution on S we therefore reduce (by 1) the size of B_1 and so $|B_1| = |B_2| = 4$. Now suppose that during the execution on S' we have that $|B'_1| = 4$ and $|B'_2| = 5$. Here, during the execution on S we reduce the size of B_2 and so, again, $|B_1| = |B_2| = 4$. This shows that the mapping π we defined is *not* a bijection. In general, in d dimensions, it is only a d-to-1 mapping, which would would break our analysis completely (it will not allow us to avoid the extra factor in d).

1.3 Our Solution - A Technical Overview

We now present a simplified version of our construction, that overcomes the challenges mentioned above. We stress that the actual construction is a bit different. Consider the following (simplified) algorithm.

1. For every axis $i \in [d]$:
    (a) Project the positive points in S onto the ith axis.
    (b) Let $\text{size}_{A_i} = 100n + \text{Noise}$ and let $\text{size}_{B_i} = 100n + \text{Noise}$, where the standard deviation of these noises is, say, $10n$.
    (c) Let A_i and B_i denote the smallest size_{A_i} and the largest size_{B_i} (projected) points, respectively, without their labels.
    (d) Let $A_i^{\text{inner}} \subseteq A_i$ be the n *largest* points in A_i. Similarly, let $B_i^{\text{inner}} \subseteq B_i$ be the n *smallest points in B_i*.
    (e) Let $a_i \leftarrow \mathcal{A}(A_i^{\text{inner}})$ and $b_i \leftarrow \mathcal{A}(B_i^{\text{inner}})$.
    (f) Delete from S all points (with their labels) whose projection onto the ith is *not* in the interval $[a_i, b_i]$.
2. Return the axis-aligned rectangle defined by the intersection of the intervals $[a_i, b_i]$ at the different axes.

There are *two* important modifications here. First, we still add noise to the size of the sets A_i, B_i, but we only use the n "inner" points from these sets. Second, we delete elements from S not based on them being inside A_i or B_i, but only based on the (privately computed) interval $[a_i, b_i]$. We now elaborate on these ideas, and present a (simplified) overview for the privacy analysis. Any informalities made herein are removed in the sections that follow.

Let S and $S' = S \cup \{(x', y')\}$ be neighboring databases, differing on the labeled point (x', y'). Consider the execution on S and on S'. The privacy analysis is based on the following two lemmas.

Lemma 1.6 (informal). *With probability at least $1 - \delta$, throughout the execution it holds that x' participates in at most $O(\log(1/\delta))$ sets A_i, B_i.*

This lemma holds because of our choice for the noise magnitude. In more detail, given that $x' \in A_i$, there is a constant probability that $x' \in A_i \setminus A_i^{\text{inner}}$. Since the interior point a_i is computed from

A_i^{inner}, in such a case we will have that $x' < a_i$, and hence, x' is deleted from the data during this iteration. This means that every time that x' is included in A_i, then there is a constant probability that x' will be deleted from the data. Thus, one can show (using concentration bounds) that the number of times i such that $x' \in A_i$ is bounded (w.h.p.).

Lemma 1.7 (informal). *In iterations i in which x' is not included in A_i or B_i, we have that a_i and b_i are distributed* exactly *the same during the execution on S and during the execution on S'.*

Indeed, in such an iteration, the point x' has no effect on the outcome distribution of $\mathcal{A}$ (who computes a_i, b_i). Overall, w.h.p., there are at most $O(\log \frac{1}{\delta})$ axes on which the point x' effects. We pay in composition only for those axes, while in all other axes we get privacy "for free". This allows us to save a factor of $\sqrt{d}$ in the sample complexity, and allows us to obtain an algorithm with sample complexity linear in d.

Note that the definition of privacy we work with is that of (ε, δ)-differential privacy. In contrast to the case of $(\varepsilon, 0)$-differential privacy, where it suffices to analyze the privacy loss w.r.t. every *single* possible outcome, with (ε, δ)-differential privacy we must account for arbitrary events. To tackle this, we had to perform a more explicit and meticulous analysis than that outlined above. Our analysis draws its structure from the proof of the advanced-composition theorem [Dwork et al., 2010], but instead of composing everything we aim to preform *effective composition*, meaning that we incurr a privacy loss only on a small fraction of the iterations. To achieve this, as we mentioned, we partition the iterations into several types – iteration on which we "pay" in privacy and iterations on which we do not. However, this partition must be done carefully, as the partition itself is random and needs to be different for different possible outcomes.

We believe that ideas from our work can be used more broadly, and hope that they find new applications in avoiding (or reducing) composition costs in other settings.

Remark 1.8. *To simplify the presentation, in the technical sections of this paper we assume that the target rectangle is placed at the origin. Our results easily extend to arbitrary axis-aligned rectangles.*

2 Preliminaries

Notations. Two datasets $S, S' \in \mathcal{X}$ are said to be *neighboring* if they differ exactly on one element, formally, $d_H(S, S') = 1$. Given a number $\ell \in \mathbb{N}$ and a dataset S containing points from an ordered domain, we use $\min(S, \ell)$ (or $\max(S, \ell)$) to indicate the subset of ℓ minimal (or maximal) values within S. When S contains points from a d-dimentional domain, we write $\min_i(S, \ell)$ (or $\max_i(S, \ell)$) to denote the subset of ℓ minimal (or maximal) values within S w.r.t. the i^{th} axis. We write $\mathrm{Lap}(\mu, b)$ to denote the *Laplase distribution* with mean μ and scale b, when the mean is zero we will simply write $\mathrm{Lap}(b)$.

We use standard definitions from statistical learning theory. See, e.g., Shalev-Shwartz and Ben-David [2014]. A classifier is a function $f : \mathcal{X} \to \{0, 1\}$.

Definition 2.1 (Generalization error). *The generalization error of a classifier f w.r.t. a distribution $\mathcal{P}$ is defined as -* $\mathrm{err}_{\mathcal{P}}(f) = \Pr_{(X,Y) \sim \mathcal{P}}[f(X) \neq Y]$.

We focus on the *realizable* setting in which for a class $\mathcal{H}$ of potential classifiers, there exist some $h^* \in \mathcal{H}$, s.t $\mathrm{err}_{\mathcal{P}}(h^*) = 0$.

Definition 2.2 (Sample error). *The empirical error of a classifier f w.r.t. a labeled-sample $S \in (\mathcal{X} \times \{0,1\})^n$ is defined as -* $\mathrm{err}_S(f) = \frac{1}{n} \sum_{(x,y) \in S} \mathbb{1}[f(x) \neq y]$

Definition 2.3 (PAC learnability Valiant [1984]). *Let $\alpha, \beta \in [0, 1]$ and let $m \in \mathbb{N}$. An algorithm $\mathcal{A}$ is an (α, β, m)-PAC-learning algorithm for a class $\mathcal{H}$ if for every distribution $\mathcal{P}$ over $\mathcal{X} \times \{0, 1\}$ s.t. $\exists h^* \in \mathcal{H}$ with $\mathrm{err}_{\mathcal{P}}(h^*) = 0$, it holds that:* $\Pr_{S \sim \mathcal{P}^n}[\mathrm{err}_{\mathcal{P}}(\mathcal{A}(S)) > \alpha] < \beta$.. *We refer to m as the* the sample complexity *of $\mathcal{A}$.*

Definition 2.4 (Private-PAC learnability). *An algorithm $\mathcal{A}$ is an $(\alpha, \beta, \varepsilon, \delta, m)$-PPAC learner for a class $\mathcal{H}$ if i) $\mathcal{A}$ is (ε, δ)-differentially private; and, ii) $\mathcal{A}$ is an (α, β, m)-PAC learning algorithm for $\mathcal{H}$.*

Definition 2.5 (Shattering). *Let $\mathcal{H}$ be a class of functions over a domain $\mathcal{X}$. A set $S = (s_1, \ldots, s_k) \subseteq \mathcal{X}$ is said to be* shattered *by $\mathcal{H}$ if $|\{(f(s_1), \ldots, f(s_k)) : f \in \mathcal{H}\}| = 2^k$*

Algorithm 1: RandMargins

Input: Data $S \subseteq \mathbb{R}^d$ of size n, and parameters $\beta < \frac{2}{5}$ and $\delta < 1/e^2, \varepsilon$
Tool used: An (ε, δ)-private algorithm $\mathcal{A}$ for solving the interior point problem with failure probability β and sample complexity $IP_{\mathcal{A}}(\varepsilon, \delta, \beta)$.

Denote $\Delta = IP_{\mathcal{A}}(\varepsilon, \delta, \beta)$
Denote $\mu = 4\Delta \log^2(1/\delta)$
Initialize $\bar{S} \leftarrow S$
for $i = 1$ **to** d **do**
    $w_i \sim Lap(\Delta \log(1/\delta))$
    $S_i = \max_i(\bar{S}, \lceil \mu + w_i \rceil)$
    $D_i = \min_i(S_i, \Delta)$
    $p_i \leftarrow \mathcal{A}(D_i, \varepsilon, \delta, \beta)$
    $R_i = \{y \in \bar{S} : y[i] \geq p_i[i]\}$
    $\bar{S} \leftarrow \bar{S} \setminus R_i$
end for
Return $(p_1, \ldots, p_d)$

Definition 2.6 (VC Dimension Vapnik and Chervonenkis [1971]). *The* VC dimension *of a class* $\mathcal{H}$, *denoted as* $VC(\mathcal{H})$, *is the cardinality of the largest set shattered by* $\mathcal{H}$. *If* $\mathcal{H}$ *shatteres sets of arbitrary large cardinality then it is said that* $VC(\mathcal{H}) = \infty$.

Theorem 2.7 (VC Dimension Generalization Bound Vapnik and Chervonenkis [1971], Blumer et al. [1989]). *Let* $\mathcal{H}$ *be a function-class and let* $\mathcal{P}$ *be a probability measure over* $\mathcal{X} \times \{0, 1\}$. *For every* $\alpha, \beta > 0$, *every* $n \in \mathcal{O}\left(\frac{1}{\alpha}\left(VC(\mathcal{H})\log(\frac{1}{\alpha}) + \log(\frac{1}{\beta})\right)\right)$ *and every* $f \in \mathcal{H}$ *it holds that* $\Pr_{S \sim \mathcal{P}^n}[\exists f \in \mathcal{H} : \mathrm{err}_{\mathcal{P}}(f) \geq \alpha \wedge \mathrm{err}_S(f) \leq \alpha/10] \leq \beta$.

3 The Algorithm

In this work we investigate the problem of privately learning the class of axis-aligned rectangles, defined as follows.

Definition 3.1 (Axis Aligned Rectangles). *Let* $\mathcal{X} = \{0, \ldots, X\}^d$ *be a finite discrete d-dimensional domain. Every* $p = (p_1, \ldots, p_d) \in \mathcal{X}$, *induces a classifier* $h_p : \mathcal{X} \rightarrow \{0, 1\}$ *s.t for a given input* $x \in \mathcal{X}$ *we have* $h_p(x) = \begin{cases} 1, \forall i \in [d] : x_i \leq p_i \\ 0, otherwise \end{cases}$. *Define the class of all* axis-aligned and origin-placed rectangles *as* $REC_d^X = \{h_p : p \in \mathcal{X}\}$.

Let $\mathcal{A}$ be an (ε, δ)-differentially private algorithm for solving the interior point problem over domain $\{0, \ldots, X\}$ with failure probability β and sample complexity $IP_{\mathcal{A}}(\varepsilon, \delta, \beta)$.

We propose the following algorithm

Theorem 3.2. *Let* $\varepsilon < 1, \delta < \frac{1}{e}, \alpha, \beta$. *Let* IP *be an algorithm for solving the interior point problem. Algorithm 1 is* $(\alpha, \beta, \tilde{\varepsilon}, \tilde{\delta})$-PPAC *learner, for the* REC_d *class, given a labeled sample of size* $\mathcal{O}\left(\frac{d\Delta}{\alpha}\log\left(\frac{1}{\alpha}\right)\log\left(\frac{1}{\delta}\right)\log\left(\frac{1}{\beta}\right)\right)$. *for* $\tilde{\delta} = (d + 2)\delta$, *and* $\tilde{\varepsilon} = \mathcal{O}\left(\log(1/\delta)\varepsilon^2 + \varepsilon\log(1/\delta)\sqrt{\log(1/\delta)}\right)$.

Remark 3.3. *Kaplan et al. [2019a] introduced the algorithm* TreeLog *which solves the interior point problem with sample complexity* $\widetilde{\mathcal{O}}\left(\frac{1}{\varepsilon}\log^{1.5}\left(\frac{1}{\delta}\right)(\log^*(|X|))^{1.5}\right)$. *Hence, using* TreeLog *within Algorithm 1 provides the result of Theorem 1.4.*

We analyze the privacy guarantees of Algorithm 1 in Section 4, and show the following lemma.

Lemma 3.4. *Let* ε *and* $\delta < \frac{1}{e}$, *given a labeled sample of size* $\mathcal{O}\left(\frac{d\Delta}{\alpha}\log\left(\frac{1}{\alpha}\right)\log\left(\frac{1}{\delta}\right)\log\left(\frac{1}{\beta}\right)\right)$, *Algorithm 1 is* $(\tilde{\varepsilon}, \tilde{\delta})$-deferentially private, *for* $\tilde{\delta} = (d + 2)\delta$, *and* $\tilde{\varepsilon} = \mathcal{O}\left(\log(1/\delta)\varepsilon^2 + \varepsilon\log(1/\delta)\sqrt{\log(1/\delta)}\right)$.

We analyze the utility guarantees of Algorithm 1 in Section 5, and show the following lemma.

Lemma 3.5. *Let $\alpha, \beta, \varepsilon, \delta$, given a labeled sample of size $\mathcal{O}\left(\frac{d\Delta}{\alpha}\log\left(\frac{1}{\alpha}\right)\log\left(\frac{1}{\delta}\right)\log\left(\frac{1}{\beta}\right)\right)$ with probability at least $1 - \beta$ Algorithm 1 is α-accurate.*

4 Privacy Analysis

Proof of Lemma 3.4. Let S and $S' = S \cup \{(x', y')\}$ be neighboring databases, differing on the labeled point (x', y'). Consider the execution on S and on S'.

We denote by $ind_i(x)$ the position of the point x on the remaining data $\bar{S}$, when the data is sorted by the i^{th} coordinate.

Denote by i^* the first iteration on which $x'[i] > p_i[i]$. For input set S, denote by $\hat{S}_i$ the remaining set at the beginning of the i^{th} iteration and its size by $\hat{n}$

Partition the iterations in the following way
• $\mathcal{I}_{in} = \{i \leq i^* \mid x' \in S'_i\}$, • $\mathcal{I}_{out} = \{i < i^* \mid x' \notin S'_i\}$, • $\mathcal{I}_{after} = \{i \mid i > i^*\}$

In the supplementary material, we use concentration bounds to show that

$$\Pr[|\mathcal{I}_{in}| > 35\log(1/\delta)] \leq \delta.$$

Next, we will denote by $\mathcal{B}$ the inner steps of the loop in the algorithm. Meaning, the input is $\hat{S}_i$, which $\mathcal{B}$ uses, along with the random noise and the mechanism $\mathcal{A}$, in order to output p_i. Note that $\mathcal{B}$ can be seen as a composition of a Laplace mechanism (represented by the addition of the Laplace noise) and the given mechanism $\mathcal{A}$. Since the Laplace mechanism is $(\varepsilon, 0)$-differentially private and $\mathcal{A}$ is (ε, δ)-differentially private, by (standard) composition theorems $\mathcal{B}$ is $(2\varepsilon, \delta)$-private.

Lemma 4.1 (Vadhan [2017]). *For every (ε, δ)-private algorithm M and every two neighboring datasets X, X', there exist events $G = G(M, X, X')$ s.t.*

i) $\Pr[M(S) \in G] > 1 - \delta$, *ii)* $\Pr[M(S') \in G] > 1 - \delta$, *iii)* $\forall x \in G : \left|\ln\left(\frac{\Pr(M(S)=x)}{\Pr(M(S')=x)}\right)\right| \leq \varepsilon.$

Define the event $G = \{p \mid \forall j \in [d] : p_j \in G(\mathcal{B}, \hat{S}_j, \hat{S}'_j)\}$, when $G(\mathcal{B}, \hat{S}_j, \hat{S}'_j)$ is the event guaranteed to exist by appling Lemma 4.1 to $\mathcal{B}, \hat{S}_j, \hat{S}'_j$. As $\hat{S}_j, \hat{S}'_j$ are induced by S, S' and $p_{<i}$ we can represent this by denoting $G(\mathcal{B}, \hat{S}_j, \hat{S}'_j) = G(\mathcal{B}, S, S', p_{<i})$.

Note that by Lemma 4.1 and the union bound $\Pr[G] \geq 1 - d\delta$.

As we wish to prove that for any possible output set P it holds that $\Pr[A(S) \in P] \leq e^{\tilde{\varepsilon}}\Pr[A(S') \in P] + \tilde{\delta}$ (for $\tilde{\varepsilon}, \tilde{\delta}$) it is sufficient to prove that [1] $\Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) > \tilde{\varepsilon}\right] \leq \tilde{\delta}$, where $\mathcal{RM}$ is an abbreviation for `RandMargins`.

$$\Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) > \tilde{\varepsilon}\right]$$

$$= \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\left(\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right) \text{ OR } \left(\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \notin G} > \tilde{\varepsilon}\right)\right]$$

$$\leq \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right] + \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \notin G} > \tilde{\varepsilon}\right]$$

$$\leq \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right] + (1 - \Pr[G])$$

$$\leq \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right] + d\delta$$

---

[1]The formal reason for that is elaborated on the supplementary material.

325 It remains to prove that $\Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right] \leq 2\delta$

$$
\Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\frac{\Pr(\mathcal{RM}(S)=p)}{\Pr(\mathcal{RM}(S')=p)}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right]
$$

$$
= \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\ln\left(\prod_{i=1}^{d} \frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right]
$$

$$
= \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\sum_{i=1}^{d} \ln\left(\frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p \in G} > \tilde{\varepsilon}\right]
$$

$$
\leq \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\sum_{i=1}^{d} \ln\left(\frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p_i \in G_i(\mathcal{B}, \hat{S}_i, \hat{S}'_i)} > \tilde{\varepsilon}\right]
$$

$$
= \Pr_{p \leftarrow \mathcal{RM}(S)}\left[\sum_{i \in \mathcal{I}_{in}} \ln\left(\frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p_i \in G_i(\mathcal{B}, \hat{S}_i, \hat{S}'_i)}\right.
$$

$$
+ \sum_{i \in \mathcal{I}_{out}} \ln\left(\frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p_i \in G_i(\mathcal{B}, \hat{S}_i, \hat{S}'_i)}
$$

$$
\left. + \sum_{i \in \mathcal{I}_{after}} \ln\left(\frac{\Pr(\mathcal{RM}(S)_i = p_i \mid \mathcal{RM}(S)_{<i} = p_{<i})}{\Pr(\mathcal{RM}(S')_i = p_i \mid \mathcal{RM}(S')_{<i} = p_{<i})}\right) \cdot \mathbb{1}_{p_i \in G_i(\mathcal{B}, \hat{S}_i, \hat{S}'_i)} > \tilde{\varepsilon}\right] \quad (1)
$$

326 In the supplementary material we bound, with high probability, each of the summands separately.
327 The proof for the bound regarding $\mathcal{I}_{in}$ is the more involved one. It makes use of the bound on the
328 size of $\mathcal{I}_{in}$ proven above and the Azuma-Hoeffding's inequality.

329 Combining the three bounds implies the desirable bound on (1) and completes the proof.

330 $\square$

5 Utility

332 *Proof of Lemma 3.5.* First, we must ensure that at every iteration, with high probability, we have
333 enough points left in $\hat{S}$. At the same time we must ensure that the axillary algorithm $\mathcal{A}$ will output
334 an inner point of the given subset. Denote $a_j = w_j + \mu$. By the definition of the noise w and the
335 mean μ, we get that for every iteration i: $\quad \Pr[a_i > 6\Delta \log(1/\delta) \log(1/\beta)] < \beta$. Hence, with
336 probability $\geq 1 - d\beta$, it holds that for every i $a_i \leq 6\Delta \log(1/\delta) \log(1/\beta)$. This means that the
337 total number of removed point is at most $6d\Delta \log(1/\delta) \log(1/\beta)$. Therefore, for a sample of size
338 $6d\Delta \log(1/\delta) \log(1/\beta)$ with high probability $\hat{S}$ will contain enough points.

339 Regarding the algorithm's accuracy, we notice that at every iteration j, $\mathcal{A}$ outputs a point which is
340 at least the $a_j - th$ largest point from *the points left in the set*. This means that, in the worst case,
341 we delete a_j points from the data set at this iteration. Hence, again in worst case, we will output the
342 $\sum_{j=1}^{i} a_j$-th largest point in the j^{th} axis.

343 By the above reasoning, with high probability we can say that for every i it holds that $a_j \leq$
344 $6\Delta \log(1/\delta) \log(1/\beta)$. Meaning that every p_j is at least the $\sum_{j=1}^{d} a_j \leq 6d\Delta \log(1/\delta) \log(1/\beta)$
345 largest point in the axis. This implies that, for sample of size $\mathcal{O}\left(\frac{d\Delta}{\alpha} \log(1/\alpha) \log(1/\delta) \log(1/\beta)\right)$,
346 denoting the by h_p the hypothesis induces by the output of Algorithm 1 $\Pr_{S \sim \mathcal{P}^n}[\mathrm{err}_S(h_p) \geq \alpha/2] \leq$
347 $\beta/2$. Since the VC-dimension of the class REC_d is $2d$, by Theorem 2.7 and the fact that the
348 sample size is at least as the sample complexity bound $\mathcal{O}\left(\frac{1}{\alpha}\left(d \log\left(\frac{1}{\alpha}\right) + \log\left(\frac{1}{\beta}\right)\right)\right)$ it holds that:
349 $\Pr_{S \sim \mathcal{P}^n}[\mathrm{err}_{\mathcal{P}}(h_p) \geq \mathrm{err}_S(h_p) + \alpha/2] \leq \beta/2$. Combining the two bounds concludes the proof. $\square$

References

Noga Alon, Roi Livni, Maryanthe Malliaris, and Shay Moran. Private PAC learning implies finite littlestone dimension. In *STOC*, pages 852–860. ACM, 2019.

Noga Alon, Amos Beimel, Shay Moran, and Uri Stemmer. Closure properties for private classification and online prediction. In *COLT*, volume 125 of *Proceedings of Machine Learning Research*, pages 119–152. PMLR, 2020.

Amos Beimel, Hai Brenner, Shiva Prasad Kasiviswanathan, and Kobbi Nissim. Bounds on the sample complexity for private learning and private data release. *Machine Learning*, 94(3):401–437, 2014.

Amos Beimel, Kobbi Nissim, and Uri Stemmer. Private learning and sanitization: Pure vs. approximate differential privacy. *Theory Comput.*, 12(1):1–61, 2016. doi: 10.4086/toc.2016.v012a001. URL https://doi.org/10.4086/toc.2016.v012a001.

Amos Beimel, Shay Moran, Kobbi Nissim, and Uri Stemmer. Private center points and learning of halfspaces. In *COLT*, volume 99 of *Proceedings of Machine Learning Research*, pages 269–282. PMLR, 2019a.

Amos Beimel, Kobbi Nissim, and Uri Stemmer. Characterizing the sample complexity of pure private learners. *J. Mach. Learn. Res.*, 20:146:1–146:33, 2019b. URL http://jmlr.org/papers/v20/18-269.html.

Amos Beimel, Kobbi Nissim, and Uri Stemmer. Learning privately with labeled and unlabeled examples. *Algorithmica*, pages 1–39, 2020.

Anselm Blumer, Andrzej Ehrenfeucht, David Haussler, and Manfred K Warmuth. Learnability and the vapnik-chervonenkis dimension. *Journal of the ACM (JACM)*, 36(4):929–965, 1989.

Mark Bun, Kobbi Nissim, Uri Stemmer, and Salil Vadhan. Differentially Private Release and Learning of Threshold Functions. *arXiv:1504.07553 [cs]*, April 2015a. URL http://arxiv.org/abs/1504.07553. arXiv: 1504.07553.

Mark Bun, Kobbi Nissim, Uri Stemmer, and Salil P. Vadhan. Differentially private release and learning of threshold functions. In *FOCS*, pages 634–649, 2015b.

Mark Bun, Kobbi Nissim, and Uri Stemmer. Simultaneous private learning of multiple concepts. *J. Mach. Learn. Res.*, 20:94:1–94:34, 2019. URL http://jmlr.org/papers/v20/18-549.html.

Mark Bun, Roi Livni, and Shay Moran. An equivalence between private classification and online prediction. In *FOCS*, pages 389–402. IEEE, 2020.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam D. Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of Cryptography, Third Theory of Cryptography Conference*, pages 265–284, 2006.

Cynthia Dwork, Guy N. Rothblum, and Salil Vadhan. Boosting and Differential Privacy. In *2010 IEEE 51st Annual Symposium on Foundations of Computer Science*, pages 51–60, Las Vegas, NV, USA, October 2010. IEEE. ISBN 978-1-4244-8525-3. doi: 10.1109/FOCS.2010.12. URL http://ieeexplore.ieee.org/document/5670947/.

Vitaly Feldman and David Xiao. Sample complexity bounds on differentially private learning via communication complexity. *SIAM J. Comput.*, 44(6):1740–1764, 2015.

Haim Kaplan, Katrina Ligett, Yishay Mansour, Moni Naor, and Uri Stemmer. Privately Learning Thresholds: Closing the Exponential Gap. *arXiv:1911.10137 [cs]*, November 2019a. URL http://arxiv.org/abs/1911.10137. arXiv: 1911.10137.

Haim Kaplan, Yishay Mansour, Yossi Matias, and Uri Stemmer. Differentially private learning of geometric concepts. In *ICML*, volume 97 of *Proceedings of Machine Learning Research*, pages 3233–3241. PMLR, 2019b.

Haim Kaplan, Katrina Ligett, Yishay Mansour, Moni Naor, and Uri Stemmer. Privately learning thresholds: Closing the exponential gap. In *COLT*, volume 125 of *Proceedings of Machine Learning Research*, pages 2263–2285. PMLR, 2020a.

Haim Kaplan, Yishay Mansour, Uri Stemmer, and Eliad Tsfadia. Private learning of halfspaces: Simplifying the construction and reducing the sample complexity. In *NeurIPS*, 2020b.

Shiva Prasad Kasiviswanathan, Homin K. Lee, Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. What can we learn privately? *SIAM J. Comput.*, 40(3):793–826, 2011.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning: From Theory to Algorithms*. Cambridge University Press, USA, 2014. ISBN 978-1-107-05713-5.

Salil Vadhan. The Complexity of Differential Privacy. In Yehuda Lindell, editor, *Tutorials on the Foundations of Cryptography*, pages 347–450. Springer International Publishing, Cham, 2017. ISBN 978-3-319-57047-1 978-3-319-57048-8. doi: 10.1007/978-3-319-57048-8_7. URL `http://link.springer.com/10.1007/978-3-319-57048-8_7`. Series Title: Information Security and Cryptography.

Leslie G Valiant. A theory of the learnable. *Communications of the ACM*, 27(11):1134–1142, 1984.

V. N. Vapnik and A. Ya. Chervonenkis. On the Uniform Convergence of Relative Frequencies of Events to Their Probabilities. *Theory of Probability & Its Applications*, 16(2):264–280, January 1971. ISSN 0040-585X. doi: 10.1137/1116025. URL `https://epubs.siam.org/doi/10.1137/1116025`. Publisher: Society for Industrial and Applied Mathematics.