Online Neural Sequence Detection with Hierarchical Dirichlet Point Process

Abstract

Neural sequence detection plays an important role in neuroscience research. Recent impressive works utilize convolutive nonnegative matrix factorization and Neyman-Scott process to solve this problems. However, they still face two limitations. Firstly, they accommodate the entire dataset into memory and perform iterative updates of multiple passes, which can be inefficient when dataset is large or grows frequently. Secondly, they rely on the prior knowledge of the number of sequence types, which can be impractical with real data when the future situation is unknown. To tackle these limitations, we propose a hierarchical Dirichlet point processes model for efficient neural sequence detection. Instead of computing the entire data, our model can sequentially detect sequences in an online unsupervised manner with Particle filter. Besides, the Dirichlet prior enables our model to automatically introduce new sequence types on the fly as needed, thus avoiding specifying the number of types in advance. We manifest these advantages on synthetic data and real-world recordings from songbird higher vocal center and rodent hippocampus.

1 Introduction

Neural sequences are a set of sequential firing neurons occurring repeatedly over time, and they play crucial roles in the brain activities of working memory [6, 10], motor production [9], and memory replay [4]. In general, it's hard to directly observe neural sequences from high-dimensional neural recordings due to the unsorted neurons. Besides, methods that use linear dimensionality reduction of neural populations may be inappropriate to handle such sequences since they form a high-dimensional structure and cannot be efficiently summarized by a low-dimensional representation [15, 20]. Finally, the relationship between neural sequences and behavior is not always so regular and predictable [27], thus an unsupervised method to identify neural sequences is required.

While a great process in neural sequence detection has been made by recent works [19, 15, 25], they have two drawbacks when it comes to the contexts of online learning. Firstly, they are ill-suited to accommodate new data or handle large datasets. Many real-world neural recordings involve plenty of hours' or days' signals that sometimes may be hard to accommodate entirely in the memory. The inference algorithms of these works (e.g., coordinate descent, Gibbs sampling, etc.) maintain the entire data and perform iterative updates of multiple passes, which may be a waste of both computational and storage resources. Secondly, these works require the number of sequence types to be specified in advance, which is inappropriate when a future situation is unknown.

To address these problems, we propose a hierarchical Dirichlet point process (HDPP) with an efficient online inference algorithm. Briefly, we use a two-level structure in our approach. At a lower level, we model the set of neural sequences by a Dirichlet nonhomogeneous Poisson process: The observed spikes are considered as a mixture of neural sequences, and those spikes belonging to different sequences are modeled via different nonhomogeneous Poisson processes, for which the intensity of

each process varies across neurons and times. At a higher level, we model the types of sequences by a Dirichlet Hawkes process[5]: The detected sequences are partitioned into an automatically inferred number of types. The temporal dynamics of these sequences are captured by several Hawkes processes [11], where each process's distinctive temporal relation will help our model to disambiguate different types of sequences with spatial overlapping neurons. Besides, the prior of each sequence type is given by a Dirichlet distribution, so either the number of sequences or the number of sequence types could vary during inference. Note that our model has only one Dirichlet point process at the lower level, which is different from the classical hierarchical Dirichlet process (HDP) [22].

We derive a Particle filter [2] to learn the HDPP in an online manner: (1) learn the model with a single pass of the data; (2) make the decisions regularly without requiring future data [1]. In particular, we use a collection of particles to sequentially approximate the posterior, taking in one spike at a time to make the update. We also develop specific mechanisms to merge similar sequences and prune inaccurate ones during inference, thus further improving the performance. We evaluate the proposed model on synthetic data as well as real-world data from songbird higher vocal center [15] and rodent hippocampus [3, 7, 8]. Results show empirically the proposed model can properly identify the neural sequence and be robust to noise in a single pass over data.

The contributions of our work include: (1) We propose a novel hierarchical Dirichlet Point Process for neural sequence detection, and different from prior works [14, 15, 25], our model does not specify the number of sequence type in advance, while determines adaptively during inference. (2) Our model with an efficient online inference algorithm performs comparable to the state-of-the-art [25] with a significantly lower time cost. (3) We use a group of Hawkes processes to capture the temporal dynamics of different types of sequences, which enables our model to distinguish sequences with spatial overlapping neurons.

2   Related works

Previous studies about neural sequence detection can be divided into three classes: supervised, bottom-up unsupervised, and top-down unsupervised [29].

Supervised methods. Averaging spikes times over multiple trials is the simplest and most used supervised method to identify neural sequences. This approach requires simultaneous sensory cues or behavioral actions recording and uses a template matching procedure to discover exact timestamps of each sequence [12, 18]. However, as previoulys mentioned, the relationship between neural activity and behavior is not always reliable [27], thus this approach may be useless under certain circumstances.

Bottom-up unsupervised methods. Bottom-up unsupervised methods [20, 21, 23] usually identify neural sequences via a variety of statistics between pairs of neurons (e.g., cross-correlations). These methods may be beneficial when involving small numbers of neurons [29], but they have high computational complexity and low statistical power when dealing with large number of neurons.

Top-down unsupervised methods. Top-down unsupervised methods can be defined as a kind of method that discover a sequence from the perspective of the full population and is robust to noise at the level of individual neurons [29]. Maboudi et al. [14] identifies neural sequences by visualizing the transition matrix of Hidden Markov Models. Peter et al. [19] and Mackevicius et al. [15] use convolutive nonnegative matrix factorization (ConvNMF) with different regularization to factorize the neural data into a couple of neural factors and temporal factors, where each neural factor encodes a type of neural sequence and each temporal factor indicates the times of sequences. Williams et al. [25] models neural sequences as a Neyman-Scott process (PP-Seq), which is a spatial-temporal point process originally designed to discover clusters in the galaxy. Each sequence in this model corresponds to a latent cause that generates spikes as the offspring events.

3   Background

A basic probabilistic model of continuous-time event stream is temporal point process whose realization can be represented as an event sequences $\{x_i\}_1^N = \{t_1, t_2, ...\}$ with times of occurrence $t_i \in [0, T]$. A way to characterize temporal point processes is via intensity function $\lambda(t)$, for which $\lambda(t)$ equals the expected instantaneous rate of happening next event given the history. The functional

Figure 1: A case with $K = 3$ sequences and $M = 2$ types of sequences is shown. The proposed model considers observed spikes as a mixture of neural sequences, where spikes within a sequence can be modeled via a nonhomogeneous Poisson process that catches their firing rates. Likewise, the detected sequences are also a mixture of certain types of sequences, where their temporal dynamics are captured by several Hawkes processes.

form of $\lambda(t)$ varies among different phenomena of interests. In a *homogeneous* Poisson process (PP), $\lambda(t)$ is assumed to be a constant over time, while in a *nonhomogeneous* Poisson process, $\lambda(t)$ is time-varying and independent of the history.

Hawkes process. A Hawkes process (HP) [11] is a self-exciting nonhomogeneous Poisson process in which past events in history have influenced the intensity of current and future events. Such influences are positive but decay exponentially with time:

$$\lambda(t) = \lambda_0 + \alpha \sum_{t_i < t} \exp(-\delta(t - t_i)), \tag{1}$$

where λ_0 is the base intensity independent of the history, α is the kernel parameter, and δ is the decay rate of that influence. An important extension of the Hawkes process is to incorporate additional information about each event, for example, an associated event "label" k_i with each event $x_i = (t_i, k_i)$. As a consequence, we can define a Hawkes process as a sum of independent Hawkes processes from different types based on the superposition principle: $\lambda(t) = \sum_{k=1}^{K} \lambda_k(t)$, where $\lambda_k(t)$ is the intensity function from k-th category.

Dirichlet Hawkes process. Dirichlet Hawkes process (DHP) [5, 16] is a method to naturally handle infinite mixture clusters with temporal dependency. As opposed to traditional parametric models, DHP allows the number of clusters to vary over time. It uses a Hawkes process to model the intensity of events (e.g., the times of neural sequences), while the Dirichlet process captures the diversity of event types (e.g., the clusters of neural sequences). Similar to the Dirichlet process, a DHP, typically denoted by $\text{DHP}(\lambda_0, \theta)$ is characterized by a concentration parameter λ_0 and a base distribution θ. It uses the samples $\theta_{1:K}$ from base distribution θ and a collection of triggering kernel functions $\phi_{\theta_i}(t, t_i)$ as the parameters for modeling K different event types. Then, the events (t_i, θ_i) from $\text{DHP}(\lambda_0, \theta)$ can be simulated as follows:

1. Sample t_1 from $\text{PP}(\lambda_0)$ and θ_1 from θ.

2. For $n > 1$, sample t_n from $\text{HP}(\lambda_0 + \sum_{k=1}^{K} \lambda_k(t_n))$

   - Sample a new θ_{K+1} from θ with probability: $\lambda_0/(\lambda_0 + \sum_{k=1}^{K} \lambda_k(t_n))$
   - Reuse previous θ_k with probability: $\lambda_k(t_n)/(\lambda_0 + \sum_{k=1}^{K} \lambda_k(t_n))$

where $\lambda_k(t_n) = \sum_{i=1}^{n-1} \phi_{\theta_i}(t_n, t_i)\mathbb{I}(\theta_i = \theta_k)$ is the intensity function of a Hawkes process for past events with type k.

4   Hierarchical Dirichlet Point Process of Neural Sequences

We model the neural sequences as a hierarchical Dirichlet point process (HDPP). We use a Dirichlet nonhomogeneous Poisson process as the prior for observed spikes, while using a Dirichlet Hawkes

process as the prior for neural sequences. As in Figure 1, the goal of HDPP is to sequentially identify sequences from observed spikes, then partition these sequences into different types based on both temporal dynamics and included neurons.

Consider a continuous-time spike train data with N neurons, its observed spikes can be denoted by a set of S labeled events $x_s = (t_s, n_s, k_s)$ referring to the spike time, $t_s \in [0, T]$, neuron, $n_s \in \{1, ..., N\}$ and indicator to the sequence that x_s belongs to, $k_s \in \{1, ..., K\}$. Note that the indicator k_s remains unknown until we infer the sequences from the data. Similarly, the inferred neural sequences can also be represented as a collection of tuples $q_k = (\tau_k, m_k)$ referring to the time $\tau_k \in [0, T]$ and indicator for sequence type $m_k \in \{1, .., M\}$.

According to the definition of the Dirichlet Hawkes process, for a spike x_s occurring at time t_s its probability of belonging to the k-th neural sequence is:

$$P(k_s = k | t_s) = \frac{g_k(t_s)}{g_0 + g_{\text{noise}} + \sum_{k=1}^{K} g_k(t_s)}, \tag{2}$$

where g_0 is the concentration parameter, g_{noise} is the firing rate for background spikes, and $g_k(t)$ is the intensity function of sequence q_k, controlling the temporal dynamics of related spikes. Likewise, the probability of assigning spike x_s to either background noise or a new sequence is given by:

$$P(k_s = k | t_s) = \begin{cases} \frac{g_{\text{noise}}}{g_0 + g_{\text{noise}} + \sum_{k=1}^{K} g_k(t_s)} & \text{for } k = 0, \\ \frac{g_0}{g_0 + g_{\text{noise}} + \sum_{k=1}^{K} g_k(t_s)} & \text{for } k = K + 1. \end{cases} \tag{3}$$

After a neural sequence $q_{k>0}$ is chosen, we assign it to an existing type m_k or create a new type on the fly as needed with probability:

$$P(m_k = m | \tau_k) = \begin{cases} \frac{\lambda_m(\tau_k)}{\lambda_0 + \sum_{m=1}^{M} \lambda_m(\tau_k)} & \text{for } m \in \{1, ..., M\}, \\ \frac{\lambda_0}{\lambda_0 + \sum_{m=1}^{M} \lambda_m(\tau_k)} & m = M + 1. \end{cases} \tag{4}$$

where $\lambda_m(\tau)$ is the intensity function that captures temporal dynamics of sequences in type m. Note that we assume $g_k(t)$ and $\lambda_m(\tau)$ take different functional forms, and $g_{kn}(t)$ can be viewed as the firing rate of neuron n caused by sequence q_k. Following the work in [25], we represent $g_{kn}(t)$ via a Gaussian form as:

$$g_{kn}(t) = \theta_{m_k n} \cdot \beta_k \cdot \mathcal{N}(t | \tau_k + \mu_{m_k n}, \sigma_{m_k n}). \tag{5}$$

Here $\theta_{m_k n}$, $\mu_{m_k n}$ and $\sigma_{m_k n}$ are parameters of each sequence type m_k, indicating the weight, offset, and width of neuron n's firing rate. β_k is the amplitude of sequence q_k, denoting the expected number of spikes induced by q_k [25]. For $\lambda_m(\tau)$, we opt the similar form as (1), with parameter $\alpha_m > 0$ controlling the self-excitation of previous sequences, hyperparameter $\delta > 0$ controls the decay and hyperparameter η denotes the expected time interval of sequences:

$$\lambda_m(\tau) = \alpha_m \sum_{\tau_k} \exp(-\delta(\tau - \tau_k - \eta)) \mathbb{I}(\theta_k = \theta_m). \tag{6}$$

Based on the definition of $g_k(t)$ and $\lambda_m(\tau)$, we regard that the temporal dynamics of spikes and neural sequences are captured by a nonhomogeneous Poisson process and a self-exciting Hawkes process, respectively. For sequence type parameters α_m, $\{\theta_{mn}\}_{n=1}^{N}$ and $\{(\mu_{mn}, \sigma_{mn})\}_{n=1}^{N}$, we assume they follow a Gamma distribution, a Dirichlet distribution, and a normal-inverse-chi-squared distribution [17, 25] for every neuron and type. For amplitude β_k and background spike rate g_{noise}, we assume they obey a Gamma distribution. Then, we can describe the proposed hierarchical Dirichlet point process in a generative way as:

1. For neural sequence q_k, $\tau_k \sim \text{HP}(\lambda_0 + \sum_{m=1}^{M} \lambda_m(\tau_{k-1}))$, $\beta_k \sim \text{Gamma}(a_1, b_1)$.

2. Sample sequence type m_k using (4).
   - If $m_k = M + 1$: $\theta_{M+1} \sim \text{Dir}(\theta_0)$, $(\mu_{M+1}, \sigma_{M+1}) \sim \text{NI}\chi^2(\mu_0, \kappa_0, \upsilon_0, \sigma_0)$, $\alpha_{M+1} \sim \text{Gamma}(a_2, b_2)$ and $M = M + 1$.

3. Sample spikes induced by sequence q_k: $s_k = \text{Poisson}(\beta_k)$, $\{n_s\}_{s=1}^{s_k} \sim \text{Categorical}(\theta_{m_k})$ and $\{t_s\}_{s=1}^{s_k} \sim \mathcal{N}(\tau_k + \mu_{m_k n_s}, \sigma_{m_k n_s})$

156   4. Sample background spikes during time interval $\Delta t = \tau_k - \tau_{k-1}$: $g_{\text{noise}} \sim \text{Gamma}(a_0, b_0)$,
157      $s_0 = \text{Poisson}(g_{\text{noise}} \cdot \Delta t)$, $\{n\}_{s=1}^{s_0} \sim \text{Categorical}(\theta_{\text{noise}})$ and $\{t_s\}_{s=1}^{s_0} \sim \text{Uniform}([\tau_{k-1}, \tau_k])$.

158   where θ_0 is a hyperparameter parameter for Dirichlet prior, $a_0, b_0, a_1, b_1, a_2, b_2$ are hyperparameter
159   parameters for Gamma prior, and $\mu_0, \kappa_0, \upsilon_0, \sigma_0$ are hyperparameter parameters for normal-inverse-
160   chi-squared prior.

5   Inference

162   Given spikes $\{x_s = (t_s, n_s)\}_{s=1}^{S}$, as previously discussed, the model aims to sample neural sequences
163   indicator k_s for each spike. Using this insight, we can use a set of particles to sequentially approximate
164   posterior $P(k_{1:s}|t_{1:s}, n_{1:s})$, while sampling indicator m_k for each sequence.

165   We derive a Particle filter approach for our proposed model. This inference algorithm exploits
166   the temporal dependencies in the observed spikes to sequentially sample the latent variables. To
167   efficiently sample from the posterior distribution, a Particle filter keeps track of an approximation
168   of $P(k_{1:s-1}|t_{1:s-1}, n_{1:s-1})$, and updates it to have an approximation for $P(k_{1:s}|t_{1:s}, n_{1:s})$ when
169   receiving a newly observed spike. The approximation is evaluated by a set of weighted particles
170   $\{p\}^P$, where the weight of each particle reflects how well the observed spikes are explained.

171   For each particle p, its weight is defined as the ratio between true posterior and importance distribution:
172   $w_s^p = \frac{P(k_{1:s}|t_{1:s}, n_{1:s})}{Q(k_{1:s}|t_{1:s}, n_{1:s})}$. As the work in [1, 5] did, we choose $P(k_s|k_{1:s-1}, t_{1:s}, n_{1:s})$ to be the
173   importance distribution. Next, the unnormalized weight w_s^p can be updated as:

$$w_s^p \propto w_{s-1}^p \cdot P(n_s|k_{1:s}, n_{1:s-1}). \tag{7}$$

174   Here, let $C^{m_{k_s} \setminus x_s}$, $C_{n_s}^{m_{k_s} \setminus x_s}$ denote the spike counts of sequence type m_{k_s} and spike counts of
175   neuron n_s in sequence type m_{k_s}, both excluding x_s. The likelihood $P(n_s|k_{1:s}, n_{1:s-1})$ is given by a
176   Dirichlet-Categorical conjugate relation [16]:

$$\frac{C_{n_s}^{m_{k_s} \setminus x_s} + \theta_{0n_s}}{C^{m_{k_s} \setminus x_s} + \sum_{n=1}^{N} \theta_{0n}}. \tag{8}$$

177   After sampling indicator k_s from posterior $P(k_s|t_s, n_s, \text{rest})$ for each spike, we then sample the type
178   indicators m_k from posterior $P(m_k|\tau_k, X_k, \text{rest})$. The posteriors of both indicators are determined by
179   the likelihood of the spike/sequence assigned to a given sequence/sequence type and by the temporal
180   prior under Dirichlet nonhomogeneous Poisson process (2)(3) or Dirichlet Hawkes process (4):

$$P(k_s|t_s, n_s, \text{rest}) \propto P(n_s|k_s, \text{rest}) \cdot P(k_s|t_s, \text{rest}), \tag{9}$$

181

$$P(m_k|\tau_k, X_k, \text{rest}) \propto P(X_k|m_k, \text{rest}) \cdot P(m_k|\tau_k, \text{rest}), \tag{10}$$

182   where *rest* represents all other latent variables with $x_{1:s-1}$, $X_k = \{n_s : k_s = k\}$ is the neurons in
183   k-th sequence. The exact form of the two posteriors is given in Supplement A.

184   **Updating parameters.** There are three groups of parameters that need to be updated after attributing
185   each spike to a neural sequence: sequence type parameters $\Theta_m = (\theta_m, \alpha_m, \{\mu_{mn}\}_{n=1}^{N}, \{\sigma_{mn}\}_{n=1}^{N})$,
186   sequence parameters $\Theta_k = \{\tau_k, \beta_k\}$ and background parameters $\Theta_\emptyset = g_{\text{noise}}$. Following the literature
187   in Particle filter devoted to the estimation of an online parameter [2], for most parameters, we perform
188   a single Gibbs sampling step to sample from their closed-form posterior under conjugate relation.
189   Details about derivations are in Supplement B.

190   **Merge and Prune.** Generally speaking, neural sequences created during this sequential inferring
191   procedure are often truly needed, as the decisions of adding new sequences are based on the accumu-
192   lated knowledge from the past. However, there is still a chance that some sequences generated at
193   early samples would become incorrect and that multiple sequences may be close in time. Thus, we
194   introduce a mechanism to merge similar sequences and prune incorrect ones.

195   The similarity of two sequences q_k and $q_{k'}$ can be defined in terms of the time difference between
196   τ_k and $\tau_{k'}$, as $d(k, k') = |\tau_k - \tau_{k'}|$. We will merge sequences $q_k, q_{k'}$ and their associated sufficient
197   statistics when $d(k, k') < \Delta_d$. We also check the variance of firing times for each neuron in

every sequence. That is, we reserve the spikes which fire consecutively in the same neuron n: $\mathrm{Var}(\{t_s\}_{s=1}^{s_n}) < \epsilon$, while removing those that appear to be sparsely distributed. Besides, we will remove an entire sequence if it has too few spikes after pruning. Note that there is no need to perform such merge or prune at every iteration. Since the operation of merge sequences takes $O(K)$ and computing variance for each sequence takes $O(s_n \cdot N)$, we propose to examine similarity and variance at a fixed interval $O(i \cdot T)$ and only for the current sampled sequence.

The overall pseudocode for inference is presented in Algorithm 1, and its time complexity is $O(SP(K + M))$, where S is the number of spikes, P is the number of particles, K is the number of sequences, and M is the number of types.

Algorithm 1: Particle filter for HDPP

Input: Spikes $\{x_s = (t_s, n_s)\}_{s=1}^S$, hyperparameters and threshold ϵ.
Initialize particle weight w^p to $\frac{1}{P}$ for all $p \in \{1, .., P\}$;
for *each spike* $(t_s, n_s), s = 1, ..., S$ **do**
    for $p \in \{1, ..., P\}$ **do**
        Sample sequence indicator k_s from (9);
        Sample sequence type indicator m_k from (10);
        Update the parameters Θ_m, Θ_k, and $\Theta_\emptyset$;
        Update the particle weight by (7);
    end
    Normalize particle weight;
    if $\|w^p\|_2^{-2} < \epsilon$ **then**
        Resample particles
    end
end

---

6 Experiments

6.1 Synthetic Data

We created three kinds of synthetic data to investigate the robustness to noise, the effectiveness of temporal dynamics, and the ability to infer the number of types of sequences, respectively, of HDPP: (1) Two types of sequences with background noise. (2) Two types of sequences occur side-by-side with spatial overlapping neurons. (3) A large set of sequence types with spatial overlapping neurons, where they are much uncertainty in sequence types.

Robustness to background noise. Figure 2(a) presents the first case of synthetic data, which demonstrates the robustness of HDPP. This data has $N = 60$ neurons and $T = 30$ seconds. The raw spikes (Figure 2(a) left panel) show no visible neural sequences. However, sequences are revealed by sorting the neurons with the learned weight, type, and offset of this sequence. Besides, background spikes can also be correctly identified as noise.

Distinguishing overlapping sequences. Figure 2(b) shows a much more complex case where two sequences with overlap populations of neurons occur side-by-side. This data has $N = 60$ neurons and $T = 20$ seconds. Usually, it's hard to distinguish these sequences from the perspective of neurons. But with the help of temporal dynamics, HDPP could be able to capture sequences' distinctive intensity functions (Figure 2(b) top panel), and disambiguate them to different types. Note that the intensities at the very beginning are missing since HDPP resamples a type indicator for the first sequence whenever it receives a spike and those empty types are dropped as well as their recorded intensities.

Inferring the types of sequences from data. Figure 2(c) shows the comparison of HDPP and PP-Seq, demonstrating that HDPP can infer the number of types from data. This data has $N = 60$ neurons and $T = 400$ seconds, where there are 11 different types of sequences: 6 types of smaller sequences involving 10 neurons, while other 5 types of larger sequences involving 20 neurons. Note that the larger sequences and smaller sequences have spatial overlapping neurons. HDPP could be able to distinguish the sequences with overlapping neurons without prior information on the number

Figure 2: Synthetic data. (a) Two types of sequences with background noise. Raw spikes (left), neurons re-sorted by HDPP (middle), sequences annotated by HDPP (right), and corresponding intensities captured by Hawkes processes (top). (b) Two types of highly overlapping sequences occur side-by-side with background noise. (c) Comparison of HDPP and PP-Seq on a large set of sequence types with spatial overlapping neurons. HDPP can infer the types of sequences from data (d) Comparison of HDPP, PP-Seq, and convNMF to identify sequences under different levels of background noise. HDPP is robust to background noise.

of types (Figure 2(c), left panel), while PP-Seq identifies the larger sequences as a new type when setting the prior of types to a Dirichlet prior with 11 categories (Figure 2(c), right panel).

Further, we also tested the robustness of HDPP quantitatively with the area under reciever operating characteriztic (ROC) curves as a metric. To keep in line with previous work[25], we simulated a dataset with $M = 1$ sequence type and $N = 100$ neurons, where we varied the background spikes g_{noise} to quantitatively measure the robustness. From the results of the area under ROC in Figure 2(d), HDPP achieves promising results as we increase the noise levels.

6.2 Performance with Neural Recordings

6.2.1 Songbird Higher Vocal Center Recording

For real-world data, we first applied our model to the deconvolved spike train from functional imaging data recorded in songbird HVC during singing [15][1]. One of the core features of this data is the high variability of the song, thus making it difficult to identify neural sequences by a template matching procedure.

Identifying neural sequences from Songbird Recording. Figure 3(a) visualizes the results from HDPP and PP-Seq[2], where we chose the neurons whose weight $\{\theta_{mn}\}_{n=1}^{N}$ was above a threshold, and sorted them based on each sequence's type m_k and offset $\{\mu_{mn}\}_{n=1}^{N}$. Figure 3(b)-(c) visualize the learned offset and weight from HDPP. For offset $\{\mu_{mn}\}_{n=1}^{N}$, there is a clear time-shift among different neurons ($\pm$ 0.25s for type 1 and $\pm$ 0.3s for type 2), and for weight $\{\theta_{mn}\}_{n=1}^{N}$, the two sequence types have their own preference for neurons (neuron 27~62 for type 1 and neuron 1~26 for type 2). Figure 3(d) indicates HDPP converges to similar parameter ranges: The total number of detected sequences over five independent runs (different random seeds for initiation) are close to each other. Finally, Figure 3(e) shows the log-likelihood comparison of HDPP and PP-Seq averaging over different runs.

---

[1] http://github.com/FeeLab/seqNMF
[2] https://github.com/lindermanlab/PPSeq.jl

Figure 3: Songbird Higher Vocal Center data. (a) Raw spike train (left) and comparison of detected sequences by HDPP (bottom) and PP-Seq (top). (b)(c) Visualization of learned offsets and weights for sequence type 1 (blue) and sequence type 2 (red). (d) The number of detected sequences over five independent runs. (e) The log-likelihoods comparison of HDPP and PP-Seq.

6.2.2 Rodent Hippocampal Recording

We then tested our model on a more complex spike train data from a rat's hippocampal recording when it performs repeating runs down a wooden 1.6m linear track [3, 8, 7][3]. The session we used is "Achilles 10252013", which has $N = 120$ neurons and $T = 2068$ seconds. As in [8], we expect to observe two sequences encoding the two opposite running directions on this liner track. To have a good knowledge of hyperparameter settings, we performed cross-validation via a "speckled holdout pattern" strategy, which was previously used in PCA [30], and has recently been applied to neural data [25, 26]. We then evaluated the performance of HDPP by calculating log-likelihood on the held-out set.

Identifying neural sequences from Hippocampal Recording. Figure 4(a)-(c) shows the raw spikes, sorted results, and two types of sequences annotated by HDPP, where we can clearly observe two groups of place coding neurons revealed by the sequences. Figure 4(d) presents the validation log-likelihoods of four key hyperparameters in HDPP, while other parameters have less impact on performance or are easy to locate the optimal range. Not surprisingly, without taking into account of efficiency, a larger number of particles has a positive effect on the performance of the model, but the improvement is not obvious during a certain range (e.g. 20~40). What's more, HDPP on this data prefers larger sequence amplitude β_k, and higher prior rate b_0 in gamma distribution, which instead means smaller noise firing rate g_{noise}.

6.3 Scalability to Large Dataset

To scale with large recordings, HDPP is supposed to process each spike in an expected constant time. In other words, the time cost of either calculating intensity functions or updating parameters should not grow with the number of sequences detected so far. In HDPP, we can note that the influences of past sequences decay exponentially, using this insight, we can reduce the computational load by ignoring those past sequences far away from the current time. More specifically, given a time window Δt, we maintain an active list of sequences $\{q_k\}_{k=1}^K$ where $t - \tau_k \leq \Delta t$. Similarly, using temporal windows is also acceptable for PP-Seq by limiting the max length of each sequence, which is supposed to reduce its loop operations. The test of performance was carried by a desktop with AMD Ryzen 7 5800X 8-Core Processor and 32 GB RAM. Figure 4(e) shows the performance comparison between HDPP and PP-Seq on rodent hippocampal recording. For HDPP, we set the particle number to 20, and for PP-Seq, we adopt parallel MCMC to parallelize the computation as well as setting the number of Gibbs sweeps to 2100 [25]. The results indicate that HDPP is still faster than parallel PP-Seq though it is benefited from the temporal window. Figure 4(f) presents the time cost as a function of detected sequences, which empirically verifies that HDPP has a constant time cost per spike after settling in.

---

[3]http://crcns.org/data-sets/hc/hc-11

Figure 4: Rodent hippocampal recording. (a) Raw spike train ($T \approx 4.6$ minutes is shown). (b) Neurons sorted by HDPP. (c) Two types of sequences identified by HDPP. (d) The validation log-likelihoods on four key hyperparameters. Each boxplot involves five different values of a hyperparameter, while other hyperparameters are set to fixed values. (e) Performance comparison between HDPP and parallel PP-Seq on rodent hippocampal recording. (f) HDPP's time cost as a function of detected sequences.

7 Discussion

We present a hierarchical Dirichlet point process (HDPP) for neural sequence detection with an efficient online inference algorithm. The proposed model follows the framework of the Dirichlet point process, where spike firing rates are modeled as a nonhomogeneous Poisson process and temporal dynamic of different sequences is captured via a Hawkes process. Unlike previous works, HDPP learns the number of sequence types adaptively during inference and takes in data in a streaming fashion, thus can be easily adapted to new data or large neural recordings. In the experiments, favorable results from both synthetic data and real-world spike recordings have demonstrated that HDPP can reliably and efficiently identify neural sequences in a single pass.

However, there are some conditions our model may fail: (1) Time warping noise. Our model does not model the variability in sequence, which is said to be a common phenomenon in neural data [25, 28]. (2) A Low firing rate of neurons. Generally speaking, a high firing rate makes it easier to identify sequence from background noise. As the firing rate becomes lower, the performance of our model and existing methods decreased (supplement material Figure 1). Furthermore, it is an exciting future direction to investigate how we can learn HDPP via online variational inference without truncated approximation of the stick-breaking construction [13, 24].

References

[1] Kevin Canini, Lei Shi, and Thomas Griffiths. Online inference of topics with latent dirichlet allocation. In *Artificial Intelligence and Statistics*, pages 65–72. PMLR, 2009.

[2] Olivier Cappé, Simon J Godsill, and Eric Moulines. An overview of existing methods and recent advances in sequential monte carlo. *Proceedings of the IEEE*, 95(5):899–924, 2007.

[3] Zhe Chen, Andres D Grosmark, Hector Penagos, and Matthew A Wilson. Uncovering representations of sleep-associated hippocampal ensemble spike activity. *Scientific reports*, 6(1):1–13, 2016.

[4] Thomas J Davidson, Fabian Kloosterman, and Matthew A Wilson. Hippocampal replay of extended experience. *Neuron*, 63(4):497–507, 2009.

[5] Nan Du, Mehrdad Farajtabar, Amr Ahmed, Alexander J Smola, and Le Song. Dirichlet-hawkes processes with applications to clustering continuous-time document streams. In *Proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pages 219–228, 2015.

[6] Mark S Goldman. Memory without feedback in a neural network. *Neuron*, 61(4):621–634, 2009.

[7] AD Grosmark, J Long, and G Buzsáki. Recordings from hippocampal area ca1, pre, during and post novel spatial learning. *CRCNS. org*, 10:K0862DC5, 2016.

[8] Andres D Grosmark and György Buzsáki. Diversity in neural firing dynamics supports both rigid and learned hippocampal sequences. *Science*, 351(6280):1440–1443, 2016.

[9] Richard HR Hahnloser, Alexay A Kozhevnikov, and Michale S Fee. An ultra-sparse code underliesthe generation of neural sequences in a songbird. *Nature*, 419(6902):65–70, 2002.

[10] Christopher D Harvey, Philip Coen, and David W Tank. Choice-specific sequences in parietal cortex during a virtual-navigation decision task. *Nature*, 484(7392):62–68, 2012.

[11] Alan G Hawkes. Spectra of some self-exciting and mutually exciting point processes. *Biometrika*, 58(1):83–90, 1971.

[12] Daoyun Ji and Matthew A Wilson. Coordinated memory replay in the visual cortex and hippocampus during sleep. *Nature neuroscience*, 10(1):100–107, 2007.

[13] Dahua Lin. Online learning of nonparametric mixture models via sequential variational approximation. *Advances in Neural Information Processing Systems*, 26, 2013.

[14] Kourosh Maboudi, Etienne Ackermann, Laurel Watkins de Jong, Brad E Pfeiffer, David Foster, Kamran Diba, and Caleb Kemere. Uncovering temporal structure in hippocampal output patterns. *Elife*, 7:e34467, 2018.

[15] Emily L Mackevicius, Andrew H Bahle, Alex H Williams, Shijie Gu, Natalia I Denisenko, Mark S Goldman, and Michale S Fee. Unsupervised discovery of temporal sequences in high-dimensional datasets, with applications to neuroscience. *Elife*, 8:e38471, 2019.

[16] Charalampos Mavroforakis, Isabel Valera, and Manuel Gomez-Rodriguez. Modeling the dynamics of learning activity on the web. In *Proceedings of the 26th International Conference on World Wide Web*, pages 1421–1430, 2017.

[17] Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

[18] Eva Pastalkova, Vladimir Itskov, Asohan Amarasingham, and Gyorgy Buzsaki. Internally generated cell assembly sequences in the rat hippocampus. *Science*, 321(5894):1322–1327, 2008.

[19] Sven Peter, Elke Kirschbaum, Martin Both, Lee Campbell, Brandon Harvey, Conor Heins, Daniel Durstewitz, Ferran Diego, and Fred A Hamprecht. Sparse convolutional coding for neuronal assembly detection. *Advances in Neural Information Processing Systems*, 30, 2017.

[20] Pietro Quaglio, Vahid Rostami, Emiliano Torre, and Sonja Grün. Methods for identification of spike patterns in massively parallel spike trains. *Biological cybernetics*, 112(1):57–80, 2018.

[21] Eleonora Russo and Daniel Durstewitz. Cell assemblies at multiple time scales with arbitrary lag constellations. *Elife*, 6:e19428, 2017.

[22] Yee Teh, Michael Jordan, Matthew Beal, and David Blei. Sharing clusters among related groups: Hierarchical dirichlet processes. *Advances in neural information processing systems*, 17, 2004.

[23] Emiliano Torre, Carlos Canova, Michael Denker, George Gerstein, Moritz Helias, and Sonja Grün. Asset: analysis of sequences of synchronous events in massively parallel spike trains. *PLoS computational biology*, 12(7):e1004939, 2016.

[24] Chong Wang and David Blei. Truncation-free online variational inference for bayesian nonparametric models. *Advances in neural information processing systems*, 25, 2012.

[25] Alex Williams, Anthony Degleris, Yixin Wang, and Scott Linderman. Point process models for sequence detection in high-dimensional neural spike trains. *Advances in neural information processing systems*, 33:14350–14361, 2020.

[26] Alex H Williams, Tony Hyun Kim, Forea Wang, Saurabh Vyas, Stephen I Ryu, Krishna V Shenoy, Mark Schnitzer, Tamara G Kolda, and Surya Ganguli. Unsupervised discovery of demixed, low-dimensional neural dynamics across multiple timescales through tensor component analysis. *Neuron*, 98(6):1099–1115, 2018.

[27] Alex H Williams and Scott W Linderman. Statistical neuroscience in the single trial limit. *Current opinion in neurobiology*, 70:193–205, 2021.

[28] Alex H Williams, Ben Poole, Niru Maheswaranathan, Ashesh K Dhawale, Tucker Fisher, Christopher D Wilson, David H Brann, Eric M Trautmann, Stephen Ryu, Roman Shusterman, et al. Discovering precise temporal patterns in large-scale neural recordings through robust and interpretable time warping. *Neuron*, 105(2):246–259, 2020.

[29] Alexander Henry Williams. *Unsupervised Methods for Neural Data Analysis with Single Trial Resolution*. Stanford University, 2019.

[30] Svante Wold. Cross-validatory estimation of the number of components in factor and principal components models. *Technometrics*, 20(4):397–405, 1978.