DEEP CONTINUOUS NETWORKS

ABSTRACT

CNNs and computational models of biological vision share some fundamental principles, which, combined with recent developments in deep learning, have opened up new avenues of research in neuroscience. However, in contrast to biological models, conventional CNN architectures are based on spatio-temporally discrete representations, and thus cannot accommodate certain aspects of biological complexity such as continuously varying receptive field sizes and temporal dynamics of neuronal responses. Here we propose deep continuous networks (DCNs), which combine spatially continuous convolutional filter representations, with the continuous time framework of neural ODEs. This allows us to learn the spatial support of the filters during training, as well as model the temporal evolution of feature maps, linking DCNs closely to biological models. We show that DCNs are versatile. Experimentally, we demonstrate their applicability to a standard classification problem, where they allow for parameter reductions and meta-parametrization. We illustrate the biological plausibility of the scale distributions learned by DCNs and explore their performance in a pattern completion task, which is inspired by models from computational neuroscience. Finally, we suggest that the continuous representations learned by DCNs may enable computationally efficient implementations.

1 INTRODUCTION

Computational neuroscience and computer vision have a long and mutually beneficial history of cross-pollination of ideas (Sejnowski, 2020; Cox & Dean, 2014). The current state-of-the-art in computer vision relies heavily on deep neural networks (DNNs), and in particular convolutional neural networks (CNNs), from which multiple analogies can be drawn to biological circuits (Kietzmann et al., 2019). Specifically, recent advances in DNNs have enabled researchers to learn more accurate models of the response properties of neurons in the visual cortex (Klindt et al., 2017; Cadena et al., 2019; Ecker et al., 2019), as well as to test decades old hypotheses from neuroscience in the domain of computer vision (Lindsey et al., 2019). However, contrary to biological models, CNNs typically operate in the domain of spatio-temporally discrete signals, and employ appropriately discretized kernels, as a natural part of digital image processing.

In computational neuroscience, on the other hand, large scale neural network models of the visual system often adopt continuous, closed-form expressions to describe spatio-temporal receptive fields, as well as the interaction strength between populations of neurons (Dayan & Abbott, 2001). Among others, such descriptions serve to limit the scope and parameter space of a model, by utilizing prior information regarding receptive field shapes (Jones & Palmer, 1987) and principles of perceptual grouping (Li, 1998). In addition, the choice of continuous—and often analytic—functions help retain some analytical tractability in complex models involving a large number of coupled populations. Our approach draws inspiration from such computational models to propose continuous representations of receptive fields in CNNs, where both the shape and the scale of the filters are trainable in the continuous domain.

In a complementary fashion, recent influential work in deep learning has introduced neural ordinary differential equations (ODEs) (Lu et al., 2018; Ruthotto & Haber, 2019; Chen et al., 2018) which propose a continuous time (or depth) interpretation of CNNs. Such continuous time models both offer end-to-end training capabilities with backpropagation which are highly applicable to computer vision problems (e.g. by way of adopting ResNet blocks (He et al., 2016)), as well as help bridge the gap to computational biology where networks are often modelled as dynamical systems which

evolve according to differential equations. In this work we aim to extend the impetus of the continuous time neural ODEs to the spatio-temporal domain.

To that end we introduce deep continuous networks (DCNs), which are spatio-temporally continuous in that the neurons have spatially well-defined receptive fields based on scale-spaces and Gaussian derivatives (Florack et al., 1996) and their activations evolve according to equations of motion comprising conventional convolutional layers. We combine spatial and temporal continuity in a network with neural ODEs by learning linear weights for a set of analytic basis functions (as opposed to pixel-based weights), which can also intuitively be parametrized as a function of time, or network depth.

The following outlines our main contributions: (i) We provide a theoretical formulation of spatio-temporally continuous deep networks building on Gaussian derivative basis functions and neural ODEs; (ii) We demonstrate the applicability of DCN models, namely, that they exhibit a reduction in parameters, and can be used to parametrize convolutional filters as a function of time in a straightforward fashion, while achieving comparable performance with ResNet and ODE-Net baselines; (iii) We show that filter scales learned by DCNs are consistent with biological observations and we propose that the combination of our design choices for spatial and temporal continuity may be helpful in studying the emergence of biological receptive field properties as well as high-level phenomena such as pattern completion; (iv) We suggest that the continuous representations learned by DCNs may be leveraged for computational savings.

We believe DCNs can bring together two communities as they provide a test bed for hypotheses and predictions pertaining to both biological systems as well as pushing the boundaries of biologically inspired computer vision.

2 DEEP CONTINUOUS NETWORKS

2.1 NEUROSCIENTIFIC MOTIVATION

There is little doubt that modern deep learning frameworks will be conducive to effective and insightful collaborations between neuroscience and machine learning (Richards et al., 2019). In particular in vision research, CNNs are becoming increasingly popular for modelling early visual areas (Batty et al., 2017; Ecker et al., 2019; Lindsey et al., 2019). Here we propose a model which can facilitate such investigations by linking the end-to-end trainable but discrete CNN architectures with the biologically more plausible and spatio-temporally continuous computational models.

Structured receptive fields. Classical receptive fields (RFs) of cortical neurons display complex response properties with a wide array of selectivity structures already at early visual areas (Van den Bergh et al., 2010). Such response properties may also vary greatly based on multiple factors. For example the RF size (spatial extent) is known to depend on eccentricity (Harvey & Dumoulin, 2011) and visual area (Smith et al., 2001) and may even change with depth within a cortical layer (Bauer et al., 1999). Similarly, studies have shown that receptive field size and spatial frequency selectivity of neurons may co-vary with input contrast (Sceniak et al., 2002).

Based on these observations, we aim to build a model which can accommodate the biological complexity better than conventional CNNs, by explicitly modelling the RF size as a trainable parameter. To that end, we adopt a Gaussian scale-space representation for the convolutional filters, which we call structured receptive fields (SRFs) (Jacobsen et al., 2016). Previously, Gaussian scale-spaces have been proposed as a plausible model of biological receptive fields and feature extraction in low-level vision (Florack et al., 1992; Lindeberg & Florack, 1994; Lindeberg, 1993). Here, we are inspired partially by computational models which investigate the origin of response properties in the visual system, by employing RFs and recurrent interaction functions which scale as a difference of Gaussians (Somers et al., 1995; Ernst et al., 2001). Partially, we are motivated by the success of algorithms which utilize Gaussian scale-spaces (Lowe, 2004).

Neural ODEs. Studies have shown that both the contrast (Albrecht et al., 2002) and spatial frequency (Frazor et al., 2004) response functions of cortical neurons display characteristic temporal profiles. However, temporal dynamics are not incorporated into typical feed-forward CNN models. In addition, it has been suggested that lateral interactions play an important role in the generation of complex and selective neuronal responses (Angelucci & Bressloff, 2006). Such activity dynamics

Figure 1: SRF filters based on N-jet filter approximation. Convolutional filters are defined as the weighted sum of Gaussian derivative basis functions up to order 2, with corresponding scales $\sigma_1 = 2.28$ (left) and $\sigma_2 = 0.90$ (right). Our DCN models learn both the coefficients α, and the scale σ end-to-end during training.

are often computationally modeled using recurrently coupled neuronal populations whose activations evolve according to coupled differential equations (Ben-Yishai et al., 1995; Ernst et al., 2001).

For temporally continuous computational representations consistent with biological models, we adopt the framework of neural ODEs (Chen et al., 2018). Neural ODE interpretation of ResNet models presents an opportunity to explicitly model the temporal dynamics of feature extractors in DNNs. Under certain assumptions, neural ODEs can be interpreted as recurrent interactions (Rousseau et al., 2019), which are biologically plausible (Liao & Poggio, 2016). Unlike ODEs based on pixel-based convolutional filters, the combination with structured filters (SRFs) also provide an intuitive way to parametrize the evolution of the kernels as a function of depth.

2.2 STRUCTURED RECEPTIVE FIELDS

We use the multiscale local N-jet formulation (Florack et al., 1996) to define the filters in convolutional layers. Structured receptive fields (SRFs) based on the Gaussian N-jet basis functions are highly applicable to CNNs, as they represent a Taylor expansion of the input image or feature maps in a local neighbourhood in space and scale, and can be used to approximate pixel-based filters (Appendix A.1). This means that each filter $F(x, y; \sigma)$ in the network is a weighted sum of N basis functions, which are partial derivatives of the isotropic two-dimensional Gaussian function $G(x, y; \sigma) = \frac{1}{2\pi\sigma^2}e^{\frac{-(x^2+y^2)}{2\sigma^2}}$. The scale, or the spatial extent, of the filter is explicitly modelled in the σ parameter of the Gaussian, which also indirectly determines the spatial frequency response of the SRF (Figure 1).

Formally, the N-jet formulation of an SRF filter $F(x, y)$ is given by:

$$F_\alpha(x, y; \sigma) = \sum_{\substack{0 \leq i, \, 0 \leq j}}^{i+j \leq N} \alpha_{i,j} \, G^{i,j}(x, y; \, \sigma) = \sum_{\substack{0 \leq i, \, 0 \leq j}}^{i+j \leq N} \alpha_{i,j} \, \frac{\partial^{i+j}}{\partial x^i \partial y^j} G(x, y; \, \sigma), \quad (1)$$

where $G^{i,j}(x, y; \, \sigma)$ are the partial derivatives of the Gaussian $G(x, y; \sigma)$ with respect to x and y, N is the degree of the Taylor polynomial which determines the basis order, and α encodes the expansion coefficients.

Defined this way, SRFs have favourable properties over pixel-based filters. SRF filters are steerable by the coefficients α and the basis functions are spatially separable. Likewise, due to their spatially continuous description, the filters can be trivially scaled, or rotated, without interpolation.

Figure 1 shows the N-jet approximation of two filters in two different scales σ_1 and σ_2. We note that both the coefficients α and the scale σ are learnable filter parameters. Instead of fixing the scale σ *a priori* and optimizing for α as in Jacobsen et al. (2016) and Sosnovik et al. (2020), we integrate both these parameters in the network optimization, thus learning not only the shape but also the spatial support of the filters.

2.3 NEURAL ODES

We model the continuous evolution of feature maps within an 'ODE block'. Formally, an ODE block contains a stack of M convolutional layers, each with its own convolutional filters $\mathbf{w}^m$ with $m = 1 \ldots M$, followed by normalization $G_{\text{norm}}(\cdot)$ and non-linear activation $\text{CELU}(\cdot)$ functions. Following the notations of Chen et al. (2018) and Ruthotto & Haber (2019), we define the equations of motion for the feature states $\mathbf{h} \in \mathbb{R}^n$ as:

$$\frac{d\mathbf{h}(t)}{dt} = f(\mathbf{h}(t), t, \mathbf{w}^m, \mathbf{d}^m) = G_{\text{norm}} \left[\mathbf{K}_2(\mathbf{w}^2) g(\mathbf{K}_1(\mathbf{w}^1) g(\mathbf{h}) + \mathbf{J}_1(\mathbf{d}^1) t) + \mathbf{J}_2(\mathbf{d}^2) t \right] \quad (2)$$

where $g(\mathbf{x}) = \text{CELU}(G_{\text{norm}}(\mathbf{x}))$, the linear operators $\mathbf{K}_m \in \mathbb{R}^{n \times n}$ denote the convolution operators parametrized by $\mathbf{w}^m$, and $\mathbf{J}_m \in \mathbb{R}^n \times \mathbb{R}$ denote the linear explicit t-terms parametrized by $\mathbf{d}^m$. The filters $\mathbf{w}^m$, $\mathbf{d}^m(\theta)$ are functions of some learnable parameters θ. As a typical CNN convolution operator, $\mathbf{K}_m(\mathbf{w}^m)$ with 2 input and 2 output channels can be written as

$$\mathbf{K}_m(\mathbf{w}^m) = \begin{pmatrix} \mathbf{K}_m^{1,1}(\mathbf{w}_{1,1}^m) & \mathbf{K}_m^{1,2}(\mathbf{w}_{1,2}^m) \\ \mathbf{K}_m^{2,1}(\mathbf{w}_{2,1}^m) & \mathbf{K}_m^{2,2}(\mathbf{w}_{2,2}^m) \end{pmatrix} \quad (3)$$

with $\mathbf{w}_{ji}^m$ the convolutional kernels for input channel i and output channel j of the m-th convolution.

In accordance with conventional ResNet blocks, we pick $M = 2$. Based on the original implementation by Chen et al. (2018), G_{norm} is defined as group normalization (Wu & He, 2018). For generalized compatibility with neural ODEs and the adjoint method, we choose a non-linear activation function with a theoretically unique and bounded adjoint, namely continuously differentiable exponential linear units, or CELU (Barron, 2017). Similarly, we keep the linear dependence of the equations of motion on time (or network depth) t. Finally, we adapt the GPU implementation of ODE solvers[1] to solve the equations of motion for a predefined time interval $t \in [0, T]$ using the adaptive step size DOPRI method.

2.4 DEEP CONTINUOUS NETWORKS WITH SRFS AND NEURAL ODES

We formulate deep continuous networks (DCNs) by employing learnable, continuous SRF filter descriptions to define the weights in the evolution of a neural ODE. This means that for DCNs, each $\mathbf{w}_{ji}^m$ in Eq. 2 is a discretization of the continuous SRF filter $F_\alpha(x, y; \sigma)$ given in Eq. 1, sampled in $[-2\sigma, 2\sigma]$. α_{ji}^m and σ^m are trainable filter parameters, where $\sigma_{ji}^m = \sigma^m$ is shared between the filters in a convolutional layer unless stated otherwise. All our code is available at[2].

Network architecture and training. We construct DCNs by stacking ODE blocks separated by downsampling blocks (Figure 2). Each downsampling block is a sequence of normalization, non-linear activation and strided convolution. We use a convolutional layer for increasing the channel dimensionality at the input level and employ global average pooling and a fully connected layer at the output level. We train our networks using cross entropy loss and the CIFAR-10 dataset (Krizhevsky, 2009). (See Appendices A.2-A.3 for further details regarding training parameters.)

As a baseline without spatial continuity, we compare DCN performance to the ODE-Net introduced in Chen et al. (2018), where the convolutions within the ODE blocks are performed using discrete, pixel-based kernels, with $k \times k$ parameters. As a baseline without temporal continuity, we define the 'ResNet-blocks' model where the ODE blocks are replaced by generic, discrete ResNet blocks, comprising two convolutional layers and a skip connection, with comparable number of parameters to the ODE-Net. In the ResNet-SRF-blocks model, we provide the discrete-time and continuous-space baseline by replacing the $k \times k$ filter definition of ResNet-blocks with SRF definitions.

We test two versions of DCNs and ResNet-SRF-blocks to quantify the viability of SRF filters outside of the ODE blocks. In DCN-ODE and ResNet-SRF-blocks we use the SRF filters only within the ODE (ResNet) blocks, and for the remaining layers we use discrete kernels with the same hyperparameters as the baselines. In the second version, DCN-full (ResNet-SRF-full), we use spatially continuous kernels everywhere, including the downsampling layers.

Finally, we investigate the case where we drop scale sharing within a layer, and optimize the scale parameter σ_{ji}^m independently for each input channel i and output channel j, which we call DCN σ_{ji}.

---

[1]https://github.com/rtqichen/torchdiffeq/
[2]code will be made available at github

Meta-parametrization. DCNs enable us to parametrize the trainable filter parameters α and σ as a function of time t. This both enables the kernels to vary smoothly over time, and lets us define temporal dynamics for the neuronal responses in our network. We test the viability of such models by introducing DCN variants where σ and/or α are defined using linear or quadratic functions of t and learnable parameters a, b, c, a_s, b_s, a_α and b_α (Table 2).

3 EXPERIMENTAL ANALYSIS

3.1 CLASSIFICATION WITH PARAMETER REDUCTION

Similar to biological models, where analytical receptive fields limit the scope of the model using prior information, we find that DCNs are more parameter efficient compared to baseline networks. Evaluated on CIFAR-10, DCNs perform on par (within standard deviation) with baselines, despite using SRFs of a small basis order 2, which means each filter shape is defined by only 6 free parameters as opposed to 9 for the conventional 3×3 kernels (Table 1).

Similarly, we find that meta-parametrized DCN variants match the classification performance of baselines and may outperform DCNs with static weights (Table 3). This is an interesting finding since we test only a few models, with little hyperparameter optimization, which indicates that DCNs can potentially be used to parametrize the dependence of convolutional kernel weights on network depth, for further parameter reduction.

Figure 2: DCN model architecture with CIFAR-10 input images. Downsampling is performed via convolutions with stride 2. The convolutional kernel size k depends on the model, and is learned during training in DCNs. The equations of motion (Eq. 2) are solved within ODE blocks.

3.2 LINK WITH BIOLOGICAL MODELS

Scale fitting. As an advantage over conventional CNNs, it is possible to directly investigate the optimal receptive field (RF) size in each ODE block after training, since DCNs fit the RF scale σ explicitly. We observe an upward trend in the RF sizes with the depth of the convolutional layer within the network (Fig. 3a). This is in line with cortical RF sizes, which grow in downstream visual areas (Smith et al., 2001). In addition, we plot the distribution of learned σ_{ji} in different ODE blocks of the model DCN σ_{ji} (Fig. 3b). Note that the scale parameter σ controls the bandwidth of the SRF filters and is thus related to their spatial frequency response. We find that the σ_{ji} distributions after training are approximately log-normal and display a positive skew, which is consistent with the scale and spatial frequency tuning distributions in the primate visual system (Yu et al., 2010). We believe these results are promising for bridging the gap between deep learning and traditional models of biological systems.

Model	Continuity		Accuracy (%)	# Parameters
	Spatial	Temporal		
ResNet-blocks	✗	✗	89.01 ± 0.17	555K
ResNet-SRF-blocks	✓	✗	88.26 ± 0.03	426K
ResNet-SRF-full	✓	✗	89.32 ± 0.39	323K
ODE-Net (Chen et al., 2018)	✗	✓	89.60 ± 0.28	560K
DCN-ODE	✓	✓	89.46 ± 0.16	429K
DCN-full	✓	✓	89.18 ± 0.32	326K
DCN σ_{ji}	✓	✓	89.74 ± 0.30	472K

Table 1: CIFAR-10 validation accuracies of DCN models, averaged over 3 runs, compared to baseline models. DCNs perform on par with spatially and/or temporally discrete baselines, despite having a lower number of trainable parameters.

Model name	Parametrization
DCN $\sigma(t)$	$\sigma = 2^{at+b}$
DCN $\sigma(t^2)$	$\sigma = 2^{at^2+bt+c}$
DCN $\sigma(t), \alpha(t)$	$\sigma = 2^{a_s t+b_s}, \alpha = a_\alpha t + b_\alpha$

Table 2: Meta-parametrization of filter parameters σ and α as a function of time t in different DCN variants.

Model	Accuracy (%)
DCN $\sigma(t)$	89.97 ± 0.30
DCN $\sigma(t^2)$	89.93 ± 0.28
DCN $\sigma(t)$ and $\alpha(t)$	89.88 ± 0.25

Table 3: CIFAR-10 validation accuracies for DCN models with meta-parametrization are on par with baseline models.

(a)   (b)   (c)

Figure 3: (a) Learned σ values increase with depth within the network. (b) σ_{ji} distributions within the ODE blocks display a positive skew in line with biological observations. (c) CIFAR-10 validation accuracies on the pattern completion task with increasing mask size.

Pattern completion. Established models from computational neuroscience, with continuous temporal dynamics and well-defined recurrent interaction structures, such as the Ermentrout-Cowan model (Bressloff et al., 2001), or neural field models (Amari, 1977), display interesting high-level phenomena such as spontaneous pattern formation and travelling waves (Coombes, 2005). Such models employ local, distance-dependent interactions, similar to the SRF based ODE blocks in the DCN formulation. Based on this resemblance, we hypothesize that DCNs can perform well in the case of locally missing information in images, through pattern completion at the feature map level.

We test this hypothesis by masking $n \times n$ pixels on the CIFAR-10 validation set at test time. The masks have zero pixel values, and are placed at the center of the image. We find that when confronted with a small patch of missing information, DCNs can generate feature maps similar to those obtained from intact images. Specifically, we observe that the difference $D(t) = \frac{1}{A} \sum |\mathbf{h}^{\text{im}}(t) - \mathbf{h}^{\text{im\_masked}}(t)|$ between the feature maps generated by an intact image $\mathbf{h}^{\text{im}}(t)$ and a masked image $\mathbf{h}^{\text{im\_masked}}(t)$, normalized by the amplitude of the intact image A, is reduced within an ODE block (Figure 4a). In terms of the overall classification performance with masked images at test time, we find that DCNs are marginally more robust against zero-masking than baselines (Fig. 3c).

3.3 CONTRAST ROBUSTNESS AND COMPUTATIONAL EFFICIENCY

We observe that DCN and ODE-Net models are sensitive to changes in input contrast. This is not unexpected since ODE blocks compute the solution to the initial value problem posed by the equations of motion and the input feature maps, and contrast variations change the initial conditions. To quantify this sensitivity we vary the contrast c of the input images at test time, where for each image H_i in the CIFAR-10 validation set we define the input as $H_j = cH_i$. When naively changing the input contrast c this way, we find that the validation accuracy decays rapidly for both models (solid lines in Fig. 4b, top).

Empirically, we notice that, with the appropriate choice of normalization functions, the input contrast c has a direct effect on the time scales of the solution $\mathbf{h}(t)$. Based on this observation, we heuristically test whether scaling the integration time interval T (used during training) of ODE block 1 by c

Figure 4: (a) Pattern completion in the DCN feature maps for an example image. Feature maps are shown for a single channel in ODE block 1. We find that the difference $D(t)$ between the feature maps $\mathbf{h}^{\text{im}}(t)$ of an intact image and $\mathbf{h}^{\text{im\_masked}}(t)$ of a masked image is reduced as $t \to T$. Example feature maps from other models are provided in Appendix A.4. (b) Top: In terms of CIFAR-10 validation performance, DCNs are more robust than baseline ODE-Nets to changes in input contrast c at test time. Interestingly, the number of function evaluations (NFEs) in the first ODE block (middle) or the whole DCN network (bottom) can be reduced considerably by modulating c.

for each input image j, $T_j = cT$, can improve contrast robustness at test time. We find that with the scaled integration interval DCN validation accuracy is relatively robust against changes in contrast c, compared to naive baselines and ODE-Net, until $c << 1$ when time scales become too fast and the ODE solver becomes unstable for all models (dashed lines in Fig. 4b, top).

Interestingly, we observe a reduction in the number of function evaluations (NFEs) in ODE block 1 for $c < 1$ (Fig. 4b, middle). Furthermore, we show that as long as the error tolerance of the ODE blocks are not decreased, this effect can be exploited by scaling the input feature maps of all ODE blocks by c for significant computational savings. We find that decreasing c leads to considerable efficiency improvements, where total NFEs can be reduced from 102 to 60, (for $c = 1$ and 0.06), with less than 0.5% loss in accuracy (Fig. 4b, bottom).

4 RELATED WORK

Our proposed DCN networks are based on prior work on continuous filters and extends existing work on continuous time neural ODEs.

Spatially continuous filter representations. Structured filters have been traditionally used in computer vision for extracting image structure at multiple scales. N-jet filter basis is first introduced by Florack et al. (1996) based on previous work on Gaussian scale-spaces (Florack et al., 1992; Lindeberg, 2013). We use the N-jet basis in order to approximate convolutional filters, as they enable a spatially continuous representation with an explicit scale parameter σ.

Similar to the N-jet basis, a set of oriented multi-scale wavelets, called a steerable pyramid, is proposed by Simoncelli et al. (1992) and complex wavelets have been used by Bruna & Mallat (2013) and Mallat (2012) as part of scattering transforms. CNN filters based on linear combinations of Gabor wavelets are adopted by Luan et al. (2017), while Worrall et al. (2017) propose circular harmonics, as spatially continuous filter representations.

Similar to our approach, Shelhamer et al. (2019) combine free-form filters with Gaussian kernels, thus learning the filter resolution. Likewise, Xiong et al. (2020) learn filter sizes using Gaussian kernels optimized using variational inference. Here, we use the N-jet framework based on Gaussian derivatives as in Jacobsen et al. (2016), however our main motivation is retaining compatibility with biological models. Also, unlike Jacobsen et al. (2016) we learn the scale parameter σ during training.

Continuous time representations in deep networks. Along with work by Lu et al. (2018) and Ruthotto & Haber (2019), networks continuous in the temporal (or depth) dimension have been

proposed by Chen et al. (2018) under the name neural ordinary differential equations (ODEs). They propose ODE-Nets based on the ResNet formulation (He et al., 2016) for classification tasks, which is used as a baseline in this paper. In this work we focus mainly on an image classification task, however, there is extensive ongoing work on generative models and normalizing flows using the neural ODE continuous time interpretation (Salman et al., 2018; Grathwohl et al., 2019). We note that DCNs can be readily incorporated into continuous flow models, as well as other spatio-temporally continuous DNN interpretations based on partial differential equations (Ruthotto & Haber, 2019).

Even though the adjoint method described in Chen et al. (2018) offers considerable computational savings, especially in terms of memory, recent work has improved upon it both in terms of stability and computational efficiency (Dupont et al., 2019; Finlay et al., 2020). Likewise, the contrast robust formulation of DCNs, as well as the synergy between the $\mathcal{O}(1)$ memory complexity of the adjoint method and spatially separable SRF filters (the implementations of which may otherwise inflate the memory cost) provide potential computational benefits.

Other studies have suggested that, similar to our DCN variants where the filter definitions are independent of time, neural ODEs based on ResNet architectures with weight sharing can be interpreted as recurrent neural networks (Rousseau et al., 2019; Kim et al., 2016), which bridges the gap between deep learning, dynamical systems and the primate visual cortex (Massaroli et al., 2020; Liao & Poggio, 2016). Similar to these works, we capitalize on the parallels between neural ODEs and the dynamical systems approach of the computational models of recurrent, biological circuits in order to extend them to fully continuous networks, where not only the depth of the network is continuous but also the shape and spatial resolution of the filters are end-to-end trainable.

5 DISCUSSION

Here, we introduced DCNs: a CNN model that learns spatio-temporally continuous representations, consistent with biological models. We showed that DCN models can match baseline performance in an image classification task while using a smaller number of parameters. Similarly, we have proposed different methods of meta-parametrization of the convolutional filter as a function of time, which may not only be viable for network compression purposes, but also for modelling the temporal profiles of biological responses.

As a further link with biological models, we have demonstrated that the learned filter scale distributions in DCNs are compatible with experimental observations, which seems promising for the applicability of DCN models to future neuroscientific investigations regarding the emergence of RF sizes. In addition, we have presented the capability of DCNs to reduce errors in feature maps caused by masking, although DCN classification performance is still equally affected as the baselines. Finally, we have empirically shown an interesting interplay between the input contrast to ODE blocks and the time scales of the solutions, which can be capitalized on for computational savings.

However, one of the biggest limitations of DCNs is that they may become unstable during training. This is a combined problem of neural ODE models and scale fitting, which may lead to exploding filter sizes with larger learning rates. Especially for meta-parametrization, it would be advisable to clip either integration time or filter parameters within a reasonable range.

Nevertheless, we believe there are exciting future research opportunuties involving DCNs. A rigorous mathematical analysis of the nonlinear system of equations describing the ODE blocks is beyond the scope of this paper, however, neural ODE formulations provide interesting opportunuties for establishing a theoretical understanding of DNNs based on dynamical systems. The interplay of input contrast and integration time is one such observation which requires further investigation.

Similarly, DCNs offer interesting possibilities for biological modelling. The in-built smooth evolution of filters can be used, for example, to incorporate response dynamics such as synaptic depression or short-term potentiation. Likewise, the equations of motion can be modified to reflect axonal delays or generate oscillations.

In short, we believe by offering a link between dynamical systems, biological models and CNNs, DCNs display an interesting potential to bring together ideas from both fields.

REFERENCES

Duane G Albrecht, Wilson S Geisler, Robert A Frazor, and Alison M Crane. Visual cortex neurons of monkeys and cats: temporal dynamics of the contrast response function. *Journal of neurophysiology*, 88(2):888–913, 2002.

Shun-ichi Amari. Dynamics of pattern formation in lateral-inhibition type neural fields. *Biological cybernetics*, 27(2):77–87, 1977.

Alessandra Angelucci and Paul C Bressloff. Contribution of feedforward, lateral and feedback connections to the classical receptive field center and extra-classical receptive field surround of primate v1 neurons. *Progress in brain research*, 154:93–120, 2006.

Jonathan T Barron. Continuously differentiable exponential linear units. *CoRR*, 2017.

Eleanor Batty, Josh Merel, Nora Brackbill, Alexander Heitman, Alexander Sher, Alan Litke, EJ Chichilnisky, and Liam Paninski. Multilayer recurrent network models of primate retinal ganglion cell responses. *ICLR*, 2017.

Ute Bauer, Michael Scholz, Jonathan B Levitt, Klaus Obermayer, and Jennifer S Lund. A model for the depth-dependence of receptive field size and contrast sensitivity of cells in layer 4c of macaque striate cortex. *Vision research*, 39(3):613–629, 1999.

Rani Ben-Yishai, R Lev Bar-Or, and Haim Sompolinsky. Theory of orientation tuning in visual cortex. *Proceedings of the National Academy of Sciences*, 92(9):3844–3848, 1995.

Paul C Bressloff, Jack D Cowan, Martin Golubitsky, Peter J Thomas, and Matthew C Wiener. Geometric visual hallucinations, euclidean symmetry and the functional architecture of striate cortex. *Philosophical Transactions of the Royal Society of London. Series B: Biological Sciences*, 356 (1407):299–330, 2001.

Joan Bruna and Stéphane Mallat. Invariant scattering convolution networks. *TPAMI*, 35(8):1872–1886, 2013.

Santiago A Cadena, George H Denfield, Edgar Y Walker, Leon A Gatys, Andreas S Tolias, Matthias Bethge, and Alexander S Ecker. Deep convolutional models improve predictions of macaque v1 responses to natural images. *PLoS computational biology*, 15(4):e1006897, 2019.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. *NeurIPS*, 2018.

Stephen Coombes. Waves, bumps, and patterns in neural field theories. *Biological cybernetics*, 93 (2):91–108, 2005.

David Daniel Cox and Thomas Dean. Neural networks and neuroscience-inspired computer vision. *Current Biology*, 24(18):R921–R929, 2014.

Peter. Dayan and L. F. Abbott. *Theoretical neuroscience : computational and mathematical modeling of neural systems*. Massachusetts Institute of Technology Press, 1st edition, dec 2001. ISBN 0262041995.

Emilien Dupont, Arnaud Doucet, and Yee Whye Teh. Augmented neural odes. In *NeurIPS*, pp. 3140–3150, 2019.

Alexander S Ecker, Fabian H Sinz, Emmanouil Froudarakis, Paul G Fahey, Santiago A Cadena, Edgar Y Walker, Erick Cobos, Jacob Reimer, Andreas S Tolias, and Matthias Bethge. A rotation-equivariant convolutional neural network model of primary visual cortex. In *International Conference on Learning Representations*, 2019.

UA Ernst, KR Pawelzik, C Sahar-Pikielny, and MV Tsodyks. Intracortical origin of visual maps. *Nature neuroscience*, 4(4):431–436, 2001.

Chris Finlay, Jörn-Henrik Jacobsen, Levon Nurbekyan, and Adam M Oberman. How to train your neural ode. *arXiv preprint arXiv:2002.02798*, 2020.

Luc Florack, Bart Ter Haar Romeny, Max Viergever, and Jan Koenderink. The gaussian scale-space paradigm and the multiscale local jet. *IJCV*, 18(1):61–75, 1996.

Luc MJ Florack, Bart M ter Haar Romeny, Jan J Koenderink, and Max A Viergever. Scale and the differential structure of images. *Image and Vision Computing*, 10(6):376–388, 1992.

Robert A Frazor, Duane G Albrecht, Wilson S Geisler, and Alison M Crane. Visual cortex neurons of monkeys and cats: temporal dynamics of the spatial frequency response function. *Journal of Neurophysiology*, 91(6):2607–2627, 2004.

Will Grathwohl, Ricky T. Q. Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. *ICLR*, 2019.

Ben M Harvey and Serge O Dumoulin. The relationship between cortical magnification factor and population receptive field size in human visual cortex: constancies in cortical architecture. *Journal of Neuroscience*, 31(38):13604–13612, 2011.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.

Jorn-Henrik Jacobsen, Jan van Gemert, Zhongyu Lou, and Arnold WM Smeulders. Structured receptive fields in cnns. In *CVPR*, pp. 2610–2619, 2016.

Judson P Jones and Larry A Palmer. An evaluation of the two-dimensional gabor filter model of simple receptive fields in cat striate cortex. *Journal of neurophysiology*, 58(6):1233–1258, 1987.

Tim C Kietzmann, Patrick McClure, and Nikolaus Kriegeskorte. Deep neural networks in computational neuroscience. In *Oxford research encyclopedia of neuroscience*. 2019.

Jiwon Kim, Jung Kwon Lee, and Kyoung Mu Lee. Deeply-recursive convolutional network for image super-resolution. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1637–1645, 2016.

David Klindt, Alexander S Ecker, Thomas Euler, and Matthias Bethge. Neural system identification for large populations separating "what" and "where". In *Advances in Neural Information Processing Systems*, pp. 3506–3516, 2017.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, Department of Computer Science, 04 2009.

Zhaoping Li. A neural model of contour integration in the primary visual cortex. *Neural Computation*, 10(4):903–940, 1998.

Qianli Liao and Tomaso Poggio. Bridging the gaps between residual learning, recurrent neural networks and visual cortex. *arXiv preprint arXiv:1604.03640*, 2016.

Tony Lindeberg. Discrete derivative approximations with scale-space properties: A basis for low-level feature extraction. *Journal of Mathematical Imaging and Vision*, 3(4):349–376, 1993.

Tony Lindeberg. *Scale-space theory in computer vision*, volume 256. Springer Science & Business Media, 2013.

Tony Lindeberg and Luc Florack. *Foveal scale-space and the linear increase of receptive field size as a function of eccentricity*. KTH Royal Institute of Technology, 1994.

Jack Lindsey, Samuel A Ocko, Surya Ganguli, and Stephane Deny. A unified theory of early visual representations from retina to cortex through anatomically constrained deep cnns. In *International Conference on Learning Representations*, 2019.

David G Lowe. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60(2):91–110, 2004.

Yiping Lu, Aoxiao Zhong, Quanzheng Li, and Bin Dong. Beyond finite layer neural networks: Bridging deep architectures and numerical differential equations. In *International Conference on Machine Learning*, pp. 3276–3285. PMLR, 2018.

Shangzhen Luan, Baochang Zhang, Chen Chen, Xianbin Cao, Qixiang Ye, Jungong Han, and Jianzhuang Liu. Gabor Convolutional Networks. *CoRR*, 2017.

Stéphane Mallat. Group invariant scattering. *Communications on Pure and Applied Mathematics*, 65(10):1331–1398, 2012.

Stefano Massaroli, Michael Poli, Jinkyoo Park, Atsushi Yamashita, and Hajime Asama. Dissecting neural odes. *arXiv preprint arXiv:2002.08071*, 2020.

Blake A Richards, Timothy P Lillicrap, Philippe Beaudoin, Yoshua Bengio, Rafal Bogacz, Amelia Christensen, Claudia Clopath, Rui Ponte Costa, Archy de Berker, Surya Ganguli, Colleen J. Gillon, Danijar Hafner, Adam Kepecs, Nikolaus Kriegeskorte, Peter Latham, Grace W. Lindsay, Kenneth D. Miller, Richard Naud, Christopher C. Pack, Panayiota Poirazi, Pieter Roelfsema, João Sacramento, Andrew Saxe, Benjamin Scellier, Anna C. Schapiro, Walter Senn, Greg Wayne, Daniel Yamins, Friedemann Zenke, Joel Zylberberg, Denis Therien, and Konrad P. Kording. A deep learning framework for neuroscience. *Nature neuroscience*, 22(11):1761–1770, 2019.

François Rousseau, Lucas Drumetz, and Ronan Fablet. Residual networks as flows of diffeomorphisms. *Journal of Mathematical Imaging and Vision*, pp. 1–11, 2019.

Lars Ruthotto and Eldad Haber. Deep neural networks motivated by partial differential equations. *Journal of Mathematical Imaging and Vision*, pp. 1–13, 2019.

Hadi Salman, Payman Yadollahpour, Tom Fletcher, and Kayhan Batmanghelich. Deep diffeomorphic normalizing flows. *CoRR*, 2018.

Michael P Sceniak, Michael J Hawken, and Robert Shapley. Contrast-dependent changes in spatial frequency tuning of macaque v1 neurons: effects of a changing receptive field size. *Journal of Neurophysiology*, 88(3):1363–1373, 2002.

Terrence J Sejnowski. The unreasonable effectiveness of deep learning in artificial intelligence. *Proceedings of the National Academy of Sciences*, 2020.

Evan Shelhamer, Dequan Wang, and Trevor Darrell. Blurring the line between structure and learning to optimize and adapt receptive fields. *CoRR*, 2019.

Eero P Simoncelli, William T Freeman, Edward H Adelson, and David J Heeger. Shiftable multiscale transforms. *IEEE transactions on Information Theory*, 38(2):587–607, 1992.

Andrew T Smith, Krish Devi Singh, AL Williams, and Mark W Greenlee. Estimating receptive field size from fmri data in human striate and extrastriate visual cortex. *Cerebral cortex*, 11(12): 1182–1190, 2001.

David C Somers, Sacha B Nelson, and Mriganka Sur. An emergent model of orientation selectivity in cat visual cortical simple cells. *Journal of Neuroscience*, 15(8):5448–5465, 1995.

Ivan Sosnovik, Michał Szmaja, and Arnold Smeulders. Scale-equivariant steerable networks. *ICLR*, 2020.

Gert Van den Bergh, Bin Zhang, Lutgarde Arckens, and Yuzo M Chino. Receptive-field properties of v1 and v2 neurons in mice and macaque monkeys. *Journal of Comparative Neurology*, 518 (11):2051–2070, 2010.

Daniel E. Worrall, Stephan J. Garbin, Daniyar Turmukhambetov, and Gabriel J. Brostow. Harmonic networks: Deep translation and rotation equivariance. In *CVPR*, July 2017.

Yuxin Wu and Kaiming He. Group normalization. In *ECCV*, pp. 3–19, 2018.

Zhitong Xiong, Yuan Yuan, Nianhui Guo, and Qi Wang. Variational context-deformable convnets for indoor scene parsing. In *CVPR*, pp. 3992–4002, 2020.

Hsin-Hao Yu, Richa Verma, Yin Yang, Heath A Tibballs, Leo L Lui, David H Reser, and Marcello GP Rosa. Spatial and temporal frequency tuning in striate cortex: functional uniformity and specializations related to receptive field eccentricity. *European Journal of Neuroscience*, 31(6): 1043–1062, 2010.

A APPENDIX

A.1 GAUSSIAN MULTISCALE LOCAL N-JET

Based on the Schwartz theory of smooth test functions, the Gaussian scale-space paradigm states that the derivatives $L_{i_1 \ldots i_n}(\vec{x}; \sigma)$ of a function $L_0(\vec{x})$ with respect to the spatial variables x_i, with $i = 1 \ldots d$, and at scale σ is given by the convolution

$$L_{i_1 \ldots i_n}(\vec{x}; \sigma) = L_0 * \partial_{i_1 \ldots i_n} G(\vec{x}; \sigma) \tag{4}$$

where $\partial_{i_1 \ldots i_n}$ is the n-th order partial derivative and $G(\vec{x}; \sigma)$ is the normalized, isotropic Gaussian kernel with standard deviation $\sigma_i = \sigma$ and mean $\mu_i = 0$ (Florack et al., 1996). Note that $L_0(\vec{x})$ does not need to be a smooth function, and therefore the Gaussian scale-space paradigm can be applied to obtain local image derivatives in different scales, where $\vec{x}$ denote the spatial coordinates and σ can be interpreted as the coordinate in the scale dimension.

Next, we observe that the N-th order Taylor expansion of an image $L : \mathbb{R}^2 \to \mathbb{R}$ around a point (a, b) is given by

$$L(x, y) = \sum_{i=0}^{N} \sum_{j=0}^{N-i} \frac{(x-a)^i (y-b)^j}{i! j!} \frac{\partial^{i+j}}{\partial x^i \partial y^j} L(a, b) \tag{5}$$

where the partial derivatives of L with respect to x and y can be interpreted as $L_{1_1 \ldots 1_n}(x, y; \sigma_0)$ and $L_{2_1 \ldots 2_n}(x, y; \sigma_0)$ from equation 4 at some original scale σ_0. The local N-jets can be seen to be parametrized by the coefficients in this expansions. By definition, we consider the Taylor expansion coefficients to be covariant derivatives of the image $L(x, y; \sigma)$, which are independent of the local coordinate system, to reach the filter approximations given in equation 1, where the coefficients take the form $\alpha_{i,j}$.

In short, the multiscale local N-jet provides a natural decomposition of an image in a local neighborhood in the spatial and scale dimensions. Under convolution with $G(\vec{x}; \sigma)$, this decomposition provides a framework for defining convolutional filters in a CNN using N-th order Taylor polynomials. The SRF filters we use are based on this N-jet definition and allow us to learn the scale, spatial frequency and orientation of the filters during training, which are fundamental properties of biological receptive fields (Jones & Palmer, 1987; Lindeberg, 1993).

In addition, theoretically interesting properties originate from the Gaussian scale-space formulation of SRFs (Jacobsen et al., 2016). For example, the semi-group property of Gaussian scale-spaces indicates for a Gaussian derivative kernel $G^{i,j}(x, y; t)$ parametrized by the variance $t = \sigma^2$

$$G^{i,j}(x, y; t + t') = G^{i,j}(x, y; t) * G(x, y; t') \tag{6}$$

where the superscripts (i, j) denote the partial derivatives with respect to x and y. This means that a translation in scale dimension can be achieved through convolution with a simple (0-th order) Gaussian kernel.

Similarly, SRF filters based on Gaussian derivatives are steerable by the coefficients $a_{i,j}$. For example, a filter with orientation θ can be described using second order basis functions as

$$G_\theta^{2,0} = a_{2,0} G^{2,0} + a_{1,1} G^{1,1} + a_{0,2} G^{0,2} = \cos^2(\theta) G^{2,0} - 2\cos(\theta)\sin(\theta) G^{1,1} + \sin^2(\theta) G^{0,2}. \tag{7}$$

Finally, the set of Gaussian derivative basis functions $G^{i,j}(x, y; \sigma)$ are spatially separable

$$G^{i,j}(x, y; \sigma) = G^i(x; \sigma) G^j(y; \sigma) \tag{8}$$

which is useful for computational efficiency in numerical applications.

A.2 TRAINING PROCEDURE

The basic architecture of all our models is given in figure 2. Unless otherwise stated, in all models we use group normalization (Wu & He, 2018) with 32 groups in every layer as the normalization function. As the nonlinear activation, we use continuously differentiable exponential linear units (Barron, 2017), or CELU for DCN models. Based on the original ODE-Net implementation (Chen et al., 2018), for ODE-Net models and ResNet-block models, we use rectified linear units (ReLU). Likewise, when defining the integration time interval T, we stick to the original implementation, with $T = 1$ for ODE-Net models, whereas we use $T = 2$ for DCN models. Otherwise, all the hyperparameters are kept constant between models. For a brief overview of hyperparameter optimization, see appendix A.3.

All models are trained for 100 epochs on the standard CIFAR-10 training set (Krizhevsky, 2009) using cross-entropy loss. As data augmentation, we use random translations up to 4 pixels in each spatial dimension and random horizontal flips. Optimization is performed using SGD with a mini-batch size of 128, initial learning rate 10^{-1}, momentum 0.9, and a learning rate decay by a factor of 0.1 at epochs 40 and 70. For continuous time models based on neural ODEs, we use the adjoint method for backpropagating the losses and ODE solvers with error tolerance set to 10^{-3}.

For convolutional layers with pixel-based $k \times k$ filters, the weights are initialized using the standard Kaiming uniform initialization (He et al., 2015). For layers using SRF filters, the initial α values are randomly sampled from a normal distribution with mean 0 and standard deviation 0.1, and initial σ values are sampled from a normal distribution with mean 0 and standard deviation 2/3.

For meta-parametrized models the initial values for the learnable parameters follow normal distributions $\mathcal{N}(\mu, \sigma_{\mathcal{N}})$: $a \sim \mathcal{N}(0, 2/3)$, $b \sim \mathcal{N}(0, 0.1)$, for the DCN $\sigma(t)$ model; $a \sim \mathcal{N}(0, 2/3)$, $b \sim \mathcal{N}(0, 2/3)$, $c \sim \mathcal{N}(0, 0.1)$ for the DCN $\sigma(t^2)$ model; and $a_s \sim \mathcal{N}(0, 2/3)$, $b_s \sim \mathcal{N}(0, 0.1)$, $a_\alpha \sim \mathcal{N}(0, 0.1)$ and $b_\alpha \sim \mathcal{N}(0, 0.05)$ for the DCN $\sigma(t)$, $\alpha(t)$ model.

For all our models using SRF filters, except for the DCN σ_{ij} model, we use scale sharing within a convolutional layer such that $\sigma_{ij}^m = \sigma^m$ for all m. This makes the GPU implementation trivial, as all filters within a layer are sampled in the interval $[-2\sigma^m, 2\sigma^m]$, and hence the convolutional kernel sizes within a layer are uniform. However, for the DCN σ_{ij} model, a GPU implementation would be highly inefficient if we truncated the kernels at a fixed factor of σ_{ij}, independently for each input and output channel i, j. Therefore for the DCN σ_{ij} model we fix the kernel size at 7×7, but we still learn the shape and the scale (bandwidth) of the filters during training.

Even though the ODE solver takes the integration time interval $t \in [0, T]$ as an input argument (or $t \in [0, 2]$ in the case of all DCN models), the DOPRI algorithm may explore time points outside of this interval. In order to avoid numerical instability and memory issues in the meta-parametrized models, we scale down and clip the integration time t when passing it into the parameter definitions as $\sigma(\tau t_{\text{clip}})$ and $\alpha(\tau t_{\text{clip}})$. We clip the t values in the interval $[-0.5, 2.5]$ and use $\tau = 0.5$.

A.3 HYPERPARAMETER TUNING

As mentioned in appendix A.2, we share all the design choices and hyperparameters between all DCN and baseline ODE-Net models, except for the nonlinear activation function and integration time interval T.

This difference in design choices arises since for the ODE-Net baseline we stay faithful to the original ODE-Net implementation, where ReLU is the nonlinear activation function and $T = 1$, whereas for DCN models we use CELU as the activation function, due to its generalized compatibility with the adjoint method, and $T = 2$. In order to verify that our design choices do not provide an unfair advantage over the ODE-Net baseline, we run some control experiments, where we vary the activation function and T in the ODE-Net baseline.

We find that the change of activation functions or integration interval T do not provide a significant increase to the CIFAR-10 classification performance in the ODE-Net baseline (Table 4).

Model	Accuracy (%)
DCN-ODE	89.46 ± 0.16
ODE-Net (baseline)	89.60 ± 0.28
ODE-Net with $T = 2$	89.50 ± 0.07
ODE-Net with CELU	89.33 ± 0.16
ODE-Net with CELU and $T = 2$	89.25 ± 0.30

Table 4: CIFAR-10 validation accuracy (averaged over 3 runs) in the control experiments testing the effect of DCN model design choices on the baseline ODE-Net.

Figure 5: Feature map evolution within the first ODE block (or ResNet block) of different models.

A.4 PATTERN COMPLETION IN FEATURE MAPS

In figure 5, we show the feature map evolution within the first ODE block (or ResNet block) of different models with and without masking of some example input images. Size of the mask depicted here is 6×6 pixels and the example images were chosen so as to have the mask located close to the middle of the object. We picked some channels with visible mask-related artifacts in the input feature maps to the first ODE (ResNet) block. Since there is no feature map trajectory in the ResNet-blocks model, but only one input and one output feature map, the difference between the feature maps of the intact and masked image is plotted as a red line connecting the two points.