Plan To Predict: Learning an Uncertainty-Foreseeing Model for Model-Based Reinforcement Learning

Abstract

In Model-based Reinforcement Learning (MBRL), model learning is critical since an inaccurate model can bias policy learning via generating misleading samples. However, learning an accurate model can be difficult since the policy is continually updated and the induced distribution over visited states used for model learning shifts accordingly. Prior methods alleviate this issue by quantifying the uncertainty of model-generated samples. However, these methods only quantify the uncertainty passively after the samples were generated, rather than foreseeing the uncertainty before model trajectories fall into those highly uncertain regions. The resulting low-quality samples can induce unstable learning targets and hinder the optimization of the policy. Moreover, while being learned to minimize one-step prediction errors, the model is generally used to predict for multiple steps, leading to a mismatch between the objectives of model learning and model usage. To this end, we propose *Plan To Predict* (P2P), an MBRL framework that treats the model rollout process as a sequential decision making problem by reversely considering the model as a decision maker and the current policy as the dynamics. In this way, the model can quickly adapt to the current policy and foresee the multi-step future uncertainty when generating trajectories. Theoretically, we show that the performance of P2P can be guaranteed by approximately optimizing a lower bound of the true environment return. Empirical results demonstrate that P2P achieves state-of-the-art performance on several challenging benchmark tasks.

1 Introduction

Through learning an approximate dynamics of the environment and then using it to assist policy learning, Model-based Reinforcement Learning (MBRL) methods [Moerland et al., 2020] have been shown to be much more sample-efficient than model-free methods both theoretically and empirically [Nagabandi et al., 2018, Chua et al., 2018, Luo et al., 2019, Janner et al., 2019]. The learning of the model is critical for MBRL, since an inaccurate model can bias policy learning through generating misleading pseudo samples, which is also referred to as the model bias issue [Deisenroth and Rasmussen, 2011]. However, learning an accurate model can be difficult, since the update of the policy continually shifts the distribution over visited states, and due to lack of enough training data for the modified distribution, the model can suffer from overfitting and become inaccurate in regions where the updated policy is likely to visit. This issue is further aggravated when using expressive models like deep neural networks, which are inherently prone to overfitting.

Figure 1: (a) Intuition for an uncertainty-foreseeing model; (b) A specific maze task modified from the D4RL benchmark [Fu et al., 2020], where an ant falls from the sky and randomly lands on the two sides of a wall. The ant aims to reach the goal using shortest time (assuming that the goal cannot be seen from the sky).

Prior methods mitigate this issue by applying uncertainty quantification techniques, typically by using a bootstrapped model ensemble [Kurutach et al., 2018, Chua et al., 2018, Janner et al., 2019]. However, due to the lack of explicit considerations of the aforementioned policy shift issue, these methods can only quantify the uncertainty passively after the samples were generated, and thus fail to prevent the trajectories induced by the current policy from running into regions with high uncertainty. This incapability to avoid uncertain regions can result in low quality of the generated samples, which provides unstable learning targets and thus may hinder the learning of the policy. Moreover, the model in the existing methods is usually used to predict for multiple steps, while the model learning objective is commonly to minimize the one-step prediction errors. In other words, there exists an objective mismatch [Lambert et al., 2020] between model learning and model usage, which means that the policy optimization generally expects accurate multi-step trajectories (i.e., model usage), yet the model is only estimated to consider the accuracy of immediate predictions (i.e., model learning).

To gain a conceptual understanding of the above two motivations, consider the scenario in Figure 1(a): 1) The approximate model $\hat{P}$ of the true environment dynamics P predicts $\hat{P}(s_1|x_0) > 0, \hat{P}(s_1'|x_0) > 0$ and $\hat{P}(s|x_0) = 0, \forall s \notin \{s_1, s_1'\}$ at the state-action pair x_0; and 2) The policy is updated from π_{old} to π_{new} to exploit the regions with high values in the model, and the resulting distribution shift exposes the model's inaccuracy at s_1 to the current policy, leading to large expected prediction error in the next step, i.e., $\sum_{a'} \pi_{\text{new}}(a'|s_1)D\big(\hat{P}(\cdot|s_1, a'), P(\cdot|s_1, a')\big) >> \sum_{a'} \pi_{\text{new}}(a'|s_1')D\big(\hat{P}(\cdot|s_1', a'), P(\cdot|s_1', a')\big)$, where $D(\cdot, \cdot)$ is some distance metrics and the symbol $>>$ means significantly greater than. Now starting from x_0, under the updated policy π_{new}, predicting s_1 is likely to direct the trajectory into highly uncertain regions with spurious high values (e.g., the grey region in Figure 1(b)), and cause considerably larger error in the subsequent trajectory generation than that of predicting s_1'. In contrast, if the model can foresee this uncertainty through explicit considerations of the current policy, then it can learn to plan for future predictions and thus jump to s_1' more often to prevent the trajectory from falling into uncertain regions (e.g., the ant falls into the right hand side of the wall in Figure 1(b)). Therefore, to generate trajectories that have small accumulation errors, the model should be aware of the update of the policy and change its predicting "strategy" by taking into account the long-term effect of immediate predictions.

Inspired by the above intuition, we propose a new framework for MBRL, named *Plan To Predict* (P2P). Our core idea is to treat the model rollout process as a sequential decision making problem and learn the model by the corresponding algorithms, such as reinforcement learning and model predictive control. During the learning of the model, the current policy is fixed and serves as the environment dynamics, while at the same time the model becomes a decision maker and is penalized via the prediction errors at each step. Through actively interacting with the current policy and minimizing the accumulative prediction errors on the resulting state distribution, the model can quickly adapt

to the state distribution shift by considering the long-term effect of the immediate predictions, thus foreseeing the uncertainty of regions that model trajectories are likely to fall into. Such foresight of uncertainty enables the model to plan to predict for multiple steps, which improves the quality of the pseudo samples generated by the model and eventually benefits policy learning. Note that the typical treatment of minimizing one-step prediction errors regardless of the current policy is in fact a greedy optimization process, and thus can be viewed as a special case of P2P. Some prior works, such as [Nagabandi et al., 2018, Luo et al., 2019], adopt similar multi-step prediction loss to learn the model, yet these works simply compute the loss on trajectories collected by previous policies and can still suffer from severe distribution shift due to the lack of considerations of the policy update.

Theoretically, we prove that P2P approximately optimizes a lower bound of the true environment return. Different from prior works [Luo et al., 2019, Janner et al., 2019], our theoretical analysis does not scale up the step-wise prediction errors to their maximum over timesteps when considering the impact of model error on the return approximation, thus resulting in a tighter bound of the true return and also justifying the objective mismatch issue. Optimizing this bound not only provides a stronger guarantee for policy improvement, but also enables the model to quickly adapt to the current policy. Empirical results demonstrate that P2P outperforms the existing state-of-the-art methods on several challenging benchmark tasks. It also deserves to note that, due to the capability to avoid model error, P2P may be particularly suited for offline learning tasks, where incremental data collection is not allowed and thus the model error is harder to be corrected than in online settings, inducing an irreversible bias on policy learning. Therefore, we also provide an evaluation of P2P in offline learning settings in the experiments, and present an interpretative visualization on how the learning objective of P2P affects the model predictions.

2 Preliminaries and Notations

A discrete time Markov desision process (MDP) $\mathcal{M}$ is defined by tuple $(\mathcal{S}, \mathcal{A}, R, P, \rho_0, \gamma)$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ the action space, $R(s, a)$ a scalar reward function of $s \in \mathcal{S}$ and $a \in \mathcal{A}$, $P(s'|s, a) \in [0, 1]$ the transition dynamics which is assumed to be unknown, $\gamma \in [0, 1)$ the discount factor and ρ_0 the initial state distribution. A stochastic policy $\pi(a|s)$ maps states to a probability distribution over the action space. The expected return of π defined by $J(\pi) := \mathbb{E}_{\pi, P} \left[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t) \right]$ is the expectation of the sum of discounted rewards induced by π. Following the general setting of reinforcement learning, the goal is to search for an optimal policy that maximizes the expected return from the environment, i.e., $\arg \max_\pi J(\pi)$.

MBRL methods learn a model $\hat{P}$ to approximate the unknown dynamics P, and then use this model to aid policy learning. While the model can be utilized in various ways, this paper focuses on the usage of generating pseudo samples to enrich the dataset, which is one of the most common usages of the model. The expected return of π predicted by the model $\hat{P}$ is denoted as $J^{\hat{P}}(\pi) := \mathbb{E}_{\pi, \hat{P}} \left[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t) \right]$. In our analysis, the reward function is assumed to be available, [1] and the policy obtained in the last iteration is denoted as the data-collecting policy π_D,

3 The Plan To Predict (P2P) Framework

In this section, we present a detailed description of our proposed algorithmic framework for MBRL, i.e., *Plan To Predict* (P2P). In Section 3.1, the model rollout process is reformulated as a sequential decision making problem using the notion of MDP and then a meta-algorithm of the P2P framework is provided as a generic solution to this reformulated problem. In Section 3.2, theoretical results are provided to guarantee the performance of P2P. In Section 3.3, two practical algorithms are developed under the P2P framework by handling some practical issues.

---

[1]Note that this is a commonly used assumption since the sample complexity of learning the reward function with supervised learning is a lower order term compared to the one of learning the transition model [Gheshlaghi Azar et al., 2013].

Algorithm 1 Meta-Algorithm of the P2P Framework

1: Initialize the policy π and the approximate model $\hat{P}$;
2: Initialize empty dataset $\mathcal{D}$;
3: **for** each epoch **do**
4:    Collect data with π in real environment: $\mathcal{D} \leftarrow \mathcal{D} \cup \{(s_i, a_i, r_i, s'_i)\}_i$;
5:    Optimize $\hat{P}$ for multi-step prediction under the current policy π: $\hat{P} \leftarrow \arg\max_{\hat{P}'} J^\pi(\hat{P}')$
6:    Optimize π under $\hat{P}$: $\pi \leftarrow \arg\max_{\pi'} \hat{J}^{\hat{P}}(\pi')$
7: **end for**

3.1   The Overall Framework

We now define the *model MDP* to reformulate the model rollout problem and outline our overall algorithm design.

Definition 1. *The model MDP $\mathcal{M}_\pi$ is defined by tuple $(S^m, A^m, R^m, P^m, \gamma, \rho_0^m)$, where at timestep t, $s_t^m := (s_t, a_t) \in S^m, a_t^m := (r_{t+1}, s_{t+1}) \in A^m, R^m(s_t^m, a_t^m) := -\big(\hat{P}(s_{t+1}|s_t, a_t) - P(s_{t+1}|s_t, a_t)\big)^2, P^m(s_{t+1}^m|s_t^m, a_t^m) := \pi(a_{t+1}|s_{t+1})\hat{P}(s_{t+1}|s_t, a_t), \gamma$ is the discount factor , $\rho_0^m := \pi(a_0|s_0)\rho_0$, and ρ_0 is the initial state distribution of the true environment.*

In the model learning process of P2P, the roles played by the policy π and the model $\hat{P}$ are reversed: π is fixed to serve as the environment dynamics and $\hat{P}$, now as the decision maker, interacts with π and is updated to minimize the accumulative prediction error along the generated trajectories. Similar to the optimization of the policy, the objective of this learning process can be written as $\arg\max_{\hat{P}} J^\pi(\hat{P})$ where $J^\pi(\hat{P}) := \mathbb{E}[\sum_t \gamma^t R^m(s_t^m, a_t^m)]$. The overall algorithmic framework of P2P is depicted in Algorithm 1, where the main difference compared to most existing MBRL methods lies in Line 5, i.e., the learning of the model. Specifically, this process can be achieved in a similar way with policy learning, i.e., generating samples by actively interacting with the policy (now viewed as the background environment), and optimizing the expected return $J^\pi(\hat{P})$ accordingly. This optimization can in principle be done by any approaches solving sequential decision making problems. As two representatives of these approaches, *Model Predictive Control* (MPC) [Camacho and Alba, 2013] and *Reinforcement Learning* (RL) [Sutton and Barto, 2018] are both applied in our practical version of P2P, which are detailed in Section 3.3. In addition, one of the biggest gaps between this theoretical construction of the *model MDP* and the practical implementation may lie in the derivation of R^m. According to Definition 1, the true environment dynamics is required to compute this reward function, while in practice the true dynamics is not accessible in the model learning phase. Therefore, depending on which underlying approach (i.e., MPC or RL) is chosen for model optimization, we propose different alternative plans to approximate R^m in Section 3.3.

3.2   Theoretical Results

In general, MBRL methods learn an approximate model of the real world dynamics and learn the policy by maximizing the expected return predicted by the model. The better this pseudo return approximates the true environment return, the stronger guarantee the model can provide for policy improvement. Thus, a critical problem in theory is how to bound the gap between the expected return of the model and the true environment, i.e., $|J^{\hat{P}}(\pi) - J(\pi)|$. Suppose that this gap can be upper bounded by C, and the policy is updated from π_D to π with the expected model return improved by $2C$, then the policy improvement in terms of the true environment can be guaranteed:

$$J(\pi) - J(\pi_D) \geq \left(J^{\hat{P}}(\pi) - C\right) - \left(J^{\hat{P}}(\pi_D) + C\right)$$
$$\geq J^{\hat{P}}(\pi) - J^{\hat{P}}(\pi_D) - 2C \geq 0.$$

Our main theoretical result is the following theorem:

Theorem 1. *The gap between the expected return of the model and the environment is bounded as:*

$$\left| J(\pi) - J^{\hat{P}}(\pi) \right| \leq \frac{R_{max}}{(1-\gamma)} \left(4\epsilon_\pi + 2(1-\gamma)\sum_{t=1}^{\infty} \gamma^t \epsilon_t^m + \sum_{t=3}^{\infty} \gamma^t \epsilon_{t-1}^m \right), \tag{1}$$

where $\epsilon_\pi := \max_s D_{TV}(\pi_D(\cdot|s)\|\pi(\cdot|s))$ denotes the policy distribution shift, $\epsilon_t^m := \mathbb{E}_{s\sim\hat{P}_{t-1}(s;\pi)}\left[\max_a D_{TV}(\hat{P}(\cdot|s,a)\|P(\cdot|s,a))\right]$ denotes the upper bound of one-step model prediction error at timestep t of the model rollout trajectory, and $\hat{P}_{t-1}(s;\pi)$ denotes the state distribution at t under $\hat{P}$ and π.

Proof. Please refer to Appendix A. □

Transforming the inequality in Eq. (1) results in $J(\pi) \geq J^{\hat{P}}(\pi) - 2C(\hat{P}, \pi)$, where $C(\hat{P}, \pi)$ denotes the right hand side in Eq. (1). Thus in principle, monotonic policy improvement can be achieved by iteratively applying the following update rule:

$$\pi, \hat{P} \leftarrow \arg\max_{\pi,\hat{P}} J^{\hat{P}}(\pi) - 2C(\hat{P}, \pi). \tag{2}$$

The update rule in Eq. (2) is ideal and usually impractical since it involves an exhaustive search in the state and action space to compute C, and requires full-horizon rollouts in the model for estimating the accumulative model errors. Thus, similar to how algorithms like TRPO [Schulman et al., 2015] approximate their theoretically monotonic version, P2P approximates this update rule by maximizing the expected model return while keeping the accumulative model error small. As for the policy shift term ϵ_π, though the bound suggests that this term may also be constrained, we found empirically that it is sufficient to only control the model error. This may be explained by the relatively small scale of policy shift with respect to model error, as observed in [Janner et al., 2019].

It is worth noting that the accumulative error here is not simply summing up the multi-step errors on trajectories collected by any other policies as in [Nagabandi et al., 2018, Luo et al., 2019], because the definition of the step-wise model error (i.e., ϵ_t^m) in Theorem 1 involves a policy-dependent expectation over the state space, indicating that this error is also affected by the update of the policy. To enable quick adaptation to this policy update, P2P minimizes the accumulative error on the state distribution induced by an active interaction between the model and the current policy, and thus better approximates the accumulative error defined in Theorem 1.

Different from most of prior work [Luo et al., 2019, Janner et al., 2019], in Theorem 1 the step-wise model prediction errors are not scaled up to their maximum over timesteps (i.e., $\max_t \epsilon_t^m$), leading to a tighter error bound. As a result, this bound not only provides stronger guarantee for policy improvement, but also justifies the objective mismatch issue between the model learning and model usage from a theoretical perspective: Scaling up these error terms by such a potentially large magnitude yields a loose bound which leads to algorithms aiming at minimizing the upper bound of individual one-step prediction losses. However, to obtain better policy improvement, the tighter bound in Eq. (1) implies that a more fine-grained model learning process is desired, which considers consecutive rollout steps and minimizes the accumulative prediction error, i.e., $\sum_t \gamma^t \epsilon_t^m$. Using the notion of *model MDP* defined in Section 3.1, the model induced by minimizing one-step prediction errors can be intuitively interpreted as a greedy decision maker, which is often considered shortsighted and may easily lead to severe suboptimality.

3.3 Practical Implementation

In this subsection, we instantiate Algorithm 1 by specifying explicit approaches to learn the model and provides solutions to some practical issues. For brevity, when mentioning the model learning process in this subsection, we rename the policy π in the original MDP as the *policy-dynamics* and the approximate model $\hat{P}$ in the original MDP as the *model-policy*.

Figure 2: Comparisons against baselines on MuJoCo. Solid curves represent the mean of runs over 5 different random seeds, and shaded regions correspond to standard deviation among these runs.

P2P-MPC: Since the policy-dynamics π is accessible, one of the simplest yet effective ways to learn the model-policy can be the model predictive control (MPC) [Camacho and Alba, 2013], which utilizes the dynamics to plan and optimize for a sequence of actions. Given the state s_t^m at step t, the MPC controller first optimizes the sequence of actions $a_{t:t+H}^m$ over a finite horizon H, and then employs the first action of the optimal action sequence, i.e., $a_{H,t}^m := \arg\max_{a_{t:t+H}^m} \mathbb{E}_{\hat{P}} \sum_{t'=t}^{t+H-1} R^m(s_{t'}^m, a_{t'}^m)$. Computing the exact $\arg\max$ is computationally challenging due to the dimension of the state and action spaces, so we adopt the random-sampling shooting method [Rao, 2009] which generates random action sequences, executes them respectively, and chooses the one with highest return predicted by the dynamics. Besides, the reward R^m, which cannot be directly computed by definition, is approximated here using a neural network and trained on the environment dataset.

P2P-RL: It is well-known that though effective, RL methods often suffer from high sample complexity. Hence, the model-policy is trained on the environment dataset instead of the samples generated by the interaction of the model-policy and policy-dynamics. However, there are two issues to be addressed: 1) The policy-dynamics is highly non-stationary due to its continuing update; and 2) The decision maker which generates the dataset is the true environment rather than our model-policy. The first issue can be addressed by updating the next state in each sampled transitions by applying the current policy-dynamics, i.e., $s_{t+1}^m \leftarrow (s_{t+1}, \pi(s_{t+1}))$. As for the second issue, since the model-generated samples are not used in model learning, it can be seen approximately as an offline learning problem and thus can be addressed by well-developed offline RL methods [Fujimoto et al., 2019, Levine et al., 2020]. Due to the effectiveness and the implementational simplicity, we adopt SAC [Haarnoja et al., 2018] with behavior cloning as the underlying learning algorithm, which bears similarities to the TD3+BC approach proposed by [Fujimoto and Gu, 2021]. Besides, an approach called DualDICE [Nachum et al., 2019] is also applied to correct the estimation of the state distribution. Finally, since the samples come from the true environment, the reward R^m can be simply approximated by re-predicting the dynamics in the sampled transitions and computing the prediction errors for the current model-policy.

For the detailed description of how to approximate R^m, please refer to Appendix B.3. Besides, the pseudo code of P2P-MPC and P2P-RL can be found in Appendix E.

4 Experiments

In this section, we first evaluate the empirical performance of P2P on a set of MuJoCo continuous control tasks [Todorov et al., 2012] in Section 4.1, and then present an quantitative analysis for

Figure 3: Quantitative analysis of the accumulative model errors. While the true environment dynamics is not accessible during learning, the errors are approximated via supervised learning on the environment dataset.

the model error in Section 4.2. The ablation study provided in Section 4.3 verifies the necessity of an active policy-model interaction when computing the multi-step prediction loss. Besides, a key parameter of P2P-MPC is also studied in Section 4.3. Finally, to gain a deeper understanding of how P2P work in offline settings, a visualization of the model's rollout trajectories is shown in Section 4.4.

4.1 Comparisons with Baselines

We compare P2P against some state-of-the-art model-free and model-based methods. The model-free baseline is SAC [Haarnoja et al., 2018], which is the model-free counterpart of P2P. The model-based baselines include MBPO [Janner et al., 2019], which uses short-horizon rollouts branched from the state distribution of previous policies, SLBO [Luo et al., 2019], which enjoys theoretical performance guarantee and uses model rollouts from the initial state distribution, and STEVE [Buckman et al., 2018], which also generates short rollouts but uses model data for estimating target values instead of policy learning. Note that our framework only focuses on model learning and can be employed as a flexible plug-in component by most MBRL algorithms that generate pseudo samples to assist policy learning. In our experiments, we plug the model learning process of P2P into MBPO since it is a widely accepted strong baseline in MBRL. The implementational details and the hyperparameter settings of P2P, as well as the environment settings, are all described in Appendix B.

As shown in Figure 2, P2P-MPC significantly outperforms the baselines on several tasks, especially on Hopper, Humanoid and Ant, which are generally considered to be the most challenging MuJoCo tasks. In Walker2d, the best rollout length is one step in our implementation and MBPO, thus resulting in similar performance between these two methods. Compared to P2P-MPC, the performance of P2P-RL is less stable. Through an investigation on the model learning process (see Appendix C), we find that P2P-RL sometimes struggles to balance the loss of behavior cloning and RL, leading to the difficulty in hyperparameter tuning and the instability of learning network parameters, while the optimization of P2P-MPC is non-parametric and thus does not suffer from this issue.

4.2 Model Error Analysis

The theoretical result presented in Section 3.2 implies that to guarantee better policy improvement, the model should learn to minimize the accumulative errors along the trajectories induced by the current policy and the model. Since P2P is designed based on this principle, the empirical results in Figure 2 verify the theoretical result in terms of the final performance. To further verify the effectiveness of this algorithmic design, we study the accumulative prediction error on three tasks that require rollouts with relative long horizons, i.e., Hopper, Ant and Humanoid. The results shown in Figure 3 together with Figure 2 strongly support our theoretical claims by demonstrating that the algorithm inducing less accumulative error achieves better performance. Besides, we can also observe that in Hopper the model errors of P2P-MPC in the first few steps are slightly larger than the other two methods. Nevertheless, as the rollout trajectory goes longer, the accumulative error induced by P2P-MPC grows significantly slower than the other methods. This further agrees with the intuition mentioned in Figure 1 by showing that P2P is able to trade the one-step model error for accumulative model error by considering the long-term effect of the immediate prediction.

4.3 Ablation Study

Figure 4: Results comparing performances induced by two ways of computing the multi-step prediction loss. The yellow curves represent the performance of P2P-MPC, which minimizes the multi-step loss on the trajectories generated by active interactions between the model and the current policy. The blue curves show the results of an ablation version of MBPO where the original one-step loss is replaced by a multi-step loss computed over the trajectories sampled from the environment dataset. The lengths of these trajectories are set to the same in this comparison.

Figure 5: Results comparing performances induced by different planning horizons of the model in P2P-MPC.

Multi-Step Prediction Loss In Section 3.2, we emphasize that the loss of P2P is essentially different from the multi-step prediction loss used in prior work, since P2P computes the multi-step loss on the state distribution induced from an active interaction between the model and the current policy, and on the contrary, prior work computes this loss on the trajectories collected by previous policies. The empirical results in Figure 4 compare the performances induced by these two kind of losses and highlight the importance of the interactive model learning process in P2P.

Planning Horizon Different from most RL methods, MPC methods can assign an explicit horizon for planning, hence P2P-MPC is able to set the planning horizon of the model to be exactly the same with the rollout horizon. This difference may partially explain the superior performance of P2P-MPC against P2P-RL. Nevertheless, longer planning horizon incurs higher computational cost, especially in tasks with high-dimensional state spaces. To trade-off the performance and the computational cost, our solution is to simply limit the planning horizon, and the empirical results shown in Figure 5 suggests that a horizon of 6 is satisfactory for the tasks experimented.

4.4 An Interpretative Experiment

To gain an intuitive understanding of how the learning objective of P2P affects the model predictions, here we present a visualization of the rollout trajectories in maze2d-medium-v1, an offline learning task in the D4RL benchmark [Fu et al., 2020]. As shown in Figure 6, the environment is slightly modified by lengthening the wall at the middle of the maze and fixing the goal to the top right corner. Besides, the number of offline samples that involve the grey region are partially discarded to increase this region's uncertainty. Figure 6 shows the top four trajectories that are most frequently generated from a fixed starting point using our methods and MOPO [Yu et al., 2020], a well-known offline model-based RL method that uses one-step error for model learning. The visualization clearly demonstrates the different rollout preferences of the two kinds of models: the model of P2P-MPC tends to generate trajectories heading to the regions with low uncertainty, while the model of MOPO fails to prevent the trajectories from being absorbed into the highly uncertain region. The

Figure 6: Visualization of models' rollout trajectories. The blue trajectories are generated by MOPO, while the yellow ones are generated by P2P-MPC.

Figure 7: Accumulative prediction error along the rollout trajectories on maze2d-medium-v1.

Environment	P2P-MPC	MOPO
maze2d-medium-v1	230.2 ± 39.5	174.2 ± 32.4
maze2d-large-v1	8.1 ± 1.1	0.8 ± 0.0

Table 1: Comparison with MOPO on two maze tasks.

resulting accumulative model errors are quantified in Figure 7, and as shown in
Table 1, the final performance of the induced policy of P2P-MPC is significantly
better than MOPO. Note that in online settings, the model error is possible to be
corrected by the newly collected data from the environment, while in offline settings this incremental
data-collecting process is not allowed. Thus, the model error can have a more detrimental effect on
policy learning, which may severely degrade the asymptotic performance as evidenced in Table 1.
Additional results on a much harder task (i.e., maze2d-large-v1) are also provided in Table 1 to further
verifies the effectiveness of P2P-MPC.

5 Conclusion and Future Work

In this paper, we propose an MBRL framework named Plan to Predict (P2P), which novelly treats the
model rollout process as a sequential decision making problem. In this problem reformulation, the
roles played by the model and the policy are reversed, where the model becomes a decision maker
and the policy instead serves as the outer environment. Through an active interaction between the
model and the current policy, the model can minimize the multi-step accumulative errors on the
induced trajectories and thus quickly adapt to the state distribution of the current policy. We provide
theoretical guarantee for P2P, which also clarifies the difference of our multi-step loss from prior
methods and justifies the mismatch of objectives between model learning and model usage. Empirical
results on several challenging benchmark tasks verify the effectiveness of P2P. Moreover, observing
that the capability to avoid model error makes P2P promising for offline settings, we also provide
preliminary results on some offline learning tasks. While this is not the major focus of this paper,
studying how P2P can be applied in offline tasks more properly is left as an important future work.

References

Thomas M Moerland, Joost Broekens, and Catholijn M Jonker. Model-based reinforcement learning:
A survey. *arXiv preprint arXiv:2006.16712*, 2020.

Anusha Nagabandi, Gregory Kahn, Ronald S Fearing, and Sergey Levine. Neural network dynamics for model-based deep reinforcement learning with model-free fine-tuning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7559–7566. IEEE, 2018.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. *Advances in neural information processing systems*, 31, 2018.

Yuping Luo, Huazhe Xu, Yuanzhi Li, Yuandong Tian, Trevor Darrell, and Tengyu Ma. Algorithmic framework for model-based deep reinforcement learning with theoretical guarantees. In *ICLR (Poster)*, 2019.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. *Advances in Neural Information Processing Systems*, 32, 2019.

Marc Deisenroth and Carl E Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *Proceedings of the 28th International Conference on machine learning (ICML-11)*, pages 465–472. Citeseer, 2011.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

Thanard Kurutach, Ignasi Clavera, Yan Duan, Aviv Tamar, and Pieter Abbeel. Model-ensemble trust-region policy optimization. *arXiv preprint arXiv:1802.10592*, 2018.

Nathan Lambert, Brandon Amos, Omry Yadan, and Roberto Calandra. Objective mismatch in model-based reinforcement learning. *arXiv preprint arXiv:2002.04523*, 2020.

Mohammad Gheshlaghi Azar, Rémi Munos, and Hilbert J Kappen. Minimax pac bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3): 325–349, 2013.

Eduardo F Camacho and Carlos Bordons Alba. *Model predictive control*. Springer science & business media, 2013.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pages 1889–1897. PMLR, 2015.

Anil V Rao. A survey of numerical methods for optimal control. *Advances in the Astronautical Sciences*, 135(1):497–528, 2009.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, pages 2052–2062. PMLR, 2019.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. *Advances in Neural Information Processing Systems*, 34, 2021.

Ofir Nachum, Yinlam Chow, Bo Dai, and Lihong Li. Dualdice: Behavior-agnostic estimation of discounted stationary distribution corrections. *Advances in Neural Information Processing Systems*, 32, 2019.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ international conference on intelligent robots and systems*, pages 5026–5033. IEEE, 2012.

Jacob Buckman, Danijar Hafner, George Tucker, Eugene Brevdo, and Honglak Lee. Sample-efficient reinforcement learning with stochastic ensemble value expansion. *Advances in neural information processing systems*, 31, 2018.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Y Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. Mopo: Model-based offline policy optimization. *Advances in Neural Information Processing Systems*, 33:14129–14142, 2020.