MORE SPACE IS ALL YOU NEED: REVISITING MOLECULAR REPRESENTATION LEARNING

ABSTRACT

Molecular representation learning (MRL) has become pivotal in leveraging limited supervised data for applications such as drug discovery and material design. While early MRL methods relied on 1D sequences and 2D graphs, recent advancements have incorporated 3D conformational information, focusing predominantly on atomic interactions within 3D space. However, we argue that the space beyond atoms is also crucial for MRL, which is overlooked by prior models. To address this, we propose a novel transformer-based framework, dubbed Space-Former, which incorporates additional 3D space beyond atoms to enhance molecular representation ability. SpaceFormer introduces three key components: (1) Precision-Preserved Gridding, which discretizes continuous 3D space into grid cells while preserving precision; (2) Grid Sampling, which employs an importance sampling strategy to improve efficiency; and (3) Linear-Complexity 3D Positional Encoding, which extends Rotary Positional Encoding to 3D space to capture pairwise directions and utilizes random Fourier features to efficiently encode pairwise distances. Extensive experiments show that SpaceFormer significantly outperforms previous 3D MRL models across various tasks, validating the benefit of leveraging the additional 3D space beyond atoms in MRL models.

1 INTRODUCTION

Molecular representation learning (MRL), or molecular pretraining, has been a key area of research for its crucial role in utilizing limited supervised data, particularly in real-world applications such as drug design and material discovery (Gilmer et al., 2017; Rong et al., 2020). The evolution of this field has progressed from 1D sequences (Xu et al., 2017; Wang et al., 2019; Heller et al., 2015) and 2D graphs (Hu et al., 2019; Rong et al., 2020; Li et al., 2021; Wang et al., 2022b) to 3D conformations (Stärk et al., 2022; Zhou et al., 2023), incorporating increasingly rich physical information and achieving superior performance. In all these prior 3D MRL models, atoms play a central role. More specifically, these models take the types and 3D positions of *atoms* (or *atom tuples*) as inputs and focus on modeling atomic interactions within 3D space, using graph neural networks or transformers (Zhou et al., 2023; Feng et al., 2023; Wang et al., 2023; Cui et al., 2024; Yang et al., 2024).

While this atom-based MRL approach appears straightforward, we argue that it has an inherent limitation: *it ignores the spaces beyond atoms*. While it might seem intuitive to assume that these empty spaces contain no valuable information and are therefore less relevant, this assumption may overlook significant physical facts. In the theory of microscopic physics, the space beyond atoms is not truly empty; it is occupied by electrons, various electromagnetic fields, and quantum phenomena (Atkins & Friedman, 2011; Zee, 2010; Weinberg, 1995). Moreover, in many computational simulation methods used in physics, it is essential to consider the entire 3D space, not just the positions of atoms. For instance, electronic density distributions and potential fields are all functions of the entire 3D space (Atkins & Friedman, 2011; Parr et al., 1979; Szabo & Ostlund, 2012).

This fact inspires us to ask the following question:

Will leveraging the 3D space beyond atoms improve molecular representation learning?

In this paper, we provide an affirmative answer to the above question by introducing a novel transformer-based MRL framework called SpaceFormer, illustrated in Fig. 1. Unlike previous 3D MRL approaches that focus solely on atomic positions, SpaceFormer incorporates the space beyond atoms. To achieve this, SpaceFormer features three key components for efficient and effective 3D space processing:

Figure 1: Overview of the SpaceFormer framework. This figure illustrates the model using a 2D plane for simplicity, while SpaceFormer actually operates in 3D space. Unlike previous 3D MRL models that focus solely on atomic positions, SpaceFormer integrates the space beyond atoms. It begins by discretizing the 3D cuboid around the molecules into grid cells. To enhance efficiency, a grid sampling strategy is applied to reduce the number of input cells. Despite the discretization, precise atomic positions are retained by incorporating in-cell positions as additional input features. Moreover, SpaceFormer utilizes 3D Directional Positional Encoding with RoPE (3D Directional PE with RoPE) and 3D Distance Positional Encoding with Random Fourier Features (3D Distance PE with RFF) to effectively encode pairwise positional relationships in 3D space.

1. *Precision-Preserved Gridding*: To efficiently process the continuous 3D space, we discretize it into a grid composed of two types of cells: atom cells and non-atom cells. To mitigate the precision loss associated with discretization, in-cell positions are additionally utilized for atom cells.

2. *Grid Sampling*. Even with grid discretization, the entire grid remains too large for efficient processing. To address this, we propose an importance sampling strategy for non-atom cells, which enhances efficiency without compromising accuracy.

3. *Linear-Complexity 3D Positional Encoding*: We extend Rotary Positional Encoding (RoPE) (Su et al., 2024) to 3D continuous space to efficiently capture pairwise directional information. Additionally, we use random Fourier features to approximate Gaussian kernels (Rahimi & Recht, 2007) on pairwise distances, enabling efficient encoding of radial distance information.

With these three key components, SpaceFormer efficiently and effectively processes discretized grid cells. Extensive experiments demonstrate its superior performance compared to previous 3D MRL models across a variety of downstream tasks. Ablation studies further validate that each component plays a critical role in enhancing SpaceFormer's performance and efficiency. Additionally, we extend the Uni-Mol (Zhou et al., 2023) baseline by incorporating empty points, revealing that empty space can also benefit atom-based models. However, compared to SpaceFormer, the performance gains are significantly smaller, and Uni-Mol struggles with the efficient handling of large number of empty points. Together, these findings underscore the effectiveness of leveraging 3D space beyond atomic positions and highlight the superior performance of the proposed SpaceFormer.

2 RELATED WORK

Molecular Representation Learning Molecular representation learning has explored various modalities, resulting in diverse methods utilizing different molecular information. Some approaches use 1D sequences, such as SMILES-BERT (Wang et al., 2019) and Xu et al. (2017). Others focus on 2D topologies; for example, MolCLR (Wang et al., 2022b), MolGNet (Li et al., 2021), Hu et al. (2019), GROVER (Rong et al., 2020). Some works further improve 2D MRL models addi-

tionally with 3D information, such as GEM (Fang et al., 2022), 3D-Infomax (Stärk et al., 2022), MoleBLEND (Yu et al., 2024), GraphMVP (Liu et al., 2021) and Transformer-M (Luo et al., 2022).

Recently, starting with Noisy Nodes (Zaidi et al., 2022) and Uni-Mol (Zhou et al., 2023), pure 3D MRL models have demonstrated superior performance across various tasks. Building on their success, recent works (Feng et al., 2023; Wang et al., 2023; Cui et al., 2024; Yang et al., 2024) have further explored the potential of 3D MRL models. While most of these efforts focus on designing new pre-training tasks based on 3D atomic positions, SpaceFormer takes a different approach by leveraging the additional empty space beyond atoms.

Apart from 3D MRL, several other domains also focus on 3D conformations, such as deep potential models (Schütt et al., 2017; Thomas et al., 2018; Gasteiger et al., 2020; 2021; Liu et al., 2022; Wang et al., 2022a; Jiao et al., 2023), protein folding (Jumper et al., 2021; Abramson et al., 2024), and 3D conformation generation (Shi et al., 2021; Zhu et al., 2022b; Xu et al., 2022; 2021). However, these works are less directly related to this paper.

Enhancing Model Performance with Additional Tokens Though counterintuitive, the use of seemingly meaningless additional tokens has been shown to improve model performance in both language and vision tasks. For instance, Darcet et al. (2023) introduced register tokens into the input sequence of vision transformers, helping to mitigate artifacts and enhance performance across multiple tasks. Similarly, Pfau et al. (2024) demonstrated that using dot tokens ("...") as chain-of-thought prompts can boost large language model performance.

The concept of leveraging empty space in SpaceFormer is related to these methods but is grounded in physical principles. In particular, unlike the repeated, seemingly meaningless tokens in (Darcet et al., 2023) and (Pfau et al., 2024), SpaceFormer incorporates empty cells (non-atom cells) with distinct 3D positions, reflecting the true physical distribution of 3D space.

Virtual Points As Intermediate Representation In the domain of point cloud, virtual points have been proposed as intermediate representations. For example, Wu et al. (2023); Yin et al. (2021) convert 2D camera images into 3D virtual points, which are then fused with 3D LiDAR points to create a unified input representation. Similarly, Zhu et al. (2022a) introduce sparse virtual points to align and fuse features from 2D camera images and 3D LiDAR data, effectively addressing the resolution disparity between the sensors. Numerous studies (Song et al., 2023a;b; Mahmoud et al., 2023) have further advanced this direction, utilizing virtual points as a bridge to align and fuse data from heterogeneous sensors. In contrast, molecular representation learning (MRL) tasks primarily focus on predicting molecular properties, where intermediate representations for merging heterogeneous data sources are not inherently required. Our study in Sec.4.4 demonstrates that simply adding virtual points to existing atom-based MRL models provides limited performance improvement. The contribution of SpaceFormer lies in identifying this gap and proposing a framework that effectively leverages empty space information, addressing an overlooked aspect of MRL.

3 SPACEFORMER

To evaluate whether incorporating the 3D space beyond atoms enhances molecular representation learning (MRL), we present SpaceFormer, a novel transformer-based MRL framework that expands beyond atomic positions. The primary challenge in this approach lies in achieving efficient implementation, since the 3D space contains an infinite number of points. To address the challenge, a common solution is grid discretization, which divides the space into discrete cells, allowing the model to process only this finite number of cells. However, this solution suffers from several drawbacks. First, even with coarse discretization, the number of cells grows cubically, which may hinder the efficiency of model training. Second, discretization can lead to a loss of precision, particularly when encoding precise atomic positions, which may negatively impact model performance.

To address these challenges, SpaceFormer incorporates 3 key components to enhance both efficiency and performance, as described below.

3.1 PRECISION-PRESERVED GRIDDING

In this subsection, we describe the details of grid discretization used in SpaceFormer, focusing on three key aspects.

The Effective Cuboid for Gridding. We aim to ensure the cuboid fully encompasses the entire molecule while minimizing its volume as much as possible. To achieve this, we apply Principal Component Analysis (PCA) to the atomic positions to compute the three orthogonal axes according to the eigenvectors, forming a right-handed, normalized coordinate system. The atomic coordinates are then transformed into this new system, and the cuboid is defined by the circumscribed rectangular cuboid of the atoms.

The Edge Length of Grid Cells. To simplify processing, we ensure that each grid cell contains at most one atom, by setting a sufficiently small cell edge length. Specifically, the cell edge length c_l must satisfy $c_l < \frac{\hat{d}}{\sqrt{3}}$, where $\hat{d}$ represents the minimum Gaussian distance between any pair of atoms. Given that this paper primarily focuses on small organic molecules, $\hat{d}$ is approximately 0.96Å corresponding to the O-H bond length.

Preserving Atomic Precise Positions after Gridding. Since each grid cell contains at most one atom, the cells can be categorized as either atom cells or non-atom cells. For a non-atom cell, the *cell center* represents its 3D position, while for an atom cell, the *precise positions of the atoms* are used to define the 3D position. In both cases, let $\boldsymbol{c}_i \in \mathbb{R}^3$ denote the 3D position of the i-th cell, where $\boldsymbol{c}_i$ represents the cell center for non-atom cells, and the precise atomic position for atom cells.

This position $\boldsymbol{c}_i$ is used in two ways. First, it is used in global 3D positional encoding, which is detailed in Sec. 3.3. Second, it is used to compute in-cell positional features, which along with the cell type will serve as input to the SpaceFormer. Formally, the input feature for the i-th cell is defined as $\boldsymbol{a}_i = \{t_i, \boldsymbol{e}_i^0, \boldsymbol{e}_i^1, \boldsymbol{e}_i^2\}$, where $t_i, \boldsymbol{e}_i^0, \boldsymbol{e}_i^1, \boldsymbol{e}_i^2 \in \mathbb{N}$ represent the cell type and the in-cell positions along the three axes, respectively. The cell type t_i corresponds to the atom type for atom cells, and a special type t_{null} for non-atom cells. The in-cell position $\boldsymbol{e}_i$ is calculated and discretized from position $\boldsymbol{c}_i$, by $\boldsymbol{e}_i = \left\lfloor \frac{\boldsymbol{c}_i \bmod c_l}{c_m} \right\rfloor$, where c_l is the cell edge length and c_m is the hyper-parameter for discretization, which is set to a very small value. As a result, each $\boldsymbol{e}_i$ is an integer value ranging from 0 to $\frac{c_l}{c_m}$. Finally, we convert the discrete input features $\boldsymbol{a}_i$ into continuous feature representations by summing the corresponding embedding layers, denoted as $\boldsymbol{x}_i = \sum_{t=0}^{3} \text{Embed}_t(\boldsymbol{a}_i^t)$, where $\text{Embed}_t(\cdot)$ represents the embedding function that maps discrete inputs to continuous representations, and $\boldsymbol{x}_i$ is the resulting input embedding for the i-th cell.

To summarize, by leveraging the above approaches, SpaceFormer achieves efficient grid discretization while preserving atomic precision.

3.2 Grid Sampling

Despite the efficient grid discretization described above, the number of grid cells remains too large for effective processing. For instance, in widely used organic molecule datasets like ZINC (Sterling & Irwin, 2015), the average number of cells is approximately 6,000, which makes the $\mathcal{O}(n^2)$ complexity of vanilla transformer models both computationally expensive and memory intensive. To address this challenge, we incorporate FlashAttention (Dao et al., 2022), which avoids the $\mathcal{O}(n^2)$ peak memory cost of vanilla attention, allowing for more efficient handling of larger number of cells. Additionally, we propose a sampling strategy to drastically reduce the number of non-atom cells.

Specifically, in microscopic physics, regions close to atoms exhibit higher electron density, with the density varying significantly within these regions. Consequently, computational simulations often apply fine-graining to regions near atoms to capture these dynamic variations more accurately, while coarse-graining is commonly used in regions farther from atoms to reduce computational cost. Inspired by this approach, we propose a sampling strategy based on the distance to atom cells.

Formally, for the i-th non-atom cell, its sampling probability is calculated as follows:

$$d_i = \min_j \left(\{ \|\boldsymbol{c}_i - \boldsymbol{c}_j\|_2 \mid j \in \mathcal{S}_{\text{atom}} \} \right), \ i \in \mathcal{S}_{\text{non\_atom}},$$

$$p_i = \frac{\exp(-d_i/\tau)}{\sum_{k \in \mathcal{S}_{\text{non\_atom}}} \exp(-d_k/\tau)}, \tag{1}$$

where $\tau > 0$ is the temperature for sampling, $\mathcal{S}_{\text{atom}}$ is the set of atom cells, and $\mathcal{S}_{\text{non\_atom}}$ is the set of non-atom cells. Based on the sampling probability p_i, we sample $m \times 100\%$ of the non-atom cells, where $m \in [0, 1]$ is a pre-defined hyper-parameter. We also perform extensive ablation studies on this sampling strategy in Sec. 4.

3.3 Linear-Complexity 3D Positional Encoding

Positional encoding is critical in both transformer-based models and 3D MRL models. However, existing methods from these models cannot be directly applied to SpaceFormer. First, the default positional encoding in transformers is typically discrete, such as sequence order in language models, while the cell positions c_i in SpaceFormer are continuous. Second, in 3D MRL models, SE(3)-invariant positional encoding (Zhou et al., 2023), often based on pairwise Gaussian distances, can be effective but are computationally inefficient because it has a memory cost of $\mathcal{O}(n^2)$ and is impractical for handling large number of grid cells.

To address these challenges, we propose an efficient positional encoding method tailored to continuous 3D coordinates by focusing on encoding pairwise positional information of grid cells. Given two 3D points, A and B, with coordinates c_A and c_B, respectively, their pairwise positional information is represented as $\vec{AB} = c_B - c_A$. Based on this, we propose two linear-complexity 3D positional encodings: the first directly encodes $\vec{AB}$, capturing directional information through raw positional deltas and retaining dependency on the coordinate system; the second encodes the pairwise distance $\|\vec{AB}\|_2$, which is invariant to the coordinate system.

3D Directional Positional Encoding with RoPE In transformer models, several types of positional encodings are commonly used (Vaswani, 2017; Dufter et al., 2022). Recently, Rotary Positional Encoding (RoPE) has become the default due to its linear-complexity in encoding relative positions. In SpaceFormer, we extend RoPE to 3D continuous space to encode directional information ($\vec{AB}$), capturing pairwise directional relationships across all three axes among cell positions.

The key idea behind RoPE is to apply a set of 2D rotation matrices to the Query and Key in the attention module, with angles dependent on positions. After performing the Query-Key dot product, the relative position between them is encoded. Formally, for an attention head with hidden dimension d_h, the i-th Query vector $q_i \in \mathbb{R}^{d_h}$ is split into $d_h/2$ tensors of length 2, with $q_{i,l} \in \mathbb{R}^2$ representing the l-th tensor. Similarly, $k_{j,l} \in \mathbb{R}^2$ represents the l-th tensor of the j-th Key. Then, during the dot product in the attention module, we compute:

$$q_{i,l} R_l(i)(k_{j,l} R_l(j))^T = q_{i,l} R_l(i) R_l(j)^T k_{j,l}^T = q_{i,l} R_l(i-j) k_{j,l}^T, \tag{2}$$

where $R_l(i) \in \mathbb{R}^{2 \times 2}$ is the l-th 2D rotation matrix, with the angle depending on position i. Due to the group property of rotation matrices, we have $R_l(i) R_l(j)^T = R_l(i-j)$, thus encoding the relative position $i - j$.

To effectively extend RoPE to 3D continuous space, we adapt its rotation matrices to handle continuous positions. Specifically, the rotation matrix $R_l(\cdot)$ is designed to accept continuous inputs. Moreover, since there are multiple rotation matrices, we partition them across the three axes in 3D space. We divide the $d_h/2$ matrices into 3 sets, each with $c_r = \lfloor d_h/6 \rfloor$ matrices, corresponding to the 3 axes. The resulting rotation matrices are:

$$\{R_0(c_i^0), \ldots, R_{c_r-1}(c_i^0), R_{c_r}(c_i^1), \ldots, R_{c_r \times 2-1}(c_i^1), R_{c_r \times 2}(c_i^2), \ldots, R_{c_r \times 3-1}(c_i^2)\}. \tag{3}$$

If d_h is not divisible by 6, the remaining $d_h/2 - c_r \times 3$ matrices will be identity matrices. In summary, this extended RoPE retains linear complexity and encodes relative continuous positions independently along each of the three axes, effectively capturing pairwise directional information in 3D space.

3D Distance Positional Encoding with RFF While the above RoPE-based encoding captures directional information, it inherently depends on the coordinate system. Although PCA is used to establish a coordinate system during gridding, it cannot always guarantee a unique solution, particularly in the presence of symmetry in molecular data. To address this, we additionally encode the pairwise distance ($\|\vec{AB}\|_2$), which is invariant to the coordinate system, offering a more stable representation of pairwise positional information.

However, directly encoding pairwise distances results in a high memory cost of $\mathcal{O}(n^2)$. To overcome this, following Rahimi & Recht (2007), we propose using random Fourier features (RFF) to approximate the Gaussian kernel on pairwise distances with linear complexity:

$$\exp\left(-\frac{\|c_i - c_j\|^2}{2\sigma^2}\right) \approx z(c_i) z(c_j)^T,$$

$$z(c_i) = \sqrt{\frac{2}{d_h}} \cos(c_i \frac{\omega}{\sigma} + b), \quad \omega \in \mathbb{R}^{3 \times d_h} \sim \mathcal{N}(0, I), b \in \mathbb{R}^{d_h} \sim \mathcal{U}([0, 2\pi]^{d_h}), \tag{4}$$

where σ controls the shape of the Gaussian, $\boldsymbol{\omega}$ is sampled from standard normal distribution, and $\boldsymbol{b}$ is sampled from a uniform distribution over $[0, 2\pi)^{d_h}$.

The random Fourier features are then combined with the Query and Key after applying the RoPE:

$$\boldsymbol{q}_i = f(\boldsymbol{q}_i, z(\boldsymbol{c}_i)) \quad \boldsymbol{k}_j = f(\boldsymbol{k}_j, z(\boldsymbol{c}_j)), \tag{5}$$

where f represents the combination function, which can be either addition or concatenation to incorporate $z(\boldsymbol{c}_i)z(\boldsymbol{c}_j)^T$ through the dot-product in the attention module. Addition is simple and efficient, though it introduces extra noise terms in the attention, such as $\boldsymbol{q}_i z(\boldsymbol{c}_j)^T$. Concatenation avoids these noise terms but is less efficient as it doubles the dimensionality of the dot-product from d_h to $2d_h$. In our early experiments, we observed no significant performance difference between the two methods, so we opted for the more efficient addition as the combination function.

3.4 OVERALL FRAMEWORK

Combining the above components, we outline the overall framework of SpaceFormer, as shown in Fig. 1. In summary, SpaceFormer is highly efficient: it utilizes grid discretization with importance sampling strategy, to convert infinite 3D continuous space into a manageable number of grid cells, and addresses the $\mathcal{O}(n^2)$ bottleneck in Transformers using FlashAttention and linear-complexity 3D positional encoding. In terms of effectiveness, SpaceFormer retains in-cell positions as input features, selectively samples important non-atom cells, and accurately captures pairwise 3D positional information through the proposed positional encoding.

4 EXPERIMENTS

To comprehensively evaluate SpaceFormer's performance, we first conduct unsupervised pretraining on large-scale unlabeled data, following previous works. The pre-trained model is then fine-tuned on various tasks with limited labeled data. Extensive ablation studies are also performed to assess the contribution of each component. Additionally, we present an in-depth comparison with atom-based models that also incorporate empty space to provide deeper insights into why SpaceFormer works.

4.1 SETTINGS

Pre-training Settings To further reduce training costs, we employ the Masked Auto-Encoder (MAE) pretraining strategy (He et al., 2022), which reduces the number of cells used during pretraining. Specifically, MAE is an encoder-decoder architecture where the encoder processes only unmasked inputs (e.g., 70% of the cells). The decoder then attempts to predict the types and in-cell positions of the masked cells based on the encoder's outputs. This approach is highly efficient because (1) the encoder processes only a subset of cells, and (2) although the decoder processes all cells, it is significantly smaller than the encoder. Furthermore, only the encoder is used during downstream task fine-tuning.

For a fair comparison, we use the same pretraining dataset as the previous work Uni-Mol (Zhou et al., 2023), which includes a total of 19 million molecules. Details of the pre-training settings are provided in Table 7 in the Appendix. For grid sampling, we set the sampling ratio m to 0.1 and the sampling temperature τ to 1.0 by default unless otherwise specified. This configuration results in a model with approximately 58.7 million parameters (55.1M in the encoder) and requires about 32 hours of training using 8 NVIDIA RTX 4090 GPUs.

Baseline Models Our primary baseline is Uni-Mol (Zhou et al., 2023), a recent 3D MRL model that achieved state-of-the-art performance on most molecular property prediction tasks. Additionally, SpaceFormer uses the same pretraining dataset as Uni-Mol, enabling an apple-to-apple comparison. We also include Mol-AE (Yang et al., 2024), which extends Uni-Mol with MAE pretraining strategy. Furthermore, for a more comprehensive comparison, we further include two 2D graph-based MRL models: GROVER (Rong et al., 2020) and GEM (Fang et al., 2022).

Downstream Tasks Most prior works use MoleculeNet (Wu et al., 2018) for downstream task evaluation. However, recent studies (Walters, 2023) have identified several limitations within the MoleculeNet dataset, including the presence of invalid structures, inconsistent chemical representations, and data curation errors. Additionally, (Sun et al., 2022) has shown that MoleculeNet fails to adequately distinguish the performance of different molecular pretraining models. To address these issues, we developed a new benchmark framework to comprehensively evaluate MRL models.

Table 1: Performance on molecular computational property prediction tasks. The best results are highlighted in **bold**, and the second-best results are underlined.

| Model | mu ↓
(D) | alpha ↓
(Bohr^3) | R^2 ↓
(Bohr^2) | ZPVE ↓
(Hartree) | C_v ↓
(cal/(mol*K)) | HOMO ↓
(Hartree) | LUMO ↓
(Hartree) | GAP ↓
(Hartree) |
|---|---|---|---|---|---|---|---|---|
| | | | | In-Distribution Split | | | | |
| GROVER | 0.6505
± 1.7e-2 | 0.7330
± 4.1e-2 | 42.0297
± 8.2e0 | 0.0006
± 5e-5 | 0.2290
± 2e-2 | 0.0052
± 5.3e-4 | 0.0055
± 4.7e-4 | 0.0079
± 1.5e-3 |
| GEM | 0.5480
± 3.6e-3 | 0.3881
± 2.8e-3 | 25.9474
± 1.8e-1 | 0.0003
± 8e-5 | 0.1514
± 7.6e-4 | 0.0039
± 8e-5 | 0.0041
± 2e-5 | 0.0057
± 4e-5 |
| Uni-Mol | 0.1552
± 2.9e-3 | 0.1675
± 1.4e-2 | 2.4775
± 1.7e-1 | 0.0003
± 5e-5 | 0.0742
± 2.7e-3 | 0.0019
± 2e-5 | 0.0018
± 2e-5 | 0.0029
± 4e-5 |
| Mol-AE | 0.1583
± 4e-3 | 0.1697
± 1.2e-2 | 2.8530
± 5.4e-1 | 0.0010
± 8e-5 | 0.0843
± 1.2e-2 | 0.0020
± 8e-5 | 0.0030
± 8e-5 | 0.0040
± 8e-5 |
| SpaceFormer | **0.0552**
± 3.6e-4 | **0.1445**
± 2.4e-3 | **1.7169**
± 3.3e-2 | **0.0001**
± 1.4e-5 | **0.0585**
± 7.4e-4 | **0.0016**
± 1.1e-5 | **0.0015**
± 1.3e-5 | **0.0026**
± 2e-5 |
| | | | | Out-of-Distribution Split | | | | |
| GROVER | 0.5062
± 2.5e-3 | 0.6456
± 1.2e-1 | 46.2615
± 4.9e0 | 0.0008
± 1.4e-4 | 0.2527
± 1.4e-2 | 0.0069
± 5.9e-4 | 0.0050
± 4.2e-4 | 0.0069
± 5.9e-4 |
| GEM | 0.4433
± 9.6e-3 | 0.3577
± 5.1e-3 | 30.8420
± 1.8e-1 | **0.0003**
± 8e-5 | 0.1540
± 4.2e-3 | 0.0041
± 5e-5 | 0.0042
± 1e-5 | 0.0061
± 1.1e-4 |
| Uni-Mol | 0.1430
± 1.7e-3 | 0.1761
± 4.1e-3 | 3.8530
± 4.4e-1 | 0.0004
± 5e-5 | 0.0914
± 1.9e-3 | 0.0020
± 7e-5 | 0.0024
± 9e-5 | 0.0034
± 1e-5 |
| Mol-AE | 0.1457
± 1.3e-3 | 0.1947
± 3.5e-2 | 4.6540
± 6.1e-1 | 0.0020
± 8e-5 | 0.0830
± 2.9e-3 | 0.0023
± 4.7e-4 | 0.0033
± 4.7e-4 | 0.0047
± 4.7e-4 |
| SpaceFormer | **0.0493**
± 1.3e-3 | **0.1425**
± 3.1e-3 | **2.8363**
± 2.8e-2 | 0.0003
± 1.3e-5 | **0.0675**
± 1.4e-3 | **0.0017**
± 1.3e-5 | **0.0019**
± 3.3e-5 | **0.0031**
± 3.1e-5 |

Our benchmark comprises two categories of tasks: molecular computational properties and molecular experimental properties. For computational properties, we sampled a 40K subset from the QM9 dataset (Ramakrishnan et al., 2014) and selected 8 representative properties. This sampling approach allows us to assess model performance on limited labeled data. For experimental properties, we selected the BBBP and BACE datasets from MoleculeNet, ensuring that all duplicate and structurally invalid molecules were excluded. Additionally, we employed the HLM, MDR1-MDCK ER (MME), and Solubility (Solu) datasets from the Biogen ADME dataset (Fang et al., 2023). A detailed description of these tasks is provided in Table 9 in the Appendix. In all tasks, datasets were split into training, validation, and test sets in an 8:1:1 ratio. We applied two splitting methods: (1) In-Distribution Split, where the sets are randomly partitioned, and (2) Out-of-Distribution Split, where the sets are divided based on fingerprint similarity. This resulted in 26 tasks, allowing for a thorough evaluation of MRL models. The hyper-parameter search space is consistent across all tasks and baseline models (see Table 8 in the Appendix). Each set of hyper-parameters is trained 3 times using different random seeds, with the mean and standard deviation recorded. For all experiments, the checkpoint with the best validation loss is selected, and the corresponding test set results are reported.

4.2 OVERALL RESULTS

Tables 1 and 2 present the overall comparison results for computational and experimental properties, respectively. The results clearly demonstrate SpaceFormer's superior performance. It ranks first in 22 out of 26 tasks and top two in 24 out of 26 tasks. SpaceFormer significantly outperforms all baselines in computational properties, with particularly strong results in the mu, R^2, and ZPVE tasks, where it surpasses the second-best models by an order of magnitude. Although it does not achieve the best results in a few experimental properties, the performance gap is minimal. In summary, by leveraging 3D space beyond atomic positions, SpaceFormer consistently outperforms previous MRL models across the comprehensive benchmark.

Table 2: Performance on molecular experimental property prediction tasks. The best results are highlighted in **bold**, and the second-best results are underlined.

Model	HLM $\downarrow$	MME $\downarrow$	Solu $\downarrow$	BBBP $\uparrow$	BACE $\uparrow$	HLM $\downarrow$	MME $\downarrow$	Solu $\downarrow$	BBBP $\uparrow$	BACE $\uparrow$
			In-Distribution Split					Out-of-Distribution Split		
GROVER	0.4190	0.5362	0.4304	0.9210	0.9137	0.4667	0.4884	0.3466	0.8567	0.5084
	$\pm$ 3.2e-2	$\pm$ 4.9e-2	$\pm$ 2.4e-2	$\pm$ 8.5e-3	$\pm$ 1.1e-2	$\pm$ 2.2e-2	$\pm$ 3.9e-2	$\pm$ 3.8e-2	$\pm$ 4e-2	$\pm$ 2.8e-2
GEM	0.3013	0.3088	0.3511	0.9314	0.9406	0.3240	0.3110	0.3190	0.9024	0.6054
	$\pm$ 7.9e-3	$\pm$ 1.6e-3	$\pm$ 4.8e-3	$\pm$ 4.1e-3	$\pm$ 3.6e-3	$\pm$ 7.1e-3	$\pm$ 2.2e-3	$\pm$ 9e-3	$\pm$ 2.3e-2	$\pm$ 1.2e-2
Uni-Mol	**0.2725**	0.3033	0.3243	0.9397	0.9317	0.3026	**0.2727**	0.3295	0.8851	**0.6793**
	$\pm$ 6.2e-3	$\pm$ 1e-2	$\pm$ 1.6e-2	$\pm$ 1.1e-2	$\pm$ 1.3e-2	$\pm$ 6.5e-3	$\pm$ 1.2e-2	$\pm$ 1e-2	$\pm$ 2e-2	$\pm$ 3.3e-2
Mol-AE	0.2727	0.3000	**0.3233**	0.9366	0.9509	0.2843	0.2930	0.2983	0.9082	0.6406
	$\pm$ 4.6e-3	$\pm$ 6.7e-3	$\pm$ 5.6e-3	$\pm$ 6.5e-3	$\pm$ 3.2e-3	$\pm$ 4.7e-4	$\pm$ 2e-2	$\pm$ 2.3e-2	$\pm$ 5.7e-2	$\pm$ 2e-2
SpaceFormer	0.2774	**0.2901**	0.3320	**0.9403**	**0.9523**	**0.2807**	0.2794	**0.2972**	**0.9099**	0.6732
	$\pm$ 3e-3	$\pm$ 2.7e-3	$\pm$ 1.1e-2	$\pm$ 4.7e-3	$\pm$ 7.6e-3	$\pm$ 1.5e-3	$\pm$ 3.2e-3	$\pm$ 6.9e-3	$\pm$ 2e-2	$\pm$ 1.6e-2

Table 3: Ablation studies on PCA and in-cell position.

No.	PCA	in-cell pos.	$R^2 \downarrow$	ZPVE $\downarrow$	$C_v \downarrow$	HOMO $\downarrow$	pre-training cost
1	✓	✓	2.8363	0.0003	0.0675	0.0017	32h
2	✗	✓	3.3088	0.0004	0.0708	0.0018	35h
3	✓	✗	5.8696	0.0004	0.0822	0.0020	32h

4.3 ABLATION STUDIES

In this subsection, we conduct a series of experiments to evaluate the proposed components of SpaceFormer. We choose the R^2, ZPVE, C_v, and HOMO properties with the Out-of-Distribution Split for all ablation experiments.

Gridding As discussed in Sec 3.1, SpaceFormer integrates several techniques for efficient grid discretization while maintaining atomic precision. We focus on evaluating two key components: PCA for determining a minimal bounding cuboid for grid discretization, and in-cell positions to preserve atomic precision. The results, summarized in Table 3, lead to the following observations:

1. Impact of PCA: Comparing No. 1 and 2, we observe that omitting PCA significantly degrades the performance of SpaceFormer and slows training by approximately 10%. This suggests that PCA not only enhances model accuracy but also reduces training costs.

2. Impact of In-Cell Position: Comparing No. 1 and 3, we see that using in-cell positions leads to better performance. This demonstrates that incorporating in-cell positions effectively preserves atomic precision and contributes to superior performance.

Grid Sampling As discussed in Sec 3.2, we propose a sampling strategy for non-atom cells to further reduce training costs. In this ablation study, we conduct a series of experiments to evaluate the efficiency and performance of different sampling strategies. Specifically, we test various importance sampling strategies with different ratios (m) and temperatures (τ), as well as several random sampling baselines. Additionally, we include two extreme cases: the atom-only model ($m = 0.0$) and the full-grid model ($m = 1.0$), to better assess the impact of non-atom cells. The results are summarized in Table 4, leading to the following conclusions:

1. Atom-Only Model (No. 1): This model performs the worst, demonstrating that non-atom cells, i.e., empty space, significantly contribute to improved model performance. This finding strongly supports the motivation behind our approach.

2. Full-Grid Model (No. 2): While this model shows strong performance, particularly for the HOMO property, its high computational cost renders it impractical for real-world applications.

3. Default Strategy (No. 4): The default sampling strategy used in SpaceFormer achieves the best balance between performance and efficiency. It is approximately 12 times faster than the full-grid model (No. 2), while delivering comparable performance.

4. Random Sampling Strategy (No. 6, 10, and 14-16): For random sampling, performance improves with a higher sampling ratio (m), but this also linearly increases training cost.

Table 4: Ablation studies on Grid Sampling. m represents the sampling ratio of non-atom cells and τ represents the temperature for sampling. $\tau =$ '-' denotes the random sampling.

No.	m	τ	$R^2 \downarrow$	ZPVE $\downarrow$	$C_v \downarrow$	HOMO $\downarrow$	pre-training cost	avg. #cells
1	0.0	N/A	3.5404	0.0004	0.0876	0.0025	12h	0.1K
2	1.0	N/A	2.8513	0.0004	0.0709	0.0015	389h	6.3K
3	0.1	0.5	2.8806	0.0004	0.0670	0.0017	32h	0.8K
4	0.1	1.0	2.8363	0.0003	0.0675	0.0017	32h	0.8K
5	0.1	2.0	3.0776	0.0005	0.0746	0.0017	32h	0.8K
6	0.1	-	2.8610	0.0005	0.0791	0.0018	32h	0.8K
7	0.2	0.5	2.9148	0.0004	0.0713	0.0017	51h	1.4K
8	0.2	1.0	3.2265	0.0004	0.0739	0.0016	51h	1.4K
9	0.2	2.0	3.2225	0.0004	0.0710	0.0016	51h	1.4K
10	0.2	-	2.8431	0.0004	0.0725	0.0017	51h	1.4K
11	0.4	0.5	3.2063	0.0007	0.0964	0.0017	103h	2.6k
12	0.4	1.0	3.6570	0.0006	0.0893	0.0018	103h	2.6K
13	0.4	2.0	2.9222	0.0004	0.0707	0.0016	103h	2.6K
14	0.4	-	2.9135	0.0004	0.0665	0.0016	103h	2.6K
15	0.6	-	2.9166	0.0004	0.0749	0.0017	193h	3.9K
16	0.8	-	2.8709	0.0003	0.0792	0.0016	300h	5.1K

Table 5: Ablation studies on 3D positional encoding.

No.	3D Directional PE with RoPE	3D Distance PE with RFF	$R^2 \downarrow$	ZPVE $\downarrow$	$C_v \downarrow$	HOMO $\downarrow$
1	✓	✓	2.8363	0.0003	0.0675	0.0017
2	✓	✗	3.4905	0.0004	0.0696	0.0017
3	✗	✗	3.7104	0.0004	0.1407	0.0022

5. Importance Sampling (No. 3–6 and No. 7–10): At smaller sampling ratios, the proposed importance sampling strategy based on eq.(4) outperforms random sampling, demonstrating its effectiveness in maintaining performance while improving efficiency.

6. However, at larger sampling ratios (No. 11-14), the importance sampling strategy cannot help to improve the performance. This is expected, as larger sampling ratios tend to include more grid cells near atoms, reducing the necessity of importance sampling strategy.

3D Positional Encoding As detailed in Sec 3.3, we introduce two 3D positional encoding methods: 3D Directional Positional Encoding with RoPE (3D Directional PE with RoPE) and 3D Distance Positional Encoding with RFF (3D Distance PE with RFF). To evaluate their contributions to the final performance, we design two ablation models: one using only 3D Directional PE with RoPE (No. 2), and another excluding both proposed encodings (No. 3). In the latter, positional information is incorporated by simply adding the linear projection of the 3D position (c_i) to the input embeddings (x_i). The results in Table 5 clearly demonstrate that the proposed 3D positional encodings significantly enhance model performance.

4.4 In-Depth Comparison with Atom-Based MRL Models

Previous experiments demonstrate the efficiency and effectiveness of SpaceFormer, but a key question remains: can incorporating empty space also enhance atom-based MRL models? To investigate this, we extend the strongest baseline, Uni-Mol, by incorporating randomly sampled empty points. Unlike SpaceFormer's grid discretization, the extended Uni-Mol samples points from continuous 3D space rather than grid cell centers. We evaluate various configurations with different numbers of sampled points/cells, as summarized in Table 6. For a fair comparison, we use the random sampling strategy for both Uni-Mol and SpaceFormer. The results lead to the following conclusions:

1. Baseline Comparison (No. 1 vs. No. 8): When excluding empty points/cells, the performance of Uni-Mol and SpaceFormer is comparable, indicating a similar baseline capability.

Table 6: Comparison with extended Uni-Mol using randomly sampled empty points. For fairness, SpaceFormer also uses random sampling strategy. As SpaceFormer samples a fraction of the entire grid, the number of sampled cells is not fixed, and the average number of sampled cells (marked with "*") is reported.

No.	Model	# Empty Points	$R^2 \downarrow$	ZPVE $\downarrow$	$C_v \downarrow$	HOMO $\downarrow$	pre-training cost
1	Uni-Mol	0	3.8530	0.0004	0.0914	0.0020	11h
2	Uni-Mol	10	3.0506	0.0004	0.0820	0.0019	12h
3	Uni-Mol	25	3.1586	0.0004	0.0886	0.0020	13h
4	Uni-Mol	50	3.0141	0.0004	0.0973	0.0019	13h
5	Uni-Mol	100	3.3509	0.0006	0.1114	0.0020	17h
6	Uni-Mol	200	3.8193	0.0005	0.1145	0.0020	35h
7	Uni-Mol	400	4.3522	0.0004	0.1337	0.0023	96h
8	SpaceFormer	0	3.5404	0.0004	0.0876	0.0025	12h
9	SpaceFormer	50*	3.6770	0.0004	0.0805	0.0025	13h
10	SpaceFormer	100*	3.3996	0.0004	0.0777	0.0024	17h
11	SpaceFormer	200*	3.2388	0.0004	0.0787	0.0024	19h
12	SpaceFormer	700*	2.8610	0.0005	0.0791	0.0018	32h
13	SpaceFormer	1300*	2.8431	0.0004	0.0725	0.0017	51h
14	SpaceFormer	1500*	2.9135	0.0004	0.0665	0.0016	103h

2. Impact of Empty Space on Uni-Mol: Incorporating a small number of empty points improves Uni-Mol's performance (No. 2 and 3 vs. No. 1), suggesting that even a limited representation of empty space can enhance the model performance.

3. Diminishing Returns for Uni-Mol: Increasing the number of empty points beyond a certain threshold does not yield further improvement (No. 3-7). This indicates that Uni-Mol struggles to utilize additional empty points effectively.

4. SpaceFormer's Scalability: In contrast, SpaceFormer continues to benefit from additional empty cells, with performance improving consistently as the number of empty cells increases (No. 8-14).

5. Efficiency of SpaceFormer: SpaceFormer scales much more efficiently with empty cells. While Uni-Mol's computational cost increases quadratically with more empty points (No. 1-7), Space-Former scales linearly (No. 8-14). For example, within 100 hours, SpaceFormer can process 1,500 cells, whereas Uni-Mol can only handle 400 points.

In summary, while incorporating empty space provides modest improvements to atom-based models like Uni-Mol, these gains are limited and come at a high computational cost. In contrast, Space-Former not only handles empty cells more efficiently but also achieves significantly better performance as the number of empty cells increases.

5 CONCLUSION

In this paper, we introduce SpaceFormer, a novel MRL framework that incorporates the 3D space beyond atomic positions to enhance molecular representation. To efficiently and effectively process 3D space, SpaceFormer leverages three key components: (1) Precision-Preserved Gridding, which discretizes continuous 3D space into a grid while maintaining atomic precision; (2) Grid Sampling, which improves efficiency by sampling grid cells without compromising accuracy; and (3) Linear-Complexity 3D Positional Encoding, which encodes pairwise positional information efficiently in 3D space. Extensive experiments validate the effectiveness and efficiency of SpaceFormer across various tasks.

Future research could explore two key areas: (1) investigating the theoretical foundations behind the effectiveness of incorporating empty space in MRL, as this work primarily provides empirical evidence, and (2) extending SpaceFormer to larger systems, such as proteins and complexes.

REFERENCES

Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J Ballard, Joshua Bambrick, et al. Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature*, pp. 1–3, 2024.

Peter W Atkins and Ronald S Friedman. *Molecular quantum mechanics*. Oxford University Press, USA, 2011.

Taoyong Cui, Chenyu Tang, Mao Su, Shufei Zhang, Yuqiang Li, Lei Bai, Yuhan Dong, Xingao Gong, and Wanli Ouyang. Geometry-enhanced pretraining on interatomic potentials. *Nature Machine Intelligence*, 6(4):428–436, 2024.

Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Timothée Darcet, Maxime Oquab, Julien Mairal, and Piotr Bojanowski. Vision transformers need registers. *arXiv preprint arXiv:2309.16588*, 2023.

Philipp Dufter, Martin Schmitt, and Hinrich Schütze. Position information in transformers: An overview. *Computational Linguistics*, 48(3):733–763, 2022.

Cheng Fang, Ye Wang, Richard Grater, Sudarshan Kapadnis, Cheryl Black, Patrick Trapa, and Simone Sciabola. Prospective validation of machine learning algorithms for absorption, distribution, metabolism, and excretion prediction: An industrial perspective. *Journal of Chemical Information and Modeling*, 63(11):3263–3274, 2023.

Xiaomin Fang, Lihang Liu, Jieqiong Lei, Donglong He, Shanzhuo Zhang, Jingbo Zhou, Fan Wang, Hua Wu, and Haifeng Wang. Geometry-enhanced molecular representation learning for property prediction. *Nature Machine Intelligence*, 4(2):127–134, 2022.

Shikun Feng, Yuyan Ni, Yanyan Lan, Zhi-Ming Ma, and Wei-Ying Ma. Fractional denoising for 3d molecular pre-training. In *International Conference on Machine Learning*, pp. 9938–9961. PMLR, 2023.

Johannes Gasteiger, Janek Groß, and Stephan Günnemann. Directional message passing for molecular graphs. *arXiv preprint arXiv:2003.03123*, 2020.

Johannes Gasteiger, Florian Becker, and Stephan Günnemann. Gemnet: Universal directional graph neural networks for molecules. *Advances in Neural Information Processing Systems*, 34:6790–6802, 2021.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 16000–16009, 2022.

Stephen R Heller, Alan McNaught, Igor Pletnev, Stephen Stein, and Dmitrii Tchekhovskoi. Inchi, the iupac international chemical identifier. *Journal of cheminformatics*, 7:1–34, 2015.

Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. *arXiv preprint arXiv:1905.12265*, 2019.

Rui Jiao, Jiaqi Han, Wenbing Huang, Yu Rong, and Yang Liu. Energy-motivated equivariant pretraining for 3d molecular graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pp. 8096–8104, 2023.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589, 2021.

Pengyong Li, Jun Wang, Yixuan Qiao, Hao Chen, Yihuan Yu, Xiaojun Yao, Peng Gao, Guotong Xie, and Sen Song. An effective self-supervised framework for learning expressive molecular global representations to drug discovery. *Briefings in Bioinformatics*, 22(6):bbab109, 2021.

Shengchao Liu, Hanchen Wang, Weiyang Liu, Joan Lasenby, Hongyu Guo, and Jian Tang. Pretraining molecular graph representation with 3d geometry. *arXiv preprint arXiv:2110.07728*, 2021.

Yi Liu, Limei Wang, Meng Liu, Yuchao Lin, Xuan Zhang, Bora Oztekin, and Shuiwang Ji. Spherical message passing for 3d molecular graphs. In *International Conference on Learning Representations (ICLR)*, 2022.

Shengjie Luo, Tianlang Chen, Yixian Xu, Shuxin Zheng, Tie-Yan Liu, Liwei Wang, and Di He. One transformer can understand both 2d & 3d molecular data. In *The Eleventh International Conference on Learning Representations*, 2022.

Anas Mahmoud, Jordan SK Hu, and Steven L Waslander. Dense voxel fusion for 3d object detection. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 663–672, 2023.

Robert G Parr, Shridhar R Gadre, and Libero J Bartolotti. Local density functional theory of atoms and molecules. *Proceedings of the National Academy of Sciences*, 76(6):2522–2526, 1979.

Jacob Pfau, William Merrill, and Samuel R Bowman. Let's think dot by dot: Hidden computation in transformer language models. *arXiv preprint arXiv:2404.15758*, 2024.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. *Advances in neural information processing systems*, 20, 2007.

Raghunathan Ramakrishnan, Pavlo O Dral, Matthias Rupp, and O Anatole Von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific data*, 1(1):1–7, 2014.

Yu Rong, Yatao Bian, Tingyang Xu, Weiyang Xie, Ying Wei, Wenbing Huang, and Junzhou Huang. Self-supervised graph transformer on large-scale molecular data. *Advances in neural information processing systems*, 33:12559–12571, 2020.

Kristof Schütt, Pieter-Jan Kindermans, Huziel Enoc Sauceda Felix, Stefan Chmiela, Alexandre Tkatchenko, and Klaus-Robert Müller. Schnet: A continuous-filter convolutional neural network for modeling quantum interactions. *Advances in neural information processing systems*, 30, 2017.

Chence Shi, Shitong Luo, Minkai Xu, and Jian Tang. Learning gradient fields for molecular conformation generation. In *International conference on machine learning*, pp. 9558–9568. PMLR, 2021.

Ziying Song, Haiyue Wei, Lin Bai, Lei Yang, and Caiyan Jia. Graphalign: Enhancing accurate feature alignment by graph matching for multi-modal 3d object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3358–3369, 2023a.

Ziying Song, Haiyue Wei, Caiyan Jia, Yongchao Xia, Xiaokun Li, and Chao Zhang. Vp-net: Voxels as points for 3-d object detection. *IEEE Transactions on Geoscience and Remote Sensing*, 61: 1–12, 2023b.

Hannes Stärk, Dominique Beaini, Gabriele Corso, Prudencio Tossou, Christian Dallago, Stephan Günnemann, and Pietro Liò. 3d infomax improves gnns for molecular property prediction. In *International Conference on Machine Learning*, pp. 20479–20502. PMLR, 2022.

Teague Sterling and John J Irwin. Zinc 15–ligand discovery for everyone. *Journal of chemical information and modeling*, 55(11):2324–2337, 2015.

Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Ruoxi Sun, Hanjun Dai, and Adams Wei Yu. Does gnn pretraining help molecular representation? *Advances in Neural Information Processing Systems*, 35:12096–12109, 2022.

Attila Szabo and Neil S Ostlund. *Modern quantum chemistry: introduction to advanced electronic structure theory*. Courier Corporation, 2012.

Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018.

A Vaswani. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.

Pat Walters. We need better benchmarks for machine learning in drug discovery, 2023. URL https://practicalcheminformatics.blogspot.com/2023/08/we-need-better-benchmarks-for-machine.html. Accessed: 2024-09-26.

Limei Wang, Yi Liu, Yuchao Lin, Haoran Liu, and Shuiwang Ji. Comenet: Towards complete and efficient message passing for 3d molecular graphs. *Advances in Neural Information Processing Systems*, 35:650–664, 2022a.

Sheng Wang, Yuzhi Guo, Yuhong Wang, Hongmao Sun, and Junzhou Huang. Smiles-bert: large scale unsupervised pre-training for molecular property prediction. In *Proceedings of the 10th ACM international conference on bioinformatics, computational biology and health informatics*, pp. 429–436, 2019.

Yuyang Wang, Jianren Wang, Zhonglin Cao, and Amir Barati Farimani. Molecular contrastive learning of representations via graph neural networks. *Nature Machine Intelligence*, 4(3):279–287, 2022b.

Yuyang Wang, Changwen Xu, Zijie Li, and Amir Barati Farimani. Denoise pretraining on nonequilibrium molecules for accurate and transferable neural potentials. *Journal of Chemical Theory and Computation*, 19(15):5077–5087, 2023.

Steven Weinberg. *The quantum theory of fields*, volume 2. Cambridge university press, 1995.

Hai Wu, Chenglu Wen, Shaoshuai Shi, Xin Li, and Cheng Wang. Virtual sparse convolution for multimodal 3d object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 21653–21662, 2023.

Zhenqin Wu, Bharath Ramsundar, Evan N Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S Pappu, Karl Leswing, and Vijay Pande. Moleculenet: a benchmark for molecular machine learning. *Chemical science*, 9(2):513–530, 2018.

Minkai Xu, Shitong Luo, Yoshua Bengio, Jian Peng, and Jian Tang. Learning neural generative dynamics for molecular conformation generation. *arXiv preprint arXiv:2102.10240*, 2021.

Minkai Xu, Lantao Yu, Yang Song, Chence Shi, Stefano Ermon, and Jian Tang. Geodiff: A geometric diffusion model for molecular conformation generation. *arXiv preprint arXiv:2203.02923*, 2022.

Zheng Xu, Sheng Wang, Feiyun Zhu, and Junzhou Huang. Seq2seq fingerprint: An unsupervised deep molecular embedding for drug discovery. In *Proceedings of the 8th ACM international conference on bioinformatics, computational biology, and health informatics*, pp. 285–294, 2017.

Junwei Yang, Kangjie Zheng, Siyu Long, Zaiqing Nie, Ming Zhang, Xinyu Dai, Wei-Ying Ma, and Hao Zhou. Mol-ae: Auto-encoder based molecular representation learning with 3d cloze test objective. *bioRxiv*, pp. 2024–04, 2024.

Tianwei Yin, Xingyi Zhou, and Philipp Krähenbühl. Multimodal virtual point 3d detection. *Advances in Neural Information Processing Systems*, 34:16494–16507, 2021.

Qiying Yu, Yudi Zhang, Yuyan Ni, Shikun Feng, Yanyan Lan, Hao Zhou, and Jingjing Liu. Multimodal molecular pretraining via modality blending. In *The Twelfth International Conference on Learning Representations*, 2024.

Sheheryar Zaidi, Michael Schaarschmidt, James Martens, Hyunjik Kim, Yee Whye Teh, Alvaro Sanchez-Gonzalez, Peter Battaglia, Razvan Pascanu, and Jonathan Godwin. Pre-training via denoising for molecular property prediction. *arXiv preprint arXiv:2206.00133*, 2022.

Anthony Zee. *Quantum field theory in a nutshell*, volume 7. Princeton university press, 2010.

Gengmo Zhou, Zhifeng Gao, Qiankun Ding, Hang Zheng, Hongteng Xu, Zhewei Wei, Linfeng Zhang, and Guolin Ke. Uni-mol: A universal 3d molecular representation learning framework. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL `https://openreview.net/forum?id=6K2RM6wVqKu`.

Hanqi Zhu, Jiajun Deng, Yu Zhang, Jianmin Ji, Qiuyu Mao, Houqiang Li, and Yanyong Zhang. Vpfnet: Improving 3d object detection with virtual point based lidar and stereo data fusion. *IEEE Transactions on Multimedia*, 25:5291–5304, 2022a.

Jinhua Zhu, Yingce Xia, Chang Liu, Lijun Wu, Shufang Xie, Yusong Wang, Tong Wang, Tao Qin, Wengang Zhou, Houqiang Li, et al. Direct molecular conformation generation. *arXiv preprint arXiv:2202.01356*, 2022b.

A APPENDIX

Table 7: Pre-training Settings

Hyper-parameters	Value
Peak learning rate	1e-4
LR scheduler	Linear
Warmup ratio	0.01
Total updates	1M
Batch size	128
Residual dropout	0.1
Attention dropout	0.1
Embedding dropout	0.1
Encoder layers	16
Encoder attention heads	8
Encoder embedding dim	512
Encoder FFN dim	2048
MAE-Decoder layers	4
MAE-Decoder attention heads	4
MAE-Decoder embedding dim	256
MAE-Decoder FFN dim	1024
Adam (β_1, β_2)	(0.9, 0.99)
Gradient clip	1.0
Mask ratio	0.3
Cell edge length c_l	0.49Å
c_m for in-cell position discretization	0.01Å

Table 8: Fine-tuning Settings

Hyper-parameters	Value
Peak learning rate	[5e-5, 1e-4]
Batch size	[32, 64]
Epochs	200
Pooler dropout	[0.0, 0.1]
Warmup ratio	0.06

Table 9: Summary information of the downstream datasets

Category	Task	Task type	Metrics	# Samples	Describe
Computational Properties	mu	Regression	MAE	40,000	The measure of the molecule's permanent electric dipole moment
	alpha	Regression	MAE	40,000	The static polarizability of a molecule
	R^2	Regression	MAE	40,000	The expectation value of the square of the electronic distance from the nucleus
	ZPVE	Regression	MAE	40,000	The energy associated with the vibrational motion of atoms in a molecule at absolute zero temperature.
	C_v	Regression	MAE	40,000	The amount of heat needed to raise the temperature of a given amount of substance by one degree Celsius at constant volume
	HOMO	Regression	MAE	40,000	The highest energy molecular orbital that is occupied by electrons
	LUMO	Regression	MAE	40,000	The lowest energy molecular orbital that is not occupied by electrons
	GAP	Regression	MAE	40,000	The energy difference between the HOMO and LUMO
Experimental Properties	HLM	Regression	MAE	3,087	Human liver microsome stability
	MME	Regression	MAE	2,642	MDRR1-MDCK efflux ratio
	Solu	Regression	MAE	2,713	Aqueous solubility
	BBBP	Classification	AUC	1,965	Blood-brain barrier penetration
	BACE	Classification	AUC	1,513	Binding results of human BACE-1 inhibitors