Recurrence along Depth: Deep Convolutional Neural Networks with Recurrent Layer Aggregation

Abstract

This paper introduces a concept of layer aggregation to describe how information from previous layers can be reused to better extract features at the current layer. While DenseNet is a typical example of the layer aggregation mechanism, its redundancy has been commonly criticized in the literature. This motivates us to propose a very light-weighted module, called recurrent layer aggregation (RLA), by making use of the sequential structure of layers in a deep CNN. Our RLA module is compatible with many mainstream deep CNNs, including ResNets, Xception and MobileNetV2, and its effectiveness is verified by our extensive experiments on image classification, object detection and instance segmentation tasks. Specifically, improvements can be uniformly observed on CIFAR, ImageNet and MS COCO datasets, and the corresponding RLA-Nets can surprisingly boost the performances by 2-3% on the object detection task. This evidences the power of our RLA module in helping main CNNs better learn structural information in images.

1   Introduction

Convolutional neural networks (CNNs) have achieved notable success in computer vision tasks, crediting to their ability to extract high-level features from input images. Due to rapid growth in the depth of CNNs in recent years, the problem of how to pass information efficiently through layers often arises when designing deep architectures. Residual connections [20, 21], or skip connections, are now cornerstone components that act as information pathways to give layers direct access to previous ones and make training feasible with hundreds of layers. In a deep feature hierarchy, higher-level features learned by the network are built upon simpler ones, but not necessarily on the layer right before it [17]. This conjecture can be supported by the stochastic depth training method [27], where layers randomly gain access to previous ones. Furthermore, it is discovered that entire layers can be removed from ResNets without impacting the performance. This observation incubated the dense connectivity in DenseNets [28, 29], where layers in a stage have direct access to all previous layers through fully connected skip connections.

We introduce a concept of layer aggregation to systematically study network designs on feature reuse, and a typical example is DenseNet. However, within a densely-connected stage, the number of network parameters grows quadratically with respect to the number of layers. These highly redundant parameters may extract similar features multiple times [7], and limit the number of channels to store new information. This motivates us to propose a very light-weighted recurrent layer aggregation (RLA) module with much fewer parameters. Specifically, we use recurrent connections to replace dense connectivity and achieve a parameter count independent of the network depth. The RLA

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

module preserves the layer aggregation functionality, and it can be added to existing CNNs for better feature extraction.

Figure 1: Schematic diagram of a CNN with recurrent layer aggregation for image classification.

Our RLA module is compatible with many CNNs used today. A schematic diagram is provided in Figure 1, where x represents hidden layers in a deep CNN and h represents hidden states in RLA modules. LeCun et al. [32] pointed out that unfolded RNNs can be seen as very deep feedforward networks where all the hidden layers share the same weights. When examined alone, an RLA module behaves similar to an unfolded RNN with layers of a deep CNN as its inputs. But applying RLA modules to CNNs is more than a simple combination of RNN and CNN (e.g., [39]). As the key idea behind layer aggregation is to provide the current layer with a version of layer history, information exchange between main CNN and RLA modules is a must. This results in a connection from the hidden unit of the RNN back to its inputs, which is hardly observable in other deep architectures. Moreover, we do not use global average pooling when passing information from the main CNN to RLA, so that the historical information is enriched and contains spatial information.

Despite its recurrent design, a convolutional-RNN-based RLA module can be easily implemented using standard convolutions with parameter sharing. Our code provides examples in both PyTorch and Keras. Empirically, RLA modules are computationally light-weighted and impose only a slight increase in model parameters and computational cost. In terms of functionality, it serves purposes beyond channel attention and can be applied on top of channel attention modules. We perform extensive experiments across a variety of tasks using different deep CNN architectures, including ResNets [20, 21], ECANets [52], Xception [10] and MobileNetV2 [41]. Our experimental results show that RLA consistently improves model performances on CIFAR, ImageNet and MS COCO datasets. On MS COCO, our RLA module can achieve 2-3% gains in terms of average precision, which significantly outperforms state-of-the-art networks with remarkable performances.

The main contributions of our work are below: (1) We introduce a definition of layer aggregation for analyzing CNN architectures. (2) We propose a novel recurrent layer aggregation module, with motivation from the layer aggregation mechanism and time series analysis. (3) We investigate detailed RLA module designs through ablation study and provide guidelines on applying RLA modules. (4) We show the effectiveness of RLA across a broad range of tasks on benchmark datasets using several popular deep CNN architectures.

2   Related work

CNN-RNN hybrid models   Deep CNNs with RLA modules should be easily distinguishable from other CNN-RNN hybrid networks, as RLA features information exchange between CNN and RNN at each layer and the corresponding recurrent update. In visual description tasks, RNNs are adopted to process the outputs of CNNs for sequence generation [14, 49, 42, 51, 5]. For video super-resolution, convolutional LSTMs can be used first to capture the temporal dependence between frames and then pass outputs to CNNs [36]. There are only a few papers that apply the concept of recurrence to CNNs. In RecResNet [1], a whole CNN is used recurrently for disparity map refinement. Moreover, in [34], convolutional layers are used recurrently to produce "deep" CNNs before the debut of ResNets.

CNNs with branching paths   CNNs with our RLA module have similar structures compared to those with branching paths, e.g., Inception networks [44, 30, 45, 46], or networks with grouped convolutions, e.g., AlexNet [31] and ResNeXt [54]. The main difference is that our RLA module has shared convolutional kernels along depth. When RLA is applied to ResNets, the resulting networks can be viewed as compressed Dual Path Networks [7].

Attention mechanisms in CNNs   Attention mechanisms have been incorporated into CNNs mainly in the form of spatial attention and channel attention. Successful applications include image captioning [55, 5], visual question answering [59], image classification [50, 16], semantic segmentation [33], face verification [6], and video frame interpolation [9]. An outstanding design of channel attention would be the Squeeze-and-Excitation (SE) block [26], which is later adopted by MobileNetV3 [25] and EfficientNet [47] and developed into compressed variants [52]. The proposed layer aggregation mechanism has a connection with channel attention across multiple layers, and meanwhile, it can be applied to networks with channel attention modules.

RNN variants   Since RLA modules adopt the form of a convolutional RNN, RNN variants give rise to different RLA designs. For example, the hidden feature maps in RLA can also be updated by the convolutional counterparts of LSTM [24, 43] or GRU cells[8]. In terms of architectural connectivity, skip connections can be introduced to RNN hidden states [38, 57, 3, 13]. Moreover, for deep RNNs, different layers of state variables can be updated at different frequencies [15]. Correspondingly, we may derive deep RLA modules that formulate stage aggregation on top of layer aggregation.

3   Recurrent layer aggregation modules

This section first introduces a concept of layer aggregation and some parsimonious models in time series analysis, which together motivate a type of light-weighted recurrent layer aggregation (RLA) modules by making use of the sequential structures of deep CNNs.

3.1   Layer aggregation

Consider a deep CNN with x^t being the hidden features at the tth layer and x^0 being the input, where L is the number of layers, and $1 \le t \le L$. The CNN is said to have the *layer aggregation mechanism* if

$$A^t = g^t(x^{t-1}, x^{t-2}, \ldots, x^0) \quad \text{and} \quad x^t = f^t(A^{t-1}, x^{t-1}), \tag{1}$$

where f^t denotes the transformation that produces new feature map at layer t of the CNN, A^t represents the aggregated information up to $(t-1)$th layer, and g^t is the corresponding transformation that summarizes these layers. For CNNs without skip connections, according to our definition, they do not involve layer aggregation since $x^t = f^t(x^{t-1})$, i.e., the information in x^ls with $l < t-1$ is only available to x^t through x^{t-1}. On the other hand, the Hierarchical Layer Aggregation [56] can be shown to have such mechanism since it satisfies Eq. (1).

It is usually more convenient to consider an additive form for the summarizing transformation, i.e.

$$A^t = \sum_{l=0}^{t-1} g_l^t(x^l), \tag{2}$$

where an additive constant c may also be included, and g_l^t can be one or more convolutions, e.g., a set of 1x1-3x3-1x1 convolutions that compose a bottleneck block. Consider a DenseNet layer

$$x^t = \text{Conv3}^t \left[\text{Conv1}^t(\text{Concat}(x^0, x^1, ..., x^{t-1})) \right], \tag{3}$$

where Conv1^t and Conv3^t denote 1x1 and 3x3 convolutions, respectively. It can be verified that

$$\text{Conv1}^t(\text{Concat}(x^0, x^1, ..., x^{t-1})) = \sum_{l=0}^{t-1} \text{Conv1}_l^t(x^l), \tag{4}$$

where the kernel weights of Conv1_l^t form a partition of the weights in Conv1^t. As a result,

$$A^t = \sum_{l=0}^{t-1} \text{Conv1}_l^{t+1}(x^l) \quad \text{and} \quad x^t = \text{Conv3}^t \left[A^{t-1} + \text{Conv1}_{t-1}^t(x^{t-1}) \right],$$

i.e., it is a typical example of the layer aggregation mechanism.

We next consider the pre-activated ResNets [21]. On the one hand, according to the ResNet update $x^t = x^{t-1} + g_{t-1}(x^{t-1})$, it may be concluded to involve no layer aggregation. On the other hand, by recursively applying the update, we have $x^t = \sum_{l=0}^{t-1} g_l(x^l) + x^0$, which satisfies Eq. (1) since $A^t = \sum_{l=0}^{t-1} g_l(x^l) + x^0$ and $x^t = A^{t-1} + g_{t-1}(x^{t-1})$. It is noticeable that g_l depends only on l, the ordinal number of previous layers, and we will discuss such a pattern in the next subsection.

Connection with channel attention   The layer aggregation mechanism in the original DenseNet can be interpreted as channel attention across layers. Specifically, the *multi-head masked self-attention* [48] mechanism can be written as

$$\text{Attention}^t = \text{Concat}(\text{head}_1^t, ..., \text{head}_m^t) \text{ with head}_i^t = \sum_{l=0}^{t-1} s_{l,i}^t \, x^l, \text{ for } i = 1, ..., m, \qquad (5)$$

where query, key and value are all set to be x^t, $s_{l,i}^t$s are scalar similarity measures and m is the number of attention heads.

Note that, when considering DenseNet layers, feature maps are tensors instead of matrices. Suppose that all x^l's have the same number of channels, denoted by k, and then Conv1^t has tk input and m output channels. Denote the $tk \times 1 \times 1 \times m$ kernel weights of Conv1^t by $\{W_{j,i}^t\}$. Let head$_i^t$ be the ith channel in Attention^t, and x_c^l be the cth channel of the feature tensor x^l, then it holds that head$_i^t = \sum_{l,c} W_{j(l,c),i}^t x_c^l$, where $j(l,c) = lk + c$ is an index. As a result, DenseNet updates coincide with a natural extension of Eq. (5) to tensor variables.

However, the above attention mechanism is too meticulous in a CNN context. For example, it will collapse when simply changing Conv1^t in DenseNets to a 3x3 convolution. In contrast, the layer aggregation interpretation of DenseNet is robust to such a modification.

3.2   Sequential structure of layers in deep networks

The complexity of summarizing transformations can drop dramatically from (1) to (2), while it may still be complicated. Actually DensNets have been frequently criticized for their redundancy. Note that the layers $\{x^t\}$ form a sequential structure, and hence this subsection will introduce some related concepts in time series analysis such that we can further compress the summarizing transformations at (1) and (2).

We first simplify Eq. (2) by assuming that g_l^t depends on the lag $t - l$ only, and this is a typical setting in time series analysis. If all x^ts are scalars and all related transformations are linear, we have

$$x^t = \beta_1 x^{t-1} + ... + \beta_{t-1} x^1 + \beta_t x^0 = \sum_{l=0}^{t-1} \beta_{t-l} x^l. \qquad (6)$$

It can also be rewritten into $\sum_{l=1}^{\infty} \beta_l x^{t-l}$ with $x^s = 0$ for $s < 0$, which has a form of autoregressive (AR) models in time series, $x^t = \sum_{l=1}^{\infty} \beta_l x^{t-l} + i^t$, with i^t being the additive error.

In time series analysis, the above AR model, which is usually referred to as the AR(∞) model, is mainly for theoretical discussions, and the commonly used running model is the autoregressive moving average (ARMA) model since it has a parsimonious structure. Consider a simple ARMA$(1, 1)$ model, $x^t = \beta x^{t-1} + i^t - \gamma i^{t-1}$. It can be verified to have an AR(∞) form of

$$\begin{aligned} x^t &= \beta x^{t-1} + i^t - \gamma i^{t-1} = \beta x^{t-1} - \gamma(x^{t-1} - \beta x^{t-2}) + i^t - \gamma^2 i^{t-2} \\ &= \cdots = \sum_{l=1}^{\infty} (\beta - \gamma)\gamma^{l-1} x^{t-l} + i^t, \end{aligned} \qquad (7)$$

where equation $i^s = x^s - \beta x^{s-1} + \gamma i^{s-1}$ is recursively applied for all $s \leq t - 1$, while there are only two parameters involved. This motivates us to use a similar pattern to construct a more parsimonious form for Eq. (6). Let

$$h^t = \alpha x^{t-1} + \gamma h^{t-1} \quad \text{and} \quad x^t = \beta_1 x^{t-1} + \beta_2 h^{t-1}. \qquad (8)$$

Assuming $h^0 = 0$, we then have $h^t = \sum_{l=1}^{t} \alpha \gamma^{l-1} x^{t-l}$ and $x^t = \beta_1 x^{t-1} + \beta_2 \alpha \sum_{l=1}^{t-1} \gamma^{l-1} x^{t-1-l}$, which has a form of (6) but involves at most four parameters. It is worthy to point out that h^t plays a role similar to that of i^t, and Eq. (8) is similar to the principle of RNNs [11].

150 We may also consider the case that g_l^t at (2) depends on l only, i.e. $x^t = f^t(\sum_{l=0}^{t-2} g_l(x^l), x^{t-1})$,
151 which leads to a ResNet-type layer. From (8), for $s > 0$, the information in x^{t-s} will be reused when
152 extracting features x^t by an amount that depends on lag s only and decays at a rate of γ^s. However,
153 as mentioned in Section 3.1, ResNet can be viewed as layer aggregation in a different pattern, and the
154 amount of information in x^l reused when extracting features x^t depends on the ordinal number l only.
155 We next conduct a small experiment to compare the ResNet-type simplification with that at (6).

156 **Comparison of two simplifications** The experiment is carried out based on the 100-layer DenseNet-
157 BC ($k = 12$) [28]. According to the two simplifications, we modify the DenseNet update (3) into the
158 following versions:

$$\text{(Shared-Lag)} \quad x^t = \text{Conv3}^t(\text{Conv1}_1(x^{t-1}) + \cdots + \text{Conv1}_{t-1}(x^1) + \text{Conv1}_0^t(x^0)), \quad (9)$$
$$\text{(Shared-Ordinal)} \quad x^t = \text{Conv3}^t(\text{Conv1}_{t-1}(x^{t-1}) + \cdots + \text{Conv1}_1(x^1) + \text{Conv1}_0^t(x^0)), \quad (10)$$

159 which correspond to (6) and ResNet, respectively. The above formulations require Conv1_l to be
160 compatible with all previous layers. For DenseNet-BC ($k = 12$), the input to dense layers x^0 has
161 $3 + 2 \times k = 27$ channels, while all later layers $x^l, 1 \le l \le 16$, have $k = 12$ channels. Thus, we
162 keep the convolutions applied to x^0 unchanged and only modify the other 1x1 convolutions. Detailed
163 explanations of the network structure of (9) are provided in the supplemental material A.2.

164 Table 2 presents the comparison of parameter count and accuracy on CIFAR-10. Detailed training
165 settings are the same as other experiments on CIFAR-10 in Section 4. Sharing the 1x1 convolutions
166 reduces the number of parameters by 25% (0.20M), while the accuracy only drops by about 0.5%.
167 This observation is consistent with the parameter sharing experiment by [35], where they found
168 that a ResNet with shared weights retains most of its performance on CIFAR-10. And the better
169 performance of Shared-Lag encourages us to pursue a more parsimonious structure along the direction
170 of (6).

171 Furthermore, we extract the weights learned by the shared 1x1 convolutions and produce Figure
172 2, following Figure 5 in [28]. A first observation is that the strongest signal in Shared-Lag (lag=1)
173 is almost twice as strong as that in Shared-Ordinal (layer=1). Secondly, we spot a quick decaying
174 pattern in the plot for Shared-Lag, which is similar to the *exponential decay* pattern in an ARMA
175 model or an RNN [58]. This observation provides us empirical evidence to adopt the principle at (8)
176 to design a light-weighted layer aggregation mechanism.

Figure 2: L_1 norm of the shared weights.

Figure 3: Diagram of an RLA module.

3.3 Recurrent layer aggregation

178 By adopting the idea at (8), we introduce a recurrent layer aggregation (RLA) mechanism below,

$$h^t = g^t(h^{t-1}, x^{t-1}) \quad \text{and} \quad x^t = f^t(h^{t-1}, x^{t-1}), \quad (11)$$

179 where $A^t = h^t$ represents the recurrently aggregated information up to $(t-1)$th layer, and it can be
180 shown to have an additive form of (2) under a linearity assumption; see supplemental material A.3.
181 By considering different forms of g^t, we can achieve various *RLA modules* to help the main CNN

Table 1: Classification error (%) on CIFAR-10 and CIFAR-100. Results are highlighted in bold if RLA-Net outperforms our re-implemented backbone model shown in the column "Re-impl.".

Dataset	Model	Params	FLOPs	Original	Re-impl.	RLA-Net	Δ Params	ΔFLOPs
C-10	ResNet-110	1.73M	8.67M	6.37	6.35	**5.88**	+0.07M	+0.37M
	ResNet-164	1.72M	8.55M	5.46	5.72	**4.95**	+0.02M	+0.19M
	Xception	2.70M	13.54M	-	6.03	**5.78**	+0.07M	+0.33M
C-100	ResNet-110	1.74M	8.69M	26.88	28.51	**27.44**	+0.07M	+0.38M
	ResNet-164	1.74M	8.67M	24.33	25.22	**23.78**	+0.02M	+0.19M
	Xception	2.75M	13.77M	-	24.31	**24.00**	+0.06M	+0.33M

better extract features, and weight sharing can be further used to regularize the layer aggregation. The form of f^t is mainly determined by the currently used mainstream CNNs, and the combination of aggregated information may be implemented in different ways.

Figure 3 gives an example for a CNN block with a residual connection, and its update can be formulated as

$$h^t = g_2[g_1(y^t) + h^{t-1}] \quad \text{and} \quad x^t = y^t + x^{t-1},$$

where $y^t = f_1^t[\text{Concat}(h^{t-1}, x^{t-1})]$. Specifically, inputs x^{t-1} and h^{t-1} are combined via concatenation and then passed to a residual unit to extract new features. One copy of this new feature map is joined with the residual connection, and the other copy is compressed via the shared 1x1 convolution and then added to h^{t-1}. Then, the RLA path goes through a pre-activated ConvRNN unit comprised of a batch normalization, a tanh activation, and a recurrent 3x3 convolution.

Practically, backbone CNNs often comprise of several stages, and RLA modules can cater to various stage structures following the guidelines below:

1. Group main CNN layers/blocks into stages so that feature maps within the same stage have the same resolution, e.g., ResNet-50/101/152 has 4 stages and MobileNetV2 has 5 stages.

2. For each stage, define (a) a shared recurrent unit, allowing information to be compressed differently at various stages, and (b) a shared 1x1 convolution, to change the channels of the residual feature maps for adding it to the RLA hidden state.

3. (*RLA path*) RLA hidden state h^0 is initialized as zero. Before entering the next stage, the RLA hidden states are downsampled to the correct resolution via average pooling.

4. (*RLA output*) For classification, the last hidden state is concatenated with the main CNN output and passed to the classifier. For detection and segmentation, RLA output can be discarded.

4 Experiments

We verify the effectiveness of our RLA module in Figure 3 on image classification, object detection and instance segmentation tasks using CIFAR, ImageNet and MS COCO datasets. All experiments are implemented on four Tesla V100 GPUs. [1] More implementation details and tabular descriptions of network architectures are provided in supplemental material B.

4.1 CIFAR and analysis

The two CIFAR datasets, CIFAR-10 and CIFAR-100, consist of 60k 32×32 RGB images of 10 and 100 classes. The training and test sets contain 50k and 10k images. We adopt a train/validation split of 45k/5k and follow the widely used data preprocessing scheme in [20, 28]. All the networks are trained from scratch using Nesterov SGD with momentum of 0.9, l_2 weight decay of 10^{-4}, and a

---

[1]Our implementation in Pytorch and Keras is provided in the supplemental materials and will be made publicly available via GitHub upon acceptance.

Table 2: Classification error of DenseNet and its parameter sharing variants on the CIFAR-10 dataset.

Model	Params	Error (%)
DenseNet	0.80M	5.80± 0.33
- Shared-Lag	0.60M	6.22
- Shared-Ordinal	0.60M	6.29

Table 3: Ablation study on the CIFAR-10 dataset.

Model	Params	Error (%)
ResNet-164	1.72M	5.72 ± 0.02
(a) channel +12	1.93M	5.27
(b) DenseNet ($k = 12$, DPN)	2.13M	5.99
(c) RLA ($k = 12$, unshared)	1.90M	5.17
(d) RLA ($k = 12$, ConvLSTM)	1.77M	5.36
(e) RLA ($k = 12$, post-act.)	1.74M	5.39

batch size of 128 for 300 epochs. The initial learning rate is set to 0.1 and is divided by 10 at 150 and 225 epochs. We choose the model with the highest validation accuracy.

We report the performance of each baseline model and its RLA-Net counterpart on CIFAR-10 and CIFAR-100 in Table 1. We observe that RLA-Net consistently improves performance across various networks with different depths, blocks and patterns of stages. For the three models in Table 1, adding the RLA module introduces about a 1%-4% increase in parameters and FLOPs. Meanwhile, our RLA-Net improves the accuracies of ResNet-110 and ResNet-164 by about 0.5% and 1.0% on CIFAR-10 and CIFAR-100, respectively.

4.2 Ablation study

Due to limited computational resources, we only conduct an ablation study on the CIFAR-10 dataset with ResNet-164 as the backbone network. To validate the effectiveness of the proposed RLA module, we compare RLA-ResNet-164 with RLA channel $k = 12$ with the following five variants: ResNet-164 with (a) channels increased by 12, (b) DenseNet-type layer aggregation, i.e., dual path network (DPN) [7], (c) RLA without parameter sharing, (d) RLA with ConvLSTM cell, and (e) RLA with the post-activated hidden unit. Results of the five variants are reported in Table 3, and the result of RLA-ResNet-164 is in Table 1. We observe that the proposed RLA module in Figure 3 outperforms all other structures with the minimum number of additional parameters.

Moreover, we also compare different strategies to combine our RLA module with the main CNN and tuned different values of RLA channel k, which is defined as the number of filters in the shared 3x3 convolution. Again, the proposed structure in Figure 3 is optimal and the best RLA channel k is consistent with the growth rate setting in DenseNet. Due to limited space, we present details of this ablation study and the investigated module structures in the supplemental material B.2.

4.3 ImageNet classification

This subsection reports experiments on the ImageNet LSVRC 2012 dataset [12]. We employ our RLA module on the widely used ResNet [20] architectures and the light-weighted MobileNetV2 [41], as well as their counterparts with SOTA channel attention ECA modules [52]. For MobileNetV2, depthwise separable convolutions are used for the shared 3x3 convolutions. When both RLA and ECA modules present, ECA modules are placed according to [52], and the output of the ECA module is then passed to our RLA module through the shared 1x1 convolution. We compare our RLA-Nets with several SOTA attention methods, including SENet [26], CBAM [53] and ECANet [52].

For training RLA-ResNets, we follow the same data augmentation and hyper-parameter settings as in [20, 28]. All the networks are trained using SGD with momentum 0.9, l_2 weight decay of 10^{-4}, and a minibatch size of 128 on 4 GPUs. We train models for 120 epochs from scratch and use the weight initialization strategy described in [18]. The initial learning rate is set to 0.1 and decreased by a factor of 10 every 30 epochs. For the light-weighted model MobileNetV2, we train the models on 2 GPUs within 400 epochs using SGD with weight decay of 4e-5, momentum of 0.9, and a mini-batch size of 96, following the settings in [41]. The initial learning rate is set to 0.045, decreased by a linear decay rate of 0.98. Parameters and FLOPs are computed by our devices.

Table 4: Comparisons of single-crop error on the ILSVRC 2012 validation set with center crop of size 224×224. All models were trained with a crop size of 224×224. The last column report increases in Top-1 accuracy by adding RLA. † Trained with some training tricks in [23]; see section B.3.

Backbone+Module	Params	FLOPs	Top-1 err.	Top-5 err.	↑Acc1
ResNet-50 [19]	24.37M	3.83G	24.70	7.80	
+RLA (Ours)	24.67M	4.17G	22.83	6.58	1.87
+SE [26]	26.77M	3.84G	23.29	6.62	
+CBAM [53]	26.77M	3.84G	22.66	6.31	
+ECA [52]	24.37M	3.83G	22.52	6.32	
+ECA+RLA (Ours)	24.67M	4.18G	**22.15**	**6.11**	0.37
ResNet-101 [19]	42.49M	7.30G	23.60	7.10	
+RLA (Ours)	42.92M	7.79G	21.48	5.80	2.12
+SE [26]	47.01M	7.31G	22.38	6.07	
+CBAM [53]	47.01M	7.31G	21.51	5.67	
+ECA [52]	42.49M	7.30G	21.35	5.66	
+ECA+RLA (Ours)	42.92M	7.80G	**21.13**	**5.61**	0.22
ResNet-152 [19]	57.40M	10.77G	23.00	6.70	
+RLA (Ours)	57.96M	11.47G	21.22	5.65	1.78
+SE [26]	63.68M	10.78G	21.57	5.73	
+ECA [52]	57.41M	10.78G	21.08	**5.45**	
+ECA+RLA (Ours)	57.96M	11.48G	**20.66**	5.49	0.42
MobileNetV2 [52, 41]	3.34M	299.6M	28.36	9.80	
+RLA (Ours)	3.46M	351.8M	27.68	**9.18**	0.68
+SE [26]	3.51M	300.3M	27.58	9.33	
+ECA [52]	3.34M	300.1M	27.44	9.19	
+ECA+RLA (Ours)	3.46M	352.4M	**27.07**	**8.89**	0.37
DenseNet-161 ($k = 48$) [52]	27.35M	7.34G	22.35	6.20	
DenseNet-264 ($k = 32$) [52]	31.79M	5.52G	22.15	6.22	
ResNet-200 [52]	74.45M	14.10G	21.80	6.00	
RLA-ResNet-50 (Ours) †	24.67M	4.17G	**21.59**	**5.68**	

Table 4 shows that our RLA-Nets obtain better results compared with their original counterparts while introducing small extra costs. Though RLA modules introduce more FLOPs when compared with channel attention modules, we find that the extra training time per epoch is almost the same. Specifically, adding SE, ECA or RLA module to ResNet-101 costs about 15%, 15% or 19% more training time. RLA-ResNets introduce about 1% increase in the number of parameters, leading to 1.9%, 2.1% and 1.8% increases in top-1 accuracy for RLA-ResNet-50/101/152, respectively. Similar results can be observed on the light-weighted MobileNetV2 architectures. Furthermore, combinations of RLA and ECA modules yield remarkably better results, achieving the best performances among these models. Last but not least, with some of the training tricks in [23], RLA-ResNet-50 can surpass much deeper CNNs. All above results demonstrate that our RLA-Net performs favorably against SOTA CNNs while benefiting from easy and direct implementation to existing SOTA architectures.

4.4 Object detection and instance segmentation on MS COCO

To show the transferability, we experiment our RLA-Net on object detection task using Faster R-CNN [40], Mask R-CNN [22] and RetinaNet [37] as detectors. For Mask R-CNN, we also show instance segmentation results. All detectors are implemented by the open source MMDetection toolkit [4]. We employ the same settings as in [52] to finetune our RLA-Nets on COCO train2017 set. Different from the classification task, we do not pass the hidden states of our RLA module to the FPN. Thus, the gains are solely from the more powerful representations learnt in the main CNNs.

We report the results on COCO val2017 set by standard COCO metrics of Average Precision (AP). Tables 5 and 6 report the performances of the object detectors. We can observe that our RLA-Net outperforms the original ResNet by 2.4% and 2.5% in terms of AP for the networks of 50 and 101 layers, respectively. More excitingly, our RLA-ResNet-50 outperforms ResNet-101 on these three detectors. In particular, our RLA module achieves more gains in AP_{75} and AP_L, indicating the high

Table 5: Object detection results of different methods on COCO val2017.

Methods	Detector	AP	AP_{50}	AP_{75}	AP_S	AP_M	AP_L	$\uparrow AP$
ResNet-50		36.4	58.2	39.2	21.8	40.0	46.2	
+RLA (Ours)		**38.8**	59.6	**42.0**	22.5	**42.9**	**49.5**	2.4
+SE		37.7	60.1	40.9	22.9	41.9	48.2	
+ECA		38.0	60.6	40.9	23.4	42.1	48.0	
+ECA+RLA (Ours)	Faster R-CNN	**39.8**	**61.2**	**43.2**	**23.9**	**43.7**	**50.8**	1.8
ResNet-101		38.7	60.6	41.9	22.7	43.2	50.4	
+RLA (Ours)		**41.2**	61.8	**44.9**	23.7	**45.7**	**53.8**	2.5
+SE		39.6	62.0	43.1	23.7	44.0	51.4	
+ECA		40.3	62.9	44.0	24.5	44.7	51.3	
+ECA+RLA (Ours)		**42.1**	**63.3**	**46.1**	**24.9**	**46.4**	**54.8**	1.8
ResNet-50		35.6	55.5	38.2	20.0	39.6	46.8	
+RLA (Ours)		**37.9**	57.0	**40.8**	**22.0**	**41.7**	49.2	2.3
+SE		37.1	57.2	39.9	21.2	40.7	49.3	
+ECA		37.3	57.7	39.6	21.9	41.3	48.9	
+ECA+RLA (Ours)	RetinaNet	**38.9**	**58.7**	**41.7**	**23.9**	**42.7**	**49.7**	1.6
ResNet-101		37.7	57.5	40.4	21.1	42.2	49.5	
+RLA (Ours)		**40.3**	59.8	**43.5**	**24.2**	**43.8**	**52.7**	2.6
+SE		38.7	59.1	41.6	22.1	43.1	50.9	
+ECA		39.1	59.9	41.8	22.8	43.4	50.6	
+ECA+RLA (Ours)		**41.5**	**61.6**	**44.4**	**25.3**	**45.7**	**53.8**	2.4

Table 6: Object detection and instance segmentation results of different methods using Mask R-CNN on COCO val2017. AP^{bb} and AP^m denote AP of bounding box detection and instance segmentation.

Methods	AP^{bb}	AP^{bb}_{50}	AP^{bb}_{75}	AP^m	AP^m_{50}	AP^m_{75}	$\uparrow AP^{bb}$	$\uparrow AP^m$
ResNet-50	37.2	58.9	40.3	34.1	55.5	36.2		
+RLA (Ours)	**39.5**	60.1	**43.3**	**35.6**	56.9	**38.0**	2.3	1.5
+SE	38.7	60.9	42.1	35.4	57.4	37.8		
+1 NL	38.0	59.8	41.0	34.7	56.7	36.6		
+GC Block	39.4	61.6	42.4	35.7	58.4	37.6		
+ECA	39.0	61.3	42.1	35.6	57.1	37.7		
+ECA+RLA (Ours)	**40.6**	**61.8**	**44.0**	**36.5**	**58.4**	**38.8**	1.6	0.9
ResNet-101	39.4	60.9	43.3	35.9	57.7	38.4		
+RLA (Ours)	**41.8**	62.3	**46.2**	37.3	59.2	**40.1**	2.4	1.4
+SE	40.7	62.5	44.3	36.8	59.3	39.2		
+ECA	41.3	63.1	44.8	37.4	59.9	39.8		
+ECA+RLA (Ours)	**42.9**	**63.6**	**46.9**	**38.1**	**60.5**	**40.8**	1.6	0.7

accuracy and effectiveness for large objects. Remarkably, exploiting RLA on ECANets can surpass all other models with large margins. We hypothesize that, with the help of RLA modules, positional information from low-level features is better preserved in the main CNN, leading to these notable improvements. In summary, the results in Tables 5 and 6 demonstrate that our RLA-Net can well generalize to various tasks with extraordinary benefits on the object detection task.

5 Conclusion and future work

This paper proposes a recurrent layer aggregation module that is light-weighted and capable of providing the backbone CNN with sequentially aggregated information from previous layers. Its potential has been well illustrated by the applications on mainstream CNNs with benchmark datasets. On the other hand, we mainly focused on controlled experiments to illustrate the effectiveness and compatibility of the RLA modules with settings adopted from existing work. Our first future work is to consider hyperparameter tuning, advanced training tricks [23, 2], or architecture search [47]. Moreover, in terms of RLA design and application, it is also an interesting direction to apply it at the stage level on top of the layer level, which leads to deep RLA modules.

References

[1] Konstantinos Batsos and Philippos Mordohai. Recresnet: A recurrent residual cnn architecture for disparity map enhancement. In *2018 International Conference on 3D Vision (3DV)*, pages 238–247. IEEE, 2018.

[2] Irwan Bello, William Fedus, Xianzhi Du, Ekin D Cubuk, Aravind Srinivas, Tsung-Yi Lin, Jonathon Shlens, and Barret Zoph. Revisiting resnets: Improved training and scaling strategies. *arXiv preprint arXiv:2103.07579*, 2021.

[3] Shiyu Chang, Yang Zhang, Wei Han, Mo Yu, Xiaoxiao Guo, Wei Tan, Xiaodong Cui, Michael Witbrock, Mark Hasegawa-Johnson, and Thomas S Huang. Dilated recurrent neural networks. In *Advances in Neural Information Processing Systems*, 2017.

[4] Kai Chen, Jiaqi Wang, Jiangmiao Pang, Yuhang Cao, Yu Xiong, Xiaoxiao Li, Shuyang Sun, Wansen Feng, Ziwei Liu, Jiarui Xu, Zheng Zhang, Dazhi Cheng, Chenchen Zhu, Tianheng Cheng, Qijie Zhao, Buyu Li, Xin Lu, Rui Zhu, Yue Wu, Jifeng Dai, Jingdong Wang, Jianping Shi, Wanli Ouyang, Chen Change Loy, and Dahua Lin. MMDetection: Open mmlab detection toolbox and benchmark. *arXiv preprint arXiv:1906.07155*, 2019.

[5] Long Chen, Hanwang Zhang, Jun Xiao, Liqiang Nie, Jian Shao, Wei Liu, and Tat-Seng Chua. Sca-cnn: Spatial and channel-wise attention in convolutional networks for image captioning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5659–5667, 2017.

[6] Sheng Chen, Yang Liu, Xiang Gao, and Zhen Han. Mobilefacenets: Efficient cnns for accurate real-time face verification on mobile devices. In *Chinese Conference on Biometric Recognition*, pages 428–438. Springer, 2018.

[7] Yunpeng Chen, Jianan Li, Huaxin Xiao, Xiaojie Jin, Shuicheng Yan, and Jiashi Feng. Dual path networks. In *Advances in Neural Information Processing Systems*, 2017.

[8] Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. In *EMNLP*, 2014.

[9] Myungsub Choi, Heewon Kim, Bohyung Han, Ning Xu, and Kyoung Mu Lee. Channel attention is all you need for video frame interpolation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 10663–10671, 2020.

[10] François Chollet. Xception: Deep learning with depthwise separable convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1251–1258, 2017.

[11] Jerome T Connor, R Douglas Martin, and Les E Atlas. Recurrent neural networks and robust time series prediction. *IEEE transactions on neural networks*, 5(2):240–254, 1994.

[12] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255. Ieee, 2009.

[13] Robert DiPietro, Christian Rupprecht, Nassir Navab, and Gregory D Hager. Analyzing and exploiting narx recurrent neural networks for long-term dependencies. *arXiv preprint arXiv:1702.07805*, 2017.

[14] Jeffrey Donahue, Lisa Anne Hendricks, Sergio Guadarrama, Marcus Rohrbach, Subhashini Venugopalan, Kate Saenko, and Trevor Darrell. Long-term recurrent convolutional networks for visual recognition and description. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2625–2634, 2015.

[15] Salah El Hihi and Yoshua Bengio. Hierarchical recurrent neural networks for long-term dependencies. In *Advances in Neural Information Processing Systems*, pages 493–499, 1996.

[16] Jun Fu, Jing Liu, Haijie Tian, Yong Li, Yongjun Bao, Zhiwei Fang, and Hanqing Lu. Dual attention network for scene segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3146–3154, 2019.

[17] Klaus Greff, Rupesh K Srivastava, and Jürgen Schmidhuber. Highway and residual networks learn unrolled iterative estimation. In *International Conference on Learning Representations*, 2017.

[18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1026–1034, 2015.

[19] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. `https://github.com/Kaiminghe/deep-residual-networks`, 2015.

[20] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

[21] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European Conference on Computer Vision*, pages 630–645. Springer, 2016.

[22] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask R-CNN. In *Proceedings of the IEEE international conference on computer vision*, pages 2961–2969, 2017.

[23] Tong He, Zhi Zhang, Hang Zhang, Zhongyue Zhang, Junyuan Xie, and Mu Li. Bag of tricks for image classification with convolutional neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 558–567, 2019.

[24] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9 (8):1735–1780, 1997.

[25] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1314–1324, 2019.

[26] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7132–7141, 2018.

[27] Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European Conference on Computer Vision*, pages 646–661. Springer, 2016.

[28] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4700–4708, 2017.

[29] Gao Huang, Zhuang Liu, Geoff Pleiss, Laurens Van Der Maaten, and Kilian Weinberger. Convolutional networks with dense connectivity. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2019.

[30] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pages 448–456. PMLR, 2015.

[31] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in Neural Information Processing Systems*, 25:1097–1105, 2012.

[32] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[33] Hanchao Li, Pengfei Xiong, Jie An, and Lingxue Wang. Pyramid attention network for semantic segmentation. In *British Machine Vision Conference*, 2018.

[34] Ming Liang and Xiaolin Hu. Recurrent convolutional neural network for object recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3367–3375, 2015.

[35] Qianli Liao and Tomaso Poggio. Bridging the gaps between residual learning, recurrent neural networks and visual cortex. *arXiv preprint arXiv:1604.03640*, 2016.

[36] Bee Lim and Kyoung Mu Lee. Deep recurrent resnet for video super-resolution. In *2017 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC)*, pages 1452–1455. IEEE, 2017.

[37] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pages 2980–2988, 2017.

[38] Tsungnan Lin, Bill G Horne, Peter Tino, and C Lee Giles. Learning long-term dependencies in narx recurrent neural networks. *IEEE Transactions on Neural Networks*, 7(6):1329–1338, 1996.

[39] Joel Moniz and Christopher Pal. Convolutional residual memory networks. *arXiv preprint arXiv:1606.05262*, 2016.

[40] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster R-CNN: Towards real-time object detection with region proposal networks. In *Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 1*, NIPS'15, page 91–99, Cambridge, MA, USA, 2015. MIT Press.

[41] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4510–4520, 2018.

[42] Baoguang Shi, Xiang Bai, and Cong Yao. An end-to-end trainable neural network for image-based sequence recognition and its application to scene text recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(11):2298–2304, 2016.

[43] Xingjian Shi, Zhourong Chen, Hao Wang, Dit-Yan Yeung, Wai-Kin Wong, and Wang-chun Woo. Convolutional lstm network: A machine learning approach for precipitation nowcasting. In *Advances in Neural Information Processing Systems*, 2015.

[44] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–9, 2015.

[45] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2818–2826, 2016.

[46] Christian Szegedy, Sergey Ioffe, Vincent Vanhoucke, and Alexander Alemi. Inception-v4, inception-resnet and the impact of residual connections on learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

[47] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pages 6105–6114. PMLR, 2019.

[48] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pages 5998–6008, 2017.

[49] Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. Show and tell: A neural image caption generator. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3156–3164, 2015.

[50] Fei Wang, Mengqing Jiang, Chen Qian, Shuo Yang, Cheng Li, Honggang Zhang, Xiaogang Wang, and Xiaoou Tang. Residual attention network for image classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3156–3164, 2017.

[51] Jiang Wang, Yi Yang, Junhua Mao, Zhiheng Huang, Chang Huang, and Wei Xu. Cnn-rnn: A unified framework for multi-label image classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2285–2294, 2016.

[52] Qilong Wang, Banggu Wu, Pengfei Zhu, Peihua Li, Wangmeng Zuo, and Qinghua Hu. Eca-net: Efficient channel attention for deep convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

[53] Sanghyun Woo, Jongchan Park, Joon-Young Lee, and In So Kweon. Cbam: Convolutional block attention module. In *Proceedings of the European conference on computer vision (ECCV)*, pages 3–19, 2018.

[54] Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1492–1500, 2017.

[55] Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. Show, attend and tell: Neural image caption generation with visual attention. In *International Conference on Machine Learning*, pages 2048–2057. PMLR, 2015.

[56] Fisher Yu, Dequan Wang, Evan Shelhamer, and Trevor Darrell. Deep layer aggregation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2403–2412, 2018.

[57] Saizheng Zhang, Yuhuai Wu, Tong Che, Zhouhan Lin, Roland Memisevic, Ruslan Salakhutdinov, and Yoshua Bengio. Architectural complexity measures of recurrent neural networks. In *Advances in Neural Information Processing Systems*, 2016.

[58] Jingyu Zhao, Feiqing Huang, Jia Lv, Yanjie Duan, Zhen Qin, Guodong Li, and Guangjian Tian. Do rnn and lstm have long memory? In *International Conference on Machine Learning*, pages 11365–11375. PMLR, 2020.

[59] Yuke Zhu, Oliver Groth, Michael Bernstein, and Li Fei-Fei. Visual7w: Grounded question answering in images. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4995–5004, 2016.