Best Arm Identification in Contaminated Stochastic Bandits

Abstract

This paper investigates the problem of best arm identification in *contaminated* stochastic multi-arm bandits, where the rewards obtained from any arm has a probability ε of getting replaced by samples from an adversarial model. A fixed confidence (infinite-horizon) setting is considered, where the goal of the learner is to identify the arm having the largest mean with a high probability. Owing to the adversarial contamination of the rewards, each arm mean is only partially identifiable. This paper proposes two algorithms, a gap-based algorithm and a successive-elimination based algorithm for best arm identification in the contaminated setting for sub-Gaussian bandits such that i) the estimator achieves the optimal error guarantee on the deviation of the true mean from the estimate asymptotically, and ii) the sample complexity for the algorithms is optimal. Specifically, for the gap-based algorithm the sample complexity is asymptotically optimal up to constant factors, and for the successive elimination-based algorithm it is optimal up to logarithmic factors. Finally, numerical experiments are provided to illustrate the gains of the algorithms designed over the existing ones.

1 Introduction

Overview. This paper investigates the problem of *best arm identification* (BAI) in stochastic multi-armed bandits (MAB), under the key assumption that the reward samples are vulnerable to adversarial corruptions. Specifically, consider a K-armed stochastic MAB, where the reward from arm $i \in [K]$ is drawn from a sub-Gaussian distribution $\mathbb{P}_i$. At each round t, the observed reward may be corrupted with probability ε. When a reward sample is corrupted, it is replaced by a sample drawn from a contamination model with distribution $\mathbb{Q}_i(t)$ which is distinct from $\mathbb{P}_i$. Such a setup is a non-trivial generalization of the canonical BAI problem due to the arbitrary corruption that may be introduced by the corruption model. This setup has far superior practical implications. For instance, consider the example of measuring drug responses, in which several compounds are evaluated in order to determine which one of them renders the maximal efficacy. It is natural to assume that a fraction of the test results are reported incorrectly, or a fraction of the samples may be contaminated [1]. Both possibilities affect the measurements (or rewards) that are used to identify the most effective drug. In a different example, consider a recommendation situation in which the goal is to recommend the most "interesting" articles to users based on their feedback on previous recommendations. In this case as well, user feedbacks are prone to be malicious (e.g., by generating spam) in reporting a fraction of the recommendations. Such examples motivate investigating the BAI problem under the additional consideration that there exists the possibility that a fraction of the reward samples might be corrupted and they obscure the process of identifying the true best arm. The problem of contaminated best arm identification (CBAI) has been studied under two main settings: (1) the fixed budget setting and (2) the fixed confidence setting. The objective in the fixed budget setting is to identify the best arm within a given sampling budget such that the misclassification rate is minimized [2], and that of the

fixed confidence setting is to obtain a prescribed confidence with the fewest samples possible (on average) [3]. In this paper, we investigate CBAI in the second setting, in which we are prescribed a fixed guarantee on the misclassification probability and the goal is to identify the arm with the highest true mean, while, in parallel, minimizing the sample complexity. The main contributions of this paper are the following.

- This paper is the first to analyze the CBAI problem for sub-Gaussian bandits in the fixed confidence setting, without altering the definition of the best arm which is defined as the arm with the highest mean reward. The existing literature on CBAI aims to identify arms with the largest median [4], which is distinct from the definition of the best arm in the canonical BAI problem.

- We provide two algorithms to address the CBAI problem, one of them being a successive elimination-based procedure and the other being a confidence gap-based procedure, both using the trimmed mean as an estimator. Specifically, we provide closed-form decision rules for dynamically selecting the arms over time, estimating the means corresponding to every arm of the bandit instance, stopping the arm-selection process and identifying the true best arm.

- We analyze the attendant performance guarantees of the proposed algorithms, specifically the decision reliability and sample complexity. While the successive elimination-based algorithm is shown to be optimal up to logarithmic factors, the confidence gap-based algorithm is shown to be asymptotically optimal up to constant factors. Both algorithms can identify the best arm even if a fraction of the reward samples are corrupted.

- Finally, we conduct numerical simulations to demonstrate the efficacy of the proposed algorithms. The experiments show that both algorithms outperform the existing methods for CBAI in both synthetic as well as real-world datasets (content recommendation and drug testing).

Related Literature. We review the existing literature in two parts – first, the literature on BAI in the fixed confidence setting, and next, the literature on contaminated stochastic MABs. The problem of BAI for stochastic MABs has a rich literature, dating back to the study in [5]. Specifically, the existing BAI algorithms can be broadly grouped into two categories: (i) algorithms that are guided by confidence bounds, and (ii) those that involve successively distilling the search space. The former class of algorithms involves the construction of confidence sets capturing the deviation of the empirical mean of an arm from its true mean. These algorithms terminate and recommend a predicted best arm once the accumulated data is sufficient for forming a decision that meets a prescribed confidence level. Some of the representative studies in this class include [6], [7], [8], and [9]. The other category of algorithms, also known as racing algorithms, involve successively identifying and rejecting the suboptimal arms until only one arm is left in the active arms set. One of the first of these algorithms was proposed in [10]. Other examples of racing algorithms for stochastic MABs include the studies in [8], [11], [12] and [13].

The literature on contaminated stochastic MABs includes analyzing adversarial corruptions in stochastic MABs for regret minimization, first studied in [14]. In this study, the adversarial power is characterized by the total number of corrupted samples C that can be introduced by the adversary until the specified time horizon. The algorithm proposed by this study degrades linearly with C, which is the optimal rate for any algorithm to achieve the optimal performance in the stochastic setting. The regret bound obtained in this study is further improved in [15]. More recent studies in this direction include [16, 17, 18, 19, 20]. The problem, however, is less investigated in the context of BAI. In the fixed budget setting, the problem of CBAI is studied in [21]. This study proposes a probabilistic sequential algorithm, which allows for trading off the suboptimality gap (in the fully stochastic regime) with the success probability using a tunable parameter. In the fixed confidence setting, CBAI is studied in [4], which modifies the definition of the "best arm" by redefining it to be the arm having the largest median. A general adversarial model is assumed in this study, where any reward sample can be contaminated by the adversary with probability ε. Furthermore, three different attack models are considered, namely the oblivious adversary, the prescient adversary, and the malicious adversary, depending on the level of adaptivity that the adversary employs to obfuscate the true reward samples. While the investigation proposes instance-adaptive algorithms matching up to logarithmic factors, in many models, the median and the mean could be considerably different, especially for the case of heavy-tailed distributions. Furthermore, this modification considerably renders the class of Bernoulli bandits impossible to analyze in the CBAI setting, since the median for each arm is either 0 or 1. Finally, the performance guarantees for the proposed algorithms are analyzed with respect to a relatively narrow class of distributions. In this paper, we investigate these

questions under the conventional definition of the best arm, where the best arm is defined as the arm having the largest mean. Furthermore, our results are derived for the class of sub-Gaussian bandits, which is a broader class of bandit instances.

2 Contaminated Best Arm Identification

Setting. Consider the canonical bandit model $\nu \in \mathsf{SG}_K(\sigma)$, where $\mathsf{SG}_K(\sigma)$ denotes the class of K-armed σ-sub-Gaussian bandits. The reward of arm $i \in [K] \triangleq \{1, \cdots, K\}$ is generated from a probability measure $\mathbb{P}_i$ with mean $\mu_i \in \mathbb{R}$. The means $\{\mu_i : i \in [K]\}$ are assumed to be unknown. At each time t, a learner interacts with the bandit instance by pulling one of the arms $A_t \in [K]$ according to a control policy, generating a random reward $X_{A_t,t} \in \mathbb{R}$. Based on the observed reward, a decision is made about the next arm to be pulled. Additionally, the setting assumes an adversary which is capable of contaminating the reward before it is observed by the learner. Specifically, it is assumed that with a fixed probability $\varepsilon \in (0,1)$, the adversary contaminates the true reward before the learner observes it by replacing it with a corrupt sample drawn from an adversarial distribution $\mathbb{Q}_i(t)$ distinct from $\mathbb{P}_i$. We consider an *oblivious* adversary which is responsible for the contamination of the reward samples. Let us define $X_{i,t}$ as the reward generated by arm $i \in [K]$ at time t according to the true distribution $\mathbb{P}_i$. The adversarial samples for each arm $i \in [K]$ at each time instant t is denoted by $X'_{i,t}$. An oblivious adversary is defined as follows.

Definition 2.1 (Oblivious adversary). *The adversary is defined as oblivious if we have that for all $i \in [K]$, the tripples $\{X_{i,t}, X'_{i,t}, B_t\}_{t \geq 1}$ are assumed to be independent of each other.*

Hence, at each time t, the adversarial action can be characterized by a Bernoulli random variable $B_t \sim \mathsf{Bern}(\varepsilon)$ such that the observed reward takes the form

$$R_{A_t} = \begin{cases} X_{A_t,t} \sim \mathbb{P}_{A_t}, & B_t = 0 \\ X'_{A_t,t} \sim \mathbb{Q}_{A_t}(t), & B_t = 1 \end{cases} . \tag{1}$$

This contamination model was first proposed in [22] in the canonical estimation framework under a single control action. Thus, the contaminated model corresponding to each arm of the bandit instance is characterized by the mixture distribution

$$\tilde{\mathbb{P}}_i(t) = (1 - \varepsilon)\mathbb{P}_i + \varepsilon\mathbb{Q}_i(t) . \tag{2}$$

The learner's sequence of actions and rewards are denoted by

$$\mathbf{A}^t \triangleq [A_1, \cdots, A_t], \quad \mathbf{R}^t \triangleq [R_{A_1}, \cdots, R_{A_t}] . \tag{3}$$

Partially Identifiable Best Arm Identification (PIBAI). Based on the accruing sequence of rewards obtained as a result of sampling the arms, the goal of the learner is to identify the best arm with a high probability. Let us denote the index of the best and second-best arms of the bandit instance by $a^\star$ and $b^\star$, respectively. Due to the action of the adversary, it is impossible to identify the true mean of any arm $i \in [K]$, even with an infinite number of samples from that arm [4]. Due to this difficulty, we consider the framework of *partially identifiable best arm identification* (PIBAI). Let us consider any arm $i \in [K]$ of the bandit instance ν. Under the PIBAI setting, we can only estimate the mean of any arm up to a constant uncertainty interval U_i around the true mean, i.e., the interval denoted by $\mathcal{I}_i \triangleq [\mu_i - U_i, \mu_i + U_i]$. Subsequently, in the context of PIBAI, the goal of identifying the best arm can be presented using the following guarantee on the identification performance.

Definition 2.2 (δ-PAC). *In the context of PIBAI, for a given set of uncertainties U_i for every $i \in [K]$, we say that a procedure is δ-PAC if it satisfies the following guarantee.*

$$\mathbb{P}\Big\{\mu_{\hat{a}_\tau} + U_{\hat{a}_\tau} < \mu_{a^\star} - U_{a^\star}\Big\} \leq \delta . \tag{4}$$

Key assumptions. Now, we formalize the key technical assumptions that are necessary for the algorithms proposed in Section 3. The first assumption ensures the feasibility of being able to identify the true best arm from the contaminated model. Essentially, there always exists adversarial models that could render the goal of CBAI infeasible, even if we have an infinite number of samples from the contaminated distribution. We assume that the algorithm operates in a regime in which it is possible to identify the true best arm. The next assumption is a standard assumption in the robust statistics literature, and it provides an upper bound on the maximum level of corruption that the adversary can inflict up on the rewards. The assumptions are formally stated below.

139   (i) The index of the best arm does not change as a result of contamination, i.e., $(\mu_{a^\star} - U_{a^\star}) >$
140       $(\mu_a + U_a)$ for every $a \in [K] \setminus a^\star$.

141   (ii) We do not require to know the precise value of the level of contamination ε. Rather, it is
142   sufficient to assume that we know an upper bound, such that at each time t, the fraction of
143   contaminated samples falls below the upper bound. Henceforth, for the rest of the paper, ε
144   denotes the upper bound on the probability of attack. We focus on the regime $\varepsilon < 1/2$.

3 CBAI Algorithms

146 We provide the CBAI algorithms in this section, and the attendant performance guarantees will be
147 analyzed in Section 4. Specifically, we propose two instance adaptive algorithms, one based on the
148 principle of successive elimination of suboptimal arms, which is inspired by [23], and the other is a
149 gap-based algorithm, which aims to reduce the overlap among the confidence intervals for different
150 arms. One common method shared by both the algorithms is the estimator for the largest mean. We
151 discuss this shared procedure before discussing the two algorithms.

Estimator. While the sample mean is widely used as an estimator for BAI algorithms, it is not

---

Algorithm 1 Gap-based algorithm for CBAI

1: **Input:** set of arms $[K]$, guarantee δ
2: **Set:** $t \leftarrow 1$, $B_t \leftarrow \infty$
3: **while** $B_t > 0$ or $t \leq K t_0(\alpha, \delta)$ **do**
4:     **if** $\exists a \in [K]$ s.t. $N_a(t) < \max\{\sqrt{t}, t_0(\alpha, \delta)\}$ **then**
5:         Sample arm $A_{t+1} = \arg\min_{i \in \mathcal{U}_t} N_i(t)$ and update $\hat{\mu}_{A_t}(t)$
6:         Update confidence interval $\beta_{A_{t+1}}(t+1, \delta)$
7:     **else**
8:         $j_t \leftarrow \arg\max_{a \in [K] \setminus \hat{a}_t} \ \hat{\mu}_a(t) + \beta_a(t, \delta) - (\hat{\mu}_{\hat{a}_t}(t) - \beta_{\hat{a}_t}(t, \delta))$
9:         $B_t \leftarrow \max_{a \in [K] \setminus \hat{a}_t} \ \hat{\mu}_a(t) + \beta_a(t, \delta) - (\hat{\mu}_{\hat{a}_t}(t) - \beta_{\hat{a}_t}(t, \delta))$
10:        $A_{t+1} \leftarrow \arg\max_{\{\hat{a}_t, j_t\}} \{\beta_{\hat{a}_t}(t, \delta), \beta_{j_t}(t, \delta)\}$
11:        Pull arm A_{t+1} and update means $\hat{\mu}_{A_{t+1}}$ and confidence intervals $\beta_{A_{t+1}}(t+1, \delta)$
12:     **end if**
13:     $t \leftarrow t + 1$
14: **end while**
15: Output: $\hat{a} = \arg\max_{a \in [K]} \hat{\mu}_a(t)$

---

153 robust to adversarial corruptions. It is well-known that the sample median is a more robust estimator
154 under such circumstances. However, while the sample median is a reasonable choice for unimodal
155 distributions or under the modified definition of the best arm, it may not be as reliable otherwise since
156 the median and the mean could be considerably different (especially, for heavy-tailed distributions).
157 For this purpose, our choice of estimator is a balance between the sample median (to remove the
158 outlier samples) and the sample mean (to form an estimate of the true mean). Specifically, for both
159 the algorithms, we use the α-trimmed mean as an estimator. This implies that given a sequence of
160 samples $\mathbf{R}_i^t \triangleq \{s = (1, \cdots, t) : R_{A_s}, A_s = i\}$ for any arm $i \in [K]$, we construct a subsequence of
161 samples $\mathbf{Y}_i^t$ by trimming the first and last α-quantile of observations from $\mathbf{R}_i^t$. Correspondingly, the
162 α-trimmed mean estimator is defined by the sample mean of the remaining samples $\mathbf{Y}_i^t$, i.e.,

$$\hat{\mu}_i(t) \ \triangleq \ \frac{1}{(1 - 2\alpha) N_i(t)} \sum_{j=1}^{\dim(\mathbf{Y}_i^t)} Y_{i,j}^t \,, \tag{5}$$

163 where $Y_{i,j}^t$ represents each entry of the data vector $\mathbf{Y}_i^t$, and $N_i(t)$ represents the number of times that

164 arm $i \in [K]$ is pulled until time t, i.e., $N_i(t) \ \triangleq \ \sum_{s=1}^{t} R_{A_s} \mathbb{1}_{\{A_s = i\}}$.

165 **Gap-based algorithm for CBAI.** This algorithm aims at reducing the maximum overlap between
166 the confidence intervals of the best arm and the most ambiguous arm. Similar to the algorithm for
167 BAI for stochastic linear MABs in [24], at each time-step, this algorithm samples the arm that reduces
168 the overlap between the current best arm and the most ambiguous arm by the largest amount. The
169 sampling process stops as soon as this overlap reaches zero. The design rules are formalized next.

Arm selection strategy. There is a rich body of literature on arm selection strategies for stochastic MABs [24, 25, 26]. The problem was solved for the family of exponential bandits in [26], through a "track and stop" arm selection rule. Building on the work in [27], this investigation proposed an arm selection strategy that tracks the optimal allocation of arm selections. The procedure was shown to exhibit asymptotic optimality (upto a constant factor). However, in the case of CBAI, this strategy is not amenable to implementation because of the fact that we do not assume that the adversarial models belong to the exponential family. Consequently, the mixture models generating our observations do not belong to the exponential family, meaning that the results obtained in [26] might not necessarily hold. Hence, we propose a confidence interval-based approach. Specifically, our proposed arm selection strategy consists of two phases: a forced exploration phase that ensures that each arm is pulled sufficiently often such that we do not get stuck in an incorrect maximum likelihood (ML) decision of the best arm, and an exploitation phase that pulls the current best and most ambiguous arms in order to reduce the overlap in the confidence intervals between the two. Subsequently, we denote the current best arm by $\hat{a}_t$ and the most ambiguous arm by j_t, i.e.,

$$j_t \triangleq \underset{a \in [K] \setminus \hat{a}_t}{\arg\min} \ \hat{\mu}_a(t) + \beta_a(t, \delta) - (\hat{\mu}_{\hat{a}_t}(t) - \beta_{\hat{a}_t}(t, \delta)) , \tag{6}$$

where $\beta_i(t, \delta)$ represents the width of the confidence interval for each arm $i \in [K]$. The choice of $\beta_i(t, \delta)$ is guided by the performance guarantee that the algorithm needs to ensure, and it is characterized in Theorem 4.2 in Section 4. The overlap in confidence interval is denoted by B_t, defined as

$$B_t \triangleq \hat{\mu}_{j_t}(t) + \beta_{j_t}(t, \delta) - (\hat{\mu}_{\hat{a}_t}(t) - \beta_{\hat{a}_t}(t, \delta)) . \tag{7}$$

Next we define a constant $t_0(\alpha, \delta)$ as follows, which is instrumental in stating the arm selection strategy.

$$t_0(\alpha, \delta) \triangleq \frac{2}{\alpha^2} \log \frac{1}{\delta} . \tag{8}$$

Based on these definitions, we provide the arm selection strategy for the gap-based CBAI algorithm: at any time t, let $\mathcal{U}_t \subseteq [K]$ be a subset of arms defined as $\mathcal{U}_t \triangleq \{i \in [K] : N_i(t) \leq \max(\sqrt{t}, t_0(\alpha, \delta))\}$. At time t, the sampling strategy pulls the arm $i \in \mathcal{U}_t$ that has been pulled the least number of times if $\mathcal{U}_t \neq \emptyset$. Otherwise, if $\mathcal{U}_t = \emptyset$, the algorithm pulls the arm between the best and the most ambiguous arms, whichever has the maximum confidence interval. Formally, at time $t + 1$ the sampling rule draws the arm A_{t+1} such that

$$A_{t+1} \in \begin{cases} \underset{i \in \mathcal{U}_t}{\arg\min} \ N_i(t) & \text{if } \mathcal{U}_t \neq \emptyset \quad \text{(forced exploration)} \\ \underset{\{\hat{a}_t, j_t\}}{\arg\max} \ \{\beta_{\hat{a}_t}(t, \delta), \beta_{j_t}(t, \delta)\} & \text{if } \mathcal{U}_t = \emptyset \quad \text{(exploitation)} \end{cases} . \tag{9}$$

Stopping rule. The stopping rule is guided by the maximum overlap of the confidence intervals corresponding to the best arm and the most ambiguous arm. As soon as the two confidence intervals cease to overlap, the algorithm stops to make a decision. However, due to the concentration of the α-trimmed mean estimator, there is a minimum number of samples that needs to be acquired before arriving at the decision. This ensures that we have enough samples to segregate the true reward samples from the outliers with a high probability. Taking into account these two aspects, the algorithm stops as soon as the overlap B_t falls below 0, and no sooner than each arm is pulled $t_0(\alpha, \delta)$ times. Formally, this is described in the following stopping rule.

$$\tau \triangleq \max \left(\frac{2K}{\alpha^2} \log \frac{1}{\delta} , \ \inf \left\{ t \in \mathbb{N} : B_t \leq 0 \right\} \right) . \tag{10}$$

The detailed steps of the procedure are described in Algorithm 1.

Successive elimination-based algorithm. In this algorithm, we maintain a set of *active* arms $\mathcal{S}_t$, which contains arms that have not yet been eliminated. At each round, we attempt to eliminate any possible suboptimal arm from the set of active arms $\mathcal{S}_t$, until we have only one element left in the set. The surviving arm is declared as the best arm. This algorithm is also based on two phases: an exploration phase, in which each arm is explored $t_0(\alpha, \delta)$ times, and an exploitation phase based on the the successive elimination of suboptimal arms. Specifically, this algorithm is similar to the Algorithm 2 in [4], with the key difference that we use the trimmed mean estimator instead of using the sample median as the estimator. The detailed steps of the procedure are described in Algorithm 2.

Algorithm 2 Successive elimination-based algorithm for CBAI

1: **Set:** $t = 1$, $\mathcal{S}_t = [K]$
2: **while** $|\mathcal{S}_t| > 1$ **do**
3:     Sample arm $i \in \mathcal{S}_t$ once and produce $\hat{\mu}_i(t)$ (from all past samples)
4:     $\mathcal{S}_{t+1} \leftarrow \left\{ i \in \mathcal{S}_t : \hat{\mu}_i(t) \geq \max_{j \in \mathcal{S}_t} \hat{\mu}_j(t) - 2\gamma_t \text{ or } N_i(t) < t_0(\alpha, \delta) \right\}$
5:     $t \leftarrow t + 1$
6: **end while**
7: Output: $\mathcal{S}_t$

---

4   Performance Guarantees

In this section, we provide the performance guarantees for the algorithms proposed in Section 3. For this purpose, let us first define the problem complexity of any CBAI instance as

$$H \triangleq \sum_{i \in [K]} \frac{2\sigma^2}{\max\{\Delta_i, \Delta_{b^\star}\}^2} \,, \tag{11}$$

where we have defined $\Delta_i \triangleq (\mu_{a^\star} - U_{a^\star}) - (\mu_i + U_i)$ for every arm $i \in [K]$. The notion of problem complexity for CBAI is a generalization of the problem complexity defined for stochastic MABs, which is subsumed by setting the uncertainty terms $U_i = 0$ for every suboptimality gap Δ_i for each arm $i \in [K]$. We will see that for the case of CBAI, the uncertainty terms U_i depend on the probability of attack ε in a way that an increase in the probability of attack results in a higher uncertainty U_i, which weakens the guarantee we can provide on the performance. We first provide a lower bound on the average sample complexity of any algorithm that is δ-PAC in the PIBAI setting.

Theorem 4.1 (Lower bound). *In the PIBAI setting, the average sample complexity of any δ-PAC procedure is lower bounded as*

$$\lim_{\delta \to 0} \frac{\mathbb{E}[\tau]}{\log(1/\delta)} \geq H \,. \tag{12}$$

Proof. See Appendix A. ∎

Next, we provide a non-asymptotic concentration bound for the α-trimmed mean estimator, which is the key lemma used for analyzing the procedures proposed in Section 3. For the following concentration on the α-trimmed mean estimator, we are considering a single arm with mean μ that we are trying to estimate. The true measure of the arm is denoted by $\mathbb{P}$, and ε denotes an upper bound on the fraction of contaminated samples.

Lemma 4.1 (Estimator concentration). *In the presence of an oblivious adversary, for the α-trimmed mean estimator with $\alpha = \varepsilon/2$, there exists $t_0(\alpha, \delta) \in \mathbb{N}$ such that for all $t > t_0(\alpha, \delta)$, we have*

$$\mathbb{P}\left\{ |\hat{\mu}_t - \mu| \geq \mathcal{O}\left(\sigma\varepsilon \sqrt{\log \frac{1}{\varepsilon}} \right) + \frac{\sigma}{1 - \varepsilon} \sqrt{\frac{2}{t} \log \frac{2}{\delta}} \right\} \leq \delta \,. \tag{13}$$

Proof. See Appendix B. ∎

From the above concentration on the α-trimmed mean estimator, we see that the bound is valid when the number of samples is at least $t_0(\alpha, \delta)$. This minimum number of samples ensures that the α-trimmed mean estimator successfully distills the outliers with a high probability. In other words, given that the total number of samples is at least $t_0(\alpha, \delta)$, the probability that any sample from the sequence $\mathbf{Y}_i^t$ is not adversarial is no less than $1 - \delta$. Thus, with a high probability, we compute the sample mean of the "good" samples, which are generated by the true model $\mathbb{P}$. It is also worth noting that the uncertainty induced as a result of using the α-trimmed mean estimator, i.e. $U_i = \mathcal{O}(\sigma\varepsilon\sqrt{\log(1/\varepsilon)})$ matches the universal lower bound on the uncertainty that can be induced by any estimator in the Huber's contamination model (2) under the σ-sub-Gaussian assumption [28]. We remark that the uncertainty term can be improved by using the empirical median as an estimator,

245 in which case it is of the order of $\mathcal{O}(\varepsilon/(1-\varepsilon))$ [4]. This is, albeit, viable at the expense of stricter
246 assumptions on the class of bandit instances.

247 The next theorem characterizes an appropriate choice of the width of the confidence intervals $\beta_i(t, \delta)$,
248 such that a δ-PAC guarantee can be ensured by Algorithm 1 in the PIBAI setting.

Theorem 4.2 (δ-PAC). *For any $\delta \in (0, 1)$, the procedure proposed in Algorithm 1 is δ-PAC in the*
250 *PIBAI setting for the choice of exploration threshold*

$$\beta_a(t, \delta) \triangleq \frac{\sigma}{1-\varepsilon} \sqrt{\frac{2}{N_a(t)} \log \frac{(K-1)Ct^\beta}{\delta}} , \tag{14}$$

251 *for every $a \in [K]$ and any $\beta > 1$, where C is a constant set as $C \triangleq (1 + (1 - \beta)^{-1})$.*

252 *Proof.* See Appendix C. ∎

253 Next, we provide an upper bound on the average sample complexity of Algorithm 1 in the asymptote
254 of diminishing error probability $\delta \to 0$.

Theorem 4.3 (Sample complexity). *In the asymptote of δ tending to 0 and for any $0 < \varepsilon < 1/2$, the*
256 *average sample complexity of the procedure proposed in Algorithm 1 is upper bounded as*

$$\lim_{\delta \to 0} \frac{\mathbb{E}[\tau]}{\log(1/\delta)} \leq \max\left\{ \frac{8K}{\varepsilon^2}, 64\beta H \right\} . \tag{15}$$

257 *Proof.* The details of the proof are provided in Appendix D. The crux of the analysis lies in the
258 fact that the additivity property of suboptimality gaps is not satisfied in the CBAI setting (Remark
259 4, [4]), which becomes a key component of the analysis for the attack-free counterpart of Algorithm 1.
260 Specifically, it can be shown that in the attack-free setting, a fixed exploration phase of one sample
261 per arm followed by the exploitation phase is sufficient to prove that Algorithm 1 is instance-optimal
262 up to logarithmic factors. The general analysis follows a similar line of arguments presented in
263 Appendix D, combined with the fact that in the attack-free setting ($U_i = 0$ for every $i \in [K]$),
264 $\Delta(i, j) = \Delta_j - \Delta_i$, where we have defined $\Delta(i, j) \triangleq \mu_i - \mu_j$. However, in the CBAI setting,
265 this relation is no longer valid. The proposed exploration phase for Algorithm 1 circumvents this
266 difficulty in the analysis, by noting that visiting each arm at least $\sqrt{t}$ number of times ensures that
267 we have that $\Delta_{\hat{a}_t} = \Delta_{a^\star}$ asymptotically as $\delta \to 0$. This is the key ingredient that differentiates the
268 analysis of Algorithm 1 in the CBAI context compared to the attack-free counterpart. This is also
269 the key reason that we are only able to provide asymptotic results on the average sample complexity
270 for the CBAI setting, while it is easy to obtain non-asymptotic high probability upper bounds on the
271 sample complexity matching up to logarithmic factors in the attack-free scenario. ∎

272 Theorem 4.3 shows that Algorithm 1 is asymptotically optimal (up to constant factors) in the limit
273 of $\delta \to 0$ for any bandit instance satisfying the property that $H > K/8\beta\varepsilon^2$. We remark that the
274 first term in the sample complexity bound is attributed to the property of the estimator, and hence,
275 is a penalty that we need to pay as a result of the ε-contamination. Also note that in the attack-free
276 scenario ($\varepsilon = 0$), the trimmed-mean estimator simply reduces to the sample-mean estimator, in which
277 case it is well-known that we do not have the first term inside the maximization. Hence, the above
278 upper-bound is only valid for $\varepsilon > 0$. The next corollary explicates the relationship between the
279 average sample complexity and the fraction of adversarial samples ε, which is a direct consequence
280 of Lemma 4.1 and Theorem 4.2.

Corollary 4.1. *In the asymptote of $\delta \to 0$, there exists a constant $C_1 \in \mathbb{R}_+$ such that the average*
282 *sample complexity of the proposed Algorithm 1 is related to the upper bound on the frequency of*
283 *adversarial samples ε as*

$$\lim_{\delta \to 0} \frac{\mathbb{E}[\tau]}{\log(1/\delta)} \leq \max\left\{ \frac{8K}{\varepsilon^2}, 64\beta \sum_{i \in [K]} \frac{2\sigma^2}{(\max\{\tilde{\Delta}_i, \tilde{\Delta}_{b^\star}\} - 2C_1\sigma\varepsilon\sqrt{\log(1/\varepsilon)})^2} \right\}, \tag{16}$$

284 *where we have defined*

$$\tilde{\Delta}_a \triangleq \mu_{a^\star} - \mu_a , \tag{17}$$

285 *for every $a \in [K]$.*

Next, we provide the performance guarantees corresponding to Algorithm 2. First, we provide a choice of γ_t that ensures that Algorithm 2 is δ-PAC in the PIBAI setting.

Theorem 4.4 (δ-PAC). *For any $\delta \in (0, 1)$, the procedure proposed in Algorithm 2 is δ-PAC in the PIBAI setting for the choice of exploration threshold*

$$\gamma_t \triangleq \frac{\sigma}{(1 - \varepsilon)} \sqrt{\frac{2}{t} \log \frac{K t^2 \pi^2}{12\delta}} \ . \tag{18}$$

Proof. See Appendix E. ∎

Finally, we provide a probabilistic upper bound on the sample complexity of the procedure in Algorithm 2.

Theorem 4.5 (Sample complexity). *With probability no lesser than $1 - \delta$ and for any $0 < \varepsilon < 1/2$, the sample complexity of the proposed procedure in Algorithm 2 is upper bounded as*

$$\tau \ \leq \ \max \left\{ \frac{8K}{\varepsilon^2} \log \frac{1}{\delta}, \ \mathcal{O}\left(\sum_{j \in [K] \setminus a^\star} \frac{1}{\Delta_j^2} \log \frac{K}{\delta \Delta_j} \right) \right\} . \tag{19}$$

Proof. See Appendix F. ∎

Theorem 4.5 shows that the sample complexity of Algorithm 2 is instance optimal up to logarithmic factors, which easily follows from the fact that $\sum_{j \in [K] \setminus a^\star} 1/\Delta_j^2 < H$.

5 Experiments

In this section, we show the empirical performance of the proposed algorithms and how it compares to the existing strategies. Specifically, we provide synthetic as well as real-world experiments which consider Gaussian bandits as a common framework for comparison with the median-based successive elimination framework proposed in [4], although our algorithms work for any sub-Gaussian bandit environment.

Experiments using synthetic data. We consider a Gaussian bandit instance with $K = 4$, and the true mean vector is $\boldsymbol{\mu} \triangleq [2.5, \ 2.3, \ 2, \ 0.6]$. For comparison, we test four strategies: (i) gap-based algorithm (Algorithm 1), (ii) successive elimination-based algorithm (Algorithm 2), (iii) Algorithm 1, along with a random sampling strategy that selects any arm $a \in [K]$ with a uniform probability, and (iv) the successive elimination-based algorithm proposed in [4], which uses the empirical median as an estimator. Figure 1 depicts the average sample complexity versus varying confidence levels δ, when the attack probability ε is set to $\varepsilon = 0.1$. We observe that in this experiment, the median-based successive elimination strategy has a slightly better performance compared to the proposed trimmed mean estimator. This improvement is a consequence of the fact that we are using a Gaussian bandit for which the empirical median yields a better error guarantee (of the order of $\mathcal{O}(\frac{\varepsilon}{1-\varepsilon})$) compared to the trimmed mean ($\mathcal{O}(\varepsilon \sqrt{\log(1/\varepsilon)})$). However, our proposed algorithms work for any sub-Gaussian bandit instance, which is not the case for the median-based strategy. Figure 2 shows how the sample complexity scales with increasing levels of contamination ε.

Our simulation study suggests that although not allowed by theory, for the proposed gap-based strategy, a confidence interval of the form $\beta_a(t, \delta) = \sigma \sqrt{2/N_a(t) \log(\log t/\delta)}$ for every arm $a \in [K]$ is also over-conservative empirically and meets the prescribed guarantee on decision confidence. The looseness in the theoretical confidence interval has also been observed in the algorithm proposed in [26] for BAI in stochastic multi-armed bandits, where the empirical performances are compared using a tighter exploration threshold (of the order of $\log((\log t)/\delta)$). Our simulation results are also with respect to the tighter choice of confidence intervals.

Experiments using real data. We use two real-world datasets, namely the New Yorker Caption Contest (NYCC) dataset and the PKIS2 dataset for comparing the proposed algorithms to existing strategies. Details about these datasets and the experiments are presented in Appendix G. For both the datasets, we plot the sample complexity versus varying levels of decision confidence δ when the probability of attack is set to $\varepsilon = 0.1$. These results are depicted in Figure 3a and Figure 3b .

Figure 1: Synthetic data: $\mathbb{E}[\tau]$ versus δ

Figure 2: Synthetic data: $\mathbb{E}[\tau]$ versus ε

Algorithms compared: (i) gap-based algorithm (Algorithm 1), (ii) successive elimination-based algorithm (Algorithm 2), (iii) median-based successive elimination proposed in [4], and (iv) random arm selection with stopping rule of Algorithm 1

Our experiments show that the proposed gap-based strategy outperforms all other strategies for both the real-world datasets as well as the synthetic data owing to the tightness in the confidence intervals (and hence, the stopping criterion). Furthermore, it is noteworthy that as we increase δ, the gap between the empirical performance of the random selection strategy and the successive elimination based strategy reduces. This is attributed to the fact that the stopping criterion for the randomized selection procedure is the same as that of the gap-based algorithm, and the improvement in performance of the randomized procedure is due to the tightness of the confidence intervals used for the algorithm. We also note that using the confidence interval defined in (14) for the gap-based algorithm, the proposed successive elimination algorithm outperforms the gap-based method. More details are provided in Appendix G.

(a) NYCC

(b) PKIS2

Figure 3: Experiments with **real data**: $\mathbb{E}[\tau]$ versus δ plotted for (i) gap-based algorithm (Algorithm 1), (ii) successive elimination-based algorithm (Algorithm 2), (iii) median-based successive elimination proposed in [4], and (iv) random arm selection with stopping rule of Algorithm 1

6 Conclusions

In this paper, we have investigated the problem of best arm identification for stochastic multi-armed bandits under adversarial corruptions. Specifically, we have assumed that with a probability ε, each reward sample may get replaced by a sample drawn from an adversarial distribution. Under this framework, we have proposed two algorithms for best arm identification and have analyzed their optimality properties in terms of the average sample complexity. Specifically, the gap-based algorithm has been shown to be asymptotically optimal up to constant factors, while the successive elimination-based algorithm is shown to be optimal up to logarithmic factors. Finally, we have performed experiments with synthetic as well as real-world data to compare the empirical performance of the proposed strategies to existing methods. One limitation of this investigation is that we have considered an oblivious adversary, while in practice, adversarial models could be more powerful. Analyzing CBAI for stronger adversaries (e.g., prescient and malicious adversaries) for the class of sub-Gaussian bandits is open for further investigation.

References

[1] M. R. Keogh-Brown, M. O. Bachmann, L. Shepstone, C. Hewitt, A. Howe, C. R. Ramsay, F. Song, J. N. Miles, D. J. Torgerson, S. Miles, D. Elbourne, I. Harvey, and M. J. Campbell. Contamination in trials of educational interventions. *Health Technol Assess*, 11(43), October 2007.

[2] S. Bubeck, R. Munos, and G. Stoltz. Pure exploration in multi-armed bandits problems. In *Proc. International Conference on Algorithmic Learning Theory*, Porto, Portugal, October 2009.

[3] E. Paulson. A sequential procedure for selecting the population with the largest mean from k normal populations. *Annals of Mathematical Statistics*, 35(1):174–180, March 1964.

[4] J. Altschuler, V. E. Brunel, and A. Malek. Best arm identification for contaminated bandits. *Journal of Machine Learning Research*, 20(91):1–39, 2019.

[5] T. L. Lai and H. Robbins. Asymptotically efficient adaptive allocation rules. *Advanced Applied Mathematics*, 6(1):4–22, March 1985.

[6] S. Kalyanakrishnan, A. Tewari, P. Auer, and P. Stone. PAC subset selection in stochastic multi-armed bandits. In *Proc. International Conference on Machine Learning*, Madison, Wisconsin, June 2012.

[7] V. Gabillon, M. Ghavamzadeh, and A. Lazaric. Best arm identification: A unified approach to fixed budget and fixed confidence. In *Proc. Advances in Neural Information Processing Systems*, Lake Tahoe, Nevada, December 2012.

[8] E. Kaufmann and S. Kalyanakrishnan. Information complexity in bandit subset selection. *Journal of Machine Learning Research*, 30:228–251, January 2013.

[9] K. Jamieson, M. Malloy, R. Nowak, and S. Bubeck. lil' ucb : An optimal exploration algorithm for multi-armed bandits. In *Proc. Conference on Learning Theory*, June 2014.

[10] O. Maron and A. W. Moore. The racing algorithm: Model selection for lazy learners. *Artificial Intelligence Review*, 11(1–5):193–225, February 1997.

[11] E. Even-Dar, S. Mannor, and Y. Mansour. Action elimination and stopping conditions for the multi-armed bandit and reinforcement learning problems. *Journal of Machine Learning Research*, 7:1079–1105, December 2006.

[12] J. Y. Audibert, S. Bubeck, and R. Munos. Best arm identification in multi-armed bandits. In *Proc. Conference on Learning Theory*, Haifa, Israel, November 2010.

[13] L. Chen, J. Li, and M. Qiao. Towards instance optimal bounds for best arm identification. In *Proc. Conference on Learning Theory*, Amsterdam, Netherlands, July 2017.

[14] T. Lykouris, V. Mirrokni, and R. P. Leme. Stochastic bandits robust to adversarial corruptions. In *Proc. ACM SIGACT Symposium on Theory of Computing*, Los Angeles, CA, 2018.

[15] A. Gupta, T. Koren, and K. Talwar. Better algorithms for stochastic bandits with adversarial corruptions. In *Proc. Conference on Learning Theory*, Phoenix, AZ, June 2019.

[16] J. Zimmert and Y. Seldin. An optimal algorithm for stochastic and adversarial bandits. In *Proc. International Conference on Artificial Intelligence and Statistics*, Okinawa, Japan, April 2019.

[17] K. S. Jun, L. Li, Y. Ma, and J. Zhu. Adversarial attacks on stochastic bandits. In *Advances in Neural Information Processing Systems*, Montreal, Canada, December 2018.

[18] A. Krishnamurthy, T. Lykouris, C. Podimata, and R. Schapire. Contextual search in the presence of irrational agents. *arXiv 2002.11650*, 2020.

[19] L. Niss and A. Tewari. What you see may not be what you get: UCB bandit algorithms robust to ε-contamination. In *Proc. Conference on Uncertainty in Artificial Intelligence*, Toronto, Canada, August 2020.

[20] A. Rangi, L. Tran-Thanh, H. Xu, and M. Franceschetti. Secure-ucb: Saving stochastic bandits from poisoning attacks via limited data verification. *arXiv 2102.07711*, 2021.

[21] Z. Zhong, W. C. Cheung, and V. Y. F. Tan. Probabilistic sequential shrinking: A best arm identification algorithm for stochastic bandits with corruptions. *arXiv 2010.07904*, 2021.

[22] P. J. Huber. Robust Estimation of a Location Parameter. *The Annals of Mathematical Statistics*, 35(1):73 – 101, 1964.

[23] E. Even-Dar, S. Mannor, and Y. Mansour. Action elimination and stopping conditions for the multi-armed bandit and reinforcement learning problems. *Journal of Machine Learning Research*, 7(39):1079–1105, 2006.

[24] L. Xu, J. Honda, and M. Sugiyama. A fully adaptive algorithm for pure exploration in linear bandits. In *Proc. International Conference on Artificial Intelligence and Statistics*, Lanzarote, Canary Islands, April 2018.

[25] V. Gabillon, M. Ghavamzadeh, and A. Lazaric. Best arm identification: A unified approach to fixed budget and fixed confidence. In *Proc. Advances in Neural Information Processing Systems*, Lake Tahoe, NV, December 2012.

[26] A. Garivier and E. Kaufmann. Optimal best arm identification with fixed confidence. In *Proc. Conference on Learning Theory*, New York, NY, June 2016.

[27] H. Chernoff. Sequential design of experiments. *The Annals of Mathematical Statistics*, 30(3): 755–770, September 1959.

[28] I. Diakonikolas and D. M. Kane. Recent advances in algorithmic high-dimensional robust statistics. *arXiv 1911.05911*, 2019.

[29] J. Steinhardt. Lecture Notes for STAT240 (Robust and Nonparametric Statistics), April 2021.

[30] D. H. Drewry, C. I. Wells, D. M. Andrews, R. A., H. Al-Ali, A. D. Axtman, S. J. Capuzzi, J. M. Elkins, P. Ettmayer, and M. Frederiksen et al. Progress towards a public chemogenomic set for protein kinases and a call for contributions. *PloS one*, 12(8), August 2017.

[31] B. Mason, L. Jain, A. Tripathy, and R. Nowak. Finding all ϵ-good arms in stochastic bandits. *arXiv 2006.08850*, 2020.