Understanding Deep Contrastive Learning via Coordinate-wise Optimization

Abstract

We show that Contrastive Learning (CL) under a broad family of loss functions (including InfoNCE) has a unified formulation of coordinate-wise optimization on the network parameter $\boldsymbol{\theta}$ and pairwise importance α, where the *max player* $\boldsymbol{\theta}$ learns representation for contrastiveness, and the *min player* α puts more weights on pairs of distinct samples that share similar representations. The resulting formulation, called $\boldsymbol{\alpha}$**CL**, unifies not only various existing contrastive losses, which differ by how sample-pair importance α is constructed, but also is able to extrapolate to give novel contrastive losses beyond popular ones, opening a new avenue of contrastive loss design. These novel losses yield comparable (or better) performance on CIFAR10 and STL-10 than classic InfoNCE. Furthermore, we also analyze the max player in detail: we prove that with fixed α, max player is equivalent to Principal Component Analysis (PCA) for deep linear network, and almost all local minima are global and rank-1, recovering optimal PCA solutions. Finally, we extend our analysis on max player to 2-layer ReLU networks, showing that its fixed points can have higher ranks.

1 Introduction

While contrastive self-supervised learning has been shown to learn good features [9, 20, 35] and in many cases, comparable with features learned from supervised learning, it remains an open problem what features it learns, in particular when deep nonlinear networks are used. Theory on this is quite sparse, mostly focusing on loss function [3] and treating the networks as a black-box function approximator.

In this paper, we present a novel perspective of contrastive learning (CL) for a broad family of contrastive loss functions $\mathcal{L}(\boldsymbol{\theta})$: minimizing $\mathcal{L}(\boldsymbol{\theta})$ corresponds to a *coordinate-wise optimization* procedure on an objective $\mathcal{E}_\alpha(\boldsymbol{\theta}) - \mathcal{R}(\alpha)$ with respect to network parameter $\boldsymbol{\theta}$ and *pairwise importance* α on batch samples, where $\mathcal{E}_\alpha(\boldsymbol{\theta})$ is an energy function and $\mathcal{R}(\alpha)$ is a regularizer, both associated with the original contrastive loss $\mathcal{L}$. In this view, the *max player* $\boldsymbol{\theta}$ learns a representation to maximize the contrastiveness of different samples and keep different augmentation view of the same sample similar, while the *min player* α puts more weights on pairs of different samples that appear similar in the representation space, subject to regularization. Empirically, this formulation, named P̲air-weighted C̲ontrastive L̲earning ($\boldsymbol{\alpha}$CL), when coupled with various regularization terms, yields novel contrastive losses that show comparable (or better) performance in CIFAR10 [30] and STL-10 [11].

We then focus on the behavior of the max player who does *representation learning* via maximizing the energy function $\mathcal{E}_\alpha(\boldsymbol{\theta})$. When the underlying network is deep linear, we show that $\max_{\boldsymbol{\theta}} \mathcal{E}_\alpha(\boldsymbol{\theta})$ is the loss function (under re-parameterization) of Principal Component Analysis (PCA) [46], a century-old unsupervised dimension reduction method. To further show they are equivalent, we prove that the

Contrastive Loss	$\phi(x)$	$\psi(x)$
InfoNCE [35]	$\tau \log(\epsilon + x)$	$e^{x/\tau}$
MINE [6]	$\log(x)$	e^x
Triplet [39]	x	$[x + \epsilon]_+$
Soft Triplet [44]	$\tau \log(1 + x)$	$e^{x/\tau+\epsilon}$
N+1 Tuplet [40]	$\log(1 + x)$	e^x
Lifted Structured [34]	$[\log(x)]^2_+$	$e^{x+\epsilon}$
Modified Triplet Eqn. 10 [12]	x	sigmoid(cx)
Triplet Contrastive Eqn. 2 [23]	linear	linear

Figure 1: Problem Setting. **Left**: Data points (i-th sample $\boldsymbol{x}[i]$ and its augmented version $\boldsymbol{x}[i']$, j-th sample $\boldsymbol{x}[j]$) are sent to networks with weights $\boldsymbol{\theta}$, to yield outputs $\boldsymbol{z}[i]$, $\boldsymbol{z}[i']$ and $\boldsymbol{z}[j]$. From the outputs $\boldsymbol{z}$, we compute pairwise squared distance d_{ij}^2 between $\boldsymbol{z}[i]$ and $\boldsymbol{z}[j]$ and intra-class squared distance d_i^2 between $\boldsymbol{z}[i]$ and $\boldsymbol{z}[i']$ for contrastive learning with a general family of contrastive loss $\mathcal{L}_{\phi,\psi}$ (Eqn. 1). **Right**: Different existing loss functions corresponds to different monotonous functions ϕ and ψ. Here $[x]_+ := \max(x, 0)$.

nonlinear training dynamics of CL with a linear multi-layer feedforward network (MLP) enjoys nice properties: with proper weight normalization, almost all its local optima are global, achieving optimal PCA objective, and are rank-1. The only difference here is that the data augmentation provides negative eigen-directions to avoid.

Furthermore, we extend our analysis to 2-layer ReLU network, to explore the difference between the rank-1 PCA solution and the solution learned by a nonlinear network. Assuming the data follow an orthogonal mixture model, the 2-layer ReLU networks enjoy similar dynamics as the linear one, except for a special *sticky weight rule* that keeps the low-layer weights to be non-negative and stays zero when touching zero. In the case of one hidden node, we prove that the solution in ReLU always picks a single mode from the mixtures. In the case of multiple hidden nodes, the resulting solution is not necessarily rank-1.

2 Related Work

Contrastive learning. While many contrastive learning techniques (e.g., SimCLR [9], MoCo [20], PIRL [33], SwAV [8], DeepCluster [7], Barlow Twins [50], InstDis [47], etc) have been proposed empirically and able to learn good representations for downstream tasks, theoretical study is relatively sparse, mostly focusing on loss function itself [42, 18, 3], e.g., the relationship of loss functions with mutual information (MI). To our knowledge, there is no analysis that combines the property of neural network and that of loss functions.

Theoretical analysis of deep networks. Many works focus on analysis of deep linear networks in supervised setting, where label is given. [5, 51, 26] analyze the critical points of linear networks. [38, 2] also analyze the training dynamics. On the other hand, analyzing nonlinear networks has been a difficult task. Existing works mostly lie in supervised learning, e.g., teacher-student setting [43, 1], landscape [37]. For contrastive learning, recent work [45] analyzes the dynamics of 1-layer ReLU networks with a specific weight structure, and [24] analyzes the collapsing behaviors in 2-layer linear network for CL. To our best knowledge, we are not aware of such analysis on deep networks (> 2 layers, linear or nonlinear) in the context of CL.

Connection between Principal Component Analysis (PCA) and Self-supervised Learning. [32] establishes the statistical connection between non-linear Canonical Component Analysis (CCA) and SimSiam [10] for any zero-mean encoder, without considering the aspect of training dynamics. In contrast, we reformulate contrastive learning as coordinate-wise optimization procedure with min/max players, in which the max player is a reparameterization of PCA optimized with gradient descent, and analyze its training dynamics in the presence of specific neural architectures.

3 Contrastive Learning as Coordinate-wise Optimization

Notation. Suppose we have N pairs of samples $\{\boldsymbol{x}[i]\}_{i=1}^{N}$ and $\{\boldsymbol{x}[i']\}_{i=1}^{N}$. Both $\boldsymbol{x}[i]$ and $\boldsymbol{x}[i']$ are augmented samples from sample i and $\boldsymbol{x}$ represents the input batch. These samples are sent to

neural networks and $z[i]$ and $z[i']$ are their outputs. The goal of contrastive learning (CL) is to find the representation to maximize the squared distance $d_{ij}^2 := \|z[i] - z[j]\|_2^2 / 2$ between distinct samples i and j, and minimize the squared distance $d_i^2 := \|z[i] - z[i']\|_2^2 / 2$ between different data augmentations $x[i]$ and $x[i']$ of the same sample i.

3.1 A general family of contrastive loss

We consider minimizing a general family of loss functions $\mathcal{L}_{\phi,\psi}$, where ϕ and ψ are monotonously increasing and differentiable scalar functions (define $\xi_i := \sum_{j \neq i} \psi(d_i^2 - d_{ij}^2)$ for notation brevity):

$$\min_{\theta} \mathcal{L}_{\phi,\psi}(\theta) := \sum_{i=1}^{N} \phi(\xi_i) = \sum_{i=1}^{N} \phi \left(\sum_{j \neq i} \psi(d_i^2 - d_{ij}^2) \right) \tag{1}$$

Both i and j run from 1 to N. With different ϕ and ψ, Eqn. 1 covers many loss functions (Tbl. 1). In particular, setting $\phi(x) = \tau \log(\epsilon + x)$ and $\psi(x) = \exp(x/\tau)$ gives a generalized version of InfoNCE loss [35]:

$$\mathcal{L}_{nce} := -\tau \sum_{i=1}^{N} \log \frac{\exp(-d_i^2/\tau)}{\epsilon \exp(-d_i^2/\tau) + \sum_{j \neq i} \exp(-d_{ij}^2/\tau)} = \tau \sum_{i=1}^{N} \log \left(\epsilon + \sum_{j \neq i} e^{\frac{d_i^2 - d_{ij}^2}{\tau}} \right) \tag{2}$$

where $\epsilon > 0$ is some constant not related to $z[i]$ and $z[i']$. $\epsilon = 1$ has been used in many works [20, 41]. Setting $\epsilon = 0$ yields SimCLR setting [9] where the denominator doesn't contains $\exp(-d_i^2/\tau)$. This is also used in [49].

3.2 The other side of gradient descent of contrastive loss

To minimize $\mathcal{L}_{\phi,\psi}$, gradient descent follows its negative gradient direction. As a first discovery of this work, it turns out that the gradient descent of the loss function $\mathcal{L}$ is the *gradient ascent* direction of another energy function $\mathcal{E}_{\alpha}$:

Theorem 1. *For any differential mapping $z = z(x; \theta)$, gradient descent of $\mathcal{L}_{\phi,\psi}$ is equivalent to* **gradient ascent** *of the objective $\mathcal{E}_{\alpha}(\theta) := \mathrm{tr}(\mathbb{C}_{\alpha}[z(\theta), z(\theta)])$:*

$$\frac{\partial \mathcal{L}_{\phi,\psi}}{\partial \theta} = -\frac{1}{2} \frac{\partial \mathcal{E}_{\alpha}}{\partial \theta} \bigg|_{\alpha = \alpha(\theta)} \tag{3}$$

Here the pairwise importance $\alpha = \alpha(\theta) := \{\alpha_{ij}(\theta)\}$ *is a function of input batch x, defined as:*

$$\alpha_{ij}(\theta) := \phi'(\xi_i)\psi'(d_i^2 - d_{ij}^2) \geq 0 \tag{4}$$

where $\phi', \psi' \geq 0$ are derivatives of ϕ, ψ. The contrastive covariance $\mathbb{C}_{\alpha}[\cdot, \cdot]$ *is defined as:*

$$\mathbb{C}_{\alpha}[a, b] := \sum_{i=1}^{N} \sum_{j \neq i} \alpha_{ij}(a[i] - a[j])(b[i] - b[j])^{\top} - \sum_{i=1}^{N} \left(\sum_{j \neq i} \alpha_{ij} \right) (a[i] - a[i'])(b[i] - b[i'])^{\top} \tag{5}$$

That is, **minimizing** *the loss function $\mathcal{L}_{\phi,\psi}(\theta)$ can be regarded as* **maximizing** *the energy function $\mathcal{E}_{\alpha = \mathrm{sg}(\alpha(\theta))}(\theta)$ with respect to θ. Here $\mathrm{sg}(\cdot)$ means stop-gradient, i.e., the gradient of θ is not backpropagated into $\alpha(\theta)$.*

Please check Supplementary Materials (SM) for all proofs. From the definition of energy $\mathcal{E}_{\alpha}(\theta)$, it is clear that α_{ij} determines the importance of each sample pair $x[i]$ and $x[j]$. For (i, j)-pair that "deserves attention", α_{ij} is large so that it plays a large role in the contrastive covariance term. In particular, for InfoNCE loss with $\epsilon = 0$, the pairwise importance α takes the following form:

$$\alpha_{ij} = \frac{\exp(-d_{ij}^2/\tau)}{\sum_{j \neq i} \exp(-d_{ij}^2/\tau)} > 0 \tag{6}$$

which means that InfoNCE focuses on (i, j)-pair with small squared distance d_{ij}^2. If both ϕ and ψ are linear, then $\alpha_{ij} = \mathrm{const}$ and $\mathcal{L}$ is a simple subtraction of positive/negative squared distances.

From Thm. 1, an important observation is that when propagating gradient w.r.t. $\boldsymbol{\theta}$ using the objective $\mathcal{E}_\alpha(\boldsymbol{\theta})$ during the backward pass, the gradient does not propagate into $\alpha(\boldsymbol{\theta})$, even if $\alpha(\boldsymbol{\theta})$ is a function of $\boldsymbol{\theta}$ in the forward pass. In fact, in Sec. 6 we show that propagating gradient through $\alpha(\boldsymbol{\theta})$ yields worse empirical performance. This suggests that α should be treated as an *independent* variable when optimizing $\boldsymbol{\theta}$. It turns out that if $\psi(x)$ is an exponential function (as in most cases of Tbl. 1), this is indeed true and α can be determined by a separate optimization procedure:

Theorem 2. *If $\psi(x) = e^{x/\tau}$, then the corresponding pairwise importance α (Eqn. 4) is the solution to the minimization problem:*

$$
\alpha(\boldsymbol{\theta}) = \arg\min_{\alpha \in \mathcal{A}} \mathcal{E}_\alpha(\boldsymbol{\theta}) - \mathcal{R}(\alpha), \qquad \mathcal{A} := \left\{ \alpha : \quad \forall i, \ \sum_{j \neq i} \alpha_{ij} = \tau^{-1} \xi_i \phi'(\xi_i), \ \alpha_{ij} \geq 0 \right\} \quad (7)
$$

Here the regularization $\mathcal{R}(\alpha) = \mathcal{R}_H(\alpha) := 2\tau \sum_{i=1}^N H(\alpha_i.) = -2\tau \sum_{i=1}^N \sum_{j \neq i} \alpha_{ij} \log \alpha_{ij}$.

For InfoNCE, the feasible set $\mathcal{A}$ becomes $\{\alpha : \alpha \geq 0, \sum_{j \neq i} \alpha_{ij} = \xi_i/(\xi_i + \epsilon)\}$. This means that if i-th sample is already well-separated (small intra-augmentation distance d_i and large inter-augmentation distance d_{ij}), then ξ_i is small, the summation of weights $\sum_{j \neq i} \alpha_{ij}$ associated with sample i is also small and such a sample is overall discounted. Setting $\epsilon = 0$ reduces to sample-agnostic constraint (i.e., $\sum_{j \neq i} \alpha_{ij} = 1$).

Thm. 2 leads to a novel perspective of *coordinate-wise optimization* for Contrastive Learning (CL):

Corollary 1 (Contrastive Learning as Coordinate-wise Optimization)**.** *If $\psi(x) = e^{x/\tau}$, minimizing $\mathcal{L}_{\phi,\psi}$ is equivalent to the following iterative procedure:*

$$
\textit{(Min-player } \alpha\textit{)} \qquad\qquad \alpha_t = \arg\min_{\alpha \in \mathcal{A}} \mathcal{E}_\alpha(\boldsymbol{\theta}_t) - \mathcal{R}(\alpha) \qquad\qquad (8a)
$$

$$
\textit{(Max-player } \boldsymbol{\theta}\textit{)} \qquad\qquad \boldsymbol{\theta}_{t+1} = \boldsymbol{\theta}_t + \eta \nabla_{\boldsymbol{\theta}} \mathcal{E}_{\alpha_t}(\boldsymbol{\theta}) \qquad\qquad (8b)
$$

Intuitively, the max player $\boldsymbol{\theta}$ (Eqn. 8b) performs one-step gradient ascent for the objective $\mathcal{E}_\alpha(\boldsymbol{\theta}) - \mathcal{R}(\alpha)$, *learns a representation* to maximize the distance of different samples and minimize the distance of the same sample with different augmentations (as suggested by $\mathbb{C}_\alpha[\boldsymbol{z}, \boldsymbol{z}]$). On the other hand, the "min player" α (Eqn. 8a) finds optimal α analytically, assigning high weights on confusing pairs for "max player" to solve.

Relation to max-min formulation. While Corollary 1 looks very similar to max-min formulation, important differences exist. Different from traditional max-min formulation, in Corollary 1 there is asymmetry between $\boldsymbol{\theta}$ and α. First, $\boldsymbol{\theta}$ only follows one step update along gradient ascent direction of $\max_{\boldsymbol{\theta}} \mathcal{E}_\alpha(\boldsymbol{\theta})$, while α is solved analytically. Second, due to the stop-gradient operator, the gradient of $\boldsymbol{\theta}$ contains no knowledge on how $\boldsymbol{\theta}$ changes α. This prevents $\boldsymbol{\theta}$ from adapting to α's response on changing $\boldsymbol{\theta}$. Both give advantages to min-player α to find the confusing sample pairs more effectively.

Relation to hard-negative samples. While many previous works [25, 36] focus on seeking and putting more weights on hard samples, Corollary 1 shows that contrastive losses already have such mechanism at the batch level, focusing on "hard-negative pairs" beyond hard-negative samples.

From this formulation, different pairwise importance α corresponds to different loss functions within the loss family specified by Eqn. 1, and choosing among this family (i.e., different ϕ and ψ can be regarded as choosing different α when optimizing the *same* objective $\mathcal{E}_\alpha(\boldsymbol{\theta})$. Based on this observation, we now propose the following training framework called $\boldsymbol{\alpha}$**CL**:

Definition 1 (Pair-weighted Contrastive Learning (αCL))**.** *Optimize $\boldsymbol{\theta}$ by gradient ascent: $\boldsymbol{\theta}_{t+1} = \boldsymbol{\theta}_t + \eta \nabla_{\boldsymbol{\theta}} \mathcal{E}_{\mathrm{sg}(\alpha_t)}(\boldsymbol{\theta})$, with the energy $\mathcal{E}_\alpha(\boldsymbol{\theta})$ defined in Thm. 1 and pairwise importance $\alpha_t = \alpha(\boldsymbol{\theta}_t)$.*

In αCL, choosing α can be achieved by either implicitly specifying a regularizer $\mathcal{R}(\alpha)$ and solve Eqn. 8a, or by a direct mapping $\alpha = \alpha(\boldsymbol{\theta})$ without any optimization. This opens a novel revenue for CL loss design. Initial experiments (Sec. 6) show that αCL gives comparable (or even better) downstream performance in CIFAR10 and STL-10, compared to vanilla InfoNCE loss.

Figure 2: Dynamics of CL with multilayer ($L = 5$) linear network (`DeepLin`) with fixed α. Running the training dynamics (Lemma 1) quickly leads to convergence towards the maximal eigenvalue of X_α. For dynamics of singular value of W_l, the largest singular values (solid lines) converges to 1 while the second largest singular values (dashed lines) decay to 0.

4 Representation Learning in Deep Linear CL is PCA

In Corollary 1, optimizing over α is well-understood, since $\mathcal{E}_\alpha(\boldsymbol{\theta})$ is *linear* w.r.t. α and $\mathcal{R}(\alpha)$ in general is a (strong) concave function. As a result, α has a unique optimal. On the other hand, understanding the max player $\max_{\boldsymbol{\theta}} \mathcal{E}_\alpha(\boldsymbol{\theta})$ is important since it performs *representation learning* in CL. It is also a hard problem because of non-convex optimization.

We start with a specific case when $\boldsymbol{z}$ is a deep linear network, i.e., $\boldsymbol{z} = W(\boldsymbol{\theta})\boldsymbol{x}$, where W is the equivalent linear mapping for the deep linear network, and $\boldsymbol{\theta}$ is the parameters to be optimized. Note that this covers many different kinds of deep linear networks, including VGG-like [38], ResNet-like [19] and DenseNet-like [22]. For notation brevity, we define $\mathbb{C}_\alpha[\boldsymbol{x}] := \mathbb{C}_\alpha[\boldsymbol{x}, \boldsymbol{x}]$.

Corollary 2 (Representation learning in Deep Linear CL reparameterizes Principal Component Analysis (PCA))**.** *When $\boldsymbol{z} = W(\boldsymbol{\theta})\boldsymbol{x}$ with a constraint $WW^\top = I$, $\mathcal{E}_\alpha$ is the objective of Principal Component Analysis (PCA) with reparameterization $W = W(\boldsymbol{\theta})$:*

$$\max_{\boldsymbol{\theta}} \mathcal{E}_\alpha(\boldsymbol{\theta}) = \mathrm{tr}(W(\boldsymbol{\theta}) X_\alpha W^\top(\boldsymbol{\theta})) \quad \text{s.t. } WW^\top = I \tag{9}$$

here $X_\alpha := \mathbb{C}_\alpha[\boldsymbol{x}]$ is the contrastive covariance of input $\boldsymbol{x}$.

As a comparison, in traditional Principal Component Analysis, the objective is [29]: $\max_W \mathrm{tr}(W\mathbb{V}_{\mathrm{sample}}[\boldsymbol{x}]W^\top)$ subject to the constraint $WW^\top = I$, where $\mathbb{V}_{\mathrm{sample}}[\boldsymbol{x}]$ is the empirical covariance of the dataset (here it is one batch). Therefore, X_α can be regarded as a generalized covariance matrix, possibly containing negative eigenvalues. In the case of supervised CL (i.e,. pairs from the same/different labels are treated as positive/negative [27]), then it is connected with Fisher's Linear Discriminant Analysis [15].

Here we show a mathematically rigorous connection between CL and dimensional reduction, as suggested intuitively in [17]. Unlike traditional PCA, due to the presence of data augmentation, while symmetric, the contrastive covariance X_α is not necessarily a PSD matrix. Nevertheless, the intuition is the same: to find the direction that corresponds to maximal variation of the data.

While it is interesting to discover that CL with deep linear network is essentially a reparameterization of PCA, it remains elusive that such a reparameterization leads to the same solution of PCA, in particular when the network is deep (and may contain local optima). Also, PCA has an overall end-to-end constraint $WW^\top = I$, while in network training, we instead use normalization layers and it is unclear whether they are equivalent or not.

In this section, we show for a specific deep linear model, almost all its local maxima of Eqn. 9 are global and it indeed solves PCA.

4.1 A concrete deep linear model

We study a concrete deep linear network with parameters/weights $\boldsymbol{\theta} := \{W_l\}_{l=1}^L$:

$$\boldsymbol{z}[i] := W_L W_{L-1} \ldots W_1 \boldsymbol{x}[i] \tag{10}$$

174 Here $W_l \in \mathbb{R}^{n_l \times n_{l-1}}$, n_l is the number of nodes at layer l, $\boldsymbol{z}[i]$ is the output of $\boldsymbol{x}[i]$ and similarly
175 $\boldsymbol{z}[i']$ for $\boldsymbol{x}[i']$. We use $\boldsymbol{\theta}$ to represent the collection of weights at all layers. For convenience, we
176 define the l-th layer activation $\boldsymbol{f}_l[i] = W_l \boldsymbol{f}_{l-1}[i]$. With this notation $\boldsymbol{f}_0[i] = \boldsymbol{x}[i]$ is the input and
177 $\boldsymbol{z}[i] = W_L \boldsymbol{f}_{L-1}[i]$.

178 We call this setting `DeepLin`. The Jacobian matrix $W_{>l} := W_L W_{L-1} \ldots W_{l+1}$ and $W := W_{>0} =$
179 $W_L W_{L-1} \ldots W_1$.

180 **Lemma 1.** *The training dynamics in* `DeepLin` *is* $\dot{W}_l = W_{>l}^\top W_{>l} W_l \mathbb{C}_\alpha[\boldsymbol{f}_{l-1}]$

181 Note that $\mathbb{C}_\alpha[\boldsymbol{f}_0] = \mathbb{C}_\alpha[\boldsymbol{x}] = X_\alpha$. Similar to supervised learning [2, 14], nearby layers are also
182 balanced: $\frac{\mathrm{d}}{\mathrm{d}t}\left(W_l W_l^\top - W_{l+1}^\top W_{l+1}\right) = 0$.

4.2 Normalization Constraints

184 Note that if we just run the training dynamics (Lemma 1) without any constraints, $\|W_l\|_F$ will go to
185 infinity. Fortunately, empirical works already suggest various ways of normalization to stabilize the
186 network training.

187 One popular technique in CL is ℓ_2 normalization. It is often put right after the output of the network
188 and before the loss function $\mathcal{L}$ [9, 16, 20], i.e., $\hat{\boldsymbol{z}}[i] = \boldsymbol{z}[i]/\|\boldsymbol{z}[i]\|_2$. Besides, LayerNorm [4] (i.e.,
189 $\hat{\boldsymbol{f}}[i] = (\boldsymbol{f}[i] - \mathrm{mean}(\boldsymbol{f}[i]))/\mathrm{std}(\boldsymbol{f}[i]))$ is extensively used in Transformer-based models [48]. Here
190 we show that for gradient flow dynamics of MLP models, such normalization layers conserve $\|W_l\|_F$
191 for any l below it, regardless of loss function.

192 **Lemma 2.** *For MLP, if the weight W_l is below a ℓ_2-norm or LayerNorm layer, then $\frac{\mathrm{d}}{\mathrm{d}t}\|W_l\|_F^2 = 0$.*

193 Note that Lemma 2 also holds for nonlinear MLP with reversible activations, which includes ReLU
194 (see SM). Therefore, without loss of generality, we consider the following complete objective for
195 max player with `DeepLin` (here Θ is the constraint set of the weights due to normalization):

$$\max_{\boldsymbol{\theta} \in \Theta} \mathcal{E}_\alpha(\boldsymbol{\theta}) := \mathrm{tr}(W X_\alpha W^\top), \quad \Theta := \{\boldsymbol{\theta} : \|W_l\|_F = 1, 1 \le l \le L\} \tag{11}$$

196

4.3 Representation Learning with `DeepLin` is PCA

198 As one of our main contributions, the following theorem asserts that almost all local optimal solutions
199 of Eqn. 11 are global, and the optimal objective corresponds to the PCA objective. Note that [26, 31]
200 proves no bad local optima for deep linear network in supervised learning, while here we give similar
201 results for CL, and additionally we also give the (simple) rank-1 structure of all local optima.

202 **Theorem 3** (Representation Learning with `DeepLin` is PCA). *If $\lambda_{\max}(X_\alpha) > 0$, then for any local*
203 *maximum $\boldsymbol{\theta} \in \Theta$ of Eqn. 11 whose $W_{>1}^\top W_{>1}$ has distinct maximal eigenvalue:*

204 • *there exists a set of unit vectors $\{\boldsymbol{v}_l\}_{l=0}^L$ so that $W_l = \boldsymbol{v}_l \boldsymbol{v}_{l-1}^\top$ for $1 \le l \le L$, in particular,*
205 *$\boldsymbol{v}_0$ is the unit eigenvector corresponding to $\lambda_{\max}(X_\alpha)$,*

206 • *$\boldsymbol{\theta}$ is global optimal with objective $\mathcal{E}^* = \lambda_{\max}(X_\alpha)$.*

207 **Corollary 3.** *If we additionally use per-filter normalization (i.e., $\|\boldsymbol{w}_{lk}\|_2 = 1/\sqrt{n_l}$), then Thm. 3*
208 *holds and $\boldsymbol{v}_l$ is more constrained: $[\boldsymbol{v}_l]_k = \pm 1/\sqrt{n_l}$ for $1 \le l \le L-1$.*

209 **Remark**. Here we prove that given fixed α, maximizing $\mathcal{E}_\alpha(\boldsymbol{\theta})$ gives rank-1 solutions for deep linear
210 network. This conclusion is an extension of [24], which shows weight collapsing happens if $\boldsymbol{\theta}$ is
211 2-layer linear network and α is fixed. If the pairwise importance α is adversarial, then it may not lead
212 to a rank-1 solution. In fact, α can magnify minimal eigen-directions and change the eigenstructure
213 of X_α continuously. We leave it for future work.

214 Note that the condition that "$W_{>1}^\top W_{>1}$ has distinct maximal eigenvalue" is important. Otherwise
215 there are counterexamples. For example, consider 1-layer linear network $\boldsymbol{z} = W_1 \boldsymbol{x}$, and X_α has
216 duplicated maximal eigenvalues (with $\boldsymbol{u}_1$ and $\boldsymbol{u}_2$ being corresponding orthogonal eigenvectors), then

$W_{>1}^\top W_{>1} = I$ (i.e., it has degenerated eigenvalues), and for any local maximal W_1, its row vector can be arbitrary linear combinations of $\boldsymbol{u}_1$ and $\boldsymbol{u}_2$ and thus W_1 is not rank-1.

Compared to recent works [23] that also relates CL with PCA in linear representation setting using constant α, our Theorem 3 has no statistical assumptions on data distribution and augmentation, and operates on vanilla InfoNCE loss and deep architectures.

5   How Representation Learning Differs in Two-layer ReLU Network

So far we have shown that the max player $\max_{\boldsymbol{\theta}} \mathcal{E}_\alpha(\boldsymbol{\theta}) := \mathrm{tr}(\mathbb{C}_\alpha[\boldsymbol{z}(\boldsymbol{\theta})])$ is essentially a PCA objective when the input-output mapping $\boldsymbol{z} = W(\boldsymbol{\theta})\boldsymbol{x}$ is linear. A natural question arises. What is the benefit of CL if its representation learning component has such a simple nature? Why can it learn a good representation in practice beyond PCA?

For this, nonlinearity is the key but understanding its role is highly nontrivial. For example, when the neural network model is nonlinear, Thm. 1 and Corollary 1 holds but *not* Corollary 2. Therefore, there is not even a well-defined X_α due to the fact that multiple hidden nodes can be switched on/off given different data input. Previous works [37, 13] also show that with nonlinearity, in supervised learning spurious local optima exist.

Here we take a first step to analyze nonlinear cases. We study 2-layer models with ReLU activation $h(x) = \max(x, 0)$. We show that with a proper data assumption, the 2-layer model shares a *modified* version of dynamics with its linear version, and the contrastive covariance term X_α (and its eigenstructure) remains well-defined and useful in nonlinear case.

5.1   The 2-layer ReLU network and data model

We consider the bottom-layer weight $W_1 = [\boldsymbol{w}_{11}, \boldsymbol{w}_{12}, \ldots, \boldsymbol{w}_{1K}]^\top$ with $\boldsymbol{w}_{1k}$ being the k-th filter. For brevity, let $K = n_1$ be the number of hidden nodes. We still consider solution in the constraint set Θ (Eqn. 11), since Lemma 2 still holds for ReLU networks. This model is named `ReLU2Layer`.

In addition, we assume the following data model:

Assumption 1 (Orthogonal mixture model within receptive field R_k). *There exists a set of orthonormal bases $\{\bar{\boldsymbol{x}}_m\}_{m=1}^M$ so that any input data $\boldsymbol{x}[i] = \sum_m a_m[i]\bar{\boldsymbol{x}}_m$ satisfies the property that $a_m[i]$ is **Nonnegative**: $a_m[i] \geq 0$, **One-hot**: for any k, $a_m[i] > 0$ for at most one m and **Augmentation** only scales $\boldsymbol{x}_k$ by a (sample-dependent) factor, i.e., $\boldsymbol{x}[i'] = \gamma[i]\boldsymbol{x}[i]$ with $\gamma[i] > 0$.*

Since all $\boldsymbol{x}$ appears in the inner-product with the weight vectors $\boldsymbol{w}_{1k}$, with a rotation of coordination, we can just set $\bar{\boldsymbol{x}}_m = \boldsymbol{e}_m$, where $\boldsymbol{e}_m$ is the one-hot vector with m-th component being 1. In this case, $\boldsymbol{x} \geq 0$ is always a one-hot vector with only at most only one positive entry.

Intuitively, the model is motivated by sparsity: in each instantiation of $\boldsymbol{x}$, there are very small number of activated modes and their linear combination becomes the input signal $\boldsymbol{x}$. As we shall see, even with this simple model, the dynamics of ReLU network behaves very differently from the linear case.

With this assumption, we only need to consider nonnegative low-layer weights and X_α is still a valid quantity for `ReLU2Layer`:

Lemma 3 (Evaluation of `ReLU2Layer`). *If Assumption 1 holds, setting $\boldsymbol{w}_{1k}' = \max(\boldsymbol{w}_{1k}, 0)$ won't change the output of `ReLU2Layer`. Furthermore, if $W_1 \geq 0$, then the formula for linear network $\mathcal{E}_\alpha = \mathrm{tr}(W_2 W_1 X_\alpha W_1^\top W_2^\top)$ still works for `ReLU2Layer`.*

On the other hand, sharing the energy function $\mathcal{E}_\alpha$ does not mean `ReLU2Layer` is completely identical to its linear version. In fact, the dynamics follows its linear counterparts, but with important modifications:

Theorem 4 (Dynamics of `ReLU2Layer`). *If Assumption 1 holds, then the dynamics of `ReLU2Layer` with $\boldsymbol{w}_{1k} \geq 0$ is equivalent to linear dynamics with the **Sticky Weight rule**: any component that reaches 0 stays 0.*

Figure 3: Theorem 6 shows that training `ReLU2Layer` could lead to more diverse hidden weight patterns beyond rank-1 solution obtained in the linear case (shown in right two figures: converged W_1 and $W_2^\top W_2$).

As we will see, this modification leads to very different dynamics and local optima in `ReLU2Layer` from linear cases, even when there is only one ReLU node.

5.2 Dynamics in One ReLU node

Now we consider the dynamics of the simplest case: `ReLU2Layer` with only 1 hidden node. In this case, $W_{>1}^\top W_{>1}$ is a scalar and thus $W_2^\top W_2 = \text{tr}(W_2^\top W_2) = 1$. We only need to consider $\boldsymbol{w}_1 \in \mathbb{R}^{n_1}$, which is the only weight vector in the lower layer, under the constraint $\|W_1\|_F = \|\boldsymbol{w}_1\|_2 = 1$ (Eqn. 11). We denote this setting as `ReLU2Layer1Hid`.

The dynamics now becomes very different from linear setting. Under linear network, according to Theorem 3, $\boldsymbol{w}_1$ converges to the largest eigenvector of $X_\alpha = \mathbb{C}_\alpha[\boldsymbol{x}_1]$. For `ReLU2Layer1Hid`, situation differs drastically:

Theorem 5. *If Assumption 1 holds, then in* `ReLU2Layer1Hid`*,* $\boldsymbol{w}_1 \to \boldsymbol{e}_m$ *for certain* m.

Intuitively, this theorem is achieved by closely tracing the dynamics. When the number of positive entries of $\boldsymbol{w}_1$ is more than 1, the linear dynamics always hits the boundary of the polytope $\boldsymbol{w}_1 \geq 0$, making one of its entry be zero, and stick to zero due to sticky weight rule. This procedure repeats until there is only one survival positive entry in $\boldsymbol{w}_1$.

Overall, this simple case already shows that nonlinear landscape can lead to many local optima: for any m, $\boldsymbol{w}_1 = \boldsymbol{e}_m$ is one local optimal. Which one the training falls into depends on weight initialization, and critically affects the properties of per-trained models.

5.3 Multiple hidden nodes

For complicated situations like multiple hidden units, completely characterizing the training dynamics like Theorem 5 becomes hard (if not impossible). Instead, we focus on fixed point analysis.

For deep linear model, using multiple hidden units does not lead to any better solutions. According to Thm. 3, at local optimal, $W_1 = \boldsymbol{v}_1 \boldsymbol{v}_0^\top$. This means that the weights $\boldsymbol{w}_{1k}$, which are row vectors of W_1, are just a scaled version of the maximal eigenvector $\boldsymbol{v}_0$ of X_α. Moreover, this is independent of the eigenstructure of X_α as long as $\lambda_{\max}(X_\alpha) > 0$.

In `ReLU2Layer`, the situation is a bit different. Thm. 6 shows that these hidden nodes are (slightly) more diverse. Fig. 3 shows one such example. The intuition here is that in nonlinear case, rank-1 structure of the critical points may be replaced with low-rank structures.

Theorem 6 (`ReLU2Layer` encourages diversity)**.** *If Assumption 1 holds, then for any local optimal* $(W_2, W_1) \in \Theta$ *of* `ReLU2Layer` *with* $\mathcal{E} > 0$*, either* $W_1 = \boldsymbol{v}\boldsymbol{e}_m^\top$ *for some* m *and* $\boldsymbol{v} \geq 0$*, or* $\text{rank}(W_1) > 1$.

6 Experiments

We evaluate our αCL framework (Def. 1) in CIFAR10 [30] and STL-10 [11] with ResNet18 [21], and compare the downstream performance of multiple losses, with regularizers taking the form of $\mathcal{R}(\alpha) = \sum_i \sum_{j \neq i} r(\alpha_{ij})$ with a constraint $\sum_{j \neq i} \alpha_{ij} = 1$. Here r can be different concave functions:

	CIFAR-10			STL-10		
	100 epochs	300 epochs	500 epochs	100 epochs	300 epochs	500 epochs
$\mathcal{L}_{quadratic}$	63.59 ± 2.53	73.02 ± 0.80	73.58 ± 0.82	55.59 ± 4.00	64.97 ± 1.45	67.28 ± 1.21
$\mathcal{L}_{nce}$	84.06 ± 0.30	87.63 ± 0.13	87.86 ± 0.12	78.46 ± 0.24	82.49 ± 0.26	83.70 ± 0.12
backprop $\alpha(\boldsymbol{\theta})$	83.42 ± 0.25	87.18 ± 0.19	87.48 ± 0.21	77.88 ± 0.17	81.86 ± 0.30	83.19 ± 0.16
αCL-r_H	84.27 ± 0.24	87.75 ± 0.25	87.92 ± 0.24	78.53 ± 0.35	82.62 ± 0.15	83.74 ± 0.18
αCL-r_γ	83.72 ± 0.19	87.51 ± 0.11	87.69 ± 0.09	78.22 ± 0.28	82.19 ± 0.52	83.47 ± 0.34
αCL-r_s	84.72 ± 0.10	86.62 ± 0.17	86.74 ± 0.15	76.95 ± 1.06	80.64 ± 0.77	81.65 ± 0.59
αCL-direct	$\mathbf{85.09 \pm 0.13}$	$\mathbf{88.00 \pm 0.12}$	$\mathbf{88.16 \pm 0.12}$	$\mathbf{79.38 \pm 0.16}$	$\mathbf{82.99 \pm 0.15}$	$\mathbf{84.06 \pm 0.24}$

Table 1: Comparison over multiple loss formulations. Top-1 accuracy with linear evaluation protocol. The temperature $\tau = 0.5$. **Bold** is highest performance and blue is second highest. Each setting is repeated 5 times with different random seeds.

- (αCL-r_H) Entropy regularizer $r_H(\alpha_{ij}) = -2\tau\alpha_{ij}\log\alpha_{ij}$;

- (αCL-r_γ) Inverse regularizers $r_\gamma(\alpha_{ij}) = \frac{2\tau}{1-\gamma}\alpha_{ij}^{1-\gamma}$ ($\gamma > 1$).

- (αCL-r_s) Square regularizer $r_s(\alpha_{ij}) = -\frac{\tau}{2}\alpha_{ij}^2$.

Besides, we also compare with the following:

- Minimizing InfoNCE or quadratic loss: $\min_{\boldsymbol{\theta}} \mathcal{L}(\boldsymbol{\theta})$ for $\mathcal{L} \in \{\mathcal{L}_{nce}, \mathcal{L}_{quadratic}\}$.

- Setting α as InfoNCE (Eqn. 6) and backpropagates through $\alpha = \alpha(\boldsymbol{\theta})$ with respect to $\boldsymbol{\theta}$.

- (αCL-direct) Directly setting α: $\alpha_{ij} = \exp(-d_{ij}^p/\tau)$ ($p > 1$).

For inverse regularizer r_γ, we pick $\gamma = 2$ and $\tau = 0.5$; for direct-set α, we pick $p = 4$ and $\tau = 0.5$; for square regularizer, we use $\tau = 5$. All training is performed with Adam [28] optimizer with learning rate 0.01. Code is written in PyTorch and a single modern GPU suffices for the experiments.

The results are shown in Tbl. 1. We can see that (1) backpropagating through $\alpha(\boldsymbol{\theta})$ is worse, justifying our perspective of coordinate-wise optimization, (2) our proposed αCL works for different regularizers, (3) using different regularizer leads to comparable or better performance than original InfoNCE $\mathcal{L}_{nce}$, (4) the pairwise importance α does not even need to come from a minimization process. Instead, we can directly set α based on pairwise squared distances d_{ij}^2 and d_i^2. For αCL-direct, normalizing α_{ij} yields slightly worse performance.

An interesting pattern is that for strong performance, $\frac{\mathrm{d}r}{\mathrm{d}\alpha_{ij}}$ should go to $+\infty$ when $\alpha_{ij} \to 0$. Regularizers that do not satisfy this condition (e.g., squared regularizer r_s) may not work as well. We leave thorough studies as future works.

7 Conclusion and Future Work

We provide a novel perspective of contrastive learning (CL) via the lens of coordinate-wise optimization and propose a unified framework called αCL that not only covers a broad family of loss functions including InfoNCE, but also allows a direct set of importance of sample pairs. Preliminary experiments on CIFAR10/STL-10 show comparable/better performance with the new loss than InfoNCE. Furthermore, we prove that with deep linear networks, the representation learning part is equivalent to Principal Component Analysis (PCA). In addition, we also extend our analysis to representation learning in 2-layer ReLU network, shedding light on the important difference in representation learning for linear/nonlinear cases.

Future work. First, our framework αCL turns various loss functions into a unified framework with different choices of pairwise importance α, potentially expanding a new design space for CL loss design. Second, our analysis of ReLU networks is a first step towards understanding how representation learning is performed in nonlinear networks. A more general theory with fewer assumptions (e.g., getting rid of Assumption 1) is the next step. Finally, while we mainly focus on representation learning with fixed pairwise importance α, in the actual training, α and $\boldsymbol{\theta}$ change concurrently. Understanding their interactions is an important next step.

References

[1] Zeyuan Allen-Zhu, Yuanzhi Li, and Yingyu Liang. Learning and generalization in overparameterized neural networks, going beyond two layers. *arXiv preprint arXiv:1811.04918*, 2018.

[2] Sanjeev Arora, Nadav Cohen, and Elad Hazan. On the optimization of deep networks: Implicit acceleration by overparameterization. In *International Conference on Machine Learning*, pages 244–253. PMLR, 2018.

[3] Sanjeev Arora, Hrishikesh Khandeparkar, Mikhail Khodak, Orestis Plevrakis, and Nikunj Saunshi. A theoretical analysis of contrastive unsupervised representation learning. *arXiv preprint arXiv:1902.09229*, 2019.

[4] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[5] Pierre Baldi and Kurt Hornik. Neural networks and principal component analysis: Learning from examples without local minima. *Neural networks*, 2(1):53–58, 1989.

[6] Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeshwar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and Devon Hjelm. Mutual information neural estimation. In *International Conference on Machine Learning*, pages 531–540. PMLR, 2018.

[7] Mathilde Caron, Piotr Bojanowski, Armand Joulin, and M. Douze. Deep clustering for unsupervised learning of visual features. In *ECCV*, 2018.

[8] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *NeurIPS*, 2020.

[9] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[10] Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *CVPR*, 2020.

[11] Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *International conference on artificial intelligence and statistics*, 2011.

[12] Juan M Coria, Hervé Bredin, Sahar Ghannay, and Sophie Rosset. A comparison of metric learning loss functions for end-to-end speaker verification. In *International Conference on Statistical Language and Speech Processing*, pages 137–148. Springer, 2020.

[13] Simon Du, Jason Lee, Yuandong Tian, Aarti Singh, and Barnabas Poczos. Gradient descent learns one-hidden-layer cnn: Don't be afraid of spurious local minima. In *International Conference on Machine Learning*, pages 1339–1348. PMLR, 2018.

[14] Simon S Du, Wei Hu, and Jason D Lee. Algorithmic regularization in learning deep homogeneous models: Layers are automatically balanced. *arXiv preprint arXiv:1806.00900*, 2018.

[15] Ronald A Fisher. The use of multiple measurements in taxonomic problems. *Annals of eugenics*, 7(2):179–188, 1936.

[16] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *NeurIPS*, 2020.

[17] Raia Hadsell, Sumit Chopra, and Yann LeCun. Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, volume 2, pages 1735–1742. IEEE, 2006.

[18] Jeff Z HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. *NeurIPS*, 2021.

[19] Moritz Hardt and Tengyu Ma. Identity matters in deep learning. *ICLR*, 2017.

[20] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, 2020.

[21] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[22] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017.

[23] Wenlong Ji, Zhun Deng, Ryumei Nakada, James Zou, and Linjun Zhang. The power of contrast for feature learning: A theoretical analysis. *arXiv preprint arXiv:2110.02473*, 2021.

[24] Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. *ICLR*, 2022.

[25] Yannis Kalantidis, Mert Bulent Sariyildiz, Noe Pion, Philippe Weinzaepfel, and Diane Larlus. Hard negative mixing for contrastive learning. *NeurIPS*, 2020.

[26] Kenji Kawaguchi. Deep learning without poor local minima. *NeurIPS*, 2016.

[27] Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *NeurIPS*, 2020.

[28] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[29] Effrosini Kokiopoulou, Jie Chen, and Yousef Saad. Trace optimization and eigenproblems in dimension reduction methods. *Numerical Linear Algebra with Applications*, 18(3):565–602, 2011.

[30] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[31] Thomas Laurent and James Brecht. Deep linear networks with arbitrary loss: All local minima are global. In *International conference on machine learning*, pages 2902–2907. PMLR, 2018.

[32] Jason D Lee, Qi Lei, Nikunj Saunshi, and Jiacheng Zhuo. Predicting what you already know helps: Provable self-supervised learning. *Advances in Neural Information Processing Systems*, 34, 2021.

[33] Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *CVPR*, 2020.

[34] Hyun Oh Song, Yu Xiang, Stefanie Jegelka, and Silvio Savarese. Deep metric learning via lifted structured feature embedding. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4004–4012, 2016.

[35] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[36] Joshua Robinson, Ching-Yao Chuang, Suvrit Sra, and Stefanie Jegelka. Contrastive learning with hard negative samples. *ICLR*, 2021.

[37] Itay Safran and Ohad Shamir. Spurious local minima are common in two-layer relu neural networks. In *International Conference on Machine Learning*, pages 4433–4441. PMLR, 2018.

[38] Andrew M Saxe, James L McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *ICLR*, 2014.

[39] Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In *CVPR*, 2015.

[40] Kihyuk Sohn. Improved deep metric learning with multi-class n-pair loss objective. In *Advances in neural information processing systems*, pages 1857–1865, 2016.

[41] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XI 16*, pages 776–794. Springer, 2020.

[42] Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? *NeurIPS*, 2020.

[43] Yuandong Tian. Student specialization in deep relu networks with finite width and input dimension. *ICML*, 2020.

[44] Yuandong Tian, Lantao Yu, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning with dual deep networks. *arXiv preprint arXiv:2010.00578*, 2020.

[45] Zixin Wen and Yuanzhi Li. Toward understanding the feature learning process of self-supervised contrastive learning. *arXiv preprint arXiv:2105.15134*, 2021.

[46] Svante Wold, Kim Esbensen, and Paul Geladi. Principal component analysis. *Chemometrics and intelligent laboratory systems*, 2(1-3):37–52, 1987.

[47] Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3733–3742, 2018.

[48] Ruibin Xiong, Yunchang Yang, Di He, Kai Zheng, Shuxin Zheng, Chen Xing, Huishuai Zhang, Yanyan Lan, Liwei Wang, and Tieyan Liu. On layer normalization in the transformer architecture. In *International Conference on Machine Learning*, pages 10524–10533. PMLR, 2020.

[49] Chun-Hsiao Yeh, Cheng-Yao Hong, Yen-Chi Hsu, Tyng-Luh Liu, Yubei Chen, and Yann LeCun. Decoupled contrastive learning. *arXiv preprint arXiv:2110.06848*, 2021.

[50] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. *arXiv preprint arxiv:2103.03230*, 2021.

[51] Yi Zhou and Yingbin Liang. Critical points of linear neural networks: Analytical forms and landscape properties. In *International Conference on Learning Representations*, 2018.