An Information-theoretic Perspective of Hierarchical Clustering

Abstract

A combinatorial cost function for hierarchical clustering was introduced by Dasgupta [10]. It has received great attention and several new cost functions from similar combinatorial perspective have been proposed. In this paper, we investigate hierarchical clustering from the *information-theoretic* perspective and formulate a new objective function. We also establish the relationship between these two perspectives. In algorithmic aspect, we present two algorithms for expander-like and well-clustered cardinality weighted graphs, respectively, and show that both of them achieve $O(1)$-approximation for our new objective function. For practical use, we consider non-binary hierarchical clustering problem. We get rid of the traditional top-down and bottom-up frameworks, and present a new one. Our new framework stratifies the sparsest level of a cluster tree recursively in guide with our objective function. Our algorithm called HCSE outputs a k-level cluster tree by an interpretable mechanism to choose k automatically without any hyperparameter. Our experimental results on synthetic datasets show that HCSE has its own superiority in finding the intrinsic number of hierarchies, and the results on real datasets show that HCSE also achieves competitive costs over the popular non-binary hierarchical clustering algorithms LOUVAIN and HLP.

1 Introduction

Hierarchical clustering for graphs plays an important role in the structural analysis of a given data set. Understanding hierarchical structures on the levels of multiple granularities is fundamental in various disciplines including artificial intelligence, physics, biology, sociology, etc [4, 11, 13, 9]. Hierarchical clustering requires a cluster tree that represents a recursive partitioning of a graph into smaller clusters as the tree nodes get deeper. A leaf represents a graph node while a non-leaf node represents a cluster containing its descendant leaves. The root is the largest one containing all leaves.

Clustering is usually formulated as an optimization problem with some objective function. For hierarchical clustering, no cost function with a clear and reasonable combinatorial explanation was developed until Dasgupta [10] introduced a cost function for cluster trees. In this definition, similarity or dissimilarity between data points is represented by weighted edges. Taking the similarity-based metrics as an example, a cluster is a set of nodes with relatively denser intra-links compared with its inter-links, and in a good cluster tree, heavier edges tend to connect leaves whose lowest common ancestor (LCA) is as deep as possible. This intuition leads to Dasgupta's cost function that is a bilinear combination of edge weights and the sizes of corresponding LCAs.

Motivated by Dasgupta's cost function, Cohen-Addad et al. [8] proposed admissible cost functions. In their definition, the size of each LCA in Dasgupta's objective is generalized to be a function of the sizes of its left and right children. For all similarity-based graphs generated from a minimal ultrametric, a cluster tree achieves the minimum cost if and only if it is a generating tree that is a

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

"natural" ground truth tree in an axiomatic sense therein. A necessary condition of admissibility of an objective function is that it achieves the same value for every cluster tree for a uniformly weighted clique that has no structure in common sense. However, any slight deviation of edge weights would generally separate the two end-points of a light edge on a high level of its optimal (similarity-based) cluster tree. Thus, it seems that admissible objective functions, which take Dasgupta's cost function as a specific form, ought to be an unchallenged criterion in evaluating cluster trees since they are formulated by an axiomatic approach.

However, an admissible cost function seems imperfect in practice. The arbitrariness of optima of cluster trees for cliques indicates that the division of each internal node on an optimal cluster tree totally neglects the *balance* of its two children. Edge weight is the unique factor that decides the structure of optimal trees. But a balanced tree is commonly considered as an ideal candidate in hierarchical clustering compared to an unbalanced one. Even clustering for cliques, a balanced partition should be preferable for each internal node. At least, the height of an optimal cluster tree which is logarithm of graph size n is intuitively more reasonable than that of a caterpillar shaped cluster tree whose height is $n - 1$. Moreover, a simple proof would imply that the optimal cluster tree for any connected graphs is binary. This property is not always useful in practice since a real system usually has its inherent number of hierarchies and a natural partition for each internal cluster. For instance, the natural levels of administrative division in a country is usually intrinsic, and it is not suitable to differentiate hierarchies for parallel cities in the same state. This structure cannot be obtained by simply minimizing admissible cost functions.

In this paper, we investigate the hierarchical clustering from the perspective of information theory. Our study is based on Li and Pan's structural information theory [14] whose core concept named structural entropy measures the complexity of hierarchical networks. We summarize our contributions as follows.

(1) We formulate **a new objective function from the information-theoretic perspective**, which builds the bridge for combinatorial and information-theoretic perspectives for hierarchical clustering. For this cost function, the balance of cluster trees will be involved naturally as a factor just like we design optimal codes, for which the balance of probability over objects is fundamental in constructing an efficient coding tree. We also define cluster trees with a specific height, which is coincident with our cognition of natural clustering.

(2) For our new objective function, we present **two polynomial-time approximation algorithms** respectively for two cases of the conductance $\Phi(G)$ of a cardinality weighted graph G. Our first result shows that *any* cluster tree of G has a approximation factor $O(\Phi(G)^{-1})$ (Theorem 3.1). So a "Huffman-merge" heuristic that solely depends on the degrees of vertices achieves this guarantee, and it achieves $O(1)$-approximation when $\Phi(G)$ is a constant. The second result is a $O(1)$-approximation algorithm for G that can be well clustered into a constant number of expanders (Theorem 3.2). The main idea of this algorithm is inspired by very rencent Manghiuc and Sun's work [15], and our approximation factors for our new objective also match their results in these two cases.

(3) For practical use, we develop **a new interpretable framework for natural hierarchical clustering** that outputs a non-binary cluster tree. The idea of our framework is essentially different from the traditional recursive division or agglomeration ones. In our framework, the *sparsest level* of the cluster tree is stratified recursively. This coincide with the intuition that when we differentiate the hierarchies of a complex system, the clearest level should be stratified first, rather than in a rigid divisive or agglomerative fashion. Therefore, this framework has much better interpretability than the traditional ones.

(4) We develop **a new non-binary clustering algorithm** (HCSE) under the new clustering framework. To find the sparsest level in each iteration, we formulate two basic operations called *stretch* and *compress*, respectively. HCSE terminates when a specific criterion that intuitively coincides with the natural hierarchies is met, and *no* hyperparameter is needed. Our extensive experiments on both synthetic and real datasets demonstrate that HCSE outperforms the present popular heuristic algorithms LOUVAIN [3] and HLP [19]. These two algorithms proceed simply by recursively invoking flat clustering algorithms based on modularity and label propagation, respectively, and the hierarchy number is solely determined by the number of rounds when the algorithm terminates. So their interpretability is quite poor. Our experimental results on synthetic datasets show that HCSE has a great advantage in finding the intrinsic number of hierarchies, and the results on real datasets show that HCSE achieves much better costs than HLP and competitive costs to LOUVAIN.

Related work. The first combinatorial objective function was proposed by Dasgupta [10]. Along with this line of study, several alternative objectives have been presented. All of them are bilinear functions of edge weights and some function of the corresponding LCAs. For Dasgupta's cost function and for the worst case study, Dasgupta showed that a recursively bipartition applying Arora's seminal algorithm for sparsest cut problem [2] yields $O(\log^{1.5} n)$-approximation, and it was improved by [20] and [5, 8] to $O(\log n)$ and $\sqrt{\log n}$, respectively. It is NP-hard to optimize the cluster tree [10] and even a $O(1)$-approximation is impossible under the Small Set Expansion hypothesis [20, 5]. Beyond the worst case, Cohen-Addad et al. [8] showed that a SVD-based algorithm achieves a $O(1 + o(1))$-approximation for the stochastic block model with high probability. Manghiuc and Sun [15] presented a $O(1)$-appromation algorithm for more generalized well-clustered graphs. The outline of their method is to utilize a flat clustering algorithm [12] to obtain the underlying clusters first, and then some relatively easy heuristics for clustering in and out of these clusters are enough for the guarantee. Our proof follows this route also.

For other lines of this study, Moseley and Wang [16] studied the dual of Dasgupta's cost function and showed that the average-linkage algorithm achieves a $(1/3)$-approximation. This factor has been improved by a series of works to 0.336 [6], 0.4246 [7] and 0.585 [1], respectively. Cohen-Addad et al. [8] considered maximization of Dasgupta's cost function for the dissimilarity-based metrics. They proved that the average-link and random partitioning algorithms achieve a $(2/3)$-approximation, which has been improved to 0.667 [6], 0.716 [18] and 0.74 [17], respectively.

For non-binary cluster tree construction, the most popular algorithm for practical use is LOUVAIN [3]. More recently, a hierarchical label propagation based algorithm HLP has been presented [19]. Both of these two algorithms construct a non-binary cluster tree with the same framework, that is, the hierarchies are formed from bottom to top one by one. In each round, they invoke different flat clustering algorithms, Modularity and Label Propagation, respectively.

2   A cost function from information-theoretic perspective

In this section, we introduce Li and Pan's structural information theory [14] and the combinatorial cost functions of Dasgupta [10] and Cohen-Addad et al. [8]. Then we propose a new cost function that is developed from structural information theory and establish the relationship between the information-theoretic and combinatorial perspectives.

Notations. Let $G = (V, E, w)$ be an undirected weighted graph with a set of vertices V, a set of edges E and a weight function $w : E \to \mathbb{R}^+$, where $\mathbb{R}^+$ denotes the set of all positive real numbers. An unweighted multigraph can be viewed as a cardinality weighted one whose edge weight is the number of parallel edges. For each vertex $u \in V$, denote by $d_u = \sum_{(u,v) \in E} w(u, v)$ the weighted degree of u. For a subset of vertices $S \subseteq V$, define the volume of S to be the sum of degrees of vertices. We denote it by $\mathrm{vol}(S) = \sum_{u \in S} d_u$. We denote by $G[S]$ the subgraph by S. A cluster tree T for graph G is a rooted tree with $|V|$ leaves, each of which is labeled by a distinct vertex $v \in V$. Each non-leaf node on T is labeled by a subset S of V that consists of all the leaves treating S as ancestor. For each node α on T, denote by α^- the parent of α. For each pair of leaves u and v, denote by $u \vee v$ the LCA of them on T.

Structural entropy of graphs. Because of the tense space limit, we just give the definition of the core concept structural entropy in structural information theory. The idea of this definition is briefly introduced in Appendix A. Readers could also refer to [14] for more information on this theory.

Given a weighted graph $G = (V, E, w)$ and a cluster tree T for G, the *structural entropy of G on T* is defined as

$$\mathcal{H}^T(G) = -\sum_{\alpha \in T} \frac{g_\alpha}{\mathrm{vol}(V)} \log \frac{\mathrm{vol}(\alpha)}{\mathrm{vol}(\alpha^-)},^1$$

where α^- denotes the parent of tree node α, and g_α denotes the sum of weights of edges in G with exactly one end-point in the set of vertices corresponding to α. The *structural entropy of G* is defined as the minimum one among all cluster trees, denoted by $\mathcal{H}(G) = \min_T \{\mathcal{H}^T(G)\}$.

---

[1] For notational convenience, for the root λ of T, set $\lambda^- = \lambda$. So the term for λ in the summation is 0. In this paper, the omitted base of logarithm is always 2.

Combinatorial explanation of structural entropy. The cost function of a cluster tree T for graph $G = (V, E)$ introduced by Dasgupta [10] is defined to be $c^T(G) = \sum_{(u,v) \in E} w(u,v)|u \vee v|$. The admissible cost function introduced by Cohen-Addad et al. [8] generalizes the term $|u \vee v|$ in the definition of $c^T(G)$ to be a general function $g(|u|, |v|)$, for which Dasgupta defined $g(x, y) = x + y$. For both definitions, the optimal hierarchical clustering of G is in correspondence with a cluster tree of minimum cost in the combinatorial sense that heavy edges are cut as far down the tree as possible. The following proposition establishes the relationship between structural entropy and this kind of combinatorial form of cost functions.

Proposition 2.1. *For a weighted graph $G = (V, E, w)$, minimizing $\mathcal{H}^T(G)$ (over T) is equivalent to minimizing the cost function*

$$cost^T(G) = \sum_{(u,v) \in E} w(u,v) \log vol(u \vee v). \tag{1}$$

We defer the proof of Proposition 2.1 to Appendix B. We call cost(SE) the cost function in Proposition 2.1 from now on. Proposition 2.1 indicates that when we view g as a function of vertices rather than that of their numbers and define $g(u, v) = \log vol(u \vee v)$, the "admissible" function becomes equivalent to structural entropy in evaluating cluster trees, although it is not admissible any more.

So what is the difference between these two cost functions? As stated by Cohen-Addad et al. [8], an important axiomatic hypothesis for admissible function, thus also for Dasgupta's cost function, is that the cost for every binary cluster tree of an unweighted clique is identical. So any binary tree for clustering on cliques is reasonable, which coincides with the common sense that structureless datasets can be organized hierarchically free. However, for structural entropy, the following theorem indicates that balanced organization is of importance even though for structureless dataset.

Proposition 2.2. *For any positive integer n, let K_n be the clique of n vertices with identical weight on every edge. Then a cluster tree T of K_n achieves minimum structural entropy if and only if T is a balanced binary tree, that is, the two children clusters of each sub-tree of T have difference in size at most 1.*

The proof of Proposition 2.2 is a bit technical, and we defer it to Appendix C. The intuition behind Proposition 2.2 is that balanced codes are the most efficient encoding scheme for unrelated data. So the codewords of the random walk that jumps freely among clusters on each level of a cluster tree have the minimum average length if all the clusters on this level are in balance.

It is worth noting that the admissible function introduced by Cohen-Addad et al. [8] is defined from the viewpoint that a generating tree T of a similarity-based graph G that is generated from a minimal ultrametric achieves the minimum cost. In this definition, the monotonicity of edge weights between clusters on each level from bottom to top on T, which is given by Cohen-Addad et al. [8] as a property of a "natural" ground-truth hierarchical clustering, is the unique factor when evaluating T. However, Proposition 2.2 implies that for cost(SE), besides cluster weights, the balance of cluster trees is implicitly involved as another factor. Moreover, for cliques, the minimum cost should be achieved on every subtree, which makes an optimal cluster tree balanced everywhere. This optimal clustering for cliques is also robust in the sense that a slight perturbation to the minimal ultrametric, which can be considered as slight variations to the weights of a batch of edges, will not change the optimal cluster tree structure wildly due to the holdback force of balance.

3 Approximation algorithms for SE-based cost function

In this section, we present approximation algorithms for expander-like and well-clustered graphs, respectively. These algorithms work for cardinality edge weights (e.g. the multiplicity of edges).

Why cardinality weights? In general, the term $\log(u \vee v)$ in Eq. 1 and thus cost(SE) may be negative when the volume of $u \vee v$ varies, which may lead to pathosis in approximation analysis. The cardinality weight function w is at least one, which makes cost(SE) non-negative. The dependence of cost(SE) on the scale of edge weights violates the scale-invariance principle. However, we emphasize that $\mathcal{H}^T(G)$ is scale-invariant and Theorem 2.1 holds for any scale variation. In this paper, we present approximation algorithms for cost(SE) in well-defined settings.

Theorem 3.1. *For any cardinality weighted graph $G = (V, E, w)$ with conductance Φ_G, it holds that any cluster tree has a cost $O(\Phi(G)^{-1}) \cdot OPT$.*

We defer the proof of Theorem 3.1 to Appendix D. When $\Phi(G)$ is as large as a constant, Theorem 3.1 implies that any cluster tree achieves $O(1)$-approximation for expanders. Thus, the balance of a cluster tree has a significant impact on its cost. Considering balance as an important factor, we present a Huffman-merging heuristic (Algorithm 1). It will serve as a subroutine for the algorithm for well-clustered graphs.

Algorithm 1: HuffmanMerge

Input: a graph $G = (V, E, w)$
Output: A cluster tree T of G
1 Create n singleton trees;
2 **while** *there are at least two trees* **do**
3 $\quad$ Select the two trees T_1 and T_2 with the least volumes;
4 $\quad$ Construct a new tree T_0 with T_1 and T_2 as two subtrees of the root;
5 **Return** the resulting binary tree T_0.

Next, we consider well-clustered graphs that are composed by a collection of densely-connected components with high inner conductance and weakly interconnections. Our settings for well-clustered graphs is the same as those in [15]. We start from the following (Φ_{in}, Φ_{out})-decomposition presented by Gharan and Trevisan [12]. Let λ_k be the k-th smallest eigenvalue of the normalized Laplacian matrix of G.

Lemma 3.1. *([12], Theorem 1.5) Let $G = (V, E, w)$ be a graph such that $\lambda_k > 0$, for some $k \geq 1$. Then, there is a local search algorithm that finds a l-partition $\{P_i\}_{i=1}^l$ of V, for some $l < k$, such that for every $1 \leq i \leq l$, $\Phi_G(P_i) = \mathcal{O}(k^6 \sqrt{\lambda_{k-1}})$ and $\Phi(G[P_i]) = \Omega(\lambda_k^2/k^4)$.*

Lemma 3.1 implies that, when graph G exhibits a clear clustering structure, there is a partition $\{P_i\}_{i=1}^l$ of V such that for each P_i both the outer and inner conductance can be bounded. This is one of the most crucial insights that we can use $\{P_i\}_{i=1}^l$ directly to construct a cluster tree.

For a high-level description, our algorithm consists of two phases: Partition and Merge. In the Partition phase, it invokes the algorithm in Lemma 3.1 to partion V into sets $\{P_i\}_{i=1}^l$. In the Merge phase it combines the trees in a "caterpillar style" according to an increasing order of there volume. This algorithm is described as Algorithm 2.

Algorithm 2: CaterpillarMerge

Input: A graph $G = (V, E, w)$, an integer $k \geq 2$ such that $\lambda_k > 0$
Output: A cluster tree T of G
1 Apply the partitioning algorithm in Lemma 3.1 on input (G, k) to obtain $\{P_i\}_{i=1}^l$ for some $l < k$;
2 Sort $P_1, ..., P_l$ be such that $\text{vol}_G(P_i) \leq \text{vol}_G(P_{i+1})$, for all $1 \leq i < l$;
3 Let $T_i = \text{HuffmanMerge}(G[P_i])$;
4 Initialize $T = T_1$;
5 **for** $i = 2, ..., l$ **do**
6 $\quad$ Let T be the tree with T and T_i as its two children;
7 **Return** T.

Note that Algorithm 2 degenerates to Algorithm 1 when $k = 2$. For the approximation guarantee, we have the following theorem.

Theorem 3.2. *Let $G = (V, E, w)$ be a cardinality weighted graph such that $\lambda_k > 0$ for some $k \geq 1$. Then Algorithm 2 constructs in polynomial time a cluster tree T of G that achieves $O\left(\frac{1}{(1-\alpha)\beta} \log \frac{k}{1-\alpha}\right)$-approximation, where $\alpha = O(k^6\sqrt{\lambda_{k-1}})$, $\beta = \Omega(\lambda_k^2/k^4)$. Consequently, when $\lambda_k = \Omega(1/poly(k))$ and $\lambda_{k-1} = O(1/k^{12})$ such that $\alpha < 1 - \rho$ for some constant $\rho \in (0, 1)$, Algorithm 2 achieves $O(poly(k))$-approximation. In addition, when k is a constant, Algorithm 2 achieves $O(1)$-approximation.*

The proof of Theorem 3.2 is given in Appendix E.

4   Practically used non-binary hierarchical clustering algorithm

In this section, we develop a non-binary hierarchical clustering algorithm based on cost(SE) optimization. At present, all existing algorithms for hierarchical clustering can be categorized into two frameworks: top-down division and bottom-up agglomeration [8]. The top-down division approach usually yields a binary tree by recursively dividing a cluster into two parts with a cut-related criterion. But a binary clustering tree is far from a practical one as we introduced in Section 1. For practical use, bottom-up agglomeration that is also known as hierarchical agglomerative clustering (HAC) is commonly preferable. It constructs a cluster tree from leaves to the root recursively, during each round of which the newly generated clusters shrink into single vertices.

Our algorithm jumps out of these two frameworks. We establish a new one that stratifies the *sparsest* level of a cluster tree recursively rather than in a sequential order. In general, in guide with cost(SE), we construct a $k + 1$-level cluster tree from the previous k-level one, during which the level whose stratification makes the average local cost that is incorporated in a local reduced subgraph decrease most is differentiated into two levels. The process of stratification consists of two basic operations: *stretch* and *compression*. Generally speaking, in stretch steps, given an internal node of a cluster tree, a local binary subtree is constructed, while in compression steps, the paths that are overlength from the root to leaves on the binary tree is compressed by shrinking tree edges that make the cost reduce most. The intuition behind the "stretch-and-compress" scheme is as follows. First, we run a fast and simple, but probably rough clustering algorithm to obtain a binary cluster subtree. So intuitively, after stretch, we unfold all the potential hierarchies such that the sparsest level is possibly to be seen. Second, we compress every overlength path that is supposed to get through each level of this subtree, during which, the edge on the sparsest level whose compression makes too many graph edges upgrade their LCAs to a large extent will be retained.

We remark that this framework can be collocated with any cost function and any binary cluster tree algorithm. For computational efficiency, especially for real networks of large scale more than 10^4, we will adopt in our experiments an HAC construction of binary cluster trees in stretch steps.

Stretch and compress. Given a cluster tree T for graph $G = (V, E)$, let u be an internal node on T and $v_1, v_2, \ldots, v_\ell$ be its children. We call this local parent-children structure rooted at u to be a u-*triangle* of T, denoted by T_u. These two operations are defined on u-triangles. Note that each child v_i of u is a cluster in G. We reduce G by shrinking each v_i to be a single vertex v'_i while maintaining each intra-link and ignoring each internal edge of v_i. This reduction captures the connections of clusters at this level in the parent cluster u. The stretch operation constructs a binary tree for u-triangle. We adopt a common HAC construction in this u-triangle. That is, initially, view each v'_i as a cluster and recursively combine two clusters into a new one for which cost(SE) drops most. The sequence of combinations yields a binary subtree T'_u rooted at u which has $v_1, v_2, \ldots, v_\ell$ as leaves. Then the compression operation is proposed to reduce the height of T'_u to be 2. Let $\hat{E}(T')$ be the set of edges on T', each of which appears on a path of length more than 2 from the root of T' to some leaf. Denote by $\Delta(e)$ for edge e be the amount of structural entropy enhanced by the shrink of e. We pick from $\hat{E}(T'_u)$ the edge e with least $\Delta(e)$. Note that the compression of a tree edge makes the grandchildren of some internal node to be children, which must amplify the cost. The compression operation picks the least amplification. The processes of stretch and compress are illustrated in Figure 3 and stated in Algorithms 5 and 6, respectively (see Appendix G).

Sparsest level. Let U_j be the set of j-level nodes on cluster tree T, that is, U_j is the set of nodes each of which has distance j from T's root. Suppose that the height of T is k, then $U_0, U_1, \ldots, U_{k-1}$ is a partition for all internal nodes of T. For each internal node u, define $\mathcal{H}(u) = -\sum_{v:v^- = u} \frac{g_u}{\text{vol}(V)} \log \frac{\text{vol}(v)}{\text{vol}(u)}$. Note that $\mathcal{H}(u)$ is the partial sum contributed by u in $\mathcal{H}^T(G)$. After a "stretch-and-compress" round on u-triangle, denote by $\Delta\mathcal{H}(u)$ the structural entropy by which the new cluster tree reduces. Since the reconstruction of u-triangle stratifies cluster u, $\Delta\mathcal{H}(u)$ is always non-negative. Define the sparsity of u to be $\text{Spar}(u) = \frac{\Delta\mathcal{H}(u)}{\mathcal{H}(u)}$, which is the relative variation of structural entropy in cluster u. From the information-theoretic perspective, this means that the uncertainty of random walk can be measured locally in any internal cluster, which reflects the quality of clustering of this local area. At last, we define the *sparsest level* of T to be the j-th level such that the average sparsity of triangles rooted at nodes in U_j is maximum, that is $\arg\max_j\{\overline{\text{Spar}}_j(T)\}$,

where $\overline{\text{Spar}}_j(T) = \sum_{u \in U_j} \text{Spar}(u)/|U_j|$. Then stratification works for the sparsest level of T. This process is illustrated in Figure 4 (see Appendix G).

For a given positive integer k, to construct a cluster tree of height k, we start from the trivial 1-level cluster tree that involves all vertices of G as leaves. Then we do not stop stratifying at the sparsest level recursively until a k-level cluster tree is obtained. This process is described in Algorithm 3.

Algorithm 3: k-Hierarchical clustering based on structural entropy (k-HCSE)

Input: a graph $G = (V, E)$, $k \in \mathbb{Z}^+$
Output: a k-level cluster tree T

1 Initialize T to be the 1-level cluster tree;
2 $h = \text{height}(T)$;
3 **while** $h < k$ **do**
4    $j' \leftarrow \arg\max_j\{\overline{\text{Spar}}_j(T)\}$;   // Find the sparsest level of T (breaking ties arbitraily);
5   **if** $\overline{\text{Spar}}_{j'}(T) = 0$ **then**
6   break;   // No cost will be saved by any further clustering;
7   **for** $u \in U_{j'}$ **do**
8       $T_u \leftarrow \text{Stretch}(u\text{-triangle } T_u)$;
9       $\text{Compress}(T_u)$;
10       $h \leftarrow h + 1$;
11   **for** $j \in [j' + 1, h]$ **do**
12   Update U_j;

13 **return** T

To determine the height of the cluster tree automatically, we derive the natural clustering from the variation of sparsity on each level. Intuitively, a natural hierarchical cluster tree T should have not only sparse boundary on clusters, but also low sparsity for triangles of T, which means that stratification within the reduced subgraphs corresponding to the triangles on the sparsest level makes little sense. For this reason, we consider the inflection points of the sequence $\{\delta_t(\mathcal{H})\}_{t=1,2,\ldots}$, where $\delta_t(\mathcal{H})$ is the structural entropy by which the t-th round of stratification reduces. Formally, denote $\Delta_t \mathcal{H} = \delta_t(\mathcal{H}) - \delta_{t-1}(\mathcal{H})$ for each $t \geq 2$. We say that $\Delta_t \mathcal{H}$ is an inflection point if both $\Delta_t \mathcal{H} \geq \Delta_{t-1}\mathcal{H}$ and $\Delta_t \mathcal{H} \geq \Delta_{t+1}\mathcal{H}$ hold. Our algorithm finds the least t such that $\Delta_t \mathcal{H}$ is an inflection point and fix the height of the cluster tree to be t (Note that after $t - 1$ rounds of stratification, the number of levels is t). This process is described as Algorithm 4.

Algorithm 4: Hierarchical clustering based on structural entropy (HCSE)

Input: a graph $G = (V, E)$
Output: a cluster tree T

1 $t \leftarrow 2$;
2 **while** $\Delta_t \mathcal{H} < \Delta_{t-1}\mathcal{H}$ *or* $\Delta_t \mathcal{H} < \Delta_{t+1}\mathcal{H}$ **do**
3   **if** $\max_j\{\overline{\text{Spar}}_j(T)\}$=0 **then**
4   break;
5    $t \leftarrow t + 1$;

6 **return** $t\text{-HCSE}(T)$

Time complexity. The running time of HCSE on graph $G = (V, E)$ for which $|V| = n$ and $|E| = m$ depends mainly on the iterations of stratification for the sparsest level. For each round of t-HCSE in Algorithm 4, since the change of structure entropy can be calculated incrementally and locally when merge siblings, the time complexity for the Stretch process is $O(mh \log n)$, where h is the height of the binary tree that Stretch yields. Since at most n times of shrinking operations on tree edges will happen, the time complexity for the Compress process is $O(hn)$. Let $h_{\max}$ be the maximum height among the binary trees that appear during all iterations. The time complexity of HCSE (and also k-HCSE) is $O(kmh_{\max} \log n + kh_{\max}n)$. In practice, k is usually very small (we can even set $k = O(1)$ in k-HCSE). Moreover, the balance property of structural entropy tends to produce a

	$\vec{p}$	HCSE	HLP	LOU
p_2	4.5E(-2)	0.89	0.79	**0.92**
p_1	1.5E(-3)	**0.93**	0.75	0.92
p_0	6E(-6)	**0.62**	0.58	$--$
p_2	5.5E(-2)	0.87	**0.89**	0.89
p_1	1.5E(-3)	**0.95**	0.87	0.87
p_0	4E(-6)	**0.72**	$--$	$--$
p_2	6.5E(-2)	0.96	0.95	**0.99**
p_1	4.5E(-3)	0.94	0.81	**0.99**
p_0	2.5E(-6)	**0.80**	$--$	$--$

Table 1: NMI for three algorithms. Each dataset has $2,500$ vertices, and the cluster numbers at three levels are 5, 25 and 250, respectively, for which the size of each cluster is accordingly generated at random. $p_3 = 0.9$ for each graph. "$--$" means the algorithm does not find this level.

Figure 1: $\delta_t(\mathcal{H})$ variations for HCSE. It can be observed easily that the inflection points for all the three datasets appear on $t = 4$, which is also the ground-truth number of hierarchies.

balanced binary tree after stretch, which makes $h_{\max} = O(\log n)$. Therefore, in this case, the time complexity is merely $O(m \log^2 n)$.

5 Experiments

We evaluate experimentally our practically used non-binary clustering algorithm both on synthetic networks generated from the Hierarchical Stochastic Block Model (HSBM) and on real datasets, respectively. We compare HCSE with the popular practical algorithms LOUVAIN [3] and HLP [19]. To avoid over-fitting to higher levels, which possibly results in under-fitting to lower levels, LOUVAIN admits a sequential input of vertices. Usually, to avert the worst-case trap, the vertices come randomly, and the resulting cluster tree depends on their order. HLP invokes the common LP algorithm recursively, and so it cannot be guaranteed to avoid under-fitting in each round. This can be seen in our experiments on synthetic datasets, for which these two algorithms usually miss ground-truth levels. For real datasets, as far as we know, no public real datasets have clear ground truth for hierarchical clustering. We do the comparative experiments on real networks. Some of them have (overlapping, possibly hierarchical) ground truth, e.g., Amazon, while others do not have. We evaluate the resulting cluster trees for the Amazon network by Jaccard index, and show the results in Appendix F, For other networks without ground truth, we evaluate results by both cost(SE) and Dasgupta's cost function cost(Das). All the source code can be downloaded from https://github.com/samwu-learn/HCSE.

Synthetic datasets generated from HSBM. Our experiments on synthetic datasets utilize 4-level HSBM. For simplicity, let $\vec{p} = (p_0, p_1, p_2, p_3)$ be the probability vector for which p_i is the probability of generating edges for vertex pairs whose LCA on the ground-truth cluster tree has depth i. Note that the 0-depth node is the root. We compare the Normalized Mutual Information (NMI) at each level of the ground-truth cluster tree to those of three algorithms. Note that the randomness in LOUVAIN, and breaking-ties rule as well as convergence of HLP make different results, we choose the most effective strategy and pick the best results in five runs for both of them. Compared to their uncertainty, our algorithm HCSE yields stable results.

Table 1 demonstrates the results in three groups of probabilities, for which the hierarchical structures get clearer one by one. Each dataset has $2,500$ vertices, and the cluster numbers at three levels are 5, 25 and 250, respectively, for which the size of each cluster is accordingly generated at random. $p_3 = 0.9$ for each graph. Our algorithm HCSE is always able to find the right number of levels, while LOUVAIN always misses the top level, and HLP misses the top level in two groups. The inflection points for choosing the intrinsic hierarchy number $t = 4$ of hierarchies are demonstrated in Figure 1.

Networks	HCSE	HLP	LOUVAIN
CSphd	1.30E4 / **5.19E4** / 5	1.54E4 / 5.58E4 / 4	**1.28E4** / 7.61E4 / 5
fb-pages-government	2.48E6 / **1.18E8** / 4	2.53E6 / 1.76E8 / 3	**2.43E6** / 1.33E8 / 4
email-univ	1.16E5 / **2.20E6** / 3	1.46E5 / 6.14E6 / 3	**1.14E5** / 2.20E6 / 4
fb-messages	1.58E5 / **4.50E6** / 4	1.76E5 / 8.12E6 / 3	**1.52E5** / 4.96E6 / 4
G22	**5.56E5** / **2.68E7** / 4	6.11E5 / 4.00E7 / 3	5.63E5 / 2.80E7 / 5
As20000102	2.64E5 / **2.36E7** / 4	3.62E5 / 7.63E7 / 3	**2.42E5** / 2.42E7 / 5
bibd-13-6	**7.41E5** / **2.56E7** / 3	8.05E5 / 4.41E7 / 2	7.50E5 / 2.75E7 / 4
delaunay-n10	4.65E4 / **3.39E5** / 4	4.87E4 / 3.55E5 / 4	**4.24E4** / 4.25E5 / 5
p2p-Gnutella05	9.00E5 / **1.48E8** / 3	1.01E6 / 2.78E8 / 3	**8.05E5** / 1.49E8 / 5
p2p-Gnutella08	5.59E5 / **5.51E7** / 4	6.36E5 / 1.28E8 / 4	**4.88E5** / 6.03E7 / 5

Table 2: "cost(SE) / cost(Das) / k" for three algorithms, where k is the hierarchy number that the algorithm finds.

Real datasets. We do our experiments on a series of real networks [2] without ground truth. We compare cost(SE) and cost(Das), respectively. Since the different level numbers given by the three algorithms influence the costs seriously, that is, lower costs are obtained just due to greater heights, we only list in Table 2 the networks for which the three algorithms yield similar level numbers that differ by at most 1 or 2. It can be observed that HLP does not achieve optima for any network, while HCSE performs best w.r.t. cost(Das) for all networks, but does not outperform LOUVAIN for most networks. This is mainly due to the fact that LOUVAIN always finds no less number of hierarchies than HCSE, and the better cost benefits from its depth. Moreover, we emphasize that there is no evidence to indicate that the lower cost(SE) or cost(Das) is, the better a non-binary cluster tree is. Our experiments on these real datasets are just demonstrations of the effectiveness for our interpretable mechanism in hierarchical clustering.

6 Conclusions and future discussions

In this paper, we investigate the hierarchical clustering problem from an information-theoretic perspective and propose a new objective function that relates to the combinatorial cost functions raised by Dasgupta [10]. For optimization of this function, we present two $O(1)$-approximation algorithms for expander-like and well-clustered cardinality weighted graphs, respectively. For practical use, we propose a new interpretable non-binary hierarchical clustering framework that stratifies the sparsest level of the cluster tree recursively, which can be collocated with any cost function. We also present an interpretable strategy to find the intrinsic number of levels without any hyper-parameter. The experimental results on k-level HSBM demonstrate that our algorithm HCSE has a great advantage in finding k compared to the popular but strongly heuristic algorithms LOUVAIN and HLP. Our results on real datasets show that HCSE also achieves competitive costs compared to these two algorithms.

There are several directions that are worth further study. The first problem is about the relationship between the concavity of g of the cost function and the balance of the optimal cluster tree. It can be checked that for cliques, being concave is not a sufficient condition for total balance. Whether is it a necessary condition? Moreover, is there any explicit necessary and sufficient condition for total balance of the optimal cluster tree for cliques? The second problem is about approximation algorithms for both structural entropy and cost(SE) in the worst case. Due to the non-linear and volume-related function g, many previous proof techniques for approximation algorithms seems unavailable. The third one is about more precise characterizations for "natural" hierarchical clustering whose depth is limited. Since any reasonable choice of g makes the cost function achieve optimum on some binary tree, a blind pursuit of minimization of cost functions seems not to be a rational approach. More criteria in this scenario need to be studied.

---

[2] http://networkrepository.com/index.php

References

[1] Noga Alon, Yossi Azar, and Danny Vainstein. Hierarchical clustering: A 0.585 revenue approximation. In Jacob D. Abernethy and Shivani Agarwal, editors, *Conference on Learning Theory, COLT 2020, 9-12 July 2020, Virtual Event [Graz, Austria]*, volume 125 of *Proceedings of Machine Learning Research*, pages 153–162. PMLR, 2020.

[2] Sanjeev Arora, Satish Rao, and Umesh V. Vazirani. Expander flows, geometric embeddings and graph partitioning. *J. ACM*, 56(2):5:1–5:37, 2009.

[3] Vincent D. Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. Fast unfolding of communities in large networks. *Journal of statistical mechanics: theory and experiment*, 2008(10):P10008, 2008.

[4] Peter F Brown, Vincent J Della Pietra, Peter V Desouza, Jennifer C Lai, and Robert L Mercer. Class-based n-gram models of natural language. *Computational linguistics*, 18(4):467–480, 1992.

[5] Moses Charikar and Vaggos Chatziafratis. Approximate hierarchical clustering via sparsest cut and spreading metrics. In Philip N. Klein, editor, *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2017, Barcelona, Spain, Hotel Porta Fira, January 16-19*, pages 841–854. SIAM, 2017.

[6] Moses Charikar, Vaggos Chatziafratis, and Rad Niazadeh. Hierarchical clustering better than average-linkage. In Timothy M. Chan, editor, *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2019, San Diego, California, USA, January 6-9, 2019*, pages 2291–2304. SIAM, 2019.

[7] Vaggos Chatziafratis, Grigory Yaroslavtsev, Euiwoong Lee, Konstantin Makarychev, Sara Ahmadian, Alessandro Epasto, and Mohammad Mahdian. Bisect and conquer: Hierarchical clustering via max-uncut bisection. In Silvia Chiappa and Roberto Calandra, editors, *The 23rd International Conference on Artificial Intelligence and Statistics, AISTATS 2020, 26-28 August 2020, Online [Palermo, Sicily, Italy]*, volume 108 of *Proceedings of Machine Learning Research*, pages 3121–3132. PMLR, 2020.

[8] Vincent Cohen-Addad, Varun Kanade, Frederik Mallmann-Trenn, and Claire Mathieu. Hierarchical clustering: Objective functions and algorithms. *Journal of the ACM (JACM)*, 66(4):1–42, 2019.

[9] Aron Culotta, Pallika Kanani, Robert Hall, Michael Wick, and Andrew McCallum. Author disambiguation using error-driven machine learning with a ranking loss function. In *Sixth International Workshop on Information Integration on the Web (IIWeb-07), Vancouver, Canada*, 2007.

[10] Sanjoy Dasgupta. A cost function for similarity-based hierarchical clustering. In Daniel Wichs and Yishay Mansour, editors, *Proceedings of the 48th Annual ACM SIGACT Symposium on Theory of Computing, STOC 2016, Cambridge, MA, USA, June 18-21, 2016*, pages 118–127. ACM, 2016.

[11] Michael B Eisen, Paul T Spellman, Patrick O Brown, and David Botstein. Cluster analysis and display of genome-wide expression patterns. *Proceedings of the National Academy of Sciences*, 95(25):14863–14868, 1998.

[12] Shayan Oveis Gharan and Luca Trevisan. Partitioning into expanders. In Chandra Chekuri, editor, *Proceedings of the Twenty-Fifth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2014, Portland, Oregon, USA, January 5-7, 2014*, pages 1256–1266. SIAM, 2014.

[13] Alexander N Gorban, Balázs Kégl, Donald C Wunsch, Andrei Y Zinovyev, et al. *Principal manifolds for data visualization and dimension reduction*, volume 58. Springer, 2008.

[14] Angsheng Li and Yicheng Pan. Structural information and dynamical complexity of networks. *IEEE Trans. Inf. Theory*, 62(6):3290–3339, 2016.

[15] Bogdan-Adrian Manghiuc and He Sun. Hierarchical clustering: O(1)-approximation for well-clustered graphs. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan, editors, *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 9278–9289, 2021.

[16] Benjamin Moseley and Joshua R. Wang. Approximation bounds for hierarchical clustering: Average linkage, bisecting k-means, and local search. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 3094–3103, 2017.

[17] Stanislav Naumov, Grigory Yaroslavtsev, and Dmitrii Avdiukhin. Objective-based hierarchical clustering of deep embedding vectors. In *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pages 9055–9063. AAAI Press, 2021.

[18] Mirmahdi Rahgoshay and Mohammad R. Salavatipour. Hierarchical clustering: New bounds and objective. *CoRR*, abs/2111.06863, 2021.

[19] Ryan A Rossi, Nesreen K Ahmed, Eunyee Koh, and Sungchul Kim. Fast hierarchical graph clustering in linear-time. In *Companion Proceedings of the Web Conference 2020*, pages 10–12, 2020.

[20] Aurko Roy and Sebastian Pokutta. Hierarchical clustering via spreading metrics. *J. Mach. Learn. Res.*, 18:88:1–88:35, 2017.

A A brief introduction to structural information

The idea of structural information is to encode a random walk with a certain rule by using a high-dimensional encoding system for a graph G. It is well known that a random walk, for which a neighbor is randomly chosen with probability proportional to edge weights, has a stationary distribution on vertices that is proportional to vertex degree.[3] So to position a random walk under its stationary distribution, the amount of information needed is typically the Shannon's entropy, denoted by

$$\mathcal{H}^{(1)}(G) = -\sum_{v \in V} \frac{d_v}{\mathrm{vol}(V)} \log \frac{d_v}{\mathrm{vol}(V)}.$$

474 By Shannon's noiseless coding theorem, $\mathcal{H}^{(1)}(G)$ is the limit of average code length generated from
475 the *memoryless* source for one step of the random walk. However, dependence of locations may
476 shorten the code length. For each level on cluster trees, the uncertainty of locations is measured by
477 the entropy of the stationary distribution on the clusters of this level. Consider an encoding for every
478 cluster, including the leaves. Each non-root node α is labeled by its order among the children of
479 its parent α^-. So the amount of self-information of α within this local parent-children substructure
480 is $-\log(\mathrm{vol}(\alpha)/\mathrm{vol}(\alpha^-))$, which is also roughly the length of Shannon code for α and its siblings.
481 The codeword of α consists of the sequential labels of nodes along the unique path from the root
482 (excluded) to itself (included). The key idea is as follows. For one step of the random walk from u to
483 v in G, to indicate v, we omit from v's codeword the longest common prefix of u and v that is exactly
484 the codeword of $u \vee v$. This means that the random walk takes this step in the cluster $u \vee v$ (and
485 also in $u \vee v$'s ancestors) and the uncertainty at this level may not be involved. Therefore, intuitively,
486 a quality similarity-based cluster tree would trap the random walk with high frequency in the deep
487 clusters that are far from the root, and long codeword of $u \vee v$ would be omitted. This shortens the
488 average code length of the random walk. Note that we ignore the uniqueness of decoding since a
489 practical design of codewords is not our purpose. We utilize this scheme to evaluate and differentiate
490 hierarchical structures.

491 Then we formulate the above scheme and measure the average code length as follows. Given a
492 weighted graph $G = (V, E, w)$ and a cluster tree T for G, note that under the stationary distribution,
493 the random walk takes one step out of a cluster α on T with probability $g_\alpha/\mathrm{vol}(V)$, where g_α is the
494 sum of weights of edges with exactly one end-point in α. Therefore, the aforementioned uncertainty
495 measured by the average code length is

$$\mathcal{H}^T(G) = -\sum_{\alpha \in T} \frac{g_\alpha}{\mathrm{vol}(V)} \log \frac{\mathrm{vol}(\alpha)}{\mathrm{vol}(\alpha^-)},$$

496 which is defined as the structural entropy of G on T. To minimize this uncertainty, the structural
497 entropy $\mathcal{H}(G)$ of G is defined as the minimum one among all cluster trees. Note that the structural
498 entropy of G on the trivial 1-level cluster tree is consistent with the previously defined $\mathcal{H}^{(1)}(G)$. It
499 doesn't have any non-trivial cluster.

---

[3]For connected graphs, this stationary distribution is unique, but not for disconnected ones. Here, we consider this canonical one for all graphs.

B Proof of Proposition 2.1

Proof. Note that

$$
\begin{aligned}
\mathcal{H}^T(G) &= -\sum_{\alpha \in T} \frac{g_\alpha}{\text{vol}(V)} \log \frac{\text{vol}(\alpha)}{\text{vol}(\alpha^-)} \\
&= -\sum_{\alpha \in T} \sum_{(u,v) \in g_\alpha} \frac{w(u,v)}{\text{vol}(V)} \log \frac{\text{vol}(\alpha)}{\text{vol}(\alpha^-)} \\
&= -\sum_{(u,v) \in E} \left(\frac{w(u,v)}{\text{vol}(V)} \sum_{\alpha : (u,v) \in g_\alpha} \log \frac{\text{vol}(\alpha)}{\text{vol}(\alpha^-)} \right).
\end{aligned}
$$

For a single edge $(u,v) \in E$, all the terms $\log(\text{vol}(\alpha)/\text{vol}(\alpha^-))$ for leaf u satisfying $(u,v) \in g_\alpha$ sum (over α) up to $\log(d_u/\text{vol}(u \vee v))$ along the unique path from u to $u \vee v$. It is symmetric for v. Therefore, considering ordered pair $(u,v) \in E$,

$$
\begin{aligned}
\mathcal{H}^T(G) &= -\sum_{\text{ordered } (u,v) \in E} \frac{w(u,v)}{\text{vol}(V)} \log \frac{d_u}{\text{vol}(u \vee v)} \\
&= \frac{1}{\text{vol}(V)} \left(-\sum_{u \in V} d_u \log d_u + \sum_{\text{ordered } (u,v) \in E} w(u,v) \log \text{vol}(u \vee v) \right) \\
&= \frac{1}{\text{vol}(V)} \left(-\sum_{u \in V} d_u \log d_u + 2 \cdot \sum_{(u,v) \in E} w(u,v) \log \text{vol}(u \vee v) \right).
\end{aligned}
$$

The second equality follows from the fact $\sum_{u \in V} d_u = \sum_{\text{ordered } (u,v) \in E} w(u,v) = \text{vol}(V)$ and the last equality from the symmetry of (u,v). Since the first summation is independent of T, Proposition 2.1 follows. $\qquad\square$

C Proof of Proposition 2.2

We restate Proposition 2.2 as follows.

Theorem 2.2. *For any positive integer n, let K_n be the clique of n vertices with identical weight on every edge. Then a cluster tree T of K_n achieves minimum structural entropy if and only if T is a balanced binary tree, that is, the two children clusters of each sub-tree of T have difference in size at most 1.*

Note that a balanced binary tree (BBT for abbreviation) means the tree is balanced on every internal node. Formally, for an internal node of cluster size k, its two sub-trees are of cluster sizes $\lfloor k/2 \rfloor$ and $\lceil k/2 \rceil$, respectively.

For cliques, since the weights of each edge are identical, we assume it safely to be 1. By Theorem 2.1, minimizing the structural entropy is equivalent to minimizing the cost function (over T)

$$
\begin{aligned}
\text{cost}^T(G) &= \sum_{(u,v) \in E} \log \text{vol}(u \vee v) \\
&= \sum_{(u,v) \in E} \log \left((n-1)|u \vee v| \right) \\
&= \sum_{(u,v) \in E} \log(n-1) + \sum_{(u,v) \in E} \log |u \vee v|
\end{aligned}
$$

Since the first term in the last equation is independent of T, the optimization turns to minimizing the last term, which we denote by $\Gamma(T)$. Grouping all edges in E by LCA of two end-points, the cost $\Gamma(T)$ can be written as the sum of the cost γ at every internal node N of T. Formally, for every

internal node N, let $A, B \subseteq V$ be the leaves of the sub-trees rooted at the left and right child of N, respectively. We have

$$\Gamma(T) \;=\; \sum_N \gamma(N)$$

$$\gamma(N) \;=\; \left(\sum_{x \in A, y \in B} 1 \right) \cdot \log\left(|A| + |B|\right)$$

$$= \;|A| \cdot |B| \cdot \log(|A| + |B|)$$

Now we only have to show the following lemma.

Lemma C.1. *For any positive integer n, a cluster tree T of K_n achieves minimum cost $\Gamma(T)$ if and only if T is a BBT.*

Proof. Lemma C.1 is proved by induction on $|V|$. The key technique of tree swapping we use here is inspired by Cohen-Addad et al [4]. The basis step holds since for $|V| = 2$ or 3, the cluster tree is balanced and unique. It certainly achieves the minimum cost exclusively.

Now, consider a clique $G = (V, E)$ with $n = |V| \geq 4$. Let T_1 be an arbitrary unbalanced cluster tree and λ be its root. We need to prove that the cost $\Gamma(T_1)$ does not achieve the minimum. Without loss of generality, we can safely assume the root node is unbalanced, since otherwise, we set T_1 to be the sub-tree that is rooted at an unbalanced node. Let T_2 be a tree with root λ whose left and right sub-trees are BBTs such that they have the same sizes with the left and right sub-trees of T_1, respectively. Let V_{ll}, V_{lr}, V_{rl} and V_{rr} be the sets of nodes on the four sub-trees at the second level of T_2 and n_{ll}, n_{lr}, n_{rl} and n_{rr} denote their sizes, respectively. Our proof is also available when some of them are empty. We always assume $n_{ll} \leq n_{lr}$ and $n_{rl} \geq n_{rr}$. Next, we construct T_3 by swapping (transplanting) V_{lr} and V_{rl} with each other. Finally, let T_4 be a tree with root λ whose left and right sub-trees are BBTs after balancing the left and right sub-trees of T_3. So T_4 is a BBT. Then we only have to prove that $\Gamma(T_1) > \Gamma(T_4)$. Note that the strict ">" is necessary since we need to negate all unbalanced cluster trees.

Then we show that the transformation process that consists of the above three steps makes the cost decrease step by step. Formally,

(a) T_1 to T_2. The sub-trees of T_1 become BBTs in T_2. Since the number of edges whose end-points treat the root as LCA is the same, by induction we have $\Gamma(T_1) \geq \Gamma(T_2)$.

(b) T_2 to T_3. We will show that $\Gamma(T_2) > \Gamma(T_3)$ in Lemma C.2.

(c) T_3 to T_4. The sub-trees of T_3 become BBTs in T_4. For the same reason as (a), we have $\Gamma(T_3) \geq \Gamma(T_4)$.

Putting them together, we get $\Gamma(T_1) > \Gamma(T_4)$ and Lemma C.1 follows.

$\square$

Lemma C.2. *After swapping V_{lr} and V_{rl}, we obtain T_3 from T_2, for which $\Gamma(T_2) > \Gamma(T_3)$.*

Proof. We only need to consider the changes in cost of three nodes: root and its left and right children, since the cost contributed by each of the remaining nodes does not change after swapping. Ignoring the unchanged costs, define

$$\text{cost}(T_2) \;=\; n_l n_r \log n + n_{ll} n_{lr} \log n_l + n_{rl} n_{rr} \log n_r$$

$$= \; n_l n_r \log n + \left\lfloor \frac{n_l}{2} \right\rfloor \left\lceil \frac{n_l}{2} \right\rceil \log n_l + \left\lceil \frac{n_r}{2} \right\rceil \left\lfloor \frac{n_r}{2} \right\rfloor \log n_r,$$

where $n_l = n_{ll} + n_{lr}, n_r = n_{rl} + n_{rr}$. Both of them are at least 1. Similarly, define

$$\text{cost}(T_3) \;=\; (n_{ll} + n_{rl})(n_{lr} + n_{rr}) \log n + n_{ll} n_{rl} \log(n_{ll} + n_{rl}) + n_{lr} n_{rr} \log(n_{lr} + n_{rr})$$

$$= \; \left\lfloor \frac{n}{2} \right\rfloor \left\lceil \frac{n}{2} \right\rceil \log n + \left\lfloor \frac{n_l}{2} \right\rfloor \left\lceil \frac{n_r}{2} \right\rceil \log \left(\left\lfloor \frac{n_l}{2} \right\rfloor + \left\lceil \frac{n_r}{2} \right\rceil \right) + \left\lceil \frac{n_l}{2} \right\rceil \left\lfloor \frac{n_r}{2} \right\rfloor \log \left(\left\lceil \frac{n_l}{2} \right\rceil + \left\lfloor \frac{n_r}{2} \right\rfloor \right)$$

556 Denote

$$
\begin{aligned}
\Delta &= \Gamma(T_2) - \Gamma(T_3) \\
&= \mathrm{cost}(T_2) - \mathrm{cost}(T_3) \\
&= \left\lfloor \frac{n_l}{2} \right\rfloor \left\lceil \frac{n_l}{2} \right\rceil \log\left(\frac{n_l}{n}\right) + \left\lceil \frac{n_r}{2} \right\rceil \left\lfloor \frac{n_r}{2} \right\rfloor \log\left(\frac{n_r}{n}\right) \\
&\quad - \left\lfloor \frac{n_l}{2} \right\rfloor \left\lceil \frac{n_r}{2} \right\rceil \log\left(\frac{\left\lfloor \frac{n_l}{2} \right\rfloor + \left\lceil \frac{n_r}{2} \right\rceil}{n}\right) - \left\lceil \frac{n_l}{2} \right\rceil \left\lfloor \frac{n_r}{2} \right\rfloor \log\left(\frac{\left\lceil \frac{n_l}{2} \right\rceil + \left\lfloor \frac{n_r}{2} \right\rfloor}{n}\right)
\end{aligned} \tag{2}
$$

557 So we only have to show that $\Delta > 0$. We consider the following three cases according to the odevity
558 of n_l and n_r.

559 **Case** 1: n_l and n_r are even.

560 **Case** 2: n_l and n_r are odd.

561 **Case** 3: n_l is odd while n_r is even.

562 The case that n_l is even while n_r is odd is symmetric to **Case** 3.

563 For **Case** 1, if both n_l and n_r are even, then notations of rounding in Eq. (2) can be removed and Δ
564 can be simplified as

$$
\Delta = \frac{n_l^2}{4} \log\left(\frac{n_l}{n}\right) + \frac{n_r^2}{4} \log\left(\frac{n_r}{n}\right) + \frac{n_l n_r}{2}.
$$

565 Let $p = n_l/n, q = n_r/n$, and so $p + q = 1$. Recall that T_1 is unbalanced on the root λ, so is T_2.
566 Thus $p \neq q$. Multiplying by $\frac{4}{n^2}$ on both sides, we only have to prove that

$$
p^2 \log p + q^2 \log q + 2pq > 0.
$$

That is,

$$
\frac{p}{q} \log p + \frac{q}{p} \log q + 2 > 0.
$$

567 Let $g(x) = \frac{x}{1-x} \log x$. Then we only need to show that $g(p) + g(q) + 2 > 0$ when $p \neq q$. Since

$$
\begin{aligned}
g'(x) &= \frac{(1-x) + \ln x}{\ln 2 \cdot (1-x)^2}, \\
g''(x) &= -\frac{x^2 - 2x \ln x - 1}{\ln 2 \cdot x (1-x)^3}.
\end{aligned}
$$

It is easy to check that $g''(x) > 0$ when $0 < x < 1$. So $g(x)$ is strictly convex in the interval $(0, 1)$.
Since $p \neq q$,

$$
g(p) + g(q) > 2g\left(\frac{p+q}{2}\right) = -2.
$$

568 Thus $\Delta > 0$ holds.

569 For **Case** 2, if both n_l and n_r are odd, then Δ can be split into two parts $\Delta = \Delta_1 + \Delta_2$, in which

$$
\begin{aligned}
\Delta_1 &= \frac{n_l^2}{4} \log\left(\frac{n_l}{n}\right) + \frac{n_r^2}{4} \log\left(\frac{n_r}{n}\right) + \frac{n_l n_r}{2} \\
\Delta_2 &= -\frac{1}{4} \log\left(\frac{n_l}{n}\right) - \frac{1}{4} \log\left(\frac{n_r}{n}\right) - \frac{1}{2}
\end{aligned}
$$

570 Since we have shown that $\Delta_1 > 0$, if we can prove $\Delta_2 \geq 0$, then the lemma will hold for **Case** 2.
571 Due to the convexity of logarithmic function, this holds clearly since

$$
2 \log\left(\frac{n}{2}\right) \geq \log n_l + \log n_r.
$$

572 For **Case** 3, if n_l is odd while n_r is even,

$$
\Delta = \frac{n_l^2 - 1}{4} \log\left(\frac{n_l}{n}\right) + \frac{n_r^2}{4} \log\left(\frac{n_r}{n}\right) - \left[\frac{(n_l - 1) n_r}{4} \log\left(\frac{n-1}{2n}\right) + \frac{(n_l + 1) n_r}{4} \log\left(\frac{n+1}{2n}\right)\right].
$$

573   Multiplying the above equation by $4 \ln 2$, without changing its sign, yields

$$(4 \ln 2)\Delta = (n_l^2 - 1) \ln\left(\frac{n_l}{n}\right) + n_r^2 \ln\left(\frac{n_r}{n}\right) - \left[(n_l - 1)n_r \ln\left(\frac{n-1}{2n}\right) + (n_l + 1)n_r \ln\left(\frac{n+1}{2n}\right)\right]$$

574   Splitting the right hand side into two parts,

$$\begin{aligned}
A &= n_l^2 \ln\left(\frac{n_l}{n}\right) + n_r^2 \ln\left(\frac{n_r}{n}\right) + 2 n_l n_r \ln 2 \\
B &= -\ln\left(\frac{n_l}{n}\right) - (n_l + 1)n_r \ln\left(1 + \frac{1}{n}\right) - (n_l - 1)n_r \ln\left(1 - \frac{1}{n}\right)
\end{aligned}$$

575   Since n is odd and the root λ of T_2 is unbalanced, we only need to consider the case that $n_l =$
576    $(n - i)/2$, $n_r = (n + i)/2$ (Note that n_l and n_r are symmetric. So if $(n - i)/2$ is even, exchange
577   n_l and n_r), where both n and i are odd satisfying $n > i \geq 3$. Next we show that in this case,
578    $A \geq \ln(1/5) + 4^2 \ln(4/5) + 2 \cdot 4 \ln 2$ and $B > \ln 2 - 3/4 - (2/3) \cdot (1/5^2)$. By calculation,
579    $\Delta = A + B > 0$ for **Case** 3.

580   **Claim C.1.** $A \geq \ln(1/5) + 4^2 \ln(4/5) + 2 \cdot 4 \ln 2$ *for odd integers* $n > i \geq 3$.

581   *Proof.* Substituting $n_l = (n - i)/2$, $n_r = (n + i)/2$ into the A yields

$$A = C(n, i) \triangleq \left(\frac{n - i}{2}\right)^2 \ln\left(\frac{n - i}{2n}\right) + \left(\frac{n + i}{2}\right)^2 \ln\left(\frac{n + i}{2n}\right) + 2 \cdot \frac{n - i}{2} \cdot \frac{n + i}{2} \ln 2.$$

582   Treat n as a continuous variable, we have

$$\frac{\partial C(n, i)}{\partial n} = \frac{1}{2}\left[(n + i) \ln\left(1 + \frac{i}{n}\right) + (n - i) \ln\left(1 - \frac{i}{n}\right) - \frac{i^2}{n}\right]$$

583   Multiplying the above equation by $2/n$ and setting $x = i/n$ yields

$$\begin{aligned}
f(x) &\triangleq (1 + x) \ln(1 + x) + (1 - x) \ln(1 - x) - x^2, \\
f'(x) &= \ln(1 + x) - \ln(1 - x) - 2x, \\
f''(x) &= \frac{2x^2}{1 - x^2}.
\end{aligned}$$

584   It is easy to check that $f(0) = 0$ and $f'(0) = 0$. When $0 < x < 1$, $f''(x) > 0$. Thus $f'(x) > 0$ and
585    $f(x) > 0$. This means that $\partial C(n, i)/\partial n > 0$ for all $n > 0$. So $C(n, i) \geq C(i + 2, i)$ for $n \geq i + 2$
586   (When i is fixed, the minimum value of n can be taken to $i + 2$, which makes $n_l = (n - i)/2$ and
587    $n_r = (n + i)/2$ integral). The curves of $C(n, i)$ for varying i are plotted in Figure 2.

Figure 2: Functions $C(n, i)$

When $n = i + 2$, we get $n_l = (n - i)/2 = 1$ and $n_r = (n + i)/2 = n - 1$. Substituting them into A yields

$$D(n) \triangleq \ln\left(\frac{1}{n}\right) + (n - 1)^2 \ln\left(1 - \frac{1}{n}\right) + 2(n - 1)\ln 2,$$

$$\frac{dD}{dn} = 1 - \frac{2}{n} + 2\ln 2 + 2(n - 1)\ln\left(1 - \frac{1}{n}\right).$$

When $n > 2$, it is easy to check that $dD/dn > 0$. So the minimum value of $d(n)$, which is also the minimum value of $C(i + 2, i)$, is achieved at $n = i + 2 = 5$. So $A = C(n, i) \geq C(i + 2, i) \geq C(5, 3) = \ln(1/5) + 4^2 \ln(4/5) + 2 \cdot 4 \ln 2$. $\qquad\square$

Claim C.2. $B > \ln 2 - 3/4 - (2/3) \cdot (1/5^2)$.

Proof. Due to the facts that

$$\ln\left(1 + \frac{1}{n}\right) < \frac{1}{n} - \frac{1}{2n^2} + \frac{1}{3n^3},$$

$$\ln\left(1 - \frac{1}{n}\right) < -\frac{1}{n} - \frac{1}{2n^2} - \frac{1}{3n^3},$$

we have

$$\begin{aligned}
B &= -\ln\left(\frac{n_l}{n}\right) - (n_l + 1)n_r \ln\left(1 + \frac{1}{n}\right) - (n_l - 1)n_r \ln\left(1 - \frac{1}{n}\right) \\
&> -\ln\left(\frac{n_l}{n}\right) + \frac{n_l n_r}{n^2} - \frac{2n_r}{n} - \frac{2n_r}{3n^3} \\
&> -\ln\left(\frac{n_l}{n}\right) + \frac{n_l n_r}{n^2} - \frac{2n_r}{n} - \frac{2}{3n^2}.
\end{aligned}$$

Let $\alpha = n_l/n$, then

$$\begin{aligned}
B &> -\ln\alpha + \alpha(1 - \alpha) - 2(1 - \alpha) - \frac{2}{3n^2} \\
&\geq \ln 2 - \frac{3}{4} - \frac{2}{3n^2}.
\end{aligned}$$

When $n \geq 5$, $B > \ln 2 - 3/4 - (2/3) \cdot (1/5^2)$. $\qquad\square$

Combining Claims C.1 and C.2, Lemma C.2 follows. $\qquad\square$

This completes the proof of Proposition 2.2.

D Proof of Theorem 3.1

Proof. Note that $\text{cost}^T(G)$ for any cluster tree T has a trivial upper bound. That is,

$$\text{cost}^T(G) = \sum_{e \in E} \text{cost}^T(e) \leq \sum_{e \in E} w_e \cdot \log(\text{vol}(G)) \leq \frac{\text{vol}(G) \cdot \log(\text{vol}(G))}{2},$$

where $\text{cost}^T(e) = w_e \log \text{vol}(\text{LCA}_T(e))$. Let T^* be the optimal cluster tree that achieves the minimum cost, we present here a lower bound for $\text{cost}^{T^*}(G)$. Referring to the dense branch technique [10, 15], we start with the root node A_0 and walk along T^* recursively as follows: at every internal node A_i, walk down to the node A_{i+1} of higher volume between its two children. This process stops when we reach node A_k such that $\text{vol}_G(A_k) \leq \frac{2\text{vol}(G)}{3}$. Denote $A \triangleq A_k$ as well as $B \triangleq V \backslash A_k$. By construction, it holds that $\text{vol}_G(A) > \frac{\text{vol}(G)}{3}$ and $\text{vol}_G(B) \geq \frac{\text{vol}(G)}{3}$. Moreover, $\text{vol}_G(A_i) > \frac{2\text{vol}(G)}{3}$

for every $0 \le i < k$. The basic idea behind the dense branch is that the $cut(A, B)$ has a significant contribution to $cost^{T^*}(G)$.

$$cost^{T^*}(G) = \sum_{e=\{u,v\}} w_e \cdot \log(\mathrm{vol}_G(u \vee v))$$

$$\ge \sum_{\substack{e=\{u,v\} \\ e \in E\{A,B\}}} w_e \cdot \log(\mathrm{vol}_G(u \vee v))$$

$$\ge w(A, B) \cdot \log\left(\frac{2\mathrm{vol}(G)}{3}\right).$$

$$\ge \Phi(G) \cdot \frac{\mathrm{vol}(G)}{3} \cdot \log\left(\frac{2\mathrm{vol}(G)}{3}\right).$$

Let T be an arbitrary cluster tree, and T^* be an optimal tree. We have

$$\frac{cost^T(G)}{cost^{T^*}(G)} \le \frac{3}{2\Phi(G)} \cdot \frac{\log(\mathrm{vol}(G))}{\log\left(\frac{2\mathrm{vol}(G)}{3}\right)} = O(\Phi(G)^{-1}).$$

$\square$

E   Proof of Theorem 3.2

Proof. To prove Theorem 3.2, we only have to prove the following lemma. Then the theorem follows from a simplification of the approximation factor.

Lemma E.1. *Let* $\alpha = \max_i\{\Phi_G(P_i)\}$ *and* $\beta = \min_i\{\Phi(G[P_i])\}$. *Algorithm 2 achieves* $\left(\left(\left(\log\left(\frac{1}{1-\alpha}\right) + 1\right) + \frac{2\alpha}{1-\alpha}\left(1 + \log\frac{k}{1-\alpha}\right)\right) \cdot \frac{3}{2\beta \log\left(\frac{4}{3}\right)}\right)$-*approximation.*

Proof. We group the edges of G into two categories: let E_1 be the set of edges in the induced subgraphs $G[P_i]$ for all $1 \le i \le l$, i.e.,

$$E_1 \triangleq \cup_{i=1}^l E[G[P_i]],$$

and E_2 be the remaining crossing edges. Then we have

$$cost^T(G) = \sum_{e \in E_1} cost^T(e) + \sum_{e \in E_2} cost^T(e).$$

We denote by $\mathrm{vol}(G[P_i])$ the volume of the induced graph $G[P_i]$, by $\mathrm{vol}_G(P_i)$ the volume of P_i in G, and by $\mathrm{parent}^T(P_i)$ the parent of P_i on T. Then it holds for every P_i that

$$\mathrm{vol}_G(\mathrm{parent}^T(P_i)) \le k \cdot \mathrm{vol}_G(P_i).$$

By the construction of T we have that

$$\mathrm{vol}_G(\mathrm{parent}^T(P_i)) = \sum_{j=1}^i \mathrm{vol}_G(P_j) \le i \cdot \mathrm{vol}_G(P_i) \le k \cdot \mathrm{vol}_G(P_i).$$

Note that

$$w(P_i, V \setminus P_i) = \mathrm{vol}_G(P_i) - \mathrm{vol}(G[P_i]) \le \alpha \cdot \mathrm{vol}_G(P_i),$$

$$(1 - \alpha) \cdot \mathrm{vol}_G(P_i) \le \mathrm{vol}(G[P_i]),$$

and thus

$$\mathrm{vol}_G(\mathrm{parent}^T(P_i)) \le k \cdot \mathrm{vol}_G(P_i) \le \frac{k}{1-\alpha}\mathrm{vol}(G[P_i]).$$

Combining the above, we have that

$$
\begin{aligned}
\sum_{e \in E_1} \text{cost}^T(e) \;\leq\; & \sum_{e \in E_1} w_e \cdot \log(\text{vol}_G(P_i)) \\
\leq\; & \sum_{e \in E_1} w_e \cdot \log\left(\frac{1}{1-\alpha}\text{vol}(G[P_i])\right) \\
=\; & \sum_{e \in E_1} \left(w_e \cdot \log\frac{1}{1-\alpha} + w_e \cdot \log(\text{vol}(G[P_i]))\right) \\
\leq\; & \left(\log\frac{1}{1-\alpha} + 1\right) \cdot \sum_{j=1}^{k} \frac{\text{vol}(G[P_i]) \cdot \log(\text{vol}(G[P_i]))}{2},
\end{aligned}
$$

and

$$
\begin{aligned}
\sum_{e \in E_2} \text{cost}^T(e) \;\leq\; & \sum_{j=1}^{k} w(P_i, V\backslash P_i) \cdot \log(\text{vol}_G(\text{parent}^T(P_i))) \\
\leq\; & \sum_{j=1}^{k} \frac{\alpha}{1-\alpha}\text{vol}(G[P_i]) \log\left(\frac{k}{1-\alpha}\text{vol}(G[P_i])\right) \\
\leq\; & \sum_{j=1}^{k} \frac{\alpha}{1-\alpha}\left(1 + \log\frac{k}{1-\alpha}\right)\text{vol}(G[P_i]) \log(\text{vol}(G[P_i])) \\
=\; & \frac{2\alpha}{1-\alpha}\left(1 + \log\frac{k}{1-\alpha}\right) \cdot \sum_{j=1}^{k} \frac{\text{vol}(G[P_i]) \cdot \log(\text{vol}(G[P_i]))}{2}.
\end{aligned}
$$

Let T^* be the optimal cluster tree of G, and OPT_G be the optimal value. We have

$$
OPT_G = \text{cost}_G(T^*) \geq \sum_{i=1}^{l} \sum_{e \in E(G[P_i])} \text{cost}_{T^*}(e) \geq \sum_{i=1}^{l} OPT_{G[P_i]}.
$$

Denote by

$$
h(\alpha, k) = \left(\left(\log\left(\frac{1}{1-\alpha}\right) + 1\right) + \frac{2\alpha}{1-\alpha}\left(1 + \log\frac{k}{1-\alpha}\right)\right).
$$

We have

$$
\begin{aligned}
\text{cost}^T(G) \;=\; & \sum_{e \in E_1} \text{cost}^T(e) + \sum_{e \in E_2} \text{cost}^T(e) \\
\leq\; & h(\alpha, k) \cdot \sum_{j=1}^{k} \frac{\text{vol}(G[P_i]) \cdot \log(\text{vol}(G[P_i]))}{2} \\
\leq\; & h(\alpha, k) \cdot \sum_{j=1}^{k} \frac{\text{vol}(G[P_i]) \cdot \log(\text{vol}(G[P_i]))}{2\Phi_{G[P_i]} \cdot \frac{1}{3}\text{vol}(G[P_i]) \cdot \log(\frac{2}{3}\text{vol}(G[P_i]))}OPT_{G[P_i]} \\
\leq\; & h(\alpha, k) \cdot \max_{i}\frac{3\log(\text{vol}(G[P_i]))}{2\Phi_{G[P_i]} \cdot \log(\frac{2}{3}\text{vol}(G[P_i]))} \sum_{j=1}^{k} OPT_{G[P_i]} \\
\leq\; & h(\alpha, k) \cdot \max_{i}\frac{3\log(\text{vol}(G[P_i]))}{2\Phi_{G[P_i]} \cdot \log(\frac{2}{3}\text{vol}(G[P_i]))}OPT_G \\
\leq\; & h(\alpha, k) \cdot \frac{3}{2\beta \log(\frac{4}{3})}OPT_G
\end{aligned}
$$

Lemma E.1 follows. □

Note that $h(\alpha, k) = O\left(\frac{1}{(1-\alpha)}\log\frac{k}{1-\alpha}\right)$, Theorem 3.2 follows. □

F Experimental results on Amazon network

We do our experiments on Amazon network [4] for which the set of ground-truth clusters has been given. For two sets A, B, the *Jaccard Index* of them is defined as $J(A, B) = |A \cap B|/|A \cup B|$. We pick the largest cluster which is a subgraph with 58283 vertices and 133178 edges. We run HCSE algorithm on it. For each ground-truth cluster c that appears in this subgraph, we find from the resulting cluster tree an internal node that has maximum Jaccard index with c. Then we calculate the average Jaccard index $\overline{J}$ over all such c. We also calculate cost(SE) and cost(Das). The results are demonstrated in Table 3. HCSE performs better for $\overline{J}$ and cost(SE), while LOUVAIN performs better for cost(Das). Because of unbalance in over-fitting and under-fitting traps, HLP outperforms none of the other two algorithms for all criteria.

index	HCSE	HLP	LOUVAIN
$\overline{J}$	**0.20**	0.16	0.17
cost(SE)	**1.85E6**	2.05E6	1.89E6
cost(Das)	5.57E8	3.99E8	**3.08E8**

Table 3: Comparisons of the average Jaccard index ($\overline{J}$), cost function based on structural entropy (cost(SE)) and Dasgupta's cost function (cost(Das)).

G Some figures and pseudocodes

Figure 3: Illustrations of stretch and compress for a u-triangle. A binary cluster tree is constructed first by stretch, and then edge e is compressed, which yields a non-binary tree.

Figure 4: Illustration of stratification for a 2-level cluster tree. The preference of (a) and (b) depends on the average sparsity of triangles at each level.

---

[4]http://snap.stanford.edu/data/

Algorithm 5: Stretch

Input: a u-triangle T_u
Output: a binary tree rooted at u
1 Let $\{v_1, v_2, \ldots, v_\ell\}$ be the set of leaves of T_u;
2 Compute $\eta(a, b)$ which is the cost reduced by merging siblings a, b into a single cluster;
3 **for** $t \in [\ell - 1]$ **do**
4      $(\alpha, \beta) \leftarrow \arg\max_{(a,b) \text{ are siblings}} \{\eta(a, b)\}$;
5   Add a new node γ;
6      $\gamma.parent \leftarrow \alpha.parent$;
7      $\alpha.parent = \gamma$;
8      $\beta.parent = \gamma$;

9 return T_u

Algorithm 6: Compress

Input: a binary tree T
1 **while** *T's height is more than* 2 **do**
2      $e \leftarrow \arg\min_{e' \in \hat{E}(T)} \{\Delta(e')\}$;
3   Denote $e = (u, v)$ where u is the parent of v;
4   **for** $w \in v.children$ **do**
5          $w.parent \leftarrow u$;
6   Delete v from T;