Learning to Understand Videos From Encoded Bytes

Abstract

We present an approach to understand video from encoded bytes, e.g., mp4s. These compressed videos are 99% smaller than the RGB pixel representations which are currently commonly used for video understanding. Encoded videos are able to compress the pixels by taking advantage of the redundant information across the frames using special encoding, such as key frames and motion residuals to handle this. However, standard video understanding models do not take advantage of this significant compression already available for each video, and instead either heavily subsample the frames or only work on short segments of the video. Here, we present an approach to understanding video from encoded bytes directly. We note that simply applying existing models, e.g., Transformers or State-Space models, to video byte sequences does not work, both due to difficulty in handling very long video byte sequences and easy overfitting. To address these challenges, we design a State-Space model with sequence parallelism to handle very long byte sequences, reaching **15 million tokens** in training, and essentially unlimited tokens in inference. We also propose a multilevel SSM activation fusion that reduces sequence length, which we find also benefits video understanding. We evaluate on six video understanding benchmarks including long, high-fps and video + audio understanding tasks and demonstrate competitive performance, illustrating, for the first time, the feasibility of learning from compressed video byte representations.

1 Introduction

Video understanding is an important problem in computer vision. Unlike images, videos contain multiple frames. In traditional settings, these frames are treated as a sequence of images (Simonyan & Zisserman, 2014; Carreira & Zisserman, 2017; Yue-Hei Ng et al., 2015; Tran et al., 2015), which greatly increases the compute costs and memory requirements and makes it hard to scale to longer and longer videos. Here, we propose an alternative approach which instead understands videos as encoded bytes, e.g., mp4 byte streams. The main advantage is the significant memory savings in processing compressed video, since the compression codecs take advantage of redundant pixels in consecutive frames, they are greatly able to reduce the size of a video. Moreover, the video byte streams are naturally suited for sequential models, as they are designed for video streaming and playback, where the decoders reconstruct the sequential frames from the bytes. And further, byte streams do not contain strong inductive biases, and so do not require operations like convolutions as in ViTs (Dosovitskiy et al., 2020). While byte-based representations are highly compressed, both pixel and byte representations contain the same information, and both have a complex, inconsistent, non-linear mapping between the inputs and semantic understanding, thus it is theoretically possible to learn any video understanding task from either input, which we explore here.

As a motivation, using the standard video representation of float16 $[F \times H \times W \times 3]$, and assuming 30fps and 480 resolution, one would need roughly 40 megabytes of memory per second of video for storing just the pixels (not including the model weights or intermediate activations). For a 10 minute video at 30 FPS and 480 resolution, this would use roughly 25GB of memory just for the pixel inputs. However, that same video encoded with a bitrate of 2Mbps (YouTube's recommended compression rate for 480p videos), would use only about 150MB for the same 10-minute video, which, compared to 25GB, yields a significant reduction in filesize, i.e., about 99% smaller. If we are able to perform video understanding on compressed byte inputs, this will allow for great compute savings and enable scaling to long videos.

Table 1: Our approach is able to handle very long byte sequences from raw compressed video formats, supporting up to **15 Million byte tokens** during training, leading to significant performance improvements.

Sequence Length	ActivityNet-QA Acc (%)
250,000	42.5
2 Million	54.2
15 Million	**56.3**

Table 2: Testing on longer sequence lengths **(20 Million bytes, which corresponds to ∼13 minutes of video)** than training (15M bytes) yields further gains, and can theoretically support unlimited tokens during inference.

Sequence Length	ActivityNet-QA Acc (%)
15 Million	56.3
20 Million	**57.1**

Further, existing specialized video models either focus on modeling sparse temporal relationships on image-based features (e.g., (Yue-Hei Ng et al., 2015; Piergiovanni et al., 2017; Chen et al., 2023; Lin et al., 2025)) or use tube-based features on short segments of video (Arnab et al., 2021; Piergiovanni et al., 2023) or apply segment-based pooling (Shou et al., 2016). These prior works perform well on video, but are essentially leveraging existing image-based models for short or sparsely sampled video segments. Instead here, based on the observation that compressed videos contain all the information needed to reconstruct the pixels, but with much less redundant information, we design an approach to directly learn specifically from video bytes. We note that many video datasets contain short clips, and datasets focused on long videos (LVBench (Wang et al., 2024a), MLVU (Zhou et al., 2024), VUE-TR (Team et al., 2025b), Neptune (Nagrani et al., 2024), etc.) are either being used for evaluation-only or are trained on relatively sparse sampling of the video frames due to memory constraints. For example, recent works, such as InternVideo2 (Wang et al., 2024b) and VIDI (Team et al., 2025b) only train on short segments with 8 frames and 1 fps up to 120 frames, respectively, and Hour-LLaVA (Lin et al., 2025) very sparsely samples video tokens from a frozen image encoder.

Training on video bytes allows using all the frames with much less memory, however, as we show in the experiments, this is a non-trivial task due to a few issues. First, encoded video bytes are very long sequences. Instead of a video being a $[F \times H \times W \times 3]$ that can be further compressed with spatial and temporal pooling, we have an input of $[L \times D]$, where L is the sequences length and D is the embedding size of the model. For video bytes, this results in sequences with millions of tokens, which is extremely long even compared to modern LLMs (e.g., LLAMA 3.1 (Grattafiori et al., 2024) supports 128,000 tokens in inference, Gemma (Team et al., 2025a) was trained with an 8k sequence length). This presents a real problem, as this becomes a long-sequence length learning problem. Second, we find that Transformers are not the best suited model for this task, due to the long sequences and poor scaling of self-attention. Finally, understanding the encoded representation is far more challenging than understanding pixels, as the representation is much more compressed. Thus, taking an existing LLM model and directly training it on encoded video bytes does not perform well at all. We propose a method to learn from encoded video bytes that works on very long sequences, which are of different structure than text inputs, and we develop a multilevel, sequentially-parallel modeling of video bytes and find it is well suited for this challenging task. We make several key contributions to enable video understanding from bytes:

- We present the first approach to understand video from raw, encoded bytes, circumventing the decoding process which increases the video volume processed by over 100x, and leveraging the highly compressed video inputs which are ubiquitous video representations.

- We propose an efficient parallelization and gradient accumulation method, with a novel correction and propagation of the state, that enables training on extremely long bytes sequences, e.g., **15 million** (Tables 1, 2), and theoretically unlimited inference length.

- To further scale, a 'multilevel' SSM efficiently accumulates SSM activations and, together with the sequence parallelism, enables scaling to very long sequences during both training and inference. This model greatly outperforms standard SSMs and Transformers when applied to encoded video bytes (Table 9).

Figure 1: Model outline. A sequentially parallel model (Sec. 3.1), here validated with a Mamba SSM, allows for parallel processing and accumulates and corrects the model state, ensuring the retention of information beyond what can fit in device memory. For further scaling, the raw bytes are embedded, then processed by SSM layers (here M) in a multilevel module (Sec. 3), which is repeated N times. This enables efficient paralelization of very long sequences.

We note that here we do not use any prior knowledge about the structure of the bytes, e.g., information about the codec, which makes the task significantly harder, but also more general. We show that data-augmentation addresses the issue, noting that injecting additional information about the sequence structure can be further leveraged in future work.

2   Learning from Raw Video Bytes

Our approach takes a sequence of raw video bytes as input, rather than pixels as in most prior works. For this work, we use the standard h.264 codec (Wiegand et al., 2003) and mp4 container (mp4, 2020) to obtain the video bytes. One observation is that these codecs are designed for streaming video. Importantly, this means that when decoding and reconstructing the pixels, the decoder algorithm does it byte-by-byte, or based on short segments of bytes. This means that bytes that are far apart do not really depend on each other to reconstruct the pixels, since they are compressed with streaming in mind and refer to different frames. As a result the standard global self-attention in Transformer models is not needed to understand video bytes. This is a unique characteristic of compressed video bytes, which is not present in text sequences and language modeling. However, to understand a video, i.e., for classification or question answering purposes, the model does need to be able to understand the whole sequence. To address this, we develop techniques which (a) work with extremely long sequences, (b) use sequential modeling to better model streaming video bytes, rather than self-attention as Transformers use and (c) a hierarchical model that is able to go from low-level bytes to semantic understanding. This allows understanding both low-level local features as well as high level details of the full video. Our approach is also generic, we simply input byte sequences without providing any details about the structure, such as i or p frames, and let the model learn with no given priors or biases, an approach that has been important in language modeling. This model is shown in Fig. 1 and described further in Sec. 3. Another issue is that the model tends to overfit and not generalize well when given bytes as input, which we address in Sec. 3.2.

On the other hand, learning from raw bytes presents opportunities for learning from much more economical and efficient compressed video formats which are already readily available, as videos are stored in these formats. Additionally, the approach directly transfers to audio+video inputs, as shown in the experiments. We further save compute in the input pipeline, as we do not need to decode the bytes into pixels , though for larger models this is not the bottleneck, as the compute time of the model is the primary bottleneck.

Input Bytes (L): 0000001A6764001FACD9A014016E0000000168EBCCB22C....

Figure 2: The multilevel SSM. The input is processed sequentially by SSM layers. The pooling layers reduce the sequence length; projection layers increase the dimensionality. This process is repeated multiple times, forming the multilevel SSM. This is further parallelized in order to handle long sequences (Sec. 3.1).

3 Proposed Approach - Parallelized Multilevel SSM

To learn from very long sequences, we first design a multilevel SSM module, which has a better handle over the sequence information. Recent SSM models (Gu et al., 2021; Gu & Dao, 2023; Gu et al., 2022b), which scale linearly and are more suitable for long sequences, are still not able to fully address some main challenges, such as long-range recall, recency bias, global sequence understanding, and still have some inefficiencies, e.g., VideoMamba (Li et al., 2024b) trained on only 8 frames and evaluated on up to 64 frames. We choose to build upon an SSM for a few reasons. First the SSM (Gu et al., 2021) does not use self-attention, thus it scales linearly to long sequences. Second, the SSM processes the bytes sequentially as they are input. Since video codecs like mp4s were designed for streaming videos, an SSM is naturally applicable to this input, processing the bytes and updating the state in the order the bytes are input. Specifically, we use the Mamba (Gu & Dao, 2023) architecture as the base model, given its strong performance among existing SSMs, hardware efficiency, and ability to vary the representation with time (Gu et al., 2021; 2022b; Gu & Dao, 2023; Chen et al., 2024). An overview of the multilevel SSM is shown in Figure 2. Given an input sequence, S, that consists of L bytes, we first embed the bytes as D-dimensional vectors, which are input to Mamba. We then apply M standard Mamba layers. After this, we pool the bytes which decreases the sequences from length L to length $\frac{L}{L_s}$, e.g, $L_s = 2$ to reduce it be half. We explore different forms of this pooling. We repeat

this stack of M Mamba layers, followed by a pooling layer N times, forming the multilevel SSM. Finally, we average pool over the remaining tokens and a fully connected layer for classification tasks. Compared to a prior hierarchical SSM (Bhirangi et al., 2024), the key differences is that our SSM is over the whole input sequence, rather over segments and we stack many levels (4 in our experiments) of the pooling, rather than just two levels. Since SSMs scale linearly with sequence length, there is no benefit to splitting the sequence into segments when running the SSM, and applying the SSM to the whole sequence allows the model to have knowledge of the whole sequence through the SSM state.

For the embedding, as there are 256 bytes, we use a vocabulary size of 256 tokens with an embedding dimension (D) of 256. We explore the embedding dimension in the ablations. We note that this embedding dimension increases, more memory is used. Despite the fact that using 256 dimensions has more expressiveness than the original 256 bytes, we found using fewer dimensions greatly reduced performance, and going above 256 did slightly improve performance, but also increases memory usage. To address this, we make a few important steps: 1) make the input to the embedding a uint8 type, rather than an int32 as is standard in LLMs (due to their larger vocabulary size). This saves $\sim 75\%$ of memory by needing only 8 bits per token; 2) we use 16-bit precision on the embeddings themselves, finding no difference to 32-bit precision, but saving memory. We evaluate attention, averaging and concatenation as pooling methods (see the Appendix for details).

3.1 Handling Long Sequences with Parallelism

Due to the very long sequences that video bytes have, we propose a sequence parallelism technique, utilizing multilevel SSM states. We observe that the SSM outputs can be computed for any part of the sequence without having access to the prior state, then propose a simple update applied when given the state. This allows us to parallelize by placing subsequences on different devices and computing the SSM on each device, then applying an update on the outputs, once each device is done computing. This allows cheap parallelism along the sequence axis, which allows us to scale more efficiently to long sequences. We find that sequence parallelism is around 2x faster than model parallelism for this SSM. Namely, we compute and store the hidden states for each device as if the sequence starts with hidden state set to zero. Consider a signal with L tokens $x = [x_1, x_2, ..., x_L]$ and V devices, we divide the signal into V subsequences each of length $K = \frac{L}{V}$ and apply SSM on each device independently, i.e., the initial hidden state is set to zero for every device. The final hidden states $h^{(i)}$ (Eq. 1) and outputs $y^{(i)}$ of the SSM (Eq. 2) applied to each of the V subsequences is as given below. Given A, B, C are the parameters of the SSM and h is the state:

$$
\begin{aligned}
h^{(1)} &= Bx_K + ABx_{K-1} + \cdots + A^{K-1}Bx_1 \\
h^{(2)} &= Bx_{2K} + ABx_{2K-1} + \cdots + A^{K-1}Bx_{K+1} \\
h^{(V)} &= Bx_L + ABx_{K-1} + \cdots + A^{K-1}Bx_{(V-1)K+1}
\end{aligned}
\tag{1}
$$

$$
\begin{aligned}
y^{(1)} &= [CBx_1, CBx_2 + CABx_1, \ldots, CBx_K + CABx_{K-1} \\
&\quad + \cdots + CA^{K-1}Bx_1] \\
y^{(2)} &= [CBx_{K+1}, CBx_{K+2} + CABx_{K+1}, \ldots, CBx_{2K} \\
&\quad + CABx_{2K-1} + \cdots + CA^{K-1}Bx_{K+1}] \\
y^{(V)} &= [CBx_{(V-1)K+1}, \ldots, CBx_{VK} + CABx_{VK-1} \\
&\quad + \cdots + CA^{K-1}Bx_{(V-1)K+1}]
\end{aligned}
\tag{2}
$$

The above hidden states are computed in parallel. As observed, they lack the contribution of state from the previous chunks, which are computed on other devices. Thus, the final hidden state from previous sequence shard is added to correct for the missing factor. The equations for corrected hidden states are given in Eq. 3.

Figure 3: Using sequence parallelism and gradient accumulation to train on sequence lengths of up to 15 million. A key benefit of the SSM is parallel computation of the states, plus a cheap correction calculation (Sec. 3.1), making it easy to scale and suited for streaming video byte data.

$$
\begin{aligned}
h^{(1)}_{corrected} &= h^{(1)} \\
h^{(2)}_{corrected} &= A^K h^{(1)} + h^{(2)} \\
h^{(V)}_{corrected} &= A^K h^{(V-1)}_{corrected} + h^{(V)}
\end{aligned}
\tag{3}
$$

Here h_0 is the hidden state to the entire sequence before splitting into subsequences. The equations for the output after the inclusion of correction factor to the hidden state is as given below (Eq. 4):

$$
\begin{aligned}
y^{(1)}_{corrected}[i] &= y^{(1)}[i] \\
y^{(2)}_{corrected}[i] &= C A^{(i)} h^{(1)}_{corrected} + y^{(2)}[i] \\
y^{(V)}_{corrected}[i] &= C A^{(i)} h^{(V-1)}_{corrected} + y^{(V)}[i]
\end{aligned}
\tag{4}
$$

Here $i \in [1, K]$ is the index of the output within the given subsequence. As shown, this allows us to compute the SSM in parallel across the devices, then correct the state afterwards, with a cheaper correction calculation. We also note here that we are building on Mamba which has the selection mechanism, however this mechanism does not depend on the states, only on the inputs, so it is unaffected by the changes we make here.

Training on even longer sequences. Building on that, we further push the limits to train on sequence lengths of up to 15 million using gradient accumulation. Here, we split a very long sequence into subsequences that are as long as we can fit into device memory. We run the first subseqeunce and compute the loss, but rather than taking an optimization step, we save the gradients, and run on the next subsequence using the last state h as the current state on the next subsequence (Fig. 3). We can then repeat this process as many times as needed to reach any length sequence, which enables learning from very long sequences. We note that this gradient accumulation approach for scaling, can theoretically introduce nonlinearities, due to the arbitrary boundaries in splitting the sequence. However, in practice we find that this is not a major limitation and the model is able to learn effectively from these long-range signals, and performs better than training without them (Table 1, 2).

3.2 Addressing Overfitting

We find that training data and augmentation is especially important. We observed that the model very easily overfits when trained on encoded videos. However, if we train on individual frames encoded on JPEGs, we did not observe this overfitting. We realized that when training on individual frames we randomly sampled one of the frames, and as Kinetics videos are 10 seconds long, and we had data at 25 fps, we had roughly 250 frames we were sampling from, i.e., we roughly increased the data by 250 times. If instead we trained the model using only a single JPEG byte string per video, e.g., the 100th frame, we saw the same overfitting behavior. In both these cases, when trained on a single encoded video or single encoded frame, the loss would go to 0 very quickly, while the evaluation accuracy would be relatively low, regardless of input format. This indicates the model needs significantly more training data, either in the form of data augmentation and/or pre-training. We find that straightforward data augmentation mitigates these effects.

Our next observation is that if we take two video clips and apply mild data augmentation, e.g., some slight color jittering, as is standard in training video models (e.g., ViViT (Arnab et al., 2021)), and encode them into mp4s, and compute the Levenshtein distance on the byte strings of these clips, we saw that over half the byte string is different. Visually, the two videos are indistinguishable. This suggests that the compressed Bytes-based representations have a large amount of variation even with seemingly small changes to the visual inputs. Because of this, when training video byte based models, we apply a large amount of data augmentation during training. Specifically, we apply random temporal and spatial cropping, color jittering, contrast adjustment, color inversion, posterization, solarization, brightness, sharpness, and cutout augmentations. These augmentations are all done on the RGB space, then encoded into mp4s and used to train the model. We don't apply any augmentation to the bytes themselves (e.g., byte-level dropout, random substrings, etc), and leave explorations of that for future work.

Self-supervised Pre-training. We also explore self-supervised pre-training for video byte based models. Byte-based representations enable many different fully self-supervised tasks. First, we can train a model that takes the encoded video bytes as input and produces the RGB pixels of the video as output. However, as video generation is a complex task, itself having many specialized models and methods which are computationally intensive (e.g., video diffusion), and since we don't care about actually generating videos, just about training a video understanding model on Byte-based representations, we simplify the RGB prediction significantly. Here, we take the output of the multilevel SSM model, and use an attention pooling layer to generate $F' \cdot H' \cdot W' \cdot D$ tokens. This is then reshaped to $F' \times H' \times W' \times D$, which gives us the rough size of the video. We then apply a small UNet-based (Ronneberger et al., 2015) model to upsample this to the video tensor $F \times H \times W \times 3$. We then apply a MSE loss between the predicted video and ground truth video RGB pixels. To further reduce compute, we generate only 10 frames per video (i.e., 1 fps for 10 second clips) at a low resolution of 128×128. While the reconstrustions do not look perfect, this provides a good enough learning signal to the model. Second, we explore a pre-training similar to how language models are trained: next byte prediction. I.e., the input to the model is a encoded mp4 byte string and the models task is to predict the next byte based on the previous bytes.

Table 3: Kinetics-600 and Kinetics-400 results. We note that our model is significantly cheaper than prior works and trained on much less data. PT stands for Pre-training.

Model	PT Data	PT Modalities	Params	TFLOPS	K600	K400
ViViT-L (Arnab et al., 2021)	JFT-300M	Img	-	-	82.9	83.5
ViViT-H (Arnab et al., 2021)	JFT-300M	Img	-	-	85.8	84.9
MerlotReserve-H (Zellers et al., 2022)	YT-1B	Vid+Audio+Text	644M	-	91.1	-
TubeViT-H (Piergiovanni et al., 2023)	ImageNet	Img	-	17.64	91.8	90.9
InternVideo2 (Wang et al., 2024b)	Many	Img+Vid+Audio+Text	6B	-	91.9	92.1
VideoMamba (Li et al., 2024b)	CLIP-400M	Img+Text	74M	28.42	-	85.0
VideoMAE (Tong et al., 2022)	None	-	600M	88.76	-	87.4
ST-MAE (Feichtenhofer et al., 2022)	IG-uncurated	Vid	600M	25.1	-	86.8
BytesSSM-B (ours)	HowTo100M	Vid	500M	1.88	60.5	61.3
BytesSSM-L (ours)	HowTo100M	Vid	1B	4.12	85.2	86.8

Table 4: Results on longer video understanding on AcitivityNet-QA (ANet) and CinePile benchmarks.

Model	ANet	CinePile
VideoCoca (Yan et al., 2022)	56.1	-
UMT-L (Li et al., 2023)	47.9	-
Mirasol-3B (Piergiovanni et al., 2024)	51.1	-
LLaVA-OV-7B Li et al. (2024a)	56.6	49.3
BytesSSM-L (ours)	57.1	47.5

4 Experiments

4.1 Main results

We present the main experimental results on the Kinetics-400 (Carreira & Zisserman, 2017), Kinetics-600 (Carreira et al., 2018), AcitivityNet-QA (Yu et al., 2019), CinePile (Rawal et al., 2024), MLB YouTube (Piergiovanni & Ryoo, 2018), and Kinetics-Sounds (Arandjelovic & Zisserman, 2017) benchmarks, which are popular video or video+audio understanding benchmarks. Please see the Appendix for implementation details.

Kinetics-400/600. Table 3 shows the classification performance of the proposed method on the commonly used activity understanding benchmarks, Kinetics-400/Kinetics-600, with 400/600 classes. We note that Kinetics has 10 second videos, and we used 25 fps (far higher than previous works) giving us 250 frames per video, but after encoding, the input is only approximately 250,000 bytes long. We also note that prior works benefit from image-based pre-training which is beneficial, while we here only use video pre-training. Our results show strong performance, even when compared to larger video and video foundational models, despite using far less data and compute. Our model uses only 2-4 TFLOPs, much fewer than others including SSM-based models.

Table 5: Results on the MLBYouTube benchmarks which is a high-fps dataset for fine-grained video understanding.

Model	Params	MAP
MLBYT (Piergiovanni & Ryoo, 2018)	-	62.6
BytesSSM-B (ours)	500M	63.5
BytesSSM-L (ours)	1B	64.5

Table 6: Kinetics-Sounds (Arandjelovic & Zisserman, 2017) results. We see that including audio in the encoded video helps.

Model	+Audio	MAP
MBT (Nagrani et al., 2021)	Yes	85.0
BytesSSM-L (ours)	No	81.4
BytesSSM-L (ours)	Yes	84.4

Figure 4: Plot of accuracy vs. runtime and frames, where the size of each model indicates how many FLOPs it uses. This shows the Bytes models scale better to longer sequences, use fewer FLOPs, even as the model scales up, showing the potential of this approach.

Long Videos. Table 4, further shows performance on longer videos which is clearly very challenging for raw bytes formats. The task is Video QA (see the appendix for details) and the videos reach 15 Million training sequence lengths.

High-Fps Videos. Table 5 further evaluates the performance on the MLB Youtube benchmark (Piergiovanni & Ryoo, 2018), which is a benchmark for distinguishing between fine-grained activities, which requires understanding motion at higher FPS than other datasets, like Kinetics. As seen, the model performs very well, outperforming the state-of-the-art approaches, using encoded bytes as input.

Audio+Video. Our model easily extends to Audio+Video from bytes, showing competitive performance (Table 6).

4.2 Model efficiency

One advantage of the proposed approach is the compute and time savings, since it operates on a highly compressed format. In Figure 4, we present the results comparing the FLOPs and runtime of the proposed model. As seen, our models are much more lightweight. Furthermore, with other approaches a very limited number of frames can be sampled, e.g., up to 32, and it becomes prohibitively expensive to sample more frames for these models, whereas here the information content of all frames is processed which exceeds the upper bounds over number of frames for other models, e.g., all 250 frames on Kinetics (10 second clips at 25fps) for ours vs 32 or 64 for prior works.

Parameter Efficiency Discussion Encoded video bytes are a compressed representation and as such we found it took more parameters and training iterations to match the performance of pixel-based models. Models operating on pixels start with a representation that is already structured for (human) perception. Nearby pixels are spatially related, and basic patterns (edges, textures) are immediately available, and that is used by convolution/patch based models. However, starting from bytes, the model must first implicitly

Table 7: Scaling ablation on Kinetics using BytesSSM-Tiny. Increasing the embedding dimension of the model leads to overfitting.

Model	K600
256 Embedding	25.4
512 Embedding	25.7
1024 Embedding	21.2

Table 8: Pooling method experiments, using BytesSSM-Tiny.

Method	TFLOPs	K600
Attention Pooling	1.33	23.9
Average Pooling	0.38	20.7
Concatenation Pooling	0.47	25.4

Table 9: Comparing different forms of the model. A standard Transformer with full global attention did not fit into memory with the long sequence lengths videos have (BytesSSM-Tiny model).

Model	K600
Transformer	N/A
Transformer with loc. attention with 512 tokens	15.4
Causal Conv ($\sim$ same params as BytesSSM-Tiny)	15.8
BF-Ti Horton et al. (2023)	17.5
Multilevel Transformer	16.7
Mamba (Baseline SSM)	18.4
BytesSSM-Tiny (with Multilevel SSM) (ours)	25.4

learn the 'language' of the codec. Thus some portion of the model's parameters are dedicated to solving this problem of 'decoding' the byte stream into a useful latent representation, which pixel-based models don't have to do, instead starting with the inductive bias of convolution/patches. In some sense, a Bytes-based model is doing more with each parameter, since it has no inductive bias. We note that the FLOPs, runtime and memory usage of the model is significantly lower than pixel-based ViTs, despite the larger parameter count. Since the relationship between FLOPs, runtime, memory usage, and parameters depends a lot on the network structure, the multilevel SSM on Bytes-based data enables these compute savings even with more parameters.

4.3 Ablations

For the ablations, we report the accuracy on Kinetics-600 using the BytesSSM-Tiny model.

Model ablations. Table 7 shows how the model scales with size, particularly, with increasing the size of the dimensionality of the feature representation in the model, which also results in larger model. As seen larger feature representation is beneficial, however, we observe overfitting for very large model sizes. Table 8 compares different versions of the pooling. We use concatenation pooling as it performs best for relatively small increase in FLOPs.

Table 9 explores several versions of the proposed model. As seen, using SSM-style models provides benefits for this application due to the sequence lengths and nature of the encoded byte structure, compared to a Transformer (Vaswani et al., 2017) model. The proposed Multilevel SSM provides a further large jump in performance, as it has much higher capacity for increased sequence lengths. We also compare to a Multilevel Transformer, which uses the same pooling methods as the Multilevel SSM, but replaces the Mamba blocks with standard Transformer blocks.

We further compare to a causal convolution based model, as well as, the one proposed in (Horton et al., 2023), which uses many pooling layers and sliding window attention for encoded e.g., JPEG/PNG images. We note that here we are using longer sequences than those tested in that paper (262,144 vs. 150,000). For both, we used models matching the same parameter count as BytesSSM-Tiny. In Table 9 (Lines 3, 4), we find that our approach significantly outperforms these variants, as well.

Table 10: Effects of pre-training tasks, using the BytesSSM-Tiny model, on HowTo100M.

Method	K600
None	25.4
RGB prediction	31.2
Next-byte prediction	28.6

Table 11: Training on JPEG bytes and transferring to mp4 bytes, using BytesSSM-Tiny model.

Method	K600
No Pre-training	25.4
JPEG Pre-trained	27.2
mp4 Pre-trained	31.2

Pre-training Experiments. Table 10 explores different methods for pre-training for the proposed models. We compare RGB reconstruction to next-byte prediction, finding that RGB reconstruction is slightly better as a pre-training task, but both are effective.

We also see how transferable Byte-based models are. In Table 11, we compare no pre-training to a model pre-trained for RGB reconstruction vs a model pre-trained on JPEG bytes for classification. Previously, most video works used image pre-trained backbones which were then further trained on video data, and this experiment is similar to that. We see some benefit from pre-training with image JPEG bytes, compared to no pre-training, but it is not as good as video byte based pre-training. This is expected, but also shows these models are learning some generalization knowledge about encoded byte structures, even for very different encodings.

Table 12: Effects of data augmentation. BytesSSM-Tiny model.

	K600
1x data	2.4
10x data	5.2
100x data	18.6
200x data	25.4

Data Augmentation Effects. Table 12 shows the effect of data augmentation when training. We generated a fixed number of samples by applying data augmentation as described above to generate 1 to 200 samples for each video. We find that increasing the data augmentation increases the performance of the model a lot.

Preprocessing Cost Comparisons We further compare the different preprocessing steps and times. In some cases, videos are stored in different formats, so a one-time transcoding operation may be needed. For these comparisons, we used the Kinetics videos. For the bytes input pipeline, we had a one-time transcoding cost of 193ms per video, 10ms to load the mp4 into memory, <1ms to transfer it to the TPU/GPU, for a total of 203ms. For pixel-based pipelines, we had 180ms to decode a mp4 into RGB pixels, 69ms for crop, resize, etc. 4ms to transfer 64 frames to TPU/GPU, a total of 254ms. These are very similar. The transcode, though, only needs to be done once, so for training, our input pipeline is significantly faster.

5 Related Works

Efficient Video Representations and Compression. Traditional video compression standards, such as H.264/AVC and HEVC, rely heavily on Discrete Cosine Transform (DCT) for spatial redundancy and motion vectors for temporal redundancy to achieve high compression rates Szczerba et al. (2009); mp4 (2020). Motivated by this efficiency, researchers have explored leveraging these compressed components directly to avoid the computational cost of full decoding. For instance, CoViAR Wiles et al. (2023) demonstrated the benefit of training directly on P-frame motion vectors and I-frame residuals. However, CoViAR still relies

on standard CNN backbones applied to these partially decoded components. More recently, works such as Deep Residual Learning in the JPEG Transform Domain Ehrlich & Davis (2019) and Learning from the CNN-Based Compressed Domain Wang et al. (2022) have pushed this further by designing networks that operate mathematically within the compressed domain (e.g., modifying convolutions to accept DCT coefficients), thereby bypassing the decoding step entirely. While promising, these methods often require specialized architectures to handle the non-spatial nature of frequency domain inputs.

Neural Codecs and Byte-Level Learning. Parallel to heuristic compression, neural video codecs have emerged as a data-driven alternative. Compressed Vision Torfason et al. (2018) proposed learning VQ-VAE models to compress video data, allowing downstream models to operate in a learned latent space. While effective for tasks like action recognition on Kinetics Carreira et al. (2018), this approach shifts the computational burden to the neural codec itself. At the extreme end of this spectrum, Horton et al. (2023) explored learning from raw image bytes. However, their approach is currently limited by sequence length constraints, effectively restricting it to small images or short clips.

Efficient Sequence Modeling with State Space Models. Addressing the computational inefficiency of Transformers, which scale quadratically $\mathcal{O}(L^2)$ with sequence length L, State Space Models (SSMs) have gained prominence for their ability to model long-range dependencies with linear complexity $\mathcal{O}(L)$. The Structured State Space model (S4) Gu et al. (2022a) successfully modeled extremely long sequences by constraining the state matrix with HiPPO theory. Building on this, Mamba Gu & Dao (2023) introduced a selective scanning mechanism that allows the model to filter irrelevant information dynamically. In the video domain, VideoMamba Li et al. (2024b) recently demonstrated that purely SSM-based architectures can rival Transformer performance on long video understanding tasks while maintaining linear scaling. This architectural efficiency is critical for processing long temporal contexts that are computationally prohibitive for standard Vision Transformers.

6 Conclusions

We propose a novel approach to understand videos from encoded and compressed byte representations. This has the advantage of saving memory and compute, compared to working on pixels, and better scales to longer sequences, reaching 15 Million. We show strong performance on this new and challenging task and demonstrate there is much potential in learning from raw video bytes.

Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here.

References

Coding of audio-visual objects. ISO/IEC 14496-14:2020, 2020.

Relja Arandjelovic and Andrew Zisserman. Look, listen and learn. In *Proceedings of the IEEE international conference on computer vision*, pp. 609–617, 2017.

Anurag Arnab, Mostafa Dehghani, Georg Heigold, Chen Sun, Mario Lučić, and Cordelia Schmid. Vivit: A video vision transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6836–6846, 2021.

Raunaq Bhirangi, Chenyu Wang, Venkatesh Pattabiraman, Carmel Majidi, Abhinav Gupta, Tess Hellebrekers, and Lerrel Pinto. Hierarchical state space models for continuous sequence-to-sequence modeling. *arXiv preprint arXiv:2402.10211*, 2024.

Joao Carreira and Andrew Zisserman. Quo vadis, action recognition? a new model and the kinetics dataset. In *CVPR*, 2017.

Joao Carreira, Eric Noland, Andras Banki-Horvath, Chloe Hillier, and Andrew Zisserman. A short note about kinetics-600. In *CVPR Workshop on Computer Vision in Sports*, 2018.

Guo Chen, Yifei Huang, Jilan Xu, Baoqi Pei, Zhe Chen, Zhiqi Li, Jiahao Wang, Kunchang Li, Tong Lu, and Limin Wang. Video mamba suite: State space model as a versatile alternative for video understanding. In *https://arxiv.org/abs/2403.09626*, 2024.

Xi Chen, Josip Djolonga, Piotr Padlewski, Basil Mustafa, Soravit Changpinyo, Jialin Wu, Carlos Riquelme Ruiz, Xiao Wang Sebastian Goodman, Yi Tay, Daniel Salz Siamak Shakeri, Mostafa Dehghani, Mario Lucic, Michael Tschannen, Arsha Nagrani, Hexiang Hu, Mandar Joshi, Bo Pang, Ceslee Montgomery, Paulina Pietrzyk, Marvin Ritter, AJ Piergiovanni, Matthias Minderer, Filip Pavetic, Austin Waters, Gang Li, Ibrahim Alabdulmohsin, Lucas Beyer, Julien Amelot, Kenton Lee, Andreas Peter Steiner, Yang Li, Daniel Keysers, Anurag Arnab, Yuanzhong Xu, Keran Rong, Alexander Kolesnikov, Mojtaba Seyed-hosseini, Anelia Angelova, Xiaohua Zhai, Neil Houlsby, and Radu Soricut. PaLI-X: On scaling up a multilingual vision and language model. In *ArXiv:2305.18565*, 2023.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Max Ehrlich and Larry S Davis. Deep residual learning in the jpeg transform domain. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 3484–3493, 2019.

Christoph Feichtenhofer, Haoqi Fan, Yanghao Li, and Kaiming He. Masked autoencoders as spatiotemporal learners. In *ArXiv:2205.09113*, 2022.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. In *arXiv:2312.00752*, 2023.

Albert Gu, Isys Johnson, Karan Goel, Khaled Saab, Tri Dao, Atri Rudra, and Christopher Re. Combining recurrent, convolutional, and continuous-time models with the structured learnable linear state space layer. 2021.

Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. In *ICLR*, 2022a.

Albert Gu, Ankit Gupta, Karan Goel, and Christopher Ré. On the parameterization and initialization of diagonal state space models. 2022b.

Maxwell Horton, Sachin Mehta, Ali Farhadi, and Mohammad Rastegari. Bytes are all you need: Transformers operating directly on file bytes. In *arxiv.org/pdf/2306.00238*, 2023.

Diederik P Kingma. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. Llava-onevision: Easy visual task transfer, 2024a. URL `https://arxiv.org/abs/2408.03326`.

Kunchang Li, Yali Wang, Yizhuo Li, Yi Wang, Yinan He, Limin Wang, and Yu Qiao. Unmasked teacher: Towards training-efficient video foundation models. In *ICCV*, 2023.

Kunchang Li, Xinhao Li, Yi Wang, Yinan He, Yali Wang, Limin Wang, and Yu Qiao. Videomamba: State space model for efficient video understanding. In *https://arxiv.org/pdf/2403.06977*, 2024b.

Jingyang Lin, Jialian Wu, Ximeng Sun, Ze Wang, Jiang Liu, Yusheng Su, Xiaodong Yu, Hao Chen, Jiebo Luo, Zicheng Liu, et al. Unleashing hour-scale video training for long video-language understanding. *arXiv preprint arXiv:2506.05332*, 2025.

Arsha Nagrani, Shan Yang, Anurag Arnab, Aren Jansen, Cordelia Schmid, and Chen Sun. Attention bottlenecks for multimodal fusion. 2021.

Arsha Nagrani, Mingda Zhang, Ramin Mehran, Rachel Hornung, Nitesh Bharadwaj Gundavarapu, Nilpa Jha, Austin Myers, Xingyi Zhou, Boqing Gong, Cordelia Schmid, et al. Neptune: The long orbit to benchmarking long video understanding. *arXiv preprint arXiv:2412.09582*, 2024.

A Piergiovanni, Chenyou Fan, and Michael Ryoo. Learning latent subevents in activity videos using temporal attention filters. In *Proceedings of the AAAI conference on artificial intelligence*, volume 31, 2017.

AJ Piergiovanni and Michael S. Ryoo. Fine-grained activity recognition in baseball videos. In *CVPR Workshop on Computer Vision in Sports*, 2018.

AJ Piergiovanni, Weicheng Kuo, and Anelia Angelova. Rethinking video vits: Sparse video tubes for joint image and video learning. *CVPR*, 2023.

AJ Piergiovanni, Isaac Noble, Dahun Kim, Michael Ryoo, Victor Gomes, and Anelia Angelova. Mirasol3B: A multimodal autoregressive model for time-aligned and contextual modalities. In *CVPR*, 2024.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

Ruchit Rawal, Khalid Saifullah, Miquel Farré, Ronen Basri, David Jacobs, Gowthami Somepalli, and Tom Goldstein. Cinepile: A long video question answering dataset and benchmark. *arXiv preprint arXiv:2405.08813*, 2024.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical image computing and computer-assisted intervention–MICCAI 2015: 18th international conference, Munich, Germany, October 5-9, 2015, proceedings, part III 18*, pp. 234–241. Springer, 2015.

Zheng Shou, Dongang Wang, and Shih-Fu Chang. Temporal action localization in untrimmed videos via multi-stage cnns. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1049–1058, 2016.

Karen Simonyan and Andrew Zisserman. Two-stream convolutional networks for action recognition in videos. *Advances in neural information processing systems*, 27, 2014.

Krzysztof Szczerba, Søren Forchhammer, Jesper Stottrup-Andersen, and Peder Tanderup Eybye. Fast compressed domain motion detection in h. 264 video streams for video surveillance applications. In *2009 Sixth IEEE International Conference on Advanced Video and Signal Based Surveillance*, pp. 478–483. IEEE, 2009.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025a.

Vidi Team, Celong Liu, Chia-Wen Kuo, Dawei Du, Fan Chen, Guang Chen, Jiamin Yuan, Lingxi Zhang, Lu Guo, Lusha Li, et al. Vidi: Large multimodal models for video understanding and editing. *arXiv preprint arXiv:2504.15681*, 2025b.

Zhan Tong, Yibing Song, Jue Wang, and Limin Wang. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pre-training. 2022.

Robert Torfason, Fabian Mentzer, Eirikur Agustsson, Michael Tschannen, Radu Timofte, and Luc Van Gool. Towards image understanding from deep compression without decoding. *arXiv preprint arXiv:1803.06131*, 2018.

Hugo Touvron, Matthieu Cord, Alaaeldin El-Nouby, Piotr Bojanowski, Armand Joulin, Gabriel Synnaeve, and Hervé Jégou. Augmenting convolutional networks with attention-based aggregation. *arXiv preprint arXiv:2112.13692*, 2021.

Du Tran, Lubomir Bourdev, Rob Fergus, Lorenzo Torresani, and Manohar Paluri. Learning spatiotemporal features with 3d convolutional networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 4489–4497, 2015.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. 2017.

Weihan Wang, Zehai He, Wenyi Hong, Yean Cheng, Xiaohan Zhang, Ji Qi, Xiaotao Gu, Shiyu Huang, Bin Xu, Yuxiao Dong, et al. Lvbench: An extreme long video understanding benchmark. *arXiv preprint arXiv:2406.08035*, 2024a.

Yi Wang, Kunchang Li, Xinhao Li, Jiashuo Yu, Yinan He, Guo Chen, Baoqi Pei, Rongkun Zheng, Zun Wang, Yansong Shi, et al. Internvideo2: Scaling foundation models for multimodal video understanding. In *European Conference on Computer Vision*, pp. 396–416. Springer, 2024b.

Zhenzhen Wang, Minghai Qin, and Yen-Kuang Chen. Learning from the cnn-based compressed domain. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 3582–3590, 2022.

Thomas Wiegand, Gary J Sullivan, Gisle Bjontegaard, and Ajay Luthra. Overview of the h. 264/avc video coding standard. *IEEE Transactions on circuits and systems for video technology*, 13(7):560–576, 2003.

Olivia Wiles, Joao Carreira, Iain Barr, Andrew Zisserman, and Mateusz Malinowski. Compressed vision for efficient video understanding. In *ACCV*, 2023.

Shen Yan, Tao Zhu, ZiRui Wang, Yuan Cao, Mi Zhang, Soham Ghosh, Yonghui Wu, and Jiahui Yu. Video-coca: Video-text modeling with zero-shot transfer from contrastive captioners. In *ArXiV:2212.04979*, 2022.

Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. Activitynet-QA: A dataset for understanding complex web videos via question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019.

Joe Yue-Hei Ng, Matthew Hausknecht, Sudheendra Vijayanarasimhan, Oriol Vinyals, Rajat Monga, and George Toderici. Beyond short snippets: Deep networks for video classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4694–4702, 2015.

Rowan Zellers, Jiasen Lu, Ximing Lu, Youngjae Yu, Yanpeng Zhao, Mohammadreza Salehi, Aditya Kusupati, Jack Hessel, Ali Farhadi, and Yejin Choi. Merlot reserve: Neural script knowledge through vision and language and sound. In *CVPR*, 2022.

Junjie Zhou, Yan Shu, Bo Zhao, Boya Wu, Shitao Xiao, Xi Yang, Yongping Xiong, Bo Zhang, Tiejun Huang, and Zheng Liu. Mlvu: A comprehensive benchmark for multi-task long video understanding. *arXiv preprint arXiv:2406.04264*, 2024.

7 Appendix

7.1 Pooling Methods

Given the input embedding sequence, $L \times D$, we input this to the SSM. Specifically, this model is the Mamba SSM architecture. We do not make any changes to the layers or operations themselves. To create the multilevel SSM, we instead add pooling or merging layers within the SSM. We explore several approaches to this: (1) using attention-based pooling layers, (2) average pooling, and (3) concatenation pooling.

Attention Pooling. Here, we pass a sub-sequence of length L_s into the attention layer and output 1 token, thus pooling L_s tokens. For example, given a sequence length of S, and $L_s = 4$, we reduce the sequence by 4 by creating a $\frac{S}{L_s} \times L_s \times D$ tensor, then applying attention pooling e.g., (Touvron et al., 2021). Specifically, we use a query vector with 1 latent embedding, when when applied to the input key/value tensor which has size $L_s \times D$, results in a $1 \times D$ output. When applied along the whole sequence, this results in a $\frac{S}{L_s} \times D$ tensor. This can then be passed to the next SSM block.

Average pooling. This is similar to the above approach, expect we apply average pooling over the L_s dimension, resulting in the same $\frac{S}{L_s} \times D$ tensor, but without the attention operation, only averaging.

Concatenation pooling. Here, we create a tensor of shape $\frac{S}{L_s} \times D \cdot L_s$, by re-arranging the tensor to group multiple tokens into 1 by combining along the embedding axis. I.e., we reshape from $S \times D$ to $\frac{S}{L_s} \times D \cdot L_s$.

Finally, after any of the pooling layers, we apply a fully-connected layer to project the resulting tensor to the final dimension D_{out}, which can either be the same as D or larger. We found $L_s = 4$ and $D_{out} = 2 \cdot D$ worked well in our experiments. This reduces the memory used by the sequence by a factor of 2 each time a pooling layer is applied.

7.2 Implementation Details

Table 13: Model configs used in the paper.

Model	Layers	D	L_s	N	M	Params	TFLOPs
Bytes-Tiny	12	256	4	4	3	103M	0.47
Bytes-B	33	256	4	4	8	500M	1.88
Bytes-L	45	256	4	4	11	1B	4.12

We encode the videos as H.264 and in mp4 containers with a image size of 384 and a bitrate of 200kbps. This roughly matches resolution standard video models use. The model architectures used, Bytes-Tiny, Bytes-Base (Bytes-B), Bytes-Large (Bytes-L), are described in Table 13. Unless otherwise noted, we use only the video stream and do not include audio in the encoded video. We find the model is sensitive to learning rates, both different tasks (e.g., pre-training vs. classification finetuning) and model scales need different learning rates. We use $9e^{-5}$ as the pre-training learning rate for the Bytes-Tiny model, $7e^{-5}$ for the Bytes-Base model and $5e^{-5}$ for Bytes-Large. For fine-tuning, we use $5e^{-5}$, $3e^{-5}$, and $1e^{-5}$ for the tiny, base and large models, respectively. We pre-train with a batch size of 64, a sequence length of $2^1 8$ (262144) and for 2,000,000 steps. We fine-tune with the same settings, but for 1,000,000 steps. We note that with sufficient data augmentation, we do not observe overfitting behaviors even with 200 epochs of training on Kinetics-600. We use the Adam optimizer (Kingma, 2014), which is also important, with default settings. We use 512 TPU v5p to train the model. The Tiny model runs at approximately 20 steps per second, Base runs about 9 steps/sec and large about 4 steps/sec. Thus to train the model it takes about 27 hours, 61, and 127 hours to pre-train the models respectively. And about 14, 30, 63 hours for fine-tuning.

In Table 13 we give the details for each model configuration used in the paper.

Long Video Training To reduce compute costs, we train the model in stages. First, we do the pre-training as above on short video segments. This provides us with a good base model that understands video bytes. Next, we do two stage of long video training, using the method described in Section 3.1. We train on the

Table 14: Experiment showing performance of different video codecs and containers, using Bytes-Tiny. We see there is a small difference between the settings, but in general, they all perform very similarly.

Codec	Container	K600
h.264	mp4	25.4
h.265	mp4	25.1
h.264	mov	25.8
h.265	mov	24.7
VP9	mp4	24.3
VP9	WebM	24.9

Table 15: Multilevel SSM applied to the whole sequence vs. Chunked sequence (as in (Bhirangi et al., 2024). We note that there is no noticeable difference in FLOPs or compute time between these two approaches.

Model	K600
Ours	25.4
Chunked (Bhirangi et al., 2024)	25.1

VideoMarathon (Lin et al., 2025) data in two stages, first with sequence lengths of 2 million then 15 million bytes, roughly 1.3 minutes and 10 minutes long. We emphasize here that we are training on the full video, without any subsampling, unlike prior works.

7.3 Additional Experiments

In Table 14, we compare the model using different codecs and containers. While these results show the performance is pretty similar across codecs, it is possible some are easier for the model to learn than others.

In Table 15, we compare our proposed multilevel SSM to the chunked based one in (Bhirangi et al., 2024), the main difference being we apply the SSM to the entire sequence, while the other chunks the sequence and then applies the SSM independently to each chunk. Due to our efficient implementation of sequence parallelism, there is no meaningful difference in compute costs or runtime between the approaches, and for video byte inputs, applying the SSM to the whole sequence is better.

8 ActivityNet-QA and Cinepile Long Video Experiments

For the experiments in table 6, we needed to add a language model to handle the question answering task. To do this, we used the Gemma model Team et al. (2025a). Specifically, we then took the final representations from the SSM model as the video representation, and added that to the enmbedded text representations and then trained gemma to generate the answers.

For CinePile, since it is a multiple choice dataset, we evalute using standard accuracy, if the predicted answer (e.g., a, b, c, or d) matches the ground truth. For ActivityNet, since it is open-ended questions, we use string equality to compare the answers.

CinePile videos average 3 minutes of duration, with some as long as 8 minutes. It has both a training and evaluation set, so we finetune the 15M token model on this data for 1 epoch. We train the entire model with a learning rate of 0.00001 on this question answering task.

ActivityNet-QA has videos with the average duration between 5 and 10 minutes. It also has a training and evaluation set, and we finetune for 1 epoch as well with a learning rate of 0.00001.

9 Discussions on Additional Pre-training

There are many other pre-training tasks could be explored, such as codec translation, e.g., mp4 (H.264) as input and generate a VP9 encoded video as output, using a standard per-token cross-entropy loss, or predicting features from a known visual encoder (e.g., CLIP (Radford et al., 2021) features) rather than directly predicting pixels. Similarly contrastive losses across different codecs could be used. Weakly supervised tasks such as predicted ASR transcripts from video byte inputs could be explored. We leave these explorations as future work.