Noisy Symbolic Abstractions for Deep RL:
A case study with Reward Machines

Abstract

Natural and formal languages provide an effective mechanism for humans to
specify instructions and reward functions. We investigate how to generate policies
via RL when reward functions are specified in a symbolic language captured by
Reward Machines, an increasingly popular automaton-inspired structure. We are
interested in the case where the mapping of environment state to the symbolic
Reward Machine vocabulary is noisy. We formulate the problem of policy learning
in Reward Machines with noisy symbolic abstractions as a special class of POMDP
optimization problem, and investigate several methods to address the problem
building on existing and new techniques, the latter focused on predicting Reward
Machine state, rather than on grounding of individual symbols. We analyze these
methods and evaluate them experimentally under varying degrees of uncertainty in
the correct interpretation of the symbolic vocabulary. We verify the strength of our
approach and the limitation of existing methods via an empirical investigation on
both illustrative, toy domains and partially observable, deep RL domains.

1 Introduction

Language is playing an increasingly important role in Reinforcement Learning (RL). It serves as a
mechanism for expressing human-interpretable reward functions as well as for conveying language-
based advice and instructions (e.g., [Luketina et al., 2019, Huang et al., 2022]). An oft-cited challenge
that faces the integration of language and machine learning is the *symbol grounding problem* – the
problem of associating the symbols or words in a language (e.g. "cat" or "chair") or properties
expressed in a language (e.g, "the robot is holding the cup") with states of the world – especially
if those states are generated via a different modality such as vision, haptics or audio. Indeed the
association of the symbols and sentences of language with observed state is contextual, complicated
and noisy, and it is this observation that broadly motivates the work in this paper.

Our general concern is with learning a policy using RL when language is used to specify reward-
worthy behaviour or task instructions over a vocabulary – a set of symbols – that captures a purposeful
abstraction of the observed environment state. We are specifically concerned with the case where
the interpretation of this vocabulary is noisy or uncertain, and how to perform RL effectively in
this context. This causes the RL agent to be uncertain about whether it is making progress on
garnering rewards and/or following instructions that have been conveyed via language. For example,
consider that an autonomous vehicle gets negative reward for driving through a red light, but where the
determination of whether "red light" is true in the current state can be compromised by a slush-covered
camera lens, specularities from the sun, or occlusion from a truck in front of the vehicle.

For the purposes of this paper, we examine this problem in the context of Reward Machines (RMs),
automata-like structures that provide a normal-form representation for (non-Markovian) reward
functions, human preferences, and instructions [Toro Icarte et al., 2018, 2022]. The virtue of RMs is

that they allow for reward specification in a diversity of formal languages that have corresponding automata representations [Camacho et al., 2019], following Chomsky's hierarchy (e.g., Hopcroft et al. [2007]). Further, RMs are typically paired with learning algorithms that exploit the reward function structure exposed in the automata to significantly improve sample efficiency. RMs have historically realized symbol grounding via so-called *labelling functions* that map environment transitions system state (or state-action-state triples) into a vocabulary of properties (e.g., "at-location-A", "light-is-red") that are *propositional* – either true or false in the state. RMs have proven effective when such functions faithfully reflect the intended interpretation of the propositional symbols, but when environments are partially observable or when labelling functions reflect uncertainty or sensors are noisy (as many real-world detectors are) they may not be adequate to determine the truth or falsity of a particular state property with certainty.

The use of formal languages in (deep) RL, including Linear Temporal Logic and Reward Machines, is a topic of broad interest because of the benefits accrued by exploiting the compositional syntax and semantics of formal languages, their connections with formal system verification, and correct-by-construction synthesis from formal specification [e.g., Aksaray et al., 2016, Li et al., 2017, 2018, Littman et al., 2017, Toro Icarte et al., 2018, Toro Icarte et al., 2019, Hasanbeig et al., 2018, Yuan et al., 2019, Jothimurugan et al., 2019, Xu and Topcu, 2019, Kuo et al., 2020, Hasanbeig et al., 2020, Xu et al., 2020a,b, Furelos-Blanco et al., 2020, Rens and Raskin, 2020, de Giacomo et al., 2020, Jiang et al., 2021, Neary et al., 2021, Shah et al., 2020, Velasquez et al., 2021, DeFazio and Zhang, 2021, Zheng et al., 2021, Camacho et al., 2021, Corazza et al., 2022, Liu et al., 2022].

The contributions of this paper are as follows:

- We study the problem of learning policies when (non-Markovian) reward functions are expressed in a symbolic language captured by a Reward Machine, but where the interpretation of the vocabulary of that language – the symbols – is noisy. We present a novel formulation of this problem as optimizing a POMDP, where the POMDP state comprises both the concrete observable environment state and the hidden Reward Machine state.

- We investigate a suite of deep RL methods for our proposed problem formulation and highlight their limitations under various conditions.

- We propose a novel deep RL algorithm, *Reward Machine State Modelling*, that makes robust decisions by being aware of the uncertainty in its interpretation of the vocabulary.

- We verify the strength of our approach and limitations of existing methods via an empirical investigation using illustrative, toy examples and partially observable, deep RL image domains.

2 Preliminaries

The goal of reinforcement learning is to learn an optimal policy π by interacting with an environment [Sutton and Barto, 1998]. Typically, the environment is modelled as a *Markov Decision Process* (MDP) [Bellman, 1957], a tuple $\langle S, T, A, P, R, \gamma, \mu \rangle$. S is the set of *states*, $T \subseteq S$ is the set of *terminal states*, A is the set of *actions*, $P(s'|s, a)$ is the *transition probability distribution*, $R : S \times A \times S \to \mathbb{R}$ is the *reward function*, γ is the *discount factor*, and μ is the *initial state distribution*.

Reward machines are an automata-based representation of (non-Markovian) reward functions [Toro Icarte et al., 2018, 2022] that provide a normal-form representation for reward specification in a diversity of formal languages [Camacho et al., 2019]. Given a *vocabulary* – a finite set of atomic propositions $\mathcal{AP}$ representing abstract (possibly human interpretable) properties or events in the environment, RMs specify temporally extended rewards over these propositions while exposing the compositional reward structure to the learning agent. Formally, Reward Machines, which we take to mean here *simple Reward Machines* from Toro Icarte et al. [2022], are defined as follows:

Definition 2.1 (Reward Machine, RM). A simple *Reward Machine* is a tuple $\langle U, u_0, F, \mathcal{AP}, \delta_t, \delta_r \rangle$, where U is a finite set of states, $u_0 \in U$ is the initial state, F is a finite set of terminal states (disjoint from U), $\mathcal{AP}$ is a finite set of atomic propositions, $\delta_u : U \times 2^{\mathcal{AP}} \to (U \cup F)$ is the state-transition function, and $\delta_r : U \times 2^{\mathcal{AP}} \to \mathbb{R}$ is the state-reward function.

Running Example: The *Mining* domain depicted in Figure 1 (adapted from [Corazza et al., 2022]) illustrates the use of RMs. The agent's state is its current square on the grid, and its task is to obtain

Figure 1: The *Mining* Domain. **Left:** A robot is tasked with digging up a stash of gold (found in any one of the four right-most squares) and then delivering it to the depot at the bottom left. Visiting the depot ends the episode. **Right:** A Reward Machine describing this task. The atomic propositions are $\mathcal{AP} = \{$ 🪙 , 🏠 $\}$, where 🪙 holds when the robot performs a "dig" action in a gold square and 🏠 holds when the robot is at the depot. A directed edge between RM states u and v labelled ϕ/r means that when ϕ (a propositional formula over $\mathcal{AP}$) is satisfied while the agent is in RM state u, the agent gets reward r and transitions to v.

88 at least one ore of gold (found at a gold square), then deliver it to the depot. Visiting the depot ends
89 the episode. Figure 1 (right) shows a possible RM for this task over propositions $\mathcal{AP} = \{$🪙, 🏠$\}$.

90 RMs can be used in place of a standard reward function in an MDP or POMDP $\mathcal{M}$ with the help of a
91 *labelling function* $\mathcal{L} : S \times A \times S \rightarrow 2^{\mathcal{AP}}$. The labelling function grounds abstract propositions from
92 $\mathcal{AP}$ in the environment $\mathcal{M}$ by mapping any transition (s_t, a_t, s_{t+1}) into the subset of propositions
93 that hold for that transition. In the *Mining* example, a labelling function $\mathcal{L}$ evaluates 🪙 to true when
94 the agent is at a gold square and performs a "dig" action and evaluates 🏠 to true when the agent is at
95 the bottom-left square.

96 At each (non-final) timestep t, if the environment transition is (s_t, a_t, s_{t+1}) and the RM state is
97 $u_t \in U$ (initially set to u_0), then the RM state is updated to $u_{t+1} = \delta_u(u_t, \mathcal{L}(s_t, a_t, s_{t+1}))$ and the
98 agent receives reward $r_t = \delta_r(u_t, \mathcal{L}(s_t, a_t, s_{t+1}))$. This process of using an RM with an MDP is
99 equivalent to using a larger MDP – which we will call the *Reward Machine MDP* – that has a standard
100 (Markovian) reward function but with state space $S \times U$ [see Toro Icarte et al., 2022, Observation 1].

101 **Definition 2.2** (Reward Machine MDP, RM-MDP). Given an MDP without a reward function
102 $\langle S, T, A, P, \gamma, \mu \rangle$, an RM $\langle U, u_0, F, \mathcal{AP}, \delta_t, \delta_r \rangle$, and a labelling function $\mathcal{L} : S \times A \times S \rightarrow 2^{\mathcal{AP}}$, the
103 corresponding *Reward Machine MDP* is an MDP $\langle S', T', A, P', R', \gamma, \mu' \rangle$ where $S' = S \times U$
104 is the state space, $T' = (T \times U) \cup (S \times F)$ are terminal states, A is the action space,
105 $P'((s_{t+1}, u_{t+1})|(s_t, u_t), a_t) = P(s_{t+1}|s_t, a_t) \cdot \mathbb{1}[\delta_u(u_t, \mathcal{L}(s_t, a_t, s_{t+1})) = u_{t+1}]$ are the transi-
106 tion probabilities, $R'((s_t, u_t), a_t, (s_{t+1}, u_{t+1})) = \delta_r(u_t, \mathcal{L}(s_t, a_t, s_{t+1}))$ is the reward function, γ is
107 the discount factor, and $\mu'(s, u) = \mu(s)\mathbb{1}[u = u_0]$ is the initial state distribution.

108 RMs are commonly integrated into deep RL algorithms by using the labelling function $\mathcal{L}$ to compute
109 the RM state u_t, which is provided as input to the policy along with s_t. In *Mining*, the RM state u_t
110 acts as salient memory, capturing whether the agent has previously obtained gold.

111 3   Decision-making under Uncertain Propositions

112 The majority of existing RL methods that employ structured reward function specifications, such as
113 RMs, assume *perfect* labelling functions in their decision-making. By exploiting the ground-truth
114 propositional values, the true state of the RM is always available to the policy. Unfortunately, faithful
115 evaluation of these abstracted propositions is unrealistic in many real-world settings; factors such
116 as sensor noise, modelling errors, partial observability or insufficient data may all lead to incorrect
117 evaluation of these propositions. Critically, the agent's estimate of the RM state may rapidly diverge
118 from reality as a result of such errors, potentially provoking unintended behaviours.

119 **Example continued:** Consider again the *Mining* example in Figure 1 when the agent is unable to
120 consistently determine if an ore is gold or another less valuable mineral in the absence of a perfect
121 labelling function. Now, the agent cannot be certain that it has obtained gold, and a false positive
122 belief may cause the agent to head to the depot, failing the task. A robust policy should be cognizant of
123 this uncertainty, perhaps digging at many squares before visiting the depot to maximize its probability
124 of successfully completing the task. Unfortunately, efficient realization of this behaviour is inherently
125 non-Markovian, as it requires the agent to remember which squares were previously mined.

126 Our goal is to investigate how agents can learn these robust behaviours when a perfect labelling
127 function is unavailable. We formulate this problem in RM-MDP as solving a special type of POMDP.

3.1 Problem Formulation

129 Given an MDP without a reward function $\langle S, T, A, P, \gamma, \mu \rangle$ and an RM $\langle U, u_0, F, \mathcal{AP}, \delta_t, \delta_r \rangle$, and
130 assuming the existence of a (hidden) labelling function $\mathcal{L} : S \times A \times S \to 2^{\mathcal{AP}}$, our objective is
131 to learn a policy that maximizes the expected discounted return according to the corresponding
132 RM-MDP (Definition 2.2) without having access to $\mathcal{L}$.

133 We formulate this goal as optimizing a POMDP with state space $S \times U$, and transitions matching
134 those in the RM-MDP. However, while an RM-MDP treats RM states $u_t \in U$ as an observable
135 component of the state, only $s_t \in S$ is observable but not u_t, because u_t depends on the ground truth
136 labelling function. We call such a POMDP an *Uncertain-Proposition Reward Machine MDP*.

137 **Definition 3.1** (Uncertain-Proposition Reward Machine MDP, URM-MDP). Given an MDP without
138 a reward function $\langle S, T, A, P, \gamma, \mu \rangle$, an RM $\langle U, u_0, F, \mathcal{AP}, \delta_t, \delta_r \rangle$, and a labelling function $\mathcal{L} :$
139 $S \times A \times S \to 2^{\mathcal{AP}}$, the corresponding *URM-MDP* is a POMDP $\langle S', \Omega, T', A, P', O, R', \gamma, \mu' \rangle$,
140 where S', T', A, P', γ and μ' are as in the corresponding RM-MDP (Definition 2.2), $\Omega = S$ is the
141 observation space, and $O(s|(s_t, u_t), a_t) = \mathbb{1}[s = s_t]$ are the observation probabilities.

142 We similarly define an *Uncertain-Proposition Reward Machine POMDP* (URM-POMDP with
143 Definition A.1 in the Appendix), where the underlying environment is only partially observable, but
144 the labelling function $\mathcal{L}$ remains a function of $S \times A \times S$.

4 Analysis of Prior Approaches

146 A number of prior approaches have considered uncertainty in the values of propositions, though
147 mainly for tabular MDPs. Unfortunately, their effectiveness remains unclear when applied to complex
148 deep RL settings where the number of states is infinite, high-level events are challenging to perfectly
149 model, or where the environment is only partially observable. We analyze and discuss these drawbacks
150 in Subsections 4.1, 4.2 before proposing a new approach for this problem setting with theoretical
151 advantages in Section 5. This analysis is further supported by empirical results in Section 6.

152 We discuss three prior approaches that consider uncertainty in the values of propositions. The
153 first two methods model the true labelling function $\mathcal{L}$ with an approximate labelling function,
154 $\hat{\mathcal{L}} : S \times A \times S \times \mathcal{AP} \to [0, 1]$ in URM-MDPs, and $\hat{\mathcal{L}} : H \times A \times \Omega \times \mathcal{AP} \to [0, 1]$ in URM-
155 POMDPs, that assigns probabilities to each proposition. Such an approximate labelling function
156 might be obtained from external sensors, handcrafted heuristics, offline data, or be trained online
157 together with the policy. Then, the predicted propositions are used to generate an estimate (or a belief)
158 of the current RM state using one of the following methods. One appeal of this technique is that the
159 approximate labelling functions can in principle be transferred to new environments and RMs, so
160 long as the high-level propositions remain the same.

161 **Thresholding.** [e.g., Ghasemi et al., 2020] This method discretizes every proposition p_i at each
162 timestep t to its most likely value under $\hat{\mathcal{L}}$. In URM-MDPs, $\hat{p}_{i,t} = \mathbb{1}[\hat{\mathcal{L}}(s_t, a_t, s_{t+1}, p_i) \geq 0.5]$ and
163 the $\hat{p}_{i,t}$ values are then used to produce a discrete prediction of an RM state $\hat{u}_t$. The learned policy
164 takes the form $\pi(a_t|s_t, \hat{u}_t)$. In URM-POMDPs, we simply change the approximate labelling function
165 to the correct form $\hat{\mathcal{L}} : H \times A \times \Omega \times \mathcal{AP} \to [0, 1]$ and change the policy to condition on histories h_t
166 rather than states s_t.

167 **Independent Belief Updating.** [e.g., Ding et al., 2011, Verginis et al., 2022] This approach main-
168 tains a probabilistic belief $\tilde{u}_t$ over the current RM state under the simplifying assumption that
169 predictions of propositions $p_{i,t}$ are independent of one another and across all timesteps. In URM-
170 MDPs, $\tilde{u}_t$ is updated each timestep for all $u \in U$, given an experience (s_t, a_t, s_{t+1}), via

$$\tilde{u}_{t+1}(u) = \sum_{\sigma_t \in 2^{\mathcal{AP}}, u_t \in U} \Pr(\sigma_t|s_t, a_t, s_{t+1}) \tilde{u}_t(u_t) \mathbb{1}[\delta_u(u_t, \sigma_t) = u]$$

171 where $\Pr(\sigma_t|s_t, a_t, s_{t+1})$ is the probability of a particular propositional assignment σ_t under $\hat{\mathcal{L}}$. The
172 learned policy then takes the form $\pi(a_t|s_t, \tilde{u}_t)$. In URM-POMDPs, we change $\hat{\mathcal{L}}$ to the correct form
173 and change the policy to condition on histories h_t rather than states s_t.

174 **Recurrent Policy.** [e.g., Kuo et al., 2020] We also consider a third approach that directly solves
175 the URM-MDP or URM-POMDP as a general partially observable RL task, by learning a recurrent
176 policy of the form $\pi(a_t|s_0, a_0, ..., s_{t-1}, a_{t-1}, s_t)$ in URM-MDPs and $\pi(a_t|o_0, a_0, ..., o_{t-1}, a_{t-1}, o_t)$
177 in URM-POMDPs. Notice that the policy does not condition on the RM state (or an estimate of
178 it); the non-Markovian task structure is instead handled by conditioning on the entire history. Thus,
179 propositional values (either ground-truth, or estimated) are not required for this approach.

4.1 Pitfalls in URM-MDPs

181 In URM-MDPs, an approximate labelling function $\hat{\mathcal{L}} : S \times A \times S \times \mathcal{AP} \to [0, 1]$ can in princi-
182 ple perfectly model the ground-truth labelling function $\mathcal{L}$. In this ideal case, both `Thresholding`
183 and `Independent Belief Updating` correctly estimate the true RM state, inheriting any optimality
184 guarantees of the RL algorithm used to train the policy [Toro Icarte et al., 2022].

185 Unfortunately, perfectly modelling the labelling
186 function can be impractical in complex, real-
187 world settings. `Thresholding` is resistant to
188 small errors in $\hat{\mathcal{L}}$, but only estimates a single,
189 discrete RM state and cannot represent the un-
190 certainty in its prediction. `Independent Belief`
191 `Updating` aims to address this by estimating a
192 belief over RM states, but the independence as-
193 sumption fails to hold for noisy predictions un-
194 der $\hat{\mathcal{L}}$. For example, consider the *Mining* do-
195 main. Repeatedly digging in a square that the
196 agent erroneously believes may contain gold
197 will increase the perceived probability of hav-
198 ing gold each time under `Independent Belief`
199 `Updating`. In reality, digging more than once in
200 any particular square is pointless since either all
201 digs will produce gold, or none will.

202 `Recurrent Policy` treats URM-MDPs as gen-
203 eral POMDPs and avoids approximating the la-
204 belling function altogether. While it retains any
205 convergence guarantees afforded by partially ob-
206 servable RL algorithms, history-based policies
207 are notoriously hard and sample-inefficient to
208 train in practice.

4.2 Pitfalls in URM-POMDPs

210 Unfortunately, significant issues arise with
211 `Thresholding` and `Independent Belief`
212 `Updating` when the underlying environment
213 is partially observable. First, even the
214 Bayes-optimal approximate labelling function
215 $\hat{\mathcal{L}}^*(h_t, a_t, o_t, p_i)$ is not necessarily identical to
216 the ground-truth labelling function $\mathcal{L}$, since the

Figure 2: Two *partially observable* RM environments that challenge existing methods. Shaded squares are unobservable to the agent. **Top:** The *Traffic Light* domain. The agent must drive through an intersection to collect a package, and then drive through again to return home. However, the agent can only see forwards and must avoid crossing a red light. **Bottom:** The *Kitchen* domain. It's the end of the day and a household robot must go to the kitchen to clean up by ensuring dishes are washed, the table is cleared, and the garbage is empty. Some chores might not require the robot's attention, e.g. the residents may have not used any dishes. This occurs with a 1/3 chance for each chore, and that chore is considered done from the start. However, the agent cannot observe what chores remain to be done until entering the kitchen.

217 propositions depend on unobservable states s_t. Second, the current RM state u_t generally cannot be
218 determined with certainty given the history h_t due to the previous remark.

219 Thus, `Thresholding` may predict an incorrect RM state, even with this ideal approximate labelling
220 function $\hat{\mathcal{L}}^*$. The *Traffic Light* example in Figure 2 highlights how a policy might abuse this, leading
221 to unsafe behaviour. The agent must safely drive through an intersection with a traffic light, but
222 cannot observe the light colour when traversing the intersection *in reverse*. If the light tends to be
223 green more often than red, `Thresholding` would predict that the agent did *not* pass a red light. Hence,
224 the agent would be incentivized to drive backwards through the intersection while ignoring the light
225 colour, rather than waiting for a green light.

Algorithm 1: Reward Machine State Modelling (for URM-MDPs; 1 iteration)

---
1 Inputs: URM-MDP $\mathcal{K}$, policy π_θ, RM belief RNN g_ϕ;
   `/* Collect on-policy data`   `*/`
2 $\mathcal{D} = \{\}$;
3 for t *from* 1 *to* T **do**
4   Compute RM state belief $\tilde{u}_t = g_\phi(\cdot|s_0, a_0, \ldots, s_{t-1}, a_{t-1}, s_t)$;
5   Execute action $a_t \sim \pi(\cdot|s_t, \tilde{u}_t)$ and observe r_t, s_{t+1}, u_{t+1} ;
6   Add $(s_t, a_t, r_t, s_{t+1}, u_t, \tilde{u}_t)$ to buffer $\mathcal{D}$;
7 end
   `/* Train RM belief RNN`   `*/`
8 Update ϕ with SGD on $L_\phi = \mathbb{E}_{\tau \sim \pi_\theta, t \sim \mathcal{U}\{1,\ldots,|\tau|\}}[- \log g_\phi(u_t|s_0, a_0, \ldots, s_{t-1}, a_{t-1}, s_t)]$
   estimated from $\mathcal{D}$;
   `/* Train policy`   `*/`
9 Update θ with SGA on $J_\theta = \mathbb{E}_{\tau \sim \pi_\theta}[\sum_{t=0}^{\infty} \gamma^t r_t]$ estimated from $\mathcal{D}$;

`Independent Belief Updating` may similarly fail to model a correct belief over RM states, even with the ideal $\hat{\mathcal{L}}^*$. We demonstrate this in the *Kitchen* example in Figure 2, where a cleaning agent cannot initially observe which chores require its attention from outside the kitchen. The Bayes-optimal $\hat{\mathcal{L}}^*$ assigns $1/3$ probability that each chore is done on each timestep while outside the Kitchen. If the agent wanders outside the kitchen for t timesteps, `Independent Belief Updating` would predict that the dishes were washed at some point with probability $1 - (2/3)^t$. The correct probability is $1/3$, since the propositions are linked over time – if the dishes are washed now, they will remain washed on the next step as well. `Independent Belief Updating` ignores this dependence and eventually predicts that all chores are done with probability close to 1, despite the agent never entering the kitchen.

Unfortunately, modelling the correct temporal dependencies between propositions is challenging. In general, one may need to model the full joint distribution over all propositional values up to time t, i.e. $\{p_{i,t'} : 1 \leq i \leq |\mathcal{AP}|, 0 \leq t' \leq t\}$, given the history h_t. Even with this joint distribution, computing an exact belief over RM states is also difficult due to the exponential number of instantiations of all the propositions.

Finally, we note that `Recurrent Policy` does not significantly distinguish between URM-POMDPs and URM-MDPs; a history-based policy is learned in each case. Thus, our remarks from the URM-MDP setting carry over to URM-POMDPs as well.

5 Proposed Approach

We propose a new approach, *Reward Machine State Modelling* (**RMSM**) to address the shortcomings of prior approaches in URM-MDPs and URM-POMDPs. Our key observation is that the utility of modeling the labelling function is to accurately predict the RM state. Thus, we propose to directly learn the belief over RM states, given the history, using a recurrent neural network (RNN) g_ϕ trained via supervised learning. The policy π_θ then conditions on this predicted belief in place of the ground-truth RM state.

We describe **RMSM** in detail for URM-MDPs in Algorithm 1. In this setting, the network inputs are $g_\phi(u_t|s_0, a_0, \ldots, s_{t-1}, a_{t-1}, s_t)$ for the RM belief RNN and $\pi_\theta(a_t|s_t, \tilde{u}_t)$ for the policy, where $\tilde{u}_t = g_\phi(\cdot|s_0, a_0, \ldots, s_{t-1}, a_{t-1}, s_t)$ is the predicted belief over RM states. Note that $\tilde{u}_t$ can be compactly represented with a vector of $|U|$ probabilities. In URM-POMDPs, the policy π_θ instead conditions on $(h_t, \tilde{u}_t)$, and the RM belief g_ϕ conditions on the observation-action history. **RMSM** then concurrently optimizes two independent objectives: prediction of a belief over RM states by minimizing a negative-log-likelihood loss L_ϕ and maximization of the policy's expected return J_θ.

5.1 Theoretical Advantages

RMSM offers a number of intuitive benefits over prior approaches. First, when the objective $\mathcal{L}_\phi$ is minimized with respect to ϕ, g_ϕ returns the Bayes-optimal belief over RM states given the history $\Pr(u_t|s_0, a_0, \ldots, s_{t-1}, a_{t-1}, s_t)$ for histories with positive probability under π_θ. In contrast, recall

Figure 3: The *Mining* toy experiment. We consider two types of errors in predicting whether a square contains gold: *uniform* (left), and *false positive* (right). The parameter ϵ linearly controls the degree of error, with $\epsilon = 0$ representing a ground-truth labelling function. Numbers in the grids represent the agent's probabilistic belief that a square yields gold for $\epsilon = 1$. The graphs report mean final performances of various baselines along with standard error over 8 runs. `Thresholding` is robust to small errors but fails when any square is misclassified, while `Independent Belief Updating` performs poorly as it ignores the dependence between propositions.

that `Thresholding` and `Independent Belief Updating` may fail to predict the correct RM state belief in URM-POMDPs, even with the Bayes-optimal approximate labelling function $\hat{\mathcal{L}}^*$. Theorem A.1 in the Appendix further adds that under some assumptions, when both `RMSM` objectives are simultaneously optimized, the resultant policy is optimal in the URM-MDP or URM-POMDP.

`Recurrent Policy`, like `RMSM`, also optimizes an objective aligned with solving the URM-MDP or URM-POMDP. However, `RMSM` exploits the task structure to reduce the complexity of the RL problem, while `Recurrent Policy` treats the problem as a general POMDP. This is evident in the URM-MDP case, where `Recurrent Policy` trains a policy conditioned on the entire state-action history, while the `RMSM` policy only conditions on the current state s_t and a compact RM state belief representation. In URM-POMDPs, both `RMSM` and `Recurrent Policy` must train policies conditioned on entire histories, but nonetheless, exposing the predicted RM belief to the policy may facilitate learning.

6 Experiments

We conduct experiments to investigate the consequences of deploying RL policies in settings where a perfect labelling function is not available. We focus on three questions: **Q1:** Are prior methods that rely on approximations of the labelling function $\hat{\mathcal{L}}$ robust to errors in $\hat{\mathcal{L}}$? **Q2:** How does `RMSM` (ours) perform compared to prior approaches in complex domains without a perfect labelling function? **Q3:** How well do `RMSM` (ours), `Thresholding`, and `Independent Belief Updating` model the true RM state in complex domains?

6.1 Toy Gridworld Problem

We investigate **Q1** on a toy grid domain with handcrafted models of $\hat{\mathcal{L}}$ and controllable levels of error.

Task: Returning to the *Mining* example in Figure 1. The agent must dig at a square containing gold and then deliver it to the depot to obtain a reward of 1, but visiting the depot without gold ends the episode without reward. The agent does not observe when gold was obtained, but instead relies on a probabilistic belief $\hat{\mathcal{L}}(s, a_{\text{dig}}, \cdot, \text{🪙})$ that a state s yields gold. We also introduce a cost of -0.05 for every movement action so that agents must carefully choose where to dig, instead of simply digging at every square.

Figure 4: Performance of RMSM (ours) vs various baselines on two partially observable, image-based domains (averaged over 8 runs, with shaded areas showing standard error). RMSM converges similarly to when learning with the ground-truth RM state, while prior approaches fail on at least one domain.

Approximate labelling function model: We consider two noisy models $\hat{\mathcal{L}}(s, a_{\mathrm{dig}}, \cdot, \text{🟡})$ of whether each square contains gold shown in Figure 3. The first gold model has a relatively uniform level of error for each square, while the second has a false positive belief that a single non-gold square may actually contain gold. For each, we control the degree of error through a parameter $\epsilon \in [0, \infty)$. $\epsilon = 0$ corresponds to the ground-truth probabilities of gold (1 if the square contains gold and 0 if not), $\epsilon = 1$ corresponds to the noisy probabilities reported in Figure 3, and the probabilities are linearly interpolated for other values of ϵ. $\hat{\mathcal{L}}$ is assumed to model 🏠 without error.

Baselines: We consider Thresholding and Independent Belief Updating with each of the noisy gold models at various levels of error ϵ. For comparison, we report the performance when using the ground-truth RM state (Perfect RM), and a belief updating approach supplied with the correct dependencies of the propositions over time (Belief Updating+).

Precisely, Belief Updating+ exploits the fact that the 🟡 proposition must maintain the same value each time you dig in state s. In other words, digging multiple times in the same state should not increase the agent's belief of having obtained gold. It is important to note that Belief Updating+ cannot easily be applied beyond tabular domains.

Each method uses tabular Q-learning [Sutton and Barto, 2018] to obtain a policy, with a linear approximation [Melo and Ribeiro, 2007] for methods conditioning on a belief over RM states. Hyperparameters can be found in the Appendix.

Results: Results are reported in Figure 3. As expected, all methods performed near-optimally under a perfect labelling function ($\epsilon = 0$), but both Thresholding and Independent Belief Updating showed sensitivity to errors in at least one case. Thresholding performed well when errors were small in all states, but failed anytime an error exceeded the threshold, resulting in a misclassification of the proposition. Independent Belief Updating showed poor performance overall. We observed that this approach usually exploited errors in $\hat{\mathcal{L}}$ by repeatedly digging in the same square. However, Belief Updating+ was significantly more robust to errors in $\hat{\mathcal{L}}$, showing the importance of considering the dependence between propositions over time.

6.2 MiniGrid Problems

We investigate **Q2** and **Q3** on two partially observable, image-based MiniGrid environments encoding the *Traffic Light* and *Kitchen* problems from Section 4.2. Experimental details, including the RM specifications, network architectures, and hyperparameters can be found in the Appendix.

Baselines: We consider RMSM, Thresholding, Independent Belief Updating, Recurrent Policy, and an RL policy conditioned on the true RM state (Perfect RM). Policies are deep neural networks trained using PPO. The RM belief predictor g_ϕ (in RMSM) and the approximate labelling function $\hat{\mathcal{L}}$ (in Thresholding and Independent Belief Updating) are learned concurrently with the policy.

Results: We report learning curves in Figure 4. In both domains, RMSM rapidly learned a strong policy on-par with the policy that exploits ground-truth RM states. While Thresholding and Independent Belief Updating each made progress in one domain, they completely failed to learn in *Traffic Light* and *Kitchen*, respectively, matching our expectations from Section 4.2. Recurrent Policy, which

does not exploit the structure of the problem, performed poorly despite enjoying similar theoretical guarantees to RMSM.

To answer **Q3**, we compared beliefs over RM states predicted by RMSM, Thresholding, and Independent Belief Updating against a handcrafted approximation of the ground-truth belief (described in the Appendix). The final networks from training (g_ϕ for RMSM and $\hat{\mathcal{L}}$ for Thresholding, Independent Belief Updating) were used, and for an equal comparison, we conditioned each method on trajectories sampled under a random policy. Results in Figure 6 (in the Appendix) show that RM state beliefs produced by RMSM are much closer to ground-truth than those produced by Thresholding or Independent Belief Updating.

7 Related Work

Many recent works have considered specifying tasks for deep RL using RMs or a formal language, such as LTL. The vast majority of these assume access to a perfect labelling function (e.g. Vaezipoor et al. [2021], Jothimurugan et al. [2021], León et al. [2021], Liu et al. [2022], Leon et al. [2020]). A few notable works in this vein learn policies that do not rely on a labelling function. Kuo et al. [2020] handle LTL tasks using a recurrent policy (inspiring the Recurrent Policy baseline), while Andreas et al. [2017], Oh et al. [2017] and Jiang et al. [2019] learn modular subpolicies that are reusable between tasks.

Prior works have considered uncertainty in the labelling function, though most of this research comes from the motion planning literature, rather than the deep RL literature. However, these works typically assume that the state space is partitioned into discrete regions, resulting in a tabular MDP. Ding et al. [2011] assumes that propositions in each state occur probabilistically in an i.i.d. manner and propose an approach exploiting this independence. Ghasemi et al. [2020], Verginis et al. [2022] consider a setting where propositions are initially unknown but can be inferred through environment interactions. Cai et al. [2021] considers learning policies that maximize the probability of satisfying an LTL task with uncertainties in the labelling function and environment dynamics. Sadigh and Kapoor [2016], Jones et al. [2013] proposes temporal logics over stochastic or partial observable properties.

More broadly, many prior works have considered the use of RMs or formal languages under uncertainty in the rewards, states, or ground-truth RM structure. Xu et al. [2020a,b], Gaon and Brafman [2020] assume a setting where rewards are known but the RM structure is not, and propose algorithms to learn the RM. Corazza et al. [2022] learns RMs with stochastic reward emissions while Velasquez et al. [2021] learns RMs with stochastic rewards and transitions. Toro Icarte et al. [2019] learns RMs in partially observable environments, but defines the labelling function over observations rather than states, and thus does not consider uncertainty over propositions. Shah et al. [2020] expresses the uncertainty over a desired behaviour as a distribution of LTL formulas.

8 Conclusion

In this paper, we studied the problem of learning Reward Machine policies under an interpretation of the vocabulary that is uncertain. We targeted our investigation towards complex, deep RL settings, where such uncertainty may naturally arise from sensor noise, modelling errors, or partial observability in the absence of a perfect labelling function. We first presented novel formulations of this problem as URM-MDPs and URM-POMDPs. Through illustrative examples and vision-based deep RL experiments, we then revealed a propensity for existing, naive approaches to exploit errors in their own model, leading to task failure and unsafe behaviour.

To address these shortcomings, we proposed an algorithm, *Reward Machine State Modelling*, that is cognizant of its uncertainty over atomic propositions and that exploits the structure of a URM-MDP or URM-POMDP to model the task-relevant RM states, rather than individual propositions. Empirical results demonstrated the robust performance of our approach without access to the ground-truth labelling function.

While we considered the problem of *symbol grounding* from the viewpoint of Reward Machines, our insights are further applicable to a diversity of language-inspired abstractions for RL. We leave these extensions to future work.

References

Derya Aksaray, Austin Jones, Zhaodan Kong, Mac Schwager, and Calin Belta. Q-learning for Robust Satisfaction of Signal Temporal Logic Specifications. In *Proceedings of the 55th IEEE Conference on on Decision and Control (CDC)*, pages 6565–6570. IEEE, 2016.

Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, pages 166–175, 2017.

Richard Bellman. A Markovian decision process. *Journal of mathematics and mechanics*, pages 679–684, 1957.

Mingyu Cai, Shaoping Xiao, Baoluo Li, Zhiliang Li, and Zhen Kan. Reinforcement learning based temporal logic control with maximum probabilistic satisfaction. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 806–812. IEEE, 2021.

Alberto Camacho, Rodrigo Toro Icarte, Toryn Q. Klassen, Richard Valenzano, and Sheila A. McIlraith. LTL and beyond: Formal languages for reward function specification in reinforcement learning. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 6065–6073, 2019.

Alberto Camacho, Jacob Varley, Andy Zeng, Deepali Jain, Atil Iscen, and Dmitry Kalashnikov. Reward machines for vision-based robotic manipulation. In *Proceedings of the 2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 14284–14290, 2021.

Jan Corazza, Ivan Gavran, and Daniel Neider. Reinforcement learning with stochastic reward machines. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 6429–6436, 2022.

Giuseppe de Giacomo, Marco Favorito, Luca Iocchi, Fabio Patrizi, and Alessandro Ronca. Temporal Logic Monitoring Rewards via Transducers. In *Proceedings of the 17th International Conference on Knowledge Representation and Reasoning (KR)*, volume 17, pages 860–870, 2020.

David DeFazio and Shiqi Zhang. Learning quadruped locomotion policies with reward machines. *CoRR*, abs/2107.10969, 2021. URL http://arxiv.org/abs/2107.10969.

Xu Chu Dennis Ding, Stephen L Smith, Calin Belta, and Daniela Rus. LTL control in uncertain environments with probabilistic satisfaction guarantees. *IFAC Proceedings Volumes*, 44(1):3515–3520, 2011.

Daniel Furelos-Blanco, Mark Law, Alessandra Russo, Krysia Broda, and Anders Jonsson. Induction of subgoal automata for reinforcement learning. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence (AAAI)*, pages 3890–3897, 2020.

Maor Gaon and Ronen Brafman. Reinforcement learning with non-Markovian rewards. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence (AAAI)*, pages 3980–3987, 2020.

Mahsa Ghasemi, Erdem Arinc Bulgur, and Ufuk Topcu. Task-oriented active perception and planning in environments with partially known semantics. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, 2020.

Mohammadhosein Hasanbeig, Alessandro Abate, and Daniel Kroening. Logically-constrained reinforcement learning. *CoRR*, abs/1801.08099, 2018. URL http://arxiv.org/abs/1801.08099.

Mohammadhosein Hasanbeig, Daniel Kroening, and Alessandro Abate. Deep reinforcement learning with temporal logics. In *Proceedings of the 18th International Conference on Formal Modeling and Analysis of Timed Systems (FORMATS)*, pages 1–22, 2020.

John E. Hopcroft, Rajeev Motwani, and Jeffrey D. Ullman. *Introduction to automata theory, languages, and computation, 3rd Edition*. Pearson international edition. Addison-Wesley, 2007.

Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. *arXiv preprint arXiv:2201.07207*, 2022.

Yiding Jiang, Shixiang Shane Gu, Kevin P Murphy, and Chelsea Finn. Language as an abstraction for hierarchical deep reinforcement learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Yuqian Jiang, Suda Bharadwaj, Bo Wu, Rishi Shah, Ufuk Topcu, and Peter Stone. Temporal-logic-based reward shaping for continuing reinforcement learning tasks. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence (AAAI)*, pages 7995–8003, 2021.

Austin Jones, Mac Schwager, and Calin Belta. Distribution temporal logic: Combining correctness with quality of estimation. In *52nd IEEE Conference on Decision and Control*, pages 4719–4724. IEEE, 2013.

Kishor Jothimurugan, Rajeev Alur, and Osbert Bastani. A Composable Specification Language for Reinforcement Learning Tasks. In *Proceedings of the 32nd Conference on Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, pages 13041–13051, 2019.

Kishor Jothimurugan, Suguman Bansal, Osbert Bastani, and Rajeev Alur. Compositional reinforcement learning from logical specifications. *Advances in Neural Information Processing Systems*, 34: 10026–10039, 2021.

Yen-Ling Kuo, Boris Katz, and Andrei Barbu. Encoding formulas as deep networks: Reinforcement learning for zero-shot execution of LTL formulas. *CoRR*, abs/2006.01110, 2020. URL https://arxiv.org/abs/2006.01110.

Borja G Leon, Murray Shanahan, and Francesco Belardinelli. Systematic generalisation through task temporal logic and deep reinforcement learning. *CoRR*, abs/2006.08767, 2020. URL https://arxiv.org/abs/2006.08767.

Borja G León, Murray Shanahan, and Francesco Belardinelli. In a nutshell, the human asked for this: Latent goals for following temporal specifications. *arXiv preprint arXiv:2110.09461*, 2021.

Xiao Li, Cristian-Ioan Vasile, and Calin Belta. Reinforcement learning with temporal logic rewards. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 3834–3839. IEEE, 2017.

Xiao Li, Yao Ma, and Calin Belta. A Policy Search Method for Temporal Logic Specified Reinforcement Learning Tasks. In *Proceedings of the 2018 Annual American Control Conference (ACC)*, pages 240–245. IEEE, 2018.

Michael L. Littman, Ufuk Topcu, Jie Fu, Charles Isbell, Min Wen, and James MacGlashan. Environment-independent task specifications via GLTL. *CoRR*, abs/1704.04341, 2017. URL http://arxiv.org/abs/1704.04341.

Jason Xinyu Liu, Ankit Shah, Eric Rosen, George Konidaris, and Stefanie Tellex. Skill transfer for temporally-extended task specifications. *arXiv preprint arXiv:2206.05096*, 2022.

Jelena Luketina, Nantas Nardelli, Gregory Farquhar, Jakob Foerster, Jacob Andreas, Edward Grefenstette, Shimon Whiteson, and Tim Rocktäschel. A survey of reinforcement learning informed by natural language. *arXiv preprint arXiv:1906.03926*, 2019.

Francisco S Melo and M Isabel Ribeiro. Q-learning with linear function approximation. In *International Conference on Computational Learning Theory*, pages 308–322. Springer, 2007.

Cyrus Neary, Zhe Xu, Bo Wu, and Ufuk Topcu. Reward machines for cooperative multi-agent reinforcement learning. In *Proceedings of the 20th International Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, pages 934–942, 2021.

Junhyuk Oh, Satinder Singh, Honglak Lee, and Pushmeet Kohli. Zero-shot task generalization with multi-task deep reinforcement learning. In *International Conference on Machine Learning*, pages 2661–2670. PMLR, 2017.

Gavin Rens and Jean-François Raskin. Learning non-Markovian reward models in MDPs. *CoRR*, abs/2001.09293, 2020. URL https://arxiv.org/abs/2001.09293.

Dorsa Sadigh and Ashish Kapoor. Safe control under uncertainty with probabilistic signal temporal logic. In *Proceedings of Robotics: Science and Systems XII*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ankit Shah, Shen Li, and Julie Shah. Planning with uncertain specifications (PUnS). *IEEE Robotics and Automation Letters*, 5(2):3414–3421, 2020.

Richard S. Sutton and Andrew G. Barto. *Reinforcement learning - an introduction*. Adaptive computation and machine learning. MIT Press, 1998. ISBN 978-0-262-19398-6. URL https://www.worldcat.org/oclc/37293240.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, second edition, 2018.

Rodrigo Toro Icarte, Toryn Klassen, Richard Valenzano, and Sheila McIlraith. Using reward machines for high-level task specification and decomposition in reinforcement learning. In *International Conference on Machine Learning*, pages 2107–2116. PMLR, 2018.

Rodrigo Toro Icarte, Toryn Q. Klassen, Richard Valenzano, and Sheila A. McIlraith. Using Reward Machines for High-Level Task Specification and Decomposition in Reinforcement Learning. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, pages 2107–2116, 2018.

Rodrigo Toro Icarte, Ethan Waldie, Toryn Q. Klassen, Rick Valenzano, Margarita P. Castro, and Sheila A. McIlraith. Learning reward machines for partially observable reinforcement learning. In *Proceedings of the 32nd Conference on Advances in Neural Information Processing Systems (NeurIPS)*, pages 15497–15508, 2019.

Rodrigo Toro Icarte, Toryn Q Klassen, Richard Valenzano, and Sheila A McIlraith. Reward machines: Exploiting reward function structure in reinforcement learning. *Journal of Artificial Intelligence Research*, 73:173–208, 2022.

Pashootan Vaezipoor, Andrew Li, Rodrigo Toro Icarte, and Sheila McIlraith. LTL2Action: Generalizing LTL instructions for multi-task RL. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pages 10497–10508, 2021.

Alvaro Velasquez, Andre Beckus, Taylor Dohmen, Ashutosh Trivedi, Noah Topper, and George Atia. Learning probabilistic reward machines from non-Markovian stochastic reward processes. *CoRR*, abs/2107.04633, 2021. URL http://arxiv.org/abs/2107.04633.

Christos Verginis, Cevahir Koprulu, Sandeep Chinchali, and Ufuk Topcu. Joint learning of reward machines and policies in environments with partially known semantics. *arXiv preprint arXiv:2204.11833*, 2022.

Zhe Xu and Ufuk Topcu. Transfer of Temporal Logic Formulas in Reinforcement Learning. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4010–4018, 2019.

Zhe Xu, Ivan Gavran, Yousef Ahmad, Rupak Majumdar, Daniel Neider, Ufuk Topcu, and Bo Wu. Joint inference of reward machines and policies for reinforcement learning. In *Proceedings of the 30th International Conference on Automated Planning and Scheduling (ICAPS)*, volume 30, pages 590–598, 2020a.

Zhe Xu, Bo Wu, Daniel Neider, and Ufuk Topcu. Active finite reward automaton inference and reinforcement learning using queries and counterexamples. *CoRR*, abs/2006.15714, 2020b. URL https://arxiv.org/abs/2006.15714.

Lim Zun Yuan, Mohammadhosein Hasanbeig, Alessandro Abate, and Daniel Kroening. Modular Deep Reinforcement Learning with Temporal Logic Specifications. *arXiv preprint arXiv:1909.11591*, 2019.

Xuejing Zheng, Chao Yu, Chen Chen, Jianye Hao, and Hankz Hankui Zhuo. Lifelong reinforcement learning with temporal logic formulas and reward machines. *CoRR*, abs/2111.09475, 2021. URL http://arxiv.org/abs/2111.09475.