LiteTransformerSearch: Training-free On-device Search for Efficient Autoregressive Language Models

Abstract

The Transformer architecture is ubiquitously used as the building block of large-scale autoregressive language models. However, finding architectures with the optimal trade-off between task performance (perplexity) and hardware constraints like peak memory utilization and latency is non-trivial. This is exacerbated by the proliferation of various hardware. We leverage the somewhat surprising empirical observation that the number of decoder parameters in autoregressive Transformers has a high rank correlation with task performance, irrespective of the architecture topology. This observation organically induces a simple search algorithm that uses decoder parameters as a proxy for perplexity without need for any model training. The search phase of our training-free algorithm, dubbed Lightweight Transformer Search (LTS), can be run directly on target devices since it does not require GPUs. We focus on extracting the pareto-frontier of perplexity versus any hardware performance cost such as latency and/or memory, using on-target-device measurements. We evaluate LTS on diverse devices from ARM CPUs to NVIDIA GPUs and two popular autoregressive Transformer backbones: GPT-2 and Transformer-XL. Results show that the perplexity of 16-layer GPT-2 and Transformer-XL can be achieved with up to $1.6\times, 2.5\times$ faster runtime and $1.3\times, 2.0\times$ lower peak memory utilization. LTS extracts the pareto-frontier in under 3 hours, running on a commodity laptop. We effectively remove the carbon footprint of training during search for hundreds of GPU hours, offering a strong simple baseline for future NAS methods in autoregressive language modeling.

1 Introduction

The Transformer architecture [35] has been used as the de-facto building block of most pre-trained language models like GPT [3]. A common problem arises when one tries to create smaller versions of Transformer models for edge or real-time applications (e.g. text prediction) with strict memory and latency constraints: it is not clear what the architectural hyperparameters should be, e.g., number of attention heads, number of layers, embedding dimension, and the inner dimension of the feed forward network, etc. This problem is exacerbated if each individual Transformer layer is allowed the freedom to have different values for these settings. This results in a combinatorial explosion of architectural hyperparameter choices and a large heterogeneous search space. For instance, the search space considered in this paper consists of over 10^{54} possible architectures.

Neural Architecture Search (NAS) is an organic solution due to its ability to automatically search through candidate models with multiple conflicting objectives like latency vs. task performance. The central challenge in NAS is prohibitively expensive function evaluation, i.e., evaluating each architecture requires training it on the dataset at hand. Thus it is often infeasible to evaluate more than a handful of architectures during the search phase. Supernets [25] have emerged as a dominant paradigm in NAS which combine all possible architectures into a single graph and jointly train them using weight-sharing. Nevertheless, supernet training imposes constraints on the expressiveness of the search space [23] and is often memory-hungry [44, 4, 43] as it creates large networks during search. Additionally, training supernets is non-trivial as children architectures may interfere with each other and rank correlation between sub-architectures is not preserved [23][1].

---

[1] See [23] for a comprehensive treatment of the difficulties of training supernets.

Figure 1: High-level overview of LTS. We propose a zero-cost proxy for evaluating the validation perplexity of candidate architectures. Pareto-frontier search is powered by evolutionary algorithms which use the proposed proxy along with real latency and memory measurements on the target hardware to evaluate sampled architectures.

We consider a different approach by proposing a training-free proxy that provides a highly accurate ranking of candidate architectures during NAS without need for costly function evaluation or supernets. Our scope is NAS for efficient Transformer-based autoregressive language models. We design a lightweight search method which is target hardware-aware and outputs a gallery of models on the pareto-frontier of perplexity versus hardware metrics. We term this method Lightweight Transformer Search (LTS). LTS relies on our somewhat surprising observation: *the decoder parameter count has a high rank correlation with the perplexity of fully trained autoregressive Transformers.*

Given a set of Transformer-based autoregressive language models, one can accurately rank them using decoder parameter count as the proxy for perplexity. Our observations are also well-aligned with the power laws in [17], shown for homogeneous autoregressive Transformers, i.e., when all decoder layers have the same configuration. We provide rigorous experiments to empirically establish the high rank correlation between perplexity and decoder parameter count for *both* homogeneous and heterogeneous search spaces.

The above phenomenon coupled with the fact that a candidate architecture's hardware performance can be measured on the target device [2] leads to a training-free search procedure: *pick one's favorite discrete search algorithm (e.g. evolutionary search), sample candidate architectures from the search space; count their decoder parameters as a proxy for task performance (i.e., perplexity); measure their hardware performance (e.g., latency and memory) directly on the target device; and progressively create a pareto-frontier estimate.* While we have chosen a reasonable search algorithm in this work, one can plug-and-play any pareto-frontier search method such as those in [15].

Building upon these insights, Figure 1 shows a high-level overview of LTS. We design the first training-free Transformer search that is performed entirely on the target (constrained) platform. As such, LTS easily performs a multi-objective NAS where several underlying hardware performance metrics, e.g., latency and peak memory utilization, are simultaneously optimized. Using our training-free proxy, we extract the 3-dimensional pareto-frontier of perplexity versus latency and memory in a record breaking time of < 3 hours on a commodity Intel Core i7 CPU. Notably, LTS eliminates the carbon foot print from hundreds of GPU hours of training associated with legacy NAS methods.

To corroborate the effectiveness of our proxy, we train over 2800 Transformer architectures on two large language modeling benchmark datasets, namely, WikiText-103 [22] and One Billion Word [5]. We use LTS to search for pareto-optimal architectural hyperparameters in two popularly used autoregressive Transformer backbones, namely, Transformer-XL [7] and GPT-2 [26]. We believe decoder parameter count should be regarded as a competitive baseline for evaluating Transformer NAS, both in terms of ranking capabilities and easy computation. We will open-source our code and our extensive library of trained models to foster future NAS research on Transformers.

2   Related Work

Here, we discuss literature on automated search for Transformer architectures in the language domain. We refer to extensive surveys on NAS [11, 41] for a broader overview of the field.

Decoder-only Architectures. So et al. [30] search over TensorFlow programs that implement an autoregressive language model via evolutionary search. Since most random sequences of programs either have errors or underperform, the search has to be seeded with the regular Transformer architecture, termed "Primer". As opposed to "Primer" which uses large computation to search a general space, our aim is to efficiently search the "backbone" of traditional decoder-only Transformers. Additionally, the objective in "Primer" is to find models that train faster. Our objective for NAS, however, is to deliver pareto-frontiers for inference, with respect to perplexity and hardware constraints.

---

[2]An insight noted in [10] and [15] that we leverage during search.

Encoder-only Architectures. Relative to decoder-only autoregressive language models, encoder-only architectures like BERT [8] have received much more recent attention from the NAS community. NAS-BERT [42] trains a supernet to efficiently search for masked language models (MLMs) which are compressed versions of the standard BERT, Such models can then be used in downstream tasks as is standard practice. Similar to NAS-BERT, [43] also train a supernet to conduct architecture search with the aim of finding more efficient BERT variants. They find interesting empirical insights into supernet training issues like differing gradients at the same node from different child architectures and different tensors as input and output at every node in the supernet. The authors propose fixes that drastically improves supernet training. Tsai et al. [34], Yin et al. [45], Gao et al. [13] also conduct variants of supernet training with the aim of finding more efficient BERT models.

Encoder-Decoder Related: Applying the well-known DARTS [19] approach to Transformer search spaces leads to memory-hungry supernets. To mitigate this issue, [51] propose a multi-split reversible network and a memory efficient backpropagation algorithm. One of the earliest papers that applied discrete NAS to Transformer search spaces was by So et al. [29], who use a modified form of evolutionary search. Due to the expense of directly performing discrete search on the search space, this work incurs extremely large computation overhead. Follow-up work by [38] uses the Once-For-All [4] approach to train a supernet for encoder-decoder architectures used in machine translation. Search is performed on subsamples of the supernet that inherit weights to estimate task accuracy. For each target device, the authors train a small neural network regressor on thousands of architectures to estimate latency. As opposed to using a latency estimator, LTS evaluates the latency of each candidate architecture on the target hardware. Notably, by performing the search directly on the target platform, LTS can easily incorporate various hardware performance metrics, e.g., peak memory utilization, for which accurate estimators may not exist. To the best of our knowledge, such holistic integration of multiple hardware metrics in Transformer NAS has not been explored previously.

3   Lightweight Transformer Search

We perform an evolutionary search over candidate architectures to extract models that lie on the pareto-frontier. In contrast to the vast majority of prior methods that deliver a single architecture from the search space, our search is performed over the entire pareto, generating architectures with a wide range of latency, peak memory utilization, and perplexity with one round of search. This alleviates the need to repeat the NAS algorithm for each hardware performance constraint.

To evaluate candidate models during the search, LTS uses a training-free proxy for the validation perplexity. By incorporating training-free evaluation metrics, LTS, for the first time, performs the entire search directly on the target (constrained) hardware. Therefore, we can use real measurements of hardware performance during the search. Algorithm 1 outlines the iterative process performed in LTS [3] for finding candidate architectures in the search space ($\mathcal{D}$), that lie on the 3-dimensional pareto-frontier of perplexity versus latency and memory ($\mathbb{F}$). At each iteration, a set of points ($\mathbb{F}'$) are subsampled from the current pareto-frontier. A new batch of architectures ($\mathbb{S}_N$) are then sampled from $\mathbb{F}'$ using evolutionary algorithms ($EA(.)$). The new samples are evaluated in terms of latency ($\mathcal{L}$), peak memory utilization ($\mathcal{M}$), and validation perplexity ($\mathcal{P}$). Latency and memory are measured directly on the target hardware while the perplexity is indirectly estimated using our accurate and training-free proxy methods.

Algorithm 1: LTS's training-free NAS

Input: Search space $\mathcal{D}$, n_{iter}
Output: Perplexity-latency-memory pareto-frontier $\mathbb{F}$

1 $\mathcal{L}, \mathcal{M}, \mathcal{P}, \mathbb{F} \leftarrow \emptyset, \emptyset, \emptyset, \emptyset$
2 **while** $N \leq n_{iter}$ **do**
3 $\quad \mathbb{F}' \leftarrow \text{Subsample}(\mathbb{F})$
4 $\quad \mathbb{S}_N \leftarrow EA(\mathbb{F}', \mathcal{D})$
$\quad$ // hardware profiling
5 $\quad \mathcal{L} \leftarrow \mathcal{L} \bigcup \text{Latency}(\mathbb{S}_N)$
6 $\quad \mathcal{M} \leftarrow \mathcal{M} \bigcup \text{Memory}(\mathbb{S}_N)$
$\quad$ // estimate perplexity
7 $\quad \mathcal{P} \leftarrow \mathcal{P} \bigcup \text{Proxy}(\mathbb{S}_N)$
$\quad$ // update the pareto front
8 $\quad \mathbb{F} \leftarrow \text{LowerConvexHull}(\mathcal{P}, \mathcal{L}, \mathcal{M})$

Finally, the pareto-frontier is recalibrated using the lower convex hull of all sampled architectures. In the context of multi-objective NAS, pareto-frontier points are those where no single metric (e.g., perplexity, latency, and memory) can be improved without degrading at least one other metric [15]. To satisfy application-specific needs, optional upper bounds can be placed on the latency and/or memory of sampled architectures during search.

---
[3]The reasonable pareto-frontier algorithm in Algorithm 1 is inspired by [10] and [16]. Other possibilities include variations proposed in [15], evaluation of which is orthogonal to our contributions in this work.

Search Space. Figure 2 shows all elastic parameters in LTS search space, namely, number of layers (n_{layer}), number of attention heads (n_{head}), decoder output dimension (d_{model}), inner dimension of the feed forward network (d_{inner}), embedding dimension (d_{embed}), and the division factor (k) of adaptive embedding [2]. These architectural parameters are compatible with popularly used autoregressive Transformer backbones[4], e.g., GPT. We adopt a heterogeneous

search space where the backbone parameters are decided on a per-layer basis. This is in contrast to the homogeneous structure commonly used in Transformers [7, 3], which reuses the same configuration for all layers. Compared to homogeneous models, the flexibility associated with heterogeneous architectures enables them to obtain much better hardware performance under the same perplexity budget (see Section 4.4).

Figure 2: Elastic parameters in LTS search space.

Heterogeneous search space was previously explored in [38]. However, due to the underlying supernet structure, not all design parameters can change freely. As an example, the dimensionality of the *Q, K, V* vectors inside the encoder and decoder layers is fixed to a large value of 512 to accommodate inheritance from the supernet. Our search space, however, allows exploration of all internal dimensions without constraints. By not relying on the supernet structure, our search space easily encapsulates various Transformer backbones with different configurations of the input/output embedding layers and elastic internal dimensions.

LTS searches over the following values for the architectural parameters in our backbones: $n_{layer} \in \{2, \ldots, 16|1\}$[5], $d_{model} \in \{128, \ldots, 1024|64\}$, $d_{inner} \in \{128, \ldots, 4096|64\}$, and $n_{head} \in \{2, 4, 8\}$. Additionally we explore adaptive input embedding [2] with $d_{embed} \in \{128, 256, 512\}$ and factor $k \in \{1, 2, 4\}$. Once a d_{model} is sampled, we adjust the lower bound of the above range for d_{inner} to $2 \times d_{model}$. Encoding this heuristic inside the search ensures that the acquired models will not suffer from training collapse. Our heterogeneous search space encapsulates more than 10^{54} different architectures. Such high dimensionality further validates the critical need for training-free NAS.

3.1 Training-free Architecture Ranking

▶ **Low-cost Ranking Proxies.** Recently, Abdelfattah et al. [1] utilize the summation of pruning scores over all model weights as the ranking proxy for Convolutional Neural Networks (CNNs), where a higher score corresponds to higher architecture rank in the search space. White et al. [40] analyze these and more recent proxies and find that no particular proxy performs consistently well over various tasks and baselines, while number of parameters and flops proxies are quite competitive. However they did not include Transformer-based search spaces in their analysis. To the best of our knowledge, low-cost (pruning-based) proxies have not been evaluated on Transformer search spaces in the language domain. Note that one cannot naively apply these proxies to language models. Specifically, since the embedding layer in Transformers is equivalent to a lookup operation, special care must be taken to omit this layer from the proxy computation. Using this insight, we perform the first systematic study of low-cost proxies for NAS on autoregressive Transformers for text prediction.

We leverage various pruning metrics, namely, `grad_norm`, `snip` [18], `grasp` [37], `fisher` [33], and `synflow` [31]. We also study `jacob_cov` [21] and `relu_log_det` [20] which are low-cost scoring mechanisms proposed for NAS on CNNs in vision tasks. While these low-cost techniques do not perform model training, they require forward and backward passes over the architecture to compute the proxy, which can be time consuming on low-end hardware. Additionally, the aforesaid pruning techniques, by definition, incorporate the final softmax projection layer in their score assessment. Such an approach seems reasonable for CNNs dealing with a few classification labels, however, it can skew the evaluation for autoregressive Transformers dealing with a large output vocabulary space. To overcome these shortcomings, we introduce a zero-cost architecture ranking strategy in the next section that outperforms the proposed low-cost proxies in terms of ranking precision, is data free, and does not perform any forward/backward propagation.

▶ **Decoder Parameter Count as a Proxy.** We empirically establish a strong correlation between the parameter count inside decoder layers and final model performance in terms of validation

---

[4]For preliminaries on autoregressive Transformers, please see Appendix A.

[5]We use the notation $\{v_{min}, \ldots, v_{max}|\text{step size}\}$ to show the valid range of values.

Figure 3: Our zero-cost proxy based on decoder parameter count is highly correlated with the (ground-truth) validation perplexity after full training on WikiText-103 and LM1B. Each plot contains 200 architectures sampled randomly from the search space of GPT-2 or Transformer-XL backbone.

perplexity. We evaluate 200 architectures sampled uniformly at random from the search space of two autoregressive Transformer backbones, namely, Transformer-XL and GPT-2. These architectures are then trained fully on WikiText-103 and One Billion Word (LM1B) datasets. Full training requires 40K and 100K steps on WikiText-103 and LM1B, respectively, and consumes over **25000** GPU-hours on NVIDIA A100 and V100 nodes. We compare the ranking obtained using our zero-cost proxy against the ground-truth ranking based on validation perplexity after full training in Figure 3. On WikiText-103, the zero-cost ranking using the decoder parameter count obtains a Spearman's Rank Correlation (SRC) of 0.97 and 0.98 with full training for Transformer-XL and GPT-2 backbones, respectively. SRC further increases to 0.99 for the more complex LM1B benchmark on the Transformer-XL backbone. This validates that the decoder parameter count is strongly correlated with final model performance, thereby providing a reliable zero-cost proxy for NAS.

4   Experiments

We conduct experiments to seek answers to the following critical questions:

❶ How well can training-free proxies perform compared to training-based methods for estimating the performance of Transformer models?

❷ How does model topology affect the performance of the proposed decoder parameter proxy?

❸ Which models are on the pareto-frontier of perplexity, latency, and memory for different hardware?

❹ Can our training-free decoder parameter count proxy be integrated inside a search algorithm to estimate the pareto-frontier? How accurate is such an estimation of the pareto?

We empirically answer questions ❶, ❷, and ❸ in Sections 4.2, 4.3, and 4.4, respectively. We further address question ❹ in Appendix C where we show the pareto-frontier models extracted by the decoder parameter count proxy are very close to the ground-truth pareto-frontier with an average of 0.6% perplexity difference. Additionally, we show the efficacy of the decoder parameter count proxy when performing search on different range of model sizes in Appendix C, Figure 10.

4.1   Experimental Setup

Please refer to Appendix B for information about the benchmarked datasets, along with the implementation details of our training, evaluation, and evolutionary search algorithm.

Backbones. We apply our search on two widely used autoregressive Transformer backbones, namely, Transformer-XL [7] and GPT-2 [26] that are trained from scratch with varying architectural hyperparameters. The internal structure of these backbones are quite similar in that they contain decoder blocks with attention and feed-forward layers. The difference between the backbones lies mainly in their dataflow structures; the models derived from Transformer-XL backbone adopt a recurrence methodology over past states, which coupled with relative positional encoding, allows for modeling longer term dependencies.

Performance Criteria. To evaluate the ranking performance of various proxies, we first establish a ground-truth ranking of candidate architectures by training them until full convergence. This ground-truth ranking is then utilized to compute two performance criteria as follows:

► Common Ratio (CR): We define CR as the percentage overlap between the ground-truth ranking of architectures versus the ranking obtained from the proxy. CR quantifies the ability of the proxy ranking to identify the top $k\%$ architectures based on their validation perplexity after full training.

Figure 4: Comparison between partial training and our zero-cost proxy, i.e., decoder parameter count, in terms of ranking performance and timing overhead. Each subplot corresponds to a topk% of the randomly sampled models, based on their validation perplexity after full training.

▶ Spearman's Rank Correlation (SRC): We use this metric to measure the correlation between the proxy ranking and the ground-truth. Ideally, the proxy ranking should have high correlation with the ground-truth over the entire search space as well as high-performing candidate models.

4.2 How do training-free proxies perform compared to training-based methods?

In this section, we benchmark several proxy methods for estimating the rank of candidate architectures. Specifically, we investigate three different ranking techniques, namely, partial training, low-cost methods, and number of decoder parameters.

▶ **Partial Training.** We first analyze the relationship between validation perplexity after a shortened training period versus that of full training for ranking candidate models. We stop the training after $\tau \in [1.25\%, 87.5\%]$ of the total training iterations needed for model convergence. Figure 4 demonstrates the SRC and CR of partial training with various τs, evaluated on 100 randomly selected models from the Transformer-XL backbone, trained on WikiText-103. The horizontal axis denotes the average time required for τ iterations of training across all sampled models. Intuitively, a higher number of training iterations results in a more accurate estimate of the final perplexity. Nevertheless, the increased wall-clock time prohibits training during search and also imposes the need for GPUs. Interestingly, very few training iterations, i.e., 1.25%, provides a very good proxy for final performance with an SRC of > 0.9 on the entire population. Our training-free proxy, i.e., decoder parameter count, also shows competitive SRC compared to partial training.

▶ **Low-cost Proxies.** We benchmark various low-cost methods introduced in Section 3.1 on 200 randomly sampled architectures from the Transformer-XL backbone, trained on WikiText-103. Figure 5 shows the SRC between low-cost proxies and the ground-truth ranking after full training.

We measure the cost of each proxy in terms of floating point operations (FLOPs). As seen, the evaluated low-cost proxies have a strong correlation with the ground-truth ranking (even the lowest performing `relu_log_det` has > 0.8 SRC), validating the effectiveness of training-free NAS on autoregressive Transformers. The lower performance of `relu_log_det` can be attributed to the fundamental difference in much higher frequency of ReLU activations in CNNs, for which the method was originally developed, compared to Transformer-based architectures. Our analysis on randomly selected models with homogeneous structure also shows a strong correlation between the low-cost proxies and validation

Figure 5: SRC between low-cost proxies and the ground-truth ranking after full training of 200 randomly sampled Transformers. The decoder parameter count obtains the best SRC with zero cost.

perplexity, with decoder parameter count outperforming other proxies (see Appendix D).

▶ **Parameter Count.** Figure 6a demonstrates the final validation perplexity versus total number of model parameters for 300 randomly sampled architectures from GPT-2 and Transformer-XL backbones. This figure contains two important observations: (1) the validation perplexity has a downward trend as the number of parameters increase, (2) The discontinuity is caused by the dominance of embedding parameters when moving to the small Transformer regime. We highlight several example points in Figure 6a where the architectures are nearly identical but the adaptive input embedding factor k is changed. Changing $k \in \{1, 2, 4\}$ (shown with different colors in Figure 6a) varies the total parameter count without much influence on the validation perplexity.

Figure 6: (a) Validation perplexity after full training versus total parameters for 300 randomly sampled architectures trained on WikiText-103. The clear downward trend suggests a strong correlation between parameter count and perplexity. (b), (c) Performance of parameter count proxies for ranking 300 randomly sampled architectures with Transformer-XL and GPT-2 backbones.

The above observations motivate us to evaluate two proxies, i.e., total number of parameters and only decoder parameter count. Figures 6b,c demonstrate the CR and SRC metrics evaluated on the 300 randomly sampled models divided into top-$k\%$ bins based on their validation perplexity. As shown, the total number of parameters has a lower SRC with the validation perplexity, compared to decoder parameter count. This is due to the masking effect of embedding parameters, particularly in the Transformer-XL backbone. The total number of decoder parameters, however, provides a highly accurate, zero-cost proxy with an SRC of 0.97 and 0.98 with the perplexity after full training on Transformer-XL and GPT-2, respectively. We further show the high correlation between decoder parameter count and validation perplexity for Transformer architectures with homogeneous decoder blocks in the supplementary material, Appendix D.

4.3 How does variation in model topology affect decoder parameters as a proxy?

The low-cost proxies introduced in Section 3.1, rely on forward and backward passes through the network. As such, they automatically capture the topology of the underlying architecture by relying on the dataflow to compute the final proxy score. The decoder parameter count proxy, however, is topology-agnostic. In this section, we investigate the effect of topology on the performance of our proposed decoder parameter count proxy. Specifically, we seek to answer whether for a given decoder parameter count budget, the aspect ratio of the architecture, i.e., trading-off the width versus the depth, can affect the final validation perplexity.

We define the aspect ratio of the architecture as d_{model} (=width), divided by n_{layer} (=depth). This metric provides a sense of how skewed the topology is and has been used in previous work which study scaling laws for language models [17]. For a given decoder parameter count budget, we generate several random architectures from the GPT-2 backbone with a wide range of the width-to-depth aspect ratios[6]. The generated models span wide, shallow topologies (e.g., d_{model}=1256, n_{layer}=2) to narrow, deep topologies (e.g., d_{model}=112, n_{layer}=100). Figure 7a shows the validation perplexity of said architectures after full training on WikiText-103 versus their aspect ratio. The maximum deviation (from median) of the validation perplexity is $< 12.8\%$ for a given decoder parameter count, across a wide range of aspect ratios $\sim 1 - 630$. Our findings on the heterogeneous search space complement the empirical results by [17] where decoder parameter count largely determines perplexity for homogeneous Transformer architectures, irrespective of shape (see Fig 5 in [17]).

We observe stable training when scaling models from the GPT-2 backbone up to 100 layers, with the perplexity increasing only when the aspect ratio nears 1. Nevertheless, such deep models are not part of our search space as they have a high latency and are unsuitable for lightweight inference. For the purposes of hardware-aware and efficient Transformer NAS, decoder parameter count proxy holds a very high correlation with validation perplexity, regardless of the architecture topology as shown in Figure 7a. We further validate the effect of topology on decoder parameter count proxy for the Transformer-XL backbone in Figure 13 of Appendix E. Our results demonstrate less than 7% deviation (from the median) in validation perplexity for aspect ratios ranging from $\sim 8 - 323$.

Note that while models with the same parameter count have very similar validation perplexities, the topology in fact affects their hardware performance, i.e., latency (up to $2.8\times$) and peak memory

---

[6]We control the aspect ratio by changing the width, i.e., d_{model} while keeping d_{inner}=$2\times d_{model}$ and n_{head}=8. The number of layers is then derived such that the total parameter count remains the same.

(a)   (b)   (c)

Figure 7: Validation perplexity after full training versus (a) the width-to-depth aspect ratio, (b) latency, and (c) peak memory utilization. Models are randomly generated from the GPT-2 backbone and trained on WikiText-103. For a given decoder parameter count, we observe low variation in perplexity across different models, regardless of their topology. The topology, however, significantly affects the latency (up to $2.8\times$) and peak memory utilization (up to $5.5\times$) for models with the same perplexity.

utilization (up to $5.5\times$), as shown in Figure 7b, 7c. This motivates the need for incorporating hardware metrics in NAS to find the best topology.

4.4 Pareto-frontier models for various hardware platforms

The straightforward way to produce architectures of different latency/memory is varying the number of layers (layer-scaling) [35, 7]. We therefore benchmark the Transformer-XL (base) and GPT-2 (small) models with homogeneous layers $\in [1, 16]$ as our baseline as any practitioner is likely to do. We compare architectures found by LTS with layer-scaled versions of the backbone models and show that LTS models have better validation perplexity and/or lower latency and peak memory utilization (better pareto). All baseline models are trained using the same setup[7] as the NAS-generated models for fair comparison using the regimen in Table 2 of Appendix B.

We conduct LTS search on different target hardware. LTS outputs *a range* of pareto-optimal architectures with various latency/memory/perplexity characteristics. During search, we fix the adaptive input embedding factor to $k = 4$ to search models that are lightweight while ensuring nearly on-par validation perplexity with non-adaptive input embedding. We compare the pareto-frontier architectures found by LTS with the baseline in Figure 8. Here, all models are trained on the LM1B dataset (See Figure 12 in Appendix G for results on WikiText-103). Note that the pareto-frontier search is performed in a 3-dimensional space, an example of which is enclosed in the Appendix, Figure 14. For better visualization, in Figure 8 we plot 2-dimensional slices of the pareto-frontier with validation perplexity on the y-axis, and a hardware performance metric (either latency or memory) on the x-axis.

As seen, in the low-latency regime, LTS consistently finds models that have significantly lower perplexity compared to naive scaling of the baseline Transformer-XL or GPT-2. On the Transformer-XL backbone, LTS finds architectures with an average of 19.8% and 28.8% lower latency and memory, while achieving similar perplexity compared to the baseline on ARM CPU. Specifically, the perplexity of the 16-layer Transformer-XL base can be replicated on the ARM device with a lightweight model that is $1.6\times$ faster and utilizes $1.9\times$ less memory during execution. On the Corei7 CPU, the pareto-frontier models found by LTS are on average 25.8% faster and consume 30.0% less memory under the same validation perplexity constraint. In this setting, LTS finds a model that replicates the perplexity of the 16-layer Transformer-XL base while achieving $1.7\times$ faster runtime and $1.9\times$ less peak memory utilization. The savings are even higher on the GPU device, where the NAS-generated models achieve the same perplexity as the baseline with average 30.5% lower latency and 27.0% less memory. Specifically, a LTS model with the same perplexity as the 16-layer Transformer-XL base has $2.5\times$ less latency and consumes $2.0\times$ less peak memory on TITAN Xp.

On the GPT-2 backbone, we observe that the NAS-generated models utilize on average 11.8% less memory while achieving the same validation perplexity and latency on an ARM CPU. The benefits are larger on Corei7 and TitanXP where the latency savings are pushed to 13.8% and 11.9%, respectively. The peak memory utilization is also decreased by 9.7% and 12.9%, on average, compared to the baseline scaled GPT-2s on Corei7 and TITAN Xp, respectively. Notably, NAS finds new architectures with the same perplexity as the 16-layer GPT-2 with $1.3\times$, $1.4\times$ faster runtime and $1.2\times$ less peak memory utilization on Corei7 and TITAN Xp.

---

[7]The best reported result in the literature for GPT-2 or Transformer-XL might be different based on the specific training hyperparameters, which is orthogonal to our investigation.

Figure 8: 2D visualization of the perplexity versus latency and memory pareto-frontier found by LTS, versus the scaled backbone models with varying number of layers, trained on the LM1B dataset. Architectural parameters for models shown here are detailed in Appendix H.

Our heterogeneous search-space allows us to find a better parameter distribution among decoder layers. Therefore, LTS delivers architectures with better performance in terms of perplexity, while reducing both latency and memory when compared to the homogeneous baselines. We provide the architecture of all baseline and LTS models shown in Figure 8 in Tables 3-6 of Appendix H.

Search Efficiency. The main component in LTS search time is the latency/peak memory utilization measurement for candidate architectures since evaluating the model perplexity is instant using the decoder parameter count. Our search only takes 0.9, 2.6, and 17.2 hours on a TITAN Xp GPU, Corei7 CPU, and an ARM core, respectively. To provide more context into the timing analysis, full training of even one 16-layer Transformer-XL base model on LM1B using a machine with $8\times$ NVIDIA V100 GPUs takes 15.8 hours. Using decoder parameters as a proxy significantly reduces our search runtime, allowing it to finish in a few hours on commodity hardware. Once the pareto-frontier models are identified, the user can pick a model based on their desired hardware constraints and fully train it on the target dataset (Please see Appendix B for details). LTS is an alternate paradigm to that of training memory-hungry supernets; our search can run directly on target device (not just memory/latency measurement) with GPUs needed only for training the chosen pareto-frontier model after search.

In Table 1 we study the ranking performance of partial training (500) steps against the decoder parameters proxy for evaluating 1200 architectures from the Transformer-XL backbone during LTS search. Astonishingly the decoder parameters proxy gets higher SRC against partial training. This proxy can hence be effectively used in the inner loop of search for NAS.

	Train Iter	GPU Hours	CO_2e (lbs)	SRC
Full Training	40,000	19,024	5433	1.0
Partial Training	500	231	66	0.92
	5,000	2690	768	0.96
# Decoder Params	**0**	**0**	**~0**	**0.98**

Table 1: Comparison in ranking abilities of full and partial training versus our proxy on 1200 models sampled during LTS search. Training time is for WikiText-103 on NVIDIA V100 GPU. The decoder parameter proxy obtains an SRC of 0.98 using zero compute.

5 Limitations and Future Work

Decoder parameter count provides a simple yet accurate proxy for ranking autoregressive models. This should serve as a strong baseline for future works on Transformer NAS. Our focus is entirely on autoregressive, decoder-only transformers. We therefore, study perplexity as the commonly used metric for language modeling tasks. Nevertheless, recent literature on scaling laws for Transformers suggest a similar correlation between parameter count and task metrics may exist for encoder only (BERT-style) Transformers or encoder-decoder models used in neural machine translation (NMT) [14]. Additionally, recent findings [32] show specific scaling laws exist between model size and downstream task metrics, e.g., GLUE [36]. Investigating such scaling laws for NAS on heterogeneous BERT-style or NMT models with new metrics is an important future avenue of research.

References

[1] Mohamed S Abdelfattah, Abhinav Mehrotra, Łukasz Dudziak, and Nicholas Donald Lane. Zero-cost proxies for lightweight nas. In *International Conference on Learning Representations*, 2020.

[2] Alexei Baevski and Michael Auli. Adaptive input representations for neural language modeling. In *International Conference on Learning Representations*, 2018.

[3] Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

[4] Han Cai, Chuang Gan, Tianzhe Wang, Zhekai Zhang, and Song Han. Once-for-all: Train one network and specialize it for efficient deployment. In *International Conference on Learning Representations*, 2019.

[5] Ciprian Chelba, Tomas Mikolov, Mike Schuster, Qi Ge, Thorsten Brants, Phillipp Koehn, and Tony Robinson. One billion word benchmark for measuring progress in statistical language modeling. *arXiv preprint arXiv:1312.3005*, 2013.

[6] Minghao Chen, Houwen Peng, Jianlong Fu, and Haibin Ling. Autoformer: Searching transformers for visual recognition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12270–12280, 2021.

[7] Zihang Dai, Zhilin Yang, Yiming Yang, Jaime G Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2978–2988, 2019.

[8] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL-HLT (1)*, 2019.

[9] Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *International Conference on Learning Representations*, 2019.

[10] Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Efficient multi-objective neural architecture search via lamarckian evolution. In *International Conference on Learning Representations*, 2019.

[11] Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey, 2019.

[12] Hugging Face. Openai gpt2 by hugging face. https://huggingface.co/docs/transformers/model_doc/gpt2.

[13] Jiahui Gao, Hang Xu, Han shi, Xiaozhe Ren, Philip L. H. Yu, Xiaodan Liang, Xin Jiang, and Zhenguo Li. Autobert-zero: Evolving bert backbone from scratch, 2021.

[14] Behrooz Ghorbani, Orhan Firat, Markus Freitag, Ankur Bapna, Maxim Krikun, Xavier Garcia, Ciprian Chelba, and Colin Cherry. Scaling laws for neural machine translation. In *International Conference on Learning Representations*, 2021.

[15] Julia Guerrero-Viu, Sven Hauns, Sergio Izquierdo, Guilherme Miotto, Simon Schrodi, Andre Biedenkapp, Thomas Elsken, Difan Deng, Marius Lindauer, and Frank Hutter. Bag of baselines for multi-objective joint neural architecture search and hyperparameter optimization. *arXiv preprint arXiv:2105.01015*, 2021.

[16] Hanzhang Hu, John Langford, Rich Caruana, Saurajit Mukherjee, Eric J Horvitz, and Debadeepta Dey. Efficient forward architecture search. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/6c468ec5a41d65815de23ec1d08d7951-Paper.pdf.

[17] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

[18] Namhoon Lee, Thalaiyasingam Ajanthan, and Philip Torr. SNIP: SINGLE-SHOT NETWORK PRUNING BASED ON CONNECTION SENSITIVITY. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1VZqjAcYX.

[19] Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable architecture search. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=S1eYHoC5FX.

[20] Joe Mellor, Jack Turner, Amos Storkey, and Elliot J Crowley. Neural architecture search without training. In *International Conference on Machine Learning*, pages 7588–7598. PMLR, 2021.

[21] Joseph Mellor, Jack Turner, Amos Storkey, and Elliot J. Crowley. Neural architecture search without training, 2021. URL https://openreview.net/forum?id=g4E6SAAvACo.

[22] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

[23] Xuefei Ning, Changcheng Tang, Wenshuo Li, Zixuan Zhou, Shuang Liang, Huazhong Yang, and Yu Wang. Evaluating efficient performance estimators of neural architectures. *Advances in Neural Information Processing Systems*, 34, 2021.

[24] NVIDIA. Transformer-xl for pytorch. https://github.com/NVIDIA/DeepLearningExamples/tree/master/PyTorch/LanguageModeling/Transformer-XL.

[25] Hieu Pham, Melody Guan, Barret Zoph, Quoc Le, and Jeff Dean. Efficient neural architecture search via parameters sharing. In *International Conference on Machine Learning*, pages 4095–4104. PMLR, 2018.

[26] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

[27] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

[28] Julien Siems, Lucas Zimmer, Arber Zela, Jovita Lukasik, Margret Keuper, and Frank Hutter. Nas-bench-301 and the case for surrogate benchmarks for neural architecture search. *arXiv preprint arXiv:2008.09777*, 2020.

[29] David R. So, Chen Liang, and Quoc V. Le. The evolved transformer, 2019.

[30] David R. So, Wojciech Mańke, Hanxiao Liu, Zihang Dai, Noam Shazeer, and Quoc V. Le. Primer: Searching for efficient transformers for language modeling, 2021.

[31] Hidenori Tanaka, Daniel Kunin, Daniel L Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. *Advances in Neural Information Processing Systems*, 33, 2020.

[32] Yi Tay, Mostafa Dehghani, Jinfeng Rao, William Fedus, Samira Abnar, Hyung Won Chung, Sharan Narang, Dani Yogatama, Ashish Vaswani, and Donald Metzler. Scale efficiently: Insights from pre-training and fine-tuning transformers. *arXiv preprint arXiv:2109.10686*, 2021.

[33] Lucas Theis, Iryna Korshunova, Alykhan Tejani, and Ferenc Huszár. Faster gaze prediction with dense networks and fisher pruning. *arXiv preprint arXiv:1801.05787*, 2018.

[34] Henry Tsai, Jayden Ooi, Chun-Sung Ferng, Hyung Won Chung, and Jason Riesa. Finding fast transformers: One-shot neural architecture search by component composition, 2020.

[35] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.

[36] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

[37] Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SkgsACVKPH.

[38] Hanrui Wang, Zhanghao Wu, Zhijian Liu, Han Cai, Ligeng Zhu, Chuang Gan, and Song Han. Hat: Hardware-aware transformers for efficient natural language processing. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7675–7688, 2020.

[39] Hongyu Wang, Shuming Ma, Li Dong, Shaohan Huang, Dongdong Zhang, and Furu Wei. Deepnet: Scaling transformers to 1,000 layers. *arXiv preprint arXiv:2203.00555*, 2022.

[40] Colin White, Mikhail Khodak, Renbo Tu, Shital Shah, Sébastien Bubeck, and Debadeepta Dey. A deeper look at zero-cost proxies for lightweight nas. In *ICLR Blog Track*, 2022. URL https://iclr-blog-track.github.io/2022/03/25/zero-cost-proxies/. https://iclr-blog-track.github.io/2022/03/25/zero-cost-proxies/.

[41] Martin Wistuba, Ambrish Rawat, and Tejaswini Pedapati. A survey on neural architecture search, 2019.

[42] Jin Xu, Xu Tan, Renqian Luo, Kaitao Song, Jian Li, Tao Qin, and Tie-Yan Liu. Nas-bert. *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, Aug 2021. doi: 10.1145/3447548.3467262. URL http://dx.doi.org/10.1145/3447548.3467262.

[43] Jin Xu, Xu Tan, Kaitao Song, Renqian Luo, Yichong Leng, Tao Qin, Tie-Yan Liu, and Jian Li. Analyzing and mitigating interference in neural architecture search, 2021.

[44] Yuhui Xu, Lingxi Xie, Xiaopeng Zhang, Xin Chen, Guo-Jun Qi, Qi Tian, and Hongkai Xiong. Pc-darts: Partial channel connections for memory-efficient architecture search. In *International Conference on Learning Representations*, 2019.

[45] Yichun Yin, Cheng Chen, Lifeng Shang, Xin Jiang, Xiao Chen, and Qun Liu. Autotinybert: Automatic hyper-parameter optimization for efficient pre-trained language models. *arXiv preprint arXiv:2107.13686*, 2021.

[46] Yang You, Jing Li, Sashank Reddi, Jonathan Hseu, Sanjiv Kumar, Srinadh Bhojanapalli, Xiaodan Song, James Demmel, Kurt Keutzer, and Cho-Jui Hsieh. Large batch optimization for deep learning: Training bert in 76 minutes. *arXiv preprint arXiv:1904.00962*, 2019.

[47] Ofir Zafrir, Ariel Larey, Guy Boudoukh, Haihao Shen, and Moshe Wasserblat. Prune once for all: Sparse pre-trained language models. *arXiv preprint arXiv:2111.05754*, 2021.

[48] Arber Zela, Julien Niklas Siems, Lucas Zimmer, Jovita Lukasik, Margret Keuper, and Frank Hutter. Surrogate nas benchmarks: Going beyond the limited search spaces of tabular nas benchmarks. In *International Conference on Learning Representations*, 2021.

[49] Xuan Zhang and Kevin Duh. Reproducible and efficient benchmarks for hyperparameter optimization of neural machine translation systems. https://github.com/Este11e/hpo_nmt.

[50] Xuan Zhang and Kevin Duh. Reproducible and efficient benchmarks for hyperparameter optimization of neural machine translation systems. *Transactions of the Association for Computational Linguistics*, 8:393–408, 2020.

[51] Yuekai Zhao, Li Dong, Yelong Shen, Zhihua Zhang, Furu Wei, and Weizhu Chen. Memory-efficient differentiable transformer architecture search, 2021.

[52] Qinqin Zhou, Kekai Sheng, Xiawu Zheng, Ke Li, Xing Sun, Yonghong Tian, Jie Chen, and Rongrong Ji. Training-free transformer architecture search. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10894–10903, 2022.